

Problem Set 4

379964037	Jun/24/2026 11:23UTC+10	tianzheyu	F - Wi-Fi	C++23 (GCC 14-64, msys2)	Accepted	62 ms	0 KB
---------------------------	----------------------------	-----------	---------------------------	--------------------------	----------	-------	------

<https://codeforces.com/submissions/tianzheyu#>

D. Wi-Fi

Process

There are n rooms. For each room i , there are 2 ways to connect to internet:

1. connect to the Internet directly, and this cost i ,
2. connect to the Internet via routers, a router in room j can cover rooms from $\min(j - k, 1)$ to $\max(j + k, n)$. And not every rooms have a spot for a router.

Challenges and Overcoming

Initially, I intuitively thought of using a 2D Interval DP ($dp[i][j]$). However, with the number of rooms n up to 200,000, an $O(N^2)$ approach would immediately cause a Memory Limit Exceeded (requiring around 320GB of memory) and a Time Limit Exceeded.

Overcoming: I reduced the state to a 1D DP, where $dp[i]$ represents the minimum cost to cover all of the first i rooms.

In a standard 1D DP, we usually only look at historical states. But here, room i can be covered by a router placed in room $i + k$ (which is in the "future").

Overcoming: I shifted my perspective. When processing room i , instead of just looking back, I actively search for a valid router j within the range $[\max(1, i - k), \min(n, i + k)]$ that can cover room i .

When implementing the nested loop to find router j , I encountered two major bugs:

- **Out of bounds (RE):** I didn't properly clamp the boundaries for checking the string `spots[j - 1]`, leading to negative indices.
- **Wrong historical cost (WA):** I mistakenly added the cost of router j to $dp[i - k - 1]$. Actually, since router j covers everything from $j - k$ to $j + k$, the latest room that still needs coverage is $j - k - 1$.

Overcoming: I strictly clamped the boundaries using `max()` and `min()`, and corrected the transition equation to $dp[\max(0, j - k - 1)] + j$. I also introduced $dp[0] = 0$ as a clean base case.

Even after fixing the bugs, the nested loop `for (int j = ...)` resulted in an $O(N * K)$ time complexity, which was still too slow for the 2-second time limit.

Overcoming: I utilized a crucial mathematical property: the dp array is monotonically non-decreasing. Because the costs only increase, the leftmost available router j that can cover room i (meaning $j \geq i - k$) will always yield the cheapest historical cost $dp[j - k - 1] + j$. By precomputing an array (e.g., `next_router`) to instantly locate the nearest router to the right, I successfully eliminated the inner loop, bringing the final time complexity down to a perfect $O(N)$!