ING

ζ

S

ɻ

e

S

d

1

9

1

5

S

```
val kotlinDsl = talk(“Kotlin, a language …”, {
    it.author = "Tiberiu Tofan"
    it.startTime = 18.30.hours
    it.endTime = 19.15.hours
})
```

(

ל

ل

ɻ

(

ل



ل

```kotlin
data class KotlinMeetup(val title: String, val talks: List<Talk>)
data class Talk(val title: String, var author: String, var startTime: LocalTime, var endTime: LocalTime)
```

TYPE-SAFE BUILDERS USING FUNCTIONAL LITERALS WITH RECEIVER





```
fun talk(title: String, init: (Talk) → Unit): Talk {
    val talk = Talk(title)
    init(talk)
    return talk
}
```

```
val kotlinDsl = talk("Kotlin, a language …", { t →
    t.author = "Tiberiu Tofan"
    t.startTime = 18.30.hours
    t.endTime = 19.15.hours
})
```

```
data class KotlinMeetup(val title: String, val talks: List<Talk>)
data class Talk(val title: String, var author: String, var startTime: LocalTime, var endTime: LocalTime)
```

TYPE-SAFE BUILDERS USING FUNCTIONAL LITERALS WITH RECEIVER

```
fun talk(title: String, init: (Talk) → Unit): Talk {
    val talk = Talk(title)
    init(talk)
    return talk
}
```

```
val kotlinDsl = talk("Kotlin, a language …", {
   it.author = "Tiberiu Tofan"
   it.startTime = 18.30.hours
   it.endTime = 19.15.hours
})
```

ING

```
data class KotlinMeetup(val title: String, val talks: List<Talk>)
data class Talk(val title: String, var author: String, var startTime: LocalTime, var endTime: LocalTime)
```

TYPE-SAFE BUILDERS USING FUNCTIONAL LITERALS WITH RECEIVER

```
fun talk(title: String, init: (Talk) → Unit): Talk {
    val talk = Talk(title)
    init(talk)
    return talk
}
```

```
val kotlinDsl = talk("Kotlin, a language …", {
   it.author = "Tiberiu Tofan"
   it.startTime = 18.30.hours
   it.endTime = 19.15.hours
})
```

ING