







ING





















































































































































































































































































































































































































































































TYPE-SAFE BUILDERS USING FUNCTIONAL INTERFACES WITH RECIPIENT

```
fun kotlinMeetup(title: String, init: KotlinMeetupBuilder.() → Unit): KotlinMeetup
```

```
fun talk(title: String, init: Talk.() → Unit): Talk
```

































































```
val kotlinTalks = kotlinMeetup("Kotlin Talks") {  
    talks(  
        talk("Kotlin for backend") {  
            author = "Cosmin Stefan"  
            startTime = 19.20.hours  
            endTime = 20.05.hours  
        },  
        talk("Effects in the wild, an introduction to functional programming") {  
            author = "Gabriel Bornea"  
            startTime = 20.10.hours  
            endTime = 20.55.hours  
        })  
    }  
}
```

this: Kollin MedelpBvilder



```
fun kotlinMeetup(title: String, init: KotlinMeetupBuilder.() → Unit): KotlinMeetup
fun talk(title: String, init: Talk.() → Unit): Talk
```

```
val kotlinTalks = kotlinMeetup("Kotlin Talks") {
    talks(
        talk("Kotlin for backend") {
            author = "Cosmin Stefan"
            startTime = 19.20.hours
            endTime = 20.05.hours
        },
        talk("Effects in the wild, an introduction to functional programming") {
            author = "Gabriel Bornea"
            startTime = 20.10.hours
            endTime = 20.55.hours
        })
    }
}
```