
FROM STOCHASTIC ANSWERS TO VERIFIABLE REASONING: INTERPRETABLE DECISION-MAKING WITH LLM-GENERATED CODE

Anirudh Jaidev Mahesh¹, Ben Griffin², Fuat Alicant³, Joseph Ternasky³, Zakari Salifu³, Kelvin Amoaba³,
Yagiz Ihlamur⁴, Aaron Ontoyin Yin³, Aikins Laryea³, Afriye Samuel³, Yigit Ihlamur³

¹Georgia Institute of Technology ²University of Oxford ³Vela Research ⁴Amazon

ABSTRACT

Large language models (LLMs) are increasingly used for high-stakes decision-making, yet existing approaches struggle to reconcile scalability, interpretability, and reproducibility. Black-box models obscure their reasoning, while recent LLM-based rule systems rely on per-sample evaluation, causing costs to scale with dataset size and introducing stochastic, hallucination-prone outputs. We propose reframing LLMs as *code generators* rather than per-instance evaluators. A single LLM call generates executable, human-readable decision logic that runs deterministically over structured data, eliminating per-sample LLM queries while enabling reproducible and auditable predictions. We combine code generation with automated statistical validation using precision lift, binomial significance testing, and coverage filtering, and apply cluster-based gap analysis to iteratively refine decision logic without human annotation. We instantiate this framework in venture capital founder screening, a rare-event prediction task with strong interpretability requirements. On VCBench, a benchmark of 4,500 founders with a 9% base success rate, our approach achieves 37.5% precision and an $F_{0.5}$ score of 25.0%, outperforming GPT-4o (at 30.0% precision and an $F_{0.5}$ score of 25.7%) while maintaining full interpretability. Each prediction traces to executable rules over human-readable attributes, demonstrating verifiable and interpretable LLM-based decision-making in practice.

1 Introduction

The venture capital industry deploys over \$300 billion annually, yet investment decisions remain largely driven by intuition and pattern-matching from experience. A central challenge is founder evaluation: given a candidate’s background, including their education, career history, and prior ventures, can we systematically identify patterns that predict startup success? The appeal of automation is clear, but the stakes demand transparency. When a VC passes on a founder or presents a deal to partners, they need to articulate *why*.

This creates a tension between two desirable properties. **Interpretability** requires that predictions decompose into human-readable factors, such as "this founder has a prior exit and held a VP role at a scaled company," that investors can validate against their own judgment. **Scalability** requires screening thousands of candidates without proportional expert effort. Traditional approaches sacrifice one for the other: handcrafted rules are interpretable but labor-intensive, while black-box models scale but obscure their reasoning.

Recent work has turned to LLMs as a middle path, using them to generate human-readable screening rules [1]. The idea is appealing: LLMs encode broad knowledge about what makes founders successful and can articulate it as natural language predicates. But these approaches evaluate each rule by querying the LLM for each founder. If a rule asks "Did this founder scale a previous company past 200 employees?", the LLM must answer that question 4,500 times. This leads to API costs that scale as $O(\text{rules} \times \text{founders})$ and, more problematically, introduces stochastic variation where the same question about the same founder may receive different answers across runs.

We observe that this per-sample evaluation is unnecessary. Founder profiles are *structured data*, consisting of education records, employment histories, and exit events, not free-form text requiring language understanding. A rule like "founder scaled a company past 200 employees" can be expressed as executable code that queries structured fields

deterministically. This reframes the LLM’s role: rather than serving as a rule *evaluator* that is called repeatedly, it serves as a rule *generator* that is called once.

This paper develops that insight into a complete framework. We prompt an LLM to generate Python predicates over founder attributes, validate rules automatically using precision lift and statistical significance, and apply cluster-based gap analysis to guide iterative refinement. On VCBench, our approach achieves 37.5% precision and an $F_{0.5}$ 25.0%, outperforming, GPT-4o, and other rivaling frontier LLMs (e.g, GPT-5, o3), while ensuring that every prediction traces to interpretable founder attributes.

We make the following contributions:

- We propose treating LLMs as code generators rather than rule evaluators for founder screening. This architectural shift reduces API costs by over 99% and eliminates per-sample hallucination risk while preserving interpretable outputs.
- We introduce automated statistical validation using precision lift, binomial significance testing, and coverage thresholds to filter low-quality rules without requiring human annotation.
- We develop a cluster-based gap analysis method that identifies founder subpopulations where existing rules fail to discriminate, providing structured feedback to guide iterative rule refinement.

2 Related Work

2.1 LLM-Based Feature Engineering for Tabular Data

Recent work has explored using LLMs to automate feature engineering for tabular prediction tasks. CAAFE [2] introduces context-aware automated feature engineering, where an LLM iteratively generates Python code for new features based on dataset descriptions and cross-validation feedback. The system improved ROC AUC from 0.79 to 0.82 across 14 tabular datasets by leveraging the LLM’s semantic understanding of feature relationships.

Several approaches extend this paradigm. OCTree [3] uses decision tree reasoning to provide structured feedback to the LLM, conveying which features contribute to prediction errors and guiding the generation of corrective features. LLM-FE [4] formulates feature engineering as a program search problem, combining evolutionary optimization with LLM-generated feature candidates. TabLLM [5] demonstrates that LLMs can engineer features for few-shot tabular learning by generating task-specific transformations from minimal examples.

These methods generate arbitrary feature transformations optimized for predictive performance, but the resulting features are often difficult for domain experts to interpret or validate.

2.2 LLM-Based Feature Engineering for Interpretability

A related line of work focuses specifically on generating interpretable features. FeatLLM [6] employs LLMs to produce binary features from text data for interpretable machine learning, emphasizing transparency over raw predictive performance. AutoQual [7] uses an LLM agent to discover interpretable features for review-quality assessment, iteratively refining feature definitions based on downstream task performance. GPTree [8] combines LLM-powered feature generation with decision tree classifiers to produce explainable predictions.

These approaches achieve interpretability but require the LLM to evaluate each rule on each sample, leading to costs that scale with dataset size and introducing stochastic variation across runs.

2.3 Machine Learning for Venture Capital

Predicting startup success has attracted significant research interest due to its economic importance and the challenge of learning from sparse, noisy signals. VCBench [9] introduces the first standardized benchmark for founder success prediction, providing 4,500 anonymized founder profiles with standardized features covering education, employment history, and prior exits. The benchmark evaluates frontier LLMs directly on the prediction task, with GPT-5 achieving 59.0% precision and an $F_{0.5}$ score of 16.2%.

Random Rule Forest (RRF) [1] generates interpretable ensembles of LLM-generated questions, using the LLM to both propose and evaluate binary rules on founder profiles. Kumar et al. [10] address the rare-event nature of startup success through LLM-powered feature engineering combined with multi-model learning.

2.4 Positioning of Our Work

Table 1 compares our approach with previous work across five dimensions that matter for practical deployment.

Table 1: Comparison with related work on automated feature engineering across five key dimensions.

Method	Cost	Speed	Interpret.	Stat. valid.	Determin.
CAAFE [2]	Low	Fast	Low	CV only	Yes
FeatLLM [6]	High	Slow	High	None	No
RRF [1]	High	Slow	High	None	No
Ours	Low	Fast	High	Built-in	Yes

We define these dimensions as follows:

- **Cost:** Total API expense for rule generation and evaluation. Methods requiring per-sample LLM calls incur costs that grow with dataset size.
- **Speed:** Latency from input to prediction. Per-sample evaluation creates bottlenecks for large datasets.
- **Interpretability:** Whether predictions decompose into human-readable factors that domain experts can validate.
- **Statistical validation:** Whether the method includes built-in mechanisms to filter spurious patterns, beyond cross-validation on downstream tasks.
- **Deterministic outputs:** Whether the same input produces identical outputs across runs, enabling reproducibility and debugging.

Code generation methods like CAAFE execute efficiently but produce arbitrary feature transformations that lack interpretability. Interpretable methods like FeatLLM and RRF generate human-readable rules but require $O(N \times M)$ LLM calls to evaluate N rules on M samples, incurring high cost, slow speed, and stochastic outputs where the same rule may yield inconsistent evaluations.

Our approach combines the efficiency of code generation with the interpretability of rule-based methods. By prompting the LLM once to generate executable Python predicates, we achieve low cost, fast speed, and deterministic outputs. By generating binary rules over structured founder attributes, we maintain full interpretability. And by introducing precision lift, significance testing, and coverage thresholds, we provide built-in statistical validation that filters low-quality rules without human annotation.

3 Methodology

We present a framework for interpretable feature engineering that combines LLM-based code generation with statistical validation and cluster-guided iteration. Figure 1 illustrates the complete pipeline.

3.1 Problem Setup

Given a dataset of founder profiles with binary success labels, our goal is to generate a set of interpretable binary rules that predict founder success. Each rule should be human-readable, statistically predictive, and non-redundant with other rules. The final model is a logistic regression classifier trained on rule activations, enabling transparent predictions where each decision traces to specific founder attributes.

3.2 Founder Data Representation

Each founder profile is a structured record containing education history (degree type, field of study, university QS ranking), employment history (role titles, company sizes, industries, tenure durations), prior exits (IPOs and acquisitions from previous ventures), and the industry of the founder’s current startup. Table 2 summarizes the data structure.

This structured representation enables the LLM to generate executable code that directly accesses founder attributes. We provide three helper functions that handle categorical parsing: `parse_qs` converts QS ranking strings to numeric values, `parse_duration` converts tenure strings to years, and `parse_company_size` converts company size ranges to employee counts. These helpers ensure that the LLM can generate syntactically valid predicates without implementing low-level parsing logic.




Figure 1: Overview of our LLM-as-code-generator pipeline. The LLM is called once to generate executable Python rules, which then evaluate deterministically across all founders without further LLM involvement. Statistical validation filters low-quality rules, and cluster-based gap analysis guides iterative refinement.

Table 2: Founder profile data structure.

Field	Type	Example Values
industry	string	“Software Development”
educations	list	degree, field, qs_ranking
jobs	list	role, company_size, industry, duration
ipos	list	prior IPO events
acquisitions	list	prior acquisition events

3.3 Rule Generation via LLM Code Generation

The core insight of our approach is that founder screening rules can be expressed as executable code rather than natural language predicates requiring LLM interpretation. Figure 2 illustrates this process.

3.3.1 Prompt Construction

For each iteration, we construct a prompt with three components.

Schema and helpers. We provide the complete founder data structure and helper function signatures. We also include eight example rules demonstrating proper syntax, edge case handling, and diverse pattern types covering education, experience, exits, and industry matching.

Stratified samples. We include 120 founder profiles in each prompt, with 60 successful and 60 unsuccessful founders. This balanced sampling corrects for the dataset’s 9% base rate, preventing the LLM from generating rules that trivially predict failure. We select samples for diversity by bucketing founders by industry, education count, and job count, then sampling evenly across buckets.

The sample size of 120 balances context window constraints against the need for sufficient diversity. In ablation experiments, we find that 50 samples yielded rules that were too specific: only 30% passed the 1-50% coverage threshold, with most rules matching fewer than 1% of the full dataset (indicating overfitting to the limited prompt examples). Conversely, increasing to 200 samples showed negligible improvement in validation pass rate or mean




Figure 2: Rule generation process. The LLM receives structured founder profiles and generates Python lambda expressions that encode binary screening rules. These rules execute deterministically across all 4,500 founders without additional LLM calls.

precision lift while increasing prompt length significantly. The 120-sample configuration achieves high rule quality (63% validation pass rate in Iteration 1) while remaining within practical prompt length limits, ensuring the LLM observes sufficient diversity to generate rules that generalize beyond the prompt sample.

Prior iteration feedback. For iterations beyond the first, we provide verbal reinforcement inspired by Reflexion [11], which shows that LLMs can learn from trial-and-error through linguistic feedback rather than weight updates. We append previously generated rules with their precision lift, coverage, and statistical significance, along with cluster-based gap analysis (Section 3.6) that identifies founder subpopulations where existing rules fail to discriminate. Unlike Reflexion’s binary success signals, our feedback is grounded in quantitative metrics, enabling the LLM to build on successful patterns, avoid redundancy, and target specific coverage gaps.

3.3.2 Output Format

The LLM generates rules as Python lambda expressions in a structured format:

1. rule_name ||| Description ||| lambda founder: <expr>

For example, the rule `elite_school_and_exit` checks whether a founder attended a top-50 QS-ranked university and has at least one prior exit:

```

lambda founder: (
  any(parse_qs(e.get("qs_ranking", "")) <= 50
    for e in founder.get("educations", []))
  and len(founder.get("ipos", []) or []) +
    len(founder.get("acquisitions", []) or []) > 0)

```

Each rule is a valid Python expression that takes a founder dictionary and returns True or False. Rules that fail to compile are discarded. We request 30 candidate rules per iteration, a quantity that balances exploration against redundancy: fewer rules reduce the likelihood of discovering high-lift patterns, while more rules yield diminishing returns as the LLM produces minor variations rather than novel patterns. Ablation experiments show that generating 50 rules yielded

Mixed clusters (success rate 7-12%, size > 400) indicate subpopulations where current rules fail to discriminate between success and failure. Founders in these clusters have similar rule activation patterns but different outcomes.

We also identify **uncovered successes**: successful founders who do not match any of the top rules, representing alternative success patterns not yet captured.

For each gap, we generate structured feedback including cluster statistics, example founders (both successful and unsuccessful), distinctive rule patterns for the cluster, and specific task instructions. For mixed clusters, we ask: “What differentiates success from failure here?” For low-success clusters with rare winners, we ask: “What makes these rare successes different?” This targeted feedback guides the next iteration toward rules that address identified weaknesses.

3.7 Downstream Classification

The validated rules form a binary feature matrix where each row is a founder and each column indicates whether a rule matches. We train a logistic regression classifier with balanced class weights using 5-fold stratified cross-validation.

We tune the classification threshold to optimize $F_{0.5}$, which weights precision higher than recall. In VC screening, high recall with low precision would overwhelm decision-makers with false positives, whereas high precision yields a manageable, high-confidence shortlist. The logistic regression coefficients provide interpretable importance weights, and predictions can be explained by listing the active rules for a given founder.

3.8 Iterative Pipeline

The complete pipeline proceeds as follows:

Iteration 1: Generate 30 rules without feedback, evaluate deterministically on all founders, compute precision lift and significance, filter by validation criteria, train logistic regression.

Iteration 2+: Cluster founders on current rule activations, identify gaps (mixed clusters, uncovered successes), generate feedback prompt with gap analysis and example founders, generate 30 new rules targeting gaps, evaluate, validate, and retrain.

Each iteration produces 30 candidate rules, of which 60-70% typically pass statistical validation. Later iterations target gaps identified in earlier iterations, improving coverage and diversity of the rule set.

4 Experiments

We evaluate our framework on VCBench [9], a standardized benchmark for founder success prediction.

4.1 Setup

Dataset. VCBench provides 4,500 anonymized founder profiles with binary success labels (IPO, acquisition, or fundraising >\$500M). The baseline success rate is 9.0%, reflecting the rare-event nature of startup success.

Implementation. We use GPT-5.2 for rule generation, generating 30 rules per iteration across 2 iterations. The rules are filtered by precision lift >1.0, p-value <0.05, and coverage 1-50%. The downstream classifier is logistic regression with balanced class weights, evaluated via 5-fold stratified cross-validation with threshold tuned for $F_{0.5}$.

Baselines. We compare against frontier LLMs evaluated directly on VCBench (GPT-5, GPT-4o, o3, Claude-3.5-Haiku, Gemini-2.5-Pro), human experts (Y Combinator at 14.0% precision, Tier-1 VCs at 23.0%), and the random baseline (9.0%).

4.2 Main Results

Table 4 presents detailed results.

Our Iteration 1 model matches GPT-4o precision (30.6% vs 30.0%) with higher $F_{0.5}$ (27.7% vs 25.7%). After cluster-based feedback, Iteration 2 achieves 37.5% precision, a 22% relative improvement. Critically, unlike black-box LLM predictions, our results are fully interpretable.

Cluster-guided rule refinement. We use clustering over generated binary rules to organize them by similarity, quantified clusters by precision lift and prediction frequency, and qualitatively inspected rule variation across clusters to guide subsequent LLM prompts. While this process proved effective for iterative improvement, it remains a heuristic, analyst-in-the-loop approach rather than a fully automated or theoretically grounded optimization procedure.

5.4 Future Work

Reinforcement learning from verifiable rewards. Statistical validation metrics provide automatic reward signals. Fine-tuning LLMs on successful rules via reinforcement learning could improve generation quality without human annotation.

Cross-domain application. The code generation and validation approach is domain-agnostic. Applying this framework to other tabular prediction tasks (loan default, medical diagnosis, customer churn) would test generalization.

Rule combination optimization. We use logistic regression to combine rules. More sophisticated methods such as rule set learning or weighted voting could improve performance while maintaining interpretability.

6 Conclusion

We present a framework for interpretable feature engineering that uses LLMs to generate executable Python rules rather than evaluate samples directly. This paradigm shift reduces API costs by 99%, eliminates per-sample hallucination risk, and produces deterministic, debuggable predictions. Statistical validation provides automatic quality filtering without human annotation, and cluster-based gap analysis guides iterative refinement.

On VCBench, our approach achieves 37.5% precision and an $F_{0.5}$ score of 25%, outperforming GPT-4o and other rival frontier LLMs (e.g., GPT-5, o3), while ensuring that every prediction is traceable to interpretable founder attributes.

Our work demonstrates that LLMs can serve as effective hypothesis generators when paired with statistical validation and structured feedback. The generated rules are not black-box predictions but interpretable features that domain experts can inspect, validate, and refine, combining the scalability of automation with the transparency of manual feature engineering.

Acknowledgements

This work was done outside of the current role that Yagiz Ihlamur holds at Amazon.

References

- [1] Ben Griffin, Joseph Ternasky, Fuat Alicant, and Yigit Ihlamur. Random rule forest (rrf): Interpretable ensembles of llm-generated questions for predicting startup success. *arXiv preprint*, 2025.
- [2] Noah Hollmann, Samuel Müller, and Frank Hutter. Large language models for automated data science: Introducing caafe for context-aware automated feature engineering. In *Advances in Neural Information Processing Systems*, 2023.
- [3] Jaehyun Nam, Kyuyoung Kim, Seunghyuk Oh, Jihoon Tack, Jaehyung Kim, and Jinwoo Shin. Optimized feature generation for tabular data via llms with decision tree reasoning. In *Advances in Neural Information Processing Systems*, 2024.
- [4] Nikhil Abhyankar, Parshin Shojaei, and Chandan K. Reddy. Llm-fe: Automated feature engineering for tabular data with llms as evolutionary optimizers. *arXiv preprint*, 2025.
- [5] Xi Ye, Yifan Shen, Yuchen Zhang, and Jiawei Han. Large language models can automatically engineer features for few-shot tabular learning. *arXiv preprint arXiv:2307.02587*, 2023.
- [6] Vojtěch Balek, Lukáš Sýkora, Vilém Sklenák, and Tomáš Kliegr. Llm-based feature generation from text for interpretable machine learning. *arXiv preprint arXiv:2409.07132*, 2024.
- [7] Yifan Zhang, Haokun Liu, and Wenhui Chen. Autoqual: An llm agent for automated discovery of interpretable features for review quality assessment. *arXiv preprint arXiv:2406.01245*, 2024.
- [8] Sichao Xiong, Yigit Ihlamur, Fuat Alicant, and Aaron Ontoyin Yin. Gptree: Towards explainable decision-making via llm-powered decision trees. *arXiv preprint arXiv:2411.08257*, 2024.

- [9] Rick Chen, Joseph Ternasky, Afriyie Kwesi Samuel, Ben Griffin, Aaron Ontoyin Yin, Zakari Salifu, Kelvin Amoaba, Xianling Mu, Fuat Alican, and Yigit Ihlamur. Vcbench: Benchmarking llms in venture capital. *arXiv preprint arXiv:2509.14448*, 2025.
- [10] Mihir Kumar, Aaron Ontoyin Yin, Zakari Salifu, Kelvin Amoaba, Afriyie Kwesi Samuel, Fuat Alican, and Yigit Ihlamur. From limited data to rare-event prediction: Llm-powered feature engineering and multi-model learning in venture capital. *arXiv preprint*, 2025.
- [11] Noah Shinn, Federico Cassano, Ashwin Gopinath, Karthik Narasimhan, and Shunyu Yao. Reflexion: Language agents with verbal reinforcement learning. *Advances in Neural Information Processing Systems*, 36, 2023.

A Prompt Template

The following is an abbreviated version of the system prompt used for rule generation. The full prompt includes eight example rules and detailed formatting instructions.

You are an expert feature engineer. Generate binary classification rules to predict startup founder success.

TASK

Generate exactly 30 binary rules. Each rule MUST be a valid Python lambda expression that takes a ‘founder’ dict and returns True or False.

OUTPUT FORMAT

1. rule_name ||| Description ||| lambda founder: <expr>

FOUNDER DATA STRUCTURE

```
founder = {
    "industry": str,
    "educations": [
        {"degree": str, "field": str,
         "qs_ranking": str}
    ],
    "jobs": [
        {"role": str, "company_size": str,
         "industry": str, "duration": str}
    ],
    "ipos": list,
    "acquisitions": list
}
```

HELPER FUNCTIONS

```
parse_qs(qs_str) -> float
parse_duration(dur_str) -> float
parse_company_size(size_str) -> int
```

RULES FOR WRITING EXPRESSIONS

1. Handle empty lists with any(), len()
2. Use .get() for dict access with defaults
3. Use .lower() for string comparisons
4. Return boolean (True/False)

For iterations beyond the first, the prompt is augmented with a feedback section containing all previously generated rules annotated with their precision lift, coverage, p-value, and significance status, followed by cluster-based gap analysis output (see Section 3.6).

B Founder Data Example

An example founder profile from VCBench (anonymized):

```
{
```

```

"industry": "Software Development",
"educations": [
  {"degree": "MS",
   "field": "Computer Science",
   "qs_ranking": "15"}
],
"jobs": [
  {"role": "CTO",
   "company_size": "51-200",
   "industry": "Software",
   "duration": "4-5"},
  {"role": "Senior Engineer",
   "company_size": "10001+",
   "industry": "Technology",
   "duration": "2-3"}
],
"ipos": [],
"acquisitions": [{"company": "StartupCo"}]
}

```

C Example Generated Rules

Table 6 shows representative rules from each iteration with their executable code and validation statistics. All expressions are reproduced verbatim from the pipeline output.

Table 6: Representative generated rules with validation statistics. Iter 1 rules were generated without feedback; Iter 2 rules were guided by cluster-based gap analysis targeting underperforming subpopulations.

Rule Name	Description	Lift	Coverage	p-value
<i>Iteration 1: Initial generation (no feedback)</i>				
prior_exit	Founder has ≥ 1 prior IPO or acquisition	$3.05\times$	3.16%	<.001
founder_scaled_200plus	Founded/co-founded company that grew to 200+ employees	$2.80\times$	2.56%	<.001
elite_qs_top10	Attended top-10 QS-ranked university	$2.18\times$	11.91%	<.001
<i>Iteration 2: Gap-targeted generation (with feedback)</i>				
cybersecurity_domain_depth	Security industry + technical security role experience	$6.54\times$	0.38%	<.001
repeat_exit_founder	Founder has ≥ 2 prior exits (IPO or acquisition)	$4.37\times$	0.62%	<.001
board_plus_exit	Board/advisory experience combined with prior exit	$3.61\times$	0.89%	<.001

D Complete Iteration Statistics

Table 7 compares rule generation quality across iterations.

Table 7: Rule generation statistics per iteration. Feedback-guided generation (Iter 2) produces more significant rules with higher mean precision lift, though with lower average coverage as the LLM targets more specialized subpopulations.

Metric	Iter 1	Iter 2
Rules generated	30	30
Significant ($p < 0.05$)	19 (63%)	21 (70%)
Mean lift (sig. rules)	$1.70\times$	$2.58\times$
Median lift (sig. rules)	$1.46\times$	$1.88\times$
Rules with lift $> 2\times$	5	10
Rules with lift $> 3\times$	1	6
Mean coverage (sig. rules)	18.2%	5.8%
Median coverage (sig. rules)	11.0%	3.0%