# Table of Contents


Introduction 1.1

1.2


## TiDB


1 TiDB 2.1

2 2.2

3 2.3

- 3.1 Key-Value 2.3.1
- 3.2 2.3.2
- 3.3 SQL 2.3.3

4 2.4

- 4.1 2.4.1
- 4.2 2.4.2

5 TiDB MySQL 2.5

6 TiDB 2.6

- 6.1 2.6.1
- 6.2 2.6.2
- 6.3 4.0 2.6.3

7 TiDB DDL 2.7

- 7.1 2.7.1
- 7.2 DDL 2.7.2
- 7.3 Sequence 2.7.3
- 7.4 AutoRandom 2.7.4

8 Titan 2.8

- 8.1 Titan 2.8.1
- 8.2 TiDB Titan 2.8.2

9 TiFlash HTAP 2.9

- 9.1 TiDB HTAP 2.9.1
- 9.2 TiFlash 2.9.2
- 9.3 TiFlash 2.9.3

10 TiDB 2.10

- 10.1 2.10.1
- 10.2 RBAC 2.10.2
- 10.3 2.10.3

11 TiSpark 2.11

- 11.1 TiSpark 2.11.1
- 11.2 TiSpark 2.11.2
- 11.3 TiSpark on TiFlash 2.11.3

11.4 TiSpark 2.11.4

1 & 3.1
1.1 TiUP & TiOps 3.1.1
1.1.1 TiUP 3.1.1.1
1.1.2 TiUP 3.1.1.2
1.1.3 TiOps 3.1.1.3
1.1.4 TiOps 3.1.1.4
1.2 TiDB on Kubernetes 3.1.2
1.2.1 TiDB-Operator 3.1.2.1
1.2.2 TIDB-Operator Kind 3.1.2.2
1.2.3 TiDB-Operator 3.1.2.3
1.2.3.1 3.1.2.3.1
1.2.3.1.1 AWS EKS TiDB 3.1.2.3.1.1
1.2.3.1.2 GCP GKE TiDB 3.1.2.3.1.2
1.2.3.1.3 TiDB 3.1.2.3.1.3
1.2.3.1.4 TiDB 3.1.2.3.1.4
1.2.3.2 3.1.2.3.2
1.2.3.2.1 3.1.2.3.2.1
1.2.3.2.2 PV 3.1.2.3.2.2
1.2.3.2.3 TiDB Operator 3.1.2.3.2.3
1.2.3.2.4 TiDB 3.1.2.3.2.4
1.2.3.2.5 3.1.2.3.2.5
1.2.3.2.6 TiDB 3.1.2.3.2.6
1.2.4 Kubernetes TiDB 3.1.2.4
1.2.5 Kubernetes BR TiDB 3.1.2.5
1.2.6 Kubernetes Lightning 3.1.2.6
1.2.7 Kubernetes TiDB 3.1.2.7
1.2.8 TiDB-Operator 3.1.2.8
1.3 3.1.3
1.3.1 TiOps 3.1.3.1
1.3.2 TiDB-Operator 3.1.3.2
1.4 3.1.4
1.4.1 TiOps 3.1.4.1
1.4.2 TiDB-Operator 3.1.4.2
1.5 3.1.5
2 TiDB 3.2
2.1 4.0 CDC 3.2.1
2.1.1 CDC 3.2.1.1
2.1.2 CDC 3.2.1.2

2.1.3 CDC 3.2.1.3
2.2 TiDB Lightning 3.2.2
2.2.1 Lightning 3.2.2.1
2.2.2 Lightning 3.2.2.2
2.3 4.0 BR 3.2.3
2.3.1 BR 3.2.3.1
2.3.2 BR 3.2.3.2
2.4 4.0 Dumpling 3.2.4
2.4.1 Dumpling 3.2.4.1
2.4.2 Dumpling 3.2.4.2

# TiDB Troubleshooting

1 SQL 4.1
1.1 TiDB 4.1.1
1.2 4.1.2
1.3 SQL Plan Management 4.1.3
1.4 4.1.4
1.5 SQL 4.1.5
2 TiDB Dashboard 4.2
2.1 4.2.1
2.2 SQL 4.2.2
2.3 4.2.3
2.4 4.2.4
2.5 CPU 4.2.5
3 4.3
3.1 4.3.1
3.2 4.3.2
3.3 4.3.3
3.4 4.3.4
3.5 SQL 4.3.5
3.6 Processlist 4.3.6
3.7 Statement Summary 4.3.7
4 TiDB 4.4
4.1 4.4.1
4.2 TiDB 4.4.2
4.4 Prometheus 4.4.3
5 4.5
5.1 GC 4.5.1
5.2 Recover/Flashback 4.5.2
5.3 4.5.3
6 TiDB-Operator Troubleshooting 4.6

# TiDB


1 5.1
2 5.2
3 5.3
3.1 Sysbench 5.3.1
3.2 TPC-C 5.3.2
4 5.4
4.1 binlog 5.4.1
4.2 Raft 5.4.2
4.3 5.4.3
4.4 AWS AZ TiDB 5.4.4
5 5.5
5.1 MySQL TiDB DM 5.5.1
5.1.1 DM MySQL TiDB 5.5.1.1
5.1.2 DM MySQL TiDB 5.5.1.2
5.2 Oracle TiDB OGG 5.5.2
5.3 SqlServer TiDB 5.5.3
5.4 SqlServer TiDBDATAX 5.5.4
5.5 DB2 TiDB CDC 5.5.5
5.6 TiDB TiDBDATAX 5.5.6
5.7 Mongodb TiDB 5.5.7
6 5.6
6.1 5.6.1
6.1.1 5.6.1.1
6.1.2 TiDB 5.6.1.2
6.1.3 5.6.1.3
6.1.4 5.6.1.4
6.1.5 hint 5.6.1.5
6.2 SQL 5.6.2
6.3 TiDB + TiSpark 5.6.3
6.4 5.6.4
6.4.1 TiDB 5.6.4.1
6.4.2 TiDB 5.6.4.2
6.4.3 TiDB 5.6.4.3
6.4.4 TiDB 5.6.4.4
6.5 TiDB 5.6.5
6.6 TiDB HBaseESDruid 5.6.6
6.7 TiDB SaikuGrafana 5.6.7
7 5.7
7.1 Oncall 5.7.1
7.2 5.7.2

7.3 TiKV is busy 5.7.3
7.4 TiDB OOM 5.7.4
7.5 TiKV 5.7.5
8 TiDB 5.8
8.1 TiDB 5.8.1
8.2 TiKV 5.8.2
8.2.1 TiKV 5.8.2.1
8.2.2 Region 5.8.2.2
8.2.3 5.8.2.3
8.3 5.8.3
8.3.1 TiDB 5.8.3.1
8.3.2 5.8.3.2

# TiDB

1 TiDB 6.1
1.1 TiDB 6.1.1
1.2 TiDB 6.1.2
1.3 TiDB 6.1.3
1.4 TiDB 6.1.4
2 TiDB 6.2
2.1 6.2.1
2.1.1 TiDB Devcon 6.2.1.1
2.1.2 TiDB TechDay 6.2.1.2
2.1.3 Infra Meetup 6.2.1.3
2.1.4 TiDB Hackathon 6.2.1.4
2.1.5 TUG 6.2.1.5
2.2 TUGTiDB User Group 6.2.2
2.3 Talent Plan 6.2.3
2.4 Challenge Program 6.2.4
2.5 PingCAP Incubator 6.2.5
2.6 PingCAP University 6.2.6
2.7 AskTUG 6.2.7
2.8 Contributor Map 6.2.8

7.1

# Gitbook

Read it: TiDB In Action: based on 4.0

Download PDF: TiDB In Action: based on 4.0

- Project
- TODO
-
- Pull Request

- markdown.
- Github

`res/{doc-path}/`

- `{doc-path}`

- `session1/chapter1/tidb-intro.md`
- `/res/session1/chapter1/tidb-intro/`
- markdown `![1.png](/res/session1/chapter1/tidb-intro/1.png)`

# TiDB in Action

TiDB in Action

-
- TiDB

-
-
-

-
  -
  -

- 
  - 
- 
- 
- 
- 
- 

--

- 
- 
  - 
  - 
  - 
  - 

markdown

```
<!--TODO:/-->
```

# License

Shield: License CC BY-SA 4.0

This work is licensed under a Creative Commons Attribution-ShareAlike 4.0 International License.

# 1 TiDB

TiDB TiDB NewSQL TiDB

- 
- SQL MySQL MySQL MySQL
- 
- ACID
- 

TiDB 4.0 TiDB

TiDB Google Spanner F1 TiDB

TiDB

1. TiDB (tidb-server, https://github.com/pingcap/tidb): SQL MySQL endpoint SQL TiDB TiDB TiDB tidb-server SQL TiKV
2. TiKV (tikv-server, https://github.com/pingcap/tikv) : KV NoSQL TiDB TiKV NoSQL TiKV API KV SI Snapshot Isolation TiDB SQL TiDB SQL SQL SQL TiKV API TiKV TiKV 3 TiFlash TiKV TiFlash
3. Placement Driver (pd-server PD https://github.com/pingcap/pd): TiDB TiKV Dashboard IDPD PD TiKV TiKV PD 3

# 2

TiDB TiKV

## 2.1 Key-Value Pairs ()

TiKV Key-Value TiKV

1. Map C++ std::map Key-Value Pairs
2. Map Key-Value pair Key Seek Key Next Key Key-Value

SQL

**TiKV KV SQL Table**

SQL TiKV Key-Value

## 2.2 RocksDB

TiKV TiKV RocksDB RocksDB RocksDB Facebook KV TiKV RocksDB Key-Value Map

## 2.3 Raft

TiKV

TiKV Raft Raft Multi Paxos Raft Raft Raft

1. Leader
2. Leader
3.

TiKV Raft Raft Raft Raft

RocksDBTiKV Raft Raft RocksDB RaftTiKV Key-Value Raft

## 2.4 Region

Region TiKV KV Map Raft Raft KV

- Hash Key Hash Hash
- Range Key Range Key

TiKV Key-Value Key Region Region TiKV 96MB Region [StartKeyEndKey)

Region SQL SQL KV Region TiKV

- Region Region
- Region Raft

Key Region Region TiDB PD Region Region PD Region Key Key Region Region Key PD

TiKV Region Region TiKV ReplicaReplica Raft Region Replica Raft Group Replica Group Leader Replica Follower Leader Leader Leader Follower Region

Region KeyValue

## 2.5 MVCC

MVCCTiKV Key Value TiKV MVCC Key MVCC TiKV

```
Key1 -> Value
Key2 -> Value
……
KeyN -> Value
```

MVCC TiKV Key

```
Key1_Version3 -> Value
Key1_Version2 -> Value
Key1_Version1 -> Value
……
Key2_Version4 -> Value
Key2_Version3 -> Value
Key2_Version2 -> Value
Key2_Version1 -> Value
……
KeyN_Version2 -> Value
KeyN_Version1 -> Value
……
```

Key Key-Value Key Key + Version Value Key Version MVCC Key Key_Version RocksDB SeekPrefix(Key_Version) API Key_Version

## 2.6 ACID

TiKV Google BigTable PercolatorTiKV

TiKV API

```
tx = tikv.Begin()
    tx.Set(Key1, Value1)
    tx.Set(Key2, Value2)
    tx.Set(Key3, Value3)
tx.Commit()
```

3 Set TiKV TiDB SQL SQL KV SQL KV TiDB MySQL

# 3

NewSQL TiDB TiKV TiDB TiKV (Key, Value) TiDB TiDB SQL TiKV TiDB TiKV TiFlash TiFlash TiFlash HTAP )

# 3.1 Key-Value

TiDB (Key, Value)

1.
2.

## 3.1.1 Key-Value

(Key, Value) KeyOLTP Key ID ID OLAP Key

1. TiDB ID `TableID` ID
2. TiDB ID `RowID` ID IDTiDB TiDB ID

(Key, Value)

```
Key:   tablePrefix{TableID}_recordPrefixSep{RowID}
Value: [col1, col2, col3, col4]
```

`tablePrefix` `recordPrefixSep` Key

## 3.1.2 Key-Value

TiDB TiDB ID `IndexID`

RowID (Key, Value)

```
Key:   tablePrefix{tableID}_indexPrefixSep{indexID}_indexedColumnsValue
Value: RowID
```

RowID (Key, Value)

```
Key:   tablePrefix{TableID}_indexPrefixSep{IndexID}_indexedColumnsValue_{RowID}
Value: null
```

## 3.1.3

`tablePrefix` `recordPrefixSep` `indexPrefixSep` Key

```
tablePrefix     = []byte{'t'}
recordPrefixSep = []byte{'r'}
indexPrefixSep  = []byte{'i'}
```

Key Key TiKV Key TiKV `RowID` TiKV Key `indexedColumnsValue` Key

## 3.1.4 Key-Value

TiDB Key-Value TiDB

```
CREATE TABLE User {
    ID int,
    Name varchar(20),
    Role varchar(20),
    Age int,
    PRIMARY KEY (ID),
    KEY idxAge (Age)
};
```

3

```
1, "TiDB", "SQL Layer", 10
2, "TiKV", "KV Engine", 20
3, "PD", "Manager", 30
```

(Key, Value) `int` `RowID` `TableID` 10 TiKV

```
t10_r1 --> ["TiDB", "SQL Layer", 10]
t10_r2 --> ["TiKV", "KV Engine", 20]
t10_r3 --> ["PD", "Manager", 30]
```

`idxAge` `IndexID` 1 TiKV

```
t10_i1_10_1 --> null
t10_i1_20_2 --> null
t10_i1_30_3 --> null
```

TiDB Key-Value

# 3.2

(Key, Value) TiDB `Database` `Table` TiDB TiKV

`Database` / `Table` ID ID Key-Value ID Key `m_` KeyValue

TiDB (Key, Value) DDL 1TiDB pd-server etcd Key "/tidb/ddl/global_schema_version"Value int64 TiDB Google F1 Online Schema etcd

# 3.3 SQL

TiDB SQL tidb-server Google F1 SQL Key-Value Key-Value TiKV TiKV

## 3.3.1 SQL

Key-Value SQL KV KV

`select count(*) from user where name = "TiDB"` `name` `TiDB`

1. Key Range `RowID` `[0, MaxInt64)` `0` `MaxInt64` `Key` `[StartKey, EndKey)`
2. Key Range Key Range TiKV
3. `name = "TiDB"`
4. `Count(*)` `Count(*)`

Work Work

1. KV TiKV RPC
2.
3.

## 3.3.2 SQL

RPC SQL `Count(*)` `Count(*)` SQL `Count(*)`

### 3.3.3 SQL

SQL TiDB SQL

SQL `Load Balancer` tidb-servertidb-server `MySQL Protocol Packet` SQL TiKV tidb-server TiKV tidb-server

# 4

TiKVTiDB KV SQL PDPlacement Driver TiKV

## 4.1

### 4.1.1

TiKV TiDB KV Region Region Replica Replica TiKV Leader /Follower Leader raft log

- Region Replica TiKV
- TiKV Raft Group Replica
- TiKV ?
- 
  - 
    - 
    - 
  - Raft Group N Raft Group Replica
    - Replica
    - Replica
- / Leader Leader
- Region Region
- IO CPU

Raft Group Region PD

### 4.1.2

- 
- 
- 
- 

- Leader
- 
- 
- 
- /

Raft Group PD

### 4.1.3

- Replica
- Replica
- Leader Raft Group Replica transfer

Raft AddReplicaRemoveReplicaTransferLeader

### 4.1.4

TiKV Region TiKV PD TiKV Region

**TiKV PD**

TiKV Store PD PD Store Store Store

- 
- 
- Region
- /
- / Snapshot Replica Snapshot
- 
- labels Tag

**Raft Group Leader PD Region**

Raft Group Leader PD Region

- Leader
- Followers
- Replica
- /

PD PD Store PD 30 Store Store Region PD PD Store PD Store Region

### 4.1.5

PD

**Region Replica**

PD Region Leader Region Replica Add/Remove Replica Replica

- Region Replica
- Replica Region Replica Replica
- max-replicas

**Raft Group Replica**

PD Replica Replica

- 
- TiKV
- TiKV IDC

Region Replica labels PD location-labels label Replica Region Replica

**Store**

region

**Leader Store**

Raft  Leader  Leader PD  Leader

**Store**

Store  Region Leader  Key /PD

**Store**

Store  Capacity  Store PD

CPU IO PD  PD

### 4.1.6

PD  Store  Leader  Region Leader PD  Region  Region Leader Region Leader  Region Leader

### 4.1.7

# 4.2

***Elastic Schedule*** TiDB 4.0 TiDB ***Adaptive Capacity*** TiDB workload TiDB DBaaS

## 4.2.1

TiDB IDC

TiDB TiDB Operator 4.0

- 
- 

## 4.2.2

Auto-Scale

Aurora CPU TiDB Server TiKV ServerQPSTiKV Server

TiDB TiDB Operator PD Auto-Scale

- TiDB Operator API TiDB / TiKV
- TiDB Operator TiDB / TiKV metrics PD
- TiDB Operator Auto-Scaling `TidbCluster.Spec.Replicas` Auto-Scaling

TiDB Operator AutoScaler API AutoScaler Controller AutoScaler API

```
apiVersion: pingcap.com/v1alpha1
kind: TidbClusterAutoScaler
metadata:
  name: autoscaler
  namespace: ela-demo
spec:
  cluster:
    name: ela-scheduling
    namespace: ela-demo
  metricsUrl: http://monitor-prometheus.ela-demo.svc:9090
  tidb:
    minReplicas: 8
    maxReplicas: 8
    scaleOutIntervalSeconds: 100
    scaleInIntervalSeconds: 100
    metricsTimeDuration: "1m"
    metrics:
      - type: "Resource"
        resource:
          name: "cpu"
          target:
            type: "Utilization"
            averageUtilization: 90
  tikv:
    minReplicas: 3
    maxReplicas: 5
    scaleOutIntervalSeconds: 100
    scaleInIntervalSeconds: 100
    metricsTimeDuration: "1m"
    metrics:
      - type: "Resource"
        resource:
          name: "cpu"
          target:
            type: "Utilization"
            averageUtilization: 70
```

- minReplicas
- maxReplicas
- scaleOutIntervalSeconds scale-out
- scaleInIntervalSeconds scale-in

TiDB TiDB TiKV PD Region

### 4.2.3

TiDB Operator TiKV PD Region

1.
2.
3.
4.

Region 2 4

1. ( Load Base Splitting)

TiDB Region TiDB 4.0 Region CRDB QPS Region QPS 20 key key key Region

1. (Isolate Frequently Access Region

TiKV Range TiDB workload non-uniform shard_bits workload TiDB PD

### 4.2.4

TiDB 4.0 TiDB Operator DBaaS TiDB 4.0 TiDB workload TiDB Follower Read TiFlash TIDB HTAP “”

# 5 TiDB MySQL

TiDB NewSQL SQL ACID TiDB MySQL MySQL MySQL TiDB

MySQL TiDB MySQL TiDB

TiDB MySQL

## 5.1

TiDB MySQL

| | **SQL** | |
|---|---|---|
| | | |

4.0 TiDB MySQL

| | **MySQL** | **TiDB** |
|---|---|---|
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| JSON | | MySQL 8.0 |
| | | |
| | | asciilatin1binaryutf8utf8mb4 |
| / | | alter-primary-key |
| CREATE TABLE tblName AS SELECT stmt | | |
| CREATE TEMPORARY TABLE | | TiDB TEMPORARY |
| DML affected rows | | |
| AutoRandom | | |
| Sequence | | |

## 5.2

(1)

TiDB

```
tidb> SHOW CHARACTER SET;
+---------|---------------|-------------------|--------+
| Charset | Description   | Default collation | Maxlen |
+---------|---------------|-------------------|--------+
| utf8    | UTF-8 Unicode | utf8_bin          |      3 |
| utf8mb4 | UTF-8 Unicode | utf8mb4_bin       |      4 |
| ascii   | US ASCII      | ascii_bin         |      1 |
| latin1  | Latin1        | latin1_bin        |      1 |
| binary  | binary        | binary            |      1 |
+---------|---------------|-------------------|--------+
5 rows in set (0.00 sec)
```

TiDB `utf8mb4` MySQL 5.7 `latin1` MySQL 8.0 `utf8mb4` `utf8` `utf8mb4` TiDB UTF8 `incorrect utf8 value` MySQL 8.0 MySQL 5.7 UTF8 TiDB TiDB "tidb_skip_utf8_check" UTF8 TiDB

Collation `utf8` Collation `utf8_bin` TiDB Collation MySQL

| | TiDB Collation | MySQL 5.7 Collation | MySQL 8.0 Collation |
|---|---|---|---|
| utf8 | utf8_bin | utf8_general_ci | utf8_general_ci |
| utf8mb4 | utf8mb4_bin | utf8mb4_general_ci | utf8mb4_0900_ai_ci |
| ascii | ascii_bin | ascii_general_ci | ascii_general_ci |
| latin1 | latin1_bin | latin1_swedish_ci | latin1_swedish_ci |
| binary | binary | binary | binary |

4.0 TiDB Collation Collation MySQL Collation `PADDING`

```
tidb> create table t(a varchar(20) charset utf8mb4 collate utf8mb4_general_ci primary key);
Query OK, 0 rows affected
tidb> insert into t values ('A');
Query OK, 1 row affected
tidb> insert into t values ('a');
Query OK, 1 row affected // MySQL  utf8mb4_general_ci  Duplicate entry 'a'.
tidb> insert into t1 values ('a ');
Query OK, 1 row affected // MySQL  Duplicate entry 'a '
```

TiDB 4.0 Collation MySQL Collation `new_collation_enabled_on_first_boostrap` Collation `mysql.tidb` `new_collation_enabled` Collation

```
tidb> select VARIABLE_VALUE from mysql.tidb where VARIABLE_NAME='new_collation_enabled';
+----------------+
| VARIABLE_VALUE |
+----------------+
| True           |
+----------------+
1 row in set (0.00 sec)
```

Collation TiDB `utf8mb4_general_bin` `utf8_general_bin` `PADDING` `utf8mb4_general_ci` `utf8_general_ci` Collation MySQL

(2)

MySQL `system_time_zone` MySQL `TZ` `--timezone`

TiDB TiDB TiDB TiDB `TZ` `mysql.tidb`

```
tidb> select VARIABLE_VALUE from mysql.tidb where VARIABLE_NAME='system_tz';
+----------------+
| VARIABLE_VALUE |
+----------------+
| Asia/Shanghai  |
+----------------+
1 row in set (0.00 sec)
```

`system_time_zone` `system_tz`

```
tidb> select @@system_time_zone;
+--------------------+
| @@system_time_zone |
+--------------------+
| Asia/Shanghai      |
+--------------------+
1 row in set (0.00 sec)
```

TiDB `time_zone`

```
tidb> set @@global.time_zone='UTC';
Query OK, 0 rows affected (0.00 sec)
```

# 6.1

ACID TiDB Percolator

## 6.1.1

AtomicityConsistencyIsolationDurability ACID

### 6.1.1.1

SQL-92 4 (READ UNCOMMITTED) (READ COMMITTED) (REPEATABLE READ) (SERIALIZABLE)

| Isolation Level | Dirty Write | Dirty Read | Fuzzy Read | Phantom |
|---|---|---|---|---|
| READ UNCOMMITTED | Not Possible | Possible | Possible | Possible |
| READ COMMITTED | Not Possible | Not possible | Possible | Possible |
| REPEATABLE READ | Not Possible | Not possible | Not possible | Possible |
| SERIALIZABLE | Not Possible | Not possible | Not possible | Not possible |

### 6.1.1.2

- OCC
- PCC

## 6.1.2 TiDB

TiDB Google Percolator ACIDSnapshot IsolationTiDB TiKV

### 6.1.2.1 Snapshot Isolation

Percolator MVCCTiDB PD TSO

- start timestamp commit timestamp
- start timestamp
- timestamp

### 6.1.2.2 2PC

TiDB (Two-Phase Commit Prewrite Commit

- Prewrite Key lock TiDB Key Primary Key Primary Key
- CommitPrewrite Primary Key Secondary Keys

Percolator Coordinator

### 6.1.2.3

1.
2. TiDB PD tso start timestamp
3.
4. Commit
5. TiDB

   i. TiDB Key Primary Key

   ii. TiDB TiKV Prewrite TiKV Prewrite

   iii. TiDB Prewrite Prewrite

   iv. TiDB PD commit timestamp

   v. TiDB Primary Key TiKV TiKV Commit Prewrite

6. TiDB
7. TiDB

## 6.1.3

### 6.1.3.1

4 RTTRound trip time

- PD 2 Timestamp
- Prewrite Commit

query `autocommit = 1`

```
UPDATE my_table SET a='new_value' WHERE id = 1;
UPDATE my_table SET a='newer_value' WHERE id = 2;
UPDATE my_table SET a='newest_value' WHERE id = 3;
```

```
START TRANSACTION;
UPDATE my_table SET a='new_value' WHERE id = 1;
UPDATE my_table SET a='newer_value' WHERE id = 2;
UPDATE my_table SET a='newest_value' WHERE id = 3;
COMMIT;
```

`INSERT`

### 6.1.3.2

TiDB

- OOM (Out of Memory)
-
-

TiDB 100500

### 6.1.3.3

(1) TiKV Prewrite TiDB TiDB

- TiDB TiDB TiKV
- TiKV Prewrite TiDB TiDB TiDB TiKV

TiDB

`txn-local-latches`：

- enable
  -
  - false
- capacity
  - Hash slot 2 slot 32 Bytes
  - 1024000

**capacity** Key Key Hash Hash **capacity** Hash

- capacity
- capacity

TiKV TiKV hash

- scheduler-concurrency
  - scheduler Key Key hash
  - 2048000

TiKV latch

Scheduler latch wait duration

(2) 2

```
ERROR 8005 (HY000) : Write Conflict, txnStartTS is stale
```

MySQL SQL MySQL TiDB TiDB SQL `tidb_disable_txn_auto_retry = off` `tidb_retry_limit`

- `tidb_disable_txn_auto_retry` 1
- `tidb_retry_limit`

set

- session

  ```
  set @@tidb_disable_txn_auto_retry = 0;
  set @@tidb_retry_limit = 10;
  ```

- 

  ```
  set @@global.tidb_disable_txn_auto_retry = 0;
  set @@global.tidb_retry_limit = 10;
  ```

`tidb_retry_limit` 0 TiDB ( `try again later` )

(3) TiDB

1. start timestamp
2. SQL
3. 

SQL SQL start timestamp start timestamp

`SELECT FOR UPDATE` `SELECT FOR UPDATE`

TiDB

## 6.1.3.4 GC

TiDB MVCCGC

GC 10 GC TiDB `safe point` 10 TiDB `safe point`

TiDB GC `mysql.tidb` SQL

```
select VARIABLE_NAME, VARIABLE_VALUE from mysql.tidb;
```

GC

```
update mysql.tidb set VARIABLE_VALUE="24h" where VARIABLE_NAME="tikv_gc_life_time";
```

GC TiKV `gc.max-write-bytes-per-sec` GC worker 0

## 6.1.4

```
MySQL [test]> insert into tran select id,star from eyesight.t_request;
Query OK, 3327 rows affected (0.17 sec)
Records: 3327  Duplicates: 0  Warnings: 0
MySQL [test]>
```

`BEGIN` `COMMIT`

```
Database changed
MySQL [test]> set autocommit=0;
Query OK, 0 rows affected (0.00 sec)

MySQL [test]> begin;
Query OK, 0 rows affected (0.00 sec)

MySQL [test]> update tran set b=8888;
Query OK, 3327 rows affected (0.12 sec)
Rows matched: 3327  Changed: 3327  Warnings: 0

MySQL [test]> commit;
Query OK, 0 rows affected (2.31 sec)

MySQL [test]>
```

```
Database changed
MySQL [test]> set autocommit=0;
Query OK, 0 rows affected (0.00 sec)

MySQL [test]> begin;
Query OK, 0 rows affected (0.00 sec)

MySQL [test]> update tran set b=9999;
Query OK, 3327 rows affected (0.04 sec)
Rows matched: 3327  Changed: 3327  Warnings: 0

MySQL [test]> commit;
Query OK, 0 rows affected (1.17 sec)

MySQL [test]>
```

TiDB `tidb.log` `startTs(415144181973647361)` `startTs(415144181960540213)` `415144181973647361` ()

```
[2020/03/08 14:36:17.121 +08:00] [WARN] [session.go:419] [sql] [label=internal] [error="[kv:9007]Write conflict, txnS
tartTS=415144181973647361, conflictStartTS=415144181960540213, conflictCommitTS=415144182052290562, key={tableID=19,
indexID=1, indexValues={415144166153256976, 114421, }} primary={tableID=19, indexID=1, indexValues={41514416615325697
6, 114421, }} [try again later]"] [txn="Txn{state=invalid}"]
[2020/03/08 14:36:17.121 +08:00] [WARN] [session.go:611] [retrying] [schemaVersion=1813] [retryCnt=0] [queryNum=1] [s
ql="update mysql.stats_meta set version = 415144181973647361, count = count + 52587, modify_count = modify_count + 52
587 where table_id = 1807"]
[2020/03/08 14:36:17.125 +08:00] [WARN] [session.go:632] ["transaction association"] ["retrying txnStartTS"=415144182
301327413] ["original txnStartTS"=415144181973647361] startTs
[2020/03/08 14:36:17.279 +08:00] [INFO] [2pc.go:1039] ["2PC clean up done"] [txnStartTS=415144181973647361]
```

`commit` (2.311.17) `SELECT`

```
MySQL [test]> select * from tran limit 2;
+--------+------+
| a      | b    |
+--------+------+
| 100007 | 8888 |
| 100036 | 8888 |
+--------+------+
2 rows in set (0.00 sec)
MySQL [test]>
```

## 6.1.5

### 6.1.5.1 tikv--server

lock

### 6.1.5.2 tidb-transaction

Transaction Retry Num
1.25
1.00
0.75
0.50
0.25
0
15:50
16:00
16:10
16:20
16:30
16:40
100
99
90

Local Latch Wait Duration
4 ms
2 ms
977 µs
488 µs
244 µs
15:50
16:00
16:10
16:20
16:30
16:40
99
95
80

# 6.2

TiDB TiDB v3.0 TiDB

## 6.2.1

- v3.0.8 TiDB
- TiDB

## 6.2.2 Percolator

Percolator Prewrite Acquire Pessimistic Lock Prewrite

- DML TiKV raft
- Write Conflictkey
- Key Prewrite Percolator
- Percolator Prewrite Write Conflict

基于 Percolator 的悲观事务

### 6.2.2.1

TiKV `Waiter Manager` `Waiter Manager` TiKV start timestamp

### 6.2.2.2

`Waiter Manager` `TiDB`

- TiKV leader
- leader

Raft leader leader

## 6.2.3

### 6.2.3.1

TiDB

- 
- 

### 6.2.3.2

v3.0.8 TiDB :

- `BEGIN PESSIMISTIC ;`

  `BEGIN /*!90000 PESSIMISTIC */;` MySQL
- `set @@tidb_txn_mode = 'pessimistic';` session autocommit
- `set @@global.tidb_txn_mode = 'pessimistic';` session autocommit

`set @@global.tidb_txn_mode = '';`

### 6.2.3.3 Batch DML

DML TiKV DML DML DML

INSERT TiKV

```
BEGIN;
INSERT INTO my_table VALUES (1);
INSERT INTO my_table VALUES (2);
INSERT INTO my_table VALUES (3);
COMMIT;
```

INSERT

```
BEGIN;
INSERT INTO my_table VALUES (1), (2), (3);
COMMIT;
```

## 6.2.3.4

TiDB 2

MySQL Repeatable Read

TiDB MySQL InnoDB

1. TiDB range WHERE DML `SELECT FOR UPDATE` `INSERT`

   InnoDB gap lock range `INSERT` statement based binlog READ COMMITTED gap lock TiDB gap lock

2. TiDB `SELECT LOCK IN SHARE MODE`

3. DDL

   MySQL DDL TiDB DDL `ERROR 1105 (HY000): Information schema is changed. [try again later]`

4. `START TRANSACTION WITH CONSISTENT SNAPSHOT` MySQL TiDB

5. autocommit

   DML autocommit TiDB

   select for update

`SET SESSION TRANSACTION ISOLATION LEVEL READ COMMITTED;` Oracle Read Committed

Oracle TiDB

# 6.3 4.0

## 6.3.1

DBA TiDB `transaction too large`

PingCAP FAQ

> 4.3.3 `Transaction too large`
>
> Raft Raft
>
> - SQL 5000
> - KV entry 6MB
> - KV entry 30w
> - KV entry 100MB

Google Cloud Spanner TiDB

- MySQL/Oracle TiDB `statement count 5001 exceeds the transaction limitation`
- kv 30W 10W `ERROR 8004 (HY000): transaction too large, len:300001`

asktug4.0 TiDB

## 6.3.2

4.0

- Prewrite Prewrite
- Prewrite

4.0

### 6.3.2.1 Min Commit Timestamp

TiDB Snapshot Isolation `start timestamp` `commit timestamp` `start timestamp`

TiDB Primary Lock `minCommitTs` `commit timestamp` `start timestamp` Primary Lock

### 6.3.2.2 Time to live(TTL)

Percolator Prewrite TiDB TiDB TTL

v4.0 TTL v4.0 `TTL Manager` Primary Lock TTL

## 6.3.3

TiDB

```
[performance]
txn-total-size-limit = 104857600
```

10737418240(10G) v3.x v4.0

(1) 3.0.5

```
mysql> insert into t1 (name, age) select name, age from t1;
Query OK, 131072 rows affected (1.86 sec)
Records: 131072  Duplicates: 0  Warnings: 0

mysql> select count(1) from t1;
+----------+
| count(1) |
+----------+
|   262144 |
+----------+
1 row in set (0.14 sec)

mysql> insert into t1 (name, age) select name, age from t1;
ERROR 8004 (HY000): transaction too large, len:300001
```

(2) 4.0

```
MySQL [test]> select count(1) from t1;
+----------+
| count(1) |
+----------+
|   262144 |
+----------+
1 row in set (0.20 sec)

MySQL [test]> insert into t1 (name, age) select name, age from t1;
Query OK, 262144 rows affected (9.20 sec)
Records: 262144  Duplicates: 0  Warnings: 0

MySQL [test]> select count(1) from t1;
c+----------+
| count(1) |
+----------+
|   524288 |
+----------+
1 row in set (0.52 sec)

MySQL [test]> create table t2 like t1;
Query OK, 0 rows affected (0.11 sec)

MySQL [test]> insert into t2 select * from t1;
Query OK, 524288 rows affected (17.61 sec)
Records: 524288  Duplicates: 0  Warnings: 0
```

4.0 `tidb_batch_insert`

## 6.3.4

TiDB GC 10min `gc_life_time` v4.0 `safepoint` `start timestamp`

- kv 6MB `Blob` TiDB
- 10GB 10GB 10GB
- 3~4 10GB 30~40GB

# 7 TiDB DDL

DDL TiDB Google F1 schema

TiDB DDL 4.0

1. 3
2. DDL DDL DDL
3. Sequence 3
4. AutoRandom

# 7.1

## 7.1.1

(schema) case

## 7.1.2

TIDB

TiDB Region Region 96MBRegion Region Raft Group Raft Group Leader TiDB Follower-ReadLeader PD

Region Region Region TIDB

## 7.1.3

### 1.

MySQL InnoDB DBA ID

TiDB Region TiDB Region Region PD Region Region Region TiKV Region TiDB Region TiKV Region

TiDB 3.0

Grafana ***Grafana*** > ***TiKV-Trouble-Shooting*** > ***Hot write***

store QPS CPU pd-ctl Region region_id

```
pd-ctl -u "http://{{pd-instance}}:2379" -d region topwrite
```

region_id

```
curl http://{{tidb-instance}}:10080/regions/{{region_id}}
```

Region Region Region TiDB

TiDB PK PK rowID_tidb_rowid SHARD_ROW_ID_BITS rowID Region RPC CPU

- SHARD_ROW_ID_BITS = 4 2^416
- SHARD_ROW_ID_BITS = 6 2^664
- SHARD_ROW_ID_BITS = 0 1

```
CREATE TABLE t (c int) SHARD_ROW_ID_BITS = 4;
ALTER TABLE t SHARD_ROW_ID_BITS = 4;
```

SHARD_ROW_ID_BITS Region

TiDB 3.1.0 `AUTO_RANDOM` `AUTO_INCREMENT` TiDB ID AUTO_RANDOM

## 2.

TiDB case

```
CREATE TABLE IF NOT EXISTS TEST_HOTSPOT(
      id         BIGINT PRIMARY KEY,
      age        INT,
      user_name  VARCHAR(32),
      email      VARCHAR(128)
)
```

id id TiDB

TiKV Region:

```
[CommonPrefix + TableID, CommonPrefix + TableID + 1)
```

Region

TiKV Region Leader Store Store Region Leader Region 23 Region 1 TiKV-Node 1

PD Node 1 Leader Node TiKV Region Node PD Region

Region

**Region**

shard_row_id_bits Region pre_split_regions pre_split_regions shard_row_id_bits 2^(pre_split_regions) Region

```
CREATE TABLE t (a INT, b INT, INDEX idx1(a)) SHARD_ROW_ID_BITS = 4 PRE_SPLIT_REGIONS = 2;
```

**Split Region Region**

Split Region TiDB Region Region TiKV

- BETWEEN lower_value AND upper_value REGIONS region_num Region region_num Region

  ```
  SPLIT TABLE table_name [INDEX index_name] BETWEEN (lower_value) AND (upper_value) REGIONS region_num
  ```

- BY value_list… Region

  ```
  SPLIT TABLE table_name [INDEX index_name] BY (value_list) [, (value_list)] ...
  ```

Region Merge split Region split split-merge-interval Region Region Merge Region Merge

TiDB 4.0 TiDB 4.0 PD Load Based Splitting Region QPS Region

## 3.

delete TiDB KV RocksDB delete

1. TiDB TiKV
2. delete
3. TiKV
4. RocksDB Compaction

TiDB Delete Ranges

1. TiDB gc_delete_range
2. Delete Ranges gc_delete_range safe point

TiDB TiKV TiKV delete TiKV RocksDB compaction

## 4.

case

- 
- TiDB MySQL DECIMAL
- 
- case TiDB 70 TP99 130ms 7 TP99 60ms

### 7.1.4

case GC

# 7.2 DDL

## 7.2.1 TiDB DDL

DDL SQL DDL SQL DDL DDL

TiDB DDL SQL SQL DBA TiDB

## 7.2.2 DDL

TiDB MySQL ADMIN DDL DDL admin

- schema versionowner DDL

```
ADMIN SHOW DDL;
```

- DDL ( DDL ) NUM ( 10 ) DDL `ADMIN SHOW DDL JOBS [NUM] [WHERE where_condition];`
  - DDL 5 DDL

    ```
    ADMIN SHOW DDL JOBS 5;
    ```

  - test DDL 5 DDL

    ```
    ADMIN SHOW DDL JOBS 5 WHERE state!='synced' AND db_name='test';
    ```

- JOB_ID DDL

```
ADMIN SHOW DDL JOB QUERIES job_id [, job_id] ...;
```

- DDL

```
ADMIN CANCEL DDL JOBS job_id [, job_id] ...;
```

- JOB_ID `RECOVER TABLE table_name`

```
RECOVER TABLE BY JOB ddl_job_id;
```

DDL `ADD INDEX` mysql-client `ctrl+c` DDL DDL

```
> admin@sbtest02:04:32>alter table sbtest1 add key idx_c_pad(c, pad);
^CCtrl-C -- sending "KILL QUERY 15768094" to server ...
Ctrl-C -- query aborted.
^CCtrl-C -- exit!
Aborted
```

`ADMIN SHOW DDL` `ctrl+c` DDL

```
> admin@(none)02:04:56>ADMIN SHOW DDL\G
*************************** 1. row ***************************
   SCHEMA_VER: 6765
     OWNER_ID: 828a4567-91a5-4070-b55f-f90702e80e7a
OWNER_ADDRESS: 10.40.216.9:4000
 RUNNING_JOBS: ID:8406, Type:add index, State:running, SchemaState:write reorganization, SchemaID:7299, TableID:7380,
 RowCount:196608, ArgLen:0, start time: 2020-03-07 14:04:53.321 +0800 CST, Err:<nil>, ErrCount:0, SnapshotVersion:415
121039339290634
      SELF_ID: 828a4567-91a5-4070-b55f-f90702e80e7a
        QUERY: alter table sbtest1 add key idx_c_pad(c, pad)
1 row in set (0.02 sec)
```

TiDB HTTP owner TiDB TiDB `ddl_id` `lease`

```
#
curl http://{TiDBIP}:10080/info/all
#
$curl http://127.0.0.1:10080/info/all
{
    "servers_num": 2,
    "owner_id": "29a65ec0-d931-4f9e-a212-338eaeffab96",
    "is_all_server_version_consistent": true,
    "all_servers_info": {
        "29a65ec0-d931-4f9e-a212-338eaeffab96": {
            "version": "5.7.25-TiDB-v4.0.0-alpha-669-g8f2a09a52-dirty",
            "git_hash": "8f2a09a52fdcaf9d9bfd775d2c6023f363dc121e",
            "ddl_id": "29a65ec0-d931-4f9e-a212-338eaeffab96",
            "ip": "",
            "listening_port": 4000,
            "status_port": 10080,
            "lease": "45s",
            "binlog_status": "Off"
        },
        "cd13c9eb-c3ee-4887-af9b-e64f3162d92c": {
        "version": "5.7.25-TiDB-v4.0.0-alpha-669-g8f2a09a52-dirty",
        "git_hash": "8f2a09a52fdcaf9d9bfd775d2c6023f363dc121e",
        "ddl_id": "cd13c9eb-c3ee-4887-af9b-e64f3162d92c",
        "ip": "",
        "listening_port": 4001,
        "status_port": 10081,
        "lease": "45s",
        "binlog_status": "Off"
        }
    }
}
```

## 7.2.3 DDL

- `tidb_ddl_reorg_worker_cnt`

| | |
|---|---|
| | GLOBAL |
| | 4 |
| | re-organize |

- `tidb_ddl_reorg_batch_size`

| | |
|---|---|
| | GLOBAL |
| | 256 |
| | 32 |
| | 10240 |
| | re-organize |

- `tidb_ddl_reorg_priority`

| | |
|---|---|
| | GLOBAL \|SESSION |
| | PRIORITY_LOW |
| | re-organize |

- `tidb_ddl_error_count_limit`

| | |
|---|---|
| | GLOBAL |
| | 512 |
| | DDL DDL |

TiDB DDL DDL DDL TiKV TiKV ADD INDEX

TiDB `tidb_ddl_reorg_worker_cnt` `tidb_ddl_reorg_batch_size` DDL DDL DDL

- `tidb_ddl_reorg_priority` SQL
- `tidb_ddl_error_count_limit` TiKV DDL

## 7.2.4 DDL

TiDB-Server SQL DDL TiDB-Server TiDB TiDB-Server DDL

TiDB-Server DDL TiDB-Server DDL DDL Job TiKV

TiDB-Server DDL worker TiDB-Server Owner DDL TiDB-Server DDL DDL Owner Owner Owner Owner

Owner worker DDL `ADD INDEX` DDL DDL TiDB `ADD INDEX` DDL `ADD INDEX` DDL Owner worker DDL DDL DDL

Owner worker `ADD INDEX` DDL `tidb_ddl_reorg_worker_cnt` `tidb_ddl_reorg_batch_size` `DDL`

DDL DDL job history queue DDL

DDL DDL

## 7.2.5 DDL

TiDB Online, Asynchronous Schema Change in F1 schema schema

`ADD INDEX` DDL

| schema | | |
|---|---|---|
| schema version 1 | absent | |
| schema version 2 | delete only | schema / |
| schema version 3 | write only | |
| schema version 4 | write reorgnization | |
| schema version 5 | public | |

TiDB `ADD COLUMN` DDL TIDB default schema "" TiKV `null` "" `null` "" `null` TiKV DDL DDL

DDL `DROP INDEX` `DROP TABLE` `DROP DATABASE` `TRUNCATE TABLE` DDL TiDB `gc_delete_range` GC DDL schema

DDL TiDB DDL architecture

# 7.3 Sequence

Sequence  SQL 2003 “Sequence ” MySQL  Sequence TiDB Sequence  MariaDBOracle  IBM Db2

- Create Sequence

```
CREATE [TEMPORARY] SEQUENCE [IF NOT EXISTS] sequence_name
[ INCREMENT [ BY | = ] INCREMENT ]
[ MINVALUE [=] minvalue | NO MINVALUE | NOMINVALUE ]
[ MAXALUE [=] maxvalue | NO MAXVALUE | NOMAXVALUE ]
[ START [ WITH | = ] start ]
[ CACHE [=] cache | NOCACHE | NO CACHE]
[ CYCLE | NOCYCLE | NO CYCLE]
[ ORDER | NOORDER | NO ORDER]
[table_options]
```

- Show Create Sequence

```
SHOW CREATE SEQUENCE sequence_name
```

- Drop Sequence

```
DROP [TEMPORARY] SEQUENCE [IF NOT EXISTS] sequence_name
```

-

```
SELECT NEXT VALUE FOR sequence_name;
SELECT NEXTVAL(sequence_name);
```

- /

```
SELECT PREVIOUS VALUE FOR sequence_name;
SELECT LASTVAL(sequence_name);
```

-

```
SELECT SETVAL(sequence_name,100)
```

## 7.3.1

TiDB Sequence

-

Sequence  Leaf - ID  uid-generator  TiDB  `Sequence`

(1)  Sequence

```
CREATE SEQUENCE seq_for_unique START WITH 1 INCREMENT BY 1 CACHE 1000 NOCYCLE;
```

(2)  TiDB  Sequence

`TiDB`

```
 Atidb[test]> SELECT NEXT VALUE FOR seq_for_unique;
+------------------------------+
| NEXT VALUE FOR seq_for_unique |
+------------------------------+
|                            1 |
+------------------------------+
1 row in set (0.00 sec)

 Btidb[test]> SELECT NEXT VALUE FOR seq_for_unique;
+------------------------------+
| NEXT VALUE FOR seq_for_unique |
+------------------------------+
|                            2 |
+------------------------------+
1 row in set (0.00 sec)
```

(3) `TiDB` TiDB

```
 Atidb[test]> SELECT NEXT VALUE FOR seq_for_unique;
+------------------------------+
| NEXT VALUE FOR seq_for_unique |
+------------------------------+
|                            1 |
+------------------------------+
1 row in set (0.00 sec)

 Btidb[test]> SELECT NEXT VALUE FOR seq_for_unique;
+------------------------------+
| NEXT VALUE FOR seq_for_unique |
+------------------------------+
|                         1001 |
+------------------------------+
1 row in set (0.00 sec)
```

- 

MySQL `auto_increment` TiDB `Sequence`

(1) Sequence

```
CREATE SEQUENCE seq_for_autoid START WITH 1 INCREMENT BY 2 CACHE 1000 NOCYCLE;
CREATE SEQUENCE seq_for_logid START WITH 100 INCREMENT BY 1 CACHE 1000 NOCYCLE;
```

(2) `default nextval(seq_name)`

```
CREATE TABLE `user` (
    `userid` varchar(32) NOT NULL,
    `autoid` int(11) DEFAULT 'nextval(`test`.`seq_for_autoid`)',
    `logid` int(11) DEFAULT 'nextval(`test`.`seq_for_logid`)',
    PRIMARY KEY (`userid`)
)
```

(3)

```
INSERT INTO user (userid) VALUES ('usera');
INSERT INTO user (userid) VALUES ('userb');
INSERT INTO user (userid) VALUES ('userc');
```

(4) `user` `autoid` `logid` `userid`

```
tidb[test]> select * from user;
+--------+--------+-------+
| userid | autoid | logid |
+--------+--------+-------+
| usera  |      1 |   100 |
| userb  |      3 |   101 |
| userc  |      5 |   102 |
+--------+--------+-------+
3 rows in set (0.01 sec)
```

- 

20 Sequence `update` Sequence

(1)

```
tidb[test]> CREATE TABLE t( a int, name varchar(32));
Query OK, 0 rows affected (0.01 sec)
```

(2) Sequence

```
tidb[test]> CREATE SEQUENCE test;
Query OK, 0 rows affected (0.00 sec)
```

(3) 1

```
for i in $(seq 1 10000)
do
   echo "insert into t values($(($RANDOM%1000)),'user${i}');" >> user.sql
done
```

```
tidb[test]> select count(*) from t;
+----------+
| count(*) |
+----------+
|    10000 |
+----------+
1 row in set (0.05 sec)
tidb[test]> select * from t;
+------+-----------+
| a    | name      |
+------+-----------+
|  355 | user1     |
|  729 | user2     |
|  684 | user3     |
|  815 | user4     |
|   39 | user5     |
|  294 | user6     |
|  407 | user7     |
|  767 | user8     |
|  246 | user9     |
|  755 | user10    |
|  496 | user11    |
...
```

(4)

```
tidb[test]> update t set a=nextval(test);
Query OK, 10000 rows affected (0.20 sec)
Rows matched: 10000  Changed: 10000  Warnings: 0
```

(5) , `a`

```
tidb[test]> select * from t;
+-------+-----------+
| a     | name      |
+-------+-----------+
|     1 | user1     |
|     2 | user2     |
|     3 | user3     |
|     4 | user4     |
|     5 | user5     |
|     6 | user6     |
|     7 | user7     |
|     8 | user8     |
|     9 | user9     |
|    10 | user10    |
|    11 | user11    |
|    12 | user12    |
|    13 | user13    |
|    14 | user14    |
|    15 | user15    |
|    16 | user16    |
|    17 | user17    |
|    18 | user18    |
|    19 | user19    |
|    20 | user20    |
...
```

## 7.3.2

`Sequence` `Sequence` `Order/No Order` `Cache/No Cache` `Sequence` `Sequence`

# 7.4 AutoRandom

AutoRandom TiDB 4.0 AutoIncrement ID

## 7.4.1 AutoRandom

TiDB `_tidb_rowid` `_tidb_rowid` Key TiKV TiKV Region

TiDB `_tidb_rowid` “” `AUTO_INCREMENT` `SHARD_ROW_ID_BITS`

`AUTO_INCREMENT` `AUTO_INCREMENT` `AUTO_RANDOM` TiDB ID

AutoRandom

- TiDB
- TiDB `PRE_SPLIT_REGION`
- AutoIncrement TiDB Server Binlog

## 7.4.2 AutoRandom

`AUTO_RANDOM` TiDB TiDB 4.0

```
column_definition:
    data_type [NOT NULL | NULL] [DEFAULT default_value]
      [AUTO_INCREMENT | AUTO_RANDOM [(length)]]
      [UNIQUE [KEY] | [PRIMARY] KEY]
      [COMMENT 'string']
      [reference_definition]
```

AutoRandom `AUTO_RANDOM` Shard Bits 5

## 7.4.3 AutoRandom

AUTO_RANDOM TiDB `experimental` `allow-auto-random = true` allow-auto-random

```
tidb> create table t (a int primary key auto_random);
```

INSERT INTO t(b) values... INSERT

```
tidb> insert into t values (), ();
Query OK, 2 rows affected (0.00 sec)
Records: 2  Duplicates: 0  Warnings: 0

tidb> select * from t;
+-----------+
| a         |
+-----------+
| 201326593 |
| 201326594 |
+-----------+
2 rows in set (0.00 sec)

tidb> insert into t values (), ();
Query OK, 2 rows affected (0.01 sec)
Records: 2  Duplicates: 0  Warnings: 0

tidb> select * from t;
+------------+
| a          |
+------------+
|  201326593 |
|  201326594 |
| 2080374787 |
| 2080374788 |
+------------+
4 rows in set (0.00 sec)

tidb> select last_insert_id();
+------------------+
| last_insert_id() |
+------------------+
|       2080374787 |
+------------------+
1 row in set (0.00 sec)
```

- INSERT a TiDB ID
- INSERT AutoIncrement TiDB
- INSERT AutoRandom ID `LAST_INSERT_ID()` `LAST_INSERT_ID()` ID

## 7.4.5 AutoRandom

AutoRandom TiDB

- alter-primary-key AutoIncrement + `SHARD_ROW_ID_BITS`

  `SHARD_ROW_ID_BITS`

- `UUID()`

  `UUID()` TiDB

`AUTO_RANDOM`

# 8 Titan

TiKV TiKV RocksDB TiKV RocksDB LSM-tree RocksDB IO CPU SSD SSD

Titan PingCAP RocksDB key-value value key LSM-tree value RocksDB compaction IO CPU SSD

## 8.1 Titan

Titan USENIX FAST 2016 WiscKeyWiscKey SSD SSD value LSM-tree

value Titan RocksDB RocksDB Titan SSD SSD IO Titan

### 8.1.1

TiKV TiKV RocksDB TiKV Titan RocksDB RocksDB TiKV Titan TiKV Titan

- value LSM-tree value
- RocksDB Titan
- 100% TiKV RocksDB
- RocksDB Titan RocksDB

### 8.1.2

Titan RocksDB Flush Compaction value LSM-tree BlobFile RocksDB Titan BlobFileTitanTableBuilder Garbage CollectionGC

#### 8.1.2.1 BlobFile

BlobFile LSM-tree KV heeaderrecord meta blockmeta index footer record key-value meta block meta index meta block

prefetch BlobFile key-value key LSM-tree value blob record key key Titan GC key GC key value Titan value BlobFile SnappyLZ4 Zstd Titan LZ4

### 8.1.2.2 TitanTableBuilder

RocksDB TableBuilder table Titan TitanTableBuilder RocksDB table value LSM-tree

RocksDB SST TitanTableBuilder value value BlobFile value Titan value RocksDB SST value BlobFile value RocksDB SST value RocksDB TableBuilder RocksDB Compaction BlobFile value SST Titan RocksDB

* KV LSM-tree Badger Titan VLog WAL LSM-tree max level 5 10 LSM-tree 1 + 1 + 10 + 10 + 10 + 10 = 42 BlobFile LSM-tree 1 : 42 WAL RocksDB Titan

### 8.1.2.3 Garbage Collection

RocksDB LSM-tree Compaction Titan Garbage Collection (GC) Titan GC GCLevel-Merge GC

1. GC

Blob GC GC GC GC

Titan GC RocksDB compaction RocksDB compaction BlobFile value Titan RocksDB compaction GC compaction SST BlobFile BlobFileSizeProperties BlobFile

inputs compaction SST BlobFileSizeProperties BlobFile ID : outputs SST BlobFile discardable size ID

BlobFileSizeProperties RocksDB TablePropertiesCollector SST Titan BlobFileSizeCollector SST BlobFile

BlobFileSizeCollector SST KV SST BlobFile

GC BlobFileTitan BlobFile discardable size RocksDB compaction BlobFile discardable size BlobFile SST BlobFile BlobFile GC GC BlobFile discardable size GC

GC Titan BlobFile record record key LSM-tree blob index blob record BlobFile BlobFile blob index LSM-tree snapshot GC Titan snapshot BlobFile GC RocksDB sequence number snapshot sequence number

1. Level-Merge

GC GC LSM-tree record key record index GC LSM-tree Titan Level-Merge LSM-tree compaction SST BlobFile BlobFile GC LSM-tree BlobFile Scan

Level-Merge RocksDB level z-1 level z SST compaction KV SST BlobFile value BlobFile SST blob index compaction key BlobFile BlobFile GC LSM-tree 99% Level-Merge Titan LSM-tree BlobFile Level-Merge

# 8.2 TiDB Titan

Titan

- Value value value Titan Titan 1KB value value 512B value Titan
- Titan RocksDB Titan RocksDB 40%
- Titan Titan RocksDB block Titan RocksDB Titan RocksDB

## 8.2.1 Titan

Titan RocksDB RocksDB TiKV Titan TiKV TiKV

```
[rocksdb.titan]
enabled = true
```

Titan Titan RocksDB compaction key-value Titan TiKV Details - Titan kv - blob file size Titan

Titan tikv-ctl compaction tikv-ctl

RocksDB Titan RocksDB Titan Titan TiKV Titan rocksdb.titan.enabled = false TiKV TiKV log “You have disabled titan when its data directory is not empty” “ Titan”

### Titan

TiKV Titan Titan Titan RocksDB Titan leader PD Titan leader count pd-ctl store weight Titan leader weight leader count

## 8.2.2

```
[rocksdb.titan]
max-background-gc1
```

Titan GC TiKV Details - Thread CPU - RocksDB CPU Titan GC Titan GC

```
[rocksdb.defaultcf.titan]
min-blob-size 1kb
```

value value value RocksDB Titan blob file value value RocksDB value value Titan RocksDB compaction

```
[rocksdb.defaultcf.titan]
blob-file-compressionlz4
```

Titan value Titan value

```
[rocksdb.defaultcf.titan]
blob-cache-size0
```

Titan value Titan OOM RocksDB block cache storage.block-cache.capacity store size blob file size blob-cache-size * 50% block cache block cache RocksDB blob cache

```
[rocksdb.defaultcf.titan]
discardable-ratio0.5
```

blob file key Titan GC Titan

= 1 / discardable_ratio

= 1 / ( 1 - discarable_ratio )

Titan GC Titan GC IO CPU

```
[rocksdb]
rate-bytes-per-sec0
```

Titan RocksDB compaction IO RocksDB compaction IO CPU Titan RocksDB compaction Titan GC IO RocksDB compaction Titan GC IO / CPU IO

### 8.2.3 Titan

rocksdb.defaultcf.titan.blob-run-mode Titanblob-run-mode

- “kNormal” Titan
- “kReadnly” value RocksDB
- “kFallback” value RocksDB RocksDB compaction Titan blob file value RocksDB

Titan blob-run-mode = “kFallback” tikv-ctl compaction blob file size 0 rocksdb.titan.enabled = false TiKV

Titan

### 8.2.4 Level Merge

TiKV 4.0 Titan Titan GC level mergeLevel merge

```
[rocksdb.defaultcf.titan]
level-merge = true
```

level merge

- Titan
- Titan GC
- Titan

level mege Titan RocksDB

Level merge Titan Titan TiKV Level merge

# 9 TiFlash HTAP

—— OLTP OLAP ETL “” T+N

HTAP HTAP OLTP OLAP 2014 Garnter / (HTAP) “” ”“ “”

TiDB NewSQL HTAP TiDB HTAP HTAP TiFlash TiFlash


- 9.1 TiDB HTAP
- 9.2 TiFlash
- 9.3 TiFlash

# 9.1 TiDB HTAP

HTAP Hybrid Transactional / Analytical Processing 2014 Gartner TP AP HTAP

HTAP TiDB

## 1.

- 
- 

TiKV TiFlash

- 
- ClickHouse SIMD
- TiKV
- TiDB

## 2. Delta Tree

TiFlash Delta Main TiFlash Delta Main LSM Delta Tree LSM LSM TiFlash

## 3.

TiFlash TiDB Multi-Raft Raft Learner TiFlash TiKV TiFlash TiKV TiFlash TiKV

**4.**

TiFlash TiKV TiDB TiSpark BI

TiDB TiDB

**5.**

ETL TiDB

**6.**

TiFlash TiKV TiKV TiDB HTAP

# 9.2 TiFlash

TiFlash Schema ClickHouse TiFlash SISnapshot Isolation TiFlash

## 9.2.1

TiFlash TiDB OLAP TiDB TiFlash MPP TiDB TiFlash

TiFlash Raft Learner Store TiKV TiKV Key Region Region Peer Raft Group Raft Group Peer Leader FollowerLearner TiKV Peer TiFlash Peer LearnerTiFlash TiKV PD Region TiDB TiSpark TiKV Coprocessor TiFlash

TiDB Table SchemaIndexRecord TiKV Table TiDB Table Schema Key-Value Region Multi-Raft TiFlash TiFlash Schema

## 9.2.2

TiFlash

## 1. Replica Manager

Index TiFlash Table TiFlash PD Region

TiFlash PD ETCD Replica Manager PD TiDB TiDB TiFlash DDL PD Placement Rule PD TiKV Key Region Learner Peer TiFlash Table TiFlash Replica Manager TiFlash Table TiDB

## 2. Raft Learner Proxy

Raft Learner TiFlash Region Learner Peer TiKV TiKV Raft Proxy Proxy TiFlash Region TiFlash

LearnerTiFLash TiFlash Raft Schema TiFlash Raft WAL

TiDB Percolator TiKV 3 CFColumn Family WriteDefaultLockTiFlash Region TiFlash CF Region Table Schema

## 3. Schema Syncer

TiFlash TiKV Table Schema TiDB Schema

## 4. Learner Read / Coprocessor

CH TiSparkCHSpark TiDB TiFlash Learner Read Raft Group Index Raft Region Version Conf Version Split/Merge/ChangePeer

Region Region PD TiKV Timestamp Snapshot Read PD Table Schema Version TiDB

1. Schema
2. Region Leader Peer Index Learner Applied Index
3. Version Conf Version Lock CF
4. Region
5. Timestamp Snapshot Read
6. Coprocessor ClickHouse

## 9.2.3 TiFlash OLAP

OLAP

- 
- 
- 

TiFlash

(1) I/O

- I/O
- 
- I/O

(2) CPU

- CPU Cache
- 

## 9.2.4 TiKV TiFlash

TiFlash TiKVTiFlash

### 9.2.5

TiFlash  TiDB HTAP

# 9.3 TiFlash

TiDB TiSpark TiFlash TiDB OLAP TiSpark OLAP

## 9.3.1 TiFlash

TiFlash TiKV MySQL TiDB DDL TiFlash

```
ALTER TABLE table_name SET TIFLASH REPLICA count;
```

- count 0 TiFlash
- DDL

1 2 TiFlash

```
ALTER TABLE `tpch50`.`lineitem` SET TIFLASH REPLICA 2;
```

2

```
ALTER TABLE `tpch50`.`lineitem` SET TIFLASH REPLICA 0;
```

SQL WHERE WHERE TiFlash

```
SELECT * FROM information_schema.tiflash_replica
WHERE TABLE_SCHEMA = '<db_name>' and TABLE_NAME = '<table_name>';
```

AVAILABLE TiFlash

`t` DDL TiFlash TiFlash

```
CREATE TABLE table_name LIKE t;
```

## 9.3.2 TiDB TiFlash

TiDB TiFlash TiFlash engine CBO (Cost Based Optimization)

## 1. CBO

TiFlash TiDB CBO TiFlash TiFlash `explain analyze`

```
mysql> explain analyze select * from t;
+-------------------+----------+--------------+-------------------------------------------------------------+----------------------------
----------------------------+-----------+
| id                | count    | task         | operator info                                               | execution info
                              | memory    |
+-------------------+----------+--------------+-------------------------------------------------------------+----------------------------
----------------------------+-----------+
| TableReader_7     | 10000.00 | root         | data:TableScan_6                                            | time:54.230814ms, loops:2,
rows:1, rpc time:54.147725ms | 163 Bytes |
| └─TableScan_6     | 10000.00 | cop[tiflash] | table:t, range:[-inf,+inf], keep order:false, stats:pseudo | time:40ms, loops:1, rows:1
                              | N/A       |
+-------------------+----------+--------------+-------------------------------------------------------------+----------------------------
----------------------------+-----------+
2 rows in set (0.06 sec)
```

## 2. Engine

Engine engine engine tikv tiflash 2

(1) SESSION GLOBAL

```
set@@session.tidb_isolation_read_engines=" engine list";
```

```
set SESSION tidb_isolation_read_engines = " engine list";
```

TiDB

```
set SESSION tidb_isolation_read_engines = "tikv,tiflash";
```

TiFlash

```
set SESSION tidb_isolation_read_engines = "tiflash";
```

(2) TiDB INSTANCE INSTANCE "tikv,tiflash" SESSION "tikv" tikv TiDB

```
[isolation-read]
engines = ["tikv", "tiflash"]
```

"tikv,tiflash" tikv tiflash

engine engine tikv engine tiflash tiflash engine

Engine engine

## 3. hint

hint TiDB TiFlash CBO engine

```
SELECT /*+ read_from_storage(tiflash[t]) */ * FROM t;
```

hint tiflash tiflash

# 10 TiDB

TiDB RBAC RBAC  TLS


- 10.1
- 10.2 RBAC
- 10.3

# 10.1

TiDB

TiDB  MySQL TiDB  MySQL

TiDB

## 10.1.1

- 
- 
- 

## 10.1.2

- mysql.user
- mysql.tables_priv
- mysql.db

TiDB

## 1.mysql.user

mysql.user

```
CREATE TABLE `user` (
  `Host` char(64) NOT NULL,
  `User` char(32) NOT NULL,
  `authentication_string` text DEFAULT NULL,
  `Select_priv` enum('N','Y') NOT NULL DEFAULT 'N',
  `Insert_priv` enum('N','Y') NOT NULL DEFAULT 'N',
  `Update_priv` enum('N','Y') NOT NULL DEFAULT 'N',
  `Delete_priv` enum('N','Y') NOT NULL DEFAULT 'N',
  `Create_priv` enum('N','Y') NOT NULL DEFAULT 'N',
  `Drop_priv` enum('N','Y') NOT NULL DEFAULT 'N',
  `Process_priv` enum('N','Y') NOT NULL DEFAULT 'N',
  `Grant_priv` enum('N','Y') NOT NULL DEFAULT 'N',
  `References_priv` enum('N','Y') NOT NULL DEFAULT 'N',
  `Alter_priv` enum('N','Y') NOT NULL DEFAULT 'N',
  `Show_db_priv` enum('N','Y') NOT NULL DEFAULT 'N',
  `Super_priv` enum('N','Y') NOT NULL DEFAULT 'N',
  `Create_tmp_table_priv` enum('N','Y') NOT NULL DEFAULT 'N',
  `Lock_tables_priv` enum('N','Y') NOT NULL DEFAULT 'N',
  `Execute_priv` enum('N','Y') NOT NULL DEFAULT 'N',
  `Create_view_priv` enum('N','Y') NOT NULL DEFAULT 'N',
  `Show_view_priv` enum('N','Y') NOT NULL DEFAULT 'N',
  `Create_routine_priv` enum('N','Y') NOT NULL DEFAULT 'N',
  `Alter_routine_priv` enum('N','Y') NOT NULL DEFAULT 'N',
  `Index_priv` enum('N','Y') NOT NULL DEFAULT 'N',
  `Create_user_priv` enum('N','Y') NOT NULL DEFAULT 'N',
  `Event_priv` enum('N','Y') NOT NULL DEFAULT 'N',
  `Trigger_priv` enum('N','Y') NOT NULL DEFAULT 'N',
  `Create_role_priv` enum('N','Y') NOT NULL DEFAULT 'N',
  `Drop_role_priv` enum('N','Y') NOT NULL DEFAULT 'N',
  `Account_locked` enum('N','Y') NOT NULL DEFAULT 'N',
  `Shutdown_priv` enum('N','Y') NOT NULL DEFAULT 'N',
  `Reload_priv` enum('N','Y') DEFAULT 'N',
  `File_priv` enum('N','Y') DEFAULT 'N',
  PRIMARY KEY (`Host`,`User`)
) ENGINE=InnoDB DEFAULT CHARSET=utf8mb4 COLLATE=utf8mb4_bin
```

mysql.user Host User Host user ip Host 192.168.1.7 root mysql.user `root @ 172.16.*` `root @ 192.168.1.*` User root ip 192.168.1.7 Host `root @ 192.168.1.*`

## 2.mysql.table, mysql.db

mysql.table mysql.db

```
CREATE TABLE `tables_priv` (
  `Host` char(60) NOT NULL,
  `DB` char(64) NOT NULL,
  `User` char(32) NOT NULL,
  `Table_name` char(64) NOT NULL,
  `Grantor` char(77) DEFAULT NULL,
  `Timestamp` timestamp DEFAULT CURRENT_TIMESTAMP,
  `Table_priv` set('Select','Insert','Update','Delete','Create','Drop','Grant','Index','Alter','Create View','Show Vi
ew','Trigger','References') DEFAULT NULL,
  `Column_priv` set('Select','Insert','Update') DEFAULT NULL,
  PRIMARY KEY (`Host`,`DB`,`User`,`Table_name`)
) ENGINE=InnoDB DEFAULT CHARSET=utf8mb4 COLLATE=utf8mb4_bin
```

```
CREATE TABLE `db` (
  `Host` char(60) NOT NULL,
  `DB` char(64) NOT NULL,
  `User` char(32) NOT NULL,
  `Select_priv` enum('N','Y') NOT NULL DEFAULT 'N',
  `Insert_priv` enum('N','Y') NOT NULL DEFAULT 'N',
  `Update_priv` enum('N','Y') NOT NULL DEFAULT 'N',
  `Delete_priv` enum('N','Y') NOT NULL DEFAULT 'N',
  `Create_priv` enum('N','Y') NOT NULL DEFAULT 'N',
  `Drop_priv` enum('N','Y') NOT NULL DEFAULT 'N',
  `Grant_priv` enum('N','Y') NOT NULL DEFAULT 'N',
  `References_priv` enum('N','Y') NOT NULL DEFAULT 'N',
  `Index_priv` enum('N','Y') NOT NULL DEFAULT 'N',
  `Alter_priv` enum('N','Y') NOT NULL DEFAULT 'N',
  `Create_tmp_table_priv` enum('N','Y') NOT NULL DEFAULT 'N',
  `Lock_tables_priv` enum('N','Y') NOT NULL DEFAULT 'N',
  `Create_view_priv` enum('N','Y') NOT NULL DEFAULT 'N',
  `Show_view_priv` enum('N','Y') NOT NULL DEFAULT 'N',
  `Create_routine_priv` enum('N','Y') NOT NULL DEFAULT 'N',
  `Alter_routine_priv` enum('N','Y') NOT NULL DEFAULT 'N',
  `Execute_priv` enum('N','Y') NOT NULL DEFAULT 'N',
  `Event_priv` enum('N','Y') NOT NULL DEFAULT 'N',
  `Trigger_priv` enum('N','Y') NOT NULL DEFAULT 'N',
  PRIMARY KEY (`Host`,`DB`,`User`)
) ENGINE=InnoDB DEFAULT CHARSET=utf8mb4 COLLATE=utf8mb4_bin
```

mysql.tables_priv mysql.db

bitmask User, Host

GRANT, REVOKE TiDB sql INSERT, UPDATE, DELETE

## 10.1.3

developer 192.168.0.* 'test_user'

```
root> CREATE USER 'developer'@'192.168.0.%' IDENTIFIED BY 'test_user';
```

developer read_table write_table

```
root> GRANT SELECT ON app.read_table TO 'developer'@'192.168.0.%';
root> GRANT INSERT, UPDATE ON app.write_table TO 'developer'@'192.168.0.%';
```

developer

```
root> SHOW GRANTS FOR 'developer'@'192.168.0.%';
GRANT USAGE ON *.* TO 'developer'@'192.168.0.%'
GRANT Select ON app.read_table TO 'developer'@'192.168.0.%'
GRANT Insert,Update,Delete ON app.write_table TO 'developer'@'192.168.0.%'
```

developer

```
developer> SEECT * FROM app.read_table;
Empty set (0.01 sec)
developer> INSERT INTO write_table VALUES (1),(2),(3);
Query OK, 3 rows affected (0.00 sec)
Records: 3  Duplicates: 0  Warnings: 0
```

developer write_table TiDB

```
developer> INSERT INTO read_table VALUES (1),(2),(3);
ERROR 1142 (42000): INSERT command denied to user 'developer'@'192.168.0.%' for table 'read_table'
```

GRANT_OPTION GRANT, REVOKE developer read_table

```
root> REVOKE SELECT ON app.read_table from 'developer'@'192.168.0.%';
```

CREATE USER

```
root> ALTER USER 'developer'@'192.168.0.%' IDENTIFIED BY 'password';
root> DROP USER 'developer'@'192.168.0.%'
```

## 10.1.4

TiDB TiDB RBAC

# 10.2 RBAC

TiDB -- RBAC

Role-based access controlRBAC

MAC (Mandatory access control) DAC (Discretionary Access Control)RBAC

TiDB (RBAC) MySQL 8.0 RBAC MySQL RBAC

## 10.2.1 RBAC

- 
- 
- 
- 
- 

## 10.2.2 RBAC

- TiDB
- session ActiveRole SET ROLE default_roles ActiveRole

- mysql.user Account_Locked Y.

```
+------+------+-----------+-------------+-------------+-------------+-------------+-------------+------------+---------
-----+-------------+-----------------+------------+--------------+------------+-----------------------+---------------
---+--------------+------------------+----------------+----------------------+--------------------+------------+------
------------+------------+--------------+------------------+----------------+----------------+---------------+
| Host | User | Password | Select_priv | Insert_priv | Update_priv | Delete_priv | Create_priv | Drop_priv | Process_
priv | Grant_priv | References_priv | Alter_priv | Show_db_priv | Super_priv | Create_tmp_table_priv | Lock_tables_pr
iv | Execute_priv | Create_view_priv | Show_view_priv | Create_routine_priv | Alter_routine_priv | Index_priv | Creat
e_user_priv | Event_priv | Trigger_priv | Create_role_priv | Drop_role_priv | Account_locked | Shutdown_priv |
+------+------+-----------+-------------+-------------+-------------+-------------+-------------+------------+---------
-----+-------------+-----------------+------------+--------------+------------+-----------------------+---------------
---+--------------+------------------+----------------+----------------------+--------------------+------------+------
------------+------------+--------------+------------------+----------------+----------------+---------------+
| %    | root |          | Y           | Y           | Y           | Y           | Y           | Y          | Y
     | Y          | Y                | Y          | Y            | Y          | Y                     | Y
   | Y           | Y                | Y            | Y                | Y                  | Y                  | Y          | Y
            | Y          | Y            | Y                | Y              | Y                  | N              | Y             |
| %    | r_1  |          | N           | N           | N           | N           | N           | N          | N
     | N          | N                | N          | N            | N          | N                     | N
   | N           | N                | N            | N                | N                  | N                  | N          | N
            | N          | N            | N                | N              | Y              | N             |
| %    | r_2  |          | N           | N           | N           | N           | N           | N          | N
     | N          | N                | N          | N            | N          | N                     | N
   | N           | N                | N            | N                | N                  | N                  | N          | N
            | N          | N            | N                | N              | Y              | N             |
+------+------+-----------+-------------+-------------+-------------+-------------+-------------+------------+---------
-----+-------------+-----------------+------------+--------------+------------+-----------------------+---------------
---+--------------+------------------+----------------+----------------------+--------------------+------------+------
------------+------------+--------------+------------------+----------------+----------------+---------------+
```

- mysql.role_edges r1 test

```
+-----------+-----------+---------+---------+-------------------+
| FROM_HOST | FROM_USER | TO_HOST | TO_USER | WITH_ADMIN_OPTION |
+-----------+-----------+---------+---------+-------------------+
| %         | r1        | %       | test    | N                 |
+-----------+-----------+---------+---------+-------------------+
```

- mysql.default_roles

```
+------+------+-------------------+-------------------+
| HOST | USER | DEFAULT_ROLE_HOST | DEFAULT_ROLE_USER |
+------+------+-------------------+-------------------+
| %    | test | %                 | r_1               |
+------+------+-------------------+-------------------+
```

## 10.2.3 RBAC

- r_1r_2

```
CREATE ROLE `r_1`@`%`, `r_2`@`%`;
```

- r_1

```
GRANT SELECT ON db_1.* TO 'r_1'@'%';
```

- r_1 test@'%'

```
grant r_1 to test@'%';
```

-

```
SET DEFAULT ROLE 'r_1';
```

- sessionsession

```
SET ROLE 'r_1';
```

-

```
SELECT CURRENT_ROLE();
```

-

```
TiDB > SHOW GRANTS FOR 'test'@'%' USING 'r_1';
+-------------------------------------+
| Grants for test@%                   |
+-------------------------------------+
| GRANT USAGE ON *.* TO 'test'@'%'    |
| GRANT Select ON test.* TO 'test'@'%' |
| GRANT 'r_1'@'%' TO 'test'@'%'       |
+-------------------------------------+
```

-

```
REVOKE 'r_1' FROM 'test'@'%', 'root'@'%';
```

### 10.2.4

bi_user

```
# reader
root@127.0.0.1:(none)>create role reader@'%';
Query OK, 0 rows affected (0.012 sec)

# reader  mysql.role_edges
root@127.0.0.1:mysql>grant select on mysql.role_edges to reader'%';
Query OK, 0 rows affected (0.017 sec)

# bi_user
root@127.0.0.1:(none)>create user bi_user@'%';
Query OK, 0 rows affected (0.011 sec)

# reader  bi_user
root@127.0.0.1:mysql>grant reader to bi_user'%';
Query OK, 0 rows affected (0.014 sec)

# bi_user
bi_user@127.0.0.1:(none)>show databases;
+--------------------+
| Database           |
+--------------------+
| INFORMATION_SCHEMA |
+--------------------+
1 row in set (0.000 sec)

# bi_user
bi_user@127.0.0.1:(none)>SELECT CURRENT_ROLE();
+----------------+
| CURRENT_ROLE() |
+----------------+
|                |
+----------------+
1 row in set (0.000 sec)

# session  bi_user  reader
bi_user@127.0.0.1:(none)>set role reader;
Query OK, 0 rows affected (0.000 sec)

# bi_user
bi_user@127.0.0.1:(none)>SELECT CURRENT_ROLE();
+----------------+
| CURRENT_ROLE() |
+----------------+
| `reader`@`%`   |
+----------------+
1 row in set (0.000 sec)

# bi_user  mysql
bi_user@127.0.0.1:mysql>select * from role_edges;
+-----------+-----------+---------+---------+-------------------+
| FROM_HOST | FROM_USER | TO_HOST | TO_USER | WITH_ADMIN_OPTION |
+-----------+-----------+---------+---------+-------------------+
| %         | reader    | %       | bi_user | N                 |
+-----------+-----------+---------+---------+-------------------+
1 row in set (0.000 sec)

# bi_user  delete
bi_user@127.0.0.1:mysql>delete from role_edges;
ERROR 1105 (HY000): privilege check fail

# bi_user
bi_user@127.0.0.1:mysql>select * from user;
ERROR 1142 (42000): SELECT command denied to user 'bi_user'@'127.0.0.1' for table 'user'

# bi_user
bi_user@127.0.0.1(none)>use mysql
ERROR 1044 (42000): Access denied for user 'bi_user'@'%' to database 'mysql'
```

## 10.2.5

RBAC RBAC TiDB ——

# 10.3

TiDB 3.0.8 TiDB TiDB TiDB MySQL

## 10.3.1

TiDB TiDB TiDB

- 
- 
- 

## 10.3.2

TiDB X.509 CA()

- CA CA
- TiDB CA CA
- 

TiDB sbject issuercipher mysql.global_priv

TiDB

## 10.3.3

## 1. CA

OpenSSL OpenSSL

```
sudo apt-get install openssl
```

CA CA

```
sudo openssl genrsa 2048 > ca-key.pem
```

CA CA

```
sudo openssl req -new -x509 -nodes -days 365000 -key ca-key.pem -out ca-cert.pem
```

```
Country Name (2 letter code) [AU]:US
State or Province Name (full name) [Some-State]:California
Locality Name (eg, city) []:San Francisco
Organization Name (eg, company) [Internet Widgits Pty Ltd]:PingCAP Inc.
Organizational Unit Name (eg, section) []:TiDB
Common Name (e.g. server FQDN or YOUR name) []:TiDB admin
Email Address []:s@pingcap.com
```

CA CA

## 2.

```
sudo openssl req -newkey rsa:2048 -days 365000 -nodes -keyout server-key.pem -out server-req.pem
```

```
Country Name (2 letter code) [AU]:US
State or Province Name (full name) [Some-State]:California
Locality Name (eg, city) []:San Francisco
Organization Name (eg, company) [Internet Widgits Pty Ltd]:PingCAP Inc.
Organizational Unit Name (eg, section) []:TiKV
Common Name (e.g. server FQDN or YOUR name) []:TiKV Test Server
Email Address []:k@pingcap.com

Please enter the following 'extra' attributes
to be sent with your certificate request
A challenge password []:
An optional company name []:
```

RAS

```
sudo openssl rsa -in server-key.pem -out server-key.pem
```

CA key

```
sudo openssl x509 -req -in server-req.pem -days 365000 -CA ca-cert.pem -CAkey ca-key.pem -set_serial 01 -out server-c
ert.pem
```

## 3.

```
sudo openssl req -newkey rsa:2048 -days 365000 -nodes -keyout client-key.pem -out client-req.pem
sudo openssl rsa -in client-key.pem -out client-key.pem
sudo openssl x509 -req -in client-req.pem -days 365000 -CA ca-cert.pem -CAkey ca-key.pem -set_serial 01 -out client-c
ert.pem
```

```
openssl verify -CAfile ca-cert.pem server-cert.pem client-cert.pem
```

```
server-cert.pem: OK
client-cert.pem: OK
```

## 4. TiDB

TiDB

TiDB [security] CA

```
[security]
ssl-cert ="path/to/server-cert.pem"
ssl-key ="path/to/server-key.pem"
ssl-ca="path/to/ca-cert.pem"
```

TiDB

```
[INFO] [server.go:264] ["secure connection is enabled"] ["client verification enabled"=true]
```

TiDB --ssl-ca

```
mysql -utest -h0.0.0.0 -P4000 --ssl-cert /path/to/client-cert.pem --ssl-key /path/to/client-key.pem --ssl-ca /path/to
/ca-cert.pem
```

TiDB subjectissuercipher

- subject subject
- issuer CA subject CA

subject issuer CA

```
create user 'u1'@'%'  require issuer '/C=US/ST=California/L=San Francisco/O=PingCAP Inc./OU=TiDB/CN=TiDB admin/emailA
ddress=s@pingcap.com' subject '/C=US/ST=California/L=San Francisco/O=PingCAP Inc./OU=TiDB/CN=tpch-user1/emailAddress=
zz@pingcap.com' cipher 'TLS_AES_256_GCM_SHA384
```

GRANT

```
> create user 'u1'@'%';
> grant all on *.* to 'u1'@'%' require issuer '/C=US/ST=California/L=San Francisco/O=PingCAP Inc./OU=TiDB/CN=TiDB adm
in/emailAddress=s@pingcap.com' subject '/C=US/ST=California/L=San Francisco/O=PingCAP Inc./OU=TiDB/CN=tpch-user1/emai
lAddress=zz@pingcap.com' cipher 'TLS_AES_256_GCM_SHA384';
```

TiDB

- SSL Server CA
- Issuer
- Subject

ERROR 1045 (28000): Access denied

## 10.3.4

CA CA CA

# 1. CA

CA ca-key.pem CA

```
mv ca-key.pem ca-key.old.pem
mv ca-cert.pem ca-cert.old.pem
```

CA

```
sudo openssl genrsa 2048 > ca-key.pem
```

CA

```
sudo openssl req -new -x509 -nodes -days 365000 -key ca-key.pem -out ca-cert.new.pem
```

CA

```
cat ca-cert.new.pem ca-cert.old.pem > ca-cert.pem
```

CA TiDB Server CA

## 2.

```
sudo openssl req -newkey rsa:2048 -days 365000 -nodes -keyout server-key.new.pem -out server-req.new.pem
sudo openssl rsa -in server-key.new.pem -out server-key.new.pem
```

CA

```
sudo openssl x509 -req -in server-req.new.pem -days 365000 -CA ca-cert.pem -CAkey ca-key.pem -set_serial 01 -out serv
er-cert.new.pem
```

TiDB

## 3.

```
sudo openssl req -newkey rsa:2048 -days 365000 -nodes -keyout client-key.new.pem -out client-req.new.pem
sudo openssl rsa -in client-key.new.pem -out client-key.new.pem
```

require subject CA

```
sudo openssl x509 -req -in client-req.new.pem -days 365000 -CA ca-cert.pem -CAkey ca-key.pem -set_serial 01 -out clie
nt-cert.new.pem
```

TiDB

```
mysql -utest -h0.0.0.0 -P4000 --ssl-cert /path/to/client-cert.new.pem --ssl-key /path/to/client-key.new.pem --ssl-ca
/path/to/ca-cert.pem
```

# 11 TiSpark

TiSpark PingCAP OLAP Spark SQL TiKV TiDB HTAP (Hybrid Transactional/Analytical Processing)

TiSpark TiSpark TiSpark PingCAP TiFlash TiSpark


- 11.1 TiSpark
- 11.2 TiSpark
- 11.3 TiSpark on TiFlash
- 11.4 TiSpark

# 11.1 TiSpark

TiSpark PingCAP OLAP Spark TiKV TiFlash TiDB HTAP (Hybrid Transactional/Analytical Processing)
TiSpark TiKV Placement Driver (PD) Spark

TiSpark Spark Apache Spark Spark

## 11.1.1

TiSpark Spark SQL TiKV OLAP

- TiSpark TiKV PD Java Client TiSpark gRPC TiKV PD TiKV / TiFlash Key-Value Pair TiSpark SQL PD TiKV Region
- TiSpark TiDB Region
- TiSpark Driver
  - PD CLient PD TiDB metadata TiDB metadata Spark metadata TiSpark TiDB
  - Spark SQL TiKV
  - PD Region
    - Region TiKV
    - 
  - region
    - 
- Spark Executor
  - TiKV
  - TiKV Spark SQL

## 11.1.2 TiKV Java Client

TiSpark TiKV Key-Value Pair TiSpark TiKV TiKV Java Client gRPC TiKV Server TiKV API

- TiKV Table Schema TiKV Schema Spark SQL Schema
- TiKV

- TiKV Key-Value Pair Key-Value Pair Spark SQL TiDB
- TiKV TiKV
- SQL TiSpark Java TiKV Client TiDB

### 11.1.3 TiKV TiSpark

Java TiKV Client TiSpark TiKV TiKV TiKV Spark Spark Spark Plan Spark SparkSessionExtensions Spark SQL Plan Spark API

TiSpark

spark.sql.extensions org.apache.spark.sql.TiExtensions

TiExtensitionsSpark SparkSessionExtensions TiSpark Spark

Spark SQL Spark SQL Catalyst DataSource API TiSpark Spark Plan SQL SQL TiKV TiKV Spark TiKV Spark TiKV

## 11.1.4

Spark SQL

Spark SQL SQL student TiDB studentID school

SELECT class, avg(score) FROM student

WHERE school = ‘engineering’ AND studentId >= 8000 AND studentId < 10100

GROUP BY class ;

studentID TiKV Region Region 2 studentId [5000 - 10000) Region 3 studentID [10000 - 15000) SQL TiKV 8000 10100 TiSpark Region 2 Region 3 TiSpark Spark Executor TiKV TiKV TiKV TiKV Spark SQL

## 11.1.5

Row ID

- 
- Row ID Region
- Spark Executor Row ID
- 

school 1,2,3,4,5,7,8,10,88 Row ID Spark Executor Row ID Row ID student TiKV Spark

## 11.1.6

TiStrategy TiSpark Spark SQL AVG(score) GROUP BY class TiSpark AVG SUM(score) / COUNT(score) TiSpark TiDB TiKV TiDB TiSpark group by bytes SUM Decimal Count Bigint TiDB Spark Spark Spark Executor Map Task TiKV Reduce Task Map Task

## 11.1.7

TiSpark TiDB JDBC TiDB TiSpark TiKV Spark DataFrame TiSpark DataFrame TiKV TiKV Java Client TiKV

- DataFrame Region
- TiKV TiKV Percolator
  - Spark Driver TiKV
  - Spark Executor DataFrame TiKV Key-Value Pair gRPC DataFrame TiKV
  - Spark Driver Spark Executor Percolator
  - Spark Excutor

## 11.1.8

TiSpark TiKV Java Client Spark Spark Plan TiKV Spark TiKV TiSpark TiSpark TiKV TiSpark TiKV TiSpark TiKV

# 11.2 TiSpark

TiSpark TiSpark

## 11.2.1 TiSpark

TiSpark Apache Spark Apache Spark 2.1 TiSpark YARN Standalone Apache Spark Spark TiSpark Release TiSpark JAR

TiSpark

1. Spark Driver Executor TiSpark JAR
2. Spark spark-defaults.conf

```
spark.sql.extensions            org.apache.spark.sql.TiExtensions
spark.tispark.pd.addresses      pd-host1:port1,pd-host2:port2,pd-host3:port3
```

Standalone TiSpark

1. SPARK_HOME/spark-defaults.conf
2. Spark TiSpark JAR spark-shell

```
./spark-shell --jars /path/your-tispark.jar
```

## 11.2.2 TiSpark

TiSpark Spark

### 11.2.2.1 spark-shell

spark-shell Spark API

spark-shell lineitem

```
scala>spark.sql("use tpch")
 tpch
scala>spark.sql("select count(*) from lineitem").show
 lineitem

+-------------+
| Count (1)   |
+-------------+
| 600000000   |
+-------------+
```

Spark SQL sql

```
scala> spark.sql(
      """select
        |   l_returnflag,
        |   l_linestatus,
        |   sum(l_quantity) as sum_qty,
        |   sum(l_extendedprice) as sum_base_price,
        |   sum(l_extendedprice * (1 - l_discount)) as sum_disc_price,
        |   sum(l_extendedprice * (1 - l_discount) * (1 + l_tax)) as sum_charge,
        |   avg(l_quantity) as avg_qty,
        |   avg(l_extendedprice) as avg_price,
        |   avg(l_discount) as avg_disc,
        |   count(*) as count_order
        |from
        |   lineitem
        |where
        |   l_shipdate <= date '1998-12-01' - interval '90' day
        |group by
        |   l_returnflag,
        |   l_linestatus
        |order by
        |   l_returnflag,
        |   l_linestatus
      """.stripMargin).show
scala>
+------------+------------+---------+--------------+--------------+
|l_returnflag|l_linestatus|  sum_qty|sum_base_price|sum_disc_price|
+------------+------------+---------+--------------+--------------+
|           A|           F|380456.00|  532348211.65|505822441.4861|
|           N|           F|  8971.00|   12384801.37| 11798257.2080|
|           N|           O|742802.00| 1041502841.45|989737518.6346|
|           R|           F|381449.00|  534594445.35|507996454.4067|
+------------+------------+---------+--------------+--------------+
```

### 11.2.2.2 Spark SQL

TiSpark Spark SQL spark-sql sql

spark-sql lineitem

```
spark-sql> use tpch;
 tpch
spark-sql> select count(*) from lineitem;
lineitem
2000
Time taken: 0.673 seconds, Fetched 1 row(s)
```

### 11.2.2.3 JDBC TiSpark

Thrift JDBC TiSpark

beeline JDBC TiSpark

```
beeline> !connect jdbc:hive2://localhost:10000
1: jdbc:hive2://localhost:10000> use testdb;
+---------+--+
| Result  |
+---------+--+
+---------+--+
No rows selected (0.013 seconds)
select count(*) from account;
+-----------+--+
| count(1)  |
+-----------+--+
| 1000000   |
+-----------+--+
1 row selected (1.97 seconds)
```

## 11.2.3 TiSpark

### 11.2.3.1 PySpark TiSpark

TiSpark on PySpark TiSpark Python Python PySpark python

PySpark TiSpark

```
./bin/pyspark --jars /PATH/tispark-${name_with_version}.jar
# Query as you are in spark-shell
spark.sql("show databases").show()
spark.sql("use tpch_test")
spark.sql("show tables").show()
spark.sql("select count(*) from customer").show()
# Result
+--------+
|count(1)|
+--------+
|     150|
+--------+
```

pip pytispark TiSpark

pip pytispark

```
pip install pytispark
```

python test.py

```
import pytispark.pytispark as pti
from pyspark.sql import SparkSession
spark = SparkSession.builder.getOrCreate()
ti = pti.TiContext(spark)
ti.tidbMapDatabase("tpch_test")
spark.sql("select count(*) from customer").show()
```

spark-submit

```
./bin/spark-submit --jars /PATH/tispark-${name_with_version}.jar test.py
# Result:
+--------+
|count(1)|
+--------+
|     150|
+--------+
```

### 11.2.3.2 TiSparkR TiSpark

TiSparkR TiSpark R R PySpark TiSparkR library

PySpark TiSpark

```
./bin/sparkR --jars /PATH/tispark-${name_with_version}.jar
sql("use tpch_test")
count <- sql("select count(*) from customer")
head(count)
# Result
+--------+
|count(1)|
+--------+
|     150|
+--------+
```

SparkR TiSpark R test.R

```
library(SparkR)
sparkR.session()
sql("use tpch_test")
count <- sql("select count(*) from customer")
head(count)
```

spark-submit

```
./bin/spark-submit  --jars /PATH/tispark-${name_with_version}.jar test.R
# Result:
+--------+
|count(1)|
+--------+
|     150|
+--------
```

### 11.2.3.3 TiSpark TiFlash

TiSpark TiFlash

# 11.3 TiSpark on TiFlash

TiFlash TiSpark TiKV TiSpark TiFlash TiSpark TiFlash TiKV TiFlash Region TiSpark TiKV TiFlash TiSpark TiFlash TiDB TiFlash TiSpark

## 11.3.1 TiSpark TiFlash

TiSpark TiSpark JAR TiExtension PD TiFlash TiSpark

TiSpark TiDB engine TiFlash:

```
spark.tispark.use.tiflash  true ( false)
```

:

1. spark-defaults.conf

```
spark.tispark.use.tiflash true
```

1. spark-shell ThriftServer

```
--conf spark.tispark.use.tiflash = true
```

1. Spark Shell :

```
spark.conf.set("spark.tispark.use.tiflash", true)
```

1. ThriftServer beeline :

```
set spark.tispark.use.tiflash = true;
```

true TiFlash false TiKV true TiFlash TiFlash

## 11.3.2

1. Region TiSpark TiFlash Region TiKV Region Spark Region TiSpark Region Region 48M 2 TiSpark Split Region

   ```
   spark.tispark.partition_per_split  2
   ```

2. TiFlash TiSpark

   ```
   spark.locality.wait 0s
   ```

# 11.4 TiSpark

TiDB

## 11.4.1 Hive

Hadoop Hive Hive TiDB Hadoop TiDB

1. SQL Hive/TiDB +
2. Hive
3. hive-site.xml Spark hive-site.xml SPARK_HOME/conf hive-site.xml Hive Metastore Spark Hive

## 11.4.2 beeline + Livy + Spark + Tispark

1.
   - Livy 0.6 Spark
   - beeline 3.1.1 Livy
   - Spark 2.4.0 yarn Spark
   - Tispark Jar 2.1.8 TiKV
   - YARN
2.

```
function runMixSQLOnLivy(){
export HIVE_HOME=/usr/local/share/apache-Hive-3.1.1-bin
/usr/local/share/apache-Hive-3.1.1-bin/bin/beeline -n hdfs_user_name -p hdfs_user_pwd --verbose=false --color=fa
lse \
  -u "jdbc:Hive2://bj0000,bj0001,bj0002:2222/;serviceDiscoveryMode=zooKeeper;zooKeeperNamespace=mix-livy" \
  --Hiveconf livy.session.conf.spark.sql.extensions=org.apache.spark.sql.TiExtensions \
  --Hiveconf livy.session.conf.spark.tispark.pd.addresses=10.10.10.10:2379,10.10.10.10:2379,10.10.10.10:2379 \
  --Hiveconf livy.session.conf.spark.jars=hdfs://com-hdfs/user/spark/tispark-core-2.1.4-spark_2.4-jar-with-depen
dencies.jar \
  --Hiveconf livy.session.name=session_name_${RANDOM}_$2 \
  --Hiveconf livy.session.queue=your_yarn_queue_name \
  -e "$1"
}
```

3.
   - shell 2 $1 SQL $2 $RANDOM session
   - beeline hdfs
   - -u JDBC URL livy
   - TiDB a) spark.sql.extensions=org.apache.spark.sql.TiExtensions
     b) spark.tispark.pd.addresses=10.10.10.11:2379,10.10.10.12:2379,10.10.13.10:2379
     c) spark.jars=hdfs://com-hdfs/user/spark/tispark-core-2.1.4-spark_2.4-jar-with-dependencies.jar
   - livy.session.name $2
   - livy.session.queue YARN
   - -e "$1"
4.

(1)

```
0: jdbc:Hive2://bj0000,bj0001,bj0002:2222/> show databases;
+----------------------------------------------------+
|                    databaseName                    |
+----------------------------------------------------+
| sales_db                                           |
| db_em                                              |
| db_test                                            |
| db_shr                                             |
+----------------------------------------------------+
```

sales_db Hive db_em TiDB

(2) TiDB

```
0: jdbc:Hive2://bj0000,bj0001,bj0002:2222/> select count(1) from db_em.app_war_room_fpyr_rt;
RSC client is executing SQL query: select count(1) from db_em.app_war_room_fpyr_rt, statementId = 91583fc3-0837-
4b26-b579-b438a53f151e, session = SessionHandle [b6933d96-8ec0-47b9-a767-ff2da5c5b2b2]
[Stage 0:>                                                          (0 + 1) / 1]
+-----------+
| count(1)  |
+-----------+
| 224       |
+-----------+
1 row selected (6.505 seconds)
```

(3) Hive

```
0: jdbc:Hive2://bj0000,bj0001,bj0002:2222/> select count(1) from sales_db.mdms_tsqa_syyt;
RSC client is executing SQL query: select count(1) from sales_db.mdms_tsqa_syyt, statementId = 324d7d1d-03bc-4d9
b-849f-18967305a454, session = SessionHandle [b6933d96-8ec0-47b9-a767-ff2da5c5b2b2]
[Stage 2:>                                                        (0 + 1) / 151]
...
[Stage 3:>                                                          (0 + 0) / 1]
+------------+
|  count(1)  |
+------------+
| 142380109  |
+------------+
1 row selected (25.169 seconds)
```

(4) Hive :

```
0: jdbc:Hive2://bj0000,bj0001,bj0002:2222/> insert into dc_tmp.test_for_mix  select count(1) as cnt from sales_d
b.mdms_tsqa_syyt union select count(1) as cnt from db_em.app_war_room_fpyr_rt;
RSC client is executing SQL query: insert into dc_tmp.test_for_mix  select count(1) as cnt from sales_db.mdms_ts
qa_syyt union select count(1) as cnt from db_em.app_war_room_fpyr_rt, statementId = 7e87c512-d5c5-4ba1-bd62-d013
ff16a4e7, session = SessionHandle [b6933d96-8ec0-47b9-a767-ff2da5c5b2b2]
[Stage 5:>                                                        (0 + 0) / 151]
......
[Stage 10:>                                                         (0 + 0) / 1]
+---------+
| Result  |
+---------+
+---------+
No rows selected (31.221 seconds)
```

(5)

```
0: jdbc:Hive2://bj0000,bj0001,bj0002:2222/> select cnt from dc_tmp.test_for_mix;
RSC client is executing SQL query: select cnt from dc_tmp.test_for_mix, statementId = 18247b15-d9fb-4b97-87a1-6f
a9cc3afad8, session = SessionHandle [b6933d96-8ec0-47b9-a767-ff2da5c5b2b2]
[Stage 11:>                                                         (0 + 1) / 1]
......
[Stage 11:>                                                         (0 + 1) / 1]
+------------+
|    cnt     |
+------------+
| 142380109  |
| 224        |
+------------+
2 rows selected (2.977 seconds)
```

HiveTiDB

## 11.4.3

## 1. TiDB

TiDB 4.0 TiSpark TiDB

- Spark JDBC TiDB MySQL
- TiSpark

TiSpark TiDB 4.0 TiSpark TiDB TiDB TiDB Github TiSpark

## 2.

TiDB Hive TiSpark TiDB TiSpark TiDB TiDB TiSpark tidb_ TiDB

```
spark.tispark.db_prefix  "tidb_"
```

## 11.4.4TiSpark

TiSpark Apache Spark Spark Apache Spark

# 1.1 TiUP & TiOps

TiDB

TiDB 4.0 TiUP https://tiup.io

TiDB

TiUP cluster

TiUP TiDB tidb/tikv/pd/tiflash prometheus/grafana/drainer/pump TiUP TiUP TiUP

# 1.1.1 TiUP

RPM Linux Yum Anaconda python TiDB Prometheus

TiDB 4.0 TiUP TiDB TiDBPDTiKV TiDB TiUP https://tiup.io/

## 1.

TiUP

```
curl --proto '=https' --tlsv1.2 -sSf https://tiup-mirrors.pingcap.com/install.sh | sh
```

TiUP `$HOME/.tiup` `$HOME/.tiup/bin` Shell Profile PATH TiUP TiUP

```
tiup --version
```

TiUP v0.0.3 TiUP

## 2.

TiUP TiUP `tiup help`

```
~$ tiup help
TiUP is a command-line component management tool that can help to download and install
TiDB platform components to the local system. You can run a specific version of a component via
"tiup <component>[:version]". If no version number is specified, the latest version installed
locally will be used. If the specified component does not have any version installed locally,
the latest stable version will be downloaded from the repository.

Usage:
  tiup [flags] <command> [args...]
  tiup [flags] <component> [args...]

Available Commands:
  install     Install a specific version of a component
  list        List the available TiDB components or versions
  uninstall   Uninstall components or versions of a component
  update      Update tiup components to the latest version
  status      List the status of instantiated components
  clean       Clean the data of instantiated components
  help        Help about any command or component

Available Components:
  playground          Bootstrap a local TiDB cluster
  package             A toolbox to package tiup component
  cluster             Deploy a TiDB cluster for production
  mirrors             Build a local mirrors and download all selected components

Flags:
  -B, --binary <component>[:version]   Print binary path of a specific version of a component <component>[:version]
                                       and the latest version installed will be selected if no version specified
      --binpath string                 Specify the binary path of component instance
  -h, --help                           help for tiup
      --skip-version-check             Skip the strict version check, by default a version must be a valid SemVer str
ing
  -T, --tag string                     Specify a tag for component instance

Component instances with the same "tag" will share a data directory ($TIUP_HOME/data/$tag):
  $ tiup --tag mycluster playground

Examples:
  $ tiup playground                    # Quick start
  $ tiup playground nightly            # Start a playground with the latest nightly version
  $ tiup install <component>[:version] # Install a component of specific version
  $ tiup update --all                  # Update all installed components to the latest version
  $ tiup update --nightly              # Update all installed components to the nightly version
  $ tiup update --self                 # Update the "tiup" to the latest version
  $ tiup list --refresh                # Fetch the latest supported components list
  $ tiup status                        # Display all running/terminated instances
  $ tiup clean <name>                  # Clean the data of running/terminated instance (Kill process if it's running)
  $ tiup clean --all                   # Clean the data of all running/terminated instances

Use "tiup [command] --help" for more information about a command.
```

TiUP

```
tiup [flags] <command> [args...]
tiup [flags] <component> [args...]
```

TiUP

1. tiup: TiUP
2. flags:
3. command component:
4. args:

- list:

- install:
- update:
- uninstall:
- status:
- clean:
- help:

flags

- `--binary`：
- `--binpath`：
- `--tag`：tag ID tag

`tiup list` playground/package/cluster

`tiup help <command|component>` `tiup <command|component> --help` `tiup <command|component> -h`

install `tiup help install` `tiup install --help` `tiup install -h`

## (1) tiup list

TiUP list

```
~$ tiup help list
List the available TiDB components if you don't specify any component name,
or list the available versions of a specific component. Display a list of
local caches by default. You must use --refresh to force TiUP to fetch
the latest list from the mirror server. Use the --installed flag to hide
components or versions which have not been installed.

  # Refresh and list all available components
  tiup list --refresh

  # List all installed components
  tiup list --installed

  # List all installed versions of TiDB
  tiup list tidb --installed

Usage:
  tiup list [component] [flags]

Flags:
  -h, --help        help for list
      --installed   List installed components only.
      --refresh     Refresh local components/version list cache.

Global Flags:
      --skip-version-check   Skip the strict version check, by default a version must be a valid SemVer string
```

- `tiup list`：
- `tiup list <component>`：

flag

- `--installed`：
- `--refresh`：

```
tiup list --installed
```

TiKV

```
tiup list tikv --refresh
```

## (2) tiup install

- `tiup install`

```
$ tiup help install
Install a specific version of a component. The component can be specified
by <component> or <component>:<version>. The latest stable version will
be installed if there is no version specified.

You can install multiple components at once, or install multiple versions
of the same component:

  tiup install tidb:v3.0.5 tikv pd
  tiup install tidb:v3.0.5 tidb:v3.0.8 tikv:v3.0.9

Usage:
  tiup install <component1>[:version] [component2...N] [flags]

Flags:
  -h, --help   help for install

Global Flags:
      --skip-version-check   Skip the strict version check, by default a version must be a valid SemVer string
```

- `tiup install <component>`：
- `tiup install <component>:[version]`：

TiUP TiDB

```
tiup install tidb
```

TiUP nightly TiDB

```
tiup install tidb:nightly
```

TiUP v3.0.6 TiKV

```
tiup install tikv:v3.0.6
```

## (3) tiup update

TiUP

```
$ tiup help update
Update some components to the latest version. Use --nightly
to update to the latest nightly version. Use --all to update all components
installed locally. Use <component>:<version> to update to the specified
version. Components will be ignored if the latest version has already been
installed locally, but you can use --force explicitly to overwrite an
existing installation. Use --self which is used to update TiUP to the
latest version. All other flags will be ignored if the flag --self is given.

  $ tiup update --all                     # Update all components to the latest stable version
  $ tiup update --nightly --all           # Update all components to the latest nightly version
  $ tiup update playground:v0.0.3 --force # Overwrite an existing local installation
  $ tiup update --self                    # Update TiUP to the latest version

Usage:
  tiup update [component1][:version] [component2..N] [flags]

Flags:
      --all       Update all components
      --force     Force update a component to the latest version
  -h, --help      help for update
      --nightly   Update the components to nightly version
      --self      Update tiup to the latest version

Global Flags:
      --skip-version-check   Skip the strict version check, by default a version must be a valid SemVer string
```

install flag

- `--all`：
- `--nightly`：nightly
- `--self`：TiUP
- `--force`：

```
tiup update --all
```

nightly

```
tiup update --all --nightly
```

TiUP

```
tiup update --self
```

## (4) tiup <component>

TiUP

```
tiup [flags] <component>[:version] [args...]
```

TiUP tag tag tag

`--tag` tag

v3.0.8 TiDB

```
tiup tidb:v3.0.8
```

tag TiKV

```
tiup --tag=experiment tikv
```

## (5) tiup status

`tiup status`

```
~$ tiup help status
List the status of instantiated components

Usage:
  tiup status [flags]

Flags:
  -h, --help   help for status

Global Flags:
      --skip-version-check   Skip the strict version check, by default a version must be a valid SemVer string
```

- Name: tag
- Component:
- PID: ID
- Status: RUNNING TERM
- Created Time:
- Directory: `--tag`
- Binary: `--binpath`
- Args:

## (6) tiup clean

`tiup clean` kill

```
~$ tiup help clean
Clean the data of instantiated components

Usage:
  tiup clean [flags]

Flags:
      --all    Clean all data of instantiated components
  -h, --help   help for clean

Global Flags:
      --skip-version-check   Skip the strict version check, by default a version must be a valid SemVer string
```

tag experiment

```
tiup clean experiment
```

```
tiup clean --all
```

## (4) tiup uninstall

TiUP TiUP

```
~$ tiup help uninstall
If you specify a version number, uninstall the specified version of
the component. You must use --all explicitly if you want to remove all
components or versions which are installed. You can uninstall multiple
components or multiple versions of a component at once. The --self flag
which is used to uninstall tiup.

  # Uninstall tiup
  tiup uninstall --self

  # Uninstall the specific version a component
  tiup uninstall tidb:v3.0.10

  # Uninstall all version of specific component
  tiup uninstall tidb --all

  # Uninstall all installed components
  tiup uninstall --all

Usage:
  tiup uninstall <component1>[:version] [flags]

Flags:
      --all    Remove all components or versions.
  -h, --help   help for uninstall
      --self   Uninstall tiup and clean all local data

Global Flags:
      --skip-version-check   Skip the strict version check, by default a version must be a valid SemVer string
```

v3.0.8 TiDB

```
tiup uninstall tidb:v3.0.8
```

TiKV

```
tiup uninstall tikv --all
```

```
tiup uninstall --all
```

## 1.1.2 TiUP

TiDB TiDB 3 PD 3 TiKV 2 TiDB TiDB TiDB TiUP TiUP playground client TiDB

## 1. playground

playground TiUP TiDB/PD/TiKV

list playground

```
tiup list playground
```

install playground

```
tiup install playground
```

`tiup playground` playground

```
~$ tiup help playground
Bootstrap a TiDB cluster in your local host, the latest release version will be chosen
if you don't specified a version.

Examples:
  $ tiup playground nightly                         # Start a TiDB nightly version local cluster
  $ tiup playground v3.0.10 --db 3 --pd 3 --kv 3    # Start a local cluster with 10 nodes
  $ tiup playground nightly --monitor               # Start a local cluster with monitor system
  $ tiup playground --pd.config ~/config/pd.toml    # Start a local cluster with specified configuration file,
  $ tiup playground --db.binpath /xx/tidb-server    # Start a local cluster with component binary path

Usage:
  tiup playground [version] [flags]

Flags:
      --db int              TiDB instance number (default 1)
      --db.binpath string   TiDB instance binary path
      --db.config string    TiDB instance configuration file
  -h, --help                help for tiup
      --host string         Playground cluster host (default "127.0.0.1")
      --kv int              TiKV instance number (default 1)
      --kv.binpath string   TiKV instance binary path
      --kv.config string    TiKV instance configuration file
      --monitor             Start prometheus component
      --pd int              PD instance number (default 1)
      --pd.binpath string   PD instance binary path
      --pd.config string    PD instance configuration file
```

playground

- 
- 
- `--host` host IP
- `--monitor` Prometheus

```
tiup playground
```

- TiUP playground v0.0.6 `tiup playground:v0.0.6`
- playground v0.0.6 TiUP

- playground TiDB/PD/TiKV release v4.0.0 `tiup playground:v0.0.6 v4.0.0`
- playground 1 TiDB1 TiKV 1 PD
- playground TiUP TiDB/PD/TiKV `tiup tidb:v4.0.0` TiDB
- playground MySQL dashboard

`--tag` TiUP tag tag tag

```
tiup --tag=my-cluster playground
```

TiUP v3.0.9

```
tiup playground v3.0.9
```

TiUP nightly

```
tiup playground nightly
```

TiKV 3 Prometheus

```
tiup playground --kv=3 --monitor
```

IP `x.x.x.x`

```
tiup playground --host x.x.x.x
```

## 2. playground

TiDB 2 TiDB 3 TiKV 3 PD playground

```
tiup playground --db=2 --kv=3 --pd=3
```

playground `--monitor`

```
tiup playground --db=2 --kv=3 --pd=3 --monitor
```

playground MySQL

```
CLUSTER START SUCCESSFULLY, Enjoy it ^-^
To connect TiDB: mysql --host 127.0.0.1 --port 4000 -u root
```

playground TiUP client

```
tiup client
```

client DOS

tag

```
tiup client <tag>
```

# 1.1.3 TiOps

## 1.TiOps

### 1.1

TiDB TiDB Ansible TiDBTiDB Ansible TiDB TiOps

### 1.2

TiOps TiDB TiDB

## 2.

### 2.1

TiOps TiDB (SSH)

### 2.2

TiDB //

## 3.

- CentOS 7.3 Linux el7
- epel-release EPEL
- `$HOME` > 10GB
-

(1)

```
yum install -y epel-release
```

(2) TiOps

rpm tiup nightly

v0.2.0

```
wget https://download.pingcap.org/tiops-v0.2.0-1.el7.x86_64.rpm
yum localinstall -y tiops-v0.2.0-1.dev.el7.x86_64.rpm
```

(3) TiOps

`tiops -h` TiOps

```
tiops -h
usage: tiops [-h] [-v]


{bootstrap-local,bootstrap-ssh,bootstrap-host,deploy,start,stop,restart,upgrade,display,destroy,reload,edit-config,sc
ale-out,scale-in,exec,quickdeploy,version}
             ...

positional arguments:
  {bootstrap-local,bootstrap-ssh,bootstrap-host,deploy,start,stop,restart,upgrade,display,destroy,reload,edit-config,
scale-out,scale-in,exec,quickdeploy,version}
                        tidb cluster commands
    bootstrap-local     init localhost
    bootstrap-ssh       init ssh for cluster hosts
    bootstrap-host      init environment for cluster hosts
    deploy              create tidb cluster
    start               start tidb cluster
    stop                stop tidb cluster
    restart             restart tidb cluster
    upgrade             upgrade tidb cluster
    display             display tidb cluster
    destroy             destroy tidb cluster
    reload              reload tidb cluster
    edit-config         edit tidb cluster configuration
    scale-out           scale out tidb cluster
    scale-in            scale in tidb cluster
    exec                run shell command on host in the tidb cluster
    quickdeploy         deploy a tidb cluster in demo mode
    version             show TiOps version and exit


optional arguments:
  -h, --help            show this help message and exit
  -v, --verbose         Print verbose output.
```

(4)

ssh key `~/.ssh/id_rsa` `~/.ssh/id_rsa.pub` ssh key ssh

```
tiops bootstrap-local
```

(5)

IP TiDB sudo

```
tiops bootstrap-ssh -H 10.9.1.1,10.9.1.2,10.9.1.3 -u root -d tidb
```

```
-H |--host hosts IP  IP  `,`  IP  IP  /usr/share/tiops/hosts.yaml.example

-u | --user  root
-p | --password
-d |--deploy-user   TiDB
-s | --ssh-port  SSH  22
-f | --forks 5
```

- ssh TiOps

- root root
-

(6)

NTP Swapirqbalance

```
tiops bootstrap-host -H 10.9.1.1,10.9.1.2,10.9.1.3 -d tidb
```

```
-H |--host hosts IP  IP  `,`  IP  IP  /usr/share/tiops/hosts.yaml.example

-d |--deploy-user   TiDB
-s | --ssh-port  SSH  22
--enable-check-ntp  NTP                 disable
--ntp-server  NTP  NTP example: 10.0.0.10 or 10.0.0.10,10.0.0.11
--timezone  Asia/Shanghai
--enable-swap  swap             disable
--disable-irqbalance  irqbalance             enable
--enable-checks                 disable
-f | --forks 5
```

- TiDB

(7)

TiOps

```
cat /usr/share/tiops/topology.yaml.example
```

- pd_serverstidb_serverstikv_serversmonitoring_servergrafana_server
- `IP` `data_dir` `deploy_dir` `port` `/usr/share/tiops/topology.yaml.example.full`

# 4.TiOps

## 4.1

`/usr/share/tiops/topology.yaml.example` `/usr/share/tiops/topology.yaml.example.full`

```
cp /usr/share/tiops/topology.yaml.example topology.yaml
```

```
vim topology.yaml
```

pd_serverstidb_serverstikv_serversmonitoring_servergrafana_server IP

```
---

pd_servers:
  - ip: 10.9.1.1
  - ip: 10.9.1.2
  - ip: 10.9.1.3

tidb_servers:
  - ip: 10.9.1.1
  - ip: 10.9.1.2

tikv_servers:
  - ip: 10.9.1.1
  - ip: 10.9.1.2
  - ip: 10.9.1.3

monitoring_server:
  - ip: 10.9.1.1

grafana_server:
  - ip: 10.9.1.1
```

## 4.2

(1)

-T TiOps `mai` `start`

```
tiops deploy -c mai -T topology.yaml -d tidb
```

```
-c | --cluster_name name
-T | --topology
-t | --tidb-version TiDB  3.0.5
-d | --deploy-user   TiDB
--enable-check-cpu  CPU vcores                    disable
--enable-check-mem  Memory Size                  disable
--enable-check-disk  Disk Available Space                   disable
--enable-check-iops  IOPS  latency                      disable
--enable-check-all   CPUMemoryDiskIOPS                    disable
--enable-firewall                     disable
--enable-check-config                    disable
--local-pkg
-f | --forks 5
```

# 5.TiOps

## 5.1 //

### :

```
tiops start -c mai
```

`Finished start.` mysql client TiDB

```
mysql -h 10.9.1.1 -P4000 -u root
```

`Server version: 5.7.25-TiDB-v3.0.9 MySQL Community Server (Apache License 2.0)` TiDB

**：**

```
-c | --cluster_name name
-T | --topology
-t | --tidb-version TiDB  3.0.5
-d | --deploy-user   TiDB
--enable-check-cpu  CPU vcores                    disable
--enable-check-mem  Memory Size                  disable
--enable-check-disk  Disk Available Space                    disable
--enable-check-iops  IOPS  latency                       disable
--enable-check-all   CPUMemoryDiskIOPS                     disable
--enable-firewall                     disable
--enable-check-config                    disable
--local-pkg
-f | --forks 5
```

**：**

- ID
-

## 5.2 //

**：**

```
tiops restart -c mai
```

TiOps  grafana, blackbox_exporter, node_exporter, prometheus, tidb, tikv, pd

**：**

```
-c | --cluster_name cluster_name
-r | --role role  TiDB                        "pd", "tikv", "pump", "tidb",  "drainer", "monitoring", "monitored", "g
rafana", "alertmanager"
-n | --node-id node_id  ID  ID  display
-f | --forks 5
```

## 5.3 //

**：**

```
tiops stop -c mai
```

TiOps  grafana, blackbox_exporter, node_exporter, prometheus, tidb, tikv, pd

**：**

```
-c | --cluster_name cluster_name
-r | --role role  TiDB                        "pd", "tikv", "pump", "tidb",  "drainer", "monitoring", "monitored", "g
rafana", "alertmanager"
-n | --node-id node_id  ID  ID  display
-f | --forks 5
```

## 5.4

### :

```
tiops destroy -c mai
```

```
-c | --cluster_name cluster_name
-f | --forks 5
```

- 

## 5.5

```
tiops upgrade -c mai -d tidb
```

```
-c | --cluster_name cluster_name
-r | --role role  TiDB                        "pd", "tikv", "pump", "tidb",  "drainer", "monitoring", "monitored", "g
rafana", "alertmanager"
-n | --node-id node_id  ID  ID  display
--force
--local-pkg
--enable-check-config                    disable
-f | --forks 5
```

## 5.6

```
tiops scale-out -c mai -T topology.yaml
```

```
-c | --cluster_name name
-T | --topology
--check-cpu  CPU vcores                    disable
--enable-check-mem  Memory Size                  disable
--enable-check-disk  Disk Available Space                    disable
--enable-check-iops  IOPS  latency                       disable
--enable-check-all   CPUMemoryDiskIOPS                     disable
--local-pkg
-f | --forks 5
```

## 5.7

```
tiops scale-in -c mai
```

```
-c | --cluster_name name
-n |  --node-id nodes  ID  ID  display
-f | --forks 5
```

## 5.8

```
tiops reload -c mai
```

```
-c | --cluster_name cluster_name
-r | --role role  TiDB                        "pd", "tikv", "pump", "tidb",  "drainer", "monitoring", "monitored", "g
rafana", "alertmanager"
-n | --node-id node_id  ID  ID  display
-f | --forks 5
```

## 5.9

```
tiops edit-config -c mai
```

```
-c | --cluster_name cluster_name
```

- reload

## 5.10

//

```
tiops display -c mai
```

```
-c | --cluster_name cluster_name
-r | --role role  TiDB                        "pd", "tikv", "pump", "tidb",  "drainer", "monitoring", "monitored", "g
rafana", "alertmanager"
-n | --node-id node_id  ID  ID  display
 --status
```

`--status` TiDB

```
TiDB cluster mai, version 3.0.9
Node list:
ID        Role        Host          Ports        Status    Data Dir                                    Deploy Dir
f5961fad  Monitoring  10.9.1.1   9090/9091    -         /home/tidb/data/mai/monitoring-f5961fad  /home/tidb/deploy/ma
i/monitoring-f5961fad
eb57cedb  PD          10.9.1.1   2379/2380    Health    /home/tidb/data/mai/pd-eb57cedb          /home/tidb/deploy/ma
i/pd-eb57cedb
hb6289b2  PD          10.9.1.2  2379/2380    Health|L  /home/tidb/data/mai/pd-hb6289b2          /home/tidb/deploy/mai
/pd-hb6289b2
dd25d798  PD          10.9.1.3  2379/2380    Health    /home/tidb/data/mai/pd-dd25d798          /home/tidb/deploy/mai
/pd-dd25d798
dded5656  TiDB        10.9.1.1  4000/10080   Up        -                                        /home/tidb/deploy/mai
/tidb-dded5656
dedfd1cb  TiDB        10.9.1.2  4000/10080   Up        -                                        /home/tidb/deploy/mai
/tidb-dedfd1cb
jbab8302  Monitored   10.9.1.1  9100/9115    -         -                                        /home/tidb/deploy/mai
/monitored-jbab8302
db46f98f  Monitored   10.9.1.2   9100/9115    -         -                                        /home/tidb/deploy/ma
i/monitored-db46f98f
h1f9fce0  Monitored   10.9.1.3  9100/9115    -         -                                        /home/tidb/deploy/mai
/monitored-h1f9fce0
g0418cd7  TiKV        10.9.1.1   20160/20180  Up        /home/tidb/data/mai/tikv-g0418cd7        /home/tidb/deploy/ma
i/tikv-g0418cd7
c7e55608  TiKV        10.9.1.2  20160/20180  Up        /home/tidb/data/mai/tikv-c7e55608        /home/tidb/deploy/mai
/tikv-c7e55608
hf2c6bb4  TiKV        10.9.1.3  20160/20180  Up        /home/tidb/data/mai/tikv-hf2c6bb4        /home/tidb/deploy/mai
/tikv-hf2c6bb4
i701ff8d  Grafana     10.9.1.1   3000         -         -                                        /home/tidb/deploy/ma
i/grafana-i701ff8d
```

```
TiDB Up/Down
PD  Health/Unhealth, PD  Down; PD Leader  L
TiKV Store  Up/Offline/Tombstone  TiKV  Down
Pump Node  Pump  Down
Drainer Node  Drainer  Down
```

Status `-`

## 5.11 TiOps

```
tiops version
```

TiOps

## 5.12 quickdeploy

```
tiops quickdeploy -c mai -d tidb -H 10.9.1.1,10.9.1.2,10.9.1.3 -T topology.yaml
```

```
-c | --cluster_name name
-T | --topology
-H | --host hosts IP  IP  `,`  IP  IP  /usr/share/tiops/hosts.yaml.example

-u | --user  root
-d | --deploy-user   TiDB
-t | --tidb-version TiDB  3.0.5
-p | --password
-s | --ssh-port  SSH  22
--enable-check-cpu  CPU vcores                    disable
--enable-check-mem  Memory Size                  disable
--enable-check-disk  Disk Available Space                    disable
--enable-check-iops  IOPS  latency                       disable
--enable-check-all   CPUMemoryDiskIOPS                     disable
--enable-firewall                     disable
--enable-check-config                    disable
--local-pkg
-f | --forks 5
```

## 6.

TiOps  TiSpark  TiFlash

## 1.1.4 TiOps

- CentOS 7.3 Linux

| | CPU | | | | | |
|---|---|---|---|---|---|---|
| PD | >= 4 Core | >= 8 GB | SSD | >= 300 GB | >= 1 | 3 |
| TiDB | >= 16 Core | >= 32 GB | SAS/SSD | >= 300 GB | >= 1 | 2 |
| TiKV | >= 16 Core | >= 32 GB | SSD | <= 2 TB | >= 1 | 3 |
| Prometheus | >= 8 Core | >= 16 GB | SAS/SSD | >= 300 GB | >= 1 | 1 |

- TiDB
  - >= 2 tidb-server
  - SAS/SSD >= 300 GB
- TiKV
  - >= 3 tikv-server
  - label label
  - SSD PCI-E SSD <= 2 TB, SSD <= 1.5 TB
- PD
  - >= 3
  - SSD >= 300 GB
- Prometheus
  - 1
- Other
  - TiDBPDPrometheus
  -
  -

TiDB TiDB

| | | |
|---|---|---|
| TiDB | 4000 | DBA |
| TiDB | 10080 | TiDB |
| TiKV | 20160 | TiKV |
| PD | 2379 | TiDB PD |
| PD | 2380 | PD |
| Pump | 8250 | Pump |
| Drainer | 8249 | Drainer |
| Prometheus | 9090 | Prometheus |
| Pushgateway | 9091 | TiDBTiKVPD |
| Node_exporter | 9100 | TiDB |
| Blackbox_exporter | 9115 | Blackbox_exporter TiDB |
| Grafana | 3000 | Web () |
| Grafana | 8686 | grafana_collector Dashboard PDF |
| Kafka_exporter | 9308 | Kafka_exporter binlog kafka |

## topology

```
---

pd_servers:
  - ip: 10.9.1.1
  - ip: 10.9.1.2
  - ip: 10.9.1.3

tidb_servers:
  - ip: 10.9.1.2
  - ip: 10.9.1.3

tikv_servers:
  - ip: 10.9.1.4
    ## The value of label can be customized, for example: 'zone=z1,rack=r1,host=h1' or 'a=a1,b=b1,c=c1', etc
    ## Can only set in tikv_servers
    # label: host=h1
  - ip: 10.9.1.5
  - ip: 10.9.1.6

monitoring_server:
  - ip: 10.9.1.7

grafana_server:
  - ip: 10.9.1.7
```

label `'zone=z1,rack=r1,host=h1'` `'a=a1,b=b1,c=c1'` label tikv_servers

"1.1.4 " TiOps TiDB

# 1.2.1 TiDB Operator

——

## 1.2.1.1

2020

“ TiDB ”

“ 2020 TiDB TiDB ”

“ deiK8s “

## 1.2.1.2

> TiDB Operator Kubernetes TiDB TiDB TiDB OperatorTiDB Kubernetes
>
> —— PingCAP

TiDB Operator “” TiDB “”“” Operator “What to do“ Operator “How to do” TiDB Operator "What to do" auto-scaler

## 1.2.1.3 TiDB Operator

## 1.2.1.4 TiDB Operator

- TiDB Cluster CRD `CustomResourceDefinition` `TidbCluster` Kubernetes TiDB Cluster `Deployment` `StatefulSet` Kubernetes TiDB Operator v1.1.0 CRD `TidbCluster` `Backup` `Restore` `BackupSchedule` `TidbMonitor` `TidbInitializer` `TidbClusterAutoScaler`
- `tidb-controller-manager`
- `tidb-scheduler` Kubernetes Kubernetes TiDB Node TiDB TiKV

## 1.2.1.5

- TiDB Cluster CR `CustomResource` TiDB Cluster `TidbCluster`

### 1.2.1.6 Kubernetes

- `kube-apiserver` Kubernetes API Server
- `kube-controller-manager` `TidbCluster` CR `StatefulSet` `Deployment` `CronJob` K8s
- `kube-scheduler` TiDB Cluster Pod `filtering` kube-scheduler `tidb-scheduler` kube-scheduler `scoring` Pod

`Deployment` `StatefulSet` `CRD` K8s `CR`

### 1.2.1.7

TiDB Operator Helm Chart TiDB

1. Helm `TidbCluster` Kubernetes `CronJob`
2. TiDB Operator Kubernetes API Server watch `TidbCluster` PDTiKVTiDB `StatefulSet` `Service`
3. Kubernetes `StatefulSet` `Deployment` `CronJob` `Pod`
4. PDTiKVTiDB `Pod` `tidb-scheduler` `tidb-scheduler` `Pod` TiDB

TiDB Operator `TidbCluster` “”

# 1.2.2 TiDB-Operator

## 1.2.2.1

Linux MacOS kind Kubernetes TiDB Operator TiDB

1. kind K8s
2. K8s TiDB Operator
3. K8s TiDB

- 4GB+CPU 2 cores
- Docker 17.03+
- Go 1.10+
- net.ipv4.ip_forward 1

## 1.2.2.2 kind K8s

1.

```
# cd /root & git clone --depth=1 https://github.com/pingcap/tidb-operator && cd tidb-operator
```

1.

```
# cd /root/tidb-operator && hack/kind-cluster-build.sh
```

:

```
########## success create cluster:[kind] ##########
To start using your cluster, run:
    kubectl config use-context kind-kind
```

1. K8s PATH

```
    # export PATH=$PATH:/root/tidb-operator/output/bin/
```

1. K8s

```
    # kubectl cluster-info
      Kubernetes master is running at https://127.0.0.1:32771
      KubeDNS is running at https://127.0.0.1:32771/api/v1/namespaces/kube-system/services/kube-dns:dns/proxy
```

K8s

```
    # helm version
      Client: &version.Version{SemVer:"v2.9.1", GitCommit:"20adb27c7c5868466912eebdf6664e7390ebe710", GitTreeState:"c
lean"}
      Server: &version.Version{SemVer:"v2.9.1", GitCommit:"20adb27c7c5868466912eebdf6664e7390ebe710", GitTreeState:"c
lean"}
```

Helm

# 1.2.2.3 K8s TiDB Operator

1. helm TiDB Operator

TiDB CRD

```
    # kubectl apply -f https://raw.githubusercontent.com/pingcap/tidb-operator/master/manifests/crd.yaml && kubectl g
et crd tidbclusters.pingcap.com
    customresourcedefinition.apiextensions.k8s.io/tidbclusters.pingcap.com unchanged
    customresourcedefinition.apiextensions.k8s.io/backups.pingcap.com unchanged
    customresourcedefinition.apiextensions.k8s.io/restores.pingcap.com unchanged
    customresourcedefinition.apiextensions.k8s.io/backupschedules.pingcap.com unchanged
    customresourcedefinition.apiextensions.k8s.io/tidbmonitors.pingcap.com unchanged
    customresourcedefinition.apiextensions.k8s.io/tidbinitializers.pingcap.com unchanged
    customresourcedefinition.apiextensions.k8s.io/tidbclusterautoscalers.pingcap.com unchanged
    NAME                        CREATED AT
    tidbclusters.pingcap.com    2020-03-06T13:38:32Z
```

TiDB Operator Helm chart

```
    # mkdir -p /root/chart/

     https://github.com/pingcap/tidb-operator/releases  tidb-operator-chart-v1.0.6.tgz  /root/chart/

    # cd /root/chart/ && tar xvf tidb-operator-chart-v1.0.6.tgz
```

/root/tidb-operator/charts/tidb-operator/values.yaml scheduler.kubeSchedulerImageName registry.cn-hangzhou.aliyuncs.com/google_containers/kube-scheduler

1. TiDB Operator

```
    # helm install --namespace=tidb-admin  --name=tidb-operator /root/tidb-operator/charts/tidb-operator -f /root/tid
b-operator/charts/tidb-operator/values.yaml
    NAME:   tidb-operator
    LAST DEPLOYED: Fri Mar  6 14:24:09 2020
    NAMESPACE: tidb-admin
    STATUS: DEPLOYED
    ...
```

1. Operator

```
    # kubectl get pods -n tidb-admin
    NAME                                       READY   STATUS    RESTARTS   AGE
    tidb-controller-manager-85d8d498bf-2n8km   1/1     Running   0          19s
    tidb-scheduler-7c67d6c77b-qd54r            2/2     Running   0          19s
```

Operator

# 1.2.2.4 K8s TiDB

1. TiDB Cluster helm chart

```
    # mkdir -p /root/chart/
     https://github.com/pingcap/tidb-operator/releases  tidb-cluster-chart-v1.0.6.tgz  /root/chart/
```

1. TiDB Cluster

```
    # cd /root/chart/ && tar xvf tidb-cluster-chart-v1.0.6.tgz
    # helm install --namespace dba-test --name=test /root/tidb-operator/charts/tidb-cluster -f /root/tidb-operator/ch
arts/tidb-cluster/values.yaml
    NAME:   test
    LAST DEPLOYED: Fri Mar  6 14:50:25 2020
    NAMESPACE: dba-test
    STATUS: DEPLOYED
```

TiDB Cluster

1. TiDB POD

```
    # kubectl get pods -n dba-test
    NAME                                READY   STATUS    RESTARTS   AGE
    test-discovery-668b48577c-lqqbz   1/1     Running   0          7m37s
    test-monitor-5b586d8cb-227qx      3/3     Running   0          7m37s
    test-pd-0                         1/1     Running   0          7m37s
    test-pd-1                         1/1     Running   0          7m37s
    test-pd-2                         1/1     Running   1          7m37s
    test-tidb-0                       2/2     Running   0          6m18s
    test-tidb-1                       2/2     Running   0          6m18s
    test-tikv-0                       1/1     Running   0          6m58s
    test-tikv-1                       1/1     Running   0          6m58s
    test-tikv-2                       1/1     Running   0          6m58s
```

TiDB Cluster Pod

1. TiDB

```
    # nohup kubectl port-forward svc/test-tidb 4000:4000 --namespace=dba-test &
    # yum install -y mysql
    # mysql -h 127.0.0.1 -uroot -P4000
    mysql -h 127.0.0.1 -P 4000 -uroot
    Welcome to the MariaDB monitor.  Commands end with ; or \g.
    Your MySQL connection id is 1
    Server version: 5.7.25-TiDB-v3.0.5 MySQL Community Server (Apache License 2.0)
    Copyright (c) 2000, 2018, Oracle, MariaDB Corporation Ab and others.
    Type 'help;' or '\h' for help. Type '\c' to clear the current input statement.
    MySQL [(none)]>
```

TiDB

# 1.2.3 TiDB-Operator

TiDB-Operator TiDB

TiDB

- AWS EKS TiDB
- GCP GKE TiDB
- TiDB
- TiDB

TiDB TiDB PV TiDB Operator TiDB TiDB

# 1.2.3.1 TiDB

TiDB

- AWS EKS TiDB
- GCP GKE TiDB
- TiDB
- TiDB

# 1.2.3.1.1 AWS EKS TiDB

Linux macOS AWS EKS (Elastic Kubernetes Service) TiDB

## 1.

- awscli >= 1.16.73 AWS

  AWS `awscli` `aws configure` :

  ```
  aws configure
  ```

  AWS Access Key ID AWS Secret Access Key

  ```
  AWS Access Key ID [None]: IOSFODNN7EXAMPLE
  AWS Secret Access Key [None]: wJaXUtnFEMI/K7MDENG/bPxRfiCYEXAMPLEKEY
  Default region name [None]: us-west-2
  Default output format [None]: json
  ```

  > Access key VPC EBS EC2 Role

- terraform >= 0.12
- kubectl >= 1.11
- helm >= 2.11.0 < 3.0.0
- jq
- aws-iam-authenticatorAWS `PATH`

  `aws-iam-authenticator`

  Linux

  ```
  curl -o aws-iam-authenticator https://amazon-eks.s3-us-west-2.amazonaws.com/1.12.7/2019-03-27/bin/linux/amd64/
  aws-iam-authenticator
  ```

  macOS

  ```
  curl -o aws-iam-authenticator https://amazon-eks.s3-us-west-2.amazonaws.com/1.12.7/2019-03-27/bin/darwin/amd64
  /aws-iam-authenticator
  ```

  ```
  chmod +x ./aws-iam-authenticator && \
  sudo mv ./aws-iam-authenticator /usr/local/bin/aws-iam-authenticator
  ```

## 2.

VPC t2.micro ec2 EKS

- 3 m5.xlarge PD

- 3 c5d.4xlarge TiKV
- 2 c5.4xlarge TiDB
- 1 c5.2xlarge

Github

```
git clone --depth=1 https://github.com/pingcap/tidb-operator && \
cd tidb-operator/deploy/aws
```

`terraform`

```
terraform init
```

```
terraform apply
```

> `terraform apply` "yes"

10 `terraform apply`

```
Apply complete! Resources: 67 added0 changed0 destroyed.

Outputs:

bastion_ip = [
  "34.219.204.217",
]
default-cluster_monitor-dns = a82db513ba84511e9af170283460e413-1838961480.us-west-2.elb.amazonaws.com
default-cluster_tidb-dns = a82df6d13a84511e9af170283460e413-d3ce3b9335901d8c.elb.us-west-2.amazonaws.com
eks_endpoint = https://9A9A5ABB8303DDD35C0C2835A1801723.yl4.us-west-2.eks.amazonaws.com
eks_version = 1.12
kubeconfig_filename = credentials/kubeconfig_my-cluster
region = us-west-21
```

`terraform output`

> 1.14 EKS NLB TiDB AWS NLB

# 3.

`terraform apply` `ssh` MySQL client TiDB

`<>` )

```
ssh -i credentials/<eks_name>.pem centos@<bastion_ip>
```

```
mysql -h <default-cluster_tidb-dns> -P 4000 -u root
```

`eks_name` `my-cluster` DNS

`kubectl` `helm` kubeconfig `credentials/kubeconfig_<eks_name>` EKS

- --kubeconfig

```
kubectl --kubeconfig credentials/kubeconfig_<eks_name> get po -n <default_cluster_name>
```

```
helm --kubeconfig credentials/kubeconfig_<eks_name> ls
```

- KUBECONFIG

```
export KUBECONFIG=$PWD/credentials/kubeconfig_<eks_name>
```

```
kubectl get po -n <default_cluster_name>
```

```
helm ls
```

# 4. Grafana

`<monitor-dns>:3000` Grafana

Grafana

- admin
- admin

# 5. TiDB

TiDB `terraform.tfvars` `default_cluster_version` `terraform apply`

TiDB 4.0.1 `default_cluster_version` `v4.0.1`

```
default_cluster_version= "v4.0.1"
```

> `kubectl --kubeconfig credentials/kubeconfig_<eks_name> get po -n <default_cluster_name> --watch`

# 6. TiDB

TiDB `terraform.tfvars` `default_cluster_tikv_count` `default_cluster_tidb_count` `terraform apply`

`default_cluster_tidb_count` 2 4 TiDB

```
default_cluster_tidb_count = 4
```

> - TiDB
> - `kubectl --kubeconfig credentials/kubeconfig_<eks_name> get po -n <default_cluster_name> --watch`

# 7.

`terraform.tfvars`

### AWS

TiDB Internal Elastic Load Balancer Amazon EC2 TiDB MySQL Sysbench SSH ELB TiDB VPC EC2 `create_bastion` `false`

TiDB `terraform.tfvars`

### TiDB

Terraform EKS TiDB `clusters.tf` `override_values` TiDB `values.yaml`

`./default-cluster.yaml` `values.yaml` ""

EKS `values.yaml` `NodeSelector` `Tolerations` `NodeSelector` `Tolerations` Terraform TiDB `cluster.tf` `tidb-cluster` module

> `values.yaml` `tidb-cluster` module

```
pd:
  storageClassName: ebs-gp2
tikv:
  stroageClassName: local-storage
tidb:
  service:
    type: LoadBalancer
    annotations:
      service.beta.kubernetes.io/aws-load-balancer-internal: '0.0.0.0/0'
      service.beta.kubernetes.io/aws-load-balancer-type: nlb
      service.beta.kubernetes.io/aws-load-balancer-cross-zone-load-balancing-enabled: >'true'
  separateSlowLog: true
monitor:
  storage: 100Gi
  storageClassName: ebs-gp2
  persistent: true
  grafana:
    config:
      GF_AUTH_ANONYMOUS_ENABLED: "true"
    service:
      type: LoadBalancer
```

### TiDB Operator

`terraform.tfvars` `operator_values` `values.yaml` TiDB Operator

```
operator_values = "./operator_values.yaml"
}
```

## 8. TiDB

`tidb-cluster` TiDB `clusters.tf` `tidb-cluster` TiDB

```
module example-cluster {
  source = "../modules/aws/tidb-cluster"

  # The target EKS, required
  eks = local.eks
  # The subnets of node pools of this TiDB cluster, required
  subnets = local.subnets
  # TiDB cluster name, required
  cluster_name    = "example-cluster"

  # Helm values file
  override_values = file("example-cluster.yaml")
  # TiDB cluster version
  cluster_version               = "v3.0.0"
  # SSH key of cluster nodes
  ssh_key_name                  = module.key-pair.key_name
  # PD replica number
  pd_count                      = 3
  # TiKV instance type
  pd_instance_type              = "t2.xlarge"
  # TiKV replica number
  tikv_count                    = 3
  # TiKV instance type
  tikv_instance_type            = "t2.xlarge"
  # The storage class used by TiKV, if the TiKV instance type do not have local SSD, you should change it to storage
class
  # TiDB replica number
  tidb_count                    = 2
  # TiDB instance type
  tidb_instance_type            = "t2.xlarge"
  # Monitor instance type
  monitor_instance_type         = "t2.xlarge"
  # The version of tidb-cluster helm chart
  tidb_cluster_chart_version    = "v1.0.0"
  # Decides whether or not to create the tidb-cluster helm release.
  # If this variable is set to false, you have to
  # install the helm release manually
  create_tidb_cluster_release   = true
}
```

> `cluster_name`

`kubectl` TiDB Terraform `outputs.tf`

```
output "example-cluster_tidb-hostname" {
  value = module.example-cluster.tidb_hostname
}

output "example-cluster_monitor-hostname" {
  value = module.example-cluster.monitor_hostname
}
```

`terraform init` `terraform apply`

`tidb-cluster` TiDB EC2

# 9.

Terraform Kubernetes TiDB Operator

- `clusters.tf` TiDB `create_tidb_cluster_release`

```
module "default-cluster" {
  ...
  create_tidb_cluster_release = false
}
```

`create_tidb_cluster_release` `false` Terraform TiDB TiDB Helm

> `create_tidb_cluster_release` `false` TiDB TiDB

# 10.

```
terraform destroy
```

> - EKS EKS TiDB
> - `terraform destroy` AWS EBS

# 11. Kubernetes

Kubernetes EKS TiDB

Terraform Terraform

- `tidb-operator` EKS EKS TiDB Operator
- `tidb-cluster` TiDB TiDB
- EKS TiDB `vpc` `key-pair` `bastion`

Kubernetes Kubernetes Terraform Terraform

```
mkdir -p deploy/aws-staging
vim deploy/aws-staging/main.tf
```

`deploy/aws-staging/main.tf`

```
provider "aws" {
  region = "us-west-1"
}

#  ssh key Kubernetes
module "key-pair" {
  source = "../modules/aws/key-pair"

  name = "another-eks-cluster"
  path = "${path.cwd}/credentials/"
}

#  VPC
module "vpc" {
  source = "../modules/aws/vpc"

  vpc_name = "another-eks-cluster"
}

#  VPC  EKS  tidb-operator
module "tidb-operator" {
  source = "../modules/aws/tidb-operator"
```

```
  eks_name           = "another-eks-cluster"
  config_output_path = "credentials/"
  subnets            = module.vpc.private_subnets
  vpc_id             = module.vpc.vpc_id
  ssh_key_name       = module.key-pair.key_name
}

#  helm  EKS
resource "local_file" "kubeconfig" {
  depends_on        = [module.tidb-operator.eks]
  sensitive_content = module.tidb-operator.eks.kubeconfig
  filename          = module.tidb-operator.eks.kubeconfig_filename
}
provider "helm" {
  alias    = "eks"
  insecure = true
  install_tiller = false
  kubernetes {
    config_path = local_file.kubeconfig.filename
  }
}

#  EKS  TiDB
module "tidb-cluster-a" {
  source = "../modules/aws/tidb-cluster"
  providers = {
    helm = "helm.eks"
  }

  cluster_name = "tidb-cluster-a"
  eks          = module.tidb-operator.eks
  ssh_key_name = module.key-pair.key_name
  subnets      = module.vpc.private_subnets
}

#  EKS  TiDB
module "tidb-cluster-b" {
  source = "../modules/aws/tidb-cluster"
  providers = {
    helm = "helm.eks"
  }

  cluster_name = "tidb-cluster-b"
  eks          = module.tidb-operator.eks
  ssh_key_name = module.key-pair.key_name
  subnets      = module.vpc.private_subnets
}

#
module "bastion" {
  source = "../modules/aws/bastion"

  bastion_name             = "another-eks-cluster-bastion"
  key_name                 = module.key-pair.key_name
  public_subnets           = module.vpc.public_subnets
  vpc_id                   = module.vpc.vpc_id
  target_security_group_id = module.tidb-operator.eks.worker_security_group_id
  enable_ssh_to_workers    = true
}

#  tidb-cluster-a  TiDB
output "cluster-a_tidb-dns" {
  description = "tidb service endpoints"
  value       = module.tidb-cluster-a.tidb_hostname
}

#  tidb-cluster-b
output "cluster-b_monitor-dns" {
  description = "tidb service endpoint"
  value       = module.tidb-cluster-b.monitor_hostname
}
```

```
#  IP
output "bastion_ip" {
  description = "Bastion IP address"
  value       = module.bastion.bastion_ip
}
```

`bastion` Terraform Terraform

Terraform `variables.tf`

Terraform Terraform Terraform

> - Terraform hashicorp/terraform#2430 Terraform `helm provider`
> - Terraform `source`
> - tidb-operator `modules`

Terraform `deploy/aws` Kubernetes `terraform apply` Terraform

# 1.2.3.1.2 GCP GKE TiDB

Linux macOS GCP GKE TiDB

> 

## 1.

- Git
- Google Cloud SDK
- Terraform >= 0.12
- kubectl >= 1.14
- Helm >= 2.11.0 < 3.0.0
- jq

## 2.

Google Cloud SDKAPITerraform

```
git clone --depth=1 https://github.com/pingcap/tidb-operator && \
cd tidb-operator/deploy/gcp
```

### Google Cloud SDK

Google Cloud SDK `gcloud init`

### API

GCP API

```
gcloud services enable cloudresourcemanager.googleapis.com \
cloudbilling.googleapis.com iam.googleapis.com \
compute.googleapis.com container.googleapis.com
```

### Terraform

Terraform 3 Terraform `.tfvars`

- `GCP_CREDENTIALS_PATH` GCP
  - Terraform `./create-service-account.sh`
  - `deploy/gcp` `JSON` `JSON`
- `GCP_REGION` `us-west1`
- `GCP_PROJECT` GCP

3 Terraform

(1) `GCP_REGION` GCP Region

```
```bash
echo GCP_REGION=\"us-west1\" >> terraform.tfvars
```
```

(2) `GCP_PROJECT` GCP GCP

```
```bash
echo "GCP_PROJECT=\"$(gcloud config get-value project)\"" >> terraform.tfvars
```
```

(3) Terraform

```
```bash
terraform init
```
```

(4) Terraform

```
```bash
./create-service-account.sh
```
```

Terraform `terraform.tfvars` `*.auto.tfvars` Terraform `GCP_REGION` `GCP_PROJECT` `terraform.tfvars` `GCP_CREDENTIALS_PATH` `credentials.auto.tfvars`

# 3. TiDB

TiDB

(1)

```
-  TiDB

    ```bash
    cat small.tfvars >> terraform.tfvars
    ```

-  benchmark

    ```bash
    cat prod.tfvars >> terraform.tfvars
    ```

    `prod.tfvars`  VPC f1-micro  GKE

    * 3  n1-standard-4  PD
    * 3  n1-highmem-8  TiKV
    * 3  n1-standard-16  TiDB
    * 3  n1-standard-2

     91  CPU GCP [](https://cloud.google.com/compute/quotas) CPU

> ****
>
>  Region  Region  3  `us-central1`  4  [Regions and Zones](https://cloud.google.com/compute/docs/regions-zones/) [](
#)
```

(2) TiDB

```
```bash
terraform apply
```

> ****
>
>  3  `terraform apply`  3 [ Terraform](#-terraform)

 10 `terraform apply` :

```
Apply complete! Resources: 23 added, 0 changed, 0 destroyed.

Outputs:

how_to_connect_to_default_cluster_tidb_from_bastion = mysql -h 172.31.252.20 -P 4000 -u root
how_to_ssh_to_bastion = gcloud compute ssh tidb-cluster-bastion --zone us-west1-b
how_to_set_reclaim_policy_of_pv_for_default_tidb_cluster_to_delete = kubectl --kubeconfig /.../credentials/kubeconfig
_tidb-cluster get pvc -n tidb-cluster -o jsonpath='{.items[*].spec.volumeName}'|fmt -1 | xargs -I {} kubectl --kubeco
nfig /.../credentials/kubeconfig_tidb-cluster patch pv {} -p '{"spec":{"persistentVolumeReclaimPolicy":"Delete"}}'
kubeconfig_file = ./credentials/kubeconfig_tidb-cluster
monitor_lb_ip = 35.227.134.146
monitor_port = 3000
region = us-west1
tidb_version = v3.0.1
```
```

# 4. TiDB

`terraform apply` TiDB  TiDB  `<>`

(1)  `ssh`

```
```bash
gcloud compute ssh <gke-cluster-name>-bastion --zone <zone>
```
```

(2) MySQL TiDB

```
```bash
mysql -h <tidb_ilb_ip> -P 4000 -u root
```

> ****
>
>  MySQL  TiDB  MySQL
```

# 5. GKE

`kubectl`  `helm` kubeconfig  `credentials/kubeconfig_<gke_cluster_name>` GKE

> `gke_cluster_name`  `tidb-cluster`  `variables.tf`  `gke_name`

- `--kubeconfig`

  ```
  kubectl --kubeconfig credentials/kubeconfig_<gke_cluster_name> get po -n <tidb_cluster_name>
  ```

  ```
  helm --kubeconfig credentials/kubeconfig_<gke_cluster_name> ls
  ```

- `KUBECONFIG`

```
export KUBECONFIG=$PWD/credentials/kubeconfig_<gke_cluster_name>
```

```
kubectl get po -n <tidb_cluster_name>
```

```
helm ls
```

# 6. TiDB

TiDB

(1) `terraform.tfvars` `tidb_version` (2) `terraform apply`

TiDB 4.0.0-rc.2 `tidb_version` `v4.0.0-rc.2`

```
tidb_version = "v4.0.0-rc.2"
```

```
kubectl --kubeconfig credentials/kubeconfig_<gke_cluster_name> get po -n <tidb_cluster_name> --watch
```

`tidb_version()` TiDB

```
select tidb_version();
```

```
*************************** 1. row ***************************
tidb_version(): Release Version: v3.0.0-rc.2
Git Commit Hash: 06f3f63d5a87e7f0436c0618cf524fea7172eb93
Git Branch: HEAD
UTC Build Time: 2019-05-28 12:48:52
GoVersion: go version go1.12 linux/amd64
Race Enabled: false
TiKV Min Version: 2.1.0-alpha.1-ff3dd160846b7d1aed9079c389fc188f7f5ea13e
Check Table Before Drop: false
1 row in set (0.001 sec)
```

# 7. TiDB

`tidb-cluster` GKE TiDB TiDB

(1) `tidbclusters.tf` `tidb-cluster`

```
```hcl
module "example-tidb-cluster" {
providers = {
    helm = "helm.gke"
}
source                      = "../modules/gcp/tidb-cluster"
cluster_id                  = module.tidb-operator.cluster_id
tidb_operator_id            = module.tidb-operator.tidb_operator_id
gcp_project                 = var.GCP_PROJECT
gke_cluster_location        = local.location
gke_cluster_name            = <gke-cluster-name>
cluster_name                = <example-tidb-cluster>
cluster_version             = "v3.0.1"
kubeconfig_path             = local.kubeconfig
tidb_cluster_chart_version = "v1.0.0"
pd_instance_type            = "n1-standard-1"
tikv_instance_type          = "n1-standard-4"
tidb_instance_type          = "n1-standard-2"
monitor_instance_type       = "n1-standard-1"
pd_node_count               = 1
tikv_node_count             = 2
tidb_node_count             = 1
monitor_node_count          = 1
}
```

> ****
>
> -  `cluster_name`
> -  Region

 `kubectl`  TiDB  Terraform  `outputs.tf`  `output`


```hcl
output "how_to_connect_to_example_tidb_cluster_from_bastion" {
value = module.example-tidb-cluster.how_to_connect_to_tidb_from_bastion
}
```

 TiDB
```

(2)

```
```bash
terraform init
```

```bash
terraform apply
```
```

# 8.

TiDB

(1) `terraform.tfvars` `tikv_count` `tidb_count` (2) `terraform apply`

> `tikv_count`

```
kubectl --kubeconfig credentials/kubeconfig_<gke_cluster_name> get po -n <tidb_cluster_name> --watch
```

`tidb_count` 1 2 TiDB

```
tidb_count     = 2
```

> 

# 9.

`terraform.tfvars`

## GCP

GCP `n1-standard-1` SSD

## TiDB

Terraform GKE TiDB `tidbclusters.tf` TiDB `override_values` `override_values_file` `override_values`

```
override_values = <<EOF
discovery:
  image: pingcap/tidb-operator:v1.0.1
  imagePullPolicy: IfNotPresent
  resources:
    limits:
      cpu: 250m
      memory: 150Mi
    requests:
      cpu: 30m
      memory: 30Mi
EOF
```

```
override_values_file = "./test-cluster.yaml"
```

`deploy/modules/gcp/tidb-cluster` `values/default.yaml`

GKE `values.yaml` `NodeSelector` `Tolerations` `NodeSelector` `Tolerations` Terraform TiDB

`tidbclusters.tf` `tidb-cluster` module

> 

`values.yaml` `tidb-cluster` module

```
pd:
  storageClassName: pd-ssd
tikv:
  stroageClassName: local-storage
tidb:
  service:
    type: LoadBalancer
    annotations:
      cloud.google.com/load-balancer-type: "Internal"
  separateSlowLog: true
monitor:
  storageClassName: pd-ssd
  persistent: true
  grafana:
    config:
      GF_AUTH_ANONYMOUS_ENABLED: "true"
    service:
      type: LoadBalancer
```

## TiDB Operator

TiDB Operator `operator_helm_values` `operator_helm_values_file` `operator_helm_values` `tidb-operator`

```
operator_helm_values = <<EOF
controllerManager:
  resources:
    limits:
      cpu: 250m
      memory: 150Mi
    requests:
      cpu: 30m
      memory: 30Mi
EOF
```

```
operator_helm_values_file = "./test-operator.yaml"
```

GKE Fluentd StackdriverFluentd CPU RAM Fluent Bit Fluentd Fluent Bit GKE Fluent Bit

(regional) (zonal) GKE Grafana `gcloud`

> GKE `gcloud compute instances delete` GKE

(1)

```bash
gcloud compute instance-groups managed list | grep monitor
```

```
gke-tidb-monitor-pool-08578e18-grp  us-west1-b  zone   gke-tidb-monitor-pool-08578e18  0     0            gke-tidb-mo
nitor-pool-08578e18  no
gke-tidb-monitor-pool-7e31100f-grp  us-west1-c  zone   gke-tidb-monitor-pool-7e31100f  1     1            gke-tidb-mo
nitor-pool-7e31100f  no
gke-tidb-monitor-pool-78a961e5-grp  us-west1-a  zone   gke-tidb-monitor-pool-78a961e5  1     1            gke-tidb-mo
nitor-pool-78a961e5  no
```

(2)

```bash
gcloud compute instance-groups managed list-instances <the-name-of-the-managed-instance-group> --zone <zone>
```

```bash
gcloud compute instance-groups managed list-instances gke-tidb-monitor-pool-08578e18-grp --zone us-west1-b
```

```
NAME                                        ZONE        STATUS   ACTION  INSTANCE_TEMPLATE                    VERSION
_NAME  LAST_ERROR
gke-tidb-monitor-pool-08578e18-c7vd  us-west1-b  RUNNING  NONE    gke-tidb-monitor-pool-08578e18
```

(3)

```bash
gcloud compute instance-groups managed delete-instances gke-tidb-monitor-pool-08578e18-grp --instances=gke-tidb-monit
or-pool-08578e18-c7vd --zone us-west1-b
```

# 10. TiDB

TiDB

```
terraform destroy
```

> `terraform destroy` `Error reading Container Cluster "tidb": Cluster "tidb" has status "RECONCILING" with message""` GCP Kubernetes master GCP `terraform destroy`

- Google Cloud Console `gcloud`

- `terraform destroy` Kubernetes PV (Persistent Volume) `Delete` `terraform destroy` `kubectl`

```
kubectl --kubeconfig /path/to/kubeconfig/file get pvc -n namespace-of-tidb-cluster -o jsonpath='{.items[*].spec.volumeName}'|fmt -1 | xargs -I {} kubectl --kubeconfig /path/to/kubeconfig/file patch pv {} -p '{"spec":{"persistentVolumeReclaimPolicy":"Delete"}}'
```

TiDB PVC (Persistent Volume Claim) PV `Delete` `terraform destroy` PVC

`change-pv-reclaimpolicy.sh` `deploy/gcp`

```
./change-pv-reclaimpolicy.sh /path/to/kubeconfig/file <tidb-cluster-namespace>
```

# 11. Kubernetes

Kubernetes Kubernetes TiDB

TiDB Terraform

- `tidb-operator` TiDB Kubernetes Control Plane TiDB Operator
- `tidb-cluster` Kubernetes TiDB
- `vpc` `bastion` `project-credentials` GKE TiDB

Kubernetes

(1) Kubernetes (2) Terraform

Terraform Kubernetes

```
mkdir -p deploy/gcp-staging && \
vim deploy/gcp-staging/main.tf
```

`deploy/gcp-staging/main.tf`

```
provider "google" {
  credentials = file(var.GCP_CREDENTIALS_PATH)
  region      = var.GCP_REGION
  project     = var.GCP_PROJECT
}

// required for taints on node pools
provider "google-beta" {
  credentials = file(var.GCP_CREDENTIALS_PATH)
  region      = var.GCP_REGION
  project     = var.GCP_PROJECT
}

locals {
  gke_name        = "another-gke-name"
  credential_path = "${path.cwd}/credentials"
  kubeconfig      = "${local.credential_path}/kubeconfig_${var.gke_name}"
}


module "project-credentials" {
  source = "../modules/gcp/project-credentials"

  path = local.credential_path
}

module "vpc" {
  source              = "../modules/gcp/vpc"
  create_vpc          = true
  gcp_project         = var.GCP_PROJECT
  gcp_region          = var.GCP_REGION
```

```
  vpc_name            = "${locals.gke_name}-vpc-network"
  private_subnet_name = "${locals.gke_name}-private-subnet"
  public_subnet_name  = "${locals.gke_name}-public-subnet"
}

module "tidb-operator" {
  source                = "../modules/gcp/tidb-operator"
  gke_name              = locals.gke_name
  vpc_name              = module.vpc.vpc_name
  subnetwork_name       = module.vpc.private_subnetwork_name
  gcp_project           = var.GCP_PROJECT
  gcp_region            = var.GCP_REGION
  kubeconfig_path       = local.kubeconfig
  tidb_operator_version = "v1.0.0"
}

module "bastion" {
  source             = "../modules/gcp/bastion"
  vpc_name           = module.vpc.vpc_name
  public_subnet_name = module.vpc.public_subnetwork_name
  gcp_project        = var.GCP_PROJECT
  bastion_name       = "${locals.gke_name}-tidb-bastion"
}

# HACK:  Helm  GKE
data "local_file" "kubeconfig" {
  depends_on = [module.tidb-operator.cluster_id]
  filename   = module.tidb-operator.kubeconfig_path
}
resource "local_file" "kubeconfig" {
  depends_on = [module.tidb-operator.cluster_id]
  content    = data.local_file.kubeconfig.content
  filename   = module.tidb-operator.kubeconfig_path
}

provider "helm" {
  alias          = "gke"
  insecure       = true
  install_tiller = false
  kubernetes {
    config_path = local_file.kubeconfig.filename
  }
}
module "tidb-cluster-a" {
  providers = {
    helm = "helm.gke"
  }
  source                     = "../modules/gcp/tidb-cluster"
  gcp_project                = var.GCP_PROJECT
  gke_cluster_location       = var.GCP_REGION
  gke_cluster_name           = locals.gke_name
  cluster_name               = "tidb-cluster-a"
  cluster_version            = "v3.0.1"
  kubeconfig_path            = module.tidb-operator.kubeconfig_path
  tidb_cluster_chart_version = "v1.0.0"
  pd_instance_type           = "n1-standard-1"
  tikv_instance_type         = "n1-standard-4"
  tidb_instance_type         = "n1-standard-2"
  monitor_instance_type      = "n1-standard-1"
}

module "tidb-cluster-b" {
  providers = {
    helm = "helm.gke"
  }
  source                     = "../modules/gcp/tidb-cluster"
  gcp_project                = var.GCP_PROJECT
  gke_cluster_location       = var.GCP_REGION
  gke_cluster_name           = locals.gke_name
  cluster_name               = "tidb-cluster-b"
  cluster_version            = "v3.0.1"
  kubeconfig_path            = module.tidb-operator.kubeconfig_path
```

```
  tidb_cluster_chart_version = "v1.0.0"
  pd_instance_type           = "n1-standard-1"
  tikv_instance_type         = "n1-standard-4"
  tidb_instance_type         = "n1-standard-2"
  monitor_instance_type      = "n1-standard-1"
}

output "how_to_ssh_to_bastion" {
  value= module.bastion.how_to_ssh_to_bastion
}

output "connect_to_tidb_cluster_a_from_bastion" {
  value = module.tidb-cluster-a.how_to_connect_to_default_cluster_tidb_from_bastion
}

output "connect_to_tidb_cluster_b_from_bastion" {
  value = module.tidb-cluster-b.how_to_connect_to_default_cluster_tidb_from_bastion
}
```

- `*.tf` `module`
- `variables.tf` `terraform.tfvars`

> - Terraform `source`
> - tidb-operator `modules`
> - Terraform hashicorp/terraform2430 **HACK: Helm GKE** Helm provider tf

Terraform `deploy/gcp` Kubernetes `terraform apply`

# 1.2.3.1.3 TiDB

Linux macOS TiDB

## 1.

- aliyun-cli >= 3.0.15 aliyun-cli

  > Access Key

- kubectl >= 1.12
- helm >= 2.11.0
- jq >= 1.6
- terraform 0.12.*

- AliyunECSFullAccess
- AliyunESSFullAccess
- AliyunVPCFullAccess
- AliyunSLBFullAccess
- AliyunCSFullAccess
- AliyunEIPFullAccess
- AliyunECIFullAccess
- AliyunVPNGatewayFullAccess
- AliyunNATGatewayFullAccess

## 2.

- VPC
- ECS
- ACK Kubernetes worker
  - 2 ECS 2 2 GB Kubernetes CoreDNS
  - 3 `ecs.g5.large` PD
  - 3 `ecs.i2.2xlarge` TiKV
  - 2 `ecs.c5.4xlarge` TiDB
  - 1 `ecs.c5.xlarge`
  - 100 GB

(Auto-scaling Group)

## 3.

(1) Region `terraform`

```
```shell
export TF_VAR_ALICLOUD_REGION=<YOUR_REGION> && \
export TF_VAR_ALICLOUD_ACCESS_KEY=<YOUR_ACCESS_KEY> && \
export TF_VAR_ALICLOUD_SECRET_KEY=<YOUR_SECRET_KEY>
```

 `variables.tf`  `-var`
```

(2) Terraform

```
```shell
git clone --depth=1 https://github.com/pingcap/tidb-operator && \
cd tidb-operator/deploy/aliyun
```

```shell
terraform init
```

`apply`  `yes`

```shell
terraform apply
```

 `terraform apply`  `terraform apply`

 5  10  `terraform output`

```
Apply complete! Resources: 3 added, 0 changed, 1 destroyed.

Outputs:

bastion_ip = 47.96.174.214
cluster_id = c2d9b20854a194f158ef2bc8ea946f20e
kubeconfig_file = /tidb-operator/deploy/aliyun/credentials/kubeconfig
monitor_endpoint = 121.199.195.236:3000
region = cn-hangzhou
ssh_key_file = /tidb-operator/deploy/aliyun/credentials/my-cluster-keyZ.pem
tidb_endpoint = 172.21.5.171:4000
tidb_version = v3.0.0
vpc_id = vpc-bp1v8i5rwsc7yh8dwyep5
```
```

(3) `kubectl` `helm`

```
```shell
export KUBECONFIG=$PWD/credentials/kubeconfig
```

```shell
kubectl version
```

```shell
helm ls
```
```

# 4.

TiDB

```
ssh -i credentials/<cluster_name>-key.pem root@<bastion_ip>
```

```
mysql -h <tidb_slb_ip> -P 4000 -u root
```

# 5.

`<monitor_endpoint>` Grafana

- admin
- admin

> VPN VPC `deploy/modules/aliyun/tidb-cluster/values/default.yaml` `monitor.grafana.service.annotations` `service.beta.kubernetes.io/alicloud-loadbalancer-address-type` `intranet`

# 6. TiDB

`terraform.tfvars` `tidb_version` `terraform apply`

```
kubectl get pods --namespace <tidb_cluster_name> -o wide --watch
```

# 7. TiDB

`terraform.tfvars` `tikv_count` `tidb_count` `terraform apply` TiDB

# 8.

```
terraform destroy
```

Kubernetes destroy Kubernetes

```
terraform state list
```

```
terraform state rm module.ack.alicloud_cs_managed_kubernetes.k8s
```

> 

# 9.

## TiDB Operator

`variables.tf` TiDB Operator `variable` `operator_helm_values` TiDB Operator `values.yaml`

- `terraform.tfvars` `operator_helm_values`

```
operator_helm_values = "./my-operator-values.yaml"
```

- `main.tf` `operator_helm_values`

```
operator_helm_values = file("./my-operator-values.yaml")
```

Terraform VPC VPC `variable.tf` `vpc_id` VPC vswitch Kubernetes

### TiDB

TiDB `./my-cluster.yaml` `values.yaml` TiDB Kubernetes TiDB

## 10. TiDB

Kubernetes TiDB `./main.tf` `tidb-cluster`

```
module "tidb-cluster-dev" {
  source = "../modules/aliyun/tidb-cluster"
  providers = {
    helm = helm.default
  }

  cluster_name = "dev-cluster"
  ack          = module.tidb-operator

  pd_count                   = 1
  tikv_count                 = 1
  tidb_count                 = 1
  override_values            = file("dev-cluster.yaml")
}

module "tidb-cluster-staging" {
  source = "../modules/aliyun/tidb-cluster"
  providers = {
    helm = helm.default
  }

  cluster_name = "staging-cluster"
  ack          = module.tidb-operator

  pd_count                   = 3
  tikv_count                 = 3
  tidb_count                 = 2
  override_values            = file("staging-cluster.yaml")
}
```

TiDB `cluster_name` `tidb-cluster`

| | | |
|---|---|---|
| `ack` | Kubernetes | `nil` |
| `cluster_name` | TiDB | `nil` |
| `tidb_version` | TiDB | `v3.0.1` |
| `tidb_cluster_chart_version` | `tidb-cluster` helm chart | `v1.0.1` |
| `pd_count` | PD | 3 |
| `pd_instance_type` | PD | `ecs.g5.large` |
| `tikv_count` | TiKV | 3 |
| `tikv_instance_type` | TiKV | `ecs.i2.2xlarge` |
| `tidb_count` | TiDB | 2 |
| `tidb_instance_type` | TiDB | `ecs.c5.4xlarge` |
| `monitor_instance_type` | | `ecs.c5.xlarge` |
| `override_values` | TiDB `values.yaml` `file()` | `nil` |
| `local_exec_interpreter` | | `["/bin/sh", "-c"]` |

# 11. Kubernetes

Kubernetes Terraform Terraform Module `.tf`

`deploy/aliyun` `deploy/modules` Terraform `tidb-operator`

(1)

```shell
mkdir -p deploy/aliyun-staging
```

(2) `deploy/aliyun` `main.tf`

```hcl
provider "alicloud" {
    region     = <YOUR_REGION>
    access_key = <YOUR_ACCESS_KEY>
    secret_key = <YOUR_SECRET_KEY>
}

module "tidb-operator" {
    source     = "../modules/aliyun/tidb-operator"

    region          = <YOUR_REGION>
    access_key      = <YOUR_ACCESS_KEY>
    secret_key      = <YOUR_SECRET_KEY>
    cluster_name    = "example-cluster"
    key_file        = "ssh-key.pem"
    kubeconfig_file = "kubeconfig"
}

provider "helm" {
    alias    = "default"
    insecure = true
    install_tiller = false
    kubernetes {
        config_path = module.tidb-operator.kubeconfig_filename
    }
}

module "tidb-cluster" {
    source = "../modules/aliyun/tidb-cluster"
    providers = {
        helm = helm.default
    }

    cluster_name = "example-cluster"
    ack          = module.tidb-operator
}

module "bastion" {
    source = "../modules/aliyun/bastion"

    bastion_name             = "example-bastion"
    key_name                 = module.tidb-operator.key_name
    vpc_id                   = module.tidb-operator.vpc_id
    vswitch_id               = module.tidb-operator.vswitch_ids[0]
    enable_ssh_to_worker     = true
    worker_security_group_id = module.tidb-operator.security_group_id
}
```

`module "bastion"`

`deploy/aliyun` `terraform apply` clone

# 12.

`pod cidr` `service cidr`

# 1.2.3.1.4 TiDB

## 1. Kubernetes

https://docs.jdcloud.com/cn/jcs-for-kubernetes/create-to-cluster

## 2.

https://docs.jdcloud.com/cn/jcs-for-kubernetes/connect-to-cluster

## 3. Helm

(1) https://github.com/helm/helm/releases Helm TiDB Operator Helm < 3.0

```
wget https://get.helm.sh/helm-v2.16.1-linux-amd64.tar.gz
```

(2)

```
tar -zxvf helm-v2.16.1-linux-amd64.tar.gz
```

(3)

```
mv linux-amd64/helm /usr/local/bin/helm
chmod +x /usr/local/bin/helm
```

(4)

```
helm help
```

(5) Tiller Role-based Access Control rbac-config.yaml

```
apiVersion: v1
kind: ServiceAccount
metadata:
  name: tiller
  namespace: kube-system
---
apiVersion: rbac.authorization.k8s.io/v1beta1
kind: ClusterRoleBinding
metadata:
  name: tiller
roleRef:
  apiGroup: rbac.authorization.k8s.io
  kind: ClusterRole
  name: cluster-admin
subjects:
  - kind: ServiceAccount
    name: tiller
    namespace: kube-system
```

(6) Helm Tiller

```
helm init --upgrade --service-account tiller
```

`--tiller-image`

(7)

```
helm version
```

```
Client: &version.Version{SemVer:"v2.16.1", GitCommit:"bbdfe5e7803a12bbdf97e94cd847859890cf4050", GitTreeState:"clean"}
Server: &version.Version{SemVer:"v2.16.1", GitCommit:"bbdfe5e7803a12bbdf97e94cd847859890cf4050", GitTreeState:"clean"}
```

(8) PingCAP chart

```
helm repo add pingcap https://charts.pingcap.org/
```

# 4. TiDB Operator

TiDB Operator CRD (Custom Resource Definition) Kubernetes TiDB Operator `TidbCluster` Kubernetes

```
kubectl apply -f https://raw.githubusercontent.com/pingcap/tidb-operator/master/manifests/crd.yaml && kubectl get crd tidbclusters.pingcap.com
```

`TidbCluster` Kubernetes TiDB Operator

(1) `tidb-operator` chart `values.yaml`

```
mkdir -p /home/tidb/tidb-operator && \
helm inspect values pingcap/tidb-operator --version=<chart-version> > /home/tidb/tidb-operator/values-tidb-operator.yaml
```

> `<chart-version>` chart `v1.0.0` `helm search -l tidb-operator`

(2) TiDB Operator

TiDB Operator k8s.gcr.io/kube-scheduler `/home/tidb/tidb-operator/values-tidb-operator.yaml` `scheduler.kubeSchedulerImageName`

(3) TiDB Operator

```
helm install pingcap/tidb-operator --name=tidb-operator --namespace=tidb-admin --version=<chart-version> -f /home/tidb/tidb-operator/values-tidb-operator.yaml && \
kubectl get po -n tidb-admin -l app.kubernetes.io/name=tidb-operator
```

# 5. TiDB Operator

`/home/tidb/tidb-operator/values-tidb-operator.yaml` TiDB Operator `values.yaml` `/home/tidb/tidb-operator/values-tidb-operator.yaml`

TiDB Operator

- tidb-controller-manager
- tidb-scheduler

`Deployment` `values.yaml` `limit` `request` `replicas`

`values.yaml`

```
helm upgrade tidb-operator pingcap/tidb-operator --version=<chart-version> -f /home/tidb/tidb-operator/values-tidb-operator.yaml
```

# 6. ulimit

TiDB Docker `ulimit` `1048576`

- Kubernetes Node

- Node
- `ulimit` ulimit

```
sudo vim /etc/security/limits.conf
```

root `soft` `hard` `nofile` `1048576`

- Docker `ulimit`

```
sudo vim /etc/systemd/system/docker.service
```

`LimitNOFILE` `1048576`

- Docker

```
systemctl daemon-reload
systemctl restart docker
```

> `LimitNOFILE` `1048576` `infinity` `systemd` bug `infinity` `systemd` `65536`

# 7. TiDB

## StorageClass

Kubernetes kubernetes.io/jdcloud-ebs provisioner Kubernetes Kubernetes StorageClass:

```
kubectl get storageclass
NAME                PROVISIONER                 AGE
default (default)   kubernetes.io/jdcloud-ebs   39d
jdcloud-hdd         kubernetes.io/jdcloud-ebs   39d
jdcloud-ssd         kubernetes.io/jdcloud-ebs   39d
```

StorageClass

```
kind: StorageClass
apiVersion: storage.k8s.io/v1
metadata:
  name: mystorageclass-hdd1
provisioner: kubernetes.io/jdcloud-ebs
parameters:
  zones: cn-north-1a, cn-north-1b
  fstype: ext4
reclaimPolicy: Retain
```

(1) provisioner kubernetes.io/jdcloud-ebs Provisioner

(2) reclaimPolicy storage class Persistent Volume reclaimPolicy Delete Retain storageClass reclaimPolicy Delete

(3) parameters

type ssd.gp1 ssd.io1 hdd.std1 SSD SSD HDD

| StorageClass type | | | |
|---|---|---|---|
| hdd.std1 | hdd | [20-16000]GiB | 10GiB |
| ssd.gp1 | ssd | [20-16000]GiB | 10GiB |
| ssd.io1 | ssd | [20-16000]GiB | 10GiB |

fstype xfs ext4 fstype ext4 fstype=ext4

https://docs.jdcloud.com/cn/jcs-for-kubernetes/deploy-storageclass

## Values

tidb-cluster chart `values.yaml`

```
mkdir -p /home/tidb/<release-name> && \
helm inspect values pingcap/tidb-cluster --version=<chart-version> > /home/tidb/<release-name>/values-<release-name>.yaml
```

> - `/home/tidb`
> - `release-name` Kubernetes PodService `helm ls -q` `release-name`
> - `chart-version` tidb-cluster chart `helm search -l tidb-cluster`
> - `values.yaml` `/home/tidb/<release-name>/values-<release-name>.yaml`

3 PD Pod3 TiKV Pod2 TiDB Pod 1 PodTiDB Operator Kubernetes 3 Kubernetes 3 PD Pod Pending TiKV TiDB Pod

Kubernetes 3 TiDB PD TiKV Pod 1 `values.yaml` `schedulerName` Kubernetes `default-scheduler`

> `default-scheduler` `default-scheduler` TiDB TiDB Pod StableScheduling

TiDB

# 8. TiDB

> `[20-16000]GiB` `10G` `values.yaml` `PD TiKV Monitor Drainer` PV

Kubernetes `values.yaml` `tidb.service.annotations` `service.beta.kubernetes.io/jdcloud-load-balancer-spec` TiDB Service Port listeners

```
tidb:
  service:
      type: LoadBalancer
      exposeStatus: true
      annotations:
        service.beta.kubernetes.io/jdcloud-load-balancer-spec: |
            version: "v1"                                 #  "v1"
            loadBalancerType: nlb                         #  JD LB
            internal: true                                # true  LB  IPfalse  IP IP

            listeners:                                    #  port  LB  listener , ports
              - protocol: "tcp"                           # listener , alb:Tcp,Http,Https,Tls;nlb:Tcp;dnlb:Tcp

                connectionIdleTimeSeconds: 1800           # alb/nlb
                backend:                                  #  JD LB  backend
                  connectionDrainingSeconds: 300          # nlb target  300s [0-3600] (Optional)

                  sessionStickyTimeout: 300               # nlb sessionStickiness  300s,  [1-3600] (Optional)

                  algorithm: "IpHash"                     # ,  [IpHash, RoundRobin, LeastConn] IP Hash RoundRobin  (Op
tional)nlbdnlbalb
              - protocol: "tcp"
                connectionIdleTimeSeconds: 1800
                backend:
                  connectionDrainingSeconds: 300
                  sessionStickyTimeout: 300
                  algorithm: "IpHash"
```

LoadBalance https://docs.jdcloud.com/cn/jcs-for-kubernetes/deploy-service-new

Secret

```
kubectl create secret generic <tidb-secretname> --from-literal=root=<password> --namespace=<namespace>
```

`values.yaml` tidb `passwordSecretName` `<tidb-secretname>` TiDB

`values.yaml` TiDB

```
helm install pingcap/tidb-cluster --name=<release-name> --namespace=<namespace> --version=<chart-version> -f /home/ti
db/<release-name>/values-<release-name>.yaml
```

> `namespace` `release-name`

Pod

```
kubectl get po -n <namespace> -l app.kubernetes.io/instance=<release-name>
```

Kubernetes TiDB Operator TiDB `release-name` `namespace` `namespace`

TiDB TiDB Service ClusterIP

```
$kubectl -n jddb get svc -l app.kubernetes.io/instance=jddb

NAME                        TYPE           CLUSTER-IP        EXTERNAL-IP
jddb-discovery          ClusterIP      192.168.189.43    <none>           10261/TCP                        65m
jddb-grafana            NodePort       192.168.190.132   <none>           3000:32445/TCP                   65m
jddb-monitor-reloader   NodePort       192.168.188.141   <none>           9089:30732/TCP                   65m
jddb-pd                 ClusterIP      192.168.188.210   <none>           2379/TCP                         65m
jddb-pd-peer            ClusterIP      None              <none>           2380/TCP                         65m
jddb-prometheus         NodePort       192.168.186.63    <none>           9090:30415/TCP                   65m
jddb-tidb               LoadBalancer   192.168.188.201   192.168.176.10   4000:30487/TCP,10080:32045/TCP   65m
jddb-tidb-peer          ClusterIP      None              <none>           10080/TCP                        62m
jddb-tikv-peer          ClusterIP      None              <none>           20160/TCP                        63m
```

jddb-tidb TiDB Service Pod CLUSTER-IP TiDB VPC EXTERNAL-IP TiDB

# 1.2.3.2.1

Kubernetes TiDB

## 1.

| | |
|---|---|
| Docker | Docker CE 18.09.6 |
| Kubernetes | v1.12.5+ |
| CentOS | CentOS 7.6 3.10.0-957 |

## 2.

| | |
|---|---|
| net.core.somaxconn | 32768 |
| vm.swappiness | 0 |
| net.ipv4.tcp_syncookies | 0 |
| net.ipv4.ip_forward | 1 |
| fs.file-max | 1000000 |
| fs.inotify.max_user_watches | 1048576 |
| fs.inotify.max_user_instances | 1024 |
| net.ipv4.conf.all.rp_filter | 1 |
| net.ipv4.neigh.default.gc_thresh1 | 80000 |
| net.ipv4.neigh.default.gc_thresh2 | 90000 |
| net.ipv4.neigh.default.gc_thresh3 | 100000 |

Kubernetes swap

```
swapoff -a
```

swap

```
free -m
```

swap 0 swap

swap `/etc/fstab` swap

SMP IRQ Affinity CPU CPU TiDB CPU

```
cat /proc/interrupts|grep <iface-name>|awk '{print $1,$NF}'
```

CPU

```
cat /proc/irq/<ir_num>/smp_affinity
```

CPU SMP IRQ Affinity

```
cat /proc/irq/<ir_num>/smp_affinity_list
```

CPU

CPU SMP IRQ Affinity CPU

- irqbalance centos7 :

  ```
  systemctl start irqbalance
  ```

- irqbalance CPU set_irq_affinity.sh

  RPS/RFS (RSS) irqbalance RPSRFS

# 3.

binary TiDB Intel x86-64 64 TiDB TiDB

diskmemoryCPU Kubernetes master etcd worker master worker master kubelet Kubernetes

3 Kubernetes master + 3 etcd + worker Kubernetes master

# 4. Kubernetes

- SAS 1T Docker kubelet Docker kubelet emptyDir
- Kubernetes , Prometheus SAS SAS SAS

  > RAID5 RAID5

- etcd Kubernetes master master etcd etcd SSD

# 5. TiDB

TiDB PDTiKVTiDB TiDB TiDB 3 PD + 3 TiKV + 2 TiDB

- PD PD 2C 4GB

  PD master 5 TiDB 3 master 5 PD 5 PD SSD GB bind mount SSD 5 filesystem by multiple filesystem PVs

  TiDB master PD master worker PD PD PD TiDB

  SSD master PD 7 7 TiDB 3 PD PD

- TiKV TiKV I/O TiKV NVMe 8C 32GB TiKV buffer
- TiDB TiDB CPU 8C 32 GB

# 6. TiDB

5 3 PD + 3 TiKV + 2 TiDB PD 2C 4GBTiDB 8C 32GBTiKV 8C 32GBKubernetes 7 3 master worker 4 worker

- master
  - 1 etcd (2C 4GB) + 2 PD (2 * 2C 2 * 4GB) + 3 TiKV (3 * 8C 3 * 32GB) + 1 TiDB (8C 32GB) 38C 140GB
  - SSD etcd 2 PD
  - RAID5 SAS Docker kubelet
  - NVMe TiKV
- worker
  - 3 PD (3 * 2C 3 * 4GB) + 2 TiKV (2 * 8C 2 * 32GB) + 2 TiDB (2 * 8C 2 * 32GB) 38C 140GB
  - SSD PD
  - RAID5 SAS Docker kubelet
  - NVMe TiKV

5 TiDB 7 3 master worker 4 worker

- master worker 48C 192GB2 SSD RAID5 SAS NVMe
- worker 48C 192GB1 SSD RAID5 SAS NVMe

master TiDB TiDB master worker master

# 1.2.3.2.2 Kubernetes

## 1.

TiDB PDTiKV TiDB Binlog Kubernetes PersistentVolume (PV)Kubernetes

- 

- 

  IDC

PV volume provisioner PV Pod PersistentVolumeClaim (PVC) PV PV PVC PV volume provisioner PVC PV PVC PV

> 

> PV volume provisioner

## 2. TiDB

TiKV Raft PD TiKV SSD

PD Raft IO SAS SSD AWS gp2 EBS GCP SSD

TiDB Binlog TiDB Binlog pump drainer IO AWS io1 EBS GCP SSD

TiDB Operator TiDB values.yaml `storageClassName` `local-storage`

## 3. PV

Kubernetes 1.11 PV `StorageClass`

```
kubectl patch storageclass <storage-class-name> -p '{"allowVolumeExpansion": true}'
```

PV

(1) PVC

```
 PVC  10 Gi 100 Gi

```shell
kubectl patch pvc -n <namespace> <pvc-name> -p '{"spec": {"resources": {"requests": {"storage": "100Gi"}}}}'
```
```

(2) PV

```
 `kubectl get pvc -n <namespace> <pvc-name>`  PV

```shell
kubectl get pv | grep <pvc-name>
```
```

# 4. PV

Kubernetes local-static-provisioner `local-volume-provisioner`

(1) Kubernetes

(2) `local-volume-provisioner`

```
```shell
kubectl apply -f https://raw.githubusercontent.com/pingcap/tidb-operator/master/manifests/local-dind/local-volume-pro
visioner.yaml
```

 Pod  PV

```shell
kubectl get po -n kube-system -l app=local-volume-provisioner && \
kubectl get pv | grep local-storage
```

`local-volume-provisioner`  (discovery directory)  PV GKE  375 GiB
```

Kubernetes local-static-provisioner

- Local PV  UUID
- IO
-

local-static-provisioner

TiDB Binlog SAS `StorageClass`

- bind mount `/mnt/disks` `local-storage` `StorageClass`

  > TiDB 1  1  PV TiDB  1  PV

- TiDB Binlog bind mount `/mnt/backup` `backup-storage` `StorageClass`

  > TiDB  Pump 1  1  PV Pump  1  PV drainer  1  PV Ad-hoc  1  PV  1  PV

- PD bind mount `/mnt/sharedssd` `shared-ssd-storage` `StorageClass`

  > TiDB  PD 1  1  PV PD  PV

- TiKV `/mnt/ssd` `ssd-storage` `StorageClass`

`local-volume-provisioner` yaml `StorageClass` yaml

```
apiVersion: storage.k8s.io/v1
kind: StorageClass
metadata:
  name: "local-storage"
provisioner: "kubernetes.io/no-provisioner"
volumeBindingMode: "WaitForFirstConsumer"
---
```

```
apiVersion: storage.k8s.io/v1
kind: StorageClass
metadata:
  name: "ssd-storage"
provisioner: "kubernetes.io/no-provisioner"
volumeBindingMode: "WaitForFirstConsumer"
---
apiVersion: storage.k8s.io/v1
kind: StorageClass
metadata:
  name: "shared-ssd-storage"
provisioner: "kubernetes.io/no-provisioner"
volumeBindingMode: "WaitForFirstConsumer"
---
apiVersion: storage.k8s.io/v1
kind: StorageClass
metadata:
  name: "backup-storage"
provisioner: "kubernetes.io/no-provisioner"
volumeBindingMode: "WaitForFirstConsumer"
---
apiVersion: v1
kind: ConfigMap
metadata:
  name: local-provisioner-config
  namespace: kube-system
data:
  nodeLabelsForPV: |
    - kubernetes.io/hostname
  storageClassMap: |
    shared-ssd-storage:
      hostDir: /mnt/sharedssd
      mountDir: /mnt/sharedssd
    ssd-storage:
      hostDir: /mnt/ssd
      mountDir: /mnt/ssd
    local-storage:
      hostDir: /mnt/disks
      mountDir: /mnt/disks
    backup-storage:
      hostDir: /mnt/backup
      mountDir: /mnt/backup
---

......

          volumeMounts:

            ......

            - mountPath: /mnt/ssd
              name: local-ssd
              mountPropagation: "HostToContainer"
            - mountPath: /mnt/sharedssd
              name: local-sharedssd
              mountPropagation: "HostToContainer"
            - mountPath: /mnt/disks
              name: local-disks
              mountPropagation: "HostToContainer"
            - mountPath: /mnt/backup
              name: local-backup
              mountPropagation: "HostToContainer"
      volumes:

        ......

        - name: local-ssd
          hostPath:
            path: /mnt/ssd
        - name: local-sharedssd
          hostPath:
            path: /mnt/sharedssd
```

```
        - name: local-disks
          hostPath:
            path: /mnt/disks
        - name: local-backup
          hostPath:
            path: /mnt/backup
......
```

`kubectl apply` `local-volume-provisioner`

```
kubectl apply -f https://raw.githubusercontent.com/pingcap/tidb-operator/master/manifests/local-dind/local-volume-pro
visioner.yaml
```

TiDB `StorageClass`

# 5.

PVC PV provisioner `StorageClass` (reclaim policy) `Retain` PV `Retain` `Retain` PV

- `StorageClass` provisioner `StorageClass` GKE pd `StorageClass` `Delete` `pd-standard` `Retain` TiDB `storageClassName` `pd-standard`

  ```
  apiVersion: storage.k8s.io/v1
  kind: StorageClass
  metadata:
    name: pd-standard
  parameters:
    type: pd-standard
  provisioner: kubernetes.io/gce-pd
  reclaimPolicy: Retain
  volumeBindingMode: WaitForFirstConsumer
  ```

- PV

  ```
  kubectl patch pv <pv-name> -p '{"spec":{"persistentVolumeReclaimPolicy":"Retain"}}'
  ```

> TiDB Operator PD TiKV PV `Retain`

PV `Retain` PV PV

(1) PV PVC

```shell
kubectl delete pvc <pvc-name> --namespace=<namespace>
```

(2) PV `Delete` PV

```shell
kubectl patch pv <pv-name> -p '{"spec":{"persistentVolumeReclaimPolicy":"Delete"}}'
```

PV PV

# 1.2.3.2.3 Kubernetes TiDB Operator

Kubernetes TiDB Operator

## 1.

TiDB Operator

- Kubernetes v1.12
- Helm >= v2.11.0 && < v3.0.0

> - TiDB Operator TiDB TiDB
> - Kubernetes v1.12

### Helm

helm `tiller` `RBAC` `tiller`

```
kubectl apply -f https://raw.githubusercontent.com/pingcap/tidb-operator/master/manifeststiller-rbac.yaml && \
helm init --service-account=tiller --upgrade
```

`tiller` Pod running

```
kubectl get po -n kube-system -l name=tiller
```

Kubernetes `RBAC` `tiller`

```
helm init --upgrade
```

Kubernetes Helm chartPingCAP helm chart `https://charts.pingcap.org/`

```
helm repo add pingcap https://charts.pingcap.org/
```

`helm search` PingCAP chart

```
helm search pingcap -l
```

```
NAME                    CHART VERSION   APP VERSION DESCRIPTION
pingcap/tidb-backup     v1.0.0                      A Helm chart for TiDB Backup or Restore
pingcap/tidb-cluster    v1.0.0                      A Helm chart for TiDB Cluster
pingcap/tidb-operator   v1.0.0                      tidb-operator Helm chart for Kubernetes
```

chart `helm repo update`

```
helm repo update
```

## 2. TiDB Operator

TiDB Operator CRD (Custom Resource Definition) Kubernetes TiDB Operator `TidbCluster` Kubernetes

```
kubectl apply -f https://raw.githubusercontent.com/pingcap/tidb-operator/master/manifests/crd.yaml && \
kubectl get crd tidbclusters.pingcap.com
```

`TidbCluster` Kubernetes TiDB Operator

(1) `tidb-operator` chart `values.yaml`

```
```shell
mkdir -p /home/tidb/tidb-operator && \
helm inspect values pingcap/tidb-operator --version=<chart-version> > /home/tidb/tidb-operator/values-tidb-operator.y
aml
```

> ****
>
> `<chart-version>` chart `v1.0.0` `helm search -l tidb-operator`
```

(2) TiDB Operator

```
TiDB Operator `k8s.gcr.io/kube-scheduler` `/home/tidb/tidb-operator/values-tidb-operator.yaml` `scheduler.kubeSche
dulerImageName` `registry.cn-hangzhou.aliyuncs.com/google_containers/kube-scheduler`
```

(3) TiDB Operator

```
```shell
helm install pingcap/tidb-operator --name=tidb-operator --namespace=tidb-admin --version=<chart-version> -f /home/tid
b/tidb-operator/values-tidb-operator.yaml && \
kubectl get po -n tidb-admin -l app.kubernetes.io/name=tidb-operator
```
```

# 3. TiDB Operator

`/home/tidb/tidb-operator/values-tidb-operator.yaml` TiDB Operator `values.yaml` `/home/tidb/tidb-operator/values-tidb-operator.yaml`

TiDB Operator

- tidb-controller-manager
- tidb-scheduler

`Deployment` `values.yaml` `limit` `request` `replicas`

`values.yaml`

```
helm upgrade tidb-operator pingcap/tidb-operator --version=<chart-version> -f /home/tidb/tidb-operator/values-tidb-op
erator.yaml
```

# 4. chart

PingCAP chart `wget http://charts.pingcap.org/tidb-cluster-<chart-version>.tgz` chart

chart `/home/tidb/` `v1.0.6`：

```
cd /home/tidb/ && tar -xvf tidb-operator-chart-v1.0.6.tgz
```

/home/tidb/tidb-operator/values.yaml TiDB Operator

```
helm install /home/tidb/tidb-operator --namespace=tidb-admin --name=tidb-operator -f /home/tidb/tidb-operator/values.
yaml
```

TiDB Operator

```
kubectl get pods -n tidb-admin
```

```
NAME                                       READY   STATUS    RESTARTS   AGE
tidb-controller-manager-85d8d498bf-2n8km   1/1     Running   0          19s
tidb-scheduler-7c67d6c77b-qd54r            2/2     Running   0          19s
```

TiDB Operator

#### 1.2.3.2.4 TiDB

(1) TiDB Cluster helm chart

```
# mkdir -p /root/charts/
 https://github.com/pingcap/tidb-operator/releases  tidb-cluster-chart-v1.0.6.tgz  /root/charts/
```

(2) TiDB Cluster

```
# cd /root/charts/ && tar xvf tidb-cluster-chart-v1.0.6.tgz
# helm install --namespace dba-test --name=test /root/charts/tidb-cluster -f /root/charts/tidb-cluster/values.yam
l
NAME:   test
LAST DEPLOYED: Sat Mar  7 05:27:57 2020
NAMESPACE: dba-test
STATUS: DEPLOYED
...
```

TiDB Cluster

(3) TiDB Cluster Pod

```
# kubectl get pods -n dba-test
NAME                                READY   STATUS    RESTARTS   AGE
test-discovery-854fb5b46c-hbg4q     1/1     Running   0          4m41s
test-monitor-66589f9748-q28lp       3/3     Running   0          4m41s
test-pd-0                           1/1     Running   1          4m40s
test-pd-1                           1/1     Running   0          4m40s
test-pd-2                           1/1     Running   0          4m40s
test-tidb-0                         2/2     Running   0          2m13s
test-tidb-1                         2/2     Running   0          2m13s
test-tikv-0                         1/1     Running   0          2m45s
test-tikv-1                         1/1     Running   0          2m45s
test-tikv-2                         1/1     Running   0          2m45s
```

TiDB Cluster Pod

(4) TiDB Cluster

```
# kubectl get svc -n dba-test
NAME                     TYPE        CLUSTER-IP       EXTERNAL-IP   PORT(S)                          AGE
test-discovery           ClusterIP   10.102.244.238   <none>        10261/TCP                        3m58s
test-grafana             NodePort    10.104.130.193   <none>        3000:32326/TCP                   3m58s
test-monitor-reloader    NodePort    10.106.105.144   <none>        9089:30818/TCP                   3m58s
test-pd                  ClusterIP   10.96.183.196    <none>        2379/TCP                         3m58s
test-pd-peer             ClusterIP   None             <none>        2380/TCP                         3m58s
test-prometheus          NodePort    10.107.17.45     <none>        9090:31800/TCP                   3m58s
test-tidb                NodePort    10.104.37.71     <none>        4000:30169/TCP,10080:30286/TCP   3m58s
test-tidb-peer           ClusterIP   None             <none>        10080/TCP                        90s
test-tikv-peer           ClusterIP   None             <none>        20160/TCP                        2m2s
```

test-tidb Service CLUSTER-IP TiDB Cluster

```
# mysql -h 10.104.37.71 -uroot -P4000
Welcome to the MySQL monitor.  Commands end with ; or \g.
Your MySQL connection id is 1
Server version: 5.7.25-TiDB-v3.0.5 MySQL Community Server (Apache License 2.0)

Copyright (c) 2000, 2019, Oracle and/or its affiliates. All rights reserved.

Oracle is a registered trademark of Oracle Corporation and/or its
affiliates. Other names may be trademarks of their respective owners.

Type 'help;' or '\h' for help. Type '\c' to clear the current input statement.

mysql>
```

TiDB Cluster

# 1.2.3.2.5 TiDB Kubernetes

# 1. TiDB PD

4 kind 5 5 node

PD TiDB

```
# kubectl get pod --all-namespaces -o wide | grep worker5|grep dba-test
dba-test      test-pd-2                                    1/1     Running   0          5m18s   10.244.5.4   kind-wor
ker5         <none>           <none>
```

kind-worker5 PD `kubectl cordon` Pod

```
# kubectl cordon kind-worker5
node/kind-worker5 cordoned
```

`kubectl drain`

```
# kubectl drain kind-worker5 --ignore-daemonsets --delete-local-data
node/kind-worker5 already cordoned
WARNING: ...
pod/test-pd-2 evicted
```

kind-worker5 Pod

```
# kubectl get pods -n dba-test|grep kind-worker5
```

kind-worker5 Pod TiDB Pod

```
# kubectl get pods -n dba-test
NAME                              READY   STATUS    RESTARTS   AGE
test-discovery-854fb5b46c-c8lng   1/1     Running   0          21m
test-monitor-59468bcd58-btbpc     3/3     Running   0          10m
test-pd-0                         1/1     Running   2          21m
test-pd-1                         1/1     Running   0          21m
test-pd-2                         1/1     Running   0          4m50s
test-tidb-0                       2/2     Running   0          19m
test-tidb-1                       2/2     Running   0          19m
test-tikv-0                       1/1     Running   0          20m
test-tikv-1                       1/1     Running   0          20m
test-tikv-2                       1/1     Running   0          20m
```

Pod

1.
2.

```
# kubectl uncordon kind-worker5
```

K8s K8s

```
# kubectl delete node kind-worker5
node "kind-worker5" deleted
```

# 2. TiKV

TiKV node

4 TiKV 3

`kubectl cordon` Pod

```
# kubectl cordon kind-worker4
node/kind-worker4 cordoned
```

TiKV

```
# kubectl get pods -n dba-test -owide|grep tikv|grep kind-worker4
test-tikv-2                       1/1     Running   0          5m28s   10.244.1.7   kind-worker4   <none>           <
none>
```

TiKV `store-id`

```
# kubectl get tc test -ojson -n dba-test| jq '.status.tikv.stores | .[] | select ( .podName == "test-tikv-2" ) | .id'
"115"
```

PD

```
# nohup kubectl port-forward svc/test-pd 2379:2379 -n dba-test &
[1] 8968
```

`pd-ctl` TiKV

```
# pd-ctl -d store delete 115
Success!
```

TiKV store `state_name` `Tombstone`

```
# pd-ctl -d store 115|grep state_name
    "state_name": "Tombstone"
```

TiKV

Pod PVC

```
# kubectl get -n dba-test pod test-tikv-2 -ojson | jq '.spec.volumes | .[] | select (.name == "tikv") | .persistentVo
lumeClaim.claimName'
"tikv-test-tikv-2"
```

PVC

```
# kubectl delete pvc/tikv-test-tikv-2 -n dba-test
persistentvolumeclaim "tikv-test-tikv-2" deleted
```

TiKV

```
# kubectl delete pod/test-tikv-2 -n dba-test
pod "test-tikv-2" deleted
```

TiKV

```
# kubectl get pods -n dba-test -owide|grep tikv
test-tikv-0                       1/1     Running   0          29m   10.244.2.6   kind-worker2   <none>           <no
ne>
test-tikv-1                       1/1     Running   0          29m   10.244.4.6   kind-worker3   <none>           <no
ne>
test-tikv-2                       1/1     Running   0          34s   10.244.3.6   kind-worker    <none>           <no
ne>
test-tikv-3                       1/1     Running   0          25m   10.244.3.5   kind-worker    <none>           <no
ne>
```

test-tikv-2 kind-worker4 kind-worker

:

1.
2.

```
# kubectl uncordon kind-worker4
```

K8s K8s

```
# kubectl delete node kind-worker4
node "kind-worker4" deleted
```

# 1.2.3.2.6 TiDB

“test” TiDB

# 1. helm TiDB Cluster

```
# helm list
NAME            REVISION    UPDATED                     STATUS      CHART                   APP VERSION    NAMESPACE

test            1           Sat Mar  7 22:30:16 2020    DEPLOYED    tidb-cluster-v1.0.6                    dba-test

tidb-operator   1           Sat Mar  7 05:02:15 2020    DEPLOYED    tidb-operator-v1.0.6                   tidb-admi
n
# helm delete test --purge
release "test" deleted
```

> TiDB

# 2. PVC

```
# kubectl delete pvc -n dba-test -l app.kubernetes.io/instance=test,app.kubernetes.io/managed-by=tidb-operator
persistentvolumeclaim "pd-test-pd-0" deleted
persistentvolumeclaim "pd-test-pd-1" deleted
persistentvolumeclaim "pd-test-pd-2" deleted
persistentvolumeclaim "pd-test-pd-3" deleted
persistentvolumeclaim "tikv-test-tikv-0" deleted
persistentvolumeclaim "tikv-test-tikv-1" deleted
persistentvolumeclaim "tikv-test-tikv-2" deleted
```

> TiDB PVC

# 3. PV

```
# kubectl get pv -l app.kubernetes.io/namespace=dba-test,app.kubernetes.io/managed-by=tidb-operator,app.kubernetes.io
/instance=test -o name|xargs -I {} kubectl patch {} -p '{"spec":{"persistentVolumeReclaimPolicy":"Delete"}}'
persistentvolume/local-pv-2c956bbd patched
persistentvolume/local-pv-3a4dae53 patched
persistentvolume/local-pv-3c7e9ebb patched
persistentvolume/local-pv-5ebe9899 patched
persistentvolume/local-pv-682d37c9 patched
persistentvolume/local-pv-af00e20c patched
persistentvolume/local-pv-d4cf548e patched
```

PV

```
# kubectl get pv
NAME                CAPACITY   ACCESS MODES   RECLAIM POLICY   STATUS      CLAIM   STORAGECLASS    REASON   AGE
local-pv-2c956bbd   1468Mi     RWO            Delete           Available           local-storage            64s
local-pv-3a4dae53   1468Mi     RWO            Delete           Available           local-storage            72s
local-pv-3c7e9ebb   1468Mi     RWO            Delete           Available           local-storage            54s
local-pv-5cb252d7   1974Mi     RWO            Delete           Available           local-storage            24h
local-pv-5ebe9899   1468Mi     RWO            Delete           Available           local-storage            58s
local-pv-682d37c9   1468Mi     RWO            Delete           Available           local-storage            72s
local-pv-af00e20c   1974Mi     RWO            Delete           Available           local-storage            24h
local-pv-d4cf548e   1468Mi     RWO            Delete           Available           local-storage            58s
local-pv-eb0e3c9f   1974Mi     RWO            Delete           Available           local-storage            24h
```

PV “test” TiDB

# 1.2.4 Kubernetes TiDB

## 1.2.4.1 Kubernetes TiDB

Kubernetes TiDB TiDB service `<release-name>-tidb.<namespace>` TiDB `tidb-cluster` Helm chart `values.yaml` `tidb.service`

```
tidb:
  service:
    type: NodePort
    # externalTrafficPolicy: Cluster
    # annotations:
    # cloud.google.com/load-balancer-type: Internal
```

1. NodePort

LoadBalancer NodePort NodePort

- `externalTrafficPolicy=Cluster` TiDB TCP

  `Cluster` IP TiDB TiDB Pod TiDB Pod

  > TiDB IP IP IP IP

- `externalTrafficPolicy=Local` TiDB TCP TiDB

  `Local` tidb-scheduler `StableScheduling` tidb-scheduler TiDB TiDB

- NodePort IP/PORT

Service Node Port TiDB Service

```
kubectl -n <namespace> get svc <release-name>-tidb -ojsonpath="{.spec.ports[?(@.name=='mysql-client')].nodePort}{'\n'
}"
```

IP TiDB

- `externalTrafficPolicy` `Cluster` IP
- `externalTrafficPolicy` `Local` TiDB

```
  kubectl -n <namespace> get pods -l "app.kubernetes.io/component=tidb,app.kubernetes.io/instance=<release-name>
" -ojsonpath="{range .items[*]}{.spec.nodeName}{'\n'}{end}"
```

- LoadBalancer

LoadBalancer GCP/AWS LoadBalancer

Kubernetes Service Service Load Balancer

## 1.2.4.2 Kubernetes TiDB

Kubernetes TiDB TiDB Kubernetes TiDB Operator

1. TiDB

TiDB Prometheus Grafana TiDB TiDB Operator TiDB TiDB TiDB Namespace Prometheus Grafana

`values.yaml` `monitor.persistent` `true` `storageClass`

1.

Grafana `NodePort` Kubernetes `values.yaml` `monitor.grafana.service.type` `LoadBalancer` `helm upgrade`

Grafana `values.yaml` `monitor.grafana.create` `false`

1.

Prometheus `NodePort` Kubernetes `values.yaml` `monitor.prometheus.service.type` `LoadBalancer` `helm upgrade`

1. Kubernetes

TiDB TiDB Kubernetes TiDB Operator Kubernetes

1.

Kubernetes Kubernetes

Kubernetes Kubernetes

- CollectD
- Nagios
- Prometheus & node_exporter
- Zabbix

Prometheus Operator Kubernetes Node Exporter Prometheus Kubernetes

1. Kubernetes

Kubernetes Kubernetes

Kubernetes Kubernetes

TiDB Operator Kubernetes Kubernetes TiDB Operator

Prometheus Operator Node Exporter Prometheus

# 1.2.4.3

1. TiDB

TiDB Prometheus Prometheus Alerts

charts

Prometheus Prometheus AlertManager

AlertManager `values.yaml` `monitor.prometheus.alertmanagerURL` Prometheus AlertManager

1. Kubernetes

Prometheus Operator Kubernetes AlertManager kube-prometheus

Kubernetes

# 1.2.5 BR TiDB

TiDB AWS S3 AWS S3 “”Ad-hoc `BR` AWS

TiDB Operator v1.1 Custom Resource Definition(CRD)

## AWS

:

(1) AWS AccessKey SecretKey :

AWS `AWS_ACCESS_KEY_ID` `AWS_SECRET_ACCESS_KEY`

(2) IAM Pod : IAM Pod Pod `kube2iam`

> - `kube2iam` Kubernetes kube2iam TiDB Operator TiDB
> - `hostNetwork` `spec.tikv.hostNetwork` `false`

(3) IAM ServiceAccount :

IAM Kubeneters `serviceAccount` ServiceAccount Pod `EKS Pod Identity Webhook`

> - AWS EKS TiDB Operator TiDB

## Ad-hoc

Ad-hoc `Backup` Custom Resource (CR) TiDB Operator `Backup`

Ad-hoc Kubernetes `test1` namespace TiDB `demo1`

### Ad-hoc

#### AccessKey SecretKey

(1) backup-rbac.yaml `test1` namespace RBAC

```
kubectl apply -f backup-rbac.yaml -n test1
```

(2) `s3-secret` secret secret S3

```
kubectl create secret generic s3-secret --from-literal=access_key=xxx --from-literal=secret_key=yyy --namespace=test1
```

(3) `backup-demo1-tidb-secret` secret secret TiDB

```
kubectl create secret generic backup-demo1-tidb-secret --from-literal=password=<password> --namespace=test1
```

#### IAM Pod

(1) backup-rbac.yaml `test1` namespace RBAC

```
kubectl apply -f backup-rbac.yaml -n test1
```

(2) `backup-demo1-tidb-secret` secret secret TiDB

```
kubectl create secret generic backup-demo1-tidb-secret --from-literal=password=<password> --namespace=test1
```

(3) IAM

AWS IAM AWS IAM `Backup` AWS S3 IAM `AmazonS3FullAccess`

(4) IAM TiKV Pod

BR TiKV Pod BR Pod S3 TiKV Pod annotation IAM

```
kubectl edit tc demo1 -n test1
```

`spec.tikv.annotations` annotation `arn:aws:iam::123456789012:role/user` TiKV Pod Pod annotation

> `arn:aws:iam::123456789012:role/user` (3) IAM

## IAM ServiceAccount

(1) backup-rbac.yaml `test1` namespace RBAC

```
kubectl apply -f backup-rbac.yaml -n test2
```

(2) `backup-demo1-tidb-secret` secret secret TiDB root

```
kubectl create secret generic backup-demo1-tidb-secret --from-literal=password=<password> --namespace=test1
```

(3) IAM

AWS EKS IAM

(4) IAM

AWS IAM `AmazonS3FullAccess` `Trust relationships`

(5) IAM ServiceAccount

```
kubectl annotate sa tidb-backup-manager -n eks.amazonaws.com/role-arn=arn:aws:iam::123456789012:role/user --namespace
=test1
```

> `arn:aws:iam::123456789012:role/user` (4) IAM

(6) ServiceAccount TiKV Pod

```
kubectl edit tc demo1 -n test1
```

`spec.tikv.serviceAccount` tidb-backup-manager TiKV Pod Pod `serviceAccountName`

## BR Amazon S3

- `Backup` CR accessKey secretKey :

```
kubectl apply -f backup-aws-s3.yaml
```

`backup-aws-s3.yaml`

```
---
apiVersion: pingcap.com/v1alpha1
kind: Backup
metadata:
  name: demo1-backup-s3
  namespace: test1
spec:
  backupType: full
  br:
    cluster: demo1
    clusterNamespace: test1
    # enableTLSClient: false
    # logLevel: info
    # statusAddr: <status-addr>
    # concurrency: 4
    # rateLimit: 0
    # timeAgo: <time>
    # checksum: true
    # sendCredToTikv: true
  from:
    host: <tidb-host-ip>
    port: <tidb-port>
    user: <tidb-user>
    secretName: backup-demo1-tidb-secret
  s3:
    provider: aws
    secretName: s3-secret
    region: us-west-1
    bucket: my-bucket
    prefix: my-folder
```

- `Backup` CR IAM Pod：

```
kubectl apply -f backup-aws-s3.yaml
```

`backup-aws-s3.yaml`

```yaml
---
apiVersion: pingcap.com/v1alpha1
kind: Backup
metadata:
  name: demo1-backup-s3
  namespace: test1
  annotations:
    iam.amazonaws.com/role: arn:aws:iam::123456789012:role/user
spec:
  backupType: full
  br:
    cluster: demo1
    sendCredToTikv: false
    clusterNamespace: test1
    # enableTLSClient: false
    # logLevel: info
    # statusAddr: <status-addr>
    # concurrency: 4
    # rateLimit: 0
    # timeAgo: <time>
    # checksum: true
  from:
    host: <tidb-host-ip>
    port: <tidb-port>
    user: <tidb-user>
    secretName: backup-demo1-tidb-secret
  s3:
    provider: aws
    region: us-west-1
    bucket: my-bucket
    prefix: my-folder
```

- `Backup` CR IAM ServiceAccount :

```
kubectl apply -f backup-aws-s3.yaml
```

`backup-aws-s3.yaml`

```yaml
---
apiVersion: pingcap.com/v1alpha1
kind: Backup
metadata:
  name: demo1-backup-s3
  namespace: test1
spec:
  backupType: full
  serviceAccount: tidb-backup-manager
  br:
    cluster: demo1
    sendCredToTikv: false
    clusterNamespace: test1
    # enableTLSClient: false
    # logLevel: info
    # statusAddr: <status-addr>
    # concurrency: 4
    # rateLimit: 0
    # timeAgo: <time>
    # checksum: true
  from:
    host: <tidb-host-ip>
    port: <tidb-port>
    user: <tidb-user>
    secretName: backup-demo1-tidb-secret
  s3:
    provider: aws
    region: us-west-1
    bucket: my-bucket
    prefix: my-folder
```

Amazon S3 Amazon S3 `acl` `endpoint` `storageClass`

Amazon S3 access-control list (ACL)

- `private`
- `public-read`
- `public-read-write`
- `authenticated-read`
- `bucket-owner-read`
- `bucket-owner-full-control`

ACL `private` AWS

Amazon S3 `storageClass`

- `STANDARD`
- `REDUCED_REDUNDANCY`
- `STANDARD_IA`
- `ONEZONE_IA`
- `GLACIER`
- `DEEP_ARCHIVE`

`storageClass` `STANDARD_IA` AWS

`Backup` CR

```
kubectl get bk -n test1 -o wide
```

`Backup` CR：

- `.spec.metadata.namespace` `Backup` CR namespace
- `.spec.from.host` TiDB
- `.spec.from.port` TiDB

- `.spec.from.user` TiDB
- `.spec.from.tidbSecretName` TiDB `.spec.from.user` secret

S3 `provider`

- `alibaba` Alibaba Cloud Object Storage System (OSS) formerly Aliyun
- `digitalocean` Digital Ocean Spaces
- `dreamhost` Dreamhost DreamObjects
- `ibmcos` IBM COS S3
- `minio` Minio Object Storage
- `netease` Netease Object Storage (NOS)
- `wasabi` Wasabi Object Storage
- `other` Any other S3 compatible provider

TiDB `BackupSchedule` CR Ad-hoc

Ad-hoc

## BR Amazon S3

- `BackupSchedule` CR TiDB accessKey secretKey

```
kubectl apply -f backup-scheduler-aws-s3.yaml
```

`backup-scheduler-aws-s3.yaml`

```yaml
---
apiVersion: pingcap.com/v1alpha1
kind: BackupSchedule
metadata:
  name: demo1-backup-schedule-s3
  namespace: test1
spec:
  #maxBackups: 5
  #pause: true
  maxReservedTime: "3h"
  schedule: "*/2 * * * *"
  backupTemplate:
    backupType: full
    br:
      cluster: demo1
      clusterNamespace: test1
      # enableTLSClient: false
      # logLevel: info
      # statusAddr: <status-addr>
      # concurrency: 4
      # rateLimit: 0
      # timeAgo: <time>
      # checksum: true
      # sendCredToTikv: true
    from:
      host: <tidb-host-ip>
      port: <tidb-port>
      user: <tidb-user>
      secretName: backup-demo1-tidb-secret
    s3:
      provider: aws
      secretName: s3-secret
      region: us-west-1
      bucket: my-bucket
      prefix: my-folder
```

- `BackupSchedule` CR TiDB IAM Pod

```
kubectl apply -f backup-scheduler-aws-s3.yaml
```

`backup-scheduler-aws-s3.yaml`

```yaml
---
apiVersion: pingcap.com/v1alpha1
kind: BackupSchedule
metadata:
  name: demo1-backup-schedule-s3
  namespace: test1
  annotations:
    iam.amazonaws.com/role: arn:aws:iam::123456789012:role/user
spec:
  #maxBackups: 5
  #pause: true
  maxReservedTime: "3h"
  schedule: "*/2 * * * *"
  backupTemplate:
    backupType: full
    br:
      cluster: demo1
      sendCredToTikv: false
      clusterNamespace: test1
      # enableTLSClient: false
      # logLevel: info
      # statusAddr: <status-addr>
      # concurrency: 4
      # rateLimit: 0
      # timeAgo: <time>
      # checksum: true
    from:
      host: <tidb-host-ip>
      port: <tidb-port>
      user: <tidb-user>
      secretName: backup-demo1-tidb-secret
    s3:
      provider: aws
      region: us-west-1
      bucket: my-bucket
      prefix: my-folder
```

- `BackupSchedule` CR TiDB IAM ServiceAccount

```
kubectl apply -f backup-scheduler-aws-s3.yaml
```

`backup-scheduler-aws-s3.yaml`

```yaml
---
apiVersion: pingcap.com/v1alpha1
kind: BackupSchedule
metadata:
  name: demo1-backup-schedule-s3
  namespace: test1
spec:
  #maxBackups: 5
  #pause: true
  maxReservedTime: "3h"
  schedule: "*/2 * * * *"
  serviceAccount: tidb-backup-manager
  backupTemplate:
    backupType: full
    br:
      cluster: demo1
      sendCredToTikv: false
      clusterNamespace: test1
      # enableTLSClient: false
      # logLevel: info
      # statusAddr: <status-addr>
      # concurrency: 4
      # rateLimit: 0
      # timeAgo: <time>
      # checksum: true
    from:
      host: <tidb-host-ip>
      port: <tidb-port>
      user: <tidb-user>
      secretName: backup-demo1-tidb-secret
    s3:
      provider: aws
      region: us-west-1
      bucket: my-bucket
      prefix: my-folder
```

```
kubectl get bks -n test1 -o wide
```

```
kubectl get bk -l tidb.pingcap.com/backup-schedule=demo1-backup-schedule-s3 -n test1
```

`backupSchedule` `backupSchedule` `backupTemplate` `backupTemplate` S3 Ad-hoc S3 BR Amazon S3 `backupSchedule`

- `.spec.maxBackups` `0`
- `.spec.maxReservedTime` `24h` 24 `func ParseDuration`
- `.spec.schedule` Cron Cron
- `.spec.pause` `false` `true` Garbage Collection (GC) `true` `false`

# BR AWS

Amazon S3 TiDB

## AccessKey SecretKey

(1) backup-rbac.yaml `test2` namespace RBAC

```
kubectl apply -f backup-rbac.yaml -n test2
```

(2) `s3-secret` secret secret S3

```
kubectl create secret generic s3-secret --from-literal=access_key=xxx --from-literal=secret_key=yyy --namespace=test2
```

(3) `restore-demo2-tidb-secret` secret secret TiDB root

```
kubectl create secret generic restore-demo2-tidb-secret --from-literal=password=<password> --namespace=test2
```

## IAM Pod

(1) backup-rbac.yaml `test2` namespace RBAC

```
kubectl apply -f backup-rbac.yaml -n test2
```

(2) `restore-demo2-tidb-secret` secret secret TiDB root

```
kubectl create secret generic restore-demo2-tidb-secret --from-literal=password=<password> --namespace=test2
```

(3) IAM

AWS IAM AWS IAM `Restore` AWS S3 IAM `AmazonS3FullAccess`

(4) IAM TiKV Pod:

BR TiKV Pod BR Pod S3 TiKV Pod annotation IAM

```
kubectl edit tc demo2 -n test2
```

`spec.tikv.annotations`, annotation `arn:aws:iam::123456789012:role/user`, , TiKV Pod Pod annotation

> `arn:aws:iam::123456789012:role/user` (3) IAM

## IAM ServiceAccount

(1) backup-rbac.yaml `test2` namespace RBAC

```
kubectl apply -f backup-rbac.yaml -n test2
```

(2) `restore-demo2-tidb-secret` secret secret TiDB root :

```
kubectl create secret generic restore-demo2-tidb-secret --from-literal=password=<password> --namespace=test2
```

(3) IAM

AWS EKS IAM

(4) IAM :

AWS IAM `AmazonS3FullAccess` `Trust relationships`

(5) IAM ServiceAccount

```
kubectl annotate sa tidb-backup-manager -n eks.amazonaws.com/role-arn=arn:aws:iam::123456789012:role/user --namespace
=test2
```

(6) ServiceAccount TiKV Pod

```
kubectl edit tc demo2 -n test2
```

`spec.tikv.serviceAccount` tidb-backup-manager , TiKV Pod Pod `serviceAccountName`

> `arn:aws:iam::123456789012:role/user` (4) IAM

## TiDB

- `Restore` CR accessKey secretKey

```
kubectl apply -f resotre-aws-s3.yaml
```

`restore-aws-s3.yaml`

```
---
apiVersion: pingcap.com/v1alpha1
kind: Restore
metadata:
  name: demo2-restore-s3
  namespace: test2
spec:
  br:
    cluster: demo2
    clusterNamespace: test2
    # enableTLSClient: false
    # logLevel: info
    # statusAddr: <status-addr>
    # concurrency: 4
    # rateLimit: 0
    # timeAgo: <time>
    # checksum: true
    # sendCredToTikv: true
  to:
    host: <tidb-host-ip>
    port: <tidb-port>
    user: <tidb-user>
    secretName: restore-demo2-tidb-secret
  s3:
    provider: aws
    secretName: s3-secret
    region: us-west-1
    bucket: my-bucket
    prefix: my-folder
```

- `Restore` CR IAM Pod

```
kubectl apply -f restore-aws-s3.yaml
```

`restore-aws-s3.yaml`

```yaml
---
apiVersion: pingcap.com/v1alpha1
kind: Restore
metadata:
  name: demo2-restore-s3
  namespace: test2
  annotations:
    iam.amazonaws.com/role: arn:aws:iam::123456789012:role/user
spec:
  br:
    cluster: demo2
    sendCredToTikv: false
    clusterNamespace: test2
    # enableTLSClient: false
    # logLevel: info
    # statusAddr: <status-addr>
    # concurrency: 4
    # rateLimit: 0
    # timeAgo: <time>
    # checksum: true
  to:
    host: <tidb-host-ip>
    port: <tidb-port>
    user: <tidb-user>
    secretName: restore-demo2-tidb-secret
  s3:
    provider: aws
    region: us-west-1
    bucket: my-bucket
    prefix: my-folder
```

- `Restore` CR IAM ServiceAccount

```
kubectl apply -f restore-aws-s3.yaml
```

`restore-aws-s3.yaml`

```yaml
---
apiVersion: pingcap.com/v1alpha1
kind: Restore
metadata:
  name: demo2-restore-s3
  namespace: test2
spec:
  serviceAccount: tidb-backup-manager
  br:
    cluster: demo2
    sendCredToTikv: false
    clusterNamespace: test2
    # enableTLSClient: false
    # logLevel: info
    # statusAddr: <status-addr>
    # concurrency: 4
    # rateLimit: 0
    # timeAgo: <time>
    # checksum: true
  to:
    host: <tidb-host-ip>
    port: <tidb-port>
    user: <tidb-user>
    secretName: restore-demo2-tidb-secret
  s3:
    provider: aws
    region: us-west-1
    bucket: my-bucket
    prefix: my-folder
```

`Restore` CR

```
kubectl get rt -n test2 -o wide
```

`Restore` CR

- `.spec.metadata.namespace` `Restore` CR namespace
- `.spec.to.host` TiDB
- `.spec.to.port` TiDB
- `.spec.to.user` TiDB
- `.spec.to.tidbSecretName` TiDB `.spec.to.user` secret

# 1.2.6 Kubernetes Lightning

## 1.

Mydumper + Loader TiDB SQL TiDB —— SQL KV TiKV

TiDB Lightning

TiDB Lightning

- `tidb-lightning` “” TiDB KV `tikv-importer`
- `tikv-importer` “” TiKV `tidb-lightning` TiKV

Kubernetes tikv-importer TiDB Helm chart 1 ( `replicas=1` ) `StatefulSet` tidb-lightning Helm chart `Job`

TiDB Lightning tikv-importer tidb-lightning

## 2. tikv-importer

tikv-importer TiDB TiDB

- TiDB tikv-importer

  (1) `tidb-cluster` `values.yaml` `importer.create` `true`

  (2)

```
helm install pingcap/tidb-cluster --name=<tidb-cluster-release-name> --namespace=<namespace> -f values.yaml --version=<chart-version>
```

- TiDB tikv-importer

  (1) TiDB `values.yaml` `importer.create` `true`

  (2) TiDB

```
helm upgrade <tidb-cluster-release-name> pingcap/tidb-cluster -f values.yaml --version=<chart-version>
```

# 3. tidb-lightning

(1) TiDB Lightning

TiDB Lightning

```
helm inspect values pingcap/tidb-lightning --version=<chart-version> > tidb-lightning-values.yaml
```

tidb-lightning Helm chart

- Mydumper Kubernetes `dataSource.local.nodeName` `dataSource.local.hostPath` Mydumper

- PVC

  PVC Mydumper TiDB namespace PVC `dataSource.adhoc.pvcName` Mydumper PVC

- rclone Mydumper tarball PV rclone Google Cloud Storage (GCS)AWS S3 Ceph Object Storage

  - `values.yaml` `dataSource.local.nodeName` `dataSource.local.hostPath`
  - rclone `Secret` rclone rclone

```yaml
apiVersion: v1
kind: Secret
metadata:
  name: cloud-storage-secret
type: Opaque
stringData:
  rclone.conf: |
  [s3]
  type = s3
  provider = AWS
  env_auth = false
  access_key_id = <my-access-key>
  secret_access_key = <my-secret-key>
  region = us-east-1
  [ceph]
  type = s3
  provider = Ceph
  env_auth = false
  access_key_id = <my-access-key>
  secret_access_key = <my-secret-key>
  endpoint = <ceph-object-store-endpoint>
  region = :default-placement
  [gcs]
  type = google cloud storage
  #  Storage Object Viewer
  #  `cat <service-account-file.json> | jq -c .`
  service_account_credentials = <service-account-json-file-content>
```

`secret.yaml` `kubectl apply -f secret.yaml -n <namespace>` `Secret`

- `dataSource.remote.storageClassName` Kubernetes

(2) TiDB Lightning

```
helm install pingcap/tidb-lightning --name=<tidb-lightning-release-name> --namespace=<namespace> --set failFast=true
-f tidb-lightning-values.yaml --version=<chart-version>
```

# 4. Demo

## Mydumper

-

namespace test-cluster cluster-1cluster-2

cluster-1 Mysql

```
'select * from cloud.test_tbl;'
+----+------------+--------+------------+
| id | title      | author | date       |
+----+------------+--------+------------+
|  1 | K8s        | shonge | 2020-03-07 |
|  2 | operator   | shonge | 2020-03-07 |
|  3 | kubernetes | shonge | 2020-03-07 |
+----+------------+--------+------------+
```

- secret

```
kubectl create secret generic backup-secret --namespace=test-backup --from-literal=user=root --from-literal=password=
<root_password>
```

```
helm install pingcap/tidb-backup --version=v1.1.0-beta.2 --name backup-cluster-1 --namespace test-backup --set-string
 clusterName=cluster-1,storage.size=500Gi
```

- 

```
kubectl -n test-backup get job -l app.kubernetes.io/instance=backup-cluster-1
NAME                            COMPLETIONS   DURATION   AGE
basic-fullbackup-202003080800   1/1           3s         3m32s
```

- 

PV

```
kubectl -n test-cluster get pvc -l app.kubernetes.io/instance=backup-cluster-1

NAME                STATUS   VOLUME        CAPACITY   ACCESS MODES   STORAGECLASS    AGE
fullbackup-202003080800   Bound    local-pv-2a2853fb   77Gi       RWO   local-storage   62m

kubectl describe pv local-pv-2a2853fb

Name:              local-pv-2a2853fb
Labels:            kubernetes.io/hostname=tidb-operator-worker2
Annotations:       pv.kubernetes.io/bound-by-controller: yes
                   pv.kubernetes.io/provisioned-by: local-volume-provisioner-tidb-operator-worker2-9d6bdbba-89ff-4180
-9917-35b4dda3a3db
Finalizers:        [kubernetes.io/pv-protection]
StorageClass:      local-storage
Status:            Bound
Claim:             test-cluster/fullbackup-202003080800
Reclaim Policy:    Delete
Access Modes:      RWO
VolumeMode:        Filesystem
Capacity:          500Gi
Node Affinity:
  Required Terms:
    Term 0:        kubernetes.io/hostname in [tidb-operator-worker2]
Message:
Source:
    Type:  LocalVolume (a persistent volume backed by local storage on a node)
    Path:  /mnt/disks/20
Events:    <none>
```

kind worker node

```
docker exec -ti tidb-operator-worker2 ls /mnt/disks/20/fullbackup-202003080800

cloud-schema-create.sql                    mysql.opt_rule_blacklist-schema.sql
cloud.test_tbl-schema.sql                  mysql.role_edges-schema.sql
cloud.test_tbl.sql                         mysql.stats_buckets-schema.sql
metadata                                   mysql.stats_feedback-schema.sql
mysql-schema-create.sql                    mysql.stats_histograms-schema.sql
mysql.GLOBAL_VARIABLES-schema.sql          mysql.stats_histograms.sql
mysql.GLOBAL_VARIABLES.sql                 mysql.stats_meta-schema.sql
mysql.bind_info-schema.sql                 mysql.stats_meta.sql
mysql.columns_priv-schema.sql              mysql.stats_top_n-schema.sql
mysql.db-schema.sql                        mysql.tables_priv-schema.sql
mysql.default_roles-schema.sql             mysql.tidb-schema.sql
mysql.expr_pushdown_blacklist-schema.sql   mysql.tidb.sql
mysql.gc_delete_range-schema.sql           mysql.user-schema.sql
mysql.gc_delete_range_done-schema.sql      mysql.user.sql
mysql.global_priv-schema.sql               test-schema-create.sql
mysql.help_topic-schema.sql
```

## Lightning

- cluster-2 importer

```
helm upgrade cluster-2 --set-string importer.create=true pingcap/tidb-cluster
```

- lightning

```
helm install pingcap/tidb-lightning --version=v1.1.0-beta.2 --name restore-cluster-1 --namespace test-cluster --set-s
tring dataSource.adhoc.pvcName='fullbackup-202003080800',targetTidbCluster.name='cluster-2'
```

-

```
kubectl -n test-cluster get job -l app.kubernetes.io/name='restore-cluster-1-tidb-lightning'

NAME                                COMPLETIONS   DURATION   AGE
restore-cluster-1-tidb-lightning   1/1           3s         9m3s
```

- `cluster-2` TiDB

```
MySQL [(none)]> select * from cloud.test_tbl;
+----+------------+--------+------------+
| id | title      | author | date       |
+----+------------+--------+------------+
|  1 | K8s        | shonge | 2020-03-07 |
|  2 | operator   | shonge | 2020-03-07 |
|  3 | kubernetes | shonge | 2020-03-07 |
+----+------------+--------+------------+
3 rows in set (0.01 sec)
```

# 1.2.7 Kubernetes TiDB

Kubernetes TiDB Kubernetes Kubernetes TiDB

## 1.2.7.1 Kubernetes PD Control

PD Control PD

PD Control Kubernetes TiDB `kubectl exec` PD：

```
kubectl exec -n <namespace> -it <pd-pod-name> sh
```

`127.0.0.1:2379` PD `pd-ctl`

```
./pd-ctl config show
```

## 1.2.7.2 Kubernetes TiKV Control

TiKV Control TiKV

TiKV Control Kubernetes TiDB TiKV Control

- TiKV Control TiKV PD `kubectl port-forward` PD TiKV

  ```
  kubectl port-forward -n <namespace> svc/<cluster-name>-pd 2379:2379 &>/tmp/portforward-pd.log &
  ```

  ```
  kubectl port-forward -n <namespace> <tikv-pod-name> 20160:20160 &>/tmp/portforward-tikv.log &
  ```

  PD TiKV

  ```
  tikv-ctl --host 127.0.0.1:20160 <subcommand>
  ```

  ```
  tikv-ctl --pd 127.0.0.1:2379 compact-cluster
  ```

- TiKV TiKV TiKV TiKV `tkctl debug` TiKV Pod `tikv-ctl`

  1. 

     ```
     kubectl annotate pod <tikv-pod-name> -n <namespace> runmode=debug
     ```

  2. TiKV

     ```
     kubectl exec <tikv-pod-name> -n <namespace> -c tikv -- kill -s TERM 1
     ```

  3. debug

     ```
     tkctl debug <tikv-pod-name> -c tikv
     ```

  4. `tikv-ctl` `tikv` `/proc/1/root`

```
tikv-ctl --db /path/to/tikv/db size -r 2
```

Kubernetes TiKV debug db `/proc/1/root/var/lib/tikv/db size -r 2`

## 1.2.7.3 Kubernetes TiDB Control

TiDB Control TiDB

TiDB Control TiDB PD `kubectl port-forward` TiDB PD

```
kubectl port-forward -n <namespace> svc/<cluster-name>-pd 2379:2379 &>/tmp/portforward-pd.log &
```

```
kubectl port-forward -n <namespace> <tidb-pod-name> 10080:10080 &>/tmp/portforward-tidb.log &
```

`tidb-ctl`

```
tidb-ctl schema in mysql
```

## 1.2.7.4 Helm

Helm Kubernetes 2.9.0 ≤ Helm < 3.0.0 Helm

1. Helm

   ```
   curl https://raw.githubusercontent.com/kubernetes/helm/release-2.16/scripts/get | bash
   ```

   macOS Homebrew Helm

   ```
   brew install helm@2
   brew link --force helm@2
   ```

2. Helm

   helm `tiller` `RBAC` `tiller`

   ```
   kubectl apply -f https://raw.githubusercontent.com/pingcap/tidb-operator/master/manifests/tiller-rbac.yaml && \
   helm init --service-account=tiller --upgrade
   ```

   `tiller` Pod running

   ```
   kubectl get po -n kube-system -l name=tiller
   ```

   Kubernetes `RBAC` `tiller`

   ```
   helm init --upgrade
   ```

Kubernetes helm chartPingCAP Kubernetes TiDB Helm chart

- `tidb-operator` TiDB Operator
- `tidb-cluster` TiDB
- `tidb-backup` TiDB

chart PingCAP helm chart `https://charts.pingcap.org/`

```
helm repo add pingcap https://charts.pingcap.org/
```

`helm search` PingCAP chart

```
helm search pingcap -l
```

```
NAME                    CHART VERSION   APP VERSION DESCRIPTION
pingcap/tidb-backup     v1.0.0                      A Helm chart for TiDB Backup or Restore
pingcap/tidb-cluster    v1.0.0                      A Helm chart for TiDB Cluster
pingcap/tidb-operator   v1.0.0                      tidb-operator Helm chart for Kubernetes
```

chart `helm repo update`

```
helm repo update
```

Helm chart YAML Helm chart YAML `values.yaml`

Helm `helm install` `helm upgrade` `helm del` `helm ls` chart `chart-name` `release-name` `values.yaml` chart chart `--version` `chart-version` ( GA

- 

  ```
  helm install <chart-name> --name=<release-name> --namespace=<namespace> --version=<chart-version> -f <values-file>
  ```

- `chart-version` chart `values.yaml`

  ```
  helm upgrade <release-name> <chart-name> --version=<chart-version> -f <values-file>
  ```

helm

```
helm del --purge <release-name>
```

`helm ls`

```
helm ls
```

Helm3 GA Helm3 helm Helm

## 1.2.7.5 Terraform

Terraform Infrastructure as CodeKubernetes TiDB Terraform TiDB

Terraform Terraform

# 1.2.8 TiDB Operator

TiDB Operator TiDB Operator TiDB Operator `values.yaml` `helm upgrade`

```
helm upgrade tidb-operator pingcap/tidb-operator --version=<chart-version> -f /home/tidb/tidb-operator/values-tidb-operator.yaml
```

tidb-operator `values.yaml` `operatorImage` `tidb-operator` chart `values.yaml` `values.yaml` `values.yaml`

TiDB Operator TiDB TiDB TiDB Operator TiDB TiDB

TiDB Operator

## 1.2.8.1 Kubernetes

Kubernetes `kubeSchedulerImageTag` Helm `helm upgrade`

# 1.3.1 TiOps

TiOps Ansible TiOps

## 1.3.1.1

TiOps SSH PD join PD

`tidb-test` TiKV PD

1. `scale.yaml` TiKV PD IP

```
---

pd_servers:
  - ip: 10.9.20.15

tikv_servers:
  - ip: 10.9.20.15
```

1. TiOps `scale.yaml`

```
$ tiops scale-out -c tidb-test -T scale.yaml
```

```
-c | --cluster-name
-T | --topology
--local-pkg
-f | --forks 5
--enable-check-cpu  CPU vcores disable
--enable-check-mem  Memory Size disable
--enable-check-disk  Disk Available Space  disable
--enable-check-iops  TiKV  IOPS  latency disable
--enable-check-all  CPUMemoryDiskIOPS disable
```

`tiops display -c tidb-test --status`

## 1.3.1.2

TiKV Binlog API TiKV Binglog

- TiKV Binlog
  - TiOps API
  - TiKV Binlog
    - 
    - 
    - 
- 
  - PD API `delete` PD
  - 
- ID `display` ID ID `d294683d` PD

```
$ tiops display -c tidb-test
TiDB cluster tidb-test, version 4.0.0-beta.1
Node list:
ID        Role        Host          Ports        Data Dir                                        Deploy Dir
e5f0e2d2  Monitoring  10.9.26.126   9090/9091    /home/tidb/data/tidb-test/monitoring-e5f0e2d2  /home/tidb/deploy/tid
b-test/monitoring-e5f0e2d2
f8cd24a7  PD          10.9.26.126   2379/2380    /home/tidb/data/tidb-test/pd-f8cd24a7          /home/tidb/deploy/tid
b-test/pd-f8cd24a7
g993a624  PD          10.9.170.207  2379/2380    /home/tidb/data/tidb-test/pd-g993a624          /home/tidb/deploy/tid
b-test/pd-g993a624
d294683d  PD          10.9.20.15    2379/2380    /home/tidb/data/tidb-test/pd-d294683d          /home/tidb/deploy/tid
b-test/pd-d294683d
a8e4c35a  TiDB        10.9.26.126   4000/10080   -                                              /home/tidb/deploy/tid
b-test/tidb-a8e4c35a
abb1e0ca  TiDB        10.9.170.207  4000/10080   -                                              /home/tidb/deploy/tid
b-test/tidb-abb1e0ca
db591398  Monitored   10.9.165.44   9100/9115    -                                              /home/tidb/deploy/tid
b-test/monitored-db591398
d444b608  Monitored   10.9.170.207  9100/9115    -                                              /home/tidb/deploy/tid
b-test/monitored-d444b608
hcbc7435  Monitored   10.9.26.126   9100/9115    -                                              /home/tidb/deploy/tid
b-test/monitored-hcbc7435
de205f0f  TiKV        10.9.26.126   20160/20180  /home/tidb/data/tidb-test/tikv-de205f0f        /home/tidb/deploy/tid
b-test/tikv-de205f0f
jd4610dc  TiKV        10.9.170.207  20160/20180  /home/tidb/data/tidb-test/tikv-jd4610dc        /home/tidb/deploy/tid
b-test/tikv-jd4610dc
bcb3e186  TiKV        10.9.165.44   20160/20180  /home/tidb/data/tidb-test/tikv-bcb3e186        /home/tidb/deploy/tid
b-test/tikv-bcb3e186
h592456d  TiKV        10.9.20.15    20160/20180  /home/tidb/data/tidb-test/tikv-h592456d        /home/tidb/deploy/tid
b-test/tikv-h592456d
h5f8ca0d  Grafana     10.9.26.126   3001         -                                              /home/tidb/deploy/tid
b-test/grafana-h5f8ca0d
```

1.

```
$ tiops scale-in -c tidb-test -n d294683d
```

```
-c | --cluster-name
-n | --node-id  ID
-f | --forks 5
```

`tiops display -c tidb-test --status`

# 1.3.2 TiDB Operator

TiDB Operator TiDB

## 1.

- TiDB Operator TiDB
- release `test` `dba-test` chart `/home/charts/tidb-cluster` TiDB
  - 3 PD
  - 2 TiDB
  - 3 TiKV

## 2.

TiDB TiDB `replicas` PDTiKVTiDB

(1) `value.yaml` `pd.replicas` `tidb.replicas` `tikv.replicas` 334

(2) `helm upgrade`

```shell
# helm upgrade test /home/charts/tidb-cluster -f /home/charts/tidb-cluster/values.yaml
Release "test" has been upgraded. Happy Helming!
LAST DEPLOYED: Sun Mar  8 15:39:57 2020
NAMESPACE: dba-test
STATUS: DEPLOYED
```

(3)

```shell
# watch kubectl get po -n dba-test
```

 Pod 3 PD 3 TiDB 4 TiKV `Running`

```shell
NAME                              READY   STATUS    RESTARTS   AGE
test-discovery-668b48577c-zw4jh   1/1     Running   0          116m
test-monitor-86797cd996-9ggfh     3/3     Running   0          116m
test-pd-0                         1/1     Running   0          116m
test-pd-1                         1/1     Running   0          116m
test-pd-2                         1/1     Running   1          116m
test-tidb-0                       2/2     Running   0          112m
test-tidb-1                       2/2     Running   0          112m
test-tidb-2                       2/2     Running   0          2m52s
test-tikv-0                       1/1     Running   0          114m
test-tikv-1                       1/1     Running   0          114m
test-tikv-2                       1/1     Running   0          114m
test-tikv-3                       1/1     Running   0          2m52s
```

> - PDTiKV
> - TiKV PD TiKV Region TiKV TiKV Pod `Running` Pod TiKV `kubectl get tidbcluster -n <namespace> <release-name> -o json | jq '.status.tikv.stores'` TiKV `Offline`
> - PDTiKV PVC PV `Reclaim Policy` `Retain` PVC
> - TiKV TiKV Store Tombstone

# 3.

(1) `values.yaml` `tidb.resources tikv.resources pd.resources`

(2) `helm upgrade`

```
```shell
# helm upgrade test /home/charts/tidb-cluster -f /home/charts/tidb-cluster/values.yaml
Release "test" has been upgraded. Happy Helming!
LAST DEPLOYED: Sun Mar  8 15:57:03 2020
NAMESPACE: dba-test
STATUS: DEPLOYED
```
```

(3)

```
```shell
# watch kubectl -n <namespace> get pod -o wide
```

 Pod `Running`
```

> - `requests` PDTiKV `Local PV` Pod `Pending`
> - TiDB TiDB

# 1.4.1 TiOps

TiDB

## 1.4.1.1

- PD
  - Leader
  - Leader Leader
    - PD Leader
    - Leader Leader
  -
- TiKV
  - PD TiKV region leader Leader
  - Leader TiKV
  - TiKV Leader
-
  -

## 1.4.1.2

4.0.0-beta.1

```
$ tiops upgrade -c tidb-test -t 4.0.0-beta.1
```

```
-c | --cluster-name
-t | --tidb-version
--enable-check-configdisable
--local-pkg
-f | --forks 5
-r | --role role  TiDB "pd", "tikv", "pump", "tidb",  "drainer", "monitoring", "monitored", "grafana", "alertmanager"

-n | --node-id  ID
--force
```

# 1.4.2 TiDB-Operator

TiDB PDTiKVTiDB Pod Pod Pod Pod

PDTiKV Leader PD * 3TiKV * 3TiDB * 2 TiKVPD

TiDB DDL Owner TiDB TiDB TiDB

TiDB

## 1.4.2.1 TiDB

1. `values.yaml` `tidb.image` `tikv.image` `pd.image`
2. `helm upgrade`

```
helm upgrade <release-name> pingcap/tidb-cluster -f values.yaml --version=<chart-version>
```

3.

```
watch kubectl -n <namespace> get pod -o wide
```

Pod `Running`

## 1.4.2.2 TiDB

TiDB

1. `values.yaml` `enableConfigMapRollout` `true`
2. `values.yaml`
3. `helm upgrade`

```
helm upgrade <release-name> pingcap/tidb-cluster -f values.yaml --version=<chart-version>
```

4.

```
watch kubectl -n <namespace> get pod -o wide
```

Pod `Running`

> - `enableConfigMapRollout` PDTiKVTiDB

## 1.4.2.3 TiDB

PD PD PD tag NodeAffinity TiDB TiDB TiDB

`force-upgrade` TiDB Operator > v1.0.0-beta.3

1. `annotation`

```
kubectl annotate --overwrite tc <release-name> -n <namespace> tidb.pingcap.com/force-upgrade=true
```

1. `helm upgrade`

```
helm upgrade <release-name> pingcap/tidb-cluster -f values.yaml --version=<chart-version>
```

# 1.5

## 1.5.1

TiDB v4.0

- 
- 

## 1.5.2

TiDB v4.0 pd-ctl component TiDBTiKVPD

(1)

4.0 TiDBTiKVPD `enable-dynamic-config = false`

(2)

```
/ # ./pd-ctl component --help
manipulate components' configs

Usage:
  pd-ctl component [command]

Available Commands:
  delete      delete component config with a given component ID (e.g. 127.0.0.1:20160)
  ids         get all component IDs with a given component (e.g. tikv)
  set         set the component config (set option with value)
  show        show component config with a given component ID (e.g. 127.0.0.1:20160)

Global Flags:
  -h, --help        Help message.
  -u, --pd string   Address of pd. (default "http://127.0.0.1:2379")
```

(3)

`component set <component> <key> <value>` `component` `tidb` `tikv` `pd` `key` `value`

```
>> component set tikv gc.batch-keys 1024
```

TiKV GC `batch-keys` 1024

(4)

`component set <address> <key> <value>` `address` IP 127.0.0.1:20160

```
>> component set 127.0.0.1:20160 gc.batch-keys 1024
```

`127.0.0.1:20160` TiKV GC `batch-keys` 1024

(5)

`component show <address>`

```
>> component show 127.0.0.1:20160
```

# 1.5.3

(1) **tidbcluster**

```
apiVersion: pingcap.com/v1alpha1
kind: TidbCluster
metadata:
  name: basic
spec:
  version: nightly
  timezone: UTC
  pvReclaimPolicy: Delete
  pd:
    baseImage: pingcap/pd
    replicas: 1
    requests:
      storage: "1Gi"
    config: {}
  tikv:
    baseImage: pingcap/tikv
    replicas: 3
    requests:
      storage: "1Gi"
    config: {}
  tidb:
    baseImage: pingcap/tidb
    replicas: 1
    service:
      type: NodePort
    config: {}
```

(2) **PD Pod**

- 

```
/ # ./pd-ctl component show basic-tikv-0.basic-tikv-peer.test-cluster.svc:20160 | grep batch-keys
  batch-keys = 512
```

- 

```
/ # ./pd-ctl component set tikv gc.batch-keys 1024
Success!
```

`Success!` 30s

- 

```
/ # ./pd-ctl component show basic-tikv-0.basic-tikv-peer.test-cluster.svc:20160 | grep batch-keys
  batch-keys = 512
```

pd-ctl

# 2 TiDB

TiDB Raft TiDB

TiDB

- **CDC** TiDB/TiKV TiDB TiDB
- **TiDB Lightning** Mydumper CSV TiDB
- **BR** TiDB TiKV SST SST TiKV
- **Dumpling** Mydumper Golang TiDB TiDB SQL CSV S3

TiDB

# 2.1 4.0  CDC

TiDB 4.0  Change Data CaptureCDC TiDB/TiKV  TiDB CDC  TiDB  TiDB  TiDB

CDC

- CDC  TiDB Binlog CDC
- CDC
- CDC  TiDB

CDC

# 2.1.1 CDC

TiCDC TiDB-Tools TiDB-Binlog TiDB-Binlog TiDB binlogTiCDC TiKV `KV Change Logs`

TiCDC

- TiCDC
- TiCDC SQL

TiCDC

- TiCDC TiDB TiDB-Binlog TiCDCPump Drainer TiDB
- TiDB-Binlog Commit Binlog TiKV 10 TiCDC
- TiDB-Binlog TiDB Transaction Big Transaction PD Commit Timestamp

TiCDC

- TiCDC watch KV
- TiCDC PD etcd
- TiDB-Binlog

# 2.1.2 CDC

**TiCDCTi**DB **C**hange **D**ata **C**apture TiDB/TiKV  TiDB  TiDB  TiDB BinlogTiCDC  TiDB

TiCDC

- **TiKV** KV KV Change LogsKV TiKV  row changed eventsTiKV  KV  TiCDC
- **Capture**TiCDC  TiCDC  capture  KV TiCDC  capture owner  processor
  - TiCDC  owner owner  capture  owner
  - processor  capture  capture  processor processor processor  capture  TiCDC  capture
  - capture  PD  etcd  capture owner  processor
  - “” change feed TiDB  TSO  KV TiCDC  task capture
- **Sink**TiCDC TiCDC
  - TiDB  MySQL  `NOT NULL`
  - TiCDC open protocol Kafka Kafka
  -

# 2.1.3 CDC

TiCDC TiDB

## 1.

- TiDB PD `10.1.1.10:2379`
- TiDB SQL `10.3.1.30:4000`
- TiCDC 3 capture
  - `10.2.1.20:8300`
  - `10.2.1.21:8300`
  - `10.2.1.22:8300`

## 2.

(1)

- CentOS 7.3 Linux x86_64 (amd64
- TiCDC Go >= 1.13
-

(2)

Github `make` `bin`

(3)

TiCDC

```
$ cdc server --pd=http://10.1.1.10:2379 --status-addr=127.0.0.1:8300
```

- `pd` : TiDB PD
- `status-addr` : capture

TiCDC TiKV

capture

```
$ cdc cli capture list --pd=http://10.1.1.10:2379
[
        {
                "id": "5d1fd3bd-efc9-4cdf-9e8a-6d955f65b3b0",
                "is-owner": true
        },
        {
                "id": "629ec61e-16a3-466c-8fd4-2b2b457dabf7",
                "is-owner": false
        },
        {
                "id": "c5cd08b4-f601-456f-995c-62c97044444b",
                "is-owner": false
        }
]
```

capture owner processor

## 3.

```
$ cdc cli changefeed create --pd=http://10.1.1.10:2379 --sink-uri="mysql://user:password@10.3.1.30:4000/" --config=~/
cdc-config.toml --start-ts=0
```

- `pd` TiDB PD
- `sink-url` TiDB DSN
- `config` TSO
- `start-ts` TSO 0 TSO

```
ignore-txn-commit-ts = []
filter-case-sensitive = false

[filter-rules]
ignore-dbs = ["test", "mysql""information_schema", ]

[[filter-rules.do-tables]]
db-name = "sns"
tbl-name = "user"

[[filter-rules.do-tables]]
db-name = "sns"
tbl-name = "following"
```

`test` `mysql` `information_schema` `sns.user` `sns.following`

## 4.

```
$ cdc cli changefeed list --pd=http://10.1.1.10:2379
[
        {
                "id": "004a0ea8-2ef1-45b4-8ce1-b3281e7dc24d"
        }
]
```

ID

```
$ cdc cli changefeed query --pd=http://10.1.1.10:2379 --changefeed-id=004a0ea8-2ef1-45b4-8ce1-b3281e7dc24d
{
        "info": {
                "sink-uri": "mysql://root:123456@127.0.0.1:3306/",
                "opts": {},
                "create-time": "2020-03-13T16:17:33.965778+08:00",
                "start-ts": 415259021527482369,
                "target-ts": 0,
                "admin-job-type": 0,
                "config": {
                        "filter-case-sensitive": false,
                        "filter-rules": null,
                        "ignore-txn-commit-ts": null
                }
        },
        "status": {
                "resolved-ts": 415259037347348481,
                "checkpoint-ts": 415259036823060481,
                "admin-job-type": 0
        }
}
```

```
$ cdc cli processor query --pd=http://10.1.1.10:2379 --changefeed-id=004a0ea8-2ef1-45b4-8ce1-b3281e7dc24d --capture-i
d=5d1fd3bd-efc9-4cdf-9e8a-6d955f65b3b0
{
        "status": {
                "table-infos": [
                        {
                                "id": 45,
                                "start-ts": 415259021527482369
                        }
                ],
                "table-p-lock": null,
                "table-c-lock": null,
                "admin-job-type": 0
        },
        "position": {
                "checkpoint-ts": 415259059393658881,
                "resolved-ts": 415259059917946881
        }
}
```

# 5. HTTP

TiCDC HTTP

capture

```
$ curl http://10.2.1.20:8300/status
{
 "version": "0.0.1",
 "git_hash": "",
 "id": "4a54c85b-fc1d-4897-9934-1be3b9aa6a45",
 "pid": 31652
}
```

`id` TiCDC capture ID `pid` ID

owner TiCDC owner owner

```
$ curl -X POST http://10.2.1.20:8300/capture/owner/resign
```

owner processor

```
$ curl -X POST -d "admin-job=X&cf-id=136a3bee-621c-42d5-80ec-4c1aaf6ddb53" http://10.2.1.20:8300/capture/owner/admin
```

`admin-job`

- `admin-job=1` processor
- `admin-job=2`
- `admin-job=3` processor

owner

owner processors etcd

```
$ curl http://10.2.1.20:8300/debug/info
```

# 2.2 TiDB  Lightning

TiDB Lightning  TiDB  SQL  3  300 GBLightning Lightning  Mydumper  CSV

# 2.2.1 TiDB Lightning

## 1.

TiDB Lightning

- **TiDB Lightning**“” TiDB  tikv-importer
- **tikv-importer**“” TiKV  TiDB Lightning  TiKV

1. TiDB Lightning TiKV “”import mode
2. TiDB Lightning
3. 200 GB+
4. TiDB Lightning gRPC tikv-importer “engine file”TiDB Lightning SQL dump TiDB tikv-importer
5. tikv-importer TiKV TiKV
6. TiDB Lightning checksum TiDB ANALYZETiDB Lightning AUTO_INCREMENT ID ID
   TiDB ID
7. TiDB Lightning TiKV “”normal mode TiDB

Lightning “”

- TiKV SST
- write stall triggers

Lightning “”

# 2. Lightning

Lightning SQL CREATE TABLE INSERT TiDB

Lightning INSERT

```
INSERT INTO `tbl` VALUES (1, 2, 3), (4, 5, 6), (7, 8, 9);
INSERT INTO `tbl` VALUES (10, 11, 12), (13, 14, 15), (16, 17, 18);
INSERT INTO `tbl` VALUES (19, 20, 21), (22, 23, 24), (25, 26, 27);
```

Lightning Lightning TiDB SQL “”KV encoder TiDB KV Lightning INSERT Lightning Importer

Lightning

- `batch-size` 5 TB+ Importer Lightning `batch-size` `batch-size` 100 GiB `batch-size` region balance leader balance region TiKV
- `table-concurrency` `batch-size`
- `index-concurrency` `table-concurrency` + `index-concurrency` Importer `max-open-engines`
- `io-concurrency` IO cache miss IO
- `block-size` Lightning block-size 64 KiB
- `region-concurrency` → → Importer

I/O `io-concurrency`

CPU `region-conconcurrency` 50 ms 20 `block-size` 64 KiB 1.28 MB `region-concurrency = 60` 75 MB/s

# 3. Importer

Importer Importer

RocksDB RocksDBRocksDB SST

SST TiKV Regions 96 MiBImporter Region PD Region TiKV

Importer SST Region Leader Ingest SST Raft group Region

- `max-open-engines` Lightning Importer Lightning Lightning `index-concurrency` + `table-concurreny` Lightning `index-concurrency` + `table-concurreny` Lightning `batch-size` 7 Importer
- `num-import-jobs`：Lightning `batch-size` Import TiKV
- `region-split-size`：100 GiB TiKV SST SST 96 MiBSST Ingest

# 4.

```
mysql> admin checksum table `datetime`;
+---------+------------+---------------------+-----------+-------------+
| Db_name | Table_name | Checksum_crc64_xor  | Total_kvs | Total_bytes |
+---------+------------+---------------------+-----------+-------------+
| vt      | datetime   | 4772761481773448246 |       210 |        8336 |
+---------+------------+---------------------+-----------+-------------+
1 row in set (0.13 sec)
```

Lightning Region Importer Checksum TiKV Checksum

Checksum Hash TiKV Checksum Lightning Checksum Checksum SST SHA-256

CRC64 XOR 64 Checksum 3

- Lightning encode
- TiDBSQL
  - ADMIN CHECKSUM TABLE `xxxx`;

# 5.

Lightning

```
ANALYZE TABLE `xxxx`;
ALTER TABLE `xxxx` AUTO_INCREMENT=123456;
```

# 6.

Lightning

- 
- 

Lightning Lightning Lightning

# 7.

- Lightning Importer Importer TiKV ~300 MB/s ~30 MB/s
- Lightning
- Importer 20 5 TB Importer TiKV Importer 5 4 TB ~2 TB
- TiKV ( × 4) 5 TB SQL 20 TB TiKV Lightning

# 8.

- `io-concurrency` cache miss
- Lightning → Importer
  - 10 Gb/s 300 MB/s Importer Lightning

    ```
    max speed = bandwidth (1.2 GB/s) / replicas (3)
    ```

  - Lightning Importer

    ```
    ram usage = (max-open-engines (8) × write-buffer-size (1 GB) × 2)
              + (num-import-jobs (24) × region-split-size (512 MB) × 2)
    ```

  - Importer ≈ N , `N = max(index-concurrency, table-concurrency)`

# 2.2.2 Lightning

Lightning

## 2.2.2.1 TiDB Lightning

- TiDB Lightning TiDB
- `tidb-lightning` “”“” CPU `tidb-lightning-ctl` “”

```
.../tidb-ansible/resouce/bin/tidb-lightning-ctl -switch-mode=normal
```

TiDB Lightning TiDB

| | SELECT | INSERT | UPDATE | DELETE | CREATE | DROP | ALTER |
|---|---|---|---|---|---|---|---|
| | Tables | Tables | Tables | Tables | Databases, tables | Databases, tables | Tables |

`checksum = true` TiDB Lightning TiDB admin

`tidb-lightning` `tikv-importer`

`tidb-lightning`

- 32+ CPU
- SSD
- 300 MB/s
- CPU `tidb-server` `region-concurrency` `tidb-lightning` CPU

`tikv-importer`

- 32+ CPU
- 40 GB+
- 1 TB+ SSD IOPS ≥8000
- N N = max(index-concurrency, table-concurrency)
- 300 MB/s
- CPUI/O

`tidb-lightning` + `tikv-importer`

# TiDB-Ansible TiDB Lightning

TiDB-Ansible sudo

(1) inventory.ini IP tidb-lightning tikv-importer

```
...
[importer_server]
# import_dir
IS1 ansible_host=172.16.4.1 deploy_dir=/data/deploy tikv_importer_port=8287 import_dir=/data/import
[lightning_server]
# data_source_dir
LS1 ansible_host=172.16.4.2 deploy_dir=/data/deploy tidb_lightning_pprof_port=8289 data_source_dir=/data/wanted
...
```

(2) data_source_dir mydumper sql csv csv conf/tidb-lightning.yml

```
...
[mydumper]
no-schema: true
[mydumper.csv]
#  ASCII
separator = ','
#  ASCII
delimiter = '"'
# CSV
#  true
header = true
# CSV  NULL
#  trueCSV  NULL
not-null = false
#  `not-null`  false CSV  NULL
#  NULL
null = '\N'
#
backslash-escape = true
#
trim-last-separator = false
...
```

(3) Lightning Importer

```
$ ansible-playbook bootsrap.yml -l IS1LS
```

(4) Lightning Importer

```
$ ansible-playbook deploy.yml -l IS1LS

$ ansible-playbook deploy.yml --tags=lightning
```

(5) Importer Lightning

Importer Lightning

1. Importer Lightning
2. 
3. Importer *scripts/start_importer.sh* Importer
4. Lightning *scripts/start_lightning.sh*

(6)

- grafana
- 

lightning ["the whole procedure completed"] ["tidb lightning exit"]

(7) Importer

Importer *scripts/stop_importer.sh*

# 2.2.2.2 TiDB Lightning

TiDB Lightning bin tikv-importer.tomltidb-lightning.tomlTiDB Lightning ansible

# 2.2.2.3 TiDB Lightning TiDB-Backend

## Importer-backend TiDB-backend

TiDB Lightning tidb-lightning TiDB Lightning Importer-backend TiDB-backend

- Importer-backendtidb-lightning SQL CSV tikv-importer Ingest TiKV
- TiDB-backendtidb-lightning INSERT TiDB SQL

| | Importer-backend | TiDB-backend |
|---|---|---|
| | | |
| | (~300 GB/) | (~50 GB/) |
| | | |
| ACID | | |
| | | |

TiDB Lightning TiDB-Backend TiDB

TiDB-backend TiDB Lightning TiDB SQL

- 16 CPU
- SSD
-

## TiDB-backend

TiDB-backend tikv-importer TiDB-backend

- tikv-importer
- TiDB-backend

(1) inventory.ini[importer_server]

```
...
[importer_server]
# keep empty
[lightning_server]
# data_source_dir
LS1 ansible_host=172.16.4.2 deploy_dir=/data/deploy tidb_lightning_pprof_port=8289 data_source_dir=/data/wante
...
```

(2) data_source_dir conf/tidb-lightning.yml backend

```
tikv_importer:
backend: "tidb" # <--  “tidb”
```

mydumper sql csv csv conf/tidb-lightning.yml

```
...
[mydumper]
no-schema: true
[mydumper.csv]
#  ASCII
separator = ','
#  ASCII
delimiter = '"'
# CSV
#  true
header = true
# CSV  NULL
#  trueCSV  NULL
not-null = false
#  `not-null`  false CSV  NULL
#  NULL
null = '\N'
#
backslash-escape = true
#
trim-last-separator = false
...
```

(3) Lightning

```
$ ansible-playbook bootsrap.yml -l LS
```

(4) Lightning

```
$ ansible-playbook deploy.yml -l LS

$ ansible-playbook deploy.yml --tags=lightning
```

(5) Lightning

1. Lightning
2. 
3. Lightning *scripts/start_lightning.sh*

(6)

gafana

# 2.2.2.4 TiDB Lightning Web

TiDB Lightning TiDB Lightning Web

TiDB Lightning web

- tidb-lightning --server-mode

```
./tidb-lightning --server-mode --status-addr :8289
```

- tidb-lightning.toml lightning.server-mode

```
[lightning]
server-mode = true
status-addr = ':8289'
```

TiDB Lightning http://127.0.0.1:8289 URL status-addr

## TiDB Lightning Web

| | |
|---|---|
| “TiDB Lightning” | |
| ⚠ | |
| | |
| + | |
| / ▶ | / |
| ⟳ | |

- Active
- Completed
- Pending

+

(task) TOML TiDB Lightning UPLOAD TOML

SUBMIT

>

TiDB Lightning

JSON

⋮

# 2.2.2.5

TiDB Lightning

```
[black-white-list]
do-dbs = ["pattern1", "pattern2", "pattern3"]
ignore-dbs = ["pattern4", "pattern5"]
```

- [black-white-list] do-dbs do-dbs
- do-dbs ignore-dbs
- do-dbs ignore-dbs

```
[[black-white-list.do-tables]]
db-name = "db-pattern-1"
tbl-name = "table-pattern-1"
#
[[black-white-list.do-tables]]
db-name = "db-pattern-2"
tbl-name = "table-pattern-2"
[[black-white-list.ignore-tables]]
db-name = "db-pattern-3"
tbl-name = "table-pattern-3"
[[black-white-list.ignore-tables]]
db-name = "db-pattern-4"
tbl-name = "table-pattern-4"
```

- do-tables do-tables
- do-tables ignore-tables
- do-tables ignore-tables

| | |
|---|---|
| logs | messages_2016messages_2017messages_2018 |
| forum | messages |
| forum_backup_2016 | messages |
| forum_backup_2017 | messages |
| forum_backup_2018 | messages |
| admin | secrets |

```
[black-white-list]
do-dbs = [
    "forum_backup_2018",  #  A
    "~^(logs|forum)$",    #  B ~  Go
]
ignore-dbs = [
    "~^forum_backup_",              #  C
]
[[black-white-list.do-tables]]      #  D
db-name = "logs"
tbl-name = "~_2018$"

[[black-white-list.ignore-tables]]  #  E
db-name = "~.*"
tbl-name = "~^messages.*"

[[black-white-list.do-tables]]      #  F
db-name = "~^forum.*"
tbl-name = "messages"
```

| | | |:----:|:----:| | `logs` | B | | `forum` | B | | `forum_backup_2016` | C | | `forum_backup_2017` | C | | forum_backup_2018 | A C | | `admin` | do-dbs |

| | |
|---|---|
| `logs` . `messages_2016` `logs` . `messages_2017` | E |
| `logs` . `messages_2018` | D E |
| `forum` . `users` | do-tables |
| `forum` . `messages` | F E |
| `forum_backup_2016` . `messages` forum_backup_2017 . messages | |
| `forum_backup_2018` .`message | F E |
| `admin` . `secrets` | |

# 2.2.2.6

Lightning

```
[checkpoint]
#
# Lightning
enable = true

#
#  - file v2.1.1
#  - mysql MySQL
driver = "file"

#
#  driver = "mysql"
# schema = "tidb_lightning_checkpoint"

#
#  `/tmp/CHECKPOINT_SCHEMA.pb`
# driver = "mysql"dsn":@tcp(:)/"
  dsn = "/tmp/tidb_lightning_checkpoint.pb"
#
# keep-after-success = false
```

TiDB Lightning  MySQL

- driver = "file" dsn  RAM disk
- driver = "mysql" MySQL 5.7  MariaDB  TiDB() MySQL  tidb-lightning

- tidb-lightning  tidb-lightning-ctl

  ```
  #  `schema`.`table` DROP""
  #  `schema`.`table`
  $ tidb-lightning-ctl --checkpoint-error-destroy='`schema`.`table`'
  ```

- “all”

  ```
  $ tidb-lightning-ctl --checkpoint-error-destroy=all
  ```

- `schema.table` “all”

  ```
  $ tidb-lightning-ctl --checkpoint-error-ignore='`schema`.`table`' &&
  $ tidb-lightning-ctl --checkpoint-error-ignore=all
  ```

  (CHECKSUM)

- --checkpoint-remove

  ```
  $ tidb-lightning-ctl --checkpoint-remove='`schema`.`table`' &&
  $ tidb-lightning-ctl --checkpoint-remove=all
  ```

- --checkpoint-dump

  ```
  # driver = "mysql"
  $ tidb-lightning-ctl --checkpoint-dump=output/directory
  ```

# 2.2.2.7 CSV

TiDB Lightning CSV TSV

CSV db_name.table_name.csv db_name table_name

CSV CSV db_name.table_name.003.csv

*.csv

CSV TiDB

- DDL CREATE TABLE db_name.table_name-schema.sql
- TiDB tidb-lightning.toml [mydumper] no-schema = true

CSV tidb-lightning.toml [mydumper.csv] MySQL LOAD DATA

```
[mydumper.csv]
# ASCII
separator = ','
# ASCII
delimiter = '""'
# CSV
# true
header = true
# CSV NULL
# trueCSV NULL
not-null = false
# `not-null` false CSV NULL
# NULL
null = '\N'
#
backslash-escape = true
#
trim-last-separator = false
```

## separator

- 
- ASCII
- 
  - CSV ','
  - TSV "\t"
- LOAD DATA FIELDS TERMINATED BY

## delimiter

- 
- delimiter
- 
  - "" RFC 4180
  - "
- LOAD DATA FIELDS ENCLOSED BY

## header

- CSV
- true false

## not-null null

- not-null
- not-null false null SQL NULL

CSV

```
A,B,C
\N,"\N",
```

- not-null = false; null = '\N' A and B TiDB NULL C " NULL

## backslash-escape

- backslash-escape true

  | | | |:----|:----| | \0 | (U+0000) | | \b | (U+0008) | | \n | (U+000A) | | \r | (U+000D) | | \t | (U+0009) | | \Z | Windows EOF (U+001A) |

- \""
- LOAD DATA FIELDS ESCAPED BY '\'

## trim-last-separator

separator

CSV

- A,,B,,
- trim-last-separator = false 5 ('A', '', 'B', '', '')
- trim-last-separator = true 3 ('A', '', 'B')

TiDB Lightning LOAD DATA

- CR\rLF\n CRLF\r\n LINES TERMINATED BY
- LINES STARTING BY
- IGNORE n LINES
- ASCII

## CSV

RFC 4180

```
[mydumper.csv]
separator = ','
delimiter = '"'
header = true
not-null = false
null = '\N'
backslash-escape = true
trim-last-separator = false
```

```
ID,Region,Count
1,"East",32
2,"South",\N
3,"West",10
4,"Nor
```

### TSV

```
[mydumper.csv]
separator = "\t"
delimiter = ''
header = true
not-null = false
null = 'NULL'
backslash-escape = false
trim-last-separator = false
```

```
ID Region Count
1 East 32
2 South NULL
3 West 10
4 North 39
```

### TPC-H DBGEN

```
[mydumper.csv]
separator = '|'
delimiter = ''
header = false
not-null = true
backslash-escape = false
trim-last-separator = true
```

```
1|East|32|
2|South|0|
3|West|10|
4|North|39|
```

## 2.2.2.8 TiDB Lightning

TiDB Lightning TiDB Lightning  TiKV Importer

TiDB Lightning “”“” TiDB Lightning

## TiDB Lightning

```
### tidb-lightning

[lightning]
#  web  Prometheus  HTTP  0
status-addr = ':8289'

#  web
# “TiDB Lightning web ”
server-mode = false

#
level = "info"
file = "tidb-lightning.log"
max-size = 128 # MB
max-days = 28
max-backups = 14
```

## TiDB Lightning

```
### tidb-lightning

[lightning]
#
# check-requirements = true

#
# “”“”
#
#  tikv-importer
#  tikv-importer  max-open-engines
index-concurrency = 2
table-concurrency = 6

#  CPU
#  CPU  75% CPU
# region-concurrency =

# I/O I/O
#  I/O
#
io-concurrency = 5

[checkpoint]
#
# TiDB Lightning
#  Lightning
enable = true
#
schema = "tidb_lightning_checkpoint"
#
#  - file
#  - mysql MySQL
driver = "file"

# dsn  (data source name)
#  driver = "file" dsn
#“/tmp/CHECKPOINT_SCHEMA.pb”
#  driver = "mysql" dsn “:@tcp(:)/” URL
#  URL [tidb]  TiDB
#  TiDB  MySQL
# dsn = "/tmp/tidb_lightning_checkpoint.pb"
```

```
#  false
#
# keep-after-success = false

[tikv-importer]
# “importer”  “tidb“
# backend = "importer"
#  “importer” tikv-importer
addr = "172.16.31.10:8287"
#  “tidb”
# - replace
# - ignore
# - error
# on-duplicate = "replace"

[mydumper]
#
read-block-size = 65536 # Byte ( 64 KB)

#
# Lightning
batch-size = 107_374_182_400 # Byte ( 100 GB)

#
# Lightning
#
# “”””  1 GB
# /
# “” 0
# 0 <= batch-import-ratio < 1
batch-import-ratio = 0.75

# mydumper
data-source-dir = "/data/my_database"
#  no-shcema = false TiDB Lightning  TiDB
#  `CREATE TABLE`
no-schema = false
#  `CREATE TABLE`
#  - utf8mb4 UTF-8  Lightning
#  - gb18030 GB-18030  Lightning
#  - auto UTF-8  GB-18030
#  - binary
# ****  binary
character-set = "auto"

#  CSV
[mydumper.csv]
#  ASCII
separator = ','
#  ASCII
delimiter = '"'
# CSV
#  header = true
# CSV  NULL
#  not-null = trueCSV  NULL
not-null = false
#  not-null = false CSV  NULL
#  NULL
null = '\N'
# “\”
backslash-escape = true
#
trim-last-separator = false

[tidb]
# tidb-server
host = "172.16.31.1"
port = 4000
user = "root"
password = ""
#  TiDB “status-port”
```

```
status-port = 10080
# pd-server
pd-addr = "172.16.31.4:2379"
# tidb-lightning  TiDB
#  TiDB
log-level = "error"

#  TiDB  Checksum  Analyze
# ″ Analyze “
build-stats-concurrency = 20
distsql-scan-concurrency = 100
index-serial-scan-concurrency = 20
checksum-table-concurrency = 16

#  SQL  SQL
sql-mode = "STRICT_TRANS_TABLES,NO_ENGINE_SUBSTITUTION"
# `max-allowed-packet`
#  `max_allowed_packet`  0
#  global  `max_allowed_packet`
max-allowed-packet = 67_108_864

# tidb-lightning  ChecksumCompact  Analyze
#  true
# Checksum -> Compact -> Analyze
[post-restore]
#  true `ADMIN CHECKSUM TABLE <table>`
#
checksum = true
#  true level-1 Compact
#  false
level-1-compact = false
#  true TiKV  full Compact
#  false
compact = false
#  true `ANALYZE TABLE <table>`
analyze = true

#
# hms
[cron]
# Lightning  TiKV
switch-mode = "5m"
#
log-progress = "5m"

# “TiDB Lightning ″
# [black-white-list]
# ...
```

## TiKV Importer

```
# TiKV Importer

#
log-file = "tikv-importer.log"
# trace, debug, info, warn, error  off
log-level = "info"

[server]
# tikv-importer tidb-lightning
addr = "192.168.20.10:8287"
# gRPC
grpc-concurrency = 16

[metric]
#  Prometheus  job
job = "tikv-importer"
#  Prometheus
interval = "15s"
# Prometheus Pushgateway
address = ""

[rocksdb]
# background job
max-background-jobs = 32

[rocksdb.defaultcf]
#
write-buffer-size = "1GB"
#
max-write-buffer-number = 8

#
#  0  KV
#  6  SST
#  1  5
compression-per-level = ["lz4", "no", "no", "no", "no", "no", "lz4"]

[rocksdb.writecf]
#
compression-per-level = ["lz4", "no", "no", "no", "no", "no", "lz4"]

[import]
#
import-dir = "/mnt/ssd/data.import/"
#  RPC
num-threads = 16
#  job
num-import-jobs = 24
#  Region
# max-prepare-duration = "5m"
#  Region
#region-split-size = "512MB"
#  stream-channel-window
# channel  stream
# stream-channel-window = 128
#
max-open-engines = 8
# Importer  TiKV /
# upload-speed-limit = "512MB"
# store_available_space/store_capacity
# Importer  SST
#  PD  Regions
min-available-ratio = 0.05
```

## tidb-lightning

tidb-lightning

| | | |
|---|---|---|
| –config *file* | *file* | |
| -V | | |
| -d *directory* | | mydumper.data-source-dir |
| -L *level* | debuginfowarnerror fatal ( info) | lightning.log-level |
| –backend *backend* | importer tidb | tikv-importer.backend |
| –log-file *file* | | lightning.log-file |
| –status-addr *ip:port* | TiDB Lightning | lightning.status-port |
| –importer *host:port* | TiKV Importer | tikv-importer.addr |
| –pd-urls *host:port* | PD endpoint | tidb.pd-addr |
| –tidb-host *host* | TiDB Server host | tidb.host |
| –tidb-port *port* | TiDB Server 4000 | tidb.port |
| –tidb-status *port* | TiDB Server 10080 | tidb.status-port |
| –tidb-user *user* | TiDB | tidb.user |
| –tidb-password *password* | TiDB | tidb.password |

cfg.toml ./tidb-lightning -L debug --config cfg.toml “debug”

## tidb-lightning-ctl

tidb-lightning-ctl

| | |
|---|---|
| –compact | full compact |
| –switch-mode *mode* | TiKV Store normal import |
| –import-engine *uuid* | TiKV Importer TiKV |
| –cleanup-engine *uuid* | TiKV Importer |
| –checkpoint-dump *folder* | CSV |
| –checkpoint-error-destroy *tablename* | |
| –checkpoint-error-ignore *tablename* | |
| –checkpoint-remove *tablename* | |

*tablename* `db.tbl` all

tidb-lightning tidb-lightning-ctl

## tikv-importer

tikv-importer

| | | |
|---|---|---|
| -C, –config *file* | *file* | |
| -V, –version | | |
| -A, –addr *ip:port* | TiKV Importer | server.addr |
| –import-dir *dir* | | import.import-dir |
| –log-level *level* | tracedebuginfowarnerror off | log-level |
| –log-file *file* | | log-file |

# 2.2.2.9 TiDB Lightning

tidb-lightning tikv-importer Prometheus (metrics) TiDB Lightning

- TiDB Ansible Lightning inventory.ini [monitored_servers]
- Lightning

## tikv-importer

tikv-importer v2.1 Pushgateway tikv-importer.toml Pushgateway

```
[metric]

#  Prometheus
job = "tikv-importer"

#  Prometheus
interval = "15s"

# Prometheus Pushgateway
address = ""
```

Prometheus tidb-lightning tidb-lightning.toml

```
[lightning]
#  Prometheus  HTTP  0
pprof-port = 8289
...
```

Prometheus Lightning

```
...
scrape_configs:
  - job_name: 'tidb-lightning'
    static_configs:
      - targets: ['192.168.20.10:8289']
```

# Grafana

Grafana Prometheus

TiDB Ansible TiDB Grafana + Prometheus

TiDB Lightning JSON

| | | |
|---|---|---|
| Import speed | write from lightning | TiDB Lightning TiKV Importer |
| Import speed | upload to tikv | TiKV Importer SST TiKV |
| Chunk process duration | | |

0

| | |
|---|---|
| Import progress | |
| Checksum progress | |
| Failures | |

| | |
|---|---|
| Memory usage | |
| Number of Lightning Goroutines | TiDB Lightning goroutines |
| CPU% | CPU |

| | | |
|---|---|---|
| Idle workers | io | io-concurrency 5 0 |
| Idle workers | closed-engine | index-concurrency table-concurrency 8 0 TiDB Lightning TiKV Importer TiDB Lightning |
| Idle workers | table | table-concurrency 0 |
| Idle workers | index | index-concurrency 0 |
| Idle workers | region | region-concurrency 0 |
| External resources | KV Encoder | KV encoder region-concurrency |
| External resources | Importer Engines | max-open-engines |

| | | |
|---|---|---|
| Chunk parser read block duration | read block | |
| Chunk parser read block duration | apply worker | io-concurrency |
| SQL process duration | row encode | |
| SQL process duration | block deliver | TiKV Importer |

TiDB Lightning I/O

| | | |
|---|---|---|
| SQL process rate | data deliver rate | TiKV Importer |
| SQL process rate | index deliver rate | TiKV Importer |
| SQL process rate | total deliver rate | |
| Total bytes | parser read size | TiDB Lightning |
| Total bytes | data deliver size | TiKV Importer |
| Total bytes | index deliver size | TiKV Importer |
| Total bytes | storage_size/3 | TiKV 1/33 |

| | | |
|---|---|---|
| Delivery duration | Range delivery | range TiKV |
| Delivery duration | SST delivery | SST TiKV |
| SST process duration | Split SST | SST |
| SST process duration | SST upload | SST |
| SST process duration | SST ingest | ingest SST |
| SST process duration | SST size | SST |

tikv-importer tidb-lightning

## tikv-importer

tikv-importer tikv *import**

tikv_import_rpc_duration

- RPC
  - request RPC
    - switch_mode — TiKV import/normal
    - open_engine —
    - write_engine —
    - close_engine —
    - import_engine — TiKV
    - cleanup_engine —
    - compact_cluster — TiKV
    - upload — SST
    - ingest — Ingest SST
    - compact — TiKV

    - resultRPC
        - ok
        - error

tikv_import_write_chunk_bytes

- Lightning

tikv_import_write_chunk_duration

- tidb-lightning

tikv_import_upload_chunk_bytes

- TiKV SST

tikv_import_range_delivery_duration

- range dispatch-job

tikv_import_split_sst_duration

- range SST

tikv_import_sst_delivery_duration

- SST dispatch-job ImportSSTJob

tikv_import_sst_recv_duration

- ImportSSTJob dispatch-job SST

tikv_import_sst_upload_duration

- ImportSSTJob SST TiKV

tikv_import_sst_chunk_bytes

- TiKV SST

tikv_import_sst_ingest_duration

- SST TiKV

tikv_import_each_phase

- 1 0
    - phaseprepare / import

tikv_import_wait_store_available_count

- TiKV SST
    - store_id TiKV ID

tikv_import_upload_chunk_duration

- TiKV

## tidb-lightning

tidb-lightning lightning_*

lightning_importer_engine

-
    - type:
        - open

        - closed

lightning_idle_workers

- worker
  - name
    - table — table-concurrency 0
    - index — index-concurrency 0
    - region — region-concurrency 0
    - io — io-concurrency 5 0
    - closed-engine — index-concurrency table-concurrency 8 0 TiDB Lightning TiKV Importer TiDB Lightning

lightning_kv_encoder

- KV KV TiDB SQL INSERT
  - type:
    - open
    - closed

lightning_tables

-
  - state
    - pending —
    - written —
    - closed —
    - imported —
    - altered_auto_inc — ID
    - checksum —
    - analyzed —
    - completed —
  - result
    - success —
    - failure —

lightning_engines

-
  - state
    - pending —
    - written —
    - closed —
    - imported —
    - completed —
  - result
    - success —
    - failure —

lightning_chunks

- Chunks
  - state: Chunk Chunk
    - estimated — Chunk
    - pending —
    - running —
    - finished — Chunk
    - failed —

lightning_import_seconds

- 

lightning_row_read_bytes

- SQL

lightning_row_encode_seconds

- SQL

lightning_row_kv_deliver_seconds

- SQL

lightning_block_deliver_seconds

- tikv-importer

lightning_block_deliver_bytes

- Importer

lightning_chunk_parser_read_block_seconds

- SQL

lightning_checksum_seconds

- Checksum

lightning_apply_worker_seconds

- worker ( lightning_idle_workers )
  - name
    - table
    - index
    - region
    - io
    - closed-engine

# 2.3 4.0 BR

BR(https://github.com/pingcap/br) BR TiKV SQL dump BR

## 2.3.1 BR

### 2.3.1.1

BR TiKV

```
* BR TiKV
* TiKV region leader iterator
* TiKV SST IO
* TiKV SST https3
* TIKV BR
```

BR

```
* TiKV
* TiKV Streaming
*
*
* PD leader
* schema
```

TiKV TiDB/TiKV percolator 3 CF defaultlockwrite TiKV SST TiKV write default

TiKV ts backup_ts write default key-value

TiKV

(backup_ts, current_ts]

SI write CF

- Put
- Delete

- Lockselect for update
- Rollback

1. region leader
2. SSTSST rocksdb /
3. S3HTTP
4. SI point-in-time

### 2.3.1.1

1. KV Scan
2. s3 TiKV SST IO
3. TiDB

- RegionError region split/mergenot leader
- KeyLocked
- Server is busy TiKV

1. GC GC GCBR BR GC GC 10

## 2.3.1.2

- database table
- table SST Split & Scatter Region
- SST TiKV
- table ID SST Key Rewrite
- SST Ingest TiKV

Key RewriteSplit & Scatter Region, Ingest SST

1. Key Rewrite TiDB TiKV

| **Key: tablePrefix{tableID}_recordPrefixSep{rowID} Value: [col1, col2, col3, col4]Key: tablePrefix{tableID}_indexPrefixSep{indexID}_indexedColumnsValue Value: rowID** |
| --- |
| |

Key tableID SST TiKV tableID

SST key tableID tableID indexID

1. Split & Scatter TiKV Region 96MBSplit Region Region Region Scatter

SST Region SST Region Region

1. Ingest SST Ingest SST sst_importer SST Raft Ingest

```
*  region leader  leader  region  TiKV
*  Key Rewrite  IO
```

BR

# 2.3.2 BR

## 1.

BR Ansible

1. ansible v4.0.0-beta.1
2. pip install -r ./requirements.txt
3. 
   i. 6IP 101-106
   ii. 101-106 TiKV 101-103 PD 104-106 TiDB

> :

br tidb-toolkit-v4.0.0-beta.1.tar.gz ansible tidb-ansible downloads

## 2.

TiDB

```
MySQL [(none)]> create database br_test;
Query OK, 0 rows affected (0.11 sec)

MySQL [(none)]> use br_test;
Database changed

MySQL [br_test]>  create table br_table(id int primary key,c varchar(128),ctime timestamp);
Query OK, 0 rows affected (0.12 sec)
```

python

```
import mysql.connector
import time
mydb = mysql.connector.connect(
    host="xxxx.104", #  tidb-server  ip
    user='root',
    port=4000,
    database='br_test'
)
mycursor = mydb.cursor()

for i in range (100000):
    mycursor.execute('insert into br_table values(%s,%s,now())',(i,str(i)+'xxxx'))
    if i%1000==0:
        mycursor.execute('commit')

mycursor.execute('commit')
mycursor.close()
mydb.close()
```

TiDB

```
MySQL [br_test]> select count(1) from br_table;
+----------+
| count(1) |
+----------+
|   100000 |
+----------+
1 row in set (0.04 sec)
```

6 TiKV

## 3.

1. tikv_gc_life_time

```
#  gc

#

SELECT VARIABLE_VALUE FROM mysql.tidb WHERE VARIABLE_NAME = 'tikv_gc_life_time';

10m0s

# 720h

UPDATE mysql.tidb SET VARIABLE_VALUE = '720h' WHERE VARIABLE_NAME = 'tikv_gc_life_time';

#

SELECT * FROM mysql.tidb WHERE VARIABLE_NAME = 'tikv_gc_life_time';

720h
```

1.

SMB/NFS

> S3GCS

TiKV, BR  TiDBPD

NFS

```
mount -t nfs //nfs_address/:/data  /data_nfs1
```

## 4.

BR

gRPC  TiKV BR  PD

## 5.

--ca--cert--key TLS

--concurrency 4

--log-file,--log-level

-u, --pd  PD 127.0.0.1:2379

--ratelimit MB

-s, --storage "local:///data_nfs1"

## 6.

```
bin/br backup full  --pd "192.168.122.101:2379" --storage "local:///data_nfs1/backup"
```

TiKV /data_nfs1/backup

```
*  PD  TiKV
*  infoSchema
* {"cluster_id":6801677637806839235,"start_key":"dIAAAAAAAAAvX3IAAAAAAAAAAA==","end_key":"dIAAAAAAAAAvX3L/////////wA
=","end_version":415142848617512967,"concurrency":4,"storage_backend":{Backend":{"Local":{"path":"/data_nfs1/backup"}
}}}"
*  TiKV  BR
* checksum [table=`br_test`.`br_table`] [Crc64Xor=12896770389982935753] [TotalKvs=100000] [TotalBytes=4788890]
*
*
```

protobuf

5_2_23_80992061af3e5194c3f28a5b79d486c5e9db2feda1afb3f84b4ca229ddce9932_write.sst

## 7.

```
MySQL [br_test]> drop table br_table;
```

> TiKV

```
bin/br restore full  --pd "192.168.122.101:2379" --storage "local:///data_nfs1/backup"
```

1. PD
2. DDLCREATE DATABASE / *!32312 IF NOT EXISTS*/ CREATE TABLE IF NOT EXISTS
3. alter auto incrementID , id
4. sst Region
5. ["Full restore summary: total restore tables: 1, total success: 1, total failed: 0, total take(s): 0.25, total size(MB): 2.28, avg speed(MB/s): 9.08, total kv: 50001"] ["restore files"=1] ["restore ranges"=1] ["split region"=6.373065871s] ["restore checksum"=45.843202ms]

```
MySQL [br_test]> select count(1) from br_table;
+----------+
| count(1) |
+----------+
|    100000|
+----------+
1 row in set (0.12 sec)
```

## 8.

```
bin/br backup db --db "br_test"  --pd "192.168.122.101:2379" --storage "local:///data_nfs1/backup"
```

```
bin/br restore db  --db "br_test" --pd "192.168.122.101:2379" --storage "local:///data_nfs1/backup"
```

## 9.

```
bin/br backup table --db "br_test"  --table "br_table"  --pd "192.168.122.101:2379" --storage "local:///data_nfs1/bac
kup"
```

```
bin/br restore table --db "br_test" --table "br_table" --pd "192.168.122.101:2379" --storage "local:///data_nfs1/back
up"
```

BR BR ( https://github.com/pingcap/br),

# 2.4.1 Dumpling

## 1.

Dumpling Dumpling PingCAP Mydumper fork TiDB TiDB Mydumper Mydumper

- TiDB Lighting
- Mydumper TiDB fork
- Mydumper C GLib Go TiDB DM
- Mydumper TiDB

Dumpling Dumpling

- Golang TiDB
- Mydumper MySQL
- SQLCSV
- S3

## 2.

Dumpling

Dumpling Black & White

- 
- 
- 
- Black & White
- 
- API

# 2.4.2 Dumpling

## 1.

- SELECT
- RELOAD
- LOCK TABLES
- REPLICATION CLIENT

TiDB TiDB

## 2.

```
dumpling -B tidb -F 2048 -H 127.0.0.1 -u root -P 4000 --loglevel debug
```

```
Release version:
Git commit hash: a35708fb6a9ca19294b92598b88d7894cf130ca6
Git branch:      master
Build timestamp: 2020-03-08 03:15:54Z
Go version:      go version go1.13.1 darwin/amd64

[2020/03/08 18:09:43.780 +08:00] [DEBUG] [config.go:72] ["parse server info"] ["server info string"=5.7.25-TiDB-v4.0.
0-beta-313-g2d5d2fde27]
[2020/03/08 18:09:43.780 +08:00] [INFO] [config.go:85] ["detect server type"] [type=TiDB]
[2020/03/08 18:09:43.780 +08:00] [INFO] [config.go:103] ["detect server version"] [version=4.0.0-beta-313-g2d5d2fde27
]
[2020/03/08 18:09:43.781 +08:00] [DEBUG] [prepare.go:27] ["list all the tables"]
[2020/03/08 18:09:43.788 +08:00] [DEBUG] [black_white_list.go:78] ["filter tables"]
[2020/03/08 18:09:43.788 +08:00] [WARN] [black_white_list.go:70] ["unsupported dump schema in TiDB now"] [schema=mysq
l]
```

## 3.

Dumpling :

| | |
|---|---|
| --consistency <level> | : auto/none/flush/lock/snapshot auto |
| -B, --database <database> | |
| -F, --filesize <size> | bytes |
| -H, --host <hostname> | 127.0.0.1 |
| --loglevel <level> | debug/info/warn/error/dpanic/panic/fatal info |
| -W, --no-views | true |
| -o, --output <dir> | `./export-2020-03-08T11:37:05+08:00` |
| -p, --password <password> | |
| -P, --port <port> | 4000 |
| --snapshot <position> | snapshot |
| -t, --threads <num> | 4 |
| -u, --user <user> | root |

# 1 SQL

SQL SQL TiDB SQL Join SQL Hint SQL SQL Hint SQL Plan Management TiDB SQL Batch SQL

SQL

# 1.1

`SQL` `SQL`

## 1.1.1 EXPLAIN

TiDB `EXPLAIN` `SQL`

`TiDB` `EXPLAIN` 5 `id` `estRows` `task` `access object` `operator info` 5 `EXPLAIN`

| | |
|---|---|
| id | ID TiDB 2.1 ID |
| estRows | 4.0 count |
| task | task task **root** task tidb-server **cop** task TiKV TiFlash task root task cop taskroot task cop task cop task TiDB TiKV TiFlash cop task TiKV TiFlash |
| access object | `table` `partition` `index` |
| operator info | operator info |

## 1.1.2 EXPLAIN ANALYZE

`EXPLAIN` `EXPLAIN ANALYZE` `SQL` `EXPLAIN` `EXPLAIN ANALYZE` `actRows` , `execution info` , `memory` , `disk`

| | |
|---|---|
| actRows | |
| execution info | time (loops)loops rows |
| memory | |
| disk | |

```
mysql> explain analyze select * from t where a < 10;
+-------------------------------+---------+---------+-----------+------------------------+-------------------------
-----------------------------------------------+-------------------------------------------------------+---------------+
------+
| id                            | estRows | actRows | task      | access object          | execution info
                                              | operator info                                         | memory        |
 disk |
+-------------------------------+---------+---------+-----------+------------------------+-------------------------
-----------------------------------------------+-------------------------------------------------------+---------------+
------+
| IndexLookUp_10                | 9.00    | 9       | root      |                        | time:641.245µs, loops:2,
rpc num: 1, rpc time:242.648µs, proc keys:0   |                                                       | 9.23046875 KB |
 N/A  |
| ├─IndexRangeScan_8(Build)     | 9.00    | 9       | cop[tikv] | table:t, index:idx_a(a) | time:142.94µs, loops:10,
                                              | range:[-inf,10), keep order:false                     | N/A           |
 N/A  |
| └─TableRowIDScan_9(Probe)     | 9.00    | 9       | cop[tikv] | table:t                 | time:141.128µs, loops:10
                                              | keep order:false                                      | N/A           |
 N/A  |
+-------------------------------+---------+---------+-----------+------------------------+-------------------------
-----------------------------------------------+-------------------------------------------------------+---------------+
------+
3 rows in set (0.00 sec)
```

`estRows` `actRows` `IndexLookUp_10` `9 KB` `SQL`

# 1.1.3

TiDB `SQL` `CPU`

**`Build`** **`Probe`** **`Build`** **`Probe`**

ID `Build` `Probe` TiDB `Build` `Probe`

```
TiDB(root@127.0.0.1:test) > explain select * from t use index(idx_a) where a = 1;
+-------------------------------+---------+-----------+------------------------+-----------------------------------
---------+
| id                            | estRows | task      | access object          | operator info
         |
+-------------------------------+---------+-----------+------------------------+-----------------------------------
---------+
| IndexLookUp_7                 | 10.00   | root      |                        |
         |
| ├─IndexRangeScan_5(Build)     | 10.00   | cop[tikv] | table:t, index:idx_a(a) | range:[1,1], keep order:false, stat
s:pseudo |
| └─TableRowIDScan_6(Probe)     | 10.00   | cop[tikv] | table:t                 | keep order:false, stats:pseudo
         |
+-------------------------------+---------+-----------+------------------------+-----------------------------------
---------+
3 rows in set (0.00 sec)
```

`IndexLookUp_7` `IndexRangeScan_5(Build)` `TableRowIDScan_6(Probe)` `IndexRangeScan_5(Build)` `RowID` `TableRowIDScan_6(Probe)` `RowID`

```
TiDB(root@127.0.0.1:test) > explain select * from t t1 use index(idx_a) join t t2 use index() where t1.a = t2.a;
+----------------------------------+----------+-----------+-------------------------+-------------------------------
-----------------------------------+
| id                               | estRows  | task      | access object           | operator info
                                   |
+----------------------------------+----------+-----------+-------------------------+-------------------------------
-----------------------------------+
| HashJoin_22                      | 12487.50 | root      |                         | inner join, inner:TableReader_
26, equal:[eq(test.t.a, test.t.a)] |
| ├─TableReader_26(Build)          | 9990.00  | root      |                         | data:Selection_25
                                   |
| | └─Selection_25                 | 9990.00  | cop[tikv] |                         | not(isnull(test.t.a))
                                   |
| |   └─TableFullScan_24           | 10000.00 | cop[tikv] | table:t2                | keep order:false, stats:pseudo
                                   |
| └─IndexLookUp_29(Probe)          | 9990.00  | root      |                         |
                                   |
|   ├─IndexFullScan_27(Build)      | 9990.00  | cop[tikv] | table:t1, index:idx_a(a) | keep order:false, stats:pseudo
                                   |
|   └─TableRowIDScan_28(Probe)     | 9990.00  | cop[tikv] | table:t1                | keep order:false, stats:pseudo
                                   |
+----------------------------------+----------+-----------+-------------------------+-------------------------------
-----------------------------------+
7 rows in set (0.00 sec)
```

`HashJoin_22` `TableReader_26(Build)` `IndexLookUp_29(Probe)` `IndexLookUp_29(Probe)` `IndexFullScan_27(Build)` `TableRowIDScan_28(Probe)` `TableRowIDScan_28(Probe)`

# 1.1.4

TiKV Block Cache

- **TableFullScan** “”
- **TableRangeScan**
- **TableRowIDScan** `RowID`
- **IndexFullScan** “”
- **IndexRangeScan**

TiDB TiKV/TiFlash “”

- **TableReader** TiKV `TableFullScan` `TableRangeScan`
- **IndexReader** TiKV `IndexFullScan` `IndexRangeScan`
- **IndexLookUp** Build TiKV RowID Probe RowID TiKV Build `IndexFullScan` `IndexRangeScan` Probe `TableRowIDScan`
- **IndexMerge** IndexLookupReader Build Probe Build TiKV RowID Probe RowID TiKV Build `IndexFullScan` `IndexRangeScan` Probe `TableRowIDScan`

**IndexLookUp**

```
mysql> explain select * from t use index(idx_a);
+------------------------------+----------+-----------+------------------------+--------------------------------+
| id                           | estRows  | task      | access object          | operator info                  |
+------------------------------+----------+-----------+------------------------+--------------------------------+
| IndexLookUp_6                | 10000.00 | root      |                        |                                |
| ├─IndexFullScan_4(Build)     | 10000.00 | cop[tikv] | table:t, index:idx_a(a) | keep order:false, stats:pseudo |
| └─TableRowIDScan_5(Probe)    | 10000.00 | cop[tikv] | table:t                | keep order:false, stats:pseudo |
+------------------------------+----------+-----------+------------------------+--------------------------------+
3 rows in set (0.00 sec)
```

`IndexLookUp_6` `IndexFullScan_4(Build)` `TableRowIDScan_5(Probe)` `IndexFullScan_4(Build)` `a` RowID `TableRowIDScan_5(Probe)` RowID TableReader IndexLookUp

### TableReader

```
mysql> explain select * from t where a > 1 or b >100;
+-------------------------+----------+-----------+---------------+---------------------------------------+
| id                      | estRows  | task      | access object | operator info                         |
+-------------------------+----------+-----------+---------------+---------------------------------------+
| TableReader_7           | 8000.00  | root      |               | data:Selection_6                      |
| └─Selection_6           | 8000.00  | cop[tikv] |               | or(gt(test.t.a, 1), gt(test.t.b, 100)) |
|   └─TableFullScan_5     | 10000.00 | cop[tikv] | table:t       | keep order:false, stats:pseudo        |
+-------------------------+----------+-----------+---------------+---------------------------------------+
3 rows in set (0.00 sec)
```

`TableReader_7` `Selection_6` `Cop Task` TiKV `Cop Task` `TableFullScan_5` `Selection` SQL SQL `WHERE` / `HAVING` / `ON` `TableFullScan_5` `IndexMerge`

### IndexMerge

> TIDB `Index Merge` 4.0 RC 4.0 `Index Merge` `or` `and` `Index Merge` session global `set @@tidb_enable_index_merge = 1;`

```
mysql> set @@tidb_enable_index_merge = 1;
mysql> explain select * from t use index(idx_a, idx_b) where a > 1 or b > 1;
+-----------------------------+---------+-----------+------------------------+-----------------------------------
-----------+
| id                          | estRows | task      | access object          | operator info
           |
+-----------------------------+---------+-----------+------------------------+-----------------------------------
-----------+
| IndexMerge_16               | 6666.67 | root      |                        |
           |
| ├─IndexRangeScan_13(Build)  | 3333.33 | cop[tikv] | table:t, index:idx_a(a) | range:(1,+inf], keep order:false, st
ats:pseudo |
| ├─IndexRangeScan_14(Build)  | 3333.33 | cop[tikv] | table:t, index:idx_b(b) | range:(1,+inf], keep order:false, st
ats:pseudo |
| └─TableRowIDScan_15(Probe)  | 6666.67 | cop[tikv] | table:t                | keep order:false, stats:pseudo
           |
+-----------------------------+---------+-----------+------------------------+-----------------------------------
-----------+
4 rows in set (0.00 sec)
```

`IndexMerge` `IndexMerge_16` `IndexRangeScan_13` `IndexRangeScan_14` `RowID` `TableRowIDScan_15` `RowID`

## 1.1.5

### Hash Aggregate

TiDB `Hash Aggregation` `Hash Aggregate`

```
TiDB(root@127.0.0.1:test) > explain select /*+ HASH_AGG() */ count(*) from t;
+--------------------------+----------+-----------+---------------+--------------------------------+
| id                       | estRows  | task      | access object | operator info                  |
+--------------------------+----------+-----------+---------------+--------------------------------+
| HashAgg_11               | 1.00     | root      |               | funcs:count(Column#7)->Column#4 |
| └─TableReader_12         | 1.00     | root      |               | data:HashAgg_5                 |
|   └─HashAgg_5            | 1.00     | cop[tikv] |               | funcs:count(1)->Column#7       |
|     └─TableFullScan_8    | 10000.00 | cop[tikv] | table:t       | keep order:false, stats:pseudo |
+--------------------------+----------+-----------+---------------+--------------------------------+
4 rows in set (0.00 sec)
```

TiDB `Hash Aggregate` TiKV/TiFlash `Coprocessor` TiDB `Coprocessor` Task

### Stream Aggregate

TiDB `Stream Aggregation` `Hash Aggregate` `Hash Aggregate` `Stream Aggregate` `Stream Aggregate`

```
TiDB(root@127.0.0.1:test) > explain select /*+ STREAM_AGG() */ count(*) from t;
+---------------------------+----------+-----------+---------------+--------------------------------+
| id                        | estRows  | task      | access object | operator info                  |
+---------------------------+----------+-----------+---------------+--------------------------------+
| StreamAgg_16              | 1.00     | root      |               | funcs:count(Column#7)->Column#4 |
| └─TableReader_17          | 1.00     | root      |               | data:StreamAgg_8               |
|   └─StreamAgg_8           | 1.00     | cop[tikv] |               | funcs:count(1)->Column#7       |
|     └─TableFullScan_13    | 10000.00 | cop[tikv] | table:t       | keep order:false, stats:pseudo  |
+---------------------------+----------+-----------+---------------+--------------------------------+
4 rows in set (0.00 sec)
```

`Hash Aggregate` TiDB `Stream Aggregate` TiKV/TiFlash `Coprocessor` TiDB `Coprocessor` Task

## 1.1.6 Join

TiDB Join

- Hash Join
- Merge Join
- Index Hash Join
- Index Merge Join
- Apply

Join

**Hash Join**

TiDB `Hash Join` `Hash Join`

```
mysql> explain select /*+ HASH_JOIN(t1, t2) */ * from t t1 join t2 on t1.a = t2.a;
+-----------------------------+----------+-----------+---------------+-----------------------------------------------
---------------------+
| id                          | estRows  | task      | access object | operator info
                     |
+-----------------------------+----------+-----------+---------------+-----------------------------------------------
---------------------+
| HashJoin_33                 | 10000.00 | root      |               | inner join, inner:TableReader_43, equal:[eq(t
est.t.a, test.t2.a)] |
| ├─TableReader_43(Build)     | 10000.00 | root      |               | data:Selection_42
                     |
| │ └─Selection_42            | 10000.00 | cop[tikv] |               | not(isnull(test.t2.a))
                     |
| │   └─TableFullScan_41      | 10000.00 | cop[tikv] | table:t2      | keep order:false
                     |
| └─TableReader_37(Probe)     | 10000.00 | root      |               | data:Selection_36
                     |
|   └─Selection_36            | 10000.00 | cop[tikv] |               | not(isnull(test.t.a))
                     |
|     └─TableFullScan_35      | 10000.00 | cop[tikv] | table:t1      | keep order:false
                     |
+-----------------------------+----------+-----------+---------------+-----------------------------------------------
---------------------+
7 rows in set (0.00 sec)
```

`Hash Join` Build `Hash Table` Probe Probe ProbeBuild Hash Table

**Merge Join**

TiDB `Merge Join` Hash Join Merge Join

```
mysql> explain select /*+ SM_JOIN(t1) */ * from t t1 join t t2 on t1.a = t2.a;
+-----------------------------------+----------+-----------+-------------------------+-----------------------------
----------------------+
| id                                | estRows  | task      | access object           | operator info
                      |
+-----------------------------------+----------+-----------+-------------------------+-----------------------------
----------------------+
| MergeJoin_6                       | 10000.00 | root      |                         | inner join, left key:test.t.
a, right key:test.t.a |
| ├─IndexLookUp_13(Build)           | 10000.00 | root      |                         |
                      |
| │ ├─IndexFullScan_11(Build)       | 10000.00 | cop[tikv] | table:t2, index:idx_a(a) | keep order:true
                      |
| │ └─TableRowIDScan_12(Probe)      | 10000.00 | cop[tikv] | table:t2                | keep order:false
                      |
| └─IndexLookUp_10(Probe)           | 10000.00 | root      |                         |
                      |
|   ├─IndexFullScan_8(Build)        | 10000.00 | cop[tikv] | table:t1, index:idx_a(a) | keep order:true
                      |
|   └─TableRowIDScan_9(Probe)       | 10000.00 | cop[tikv] | table:t1                | keep order:false
                      |
+-----------------------------------+----------+-----------+-------------------------+-----------------------------
----------------------+
7 rows in set (0.00 sec)
```

`Merge Join` Build Join Group Probe Probe Build Join Group “” Join Group Join Key

**Index Hash Join**

INL_HASH_JOIN(t1_name [, tl_name]) Index Nested Loop Hash Join Index Nested Loop Join

```
mysql> explain select /*+ INL_HASH_JOIN(t1) */ * from t t1 join t t2 on t1.a = t2.a;
+---------------------------------+----------+-----------+-------------------------+-----------------------------
-------------------------------------------+
| id                              | estRows  | task      | access object           | operator info
                                           |
+---------------------------------+----------+-----------+-------------------------+-----------------------------
-------------------------------------------+
| IndexHashJoin_32                | 10000.00 | root      |                         | inner join, inner:IndexLookUp_
23, outer key:test.t.a, inner key:test.t.a |
| ├─TableReader_35(Build)         | 10000.00 | root      |                         | data:Selection_34
                                           |
| │ └─Selection_34                | 10000.00 | cop[tikv] |                         | not(isnull(test.t.a))
                                           |
| │   └─TableFullScan_33          | 10000.00 | cop[tikv] | table:t2                | keep order:false
                                           |
| └─IndexLookUp_23(Probe)         | 1.00     | root      |                         |
                                           |
|   ├─Selection_22(Build)         | 1.00     | cop[tikv] |                         | not(isnull(test.t.a))
                                           |
|   │ └─IndexRangeScan_20         | 1.00     | cop[tikv] | table:t1, index:idx_a(a) | range: decided by [eq(test.t.a
, test.t.a)], keep order:false             |
|   └─TableRowIDScan_21(Probe)    | 1.00     | cop[tikv] | table:t1                | keep order:false
                                           |
+---------------------------------+----------+-----------+-------------------------+-----------------------------
-------------------------------------------+
8 rows in set (0.00 sec)
```

**Index Merge Join**

INL_MERGE_JOIN(t1_name [, tl_name]) Index Nested Loop Merge Join INL_JOIN INL_JOIN join keys index index join keys

```
mysql> explain select /*+ INL_MERGE_JOIN(t1) */ * from t t1 where  t1.a  in ( select t2.a from t2 where t2.b < t1.b);
+-----------------------------+----------+-----------+---------------+-----------------------------------------------
-------------------------------------------------------+
| id                          | estRows  | task      | access object | operator info
                                                        |
+-----------------------------+----------+-----------+---------------+-----------------------------------------------
-------------------------------------------------------+
| HashJoin_26                 | 8000.00  | root      |               | semi join, inner:TableReader_49, equal:[eq(te
st.t.a, test.t2.a)], other cond:lt(test.t2.b, test.t.b) |
| ├─TableReader_49(Build)     | 10000.00 | root      |               | data:Selection_48
                                                        |
| │ └─Selection_48            | 10000.00 | cop[tikv] |               | not(isnull(test.t2.a)), not(isnull(test.t2.b)
)                                                       |
| │   └─TableFullScan_47      | 10000.00 | cop[tikv] | table:t2      | keep order:false
                                                        |
| └─TableReader_38(Probe)     | 10000.00 | root      |               | data:Selection_37
                                                        |
|   └─Selection_37            | 10000.00 | cop[tikv] |               | not(isnull(test.t.a)), not(isnull(test.t.b))
                                                        |
|     └─TableFullScan_36      | 10000.00 | cop[tikv] | table:t1      | keep order:false
                                                        |
+-----------------------------+----------+-----------+---------------+-----------------------------------------------
-------------------------------------------------------+
7 rows in set, 1 warning (0.01 sec)
```

**Apply**

```
mysql> explain select /*+ INL_MERGE_JOIN(t1) */ * from t t1 where  t1.a  in ( select avg(t2.a) from t2 where t2.b < t
1.b);
+----------------------------------+----------+-----------+---------------+----------------------------------------
-------------------------------------+
| id                               | estRows  | task      | access object | operator info
                                     |
+----------------------------------+----------+-----------+---------------+----------------------------------------
-------------------------------------+
| Projection_10                    | 10000.00 | root      |               | test.t.id, test.t.a, test.t.b
                                     |
| └─Apply_12                       | 10000.00 | root      |               | semi join, inner:StreamAgg_30, equal:[eq(
Column#8, Column#7)]                 |
|   ├─Projection_13(Build)         | 10000.00 | root      |               | test.t.id, test.t.a, test.t.b, cast(test.
t.a, decimal(20,0) BINARY)->Column#8 |
|   │ └─TableReader_15             | 10000.00 | root      |               | data:TableFullScan_14
                                     |
|   |   └─TableFullScan_14         | 10000.00 | cop[tikv] | table:t1      | keep order:false
                                     |
|   └─StreamAgg_30(Probe)          | 1.00     | root      |               | funcs:avg(Column#12, Column#13)->Column#7
                                     |
|     └─TableReader_31             | 1.00     | root      |               | data:StreamAgg_19
                                     |
|       └─StreamAgg_19             | 1.00     | cop[tikv] |               | funcs:count(test.t2.a)->Column#12, funcs:
sum(test.t2.a)->Column#13            |
|         └─Selection_29           | 8000.00  | cop[tikv] |               | lt(test.t2.b, test.t.b)
                                     |
|           └─TableFullScan_28     | 10000.00 | cop[tikv] | table:t2      | keep order:false
                                     |
+----------------------------------+----------+-----------+---------------+----------------------------------------
-------------------------------------+
10 rows in set, 1 warning (0.00 sec)
```

# 1.1.7 EXPLAIN FOR CONNECTION

`EXPLAIN FOR CONNECTION` `EXPLAIN` TiDB MySQL

- MySQL TiDB
- MySQL MySQL `PROCESS` TiDB `SUPER`

# 1.2

TiDB System R SQL Join

## 1.2.1

### 1

TiDB

- DataSource `select * from t` `t`
- Selection `select * from t where a = 5` `where a = 5`
- Projection `select c, a + b from t` `c` `a + b`
- Join `select t1.b, t2.c from t1 join t2 on t1.a = t2.a` `t1 join t2 on t1.a = t2.a` `t1` `t2` Join

SelectionProjectionJoin SPJ 3

### 2

| 1 | 2 |
|---|---|
| 1 | 6 |
| 2 | 7 |
| 3 | 8 |
| 4Max / Min | 9 |
| 5 | 10TopN / Limit |

#### 1

- 1LogicalJoin LogicalJoin outer plan
- 2
  - 2.1LogicalJoin join key inner plan
  - 2.2LogicalJoin

1 2 2.1 2.2

1 2.1

```
select t1.a from t1 left join t2 on t1.b = t2.b;
```

```
select t1.a from t1;
```

#### 2 `Max` / `Min`

`Max` / `Min` `Max` / `Min`

```
select min(id) from t;
```

```
select id from t order by id desc limit 1;
```

TableScan Aggregation TableScan + Sort + Limit id Sort TableScan/IndexLookUp + Limit

“”

# 1.2.2

- 
- 
- 
- 

# 1.2.3

TiDB NULL TOPN

## 1

`ANALYZE` `tidb_enable_fast_analyze` 0 1 person fast analyze

```
set @@tidb_enable_fast_analyze = 1;
analyze table person;
```

`show analyze status` `where`

```
mysql> show analyze status where job_info = 'analyze columns';
+--------------+------------+-----------------+---------------------+----------+
| Table_schema | Table_name | Job_info        | Start_time          | State    |
+--------------+------------+-----------------+---------------------+----------+
| test         | person     | analyze columns | 2020-03-07 06:22:34 | finished |
| test         | customer   | analyze columns | 2020-03-07 06:32:19 | finished |
| test         | person     | analyze columns | 2020-03-07 06:35:27 | finished |
+--------------+------------+-----------------+---------------------+----------+
3 rows in set (0.01 sec)
```

## 2

DML TiDB 1 20 * stats-lease

> stats-lease 3s 0

## 3

meta

```
mysql> show stats_meta where table_name = 'person';
+---------+------------+----------------+---------------------+--------------+------------+
| Db_name | Table_name | Partition_name | Update_time         | Modify_count | Row_count |
+---------+------------+----------------+---------------------+--------------+------------+
| test    | person     |                | 2020-03-07 07:20:54 |            0 |          4 |
+---------+------------+----------------+---------------------+--------------+------------+
1 row in set (0.01 sec)
```

```
mysql> show stats_healthy where table_name = 'person';
+---------+------------+----------------+---------+
| Db_name | Table_name | Partition_name | Healthy |
+---------+------------+----------------+---------+
| test    | person     |                |     100 |
+---------+------------+----------------+---------+
1 row in set (0.00 sec)
```

`SHOW STATS_HISTOGRAMS` NULL：

```
mysql> show stats_histograms where table_name = 'person';
+---------+------------+----------------+-------------+----------+---------------------+----------------+------------
+--------------+-------------+
| Db_name | Table_name | Partition_name | Column_name | Is_index | Update_time         | Distinct_count | Null_count
| Avg_col_size | Correlation |
+---------+------------+----------------+-------------+----------+---------------------+----------------+------------
+--------------+-------------+
| test    | person     |                | name        |        0 | 2020-03-07 07:20:54 |              4 |          0
|         6.25 |        -0.2 |
+---------+------------+----------------+-------------+----------+---------------------+----------------+------------
+--------------+-------------+
1 row in set (0.00 sec)
```

`SHOW STATS_BUCKETS`

```
mysql> show stats_buckets;
+---------+------------+----------------+-------------+----------+-----------+-------+---------+-------------+-------
------+
| Db_name | Table_name | Partition_name | Column_name | Is_index | Bucket_id | Count | Repeats | Lower_Bound | Upper_
Bound |
+---------+------------+----------------+-------------+----------+-----------+-------+---------+-------------+-------
------+
| test    | person     |                | name        |        0 |         0 |     1 |       1 | jack        | jack
      |
| test    | person     |                | name        |        0 |         1 |     2 |       1 | peter       | peter
      |
| test    | person     |                | name        |        0 |         2 |     3 |       1 | smith       | smith
      |
| test    | person     |                | name        |        0 |         3 |     4 |       1 | tom         | tom
      |
+---------+------------+----------------+-------------+----------+-----------+-------+---------+-------------+-------
------+
4 rows in set (0.01 sec)
```

## 4

`DROP STATS`

```
mysql> DROP STATS person;
```

## 5

`${db_name}` `${table_name}` json

```
http://${tidb-server-ip}:${tidb-server-status-port}/stats/dump/${db_name}/${table_name}
```

test person

```
curl -G "http://127.0.0.1:10080/stats/dump/test/person" > person.json
```

json

```
mysql> LOAD STATS 'file_name';
```

file_name

# 1.3 SQL Plan Management

## 1.3.1

SQL SQL TiDB SQL Plan Management SQL

## 1.3.2 SQL Bind

SQL Bind SQL Plan Management TiDB 3.0 GA SQL SQL Bind

SQL

```
CREATE [GLOBAL | SESSION] BINDING FOR SelectStmt USING SelectStmt;
```

GLOBAL SESSION SQL SESSION SQL SQL SQL SQL Hint

“” SQL "?"

```
TiDB(root@127.0.0.1:test) > create binding for select * from t where a = 1 using select * from t use index(idx_a) whe
re a = 1;
Query OK, 0 rows affected (0.00 sec)
```

binding `Original_sql` SQL

```
TiDB(root@127.0.0.1:test) > show bindings;
+----------------------------+--------------------------------------------+------------+--------+-----------------
--------+-------------------------+---------+-----------------+
| Original_sql               | Bind_sql                                   | Default_db | Status | Create_time
        | Update_time             | Charset | Collation       |
+----------------------------+--------------------------------------------+------------+--------+-----------------
--------+-------------------------+---------+-----------------+
| select * from t where a = ? | select * from t use index(idx_a) where a = 1 | test       | using  | 2020-03-08 14:00
:28.819 | 2020-03-08 14:00:28.819 | utf8    | utf8_general_ci |
+----------------------------+--------------------------------------------+------------+--------+-----------------
--------+-------------------------+---------+-----------------+
1 row in set (0.00 sec)
```

binding

```
TiDB(root@127.0.0.1:test) > drop binding for select * from t where a = 1;
Query OK, 0 rows affected (0.00 sec)

TiDB(root@127.0.0.1:test) > show bindings;
Empty set (0.00 sec)
```

## 1.3.3 Baseline Evolution

Binding 4.0 TiDB Binding `tidb_capture_plan_baselines` `on` SQL TiDB SQL SQL TiDB 4.0 Statements Summary SQL

```
set tidb_enable_stmt_summary = 1;       --  statement summary
set tidb_capture_plan_baselines = 1;    --
```

```
TiDB(root@127.0.0.1:test) > select * from t;
Empty set (0.01 sec)

TiDB(root@127.0.0.1:test) > select * from t;
Empty set (0.00 sec)
```

global bindings binding

```
TiDB(root@127.0.0.1:test) > show global bindings;
+-----------------+-------------------------------------------------------------+------------+--------+------------------
-------+-------------------------+---------+-----------+
| Original_sql    | Bind_sql                                                    | Default_db | Status | Create_time
       | Update_time             | Charset | Collation |
+-----------------+-------------------------------------------------------------+------------+--------+------------------
-------+-------------------------+---------+-----------+
| select * from t | SELECT /*+ USE_INDEX(@`sel_1` `test`.`t` )*/ * FROM `t` | test       | using  | 2020-03-08 14:09:
30.129 | 2020-03-08 14:09:30.129 |         |           |
+-----------------+-------------------------------------------------------------+------------+--------+------------------
-------+-------------------------+---------+-----------+
1 row in set (0.00 sec)
```

4.0 `set global tidb_evolve_plan_baselines = 1` SQL SQL

SQL TiDB

`tidb_evolve_plan_task_max_time` `tidb_evolve_plan_task_start_time` `tidb_evolve_plan_task_end_time`

# 1.4

## 1.4.1

TiDB

```
TiDB(root@127.0.0.1:test) > show variables like "%tidb%opt%";
+----------------------------------+-------+
| Variable_name                    | Value |
+----------------------------------+-------+
| tidb_opt_agg_push_down           | 0     |
| tidb_opt_concurrency_factor      | 3     |
| tidb_opt_copcpu_factor           | 3     |
| tidb_opt_correlation_exp_factor  | 1     |
| tidb_opt_correlation_threshold   | 0.9   |
| tidb_opt_cpu_factor              | 3     |
| tidb_opt_desc_factor             | 3     |
| tidb_opt_disk_factor             | 1.5   |
| tidb_opt_insubq_to_join_and_agg  | 1     |
| tidb_opt_join_reorder_threshold  | 0     |
| tidb_opt_memory_factor           | 0.001 |
| tidb_opt_network_factor          | 1     |
| tidb_opt_scan_factor             | 1.5   |
| tidb_opt_seek_factor             | 20    |
| tidb_opt_write_row_id            | 0     |
| tidb_optimizer_selectivity_level | 0     |
+----------------------------------+-------+
16 rows in set (0.01 sec)
```

## 1.4.2

10

```
TiDB(root@127.0.0.1:test) > show variables like "%tidb%factor%";
+---------------------------------+-------+
| Variable_name                   | Value |
+---------------------------------+-------+
| tidb_opt_concurrency_factor     | 3     |
| tidb_opt_copcpu_factor          | 3     |
| tidb_opt_correlation_exp_factor | 1     |
| tidb_opt_cpu_factor             | 3     |
| tidb_opt_desc_factor            | 3     |
| tidb_opt_disk_factor            | 1.5   |
| tidb_opt_memory_factor          | 0.001 |
| tidb_opt_network_factor         | 1     |
| tidb_opt_scan_factor            | 1.5   |
| tidb_opt_seek_factor            | 20    |
+---------------------------------+-------+
10 rows in set (0.01 sec)
```

TiKV `tidb_opt_desc_factor`

:

```
TiDB(root@127.0.0.1:test) > desc select * from t order by a desc;
+---------------------------------+----------+-----------+-------------------------+-------------------------------
-----+
| id                              | estRows  | task      | access object           | operator info
     |
+---------------------------------+----------+-----------+-------------------------+-------------------------------
-----+
| Projection_13                   | 10000.00 | root      |                         | test.t.a, test.t.b
     |
| └─IndexLookUp_12                | 10000.00 | root      |                         |
     |
|   ├─IndexFullScan_10(Build)     | 10000.00 | cop[tikv] | table:t, index:idx_a(a) | keep order:true, desc, stats:ps
eudo |
|   └─TableRowIDScan_11(Probe)    | 10000.00 | cop[tikv] | table:t                 | keep order:false, stats:pseudo
     |
+---------------------------------+----------+-----------+-------------------------+-------------------------------
-----+
4 rows in set (0.00 sec)
```

TiKV

```
TiDB(root@127.0.0.1:test) > set @@tidb_opt_desc_factor = 10;
Query OK, 0 rows affected (0.00 sec)

TiDB(root@127.0.0.1:test) > desc select * from t order by a desc;
+-------------------------+----------+-----------+---------------+--------------------------------+
| id                      | estRows  | task      | access object | operator info                  |
+-------------------------+----------+-----------+---------------+--------------------------------+
| Sort_4                  | 10000.00 | root      |               | test.t.a:desc                  |
| └─TableReader_8         | 10000.00 | root      |               | data:TableFullScan_7           |
|   └─TableFullScan_7     | 10000.00 | cop[tikv] | table:t       | keep order:false, stats:pseudo |
+-------------------------+----------+-----------+---------------+--------------------------------+
3 rows in set (0.00 sec)
```

# 1.4.3

TiDB Join Join SQL

Join

```
TiDB(root@127.0.0.1:test) > desc select count(*) from t t1 join t t2 on t1.a = t2.a group by t1.a;
+------------------------------+----------+-----------+-------------------------+---------------------------------
-----------------+
| id                           | estRows  | task      | access object           | operator info
                 |
+------------------------------+----------+-----------+-------------------------+---------------------------------
-----------------+
| HashAgg_10                   | 7992.00  | root      |                         | group by:test.t.a, funcs:count(1)
->Column#7       |
| └─MergeJoin_13               | 12487.50 | root      |                         | inner join, left key:test.t.a, ri
ght key:test.t.a |
|   ├─IndexReader_41(Build)    | 9990.00  | root      |                         | index:IndexFullScan_40
                 |
|   | └─IndexFullScan_40       | 9990.00  | cop[tikv] | table:t2, index:idx_a(a) | keep order:true, stats:pseudo
                 |
|   └─IndexReader_39(Probe)    | 9990.00  | root      |                         | index:IndexFullScan_38
                 |
|     └─IndexFullScan_38       | 9990.00  | cop[tikv] | table:t1, index:idx_a(a) | keep order:true, stats:pseudo
                 |
+------------------------------+----------+-----------+-------------------------+---------------------------------
-----------------+
6 rows in set (0.00 sec)
```

`tidb_opt_agg_push_down` Join

```
TiDB(root@127.0.0.1:test) > set tidb_opt_agg_push_down = 1;
Query OK, 0 rows affected (0.00 sec)

TiDB(root@127.0.0.1:test) > desc select count(*) from t t1 join t t2 on t1.a = t2.a group by t1.a;
+--------------------------------+---------+-----------+-------------------------+---------------------------------
----------------------------------------------+
| id                             | estRows | task      | access object           | operator info
                                              |
+--------------------------------+---------+-----------+-------------------------+---------------------------------
----------------------------------------------+
| HashAgg_11                     | 7992.00 | root      |                         | group by:test.t.a, funcs:count(Co
lumn#8)->Column#7                             |
| └─HashJoin_24                  | 9990.00 | root      |                         | inner join, inner:HashAgg_37, equ
al:[eq(test.t.a, test.t.a)]                   |
|   ├─HashAgg_37(Build)          | 7992.00 | root      |                         | group by:test.t.a, funcs:count(1)
->Column#8, funcs:firstrow(test.t.a)->test.t.a |
|   │ └─IndexReader_44           | 9990.00 | root      |                         | index:IndexFullScan_43
                                              |
|   |   └─IndexFullScan_43       | 9990.00 | cop[tikv] | table:t2, index:idx_a(a) | keep order:false, stats:pseudo
                                              |
|   └─IndexReader_48(Probe)      | 9990.00 | root      |                         | index:IndexFullScan_47
                                              |
|     └─IndexFullScan_47         | 9990.00 | cop[tikv] | table:t1, index:idx_a(a) | keep order:false, stats:pseudo
                                              |
+--------------------------------+---------+-----------+-------------------------+---------------------------------
----------------------------------------------+
7 rows in set (0.00 sec)
```

TiDB `mysql.opt_rule_blacklist`

```
TiDB(root@127.0.0.1:test) > desc select * from t where a > 10;
+-------------------------+----------+-----------+---------------+--------------------------------+
| id                      | estRows  | task      | access object | operator info                  |
+-------------------------+----------+-----------+---------------+--------------------------------+
| TableReader_7           | 3333.33  | root      |               | data:Selection_6               |
| └─Selection_6           | 3333.33  | cop[tikv] |               | gt(test.t.a, 10)               |
|   └─TableFullScan_5     | 10000.00 | cop[tikv] | table:t       | keep order:false, stats:pseudo |
+-------------------------+----------+-----------+---------------+--------------------------------+
3 rows in set (0.00 sec)
```

predicate_pushdown

```
TiDB(root@127.0.0.1:test) > insert into mysql.opt_rule_blacklist values("predicate_push_down");
Query OK, 1 row affected (0.00 sec)
```

session reload

```
TiDB(root@127.0.0.1:test) > admin reload opt_rule_blacklist;
Query OK, 0 rows affected (0.00 sec)
```

TiKV

```
TiDB(root@127.0.0.1:test) > desc select * from t where a > 10;
+-------------------------+----------+-----------+---------------+--------------------------------+
| id                      | estRows  | task      | access object | operator info                  |
+-------------------------+----------+-----------+---------------+--------------------------------+
| Selection_5             | 8000.00  | root      |               | gt(test.t.a, 10)               |
| └─TableReader_7         | 10000.00 | root      |               | data:TableFullScan_6           |
|   └─TableFullScan_6     | 10000.00 | cop[tikv] | table:t       | keep order:false, stats:pseudo |
+-------------------------+----------+-----------+---------------+--------------------------------+
3 rows in set (0.00 sec)
```

# 1.4.4

TiDB TiKV TiDB TiKV TiDB TiDB

`mysql.expr_pushdown_blacklist`

- `mysql.expr_pushdown_blacklist`
- `admin reload expr_pushdown_blacklist`

- `mysql.expr_pushdown_blacklist`
- `admin reload expr_pushdown_blacklist`

```
TiDB(root@127.0.0.1:test) > explain select * from t where a < 2;
+-------------------------+----------+-----------+---------------+--------------------------------+
| id                      | estRows  | task      | access object | operator info                  |
+-------------------------+----------+-----------+---------------+--------------------------------+
| TableReader_7           | 3323.33  | root      |               | data:Selection_6               |
| └─Selection_6           | 3323.33  | cop[tikv] |               | lt(test.t.a, 2)                |
|   └─TableFullScan_5     | 10000.00 | cop[tikv] | table:t       | keep order:false, stats:pseudo |
+-------------------------+----------+-----------+---------------+--------------------------------+
3 rows in set (0.00 sec)
```

`<`

```
TiDB(root@127.0.0.1:test) > insert into mysql.expr_pushdown_blacklist values('<');
Query OK, 1 row affected (0.00 sec)

TiDB(root@127.0.0.1:test) > admin reload expr_pushdown_blacklist;
Query OK, 0 rows affected (0.00 sec)
```

`<` TiKV

```
TiDB(root@127.0.0.1:test) > explain select * from t where a < 2;
+-------------------------+----------+-----------+---------------+--------------------------------+
| id                      | estRows  | task      | access object | operator info                  |
+-------------------------+----------+-----------+---------------+--------------------------------+
| Selection_5             | 8000.00  | root      |               | lt(test.t.a, 2)                |
| └─TableReader_7         | 10000.00 | root      |               | data:TableFullScan_6           |
|   └─TableFullScan_6     | 10000.00 | cop[tikv] | table:t       | keep order:false, stats:pseudo |
+-------------------------+----------+-----------+---------------+--------------------------------+
3 rows in set (0.00 sec)
```

# 1.5 SQL

SQLSQLSQLOOM

## 1.5.1 SQL

SQL

1. 
2. `oom-action`
   - "log"
   - TiDB SQL `mem-quota-query`
   - ["log", "cancel"]
   - "log" SQL TiDB log LOG SQL OOM LOG SQL
   - "cancel" SQL TiDB SQL errorerror SQL
3. `mem-quota-query`
   - 3435973836832GB
   - SQL
   - `oom-action`
4. `oom-use-tmp-storage`
   - true
   - SQL `mem-quota-query`
5. `tmp-storage-path`
   - <>/tidb/tmp-storage
   - SQL `mem-quota-query`
   - `oom-use-tmp-storage` true
6. session
7. `tidb_mem_quota_query`
   - 32 GB
   - TiDB `OOMAction`
8. `tidb_mem_quota_hashjoin`
   - 32 GB
   - `HashJoin` `HashJoin` TiDB `OOMAction`
9. `tidb_mem_quota_mergejoin`
   - 32 GB
   - `MergeJoin` `MergeJoin` TiDB `OOMAction`
10. `tidb_mem_quota_sort`
    - 32 GB
    - Sort `Sort` TiDB `OOMAction`
11. `tidb_mem_quota_topn`
    - 32 GB
    - TopN `TopN` TiDB `OOMAction`
12. `tidb_mem_quota_indexlookupreader`
    - 32 GB
    - `IndexLookupReader` `IndexLookupReader` TiDB `OOMAction`
13. `tidb_mem_quota_indexlookupjoin`
    - 32 GB
    - `IndexLookupJoin` `IndexLookupJoin` TiDB `OOMAction`
14. `tidb_mem_quota_nestedloopapply`
    - 32 GB

- `NestedLoopApply` `NestedLoopApply` TiDB `OOMAction`

SQL 8GB

```
set @@tidb_mem_quota_query = 8 << 30;
```

SQL 8MB

```
set @@tidb_mem_quota_query = 8 << 20;
```

1. Optimizer Hints
2. `memory_quota`
   - Hint MB GB
   - log

SQL1024 MB

```
select /*+ MEMORY_QUOTA(1024 MB) */ * from t;
```

## 1.5.2 SQL

1. session/global
2. `max_execution_time`
   - ms
   - statement SELECT 100ms

10

```
set @@global.MAX_EXECUTION_TIME=10000
```

1. Optimizer Hints
2. `max_execution_time`
   - ms
   - N

SQL1000 1

```
select /*+ MAX_EXECUTION_TIME(1000) */ * from t1 inner join t2 where t1.id = t2.id;
```

## 1.5.3

SQL/ `tidb.log` Expensive query

```
[2020/02/05 15:32:25.096 +08:00] [WARN] [expensivequery.go:167] [expensive_query] [cost_time=60.008338935s] [wait_tim
e=0s] [request_count=1] [total_keys=70] [process_keys=65] [num_cop_tasks=1] [process_avg_time=0s] [process_p90_time=0
s] [process_max_time=0s] [process_max_addr=10.0.1.9:20160] [wait_avg_time=0.002s] [wait_p90_time=0.002s] [wait_max_ti
me=0.002s] [wait_max_addr=10.0.1.9:20160] [stats=t:pseudo] [conn_id=60026] [user=root] [database=test] [table_ids="[1
22]"] [txn_start_ts=414420273735139329] [mem_max="1035 Bytes (1.0107421875 KB)"] [sql="insert into t select sleep(1)
from t"]
```

- `cost_time`
- `stats` pesudo analyze
- `table_ids` ID
- `txn_start_ts` ID TiDB
- `sql` SQL

- `mem_max` Bytes MBGB

- `user`
- `conn_id` ID con:60026 TiDB
- `database` database

TiKV Coprocessor Task

- `wait_time` TiKV TiKV Coprocessor Coprocessor
- `request_count` Coprocessor
- `total_keys` Coprocessor key
- `processed_keys` Coprocessor key `total_keys` `processed_keys` MVCC processed_keys total_keys
- `num_cop_tasks` Coprocessor
- `process_avg_time` Coprocessor task
- `process_p90_time` Coprocessor task P90
- `process_max_time` Coprocessor task
- `process_max_addr` task Coprocessor
- `wait_avg_time` Coprocessor task
- `wait_p90_time` Coprocessor task P90
- `wait_max_time` Coprocessor task
- `wait_max_addr` task Coprocessor

# 2.1

TiDB Dashboard Key Visualizer (KeyVis) TiDB DBA CT

## 1.

- Bucket

  TiDB Region Region Region 1500 Bucket Region Region Bucket Region Bucket

-

  X Y Region TiDB cold Region hot

## 2.

-
-
-

## 3. Region

6 Bucket Region

-
- Select & Zoom
- Reset Region
-

Region

# 4.

Bucket cold Region hot  Brightness

# 5.

Auto Refresh  Region

# 6.

- Read (bytes)
- Write (bytes)
- Read (keys)
- Write (keys)
- All

# 7.

Region TiKV KeyVis  Region  DBA

-
-
-
-
-
-
- scale 10
- ()

CRUD TiDB Dashboard  DBA

# 8.

-

  (sysbench prepare ) sbtest1, sbtest2, sbtest3,

- KeyVis

165.25 ,  sbtest1  k_1,  key  start key  end key

165.25 M
bytes/min
2020-03-07 15:32:37 ~ 2020-03-07 15:33:37
sbtest1
k_1
START KEY (INCL.):
748000000000000ff2d5f69800000000...
END KEY (EXCL.):
748000000000000ff2d5f72800000000...

•

-

TiDB 4.0

# 2.2 SQL

KeyVis TiDB

TiDB Dashboard Statements SQL SQL

## 1. Statements

Statement SQL

SQL TiDB Dashboard Statements SQL

SQL

## 2. Statements

TiDB

1. Grafana SQL
2. Slow log SQL
3. General log
4. Explain analyze
5. Profile

Statements SQL

## 3. Statements

SQL

SQL

1.
2.
3.

> SQL SQL SQL SQL

```
SELECT * FROM employee WHERE id IN (1, 2, 3);
select * from EMPLOYEE where ID in (4, 5);
```

```
select * from employee where id in (...);
```

# 4. Statements

SQL SQL SQL SQL

Statements

1. SQL
2.
3.
4.

# 5. Statements

- `tidb_enable_stmt_summary`

  Statements

  ```
  set global tidb_enable_stmt_summary = true;
  ```

- `tidb_stmt_summary_refresh_interval`

`performance_schema.events_statements_summary_by_digest` (s) 1800

```
set global tidb_stmt_summary_refresh_interval = 1800;
```

- `tidb_stmt_summary_history_size`

  `performance_schema.events_statements_summary_by_digest_history` SQL 24

  ```
  set global tidb_stmt_summary_history_size = 24;
  ```

Statements SQL SQL config.toml `[stmt-summary]`

- `max-stmt-count` SQL 200 SQL `max-stmt-count` SQL
- `max-sql-length` `DIGEST_TEXT` `QUERY_SAMPLE_TEXT` 4096

> `tidb_stmt_summary_history_size` `max-stmt-count` `max-sql-length`

Statements SQL KeyVis

# 2.3

+

TiDB DBA

html

## 2.3.1

### 1.

PD `pd-server.metric-storage` prometheus

```
curl -X POST -d '{"metric-storage":"http://{PROMETHEUS_ADDRESS}"}' http://{PD_ADDRESS}/pd/api/v1/config
```

```
curl -X POST -d '{"metric-storage":"http://127.0.0.1:9090"}' http://127.0.0.1:2379/pd/api/v1/config
```

### 2.

2 min ~ 60 min 1

### 3.

**4.**

2 start end 10

**5.**

- i i
- expand expand instance, label

Load

the disk write latency in each node

| METRIC_NAME | instance | AVG | MAX | MIN |
|---|---|---|---|---|
| node_disk_write_latency fold | | 0.0002 | 0.0003 | 0.000007 |
| \|-- node_disk_write_latency | 172.16.5.40:19110 | 0.0002 | 0.0003 | 0.000007 |
| node_disk_read_latency expand | | | | |
| node_cpu_usage expand | | 80.56% | 81.55% | 79.4% |
| node_mem_usage expand | | 27.9% | 28.71% | 26.89% |

## 2.3.2

TiDB 4.0 `INSPECTION_RESULT`

## 2.3.3

### 1. Header

### (1) Report Time Range

| START_TIME | END_TIME |
| --- | --- |
| 2020-03-05 16:30:00 | 2020-03-05 16:50:00 |

## (2) cluster hardware

| HOST | INSTANCE | CPU_CORES | MEMORY (GB) | DISK (GB) | UPTIME (DAY) |
| --- | --- | --- | --- | --- | --- |
| 172.16.5.40 | `tidb*1 tikv*4 pd*1` | 20/40 | 122.696 | sda3: 1465.187500<br>nvme0n1: 343.715603<br>sda1: 0.185237 | 253.14520396237572 |

- HOST
- INSTANCE `tidb*1 tikv*4 pd*1` 1 TiDB 4 TiKV 1 PD
- CPU_CORESCPU /
- MEMORY GB
- DISK GB
- UPTIME: Day

## (3) cluster info

TiDB `information_schema.cluster_info`

| TYPE | INSTANCE | STATUS_ADDRESS | VERSION | GIT_HASH |
| --- | --- | --- | --- | --- |
| tidb | 172.16.5.40:4009 | 172.16.5.40:10089 | 5.7.25-TiDB-v4.0.0-beta-311-gd93c06149 | d93c061491d8094751a53c510bd8de886722952a |
| pd | 172.16.5.40:24799 | 172.16.5.40:24799 | 4.1.0-alpha | 61d9f9cc35d3f191eb5e7ea1eb4f8e29eb73eda0 |
| tikv | 172.16.5.40:21150 | 172.16.5.40:21151 | 4.1.0-alpha | 8fa0e059e14c3a1433fcb581452f9ea0a14a72ce |
| tikv | 172.16.5.40:22150 | 172.16.5.40:22151 | 4.1.0-alpha | 8fa0e059e14c3a1433fcb581452f9ea0a14a72ce |
| tikv | 172.16.5.40:23150 | 172.16.5.40:23151 | 4.1.0-alpha | 8fa0e059e14c3a1433fcb581452f9ea0a14a72ce |
| tikv | 172.16.5.40:20150 | 172.16.5.40:20151 | 4.1.0-alpha | 8fa0e059e14c3a1433fcb581452f9ea0a14a72ce |

# 2. Load info

## (1) node load

/ CPUMemory AVG MAX MIN

| METRIC_NAME | instance | AVG | MAX | MIN |
|---|---|---|---|---|
| node_disk_write_latency | | 0.0002 | 0.0003 | 0.000007 |
| node_disk_read_latency | | | | |
| node_cpu_usage | | 80.56% | 81.55% | 79.4% |
| node_mem_usage | | 27.9% | 28.71% | 26.89% |

## (2) process cpu usage

TiDB / PD / TiKV CPU AVG MAX MIN

| instance | job | AVG | MAX | MIN |
|---|---|---|---|---|
| 172.16.5.40:10089 | tidb | 18.38 | 19.16 | 17.76 |
| 172.16.5.40:20151 | tikv | 9.68 | 10.03 | 9.42 |
| 172.16.5.40:24799 | pd | 0.6 | 0.63 | 0.56 |
| 172.16.5.40:22151 | tikv | 0.36 | 1.08 | 0.04 |
| 172.16.5.40:23151 | tikv | 0.3 | 1.07 | 0.04 |
| 172.16.5.40:21151 | tikv | 0.27 | 0.71 | 0.04 |

## (3) TiKV Thread CPU Usage

TiKV CPU

| METRIC_NAME | instance | AVG | MAX | MIN | |
|---|---|---|---|---|---|
| raftstore fold>) | | 0.01 | 0.06 | 0 | |
| \ | -- raftstore | 172.16.5.40:20151 | 0.06 | 0.06 | 0.05 |
| \ | -- raftstore | 172.16.5.40:22151 | 0.00003 | 0.0002 | 0 |
| \ | -- raftstore | 172.16.5.40:23151 | 0 | 0 | 0 |
| \ | -- raftstore | 172.16.5.40:21151 | 0 | 0 | 0 |
| apply expand>) | | 0 | 0 | 0 | |
| sched_worker expand>) | | 0 | 0 | 0 | |
| snap expand>) | | 0.000002 | 0.0002 | 0 | |
| cop expand>) | | 0.01 | 0.18 | 0 | |
| grpc expand>) | | 0.16 | 0.85 | 0 | |

## (4) goroutines count

TiDB / PD goroutines AVG MAX MIN

| instance | job | AVG | MAX | MIN |
|---|---|---|---|---|
| 172.16.5.40:10089 | tidb | 899 | 996 | 651 |
| 172.16.5.40:24799 | pd | 114 | 115 | 113 |

## 3. Overview

## (1) Time Consume

| METRIC_NAME | LABEL | TIME_RATIO | TOTAL_TIME | TOTAL_COUNT | P999 | P99 |
|---|---|---|---|---|---|---|
| tidb_query expand>) | | 1 | 184598.05 | 9467997 | 0.4 | 0.12 |
| tidb_get_token expand>) | | 0.00007 | 12.1 | 9467600 | 0.0002 | 0.000001 |
| tidb_parse expand>) | | 0.000007 | 1.23 | 3593 | 0.04 | 0.008 |
| tidb_compile expand>) | | 0.00001 | 1.82 | 3593 | 0.04 | 0.03 |
| tidb_execute expand>) | | 0.000007 | 1.26 | 3593 | 0.2 | 0.17 |
| tidb_distsql_execution expand>) | | 0.0003 | 56.72 | 1953 | 1.41 | 0.5 |
| tidb_cop expand>) | | 0.001 | 206.21 | 2756 | 2.01 | 1.66 |
| tidb_transaction expand>) | | 0.09 | 15920.8 | 9456815 | 0.49 | 0.06 |

- METRIC_NAME
- LABEL LABEL  expand  LABEL
- TIME_RATIO TIME_RATIO  1

```
    tidb_cop  tidb_query  0.001
```

- TOTAL_TIME
- TOTAL_COUNT
- P999  P999
- P99 P99
- P90 P90
- P80 P80

## (2) Error

error

| METRIC_NAME | LABEL | TOTAL_COUNT | |
|---|---|---|---|
| tidb_binlog_error_total_count | | 0 | |
| tidb_handshake_error_total_count | | 0 | |
| tidb_transaction_retry_error_total_count | | | |
| tidb_kv_region_error_total_count fold>) | | 739 | |
| \ | -- tidb_kv_region_error_total_count | not_leader | 481 |
| \ | -- tidb_kv_region_error_total_count | stale_command | 256 |
| \ | -- tidb_kv_region_error_total_count | epoch_not_match | 1 |
| tidb_schema_lease_error_total_count | | | |
| tikv_grpc_error_total_count | | | |
| tikv_critical_error_total_count | | | |
| tikv_scheduler_is_busy_total_count | | | |
| tikv_channel_full_total_count | | | |
| tikv_coprocessor_request_error_total_count fold>) | | 8 | |
| \ | -- tikv_coprocessor_request_error_total_count | meet_lock | 7 |
| \ | -- tikv_coprocessor_request_error_total_count | not_leader | 1 |
| tikv_engine_write_stall | | 0 | |
| tikv_server_report_failures_total_count | | 0 | |
| tikv_storage_async_request_error fold>) | | 793 | |
| \ | -- tikv_storage_async_request_error | snapshot | 793 |
| tikv_lock_manager_detect_error_total_count | | 0 | |
| tikv_backup_errors_total_count | | | |
| node_network_in_errors_total_count | | 0 | |
| node_network_out_errors_total_count | | 0 | |

## 4. TiDB

TiDB

## (1) Time Consume

TiDB Overview label

## (2) Transaction

TiDB

| METRIC_NAME | LABEL | TOTAL_VALUE | TOTAL_COUNT | P999 | P99 | P90 |
|---|---|---|---|---|---|---|
| tidb_transaction_retry_num | | 0 | 0 | 0 | 0 | 0 |
| tidb_transaction_statement_num expand>) | | 17524099 | 17500676 | 511 | 501 | 398 |
| tidb_txn_region_num expand>) | | 900385 | 900095 | 4 | 1 | 1 |
| tidb_txn_kv_write_num expand>) | | 658293 | 1379 | 1023 | 1011 | 896 |
| tidb_txn_kv_write_size expand>) | | 216307980 | 1379 | 1043333 | 996147 | 2487 |
| tidb_load_safepoint_total_num expand>) | | 67 | | | | |
| tidb_lock_resolver_total_num expand>) | | 40 | | | | |

- TOTAL_VALUE
- TOTAL_COUNT
- P999 P999
- P99 P99
- P90 P90
- P80 P80

`tidb_txn_kv_write_size` 1379 kv kv 216307980 P999P99P90P80 1043333996147248705235266 byte

## (3) DDL-owner

TiDB DDL owner

| MIN_TIME | DDL OWNER |
|---|---|
| 2020-03-05 16:30:00 | 172.16.5.40:10089 |

> owner owner TiDB `ddl_worker` DDL owner `ddl_worker` DDL job owner

## 5. PD / TiKV

PD TiKV i

## 6. Config

## (1) Scheduler Config

PD Scheduler change history

| MIN_TIME | CONFIG_ITEM | VALUE | CHANGE_COUNT |
|---|---|---|---|
| 2020-03-05 16:30:00.000000 | enable-makeup-replica | 1 | 1 |
| 2020-03-05 16:30:00.000000 | enable-remove-down-replica | 1 | 1 |
| 2020-03-05 16:30:00.000000 | enable-remove-extra-replica | 1 | 1 |
| 2020-03-05 16:30:00.000000 | enable-replace-offline-replica | 1 | 1 |
| 2020-03-05 16:30:00.000000 | high-space-ratio | 0.6 | 1 |
| 2020-03-05 16:30:00.000000 | hot-region-cache-hits-threshold | 3 | 1 |
| 2020-03-05 16:30:00.000000 | hot-region-schedule-limit | 4 | 1 |
| 2020-03-05 16:30:00.000000 | leader-schedule-limit | 4 | 2 |
| 2020-03-05 16:46:00.000000 | leader-schedule-limit | 8 | 2 |
| 2020-03-05 16:30:00.000000 | low-space-ratio | 0.8 | 1 |
| 2020-03-05 16:30:00.000000 | max-merge-region-keys | 200000 | 1 |
| 2020-03-05 16:30:00.000000 | max-merge-region-size | 20 | 1 |
| 2020-03-05 16:30:00.000000 | max-pending-peer-count | 16 | 1 |
| 2020-03-05 16:30:00.000000 | max-replicas | 3 | 1 |
| 2020-03-05 16:30:00.000000 | max-snapshot-count | 3 | 1 |
| 2020-03-05 16:30:00.000000 | merge-schedule-limit | 8 | 1 |
| 2020-03-05 16:30:00.000000 | region-schedule-limit | 2048 | 1 |
| 2020-03-05 16:30:00.000000 | replica-schedule-limit | 64 | 1 |
| 2020-03-05 16:30:00.000000 | store-balance-rate | 15 | 1 |
| 2020-03-05 16:30:00.000000 | tolerant-size-ratio | 0 | 1 |

- MIN_TIME
- CONFIG_ITEM
- VALUE
- CHANGE_COUNT

`leader-schedule-limit`

- 2020-03-05 16:30:00 `leader-schedule-limit` 4
- 2020-03-05 16:46:00 `leader-schedule-limit` 8 2020-03-05 16:46:00

> `leader-schedule-limit` 2020-03-05 16:46:00 prometheus

## (2) TiDB GC Config

TiDB GC change history

| MIN_TIME | CONFIG_ITEM | VALUE | CHANGE_COUNT |
|---|---|---|---|
| 2020-03-03 17:00:00.000000 | tikv_gc_life_time | 6000 | 1 |
| 2020-03-03 17:00:00.000000 | tikv_gc_run_interval | 60 | 1 |

## (3) TiDB / PD / TiKV Current Config

TiDB `information_schema.cluster_config`

> current Config

# 2.4

TiDB Dashboard TiDB

## 1.

:

- 
- 
- 
- regex

## 2.

- 
- Dashboard
- 

- ()
- Cancel
- Retry

## 3.

4

- 
- WARNERROR
- TiDBTiKVPD
- 512

## 4.

- zip log
- tar zip zip log

# 2.5 CPU

TiDBTiKVPD

go profile CPU

## 1.

Dashboard →

( 30 120 )

## 2.

1

> Dashboard PD gogo pprofGraphViz TiDB PD TiKV

## 3.

TiDBTiKV

- TiDB Profile

- TiKV CPU

TiDB 4.0 CPU TiDB

# 3

TiDB 4.0 ———— SQL SQL TiDB 4.0 SQL

3.1 SQL TiDB 4.0 Statements SQL

3.2 3.4 SQL TiDB 4.0 `metrics_schema` SQL SQL TiDB SQL

3.3 SQL SQL SQL SQL `select * from inspection_result`

3.5 3.6 `processlist` `slow_query` SQL `cluster_processlist` `cluster_slow_query` `cluster_processlist` TiDB `cluster_slow_query`

3.7 `Statement Summary` `Statement Summary` SQL SQL

# 3.1

## 3.1.1

TiDB TiDB 4.0 SQL

TiDB 4.0

## 3.1.2

TiDB 4.0

- `information_schema.cluster_info` Git Hash
- `information_schema.cluster_config` TiDB 4.0 HTTP API
- `information_schema.cluster_hardware`
- `information_schema.cluster_load`
- `information_schema.cluster_systeminfo` sysctl
- `information_schema.cluster_log` grep

TiDB 4.0 TiDB 4.0 TiDB

## 3.1.3

### 1.

`information_schema.cluster_info`

```
mysql> select type, instance, status_address, uptime from cluster_info;
+------+-----------------+-----------------+---------------+
| type | instance        | status_address  | uptime        |
+------+-----------------+-----------------+---------------+
| tidb | 127.0.0.1:4000  | 127.0.0.1:10080 | 11m6.204302s  |
| tidb | 127.0.0.1:4001  | 127.0.0.1:10081 | 11m6.204306s  |
| tidb | 127.0.0.1:4002  | 127.0.0.1:10082 | 11m6.204307s  |
| pd   | 127.0.0.1:2380  | 127.0.0.1:2380  | 11m16.204308s |
| pd   | 127.0.0.1:2381  | 127.0.0.1:2381  | 11m16.20431s  |
| pd   | 127.0.0.1:2382  | 127.0.0.1:2382  | 11m16.204311s |
| tikv | 127.0.0.1:20161 | 127.0.0.1:20181 | 11m11.204312s |
| tikv | 127.0.0.1:20162 | 127.0.0.1:20182 | 11m11.204313s |
| tikv | 127.0.0.1:20160 | 127.0.0.1:20180 | 11m11.204314s |
| tikv | 127.0.0.1:20163 | 127.0.0.1:20183 | 11m11.204315s |
+------+-----------------+-----------------+---------------+
10 rows in set (0.01 sec)
```

:

- TYPE pd/tikv/tidb
- INSTANCE IP:PORT
- STATUS_ADDRESSHTTP API tikv-ctl / pd-ctl / tidb-ctl HTTP API HTTP API
- VERSIONTiDB MySQL ${mysql-version}-${tidb-version}
- GIT_HASH git commit hash
- START_TIME
- UPTIME

### 2.

`information_schema.cluster_config` TiDB 4.0 HTTP API TiKV Coprocessor

```
mysql> select * from cluster_config where type='tikv' and `key`='coprocessor.batch-split-limit';
+------+-----------------+------------------------------+-------+
| TYPE | INSTANCE        | KEY                          | VALUE |
+------+-----------------+------------------------------+-------+
| tikv | 127.0.0.1:20163 | coprocessor.batch-split-limit | 10    |
| tikv | 127.0.0.1:20161 | coprocessor.batch-split-limit | 10    |
| tikv | 127.0.0.1:20162 | coprocessor.batch-split-limit | 10    |
| tikv | 127.0.0.1:20160 | coprocessor.batch-split-limit | 10    |
+------+-----------------+------------------------------+-------+
4 rows in set (2.98 sec)
```

TiDB SQL `log.file.filename` / `port` / `status.status-port`

```
mysql> select `key`,count(distinct value) as c from cluster_config where type='tidb' group by `key` having c > 1;
+--------------------+---+
| key                | c |
+--------------------+---+
| log.file.filename  | 3 |
| port               | 3 |
| status.status-port | 3 |
+--------------------+---+
3 rows in set (0.01 sec)
```

- TYPE `information_schema.cluster_info` TYPE tidb/pd/tikv
- INSTANCE `information_schema.cluster_info` STATUS_ADDRESS
- KEY
- VALUE

## 3.

`information_schema.cluster_hardware` CPU

```
mysql> select type, instance, name, value from cluster_hardware where name='cpu-logical-cores';
+------+-----------------+-------------------+-------+
| type | instance        | name              | value |
+------+-----------------+-------------------+-------+
| tidb | 127.0.0.1:10080 | cpu-logical-cores | 8     |
| tidb | 127.0.0.1:10081 | cpu-logical-cores | 8     |
| tidb | 127.0.0.1:10082 | cpu-logical-cores | 8     |
| pd   | 127.0.0.1:2380  | cpu-logical-cores | 8     |
| pd   | 127.0.0.1:2381  | cpu-logical-cores | 8     |
| pd   | 127.0.0.1:2382  | cpu-logical-cores | 8     |
| tikv | 127.0.0.1:20160 | cpu-logical-cores | 8     |
| tikv | 127.0.0.1:20163 | cpu-logical-cores | 8     |
| tikv | 127.0.0.1:20161 | cpu-logical-cores | 8     |
| tikv | 127.0.0.1:20162 | cpu-logical-cores | 8     |
+------+-----------------+-------------------+-------+
10 rows in set (0.78 sec)
```

- TYPE `information_schema.cluster_info` TYPE tidb/pd/tikv
- INSTANCE `information_schema.cluster_info` STATUS_ADDRESS
- DEVICE_TYPE cpu/memory/disk/net
- DEVICE_NAME DEVICE_TYPE
  - cpu cpu
  - disk
  - netNIC
  - memory memory
- NAME cpu `cpu-logical-cores` / `cpu-physical-cores` `select name from cluster_hardware where device_type='cpu'`

`group by name` NAME
- VALUECPU

## 4.

`information_schema.cluster_load` SQL CPU

```
mysql> select type, instance, name, value from cluster_load where device_type='cpu' and device_name='cpu' and name='l
oad1';
+------+-----------------+-------+-----------+
| type | instance        | name  | value     |
+------+-----------------+-------+-----------+
| tidb | 127.0.0.1:10080 | load1 | 3.10      |
| tidb | 127.0.0.1:10081 | load1 | 3.10      |
| tidb | 127.0.0.1:10082 | load1 | 3.10      |
| pd   | 127.0.0.1:2380  | load1 | 3.10      |
| pd   | 127.0.0.1:2381  | load1 | 3.10      |
| pd   | 127.0.0.1:2382  | load1 | 3.10      |
| tikv | 127.0.0.1:20163 | load1 | 3.1015625 |
| tikv | 127.0.0.1:20161 | load1 | 3.1015625 |
| tikv | 127.0.0.1:20162 | load1 | 3.1015625 |
| tikv | 127.0.0.1:20160 | load1 | 3.1015625 |
+------+-----------------+-------+-----------+
10 rows in set (0.55 sec)
```

- TYPE `information_schema.cluster_info` TYPE tidb/pd/tikv
- INSTANCE `information_schema.cluster_info` STATUS_ADDRESS
- DEVICE_TYPE cpu/memory/disk/net
- DEVICE_NAME DEVICE_TYPE
  - cpu cpu
  - disk
  - netNIC
  - memory memory
- NAME cpu `load1/load5/load15` CPU 1min/5min/15min `select name from cluster_load where device_type='cpu' group by name` NAME
- VALUE CPU 1min/5min/15min

## 5.

`information_schema.cluster_systeminfo` sysctl TiDB fd

```
mysql> select type, instance, name, value from cluster_systeminfo where type='tidb' and name like '%fd%';
+------+-----------------+------------------------------+-------+
| type | instance        | name                         | value |
+------+-----------------+------------------------------+-------+
| tidb | 127.0.0.1:10080 | net.inet6.ip6.maxifdefrouters | 16    |
| tidb | 127.0.0.1:10080 | net.necp.client_fd_count      | 89    |
| tidb | 127.0.0.1:10080 | net.necp.observer_fd_count    | 0     |
| tidb | 127.0.0.1:10081 | net.inet6.ip6.maxifdefrouters | 16    |
| tidb | 127.0.0.1:10081 | net.necp.client_fd_count      | 89    |
| tidb | 127.0.0.1:10081 | net.necp.observer_fd_count    | 0     |
| tidb | 127.0.0.1:10082 | net.inet6.ip6.maxifdefrouters | 16    |
| tidb | 127.0.0.1:10082 | net.necp.client_fd_count      | 89    |
| tidb | 127.0.0.1:10082 | net.necp.observer_fd_count    | 0     |
+------+-----------------+------------------------------+-------+
9 rows in set (0.04 sec)
```

- TYPE `information_schema.cluster_info` TYPE tidb/pd/tikv

- INSTANCE `information_schema.cluster_info` STATUS_ADDRESS
- SYSTEM_TYPE system
- SYSTEM_NAME SYSTEM_NAME sysctl
- NAMEsysctl
- VALUEsysctl

## 6.

`information_schema.cluster_log` TiDB grep warning

```
mysql> select * from cluster_log where level='warn'\G
*************************** 1. row ***************************
    TIME: 2020/03/08 12:17:41.329
    TYPE: pd
INSTANCE: 127.0.0.1:2382
   LEVEL: WARN
 MESSAGE: [grpclog.go:60] ["transport: http2Server.HandleStreams failed to read frame: read tcp 127.0.0.1:2382->127.0
.0.1:57030: use of closed network connection"]
*************************** 2. row ***************************
    TIME: 2020/03/08 12:17:41.338
    TYPE: pd
INSTANCE: 127.0.0.1:2382
   LEVEL: WARN
 MESSAGE: [grpclog.go:60] ["transport: http2Server.HandleStreams failed to read frame: read tcp 127.0.0.1:2382->127.0
.0.1:57029: use of closed network connection"]
*************************** 3. row ***************************
    TIME: 2020/03/08 12:17:41.361
    TYPE: pd
INSTANCE: 127.0.0.1:2382
   LEVEL: WARN
 MESSAGE: [grpclog.go:60] ["transport: http2Server.HandleStreams failed to read frame: read tcp 127.0.0.1:2382->127.0
.0.1:57031: use of closed network connection"]
3 rows in set (0.01 sec)
```

- TIME
- TYPE `information_schema.cluster_info` TYPE tidb/pd/tikv
- INSTANCE `information_schema.cluster_info` INSTANCE
- LEVEL
- MESSAGE

> select *from cluter_log where instance='tikv-1' tikv-1 message like regexp pattern regexp message grep pipeline select* from cluster_log where message like 'coprocessor%' and message regexp '*.slow.*' grep 'coprocessor' xxx.log | grep -E '*.slow.*'

TiDB 4.0 TiDB 4.0 region id region txn id key

# 3.2

TiDB 4.0

TiDB 4.0 `metrics_schema` SQL SQL

## 3.2.1

`tidb_query_duration` TiDB query P999P99P90

| | | |
|---|---|---|
| TIME | unsigned | query |
| INSTANCE | varchar(512) | query TiDB `IP:PORT` |
| SQL_TYPE | varchar(512) | query `Select` `internal` |
| QUANTILE | double unsigned | query |
| VALUE | double unsigned | `QUANTILE` |

SQL P90 TiDB Query `Select` Query P90 0.0384 `internal` P90 0.00327 `instance` TiDB

```
metrics_schema> select * from tidb_query_duration where value is not null and time=now() and quantile=0.90;
+---------------------+------------------+----------+----------+------------------+
| time                | instance         | sql_type | quantile | value            |
+---------------------+------------------+----------+----------+------------------+
| 2020-03-08 13:34:40 | 172.16.5.40:10089 | Select   | 0.9      | 0.0384           |
| 2020-03-08 13:34:40 | 172.16.5.40:10089 | internal | 0.9      | 0.00327692307692 |
+---------------------+------------------+----------+----------+------------------+
```

## 3.2.2

`information_schema.metrics_tables` SQL `select * from information_schema.metrics_tables`

| | | |
|---|---|---|
| TABLE_NAME | varchar(64) | metrics_schema |
| PROMQL | varchar(64) | SQL PromQL prometheus SQL PromQL |
| LABELS | varchar(64) | label label SQL PromQL |
| QUANTILE | double unsigned | 0 |
| COMMENT | varchar(256) | |

## 3.2.3

`PROMQL` TiDB SQL `PromQL` prometheus

SQL `MemTableScan` `PromQL` `start_time` `end_time` `step` 1 prometheus range query HTTP API

```
metrics_schema> desc select * from tidb_query_duration where value is not null and time=now() and quantile=0.90;
+------------------+----------+------+-----------------------------------------------------------------------------------------
-----------------------------------------------------------------------------------------------------------------------------------
---+
| id               | estRows  | task | operator info

   |
+------------------+----------+------+-----------------------------------------------------------------------------------------
-----------------------------------------------------------------------------------------------------------------------------------
---+
| Selection_5      | 8000.00  | root | not(isnull(Column#5))

   |
| └─MemTableScan_6 | 10000.00 | root | PromQL:histogram_quantile(0.9, sum(rate(tidb_server_handle_query_duration_seco
nds_bucket{}[60s])) by (le,sql_type,instance)), start_time:2020-03-08 13:13:15, end_time:2020-03-08 13:13:15, step:1m
0s |
+------------------+----------+------+-----------------------------------------------------------------------------------------
-----------------------------------------------------------------------------------------------------------------------------------
---+
```

SQL `Where` time 10

### 3.2.4 session

2 session session

- `tidb_metric_query_step` prometheus query_range startendstep step
- `tidb_metric_query_range_duration` PromQL PromQL $RANGE_DURATION 60

> range query prometheus query
>
> - query=: PromQL
> - start=:
> - end=:
> - step=: query resolution
> - timeout=:
>
> prometheus PromQL
>
> - [start, end] start step
> - start=10end=20step=2 ts=10ts=12ts=14ts=16ts=18ts=206 6 6

60

```
set @@session.tidb_metric_query_step=60
```

TiDB PD `prometheus` `prometheus` PD `prometheus` `instance` `sql_type` `['2020-03-08 13:23:00', '2020-03-08 13:33:00')` P99 avg, max, min

```
metrics_schema> select instance,sql_type, avg(value),max(value),min(value) from tidb_query_duration where time >= '20
20-03-08 13:23:00' and time < '2020-03-08 13:33:00' and value is not null and quantile=0.99 group by instance,sql_typ
e;
+-------------------+----------+-------------------+------------------+-------------------+
| instance          | sql_type | avg(value)        | max(value)       | min(value)        |
+-------------------+----------+-------------------+------------------+-------------------+
| 172.16.5.40:10089 | Select   | 0.00800917072138  | 0.00824108821892 | 0.00790462559176  |
| 172.16.5.40:10089 | internal | 0.012384          | 0.01554          | 0.0062            |
| 172.16.5.40:10089 | Insert   | 0.00687276884265  | 0.0069763539823  | 0.00670463917526  |
| 172.16.5.40:10089 | general  | 0.000923958333333 | 0.00133333333333 | 0.000666666666667 |
+-------------------+----------+-------------------+------------------+-------------------+
```

# 3.3

## 1.

3.1 3.2 TiDB 4.0 SQL `information_schema.cluster_config` `information_schema.cluster_info`

SQL TiDB 4.0

- `information_schema.inspection_result`
- `information_schema.inspection_summary`

SQL `select * from information_schema.inspection_result`

`warning` / `critical` `details`

## 2.

`information_schema.inspection_result`

```
mysql> desc inspection_result;
+-----------+--------------+------+------+---------+-------+
| Field     | Type         | Null | Key  | Default | Extra |
+-----------+--------------+------+------+---------+-------+
| RULE      | varchar(64)  | YES  |      | NULL    |       |
| ITEM      | varchar(64)  | YES  |      | NULL    |       |
| TYPE      | varchar(64)  | YES  |      | NULL    |       |
| INSTANCE  | varchar(64)  | YES  |      | NULL    |       |
| VALUE     | varchar(64)  | YES  |      | NULL    |       |
| REFERENCE | varchar(64)  | YES  |      | NULL    |       |
| SEVERITY  | varchar(64)  | YES  |      | NULL    |       |
| DETAILS   | varchar(256) | YES  |      | NULL    |       |
+-----------+--------------+------+------+---------+-------+
8 rows in set (0.00 sec)
```

- RULE `select * from inspection_rules where type='inspection'`
  - `config` warning
  - `version` `githash` critical
  - `current-load` warning
  - `critical-error` warning
  - `threshold-check`
- ITEM
- TYPE tidb/tikv/pd
- INSTANCE
- VALUE
- REFERENCE VALUE
- SEVERITYwarning/critical
- DETAILS SQL

```
mysql> select * from inspection_rules where type='inspection';
+-----------------+------------+---------+
| NAME            | TYPE       | COMMENT |
+-----------------+------------+---------+
| config          | inspection |         |
| version         | inspection |         |
| current-load    | inspection |         |
| critical-error  | inspection |         |
| threshold-check | inspection |         |
+-----------------+------------+---------+
5 rows in set (0.00 sec)
```

# 3.

Coprocessor 8 Coprocessor CPU 750% workload `information_schema.inspection_summary`

`information_schema.inspection_summary`

```
mysql> desc inspection_summary;
+--------------+-----------------------+------+------+---------+-------+
| Field        | Type                  | Null | Key  | Default | Extra |
+--------------+-----------------------+------+------+---------+-------+
| RULE         | varchar(64)           | YES  |      | NULL    |       |
| INSTANCE     | varchar(64)           | YES  |      | NULL    |       |
| METRICS_NAME | varchar(64)           | YES  |      | NULL    |       |
| LABEL        | varchar(64)           | YES  |      | NULL    |       |
| QUANTILE     | double unsigned       | YES  |      | NULL    |       |
| AVG_VALUE    | double(22,6) unsigned | YES  |      | NULL    |       |
| MIN_VALUE    | double(22,6) unsigned | YES  |      | NULL    |       |
| MAX_VALUE    | double(22,6) unsigned | YES  |      | NULL    |       |
+--------------+-----------------------+------+------+---------+-------+
8 rows in set (0.00 sec)
```

- RULE `select * from inspection_rules where type='summary'`
- INSTANCE
- METRIC_NAME
- QUANTILE QUANTILE `select * from inspection_summary where rule='ddl' and quantile in (0.80, 0.90, 0.99, 0.999)` ddl 80/90/99/999 AVG_VALUE/MIN_VALUE/MAX_VALUE

> :
>
> `information_summary` SQL rule `select * from inspection_summary` `select * from inspection_summary where rule in ('read-link', 'ddl')` DDL

# 4.

hint `select /*+ time_range('2020-03-07 12:00:00','2020-03-07 13:00:00') */ * from inspection_summary` `2020-03-07 12:00:00` - `2020-03-07 13:00:00`

```
mysql> SELECT
         t1.avg_value / t2.avg_value AS ratio,
         t1.*,
         t2.*
       FROM
         (
           SELECT
             /*+ time_range("2020-01-16 16:00:54.933", "2020-01-16 16:10:54.933")*/ *
           FROM inspection_summary WHERE rule='read-link'
         ) t1
         JOIN
         (
           SELECT
             /*+ time_range("2020-01-16 16:10:54.933","2020-01-16 16:20:54.933")*/ *
           FROM inspection_summary WHERE rule='read-link'
         ) t2
         ON t1.metrics_name = t2.metrics_name
         and t1.instance = t2.instance
         and t1.label = t2.label
       ORDER BY
         ratio DESC;
```

# 3.4

TiDB TiDB 4.0 `information_schema.metrics_summary` `information_schema.metrics_summary_by_label` `information_schema.metrics_summary_by_label` `label`

## 1.

`['2020-03-08 13:23:00', '2020-03-08 13:33:00')` TiDB 3 `information_schema.metrics_summary` `/*+ time_range() */` hint SQL

```
mysql> select /*+ time_range('2020-03-08 13:23:00','2020-03-08 13:33:00') */ *
       from information_schema.`METRICS_SUMMARY`
       where metrics_name like 'tidb%duration'
         and avg_value > 0
         and quantile = 0.99
       order by avg_value desc
       limit 3\G
***************************[ 1. row ]***************************
METRICS_NAME | tidb_get_token_duration
QUANTILE     | 0.99
SUM_VALUE    | 8.972509
AVG_VALUE    | 0.996945
MIN_VALUE    | 0.996515
MAX_VALUE    | 0.997458
COMMENT      |  The quantile of Duration (us) for getting token, it should be small until concurrency limit is reache
d(second)
***************************[ 2. row ]***************************
METRICS_NAME | tidb_query_duration
QUANTILE     | 0.99
SUM_VALUE    | 0.269079
AVG_VALUE    | 0.007272
MIN_VALUE    | 0.000667
MAX_VALUE    | 0.01554
COMMENT      | The quantile of TiDB query durations(second)
***************************[ 3. row ]***************************
METRICS_NAME | tidb_kv_request_duration
QUANTILE     | 0.99
SUM_VALUE    | 0.170232
AVG_VALUE    | 0.004601
MIN_VALUE    | 0.000975
MAX_VALUE    | 0.013
COMMENT      | The quantile of kv requests durations by store
```

> `tidb_get_token_duration` `COMMENT` us

`metrics_summary_by_label`

```
mysql> select /*+ time_range('2020-03-08 13:23:00','2020-03-08 13:33:00') */ *
       from information_schema.`METRICS_SUMMARY_BY_LABEL`
       where metrics_name like 'tidb%duration'
         and avg_value > 0
         and quantile = 0.99
       order by avg_value desc
       limit 10\G
***************************[ 1. row ]***************************
INSTANCE     | 172.16.5.40:10089
METRICS_NAME | tidb_get_token_duration
LABEL        |
QUANTILE     | 0.99
SUM_VALUE    | 8.972509
AVG_VALUE    | 0.996945
MIN_VALUE    | 0.996515
MAX_VALUE    | 0.997458
COMMENT      |  The quantile of Duration (us) for getting token, it should be small until concurrency limit is reache
d(second)
***************************[ 2. row ]***************************
INSTANCE     | 172.16.5.40:10089
METRICS_NAME | tidb_query_duration
LABEL        | Select
QUANTILE     | 0.99
SUM_VALUE    | 0.072083
AVG_VALUE    | 0.008009
MIN_VALUE    | 0.007905
MAX_VALUE    | 0.008241
COMMENT      | The quantile of TiDB query durations(second)
***************************[ 3. row ]***************************
INSTANCE     | 172.16.5.40:10089
METRICS_NAME | tidb_query_duration
LABEL        | Rollback
QUANTILE     | 0.99
SUM_VALUE    | 0.072083
AVG_VALUE    | 0.008009
MIN_VALUE    | 0.007905
MAX_VALUE    | 0.008241
COMMENT      | The quantile of TiDB query durations(second)
```

`metrics_summary_by_label` `metrics_summary` `LABEL` , 2, 3 `tidb_query_duration` `Select` / `Rollback`

# 2.

t1 baseline

- t1 : ("2020-03-03 17:08:00", "2020-03-03 17:11:00")
- t2 : ("2020-03-03 17:18:00", "2020-03-03 17:21:00")

METRICS_NAME join `/*+ time_range() */` hint

1. t1.avg_value / t2.avg_value 10

```
mysql> SELECT
         t1.avg_value / t2.avg_value AS ratio,
         t1.metrics_name,
         t1.avg_value,
         t2.avg_value,
         t2.comment
       FROM
         (
           SELECT /*+ time_range("2020-03-03 17:08:00", "2020-03-03 17:11:00")*/
             *
           FROM information_schema.metrics_summary
         ) t1
         JOIN
         (
           SELECT /*+ time_range("2020-03-03 17:18:00", "2020-03-03 17:21:00")*/
             *
           FROM information_schema.metrics_summary
         ) t2
         ON t1.metrics_name = t2.metrics_name
       ORDER BY
         ratio DESC limit 10;
+----------------+----------------------------------+-------------------+-------------------+-----------------------
--------------------------------------------------+
| ratio          | metrics_name                     | avg_value         | avg_value         | comment
                                                  |
+----------------+----------------------------------+-------------------+-------------------+-----------------------
--------------------------------------------------+
| 17.6439787379  | tikv_region_average_written_bytes |   30816827.0953   |    1746591.71568  | The average rate of wr
iting bytes to Regions per TiKV instance          |
|  8.88407551364 | tikv_region_average_written_keys  |     108557.034612 |      12219.283193 | The average rate of wr
itten keys to Regions per TiKV instance           |
|  6.4105335594  | tidb_kv_write_num                 |       4493.293654 |        700.923505 | The quantile of kv wri
te times per transaction execution                |
|  2.99993333333 | tidb_gc_total_count               |          1.0      |          0.333341 | The total count of kv
storage garbage collection time durations         |
|  2.66412165823 | tikv_engine_avg_seek_duration     |       6569.879007 |       2466.05818  | The time consumed when
 executing seek operation, the unit is microsecond |
|  2.66412165823 | tikv_engine_max_seek_duration     |       6569.879007 |       2466.05818  | The time consumed when
 executing seek operation, the unit is microsecond |
|  2.49994444321 | tikv_region_change                |         -0.277778 |         -0.111114 | The count of region ch
ange per TiKV instance                            |
|  2.16063829787 | etcd_wal_fsync_duration           |          0.002539 |          0.001175 | The quantile time cons
umed of writing WAL into the persistent storage   |
|  2.06089264604 | node_memory_free                  | 4541448192.0      | 2203631616.0      |
                                                  |
|  1.96749064186 | tidb_kv_write_size                |     514489.28     |     261495.159902 | The quantile of kv wri
te size per transaction execution                 |
+----------------+----------------------------------+-------------------+-------------------+-----------------------
--------------------------------------------------+
```

- t1 tikv_region_average_written_bytes region t2 17.6
- t1 tikv_region_average_written_keys region keys t2 8.8
- t1 tidb_kv_write_size tidb kv t2 1.96

t1 t2

1. t2.avg_value / t1.avg_value 10

```
mysql> SELECT
         t2.avg_value / t1.avg_value AS ratio,
         t1.metrics_name,
         t1.avg_value,
         t2.avg_value,
         t2.comment
       FROM
         (
           SELECT /*+ time_range("2020-03-03 17:08:00", "2020-03-03 17:11:00")*/
             *
           FROM information_schema.metrics_summary
         ) t1
         JOIN
         (
           SELECT /*+ time_range("2020-03-03 17:18:00", "2020-03-03 17:21:00")*/
             *
           FROM information_schema.metrics_summary
         ) t2
         ON t1.metrics_name = t2.metrics_name
       ORDER BY
         ratio DESC limit 10;
+----------------+----------------------------------------+----------------+------------------+---------------------
-----------------------------------------------------------------------+
| ratio          | metrics_name                           | avg_value      | avg_value        | comment
                                                                        |
+----------------+----------------------------------------+----------------+------------------+---------------------
-----------------------------------------------------------------------+
| 5865.59537065  | tidb_slow_query_cop_process_total_time  |       0.016333 |        95.804724 | The total time of Ti
DB slow query statistics with slow query total cop process time(second) |
| 3648.74109023  | tidb_distsql_partial_scan_key_total_num |   10865.666667 |  39646004.4394   | The total num of dis
tsql partial scan key numbers                                           |
|  267.002351165 | tidb_slow_query_cop_wait_total_time     |       0.003333 |         0.890008 | The total time of Ti
DB slow query statistics with slow query total cop wait time(second)    |
|  192.43267836  | tikv_cop_total_response_total_size      | 2515333.66667  | 484032394.445    |
                                                                        |
|  192.43267836  | tikv_cop_total_response_size            |   41922.227778 |   8067206.57408  |
                                                                        |
|  152.780296296 | tidb_distsql_scan_key_total_num         |    5304.333333 |    810397.618317 | The total num of dis
tsql scan numbers                                                       |
|  126.042290167 | tidb_distsql_execution_total_time       |       0.421622 |        53.142143 | The total time of di
stsql execution(second)                                                 |
|  105.164020657 | tikv_cop_scan_details                   |     134.450733 |     14139.379665 |
                                                                        |
|  105.164020657 | tikv_cop_scan_details_total             |    8067.043981 |    848362.77991  |
                                                                        |
|  101.635495394 | tikv_cop_total_kv_cursor_operations     |    1070.875    |    108838.91113  |
                                                                        |
+----------------+----------------------------------------+----------------+------------------+---------------------
-----------------------------------------------------------------------+
```

- t2 tidb_slow_query_cop_process_total_time tidb cop process t1 5865
- t2 tidb_distsql_partial_scan_key_total_numtidb distsql key t1 3648
- t2 tikv_cop_total_response_sizetikv cop t1 192
- t2 tikv_cop_scan_detailstikv cop scan t1 105

2 t2 Cop t2 TiKV Copprocessor cop task t2

t1 ~ t2 go-ycsb t2 20 tpch tpch cop

# 3.5 SQL

TiDB SQL SQL `information_schema.slow_query` TiDB TiDB 4.0 `information_schema.cluster_slow_query` TiDB

```
# Time: 2019-08-14T09:26:59.487776265+08:00
# Txn_start_ts: 410450924122144769
# User: root@127.0.0.1
# Conn_ID: 3086
# Query_time: 1.527627037
# Parse_time: 0.000054933
# Compile_time: 0.000129729
# Process_time: 0.07 Wait_time: 0.002 Backoff_time: 0.002 Request_count: 1 Total_keys: 131073 Process_keys: 131072 Pr
ewrite_time: 0.335415029 Commit_time: 0.032175429 Get_commit_ts_time: 0.000177098 Local_latch_wait_time: 0.106869448
Write_keys: 131072 Write_size: 3538944 Prewrite_region: 1
# DB: test
# Is_internal: false
# Digest: 50a2e32d2abbd6c1764b1b7f2058d428ef2712b029282b776beb9506a365c0f1
# Stats: t:414652072816803841
# Num_cop_tasks: 1
# Cop_proc_avg: 0.07 Cop_proc_p90: 0.07 Cop_proc_max: 0.07 Cop_proc_addr: 172.16.5.87:20171
# Cop_wait_avg: 0 Cop_wait_p90: 0 Cop_wait_max: 0 Cop_wait_addr: 172.16.5.87:20171
# Mem_max: 525211
# Succ: true
# Plan_digest: e5f9d9746c756438a13c75ba3eedf601eecf555cdb7ad327d7092bdd041a83e7
# Plan: tidb_decode_plan('ZJAwCTMyXzcJMAkyMAlkYXRhOlRhYmxlU2Nhbl82CjEJMTBfNgkxAR0AdAEY1Dp0LCByYW5nZTpbLWluZiwraW5mXSw
ga2VlcCBvcmRlcjpmYWxzZSwgc3RhdHM6cHNldWRvCg==')
insert into t select * from t;
```

(1)

- `Time`
- `Query_time`
- `Parse_time`
- `Compile_time`
- `Digest` SQL
- `Stats` table `pseudo`
- `Txn_start_ts` ID TiDB
- `Is_internal` TiDB SQL `true` TiDB SQL `false` SQL
- `Index_ids` ID
- `Succ`
- `Backoff_time` lockRegion tikv server is busy
- `Plan_digest` plan
- `Plan` `select tidb_decode_plan('...')`
- `Query` SQL `Query` `Query`

(2)

- `Prewrite_time` `prewrite`

- `Commit_time` commit
- `Get_commit_ts_time` commit commit
- `Local_latch_wait_time` commit TiDB
- `Write_keys` TiKV Write CF Key
- `Write_size` key value
- `Prewrite_region` prewrite TiKV Region Region

(3)

- `Memory_max` TiDB `byte`

(4)

- `User`
- `Conn_ID` ID `con:3` TiDB
- `DB` database

(5) TiKV Coprocessor Task

- `Process_time` SQL TiKV TiKV `Query_time`
- `Wait_time` TiKV TiKV Coprocessor Coprocessor
- `Request_count` Coprocessor
- `Total_keys` Coprocessor key
- `Process_keys` Coprocessor key `total_keys` `processed_keys` MVCC `processed_keys` `total_keys`
- `Cop_proc_avg` cop-task
- `Cop_proc_p90` cop-task P90
- `Cop_proc_max` cop-task
- `Cop_proc_addr` cop-task
- `Cop_wait_avg` cop-task
- `Cop_wait_p90` cop-task P90
- `Cop_wait_max` cop-task
- `Cop_wait_addr` cop-task

SQL TiDB

## Top N

SQL TiDB Top 2

```
> select query_time, query
    from information_schema.slow_query   --  TiDB
   where is_internal = false             --  TiDB
  order by query_time desc
  limit 2;
+--------------+-------------------------------------------------------------+
| query_time   | query                                                       |
+--------------+-------------------------------------------------------------+
| 12.77583857  | select * from t_slim, t_wide where t_slim.c0=t_wide.c0;     |
|  0.734982725 | select t0.c0, t1.c1 from t_slim t0, t_wide t1 where t0.c0=t1.c0; |
+--------------+-------------------------------------------------------------+
```

## Top N

SQL TiDB `test` Top 2

```
> select query_time, query, user
    from information_schema.cluster_slow_query  --  TiDB
  where is_internal = false
    and user = "test"
  order by query_time desc
  limit 2;
+-------------+-------------------------------------------------------------------+----------------+
| Query_time  | query                                                             | user           |
+-------------+-------------------------------------------------------------------+----------------+
| 0.676408014 | select t0.c0, t1.c1 from t_slim t0, t_wide t1 where t0.c0=t1.c1; | test           |
+-------------+-------------------------------------------------------------------+----------------+
```

Top N  SQL

```
--  Top N  SQL
> select query_time, query, digest
    from information_schema.cluster_slow_query
   where is_internal = false
  order by query_time desc
  limit 1;
+-------------+----------------------------+-------------------------------------------------------------------+
| query_time  | query                      | digest                                                            |
+-------------+----------------------------+-------------------------------------------------------------------+
| 0.302558006 | select * from t1 where a=1; | 4751cb6008fda383e22dacb601fde85425dc8f8cf669338d55d944bafb46a6fa |
+-------------+----------------------------+-------------------------------------------------------------------+

--  SQL
> select query, query_time
    from information_schema.cluster_slow_query
   where digest = "4751cb6008fda383e22dacb601fde85425dc8f8cf669338d55d944bafb46a6fa";
+----------------------------+-------------+
| query                      | query_time  |
+----------------------------+-------------+
| select * from t1 where a=1; | 0.302558006 |
| select * from t1 where a=2; | 0.401313532 |
+----------------------------+-------------+
```

## pseudo

`pseudo` TiDB  `analyze table` SQL

```
> select query, query_time, stats
    from information_schema.cluster_slow_query
  where is_internal = false
    and stats like '%pseudo%';
+----------------------------+-------------+--------------------------------+
| query                      | query_time  | stats                          |
+----------------------------+-------------+--------------------------------+
| select * from t1 where a=1; | 0.302558006 | t1:pseudo                      |
| select * from t1 where a=2; | 0.401313532 | t1:pseudo                      |
| select * from t1 where a>2; | 0.602011247 | t1:pseudo                      |
| select * from t1 where a>3; | 0.50077719  | t1:pseudo                      |
| select * from t1 join t2;   | 0.931260518 | t1:407872303825682445,t2:pseudo |
+----------------------------+-------------+--------------------------------+
```

SQL  SQL

```
> select count(distinct plan_digest) as count, digest,min(query)
    from information_schema.cluster_slow_query
  group by digest
  having count>1
  limit 3\G
***************************[ 1. row ]***************************
count      | 2
digest     | 17b4518fde82e32021877878bec2bb309619d384fca944106fcaf9c93b536e94
min(query) | SELECT DISTINCT c FROM sbtest25 WHERE id BETWEEN ? AND ? ORDER BY c [arguments: (291638, 291737)];
***************************[ 2. row ]***************************
count      | 2
digest     | 9337865f3e2ee71c1c2e740e773b6dd85f23ad00f8fa1f11a795e62e15fc9b23
min(query) | SELECT DISTINCT c FROM sbtest22 WHERE id BETWEEN ? AND ? ORDER BY c [arguments: (215420, 215519)];
***************************[ 3. row ]***************************
count      | 2
digest     | db705c89ca2dfc1d39d10e0f30f285cbbadec7e24da4f15af461b148d8ffb020
min(query) | SELECT DISTINCT c FROM sbtest11 WHERE id BETWEEN ? AND ? ORDER BY c [arguments: (303359, 303458)];

--  SQL
> select min(plan),plan_digest
    from information_schema.cluster_slow_query
  where digest='17b4518fde82e32021877878bec2bb309619d384fca944106fcaf9c93b536e94'
  group by plan_digest\G
*************************** 1. row ***************************
  min(plan):    Sort_6                  root    100.00131380758702      sbtest.sbtest25.c:asc
        └─HashAgg_10            root    100.00131380758702      group by:sbtest.sbtest25.c, funcs:firstrow(sbtest.sbt
est25.c)->sbtest.sbtest25.c
          └─TableReader_15      root    100.00131380758702      data:TableRangeScan_14
            └─TableScan_14      cop     100.00131380758702      table:sbtest25, range:[502791,502890], keep order:fal
se
plan_digest: 6afbbd21f60ca6c6fdf3d3cd94f7c7a49dd93c00fcf8774646da492e50e204ee
*************************** 2. row ***************************
  min(plan):    Sort_6                  root    1                       sbtest.sbtest25.c:asc
        └─HashAgg_12            root    1                       group by:sbtest.sbtest25.c, funcs:firstrow(sbtest.sbt
est25.c)->sbtest.sbtest25.c
          └─TableReader_13      root    1                       data:HashAgg_8
            └─HashAgg_8         cop     1                       group by:sbtest.sbtest25.c,
              └─TableScan_11    cop     1.2440069558121831      table:sbtest25, range:[472745,472844], keep order:fal
se
```

SQL TiDB

```
> select instance, count(*)
    from information_schema.cluster_slow_query
   where time >= "2020-03-06 00:00:00"
     and time < now()
  group by instance;
+---------------+----------+
| instance      | count(*) |
+---------------+----------+
| 0.0.0.0:10081 | 124      |
| 0.0.0.0:10080 | 119771   |
+---------------+----------+
```

`2020-03-10 13:24:00` `2020-03-10 13:27:00` QPS SQL

```
> select * from
    (select /*+ AGG_TO_COP(), HASH_AGG() */ count(*),
         min(time),
         sum(query_time) AS sum_query_time,
         sum(Process_time) AS sum_process_time,
         sum(Wait_time) AS sum_wait_time,
         sum(Commit_time),
         sum(Request_count),
         sum(process_keys),
         sum(Write_keys),
         max(Cop_proc_max),
         min(query),min(prev_stmt),
         digest
    from information_schema.cluster_slow_query
    where time >= '2020-03-10 13:24:00'
      and time < '2020-03-10 13:27:00'
      adn Is_internal = false
    group by  digest) AS t1
  where t1.digest not in
    (select /*+ AGG_TO_COP(), HASH_AGG() */ digest
    from information_schema.cluster_slow_query
    where time >= '2020-03-10 13:20:00' --  `2020-03-10 13:20:00` ~ `2020-03-10 13:23:00`
      and time < '2020-03-10 13:23:00'
   group by  digest)
  order by t1.sum_query_time desc
  limit 10\G
***************************[ 1. row ]***************************
count(*)           | 200
min(time)          | 2020-03-10 13:24:27.216186
sum_query_time     | 50.114126194
sum_process_time   | 268.351
sum_wait_time      | 8.476
sum(Commit_time)   | 1.044304306
sum(Request_count) | 6077
sum(process_keys)  | 202871950
sum(Write_keys)    | 319500
max(Cop_proc_max)  | 0.263
min(query)         | delete from test.tcs2 limit 5000;
min(prev_stmt)     |
digest             | 24bd6d8a9b238086c9b8c3d240ad4ef32f79ce94cf5a468c0b8fe1eb5f8d03df
```

# 3.6 processlist

processlist TiDB

## 3.6.1 processlist

3 processlist

### 1. SQL: `SHOW [FULL] PROCESSLIST`

TiDB

```
SHOW FULL PROCESSLIST;
```

```
+------+--------+-----------+--------+-----------+--------+---------+-----------------------+
| Id   | User   | Host      | db     | Command   | Time   | State   | Info                  |
|------+--------+-----------+--------+-----------+--------+---------+-----------------------|
| 1    | root   | 127.0.0.1 | <null> | Sleep     | 127    | 2       | <null>                |
| 3    | root   | 127.0.0.1 | <null> | Sleep     | 75     | 2       | <null>                |
| 5    | root   | 127.0.0.1 | <null> | Query     | 0      | 2       | show full processlist |
+------+--------+-----------+--------+-----------+--------+---------+-----------------------+
```

- Id TiDB `KILL TiDB {ID}` Id
- User
- Host
- db null
- CommandSleepQuery
- Time
- StatesqlSending dataSorting for groupCreating tmp tableLocked
- Info NULL

`FULL`

### 2. `INFORMATION_SCHEMA.PROCESSLIST`

`show processlist` `MEM` `TxnStart`

```
* `MEM` byte v3.0.5
* `TxnStart` v4.0.0
```

```
select *
from information_schema.processlist
where command != 'Sleep'
order by time desc\G
```

```
*************************** 1. row ***************************
      ID: 1
    USER: root
    HOST: 172.16.5.169
      DB: NULL
 COMMAND: Query
    TIME: 0
   STATE: 2
    INFO: select * from information_schema.processlist where command != 'Sleep' order by time desc
     MEM: 4588
TxnStart:
1 row in set (0.00 sec)
```

### 3. `INFORMATION_SCHEMA.CLUSTER_PROCESSLIST`

TiDB `INFORMATION_SCHEMA.PROCESSLIST` TiDB TiDB 4.0 `INFORMATION_SCHEMA.CLUSTER_PROCESSLIST` TiDB `PROCESSLIST` `PROCESSLIST` `CLUSTER_PROCESSLIST` `PROCESSLIST` `INSTANCE` TiDB

```
SELECT * FROM INFORMATION_SCHEMA.CLUSTER_PROCESSLIST\G
```

```
*************************** 1. row ***************************
INSTANCE: 172.16.4.235:10070
      ID: 1
    USER: root
    HOST: 172.16.5.169
      DB: NULL
 COMMAND: Query
    TIME: 0
   STATE: 2
    INFO: SELECT * FROM INFORMATION_SCHEMA.CLUSTER_PROCESSLIST
     MEM: 0
TxnStart: 04-12 16:51:39.735(415939035066531841)
*************************** 2. row ***************************
INSTANCE: 172.16.5.189:10070
      ID: 1
    USER: root
    HOST: 172.16.5.169
      DB: NULL
 COMMAND: Sleep
    TIME: 6
   STATE: 2
    INFO: NULL
     MEM: 0
TxnStart:
2 rows in set (0.00 sec)
```

> : root `ProcessPriv` User User User

## 3.6.2 KILL [TIDB]

`KILL TIDB` TiDB

### KILL

TiDB KILL xxx MySQL TiDB TIDB KILL TIDB xxx TiDB `compatible-kill-query = true` TIDB

### KILL

Ctrl+C MySQL KILL TiDB TiDB TiDB TiDB KILL KILL compatible-kill-query TiDB `compatible-kill-query = true`

## KILL

```
SHOW PROCESSLIST;
```

```
+------+--------+-----------+--------+-----------+--------+---------+-----------------------+
| Id   | User   | Host      | db     | Command   | Time   | State   | Info                  |
|------+--------+-----------+--------+-----------+--------+---------+-----------------------|
| 5    | root   | 127.0.0.1 | <null> | Query     | 0      | 2       | show full processlist |
+------+--------+-----------+--------+-----------+--------+---------+-----------------------+
```

```
KILL TIDB 5;
```

```
Query OK, 0 rows affected (0.00 sec)
```

ID 5 kill

# 3.6.3 INFORMATION_SCHEMA.PROCESSLIST

`show full processlist` `state` `Sleep` `select` `PROCESSLIST`

```
--  Sleep
select *
from information_schema.processlist
where command != 'Sleep'
order by time desc \G
```

info SQL

```
*************************** 1. row ***************************
      ID: 1
    USER: root
    HOST: 172.16.5.169
      DB: NULL
 COMMAND: Query
    TIME: 0
   STATE: 2
    INFO: select *
from information_schema.processlist
where command != 'Sleep'
order by time desc
     MEM: 4588
TxnStart:
1 row in set (0.00 sec)
```

SQL `EXPLAIN ANALYZE` SQL `EXPLAIN ANALYZE` EXPLAIN SQL

TiDB 10 SQL

```
--  Sleep  top10
select *
from information_schema.processlist
where command != 'Sleep'
order by mem desc
limit 10 \G
```

```
*************************** 1. row ***************************
      ID: 1
    USER: root
    HOST: 172.16.5.169
      DB: NULL
 COMMAND: Query
    TIME: 0
   STATE: 2
    INFO: select *
from information_schema.processlist
where command != 'Sleep'
order by mem desc
limit 10
     MEM: 4588
TxnStart:
1 row in set (0.00 sec)
```

SQL `EXPLAIN ANALYZE` SQL

command time ID kill ID kill concat() kill

```
-- 2 sleep  kill
select concat('kill ', 'TiDB', id, ';')
from information_schema.processlist
where command != 'Sleep'
and time > 2*60
order by time desc
```

```
-- 2 sleep  kill
select *
from information_schema.processlist
where command != 'Sleep'
and time > 2*60
order by time desc
```

```
+------+--------+--------+------+-----------+--------+---------+--------+-------+------------+
| ID   | USER   | HOST   | DB   | COMMAND   | TIME   | STATE   | INFO   | MEM   | TxnStart   |
|------+--------+--------+------+-----------+--------+---------+--------+-------+------------|
+------+--------+--------+------+-----------+--------+---------+--------+-------+------------+
```

## 3.6.4 INFORMATION_SCHEMA.CLUSTER_PROCESSLIST

`INFORMATION_SCHEMA.CLUSTER_PROCESSLIST` TiDB 2

```
select instance, count(*)
from INFORMATION_SCHEMA.CLUSTER_PROCESSLIST
where command != 'Sleep'
and time > 2*60
group by instance;
```

```
+---------------+----------+
| instance      | count(*) |
+---------------+----------+
| 0.0.0.0:10081 | 1        |
| 0.0.0.0:10080 | 3        |
+---------------+----------+
```

`EXPLAIN ANALYZE` SQL

## 3.6.5 MySQL

- KILL TIDB TiDB TiDB `compatible-kill-query = true`
- TiDB `State` TiDB GO
- TiDB `show processlist` MySQL `show processlist` ID session ID TiDB `show processlist` MySQL `show processlist`
  - TiDB tidb-server SQL TiDB MySQL tidb-servershow processlist tidb-server session session MySQL show processlist MySQL SQL

# 3.7 Statement Summary

2.2 TiDB Dashboard Statements Statements Statement Summary

## 3.7.1 Statement Summary

Statement Summary "Dynamic Performance Views" "Profile Tables" "SQL Audit" SQL

SQL TiDB 4.0 Statement Summary Tables MySQL

Statement Summary SQL TiDB

### 3.7.1.1 “ SQL ”

SQL SQL SQL

```
select * from `order` where item_id=1000;

SELECT *
FROM `order`
WHERE item_id=1001;
```

SQL SQL SQL

SQL SQL

IndexLookup TableScan

### 3.7.1.2

TiDB 4.0 60

- SQL
- TiDB
- TiKV CopTask
-

slow log

```
mysql> select * from events_statements_summary_by_digest limit 1\G
*************************** 1. row ***************************
       SUMMARY_BEGIN_TIME: 2020-03-04 13:00:00
         SUMMARY_END_TIME: 2020-03-04 13:30:00
                 STMT_TYPE: select
               SCHEMA_NAME: test
                    DIGEST: d8cc0047ec3514d418e6f425d6203966de0094f025dab14babab8f4db0947736
               DIGEST_TEXT: select buyer_id , item_id from order where order_id = ?
               TABLE_NAMES: test.order
               INDEX_NAMES: NULL
               SAMPLE_USER: root
                EXEC_COUNT: 8
               SUM_LATENCY: 2591978
               MAX_LATENCY: 1345860
               MIN_LATENCY: 135860
               AVG_LATENCY: 323997
        AVG_PARSE_LATENCY: 69993
        MAX_PARSE_LATENCY: 78761
      AVG_COMPILE_LATENCY: 137604
      MAX_COMPILE_LATENCY: 881880
……
                   AVG_MEM: 0
                   MAX_MEM: 0
        AVG_AFFECTED_ROWS: 0
               FIRST_SEEN: 2020-03-04 13:20:55
                LAST_SEEN: 2020-03-04 13:21:24
        QUERY_SAMPLE_TEXT: select buyer_id, item_id from `order` where order_id=1001221
         PREV_SAMPLE_TEXT:
               PLAN_DIGEST: 28ccfb38e96b6e4eaab31e82d12f349eb4edcb97bed3be49cb3f73051f2cd9d2
                      PLAN:     Point_Get_1    root    1    table:order, handle:1001221
1 row in set (0.00 sec)
```

### 3.7.1.3

`events_statements_summary_by_digest`

TiDB `events_statements_summary_by_digest_history` `events_statements_summary_by_digest` `SUMMARY_BEGIN_TIME` `SUMMARY_END_TIME`

24

## 3.7.2

SQL Statement Summary

### 3.7.2.1

SQL 10ms Grafana

`QUERY_SAMPLE_TEXT`

```
mysql> select avg_latency, query_sample_text from events_statements_summary_by_digest where QUERY_SAMPLE_TEXT LIKE 's
elect buyer_id, item_id from `order`%'\G
*************************** 1. row ***************************
      avg_latency: 202225
query_sample_text: select buyer_id, item_id from `order` where order_id=1001221
1 row in set (0.00 sec)
```

`avg_latency` 0.2ms 10ms

### 3.7.2.2

SQL

```
mysql> select sum_latency, query_sample_text, digest
    ->     from events_statements_summary_by_digest
    ->     where summary_begin_time='2020-3-1 3:00:00'
    ->     order by sum_latency desc limit 3\G
*************************** 1. row ***************************
      sum_latency: 120663574508
query_sample_text: select buyer_id, item_id from `order` where order_id=1001221
           digest: d8cc0047ec3514d418e6f425d6203966de0094f025dab14babab8f4db0947736
*************************** 2. row ***************************
      sum_latency: 97252462621
query_sample_text: select count(1) from item
           digest: 1626b9d694faefc4e88ae9fd5e8917e85ed26fe62dbe781eb65edad3aa939ae8
*************************** 3. row ***************************
      sum_latency: 65914323442
query_sample_text: select count(1) from buyer
           digest: b07c73323c511d3c18407771adb8aec865c0409f4e9a4f53baedc409fd5a1cd0
3 rows in set (0.00 sec)
```

SQL

`digest` SQL ID `digest`

### 3.7.2.3

SQL 10 2

SQL

```
mysql> select abnormal.avg_latency/normal.avg_latency,
    -> abnormal.avg_process_time/normal.avg_process_time,
    -> abnormal.avg_total_keys/normal.avg_total_keys,
    -> abnormal.avg_wait_time/normal.avg_wait_time
    -> from events_statements_summary_by_digest_history abnormal,
    -> events_statements_summary_by_digest_history normal
    -> where normal.summary_begin_time='2020-3-1 10:00:00'
    -> and abnormal.summary_begin_time='2020-3-1 14:00:00'
    -> and abnormal.digest=normal.digest
    -> and normal.digest = 'd8cc0047ec3514d418e6f425d6203966de0094f025dab14babab8f4db0947736'\G
*************************** 1. row ***************************
          abnormal.avg_latency/normal.avg_latency: 6.3433
abnormal.avg_process_time/normal.avg_process_time: 8.9993
    abnormal.avg_total_keys/normal.avg_total_keys: 12.6666
      abnormal.avg_wait_time/normal.avg_wait_time: 0.9883
1 row in set, 1 warning (0.00 sec)
```

`avg_total_keys` TiKV `avg_process_time` TiKV GC

## 3.7.3

Statement Summary

- `tidb_enable_stmt_summary`
- `tidb_stmt_summary_refresh_interval`
- `tidb_stmt_summary_history_size`
- `max-stmt-count` SQL
- `max-sql-length` SQL

## 3.7.4 FAQ

Statement Summary

### 3.7.4.1

Q SQL `tidb_stmt_summary_history_size` `max-stmt-count`

A Statement Summary Tables TiDB server

### 3.7.4.2 commit

Q TiDB commit commit

A commit `prev_sample_text` digest commit commit

### 3.7.4.3 `schema_name`

QSQL `schema_name`

A `schema_name` schema schema `use db` db `table_names` "{schema}.{table}" schema `table_names`

### 3.7.4.4

QStatement Summary SQL

ASysbench TPCC 2% TiDB 2% 4.0

# 4 TiDB

## TiDB

TiDB Prometheus Grafana

## Prometheus TiDB

Prometheus Prometheus

Prometheus TiDB

- Prometheus Server
- Client Metric
- Alertmanager

## Grafana TiDB

Grafana metric TiDB Grafana TiDB

TiDB TiDB TiDB

# 4.1

TiDB

TiDB TiDB SQL

# 1. TiDB

- TiDB Server MySQL session token Connection Count TiDB TiDB 500
- session TiDB SQL Parse TiDB Executor/Parse Duration 10ms
- TiDB CompileExecutor/Compile Duration
- Executor
  - DML TiDB Transaction Commit TiKV

    - TiDB DistSQL TiKV region
    - TiDB TiKV KV Request/KV Request Duration 99 by type
- TiDB PD TSO PD TiDB
    - channel PD Client/PD TSO Wait Duration
    - TiDB PD PD Client/PD TSO RPC duration

# 2. TiKV

-
- TiKV 6 gRPCSchedulerraftstoreapplystorage-readpool coprocessor-readpool
    - gRPC TiKV
        - scheduler
        - kv get kv batch get storage-readpool
        - TiDB DistSQL Coprocessor coprocessor-readpool 4.0 storage-readpool coprocessor-readpool
        - PD region raftstore
    - scheduler key-value raftstore
        - scheduler Scheduler-/Scheduler command durationPrewrite Scheduler-prewrite
        - raft RocksDB Storage/async write duration
    - raftstore raft apply
        - raftstore Raft IO/Commit log durationraft Raft Propose/Propose wait duration
    - apply scheduler key-value RocksDB gRPC
        - apply Raft IO/Apply log duration RocksDB Raft Propose/Apply wait duration
    - storage-readpool kv get kv batch get
    - coprocessor-readpool
- TiKV RocksDB raftstore raft raft TiKV
- 8.2.1 TiKV

# 3. RocksDB

RocskDB TiDB

- RocksDB
    - Memtable Memtable
        - Memtable Block-Cache
        - Block-Cache 45%
    - WAL Write Ahead Log logfile Memtable
    - SST Memtable SST logfile log
        - SST
        - Compaction

# 4.2 TiDB

CPU IOPS TiDB

1.
2.
3.

## 4.2.1

SQL TiKV Key-Value Schema

1. TiKV Key-Value
2. TiKV Key-Value
3. TiDB
4. TiDB Key-Value Schema
5. TiDB

SQL

### (1) TiKV Key-Value

TiKV RocksDB TiKV Query KV RocksDB SnapshotSnapshot RocksDB DB Snapshot Get KV Iterator

### Point-lookup: Get(key)

“P” L0 value

1. Memtable SST
2. L0 key key key L0 L0
3. SST
   - SST Index Block Key Block
   - Block Bloom filter Key
     - Bloom filter false key block
     - Bloom filter ture key block
4. Index Block key Block SST Block

5. Data Block value

## Range-lookup: Iterator

Iterator Iterator Iterator LSM-tree

1. MemTableMutable / Immutable

2. Block (Index Block / Data Block)RocksDB TwoLevelIterator SST File first_level_iter Index Block second_level_iter Data Block

Point-lookup Range-lookup SST File Data Block point get, Memtable SST KV IO SST File Data Block IO RocksDB Block Cache Key-Value

1. Block Cache Memory

   a. Block cache sizeblock cache shared-block-cache CF block cache b. Block cache hitblock cache c. Block c flow block cache d. Block cache operations block cache

2. SST Files IO

   a. SST read duration SST

3. Key CPU

   a. RocksDB CPURocksDB CPU

Key-Value Block cache size SST File IO CPU

Block cache Block cache flow Block cache operations Block cache

## (2) TiKV Key-Value

TiDB gRPC kv_get / kv_batch_get / coprocessor

- gRPC message count gRPC
- gRPC message failed gRPC
- gRPC message durationgRPC
- gRPC poll CPUgRPC CPU gRPC CPU IO gRPC gRPC

TiDB 4.0 kv_get / kv_batch_get / coprocessor Storage read threads pool (kv_get / kv_batch_get ) Coprocessor threads pool (coprocessor ) TiDB 4.0 Unified Read Pool

## Storage read threads pool

kv_get / kv_batch_get gRPC FuturePool FuturePool Pool

1. RocksDB Snapshot
2. Snapshot Point-lookup Key-Value

Snapshot Snapshot KV Storage read threads pool

- Storage async snapshot duration get RocksDB->GetSnapshot() + Snapshot->Get(key)
- Storage command total get
- Storage ReadPool CPU CPU

CPU CPU Storage async snapshot duration Snapshot Snapshot KV

## Coprocessor threads pool

Coprocessor

1. TiKV coprocessor Coprocessor
2. Coprocessor Snapshot
3. Snapshot Handler

Coprocessor

1. Coprocessor CPU CPU
2. Wait duration + Snapshot + Handler max / .99 / .95
   a. IO CPU CPU b. Handler CPU c. Snapshot CP
3. Handle duration Handler Handle
   a. CPU CPU CPU b. TableScan / IndexScan Snapshot Range-lookup CPU Handle duration Range-lookup

- Total Request errors
- Total DAG executorsDAG executor TableScan CPU
- Total KV Cursor Operations scan key Scan keys
- Total Ops Details (Table Scan)table scan Snapshot Iterator
- Total Ops Details (Index Scan)index scan Snapshot Iterator
- Total RocksDB Perf Statistics scan perf RocksDB operation

## Unified Read Pool

TiDB 4.0 (yatp, yet another thread pool) Unified Read Pool

Unified Read Pool Unified Read Pool

- Unified ReadPool CPU CPU

- Time used by level level CPU
- Running tasks

## (3) TiDB

TiKV KV SQL TiKV KV

1. Socket SQL
2. Token
3. PD TSO ( tsFuture tsFuture TSO)
4. Parser SQL parse AST
5. AST compile Validator / LogicalPlanOptimizer / PhysicalPlanOptimizer / Executor builder Compile duration
6. 

   a. Executor.Open() Executor SQL Key TiKV distsql API TiKV b. Executor.Next() Executc Executor

1. QPS
2. DurationSQL
3. Get Token Duration Token
4. Parse DurationSQL
5. Compile Duration SQL AST
6. Execution DurationSQL

1. Parse Duration / Compile Duration CPU CPU insert ... values Compile
2. Get Token Duration SQL TokenLimiter Token
3. Execution Duration Executor
4. TSO

## TSO

TSO

TiDB PD PD Client Store PD TSO

1. TSO channel channel TSO PD TSO channel batch
2. TSO

TSO

1. TSO channel GetTSAsync tsFuture
2. TSO channel PD RPC TSO TSO
3. TSO tsFuture TSO tsFuture.Wait()

channel GetTSAsync channel RPC RPC Duration

- PD TSO RPC Duration PD RPC
  - TiDB PD
  - PD TSO RPC
- PD TSO Wait Duration tsFuture Parse Compile tsFuture.Wait() PD TSO RPC

TSO

TSO RPC Duration TSO TSO SQL Parse + CompileParse + Compile tsFuture TSO TSO Async Duration = Parse + Compile Duration

- CASE 1TSO RPC Duration >= Parse + Compile Duration Wait TSO  RPC  TSO TSO Wait Duration > 0
- CASE 2TSO RPC Duration < Parse + Compile Duration  tsFuture.Wait()  RPC  TSO Wait Duration = 0

## DistSQL

distsql API

1. Build Request
2. Send Request
3. Recv Response
4. Decode Response

Build Request / Decode Response Send Request / Recv Response  Send Request  Recv Response

1. Send Request

a. Key  RegionCache  Region copTask  b. copIteratorWorker goroutine  c. copIteratorTaskSender gorouti
copIteratorWorker  copTask TiKV  gRPC

1. Recv Response

   a.

   b.

Send Request Recv Response

- DistSQL
  - Distsql DurationDistsql
  - Distsql QPSDistsql
  - Distsql Partial QPS Partial Results
  - Scan Keys Num Query Key
  - Scan Keys Partial Num Partial Result Key
  - Partial Num SQL Partial Results
- KV Request
  - KV Request Duration 999 by storeKV Request TiKV
  - KV Request Duration 999 by typeKV Request
  - KV Request OPSKV
- Transaction
  - Transaction OPS
  - Transaction Regions Num 90 Region
  - Transaction Max Write Size Bytes
  - Transaction Max Write KV Num Key-Value
  - Load SafePoint OPS SafePoint

TiKV

1. Region Region Backoff (sleep ) a. Region Region b. Region leader Leader
2. Key Resolve lock
3.

KV Errors

- KV Backoff Duration
- TiClient Region Error OPSTiKV Region
- KV Backoff OPSTiKV
- Lock Resolve OPS
- Other Errors OPS SafePoint

## (4) TiDB Key-Value Schema

TiDB Key-Value

1. Coprocessor chunk
2. Get / Batch Get Key-Value

Coprocessor chunk value column Get / Batch Get Key-Value encode decode

### (5) TiDB

Socket

# 4.2.2

SQL Schama Key-Value Key-Value TiKV TiDB Executor Executor TableReaderExecutor / IndexReaderExecutor / IndexLookupExecutor Exceutor distsql API Executor Insert / Update / Delete 2PC

1. TiDB 2PC
2. TiKV Scheduler
3. TiKV Raftstore

## (2)

Insert / Update / Delete Key-Value In-Memory Buffer

1.
2.

Key Value Key-Value Key-Value

In-Memory Buffer Key-Value tikv client TiKV

1. Prewrite
2. Commit

Transaction TSO start_ts Prewrite Commit TSO commit_ts

tidb commit transaction
client
tidb
pd
tikv
begin
get tso as start_ts
loop
[do sql]
alt
[do read]
do read
[do write]
do write in memory.
commit
group keys by region.
opt
[Do prewrite]
loop
[prewrite to each region in parallel.]
do prewrite
prewrite error
opt
[key is locked]
try to reslove lock
opt
[if resolve lock failed, restart 2pc]
[if resolve lock success, retry prewrite.]
[if write conflict(start_ts is time out)]
restart 2pc.
[unknow error]
return error.
get tso as commit_ts
opt
[do commit]
commit primary key
opt
[commit primary failed]
rollback all keys.
opt
[lock not exist(may rollbacked by other thread)]
restart 2pc
[unknow error]
return error.
loop
[async prewrite secondary key in parallel.]
return ok
client
tidb
pd
tikv
www.websequencediagrams.com

### (3)

```
[txn-local-latches]
enabled = true
capacity = 2048000
```

Prewrite

- Local Latch Wait Duration

### (4)

Distsql

- Transaction
  - Transaction OPS
  - Duration Latches Latches
  - Transaction Retry Num
  - Transaction Statement Num SQL
  - Session Retry Error OPS
  - KV Transaction OPS
  - Transaction Regions Num 90 Region
  - Transaction Max Write Size Bytes
  - Transaction Max Write KV Num Key-Value
- KV Errors
  - KV Backoff DurationKV
  - TiClient Region Error OPSTiKV Region
  - KV Backoff OPSTiKV
  - Lock Resolve OPS

TiDB 2PC TiKV

## (5) TiKV Scheduler

## Scheduler

Scheduler

```
1.  Latches
2.  /
```

Latches TiDB Prewrite Commit Key-Value Key Scheduler

1. Snapshot
2. Snapshot PrewriteCommit Resolve Lock

Prewrite Commit

1. Prewrite

   a. Keyload lock key key KeyIsLocked b. key c. Key Key Key raftstore

2. Commit

   a. Keyload lock lock key Prewrite TxnLockNotFound Value b. Key-Value raftstore

1. Scheduler CPU
2. Command
3. 
4. Snapshot
5. Load lock
6. 
7. Scheduler

## Scheduler

- gRPC
  - gRPC duration TiKV Prewrite / Commit TiKV gRPC duration TiDB KV duration gRPC duration TiDB KV duration TiDB TiKV TiDB TiKV TiDB TiKV Schduler Duration gRPC duration gRPC Scheduler Scheduler
- Scheduler
  - Scheduler stage total
  - Scheduler priority commands
  - Scheduler pending commands TiKV pending
  - Scheduler duration latch-wait duration + async-snapshot duration + load lock (all keys total) + async-write duration
  - Scheduler worker CPUscheduler worker CPU
  - Scheduler latch wait durationlatch wait
    - key key region key prewritecommit acquire-pessimistic-lock raft latch
  - Scheduler keys readcommit key
  - Scheduler keys writtencommit key
  - Scheduler scan details commit CF key
  - Scheduler scan details [lock] commit lock CF key
  - Scheduler scan details [write] commit write CF key
  - Scheduler scan details [default] commit default CF key
- Storage
  - Storage async-snapshot duration raft snapshot snapshot
  - Storage async-write durationraft Raftstore

Schduler Snapshot Raftstore Scheduler Snapshot Scheduler worker CPU CPU Raftstore

## (6) TiKV Raftstore

Raftstore TiKV Region Raftstore Raft Region Key-Value RocksDB

Raftstore Write Raft Log Apply Raft Log

1. IO RocksDB
   - Raft RocksDB Raft
   - KV RocksDB Key-Value
2. CPU
   - raft
   - apply
3. Networkleader follower

PeerMsg::RaftCommand Key-Value RaftCommand Router raft raft Raft Raft RocksDB Peerapply KV RocksDB

TiKV dashboard Raft IO / Raft process / Raft messages / Raft propose

- Thread CPU
  - Raft store CPUraft CPU 80%
  - Async apply CPUapply CPU 90%
- Raft propose
  - Raft proposals per ready mio tick Region proposal
  - Raft read/write proposals proposal

  - Propose wait duration raftstore raftstore raftstore append log raftstore
  - Apply wait durationcommitted raft log apply apply apply log apply apply CPU
  - Raft log speedpeer propose
- Raft IO
  - Apply log durationRaft apply raft log apply log kvdb
  - Append log durationRaft append raft log raft log raftdb 50ms Raft RocksDB
  - Commit log durationRaft
- Raft message
  - Sent messages per server TiKV Raft
  - Flush messages per server TiKV Raft
  - Receive messages per server TiKV Raft
  - Messages Raft
  - VoteRaft
  - Raft dropped messages Raft

## (7) RocksDB Titan

TiKV RocksDB TiKV RocksDB

- Raft RocksDB Raft Log
- KV RocksDB KV Region

RocksDB LSM-tree level

1. Memtable WAL
   - Memtable size CF memtable
   - WAL sync operationssync WAL
   - WAL sync durationsync WAL
   - Write operationswrite
   - Write durationwrite
   - Write flow
2. Memtable Immutable Memtable level (level0)
3. Compaction
   - Compaction operationsCompaction flush
   - Compaction durationCompaction flush
   - Compaction flowCompaction
   - Compaction pending bytes Compaction

level0 / Memtable / compaction RocksDB Write Stall

- Write stall duration write stall 0
- Stall conditions changed of each CF CF stall

Titan 1 8 Titan LSM-tree Key-Value Value Blob Titan LSM-tree RocksDB Blob

- Blob file sizeBlob
- Blob seek durationBlob seek
- Blob get durationBlob get
- Blob bytes/keys flowBlob

Titan Blob GC

- Blob GC fileBlob GC
- Blob GC durationBlob GC
- Blob GC bytes / keys flowBlob GC

# 4.4 Prometheus

Prometheus TiDB Prometheus Prometheus TiDB Prometheus alertmanager

## 4.4.1 Prometheus

TiDB Prometheus Grafana

Prometheus prometheus server prometheus server prometheus server grafana Prometheus alertmanagerpushgateway exporters

prometheus server MySQL zabbix zabbixprometheus server prometheus server prometheus server pushgateway

Prometheus exporter exporters

Prometheus exporters TiDB; exporter snmp_exporter; pushgateway exporter exporter ceph

kurbernetes Prometheus Prometheus

## 4.4.2

Prometheus

Prometheus prometheus server Prometheus

Alertmanger prometheus server webhook

Prometheus exporter agent Prometheus TiDB exporter

PromQL Prometheus prometheus server web UI PromQL PromQL grafana API

Prometheus exporters service discovery kubernetes node,pod,service

exporter service discovery push pushgatewaypushgateway prometheus server exporterprometheus server exporters pushgateway

# 4.4.3

Prometheus kubernetes Prometheus docker

prometheus --config.file=conf/prometheus.yml

systemd TiDB prometheus

## 1. Prometheus server

prometheus server yaml --config.file prometheus.yml

```
global:
  scrape_interval: 15s
    scrape_timeout: 10s
  external_labels:
    monitor: 'codelab-monitor'

rule_files:
  - rules/centos7.rules.yml
  - rules/mariadb.rules.yml

alerting:
  alertmanagers:
  - static_configs:
    - targets:
      - 21.129.127.3:9093

scrape_configs:
   - job_name: 'prometheus'
    scrape_interval: 5s
    static_configs:
      - targets: ['localhost:9090']

    - job_name: 'node'
    file_sd_configs:
      - files:
        - conf.d/centos.yml
```

- global:
- scrape_interval: 15
- scrape_timeout: 10
- external_labels: federation, remote storage, Alertmanager
- rule_files: alertmanger
- alerting: alertmanager alertmanager
- scrape_configs
- job_name job job
- static_configs:
- targets instance)
- file_sd_configs:

## 2.

```
groups:
- name: alert.rules
  rules:
   - alert: InstanceDown
    expr: up == 0
    for: 1s
    labels:
      level: emergency
    annotations:
      summary: ""
      description: " , service: "
```

- groups
- name:
- alert
- expr
- for: client
- labels
- annotations:

# 4.4.4 Prometheus TiDB

Promethues TiDB Prometheus PromQL TiDB

## 1. TiDB Prometheus

TiDB Prometheus 2.1 TiDB TiDB pushgateway prometheus server pushgateway 2.1 TiDB Metrics prometheus server Prometheus pushgateway grafana alertmanager altermanager

## 2. Prometheus PromQL TiDB

PromQL(Prometheus Query Language) Promehteus PromQL TiDB

(1)

Promethes 4

- Instant vector - ;
- Range vector - ;
- Scalar - ;
- String -

(2) web UI

web UI ( http://prometheus-server:9090/graph) up{instance="21.129.14.103:2998"}

(3)

- up: up Prometheus 1 0 0
- instance, job, project, service, alert_lev instance job prometheus.yaml project, service, alert_lev instance prometheus target
- 1

## 3. Instant vector

Instant vector

- : server_query_total
- {} : server_query_total{job="tikv"}
- : server_query_total{job=~"tikv|tidb"}
- : server_query_total{job!~"tikv|pd"}
- : up{tidb=~".+"} tidb up
- : tikv_engine_bytes_written{instance="21.129.14.104:21910"}/1024/1024 > 500

## 4. Range vector

Range vector instance vector []

- s - seconds
- m - minutes
- h - hours
- d - days
- w - weeks
- y - years

TiDB QPS 172.16.4.51:10080 TiDB QPS

## 5. offset

offset TiDB

sum((tidb_server_query_total{result="OK"} offset 1d))

## 4.4.5 TiDB

TiDB

**rate irate**

counter irate() rate() irate() TiDB CPU rate(process_cpu_seconds_total{job="tidb"}[1m])

**sum avg**

sum avg sum(tikv_store_size_bytes{instance=~"$instance"}) by (instance) TiKV

**increase**

increase sum(increase(tidb_server_execute_error_total[1m])) by (type) type 1 Failed Query OPM

**histogram_quantile**

histogram_quantile histogram_quantile(φ float, b instant-vector) φ 0 1 0.95 200 200 95% tidb-server 99%

histogram_quantile(0.99, sum(rate(tidb_server_handle_query_duration_seconds_bucket[1m])) by (le, instance))

## 4.4.6 alertmanager TiDB

TiDB Promethues tidb-ansible Promethues tidb-ansbile/roles/prometheus/files/tidb.rules.yml

## 1. TiDB

TiDB

level: emergency TiDB_schema_error TiDB Lease Schema TiDB TiKV Region TiKV TiKV

```
- alert: TiDB_schema_error
   expr: increase(tidb_session_schema_lease_error_total{type="outdated"}[15m]) > 0
   for: 1m
   labels:
     env: ENV_LABELS_ENV
     level: emergency
     expr:  increase(tidb_session_schema_lease_error_total{type="outdated"}[15m]) > 0
   annotations:
     description: 'cluster: ENV_LABELS_ENV, instance: , values:'
     value: ''
     summary: TiDB schema error
```

level: critical tidb-server TiDB panic panic tidb-server OOM

```
- alert: TiDB_server_panic_total
  expr: increase(tidb_server_panic_total[10m]) > 0
  for: 1m
  labels:
    env: ENV_LABELS_ENV
    level: critical
    expr:  increase(tidb_server_panic_total[10m]) > 0
  annotations:
    description: 'cluster: ENV_LABELS_ENV, instance: , values:'
    value: ''
    summary: TiDB server panic total
```

level: warning tidb-server tidb-server 10GB Join

```
- alert: TiDB_memory_abnormal
  expr: go_memstats_heap_inuse_bytes{job="tidb"} > 1e+10
  for: 1m
  labels:
    env: ENV_LABELS_ENV
    level: warning
    expr: go_memstats_heap_inuse_bytes{job="tidb"} > 1e+10
  annotations:
    description: 'cluster: ENV_LABELS_ENV, instance: , values:'
    value: ''
    summary: TiDB heap memory usage is over 10 GB
```

TiDB TiDB

## 2. TiDB alertmanager

Prometheus webhook alertmanger

TiDB alertmanager prometheus server tidb-ansible TiDB alertmanager tidb-ansible/conf/alertmanager.yml

```
routes:
- match:
    env: test-cluster
    level: emergency
  receiver: tidb-emergency
  group_by: [alertname, cluster, service]
```

- match
- env level Prometheus
- receiver name
- group_by

```
receivers:
- name: 'tidb-emergency'
  webhook_configs:
  - url: 'xxxx'
  wechat_configs:
  - corp_id: 'xxxxx'
    to_party: 'xxx'
    agent_id: 'xxxx'
    api_url: 'https://qyapi.weixin.qq.com/cgi-bin/'
    api_secret: 'xxxxxx'
```

- name receiver
- webhook_configs webhook
- wechat_configs
- webhook

# 5.1 GC

Oracle MySQL binlog NewSQL TiDB SQL client driver/TiDB

## 5.1.1

TiDB MVCC/

TiDB GCGarbage Collection 10 GC TiDB safe point 10 TiDB safe point

TiDB GC mysql.tidb SQL

```
select VARIABLE_NAME, VARIABLE_VALUE from mysql.tidb where VARIABLE_NAME like 'tikv_gc%';

+--------------------------+-----------------------------------------------------------------------------------------
-----------+
| VARIABLE_NAME            | VARIABLE_VALUE
           |
+--------------------------+-----------------------------------------------------------------------------------------
-----------+
| tikv_gc_leader_uuid      | 5afd54a0ea40005
           |
| tikv_gc_leader_desc      | host:tidb-cluster-tidb-0, pid:215, start at 2019-07-15 11:09:14.029668932 +0000 UTC m=+0
.463731223 |
| tikv_gc_leader_lease     | 20190715-12:12:14 +0000
           |
| tikv_gc_enable           | true
           |
| tikv_gc_run_interval     | 10m0s
           |
| tikv_gc_life_time        | 10m0s
           |
| tikv_gc_last_run_time    | 20190715-12:09:14 +0000
           |
| tikv_gc_safe_point       | 20190715-11:59:14 +0000
           |
| tikv_gc_auto_concurrency | true
           |
| tikv_gc_mode             | distributed
           |
+--------------------------+-----------------------------------------------------------------------------------------
-----------+
13 rows in set (0.00 sec)
```

GC

```
update mysql.tidb set VARIABLE_VALUE="24h" where VARIABLE_NAME="tikv_gc_life_time";
```

> mysql.tidbGCTiDB GC GC
>
> . tikv_gc_leader_uuidtikv_gc_leader_desc tikv_gc_leader_lease GC leader
>
> . tikv_gc_last_run_time GC
>
> . tikv_gc_safe_point GC safe point
>
> . tikv_gc_life_time:
>
> . tikv_gc_safe_point: safePoint safePoint snapshot safePoint GC

## 5.1.2

: tidb_snapshot Session Set TSOTSO PD ; “2016-10-08 16:45:26.999””2016-10-08 16:45:26” TiDB Snapshot Snapshot

> **:** TiDB PD PD Snapshot tidb_snapshot TiDB Server PD Server PD

Session Set tidb_snapshot “"

# 5.1.3

1.

```
create table t (c int);
Query OK, 0 rows affected (0.01 sec)

insert into t values (1), (2), (3);
Query OK, 3 rows affected (0.00 sec)
```

2.

```
select * from t;
+------+
| c    |
+------+
|    1 |
|    2 |
|    3 |
+------+
3 rows in set (0.00 sec)
```

3.

```
select now();
+---------------------+
| now()               |
+---------------------+
| 2016-10-08 16:45:26 |
+---------------------+
1 row in set (0.00 sec)
```

4.

```
update t set c=22 where c=2;
Query OK, 1 row affected (0.00 sec)
```

5.

```
select * from t;
+------+
| c    |
+------+
|    1 |
|   22 |
|    3 |
+------+
3 rows in set (0.00 sec)
```

6. session scope

```
set @@tidb_snapshot="2016-10-08 16:45:26";
Query OK, 0 rows affected (0.00 sec)
```

> update tidb_snapshot @@ @ @@ @

update

```
select * from t;
+------+
| c    |
+------+
|    1 |
|    2 |
|    3 |
+------+
3 rows in set (0.00 sec)
```

7.

```
set @@tidb_snapshot="";
Query OK, 0 rows affected (0.00 sec)

select * from t;
+------+
| c    |
+------+
|    1 |
|   22 |
|    3 |
+------+
3 rows in set (0.00 sec)
```

> tidb_snapshot @@ @ @@ @

## 5.1.4 /

/

> gc

1GC GC

```
update mysql.tidb set VARIABLE_VALUE="24h" where VARIABLE_NAME="tikv_gc_life_time";
```

> 

2

```
set @@tidb_snapshot="2016-10-08 16:45:26";
create table t_20161008 like t;
```

3

```
insert into t_20161008 select * from t where c=2;
```

4

5

6GC

```
update mysql.tidb set VARIABLE_VALUE="10m0s" where VARIABLE_NAME="tikv_gc_life_time"
```

7

# 5.2 Recover/Flashback

DBA DBA / TiDB

## 5.2.1 Recover

TiDB mysql.gc_delete_range TiDB GC Worker mysql.gc_delete_range GC lifetime key

RECOVER TABLE GC Worker mysql.gc_delete_range TiDB TiDB CREATE TABLE RECOVER TABLE DDL

## 5.2.2

```
MySQL [test]> show tables;

+----------------+
| Tables_in_test |
+----------------+
| t1             |
| t3             |
+----------------+

**2 rows in set (0.00 sec)**

MySQL [test]> create table t2 like t1;

**Query OK, 0 rows affected (0.10 sec)**

MySQL [test]> insert into t2 select * from t1;

**Query OK, 524288 rows affected (17.10 sec)**

**Records: 524288  Duplicates: 0  Warnings: 0**

MySQL [test]> show tables;

+----------------+
| Tables_in_test |
+----------------+
| t1             |
| t2             |
| t3             |
+----------------+

**3 rows in set (0.00 sec)**
```

DDL t2

```
MySQL [test]> drop table t2;

**Query OK, 0 rows affected (0.24 sec)**

MySQL [test]> show tables;

+----------------+
| Tables_in_test |
+----------------+
| t1             |
| t3             |
+----------------+

**2 rows in set (0.00 sec)**

MySQL [test]> select * from t2 limit 1;

ERROR 1146 (42S02): Table 'test.t2' doesn't exist
```

recover

```
MySQL [test]> recover table t2;

**Query OK, 0 rows affected (1.17 sec)**

MySQL [test]> show tables;

+----------------+
| Tables_in_test |
+----------------+
| t1             |
| t2             |
| t3             |
+----------------+

**3 rows in set (0.00 sec)**

MySQL [test]> select count(1) from t2;

+----------+
| count(1) |
+----------+
|   524288 |
+----------+

**1 row in set (0.55 sec)**
```

table t2 gc

```
MySQL [test]> recover table t2;

ERROR 8055 (HY000): snapshot is older than GC safe point 2020-03-08 15:06:19 +0800 CST
```

ddl jobs job id

```
MySQL [test]> ADMIN SHOW DDL JOBS;

+--------+---------+------------+---------------+--------------+-----------+----------+-----------+------------------
-----------------+----------------------------------+--------+
| JOB_ID | DB_NAME | TABLE_NAME | JOB_TYPE      | SCHEMA_STATE | SCHEMA_ID | TABLE_ID | ROW_COUNT | START_TIME
                 | END_TIME                         | STATE  |
+--------+---------+------------+---------------+--------------+-----------+----------+-----------+------------------
-----------------+----------------------------------+--------+
|     73 | test    | t2         | drop table    | none         |         1 |       71 |         0 | 2020-03-08 15:38:
47.076 +0800 CST | 2020-03-08 15:38:47.276 +0800 CST | synced |
|     72 | test    | t2         | create table  | public       |         1 |       71 |         0 | 2020-03-08 15:38:
37.626 +0800 CST | 2020-03-08 15:38:37.726 +0800 CST | synced |
|     70 | test    | t2         | drop table    | none         |         1 |       66 |         0 | 2020-03-08 15:38:
20.576 +0800 CST | 2020-03-08 15:38:20.776 +0800 CST | synced |
+--------------------------------------------------------------------------------------------------------------------------
-----------------------------------------------------------+
```

DDL 2 drop table t2 recover table t2

```
MySQL [test]> recover table by job 70;

**Query OK, 0 rows affected (1.15 sec)**
```

## 5.2.3

recover table

- DDL truncate tabledelete
- GC GC
- binlog recover table MySQL GC apply recover table GC

## 5.2.4 Flashback

Flashback Recover table recover recover truncate table recover

```
MySQL [test]> show tables;

+----------------+
| Tables_in_test |
+----------------+
| t1             |
| t2             |
| t3             |
+----------------+

**3 rows in set (0.00 sec)**

MySQL [test]> truncate table t2;

**Query OK, 0 rows affected (0.11 sec)**

MySQL [test]> flashback table t2 to t4;

**Query OK, 0 rows affected (1.16 sec)**

MySQL [test]> show tables;

+----------------+

| Tables_in_test |

+----------------+
| t1             |
| t2             |
| t3             |
| t4             |
+----------------+

**4 rows in set (0.00 sec)**

MySQL [test]> select count(1) from t2;

+----------+
| count(1) |
+----------+
|        0 |
+----------+

**1 row in set (0.01 sec)**

MySQL [test]> select count(1) from t4;

+----------+
| count(1) |
+----------+
|   524288 |
+----------+

**1 row in set (0.39 sec)**
```

flashback ddl job id

# 5.3

## 5.3.1

TiDB 3 Region 3 Raft Leader Raft 3 2 region 2 2 3

TiDB

- TiDB TiKV
- TiDB

Region Region TiDB

## 5.3.2

Region

- Region Region
  - Region 1 Region Peer Raft Log
  - Region Region 1 Region Region
  - Region Region Region IDRegion
-
  - Region ID 5 min DDL
  -

## 5.3.3 Region

Region PD Region Region Region

- PD
  -
    - `pd-ctl config get` region-schedule-limitreplica-schedule-limitleader-schedule-limitmerge-schedule-limit 4
    - `pd-ctl config set` 4 0
    - 4
- Region
  - pd-ctl Region ID 145 `pd-ctl -u <endpoint> -d region --jq='.regions[] | {id: .id, peer_stores: [.peers[].store_id] | select(length as $total | map(if .==(1,4,5) then . else empty end) | length>=$total-length) }'`
  - Region 2 Store TiKV
    - Region Region Peer Region `tikv-ctl --db /path/to/tikv-data/db unsafe-recover remove-fail-stores -s <s1,s2> -r <r1,r2,r3>`
    - Region Peer `tikv-ctl --db /path/to/tikv-data/db unsafe-recover remove-fail-stores -s <s1,s2> --all-regions`
    - Region Leader
- Region
  - PD TiKV `pd-ctl` Leader Region `pd-ctl -u <endpoint> -d region --jq '.regions[]|select(has("leader")|not)|{id: .id, peer_stores: [.peers[].store_id]}'`
  - Region Unavailable Store TiKV `tikv-ctl --db /path/to/tikv-data/db recreate-region --pd <endpoint> -r <region_id>`

# 6 TiDB Operator

Kubernetes TiDB

## 6.1

### 6.1.1

Kubernetes

docker-wrapper

```
git clone https://github.com/silenceshell/docker-wrapper.git
cd docker-wrapper/
#  k8s.gcr.io
./docker-wrapper.py pull k8s.gcr.io/kube-apiserver:v1.16.0
-- pull k8s.gcr.io/kube-apiserver:v1.16.0 from gcr.azk8s.cn/google-containers/kube-apiserver:v1.16.0 instead --
...
-- pull k8s.gcr.io/kube-apiserver:v1.16.0 done --
```

Kubernetes Kubernetes image registry TiDB helm chart image

### 6.1.2 PD Running TiKV

Pod Running Pod

PD Pod pd_start_script.sh Service DNS discovery discovery Service DNS PD members

Pod

```
#  pods
kubectl  get pods -n <namespace>
#  events
kubectl describe -n <namespace> pods <pd pod-name>
# ,  nslookup
kubectl logs -n <namespace> pods <pd pod-name>
#
tkctl debug <pd-name>
```

- DNS

```
#  DNS
kubectl exec -it <discovery pod name> -n=<namespace>  -- nslookup <service dns>
#  headless service dns
$ kubectl exec -it tidb-cluster-discovery-6b7f8d9954-48ngh -n=tidb  -- nslookup tidb-cluster-pd-peer.tidb.svc
Name:      tidb-cluster-pd-peer.tidb.svc
Address 1: 10.244.2.19 tidb-cluster-pd-0.tidb-cluster-pd-peer.tidb.svc.cluster.local
Address 2: 10.244.1.13 10-244-1-13.tidb-cluster-pd.tidb.svc.cluster.local
Address 3: 10.244.3.11 10-244-3-11.tidb-cluster-pd.tidb.svc.cluster.local
#  cluser ip service dns
$ kubectl exec -it tidb-cluster-discovery-6b7f8d9954-48ngh -n=tidb  -- nslookup tidb-cluster-prometheus.tidb.svc
Name:      tidb-cluster-prometheus.tidb.svc
Address 1: 10.107.103.198 tidb-cluster-prometheus.tidb.svc.cluster.local
```

DNS CoreDNS

```
#
nslookup: can't resolve 'tidb-cluster-prometheus.tidb.svc1': Name does not resolve
command terminated with exit code
#  CoreDNS
kubectl  get pods -n kube-system | grep core
coredns-9d85f5447-642rs          1/1     Running   1          13h
coredns-9d85f5447-8swr2          1/1     Running   1          13h
#  CoreDNS  DNS
#  pd pod /etc/resov  nameserver
kubectl exec -it tidb-cluster-pd-0 -n=tidb  -- cat /etc/resolv.conf
```

- IP

1.5 Pod

## 6.1.3 CrashLoopBackOff

Pod CrashLoopBackOff Pod CrashLoopBackOff Pod

- Pod

```
#
kubectl -n <namespace> logs -f <pod-name>
#  Pod  CrashLoopBackOff
kubectl -n <namespace> logs -p <pod-name>
```

tidb-server tikv-server pd-server

- TiKV Pod “cluster id mismatch”

TiKV Pod TiKV Pod PV local volume provisioner PV

TiKV PV TiKV Pod PVCTiKV Pod PV Kubernetes PV local volume provisioner PVC PV reclaimPolicy PV

- Node ulimit

```
root             soft    nofile          1000000
root             hard    nofile          1000000
root             soft    core            1048576
root             hard    core            1048576
```

TiKV ulimit Kubernetes /etc/security/limits.conf ulimit

- pd pod CrashLoopBackOff

pd pod CrashLoopBackOff pod

```
waiting for discovery service to return start args...
```

Kubernetes discovery service:

```
kubectl get service -n {your namespace} | grep discovery //get ip port
telnet {ip} {port}
```

discovery

```
kubectl delete po {clustername}-discovery-xxxxxxxx-xxxxx -n {your namespace}
```

discovery pod

```
kubectl logs -f {clustername}-discovery-xxxxxxxx-xxxxx -n {your namespace}
```

```
E1218 15:49:00.395064       1 mux.go:58] failed to discover: {cluster-name}-pd-3.{cluster-name}-pd-peer.{cluster-name
}.svc:2380, Get http://{cluster-name}-pd.{cluster-name}:2379/pd/api/v1/members: dial tcp x.x.x.x:2379: connect: conne
ction refused
```

pd service

```
wget -c http://{cluster-name}-pd.{cluster-name}:2379/pd/api/v1/members
```

pd pod

```
wget -c http://{ip of pd's pod}:2379/pd/api/v1/members
```

wget wget Kubernetes kube-proxy kube-proxy Kubernetes kube-proxy kube-proxy

nginx

```
kubectl apply -f https://raw.githubusercontent.com/kubernetes/website/master/content/en/examples/service/networking/r
un-my-nginx.yaml
```

service

```
kubectl expose deployment/my-nginx
```

service kube-proxy kube-proxy Kubernetes Kubernetes

- pd pod CrashLoopBackOff

chart pd replicas 3 pd pod 5 3 running 3 join CrashLoopBackoff

```
[                                    ~]# kubectl get po
NAME                                                  READY   STATUS             RESTARTS   AGE
tidbcluster-v        i-discovery-68d7c75556-956kw     1/1     Running            1          15d
tidbcluster-v        i-monitor-84cc9cc5-m6rml         3/3     Running            3          15d
tidbcluster-         i-pd-0                           1/1     Running            1          15d
tidbcluster-         i-pd-1                           1/1     Running            15         12d
tidbcluster-        li-pd-2                           0/1     CrashLoopBackOff   283        24h
tidbcluster-         i-pd-3                           0/1     CrashLoopBackOff   308        26h
tidbcluster-v        i-pd-4                           0/1     CrashLoopBackOff   3032       11d
tidbcluster-v        i-tidb-0                         2/2     Running            0          15d
tidbcluster-v        i-tidb-1                         2/2     Running            0          15d
tidbcluster-         i-tidb-initializer-p8r2l         0/1     Completed          129        29d
tidbcluster          i-tikv-0                         1/1     Running            0          15d
tidbcluster          i-tikv-1                         1/1     Running            0          15d
tidbcluster-         i-tikv-2                         1/1     Running            0          15d
```

PD pod

```
[                                    ~]# kubectl logs --tail=200                    -pd-2

Name:                                  -pd-2.                    -pd-peer.                    .svc
Address 1: 10.42.40.80                 -pd-2.                    -pd-peer.                    .svc.cluster.local
nslookup domain                                  -pd-2.                    -pd-peer.                    .svc.svc success
starting pd-server ...
/pd-server --data-dir=/var/lib/pd --name=                                  -pd-2 --peer-urls=http://0.0.0.0:2380 --advertise-peer-urls=http://tid
bcluster-          -pd-2.tidbcluster          -pd-peer.tidbcluster-          .svc:2380 --client-urls=http://0.0.0.0:2379 --advertise-c
lient-urls=http://tidbcluster-          -pd-2.tidbcluster-          -pd-peer.tidbcluster          .svc:2379 --config=/etc/pd/pd.toml -
-join=http://tidbcluster-          -pd-3.tidbcluster-          -pd-peer.tidbcluster-          .svc:2380,http://tidbcluster-          -pd
-1.tidbcluster-          -pd-peer.tidbcluster-          .svc:2380,http://tidbcluster-          -pd-0.tidbcluster-          -pd-peer.tidb
cluster-          .svc:2380
[2020/02/06 16:50:46.071 +08:00] [INFO] [util.go:59] ["Welcome to Placement Driver (PD)"]
[2020/02/06 16:50:46.071 +08:00] [INFO] [util.go:60] [PD] [release-version=v3.0.5]
[2020/02/06 16:50:46.071 +08:00] [INFO] [util.go:61] [PD] [git-hash=4934a651d2d428411a9610a5b6b9d7156a439355]
[2020/02/06 16:50:46.071 +08:00] [INFO] [util.go:62] [PD] [git-branch=HEAD]
[2020/02/06 16:50:46.071 +08:00] [INFO] [util.go:63] [PD] [utc-build-time="2019-10-25 03:24:57"]
[2020/02/06 16:50:46.071 +08:00] [INFO] [metricutil.go:80] ["disable Prometheus push client"]
[2020/02/06 16:50:46.071 +08:00] [ERROR] [join.go:212] ["failed to open directory"] [error="open /var/lib/pd/member: no such file or
 directory"]
2020/02/06 16:50:46.071 grpclog.go:45: [info] parsed scheme: "endpoint"
2020/02/06 16:50:46.071 grpclog.go:45: [info] ccResolverWrapper: sending new addresses to cc: [{http://tidbcluster-          -pd-3.ti
dbcluster-          -pd-peer.tidbcluster-          .svc:2380 0  <nil>} {http://tidbcluster-          -pd-1.tidbcluster-          -pd-pee
r.tidbcluster-          .svc:2380 0  <nil>} {http://tidbcluster-          -pd-0.tidbcluster-          -pd-peer.tidbcluster-          .sv
c:2380 0  <nil>}]
2020/02/06 16:50:46.079 grpclog.go:60: [warning] grpc: addrConn.createTransport failed to connect to {http://tidbcluster-          -p
d-3.tidbcluster-          -pd-peer.tidbcluster-          .svc:2380 0  <nil>}. Err :connection error: desc = "transport: Error while di
aling dial tcp: lookup tidbcluster-wuhanwuli-pd-3.tidbcluster-          -pd-peer.tidbcluster-          .svc on 10.43.0.10:53: no such
host". Reconnecting...
[2020/02/06 16:50:46.081 +08:00] [FATAL] [main.go:91] ["join meet error"] [error="there is a member that has not joined successfully
"] [stack="github.com/pingcap/log.Fatal\n\t/home/jenkins/agent/workspace/release_tidb_3.0/go/pkg/mod/github.com/pingcap/log@v0.0.0-2
0190715063458-479153f07ebd/global.go:59\nmain.main\n\t/home/jenkins/agent/workspace/release_tidb_3.0/go/src/github.com/pingcap/pd/cm
d/pd-server/main.go:91\nruntime.main\n\t/usr/local/go/src/runtime/proc.go:200"]
2020/02/06 16:50:46.081 grpclog.go:60: [warning] Failed to dial http://tidbcluster-          -pd-3.tidbcluster-          -pd-peer.tidb
cluster-          .svc:2380: context canceled; please retry.
                                    ~]#
```

pod PV Retain

provisioner

```
I0206 09:47:40.383224       1 cache.go:64] Updated pv "local-pv-863ba702" to cache
I0206 09:47:40.383244       1 cache.go:64] Updated pv "local-pv-ca3501f4" to cache
I0206 09:51:42.745063       1 cache.go:64] Updated pv "local-pv-863ba702" to cache
I0206 09:51:52.419372       1 deleter.go:195] Start cleanup for pv local-pv-863ba702
I0206 09:51:52.419505       1 deleter.go:266] Deleting PV file volume "local-pv-863ba702" contents at hostpath "/mnt/disks/tikv1", m
ountpath "/mnt/disks/tikv1"
I0206 09:52:02.420739       1 deleter.go:165] Deleting pv local-pv-863ba702 after successful cleanup
I0206 09:52:02.430763       1 cache.go:64] Updated pv "local-pv-863ba702" to cache
I0206 09:52:02.439564       1 cache.go:73] Deleted pv "local-pv-863ba702" from cache
I0206 09:52:12.433960       1 discovery.go:299] Found new volume at host path "/mnt/disks/tikv1" with capacity 3935254495232, creati
ng Local PV "local-pv-863ba702", required volumeMode "Filesystem"
I0206 09:52:12.443227       1 discovery.go:332] Created PV "local-pv-863ba702" for volume at "/mnt/disks/tikv1"
I0206 09:52:12.443520       1 cache.go:55] Added pv "local-pv-863ba702" to cache
```

PV pd kube-apiserver PV kube-apiserver

```
--v=4
```

pd pd-recover

### 6.1.4 Pending

```
kubectl get pod
NAME   READY   STATUS    RESTARTS   AGE
pod-pvc-pv   0/1     Pending   0          4s
```

Pod Pending

- PD/TiKV/Monitor Pod PVC StorageClass PV
- Kubernetes Pod CPU
- PD TiKV Replicas tidb-scheduler

- kubectl describe Pending

```
kubectl describe pod -n <namespace> <pod-name>
kubectl describe pod pod-pvc-pv
Name:         pod-pvc-pv
...
Status:       Pending
...
Warning  FailedScheduling  21s (x4 over 4m28s)  default-scheduler  0/1 nodes are available: 1 node(s) didn't find ava
ilable persistent volumes to bind.
```

- 

  CPU Kubernetes

- StorageClass

values.yaml storageClassName StorageClass helm upgrade Statefulset PVC StorageClass

```
kubectl get storageclass
```

- Local PV

  PV Local PV PV

## 6.1.5 Pod

TiDB Pod Pod Headless Service TiDB Operator PD Service service-name PD

Pod Pod

1. Service Headless Service Endpoints

```
kubectl -n <namespace> get endpoints <release-name>-pd
kubectl -n <namespace> get endpoints <release-name>-tidb
kubectl -n <namespace> get endpoints <release-name>-pd-peer
kubectl -n <namespace> get endpoints <release-name>-tikv-peer
kubectl -n <namespace> get endpoints <release-name>-tidb-peer
```

ENDPOINTS cluster_ip:port Pod kube-controller-manager

1. Pod Network Namespace

```
tkctl debug -n <namespace> <pod-name>
```

shell dig DNS DNS Kubernetes DNS

```
dig <HOSTNAME>
```

ping IP IP dig ClusterIP:

```
ping <TARGET_IP>
```

ping Kubernetes ping telnet

```
telnet <TARGET_IP> <TARGET_PORT>
```

telnet Pod

```
#
kubectl -n <namespace> get po <pod-name> -ojson | jq '.spec.containers[].ports[].containerPort'

#
# PD,  2379
kubectl -n <namespace> -it exec <pod-name> -- cat /etc/pd/pd.toml | grep client-urls
# TiKV,  20160
kubectl -n <namespace> -it exec <pod-name> -- cat /etc/tikv/tikv.toml | grep addr
# TiDB,  4000
kubectl -n <namespace> -it exec <pod-name> -- cat /etc/tidb/tidb.toml | grep port
```

## 6.1.6 TiDB

TiDB TiDB

Running

```
kubectl get po -n <namespace>
```

TiDB

```
kubectl logs -f <tidb-pod-name> -n <namespace> -c tidb
```

1. NodePort TiDB node service domain clusterIP TiDB serviceName clusterIP Kubernetes
   - node
   - TiDB service externalTrafficPolicy Local Local TiDB Pod node IP
2. service domain clusterIP TiDB TiDB :4000 PodIP TiDB service domain clusterIP PodIP
   - DNS

     ```
     kubectl get po -n kube-system -l k8s-app=kube-dns
     dig <tidb-service-domain>
     ```

   - node kube-proxy

     ```
     kubectl get po -n kube-system -l k8s-app=kube-proxy
     ```

   - node iptables TiDB

```
iptables-save -t nat |grep <clusterIP>
```

- endpoint

3. PodIP TiDB Pod
   - node route
   - 
   - Pod

# 6.2

## 6.2.1 TiKV PD

## 6.2.2 TiKV Store Tombstone

TiKV Pod Pod Running TiKV Store Store UP TiKV TiKV Store Tombstone

Store Pod TiKV Pod Store Offline Pod Store

1. TiKV Store

```
kubectl get -n <namespace> tidbcluster <release-name> -ojson | jq '.status.tikv.stores'
```

1. TiKV Pod

```
kubectl get -n <namespace> po -l app.kubernetes.io/component=tikv
```

1. Store Pod TiKV Pod Store Offline Pod Store
   i. PD

   ```
   kubectl port-forward -n <namespace> svc/<cluster-name>-pd <local-port>:2379 &>/tmp/portforward-pd.log &
   ```

   ii. Store

   ```
   curl -X POST http://127.0.0.1:2379/pd/api/v1/store/<store-id>/state?state=Up
   ```

2. TiKV Pod lastHeartbeatTime Store Tombstone Pod PV
   i. Store PV reclaimPolicy Delete

```
kubectl patch $(kubectl get pv -l app.kubernetes.io/instance=<release-name>,tidb.pingcap.com/store-id=<store
-id> -o name) -p '{"spec":{"persistentVolumeReclaimPolicy":"Delete"}}
```

ii. Pod PVC

```
kubectl delete -n <namespace> pvc tikv-<pod-name> --wait=false
```

iii. Pod Pod

```
kubectl delete -n <namespace> pod <pod-name>
```

Pod Store

### 6.2.3 TiDB

(Load Balancer) TiDB TiDB

TiDB tcp-keep-alive TCP keepalive

- Kubernetes kubelet --allowed-unsafe-sysctls=net.* kubelet TiDB

```
tidb:
 ...
 podSecurityContext:
 sysctls:
 - name: net.ipv4.tcp_keepalive_time
 value: "300"
```

- Kubernetes kubelet --allowed-unsafe-sysctls=net.* TiDB

```
tidb:
 annotations:
 tidb.pingcap.com/sysctl-init: "true"
 podSecurityContext:
 sysctls:
 - name: net.ipv4.tcp_keepalive_time
 value: "300"
 ...
```

> TiDB Operator 1.1

## 6.3

Pod CrashLoopBackoff Pod kubectl exec tkctl debugTiDB in Kubernetes PD/TiKV/TiDB Pod Pod Crash
kubectl exec tkctl debug Pod

Pod CrashLoopBackoff

```
$ kubectl get pods -n tidbcluster1
NAME                              READY   STATUS             RESTARTS   AGE
demo-discovery-5c78d6bcd8-5ttcl   1/1     Running            0          20h
demo-monitor-6ddc6d6674-kcmhh     3/3     Running            0          3d22h
demo-pd-0                         1/1     Running            0          3d22h
demo-pd-1                         0/1     CrashLoopBackOff   911        3d22h
demo-pd-2                         1/1     Running            10         3d22h
demo-pd-3                         0/1     CrashLoopBackOff   932        3d22h
demo-pd-4                         1/1     Running            0          3d22h
demo-pd-5                         1/1     Running            0          3d22h
demo-tidb-0                       2/2     Running            1          3d22h
demo-tidb-1                       2/2     Running            0          3d22h
demo-tikv-0                       1/1     Running            0          3d22h
demo-tikv-1                       1/1     Running            0          3d22h
demo-tikv-2                       1/1     Running            0          3d22h
demo-tikv-3                       1/1     Running            0          3d22h
demo-tikv-4                       1/1     Running            0          3d22h
demo-tikv-5                       1/1     Running            0          3d22h
```

Pod Annotation

```
kubectl annotate pod <pod-name> -n <namespace> runmode=debug
# kubectl annotate pod  demo-pd-1 -n tidbcluster1 runmode=debug
```

Pod Annotation Pod Running

```
watch kubectl get pod <pod-name> -n <namespace>
# watch kubectl get pod demo-pd-1 -n tidbcluster1
```

```
Every 2.0s: kubectl get pod demo-pd-1 -n tidbcluster1

NAME         READY   STATUS    RESTARTS   AGE
demo-pd-1    1/1     Running   912        3d22h
```

kubectl exec

```
#  kubectl logs  pod
$ kubectl logs demo-pd-1 -n tidbcluster1
entering debug mode.
#  pod
kubectl exec -it <pod-name> -n <namespace> -- /bin/sh
# kubectl exec -it demo-pd-1 -n tidbcluster1 -- /bin/sh
```

Pod

```
kubectl delete pod <pod-name> -n <namespace>
# kubectl delete pod demo-pd-1 -n tidbcluster1
```

```
pod "demo-pd-1" deleted
```

Pod

# 1

“TiDB” TiDB

# 1. TiDB

20 “ SQL ”(RDBMS)KV SQL NoSQL NoSQL SQL -> NoSQL ->No only SQL

SQL NewSQL TiDB NewSQL MySQL TiDB TiDB SQL ACID TiDB

TiDB TiDB

- MySQL
- Raft
-
-

# 2.

## OLTP

MySQL MySQL NewSQL MySQL

Hash Sharding DB DDL Join / /

TiDB MySQL TiDB KV SQL DDLPercolator ACID Region Multi-Raft

| | | **TiDB** |
|---|---|---|
| | | |
| | | |
| (JOIN/ GROUP BY/...) | | |
| | | |
| | | |
| | | |
| ID | | |
| | | |

TiDB MySQL MySQL TiDB TiDB 4.0 K8s TiKV Pod Region

- TiDB

https://pingcap.com/cases-cn/user-case-zhihu/

- TiDB at

https://pingcap.com/cases-cn/user-case-fengchao/

ETL

TiDB 4.0 3.0 TiSpark Spark TiDB TiKV Spark “”

TiDB 4.0 TiFlash Raft learner Engine tag TiFlash TiKV TiFlash TiDB HATP

Raft learner TiFlash Oracle DataGuard TiDB HTAP

- TiDB / TiSpark

https://pingcap.com/cases-cn/user-case-yiguo/

ABC A

- Oracle Extended RAC
- A B Oracle GoldenGate
-

TiDB TiDB Server Web TiKV Server PD Server Raft TiKV Server Region Multi-Raft DC / Zone / Rack / Host Raft Leader Reject IO PD Server Raft 3

TiDB Raft TiDB 4.0 Follower Read

- TiDB

https://pingcap.com/cases-cn/user-case-beijing-bank/

- TiDB

https://pingcap.com/cases-cn/user-case-webank/

# 3.

TiDB  TiDB

https://pingcap.com/cases-cn/

# 2

TiDB

## 2.1 TiDB server

TP tidb-server tidb-server cpu OLAP 16GB

- OLAP
- OLAP
- mydumper

## 2.2 PD

PD , SSD PD PD PD TiDB PD

## 2.3 TiKV

TiKV TiKV TiKV TiKV (max-replicas) location-label TiKV /

## 2.4

4-8GB 2-4 CPU 16GB 8 CPU 8GB 4 CPU Prometheus/Alertmanager/Grafana TiDB

## 2.5 Pump

- CPU4
- 8GB
- SSD
-

Pump

## 2.6 Drainer

- CPU4
- 8GB
- Drainer SSD
-

Drainer Drainer

## 2.7

mydumper/myloader

- CPU16
- 32GB
- SSD
-

64GB

# 3

SysbenchTPC-CTPC-H  Sysbench  TPC-C  OLTP

# 3.1 Sysbench

TiDB MySQL OLTP OLAP TiDB MySQL sysbench

## 3.1.1

- sysbench

```
mkdir -p /tmp/sysbench
cd /tmp/sysbench
wget https://github.com/akopytov/sysbench/archive/1.0.14.tar.gz
yum -y install make automake libtool pkgconfig libaio-devel
yum -y install mariadb-devel
./autogen.sh
./configure
make -j
make install
sysbench --version
```

-

| | | | |
|---|---|---|---|
| TiDB & PD | CPU2*E5-2650 v4@2.20GHz<br>128G<br>2*800G 3*1.6T SSD<br>2 * bond-1 | 3 | TiDB PD ext4 |
| TiKV | CPU2*E5-2650 v4@2.20GHz<br>256G<br>2*480G 4*1.92T NVMe SSD<br>2 * bond-1 | 3 | TiKV ext4PCIe |
| monitor | 8 32G800G | 3 | Grafana + Prometheus |

-

| | |
|---|---|
| | Redhat 7.4 |
| TiDB | TiDB-v3.0.5 |
| TiDB & PD | "TiDB " 2 tidb-server + 1 pd-server |
| TiKV | "TiKV " 4 tikv-server |
| TiDB | performance:<br>max-procs: 24 |
| TiKV | readpool:<br>coprocessor:<br>high-concurrency: 8<br>normal-concurrency: 8<br>low-concurrency: 8<br>storage:<br>block-cache:<br>capacity: "32GB" |

## 3.1.2

# 1.

- sysbench

```
mysql-host=192.168.xxx.xxx
mysql-port=4000
mysql-user=sysbench
mysql-password=******
mysql-db=test
time=60
threads=16
report-interval=10
db-driver=mysql
```

- sysbench

```
--threads=8  8
--report-interval=10  10
--rand-type=uniform uniform ()gaussian ()special ()pareto ()
--time=120  120
--events=0  0 0
--percentile=99  95% 1%  99%
```

- sysbench

```
sysbench 1.0.14 (using bundled LuaJIT 2.1.0-beta2)
Running the test with following options:
Number of threads: 16
Report intermediate results every 10 second(s)
Initializing random number generator from current time
Initializing worker threads...
Threads started!
#  10 tps95%
[ 10s ] thds: 16 tps: 21532.38 qps: 21532.38 (r/w/o: 21532.38/0.00/0.00) lat (ms,95%): 1.04 err/s: 0.00 reconn/s: 0.0
0
[ 20s ] thds: 16 tps: 21617.20 qps: 21617.20 (r/w/o: 21617.20/0.00/0.00) lat (ms,95%): 1.01 err/s: 0.00 reconn/s: 0.0
0
[ 30s ] thds: 16 tps: 21550.98 qps: 21550.98 (r/w/o: 21550.98/0.00/0.00) lat (ms,95%): 1.03 err/s: 0.00 reconn/s: 0.0
0
[ 40s ] thds: 16 tps: 21544.16 qps: 21544.16 (r/w/o: 21544.16/0.00/0.00) lat (ms,95%): 1.01 err/s: 0.00 reconn/s: 0.0
0
[ 50s ] thds: 16 tps: 21639.76 qps: 21639.76 (r/w/o: 21639.76/0.00/0.00) lat (ms,95%): 0.99 err/s: 0.00 reconn/s: 0.0
0
[ 60s ] thds: 16 tps: 21597.56 qps: 21597.56 (r/w/o: 21597.56/0.00/0.00) lat (ms,95%): 1.01 err/s: 0.00 reconn/s: 0.0
0
SQL statistics:
    queries performed:
        read:                           1294886                        #
        write:                          0                              #
        other:                          0                              #  (COMMIT )
        total:                          1294886                        #
    transactions:                       1294886 (21579.74 per sec.)    #  (  )
    queries:                            1294886 (21579.74 per sec.)    #  (  )
    ignored errors:                     0      (0.00 per sec.)         #  (  )
    reconnects:                         0      (0.00 per sec.)         #  (  )
General statistics:
    total time:                         60.0029s                       #
    total number of events:             1294886                        #

Latency (ms):
         min:                                    0.36                  #
         avg:                                    0.74                  #
         max:                                    8.90                  #
         95th percentile:                        1.01                  #  95%
         sum:                               959137.19
Threads fairness:
    events (avg/stddev):           80930.3750/440.48                  #  80930.3750  event 440.48
    execution time (avg/stddev):   59.9461/0.00                       #  59.9  0
```

- 
```
sysbench --config-file=sysbench-thread-16.cfg oltp_point_select --tables=32 --table-size=10000000 prepare
```

- 

block cache sbtest1 SQL

```
SELECT COUNT(pad) FROM sbtest1 USE INDEX(k_1);
```

analyze sbtest* sbtest1

```
ANALYZE TABLE sbtest1;
```

# 2.

- Point select
```
sysbench --config-file=sysbench-thread-16.cfg oltp_point_select --tables=32 --table-size=10000000 run
```
- Update index
```
sysbench --config-file=sysbench-thread-16.cfg oltp_update_index --tables=32 --table-size=10000000 run
```
- Read-only
```
sysbench --config-file=sysbench-thread-16.cfg oltp_read_only --tables=32 --table-size=10000000 run
```
- Write-only
```
sysbench --config-file=sysbench-thread-16.cfg oltp_write_only --tables=32 --table-size=10000000 run
```
- Read-Write
```
sysbench --config-file=sysbench-thread-16.cfg oltp_read_write --tables=32 --table-size=10000000 run
```

# 3.

32 10MB tidb-server sysbench

- oltp_point_select

| type | thread | tps | qps | min latency | avg latency | 95th latency | max latency |
|---|---|---|---|---|---|---|---|
| point_select | 64 | 148098.00 | 148098.00 | 0.26 | 0.43 | 0.52 | 276.54 |
| point_select | 128 | 257760.00 | 257760.00 | 0.27 | 0.50 | 0.65 | 261.51 |
| point_select | 256 | 343215.00 | 343215.00 | 0.28 | 0.75 | 1.89 | 253.23 |
| point_select | 512 | 448683.00 | 448683.00 | 0.29 | 1.14 | 3.55 | 290.85 |
| point_select | 1024 | 567063.00 | 567063.00 | 0.30 | 1.80 | 5.57 | 70.21 |
| point_select | 2048 | 663217.00 | 663217.00 | 0.29 | 3.08 | 8.90 | 330.19 |
| point_select | 4096 | 736094.00 | 736094.00 | 0.33 | 5.55 | 15.00 | 431.72 |

- read_only

| type | thread | tps | qps | min latency | avg latency | 95th latency | max latency |
|---|---|---|---|---|---|---|---|
| read_only | 64 | 5984.48 | 95751.60 | 7.87 | 10.69 | 14.21 | 85.24 |
| read_only | 128 | 9741.39 | 155862.00 | 7.64 | 13.14 | 18.28 | 236.37 |
| read_only | 256 | 13080.20 | 209284.00 | 9.22 | 19.56 | 28.16 | 99.79 |
| read_only | 512 | 15678.40 | 250854.00 | 10.40 | 32.62 | 49.34 | 115.78 |
| read_only | 1024 | 17691.40 | 283063.00 | 10.87 | 57.73 | 87.56 | 378.12 |
| read_only | 2048 | 19086.60 | 305386.00 | 7.68 | 107.12 | 164.45 | 710.91 |

- oltp_update_index

| type | thread | tps | qps | min latency | avg latency | 95th latency | max latency |
|---|---|---|---|---|---|---|---|
| update_index | 64 | 19232.10 | 19232.10 | 1.75 | 3.33 | 4.74 | 274.86 |
| update_index | 128 | 25898.20 | 25898.20 | 1.67 | 4.94 | 7.98 | 330.88 |
| update_index | 256 | 31214.00 | 31214.00 | 1.67 | 8.20 | 14.73 | 5189.46 |
| update_index | 512 | 36213.50 | 36213.50 | 1.74 | 14.13 | 27.66 | 5487.91 |
| update_index | 1024 | 40731.20 | 40731.20 | 1.74 | 25.12 | 52.89 | 7395.50 |
| update_index | 2048 | 44423.50 | 44423.50 | 1.77 | 46.04 | 99.33 | 5563.36 |

- write_only

| type | thread | tps | qps | min latency | avg latency | 95th latency | max latency |
|---|---|---|---|---|---|---|---|
| write_only | 64 | 7882.92 | 47297.50 | 3.05 | 8.12 | 12.52 | 341.78 |
| write_only | 128 | 9780.01 | 58680.10 | 3.07 | 13.08 | 21.50 | 504.41 |
| write_only | 256 | 11450.20 | 68701.20 | 3.12 | 22.34 | 36.89 | 6874.97 |
| write_only | 512 | 13330.00 | 79979.20 | 3.04 | 38.39 | 65.65 | 6316.33 |
| write_only | 1024 | 14761.20 | 88567.40 | 3.30 | 68.39 | 118.92 | 5426.65 |
| write_only | 2048 | 16825.20 | 100951.00 | 3.25 | 121.50 | 223.34 | 5551.31 |

- read_write

| type | thread | tps | qps | min latency | avg latency | 95th latency | max latency |
|---|---|---|---|---|---|---|---|
| read_write | 64 | 2698.01 | 53960.20 | 13.91 | 23.72 | 29.72 | 321.56 |
| read_write | 128 | 4066.40 | 81328.10 | 12.19 | 31.47 | 42.85 | 411.31 |
| read_write | 256 | 4915.23 | 98304.50 | 12.94 | 52.06 | 70.55 | 626.57 |
| read_write | 512 | 5988.96 | 119779.00 | 12.99 | 85.42 | 121.08 | 5023.20 |
| read_write | 1024 | 7260.19 | 145204.00 | 13.25 | 140.67 | 196.89 | 5767.52 |
| read_write | 2048 | 8228.84 | 164577.00 | 13.96 | 248.19 | 376.49 | 5475.98 |

# 3.1.3

TiDB MySQL TiDB MySQL MySQL TiDB

TiDB MySQL TiDB region KV region region TiDB TiKV MySQL

# 3.2 TPC-C

TiDB TPC-C

## 1. TPC-C

TPC TPC-CTransaction Processing Performance Council OLTP TPC-C TPC-C

BenchmarkSQL TPCC PostgreSQLMySQLOracleTIDB

## 2. BenchmarkSQL

TPC-C OLTP OLTP

- NewOrder –
- Payment –
- OrderStatus –
- Delivery –
- StockLevel –

TPC-C Benchmark ITEM 10 WAREHOUSE W

- STOCK W * 10 10
- DISTRICT W * 10 10
- CUSTOMER W * 10 * 3000 3000
- HISTORY W * 10 * 3000
- ORDER W * 10 * 3000 3000 900 NEW-ORDER 5 ~ 15 ORDER-LINE

TPC-C tpmC Transactions per MinuteMQThMax Qualified Throughput Transactions NewOrder Transaction

## 3. TIDB

1000 warehous 3

3 1 TiDB1 PD 1 TiKV

| | |
|---|---|
| OS | Linux (CentOS 7.3.1611) |
| CPU | 40 vCPUs, Intel(R) Xeon(R) CPU E5-2630 v4 @ 2.20GHz |
| RAM | 128GB |
| DISK | Optane 500GB SSD |

CPU NUMA `taskset` `lscpu` NUMA node

```
NUMA node0 CPU(s):     0,2,4,6,8,10,12,14,16,18,20,22,24,26,28,30,32,34,36,38
NUMA node1 CPU(s):     1,3,5,7,9,11,13,15,17,19,21,23,25,27,29,31,33,35,37,39
```

TiDB

```
nohup taskset -c 0,2,4,6,8,10,12,14,16,18,20,22,24,26,28,30,32,34,36,38 bin/tidb-server && \
nohup taskset -c 1,3,5,7,9,11,13,15,17,19,21,23,25,27,29,31,33,35,37,39 bin/tidb-server
```

HAproxy TiDB node nbproc CPU

| | TIDB | TIKV | PD |
|---|---|---|---|
| node1 | 1 | 1 | 1 |
| node2 | 1 | 1 | 1 |
| node3 | 1 | 1 | 1 |

# 4. TIDB

1

```
[log]
level = "error"
```

2 CPU TiDB CPU

```
performance:
# Max CPUs to use, 0 use number of CPUs in the machine.
  max-procs: 20
```

3 TiDB prepared plan cache

```
prepared_plan_cache:
  enabled: true
```

4 TiKV 16

```
tikv_client:
# Max gRPC connections that will be established with each tikv-server.
  grpc-connection-count: 4
```

5

```
txn_local_latches:
# Enable local latches for transactions. Enable it when
# there are lots of conflicts between transactions.
  enabled: true
```

# 5. TIKV

1 TiKV

```
global:
  log-level = "error"
```

2 sync-logTiKV Raft raftstore sync-log

```
[raftstore]
sync-log = false
```

3 TiKV RocksDB block cache 20 GB TiKV block cache

```
[storage.block-cache]
capacity = "10GB"
```

3 Grafana [TiKV ] TiKV

# 6. BenchmarkSQL

benchmarksql/run/props.mysql

```
conn=jdbc:mysql://{HAPROXY-HOST}:{HAPROXY-PORT}/tpcc?useSSL=false&useServerPrepStmts=true&useConfigs=maxPerformance

warehouses=1000 #  1000  warehouse

terminals=500   #  500

loadWorkers=32  #
```

# 7.

TPC-C

1 TiDB-Server

```
create database tpcc
```

2 shell BenchmarkSQL

```
cd run && \
./runSQL.sh props.mysql sql.mysql/tableCreates.sql && \
./runSQL.sh props.mysql sql.mysql/indexCreates.sql
```

3

1 BenchmarkSQL

```
./runLoader.sh props.mysql
```

2 TiDB Lightning warehouse 1000 warehouse BenchmarkSQL csv TiDB Lightning Lightning csv

a BenchmarkSQL warehouse csv 77 MB csv `benchmarksql/run/props.mysql`

```
fileLocation=/home/user/csv/  #  csv
```

Lightning csv Lightning `{database}.{table}.csv`

```
fileLocation=/home/user/csv/tpcc.  #  csv  + database
```

csv `tpcc.bmsql_warehouse.csv` Lightning

b csv

```
./runLoader.sh props.mysql
```

c inventory.ini

IP

```
[importer_server]
IS1 ansible_host=172.16.5.34 deploy_dir=/data2/is1 tikv_importer_port=13323 import_dir=/data2/import

[lightning_server]
LS1 ansible_host=172.16.5.34 deploy_dir=/data2/ls1 tidb_lightning_pprof_port=23323 data_source_dir=/home/user/csv
```

d conf/tidb-lightning.yml

```
mydumper:
  no-schema: true
csv:
  separator: ','
  delimiter: ''
  header: false
  not-null: false
  'null': 'NULL'
  backslash-escape: true
  trim-last-separator: false
```

e Lightning Importer

```
ansible-playbook deploy.yml --tags=lightning
```

f

- Lightning Importer
-
- Importer `scripts/start_importer.sh` Importer
- Lightning `scripts/start_lightning.sh`

ansible Lightning `sql.common/test.sql` SQL

# 8.

BenchmarkSQL

```
nohup ./runBenchmark.sh props.mysql &> test.log &
```

`test.log`

```
07:09:53,455 [Thread-351] INFO   jTPCC : Term-00, Measured tpmC (NewOrders) = 77373.25

07:09:53,455 [Thread-351] INFO   jTPCC : Term-00, Measured tpmTOTAL = 171959.88

07:09:53,455 [Thread-351] INFO   jTPCC : Term-00, Session Start     = 2019-03-21 07:07:52

07:09:53,456 [Thread-351] INFO   jTPCC : Term-00, Session End       = 2019-03-21 07:09:53

07:09:53,456 [Thread-351] INFO   jTPCC : Term-00, Transaction Count = 345240
```

tpmC

# TiDB-Binlog

TiDB Binlog  TiDB  binlog MySQL MySQL  binlog TiDB Binlog  TiDB  TiDB  binlog TiDB  TiDB
TiDB Binlog

# TiDB Binlog

1. Pump  Pump
2. TiDB  Pump Client  binlog  Pump Pump  TiDB
3. Pump  kv  binlog binlog
4. binlog  Pump  Pump
5. Drainer  Pump  binlog

TiDB-Binlog  T+1

TiDB binlog  MySQL  master/slave

- 
-

binlog

- *

TiDB binlog

-

Pump Drainer Intel x86-64 64

| | | CPU | | |
|---|---|---|---|---|
| Pump | 3 | 8+ | SSD, 200 GB+ | 16G |
| Drainer | 1 | 8+ | SAS, 100 GB+ binlog | 16G |

-

300M

1. Pump
   i. tidb-ansible/inventory.ini ( TiDB )
      i. enable_binlog = True TiDB binlog

```
enable_binlog = True
```

```
2.  pump_servers  IP

  ```
  ## Binlog Part
  [pump_servers]
  172.16.10.72
   172.16.10.73
  172.16.10.74
  ```

3.  Pump  7  tidb-ansible/conf/pump.ymlTiDB 3.0.2  tidb-ansible/conf/pump-cluster.yml gc


  ```
  global:

  # an integer value to control the expiry date of the binlog data, which indicates for how long (in days) the bin
log data would be stored

  # must be bigger than 0

  # gc: 7
  ```

4.  binlog[](https://pingcap.com/docs-cn/stable/how-to/deploy/orchestrated/ansible#%E8%B0%83%E6%95%B4%E9%83%A8%E7%
BD%B2%E7%9B%AE%E5%BD%95) Pump

  ```
  ## Binlog Part
  [pump_servers]
  pump1 ansible_host=172.16.10.72 deploy_dir=/data1/pump
  pump2 ansible_host=172.16.10.73 deploy_dir=/data2/pump
  pump3 ansible_host=172.16.10.74 deploy_dir=/data3/pump
  ```
```

1. Pump TiDB
   i. pump_servers node_exporters

```
$ ansible-playbook deploy.yml --tags=pump -l ${pump1_ip},${pump2_ip},[${alias1_name},${alias2_name}]
###
```

   i. pump_servers

```
$ ansible-playbook start.yml --tags=pump
```

   i. tidb_servers

```
$ ansible-playbook rolling_update.yml --tags=tidb
```

   i.

```
$ ansible-playbook rolling_update_monitor.yml --tags=prometheus
```

2. Pump

binlogctl Pump pd-urls PD State online Pump

```
   $ cd /home/tidb/tidb-ansible &&
   resources/bin/binlogctl -pd-urls=http://172.16.10.72:2379 -cmd pumps
   INFO[0000] pump: {NodeID: ip-172-16-10-72:8250, Addr: 172.16.10.72:8250, State: online, MaxCommitTS: 4030515256908
84099, UpdateTime:   2018-12-25 14:23:37 +0800 CST}
   INFO[0000] pump: {NodeID: ip-172-16-10-73:8250, Addr: 172.16.10.73:8250, State: online, MaxCommitTS: 4030515257039
91299, UpdateTime:   2018-12-25 14:23:36 +0800 CST}
   INFO[0000] pump: {NodeID: ip-172-16-10-74:8250, Addr: 172.16.10.74:8250, State: online, MaxCommitTS: 4030515257173
60643, UpdateTime:   2018-12-25 14:23:35 +0800 CST}
```

1. TSO

Drainer initial_commit_ts initial_commit_ts

```
$ cd /home/tidb/tidb-ansible &&
resources/bin/binlogctl -pd-urls=http://127.0.0.1:2379 -cmd generate_meta
INFO[0000] [pd] create pd client with endpoints [http://192.168.199.118:32379]
INFO[0000] [pd] leader switches to: http://192.168.199.118:32379, previous:
INFO[0000] [pd] init cluster id 6569368151110378289
2018/06/21 11:24:47 meta.go:117: [info] meta: &{CommitTS:400962745252184065}
```

meta: &{CommitTS:400962745252184065} CommitTS

1. mydumper
2. loader
3. Drainer Drainer

   i. tidb-ansible/inventory.ini drainer_servers IPinitial_commit_ts initial_commit_ts Drainer ``` [drainer_servers] drainer_mysql ansible_host=172.16.10.71 initial_commit_ts="402899541671542785"

```

2.
```

cd /home/tidb/tidb-ansible/conf && cp drainer.toml drainer_mysql_drainer.toml && vi drainer_mysql_drainer.toml

```
```
[syncer]
# downstream storage, equal to --dest-db-type
# Valid values are "mysql", "file", "tidb", "kafka".
db-type = "mysql"
# the downstream MySQL protocol database
[syncer.to]
host = "172.16.10.72"
user = "root"
password = "123456"
port = 3306
```

   i. Drainer

```
ansible-playbook deploy_drainer.yml
```

   ii. Drainer

```
ansible-playbook start_drainer.yml
```

   Drainer
```

sync-diff-inspector PingCAP sync-diff-inspector

TiDB-Binlog TiDB TiDB MySQL Drainer PB TiDB-Binlog PingCAP

# 4.1

## 4.1.1 Raft

1.Raft TiDB PD TiKV Raft Raft

- Raft Raft Raft leader
- Raft Raft Group leader Raft Group quorum leader

2.Raft TiDB Raft Raft Group n Raft Group

- n Raft Group (n-1)/2
- n Raft Group n/2 -1

3. Raft Group

- 1 1 4
- n/2 leader
- leader

4. Raft

- 1 3
- 1 3
- 1 3
- 1 3

Raft 3 Raft on-premise 3 2 3

Raft 2:1 3 ACID

TiKV Raft Raft

## 4.1.2

TiDB Raft

3 6 Raft 3

- 
- 
- 
- RPORecovery Point Objective 0 RTORecovery Time Objective

### 4.1.3

Raft Raft Group quorumquorum Raft Group TiKV Raft Group quorum 2:1 Raft leader quorum 3 quorum 2

## 1. TiKV

TiKV custom quorum quorum Q1(n) = floor((n + 1) / 2) + 1 quorum quorum 3 leader follower

**(1)**

TiKV `max-idle-time` region raft group leader `max-idle-time` Oracle DG // region raft group leader quorum Q2(n) = floor(n / 2) + 1 2 term Raft log gap quorum Q1(n) PD

**(2)**

5 & 3 5%

## 2. TiDBPD

TiDB tidb-server PD 2:1 quorum PD pd-recover

## 3.

`max-idle-time`

### 4.1.4

**(1)**

`max-idle-time` `max-idle-time` region `max-idle-time`

**(2)**

TiKV `max-idle-time` `max-idle-time` `max-store-down-time` PD PD

**(3)**

TiKV region `pd-recover` PD `tikv-ctl`

## 4. RPO RTO

- RPO = 0
  - 0
- RTO
  - RTO `max-idle-time`
  - RTO `max-idle-time`

- RTO PD DBA TiKV DBA

# 1.

TiDB Raft Region leader PD leader

## 1.1

TiDB IDC1 IDC2 IDC3 3ms ISP 20ms

1

- TiDB-Binlog
- IDC1 IDC2 IDC3
- 5 IDC1 IDC2 2 IDC3 1 TiKV Label
- TiDB-Binlog

1

PD region leader region leader

- 
- 
- 

Raft Raft

## 1.2

2

1. 2 IDC1 IDC2 IDC1 RAC1RAC2RAC3 IDC2 RAC4RAC5 IDC3 RAC6RAC7 RAC7 TiDB T+1

2. RAC1 TiDBPD TiKV TiKV 2 TiKV tikv-server TiKV PCIe SSD TiKV RAC2RAC4RAC5RAC6

3. RAC3 TiDB-Server + TiDB-Server + TiDB-AnsiblePrometheusGrafana
4. 2 TiKV 3 TiDB PD
5. Mydumper Dranier Drainer PB

# 2.

## 2.1 inventory

inventory.ini

```
## TiDB Cluster Part
[tidb_servers]
TiDB-10   ansible_host=10.63.10.10     deploy_dir=/data/tidb_cluster/tidb
TiDB-11   ansible_host=10.63.10.11     deploy_dir=/data/tidb_cluster/tidb
TiDB-12   ansible_host=10.63.10.12     deploy_dir=/data/tidb_cluster/tidb
TiDB-13   ansible_host=10.63.10.13     deploy_dir=/data/tidb_cluster/tidb
TiDB-14   ansible_host=10.63.10.14     deploy_dir=/data/tidb_cluster/tidb

[tikv_servers]
TiKV-30   ansible_host=10.63.10.30     deploy_dir=/data/tidb_cluster/tikv  tikv_port=20171   labels="dc=1,rack=1,zone
=1,host=30"
TiKV-31   ansible_host=10.63.10.31     deploy_dir=/data/tidb_cluster/tikv  tikv_port=20171   labels="dc=1,rack=2,zone
```

```
=2,host=31"
TiKV-32   ansible_host=10.63.10.32     deploy_dir=/data/tidb_cluster/tikv  tikv_port=20171   labels="dc=2,rack=3,zone
=3,host=32"
TiKV-33   ansible_host=10.63.10.33     deploy_dir=/data/tidb_cluster/tikv  tikv_port=20171   labels="dc=2,rack=4,zone
=4,host=33"
TiKV-34   ansible_host=10.63.10.34     deploy_dir=/data/tidb_cluster/tikv  tikv_port=20171   labels="dc=3,rack=5,zone
=5,host=34"

[pd_servers]
PD-10    ansible_host=10.63.10.10    deploy_dir=/data/tidb_cluster/pd
PD-11    ansible_host=10.63.10.11    deploy_dir=/data/tidb_cluster/pd
PD-12    ansible_host=10.63.10.12    deploy_dir=/data/tidb_cluster/pd
PD-13    ansible_host=10.63.10.13    deploy_dir=/data/tidb_cluster/pd
PD-14    ansible_host=10.63.10.14    deploy_dir=/data/tidb_cluster/pd

[spark_master]

[spark_slaves]

[lightning_server]

[importer_server]

## Monitoring Part
# prometheus and pushgateway servers
[monitoring_servers]
proth-60 ansible_host=10.63.10.60     prometheus_port=8380  deploy_dir=/data/tidb_cluster/prometheus

[grafana_servers]
graf-60   ansible_host=10.63.10.60     grafana_port=8690  grafana_collector_port=8691  deploy_dir=/data/tidb_cluster/
grafana

# node_exporter and blackbox_exporter servers
[monitored_servers]
10.63.10.10
10.63.10.11
10.63.10.12
10.63.10.13
10.63.10.14
10.63.10.30
10.63.10.31
10.63.10.32
10.63.10.33
10.63.10.34

[alertmanager_servers]
alertm  ansible_host=10.63.10.60    deploy_dir=/data/tidb_cluster/alertmanager

[kafka_exporter_servers]

## Binlog Part
[pump_servers]
pump-10    ansible_host=10.63.10.10    deploy_dir=/data/tidb_cluster/pump
pump-11    ansible_host=10.63.10.11    deploy_dir=/data/tidb_cluster/pump
pump-12    ansible_host=10.63.10.12    deploy_dir=/data/tidb_cluster/pump
pump-13    ansible_host=10.63.10.13    deploy_dir=/data/tidb_cluster/pump

[drainer_servers]

## Group variables
[pd_servers:vars]
location_labels = ["dc","rack","zone","host"]

## Global variables
[all:vars]
deploy_dir = /data/tidb_cluster/tidb

## Connection
# ssh via normal user
ansible_user = tidb

cluster_name = test
```

```
tidb_version = v3.0.5

# process supervision, [systemd, supervise]
process_supervision = systemd

timezone = Asia/Shanghai

enable_firewalld = False
# check NTP service
enable_ntpd = False
set_hostname = False

## binlog trigger
enable_binlog = True

# kafka cluster address for monitoring, example:

# zookeeper address of kafka cluster for monitoring, example:
# zookeeper_addrs = "192.168.0.11:2181,192.168.0.12:2181,192.168.0.13:2181"

# enable TLS aut hentication in the TiDB cluster
enable_tls = False

# KV mode
deploy_without_tidb = False

# wait for region replication complete before start tidb-server.
wait_replication = True

# Optional: Set if you already have a alertmanager server.
# Format: alertmanager_host:alertmanager_port
alertmanager_target = ""

grafana_admin_user = ""
grafana_admin_password = ""

### Collect diagnosis
collect_log_recent_hours = 2
enable_bandwidth_limit = True
# default: 10Mb/s, unit: Kbit/s
collect_bandwidth_limit = 10000
```

# 2.2 inventory

inventory.ini TiDB ansible-playbook -l

1.TiDB Servers

```
[tidb_servers]
TiDB-10  ansible_host=10.63.10.10  deploy_dir=/data/tidb_cluster/tidb
TiDB-11  ansible_host=10.63.10.11  deploy_dir=/data/tidb_cluster/tidb
```

2.TiKV Servers tikv label PD

```
[tikv_servers]
TiKV-30 ansible_host=10.63.10.30 deploy_dir=/data/tidb_cluster/tikv1 tikv_port=20171  labels="dc=1,rack=1,zone=1,host
=30"
TiKV-31 ansible_host=10.63.10.31 deploy_dir=/data/tidb_cluster/tikv1 tikv_port=20171  labels="dc=1,rack=2,zone=2,host
=31"
```

3.PD PD TiKV

```
[pd_servers:vars]
location_labels = ["dc","rack","zone","host"]
```

## 2.3 Labels

Labels DCAZRACKHOST

3 label

## 2.4

- tikv.yml

/tidb-ansible/conf/tikv.yml

```
+ block-cache-size
 TiKV
```

capacity = MEM_TOTAL * 0.5 / TiKV ：

```
```
Storage:
  block-cache:
     capacity: “1G”
```
```

- grpc gRPC

```
server:
grpc-compression-type: gzip
```

- pd.yml /tidb-ansible/conf/pd.yml

PD balance PD PD score store leader Region Region size PD balance

```
```
schedule:
  tolerant-size-ratio: 20.0
```
```

- DC3 TiKV /tikv/conf/tikv.toml

TiKV raft DC3 TiKV DC3 TiKV

```
```
raftstore:
 raft-min-election-timeout-ticks= 1000
 raft-max-election-timeout-ticks= 1020
```
```

- PD control
  - TiKV raft 5

    ```
    config set max-replicas 5
    ```

  - raft leader raft leader TiDB raft leader

    ```
    config set label-property reject-leader dc dc3
    ```

  - PD PD leader PD () PD

    ```
    member leader_priority PD-10 5
    member leader_priority PD-11 5
    member leader_priority PD-12 5
    member leader_priority PD-13 5
    member leader_priority PD-14 1
    ```

# 4.4 AWS AZ TiDB

AWS (region)Availability Zones AZ TiDB

## 4.4.1

TiDB EC2 AWS TiDB AZ

### 1.

PD AWS AZ TiKV region AWS AZ

- PD AZ PD
- max-replicas 3

AZ PD region AWS AZ Northern Virginia AZ AWS AZ

- PD AZ (2:2:1)
- max-replicas 5

max-replicas=3 AZ EC2

### 2. (location labels)

TiKV

- 
- 
- (logical group)
- AZ

10 TiKV AZ 1a:1b:1c=2:4;4max-replicas=5

- PDlocation-labels = ["az","zone","host"]
- TiKV

| az | zone | host |
|---|---|---|
| az=1a | zone=1 | host=1a_1 |
| az=1a | zone=1 | host=1a_2 |
| az=1b | zone=2 | host=1b_1 |
| az=1b | zone=2 | host=1b_2 |
| az=1b | zone=3 | host=1b_3 |
| az=1b | zone=3 | host=1b_4 |
| az=1c | zone=4 | host=1c_1 |
| az=1c | zone=4 | host=1c_2 |
| az=1c | zone=5 | host=1c_3 |
| az=1c | zone=5 | host=1c_4 |

zone PD Region Peer AZ(3 AZ ,5 ) az.zone ( 5 zone5 ) az.zone Region peer zone az.zone 5 zone AZ az.zone.host Region peers

### 3. (placement groups)

Placement Groups Partition Placement Groups Spread Placement Groups placement groups

### 4.

AWS

(Recovery Time Objective, RTO)

## 4.4.2 AZ

AWS AZ AZ 1 AZ 23

AZ (1a, 1b, 1c) AZ (1a) AZ

### Reject region leaders

AZ region leader

```
$ pd-ctl --pd="http://pd-url:2379"

» config set label-property reject-leader az 1a

» config show label-property

{
  "reject-leader": [
    {
      "key": "az",
      "value": "1a"
    }
  ]
}
```

### 1. PD leader

AZ PD leader AZ PD leader 1a PD leader_priority 3 1b 1c PD leader_priority 5 leader_priority

```
» member leader_priority pd_1a_1 3
Success!

» member leader_priority pd_1c_1 5
Success!

» member leader_priority pd_1b_1 5
Success!


» member
{
...
  "members": [
    {
      "name": "pd_1a_1",
...
      "leader_priority": 3
    },
    {
      "name": "pd_1b_1",
...
      "leader_priority": 5
    },
...
    {
      "name": "pd_1c_1",
...
      "leader_priority": 5
    }
  ],
  "leader": {
...
  },
  "etcd_leader": {
...
  }
}
```

## 2. TiDB server

TiDB server AZ AZ AZ TiDB 1a1b 1c 1a TiDB 1b 1c1b 1c —— TiDB AZ

# 4.4.3

## 1.

Adjust the alerts if you know for sure that triggered alerts are false alarms due to AWS hardware. For our deployment on AWS, alerts related to disk latency had to be adjusted in 2 ways:

- Increase “for” duration from 1m to 5m so that intermittent performance degradations for short period are ignored
- Increase the threshold so that lower hardware performance compared to the on-prem deployment is accounted for

AWS AWS

- “for” 1m 5m
- 

## 2.

EC2 20

- TiDB
- EC2 —— TiDB

# 5

IBM Db2MongodbMySQLOracle DRDSSQL ServerTiDBTiDB

- IBM Db2  TiDB (CDC)
- MongoDB  TiD
- DM  MySQL  TiDB
- Oracle  TiDB (OGG)
- DM  MySQL  TiDB
- DM  MySQL  TiDB
- SQLServer  TiDB (DataX)
- SQL Server  TiDB (yutong)
- TiDB  TiDB (DataX)

# 5.1 DM  MySQL  TiDB

DM (Data Migration)  MySQL  MariaDB  TiDB

DM

# 5.1.1 DM MySQL TiDB

MySQL TiDB

8 DM 1.0.2

- DM
- DM
- DM
- 
- task
- 
- 
- tips

## 1. DM

- &
- SQL
- 
- 

## 2. DM

- 
  - 5.5 < MySQL < 8.0
  - MariaDB >= 10.1.2
- TiDB parser DDL
- sql_model
- binlog binlog_format=ROW
- 

## 3. DM

DM 5

- DM-masterDM
- DM-woker
  - DM-worker MySQL MariaDB slave
  - DM DM-worker MySQL MariaDB
  - DM-worker
  - Dumper
  - Loader dumper TiDB
  - Syncer relay log binlog event event SQL SQL TiDB
- dmctlDM DM-Master
- task DM-worker DM-worker
- Prometheus

# 4.

- 

| | | |
|---|---|---|
| DM-Master | 172.16.10.71 | 8261 |
| DM-worker | 172.16.10.72 | 8262 |
| MariaDB | 172.16.10.81 | 3306 |
| TiDB | 172.16.10.83 | 4000 |

- 
  - MySQL book session TiDB
  - mysql,information_schema,percona,performance_schema
  - droptruncate
  - book draft
- DMTiDBinventory.ini
  - [dm_worker_servers]
    - 1.server_id MySQL TiDB
    - 2.source_id task
    - 3.mysql_password dmctl task
      - eg: dm-ansible/resources/bin/dmctl -encrypt
    - 3.enable_gtid GTID MySQL GTID
    - 4.

```
[dm_worker_servers]
dm-worker1 ansible_host=1.1.1.1 source_id="mariadb-01" server_id=101 mysql_host=172.16.10.81 mysql_user=tidbdm mysql_
password="encryptpwd" mysql_port=3306
```

- MySQL
  - 
    - REPLICATION SLAVE
    - REPLICATION CLIENT
    - RELOAD
    - SELECT
- TiDB
- task
  - 
    - 
    - 
    - (binlog position) binlog
  - Binlog
    - book
    - 
    - 

# 5. task

task DM-Worker 9

-

```
name: "taskname"    #  task
task-mode: all      #
meta-schema: "dm_meta"   # checkpoint
remove-meta: false    #  checkpoint
```

- target-database TiDB DM-Worker
- mysql-instances MySQL source-id

```
source-id: "mariadb-01"    # dm-worker  source-id
route-rules: ["book-route-rules-schema", "book-route-rules"] #
filter-rules: ["book-filter-1"]   #  binlog event
black-white-list:  "bookblack"     #

mydumper-config-name: "global"    # mydumper
mydumper-thread: 4

loader-config-name: "global"      # loader
loader-thread: 8

syncer-config-name: "global"      # syncer
syncer-thread: 9
```

- routes

```
book-route-rules-schema: # mysql-instances
    schema-pattern: "book"
    target-schema: "book"
book-route-rules:
    schema-pattern: "book"
    table-pattern: "session"
    target-schema: "book"
    target-table: "session"
```

- filtersBinlog Event

```
book-filter-1:
    schema-pattern: "book"
    table-pattern: "session"
    events: ["truncate table", "drop table"]
    action: Ignore
```

- black-white-list

```
bookblack:
    do-dbs: ["~^book.*"]
    ignore-dbs: ["mysql", "performance_schema", "percona", "information_schema"]
    ignore-tables:
     - db-name: "book.*"
       tbl-name: "draft"
```

- mydumpers

```
global:
    mydumper-path: "./bin/mydumper"
    threads: 4
    chunk-filesize: 64
    skip-tz-utc: true
```

- loaders

```
global:
    pool-size: 8
    dir: "./dumped_data"
```

- syncers

```
global:
    worker-count: 8
    batch: 100
```

# 6.

task dmctl

- dmctl DM-master task

```
./dmctl -master-addr 172.16.10.71:8261
```

-

```
» check-task  task-path
{
 "result": true,
 "msg": "check pass!!!"
}
```

-

```
» start-task  task-path
{
 "result": true,
 "msg": "",
 "workers": [
    {
        "result": true,
        "worker": "172.16.10.72:8262",
        "msg": ""
        },
    ]
  }
```

- result trueworker binlog

```
query-status  taskname
```

-

```
query-error taskname
```

-

```
start-task  taskname
```

-

# 7.

- task
- resume-task
- SQL
- Data Migration

- task

```
"msg": "[code=44003:class=schema-tracker:scope=downstream:level=high] current pos (mysql-bin.000010, 814332497): fail
ed to create table for `db_1`.`tb_1` in schema tracker: [types:1067]Invalid default value for 'expire_time'
```

- db_1.tb_1

```
expire_time  datetime NOT NULL DEFAULT '0000-00-00 00:00:00'
```

-
- sql_modedatetime '0000-00-00 00:00:00'

```
TiDB> show variables like 'sql_mode';
+---------------+--------------------------------------------+
| Variable_name | Value                                      |
+---------------+--------------------------------------------+
| sql_mode      | STRICT_TRANS_TABLES,NO_ENGINE_SUBSTITUTION |
+---------------+--------------------------------------------+
```

- sql_mode task

# 8. Tips

- task MySQL
- task meta binlog
-
- task DM Portal
- DM-worker Rely log

# 5.1.2 DM MySQL TiDB

## 5.1.2.1 DM

DRDS DM TiDB

1.
2. DBA
3. TiDB

ID DM

dm loader binlog

### 1.

| IP | | | | |
|---|---|---|---|---|
| 192.168.128.131 | centos7.3 x86_64 | MySQL5.7 | 3306 | root/password |
| 192.168.128.131 | centos7.3 x86_64 | MySQL5.7 | 3307 | root/password |
| 192.168.128.131 | centos7.3 x86_64 | MySQL5.7 | 3308 | root/password |
| 192.168.128.132 | centos7.3 x86_64 | dm-master/dmctl | | root/password |
| 192.168.128.133 | centos7.3 x86_64 | dm-worker | dm-worker | root/password |
| 192.168.206.28 | centos7.3 x86_64 | TiDB | 4000 | root/password |

### 2.

**root 192.168.128.132**

```
[tidb@dmmaster ~]# yum -y install epel-release git curl sshpass
[tidb@dmmaster ~]# yum -y install python-pip
```

**tidb SSH**

1 tidb

```
[tidb@dmmaster ~]# useradd -m -d /home/tidb tidb
```

2 tidb

```
[tidb@dmmaster ~]# echo "password" | passwd --stdin tidb
```

3 tidb sudo

```
[tidb@dmmaster ~]# echo "tidb ALL=(ALL) NOPASSWD: ALL" >>/etc/sudoers
```

4 tidb home SSH

```
[tidb@dmmaster ~]# su - tidb
[tidb@dmmaster ~]$ ssh-keygen -t rsa
```

**tidb DM-Ansible**

```
[tidb@dmmaster ~]$ wget https://download.pingcap.org/dm-ansible-v1.0.2.tar.gz
```

**DM-Ansible**

```
[tidb@dmmaster ~]$ tar -xf dm-ansible-v1.0.2.tar.gz
[tidb@dmmaster ~]$ mv dm-ansible-v1.0.2.tar.gz dm-ansible
[tidb@dmmaster ~]$ cd /home/tidb/dm-ansible
[tidb@dmmaster dm-ansible]$ sudo pip install --upgrade pip
[tidb@dmmaster dm-ansible]$ sudo pip install -r ./requirements.txt
```

**: ssh sudo**

```
[tidb@dmmaster dm-ansible]$ cat hosts.ini
[servers]
192.168.128.132
192.168.128.133
[all:vars]
username = tidb
ansible_ssh_port = 22
ntp_server = ntp.aliyun.com
```

dm-worker tidb root password

```
[tidb@dmmaster dm-ansible]$ ansible-playbook -i hosts.ini create_users.yml -u root -k
SSH password:
PLAY [all]
*******************************************************************
TASK [create user]
*******************************************************************
changed: [192.168.128.133]
TASK [set authorized key]
*******************************************************************
changed: [192.168.128.133]
TASK [update sudoers file] ******************************************************************
changed: [192.168.128.133]
PLAY RECAP
*******************************************************************
192.168.128.133    : ok=3    changed=3    unreachable=0    failed=0
```

**DM**

```
[tidb@dmmaster dm-ansible]$ ansible-playbook local_prepare.yml
PLAY [do local preparation] *****************************************************************
TASK [download : Stop if ansible version is too low, make sure that the Ansible version is Ansible 2.5.0 or later, ot
herwise a compatibility issue occurs.]
*******************************************************************
ok: [localhost] => {
    "changed": false,
    "msg": "All assertions passed"
}

localhost  : ok=13   changed=5    unreachable=0    failed=0
```

**MySQL TiDB**

```
root@localhost >grant Reload,Replication slave, Replication client,select on *.* to tidb@'%' IDENTIFIED by 'tidb@2020
';
```

**dmctl**

```
[tidb@dmmaster bin]$ dmctl -encrypt tidb@2020
BXTTVvKeWhXgAefaFRNoN0BS4XjZ85uZByE=
```

## 3. dm-worker

**inventory.ini**

dm-master dm-worker dm-worker

```
[tidb@dmmaster dm-ansible]$ cat inventory.ini
## DM modules
[dm_master_servers]
dm_master ansible_host=192.168.128.132
[dm_worker_servers]
dm_worker3306 ansible_host=192.168.128.133 deploy_dir=/data/mysql3306 dm_worker_port=13306 source_id="mysql3306" serv
er_id=13306 mysql_host=192.168.128.131 mysql_user=tidb mysql_password=BXTTVvKeWhXgAefaFRNoN0BS4XjZ85uZByE mysql_port=
3306
dm_worker3307 ansible_host=192.168.128.133 deploy_dir=/data/mysql3307 dm_worker_port=13307 source_id="mysql3307" serv
er_id=13307 mysql_host=192.168.128.131 mysql_user=tidb mysql_password=BXTTVvKeWhXgAefaFRNoN0BS4XjZ85uZByE mysql_port=
3307
dm_worker3308 ansible_host=192.168.128.133 deploy_dir=/data/mysql3308 dm_worker_port=13308 source_id="mysql3308" serv
er_id=13308 mysql_host=192.168.128.131 mysql_user=tidb mysql_password=BXTTVvKeWhXgAefaFRNoN0BS4XjZ85uZByE mysql_port=
3308
[dm_portal_servers]
dm_portal ansible_host=192.168.128.132
## Monitoring modules
[prometheus_servers]
prometheus ansible_host=192.168.128.132
[grafana_servers]
grafana ansible_host=192.168.128.132
[alertmanager_servers]
alertmanager ansible_host=192.168.128.132
## Global variables
[all:vars]
cluster_name = dm-cluster
ansible_user = tidb
ansible_port = 5622
dm_version = v1.0.2
deploy_dir = /home/tidb/deploy
grafana_admin_user = "admin"
grafana_admin_password = "admin"
```

```
inventory.ini
[dm_master_servers]  dm-master  dm-master
[dm_worker_servers]  dm-worker  dm-worker
----dm_worker3306    dmansible-playbook -l
----ansible_host      dm-worker
----dm_worker_port    dm-worker
----deploy_dir        dm-worker
----source_id         dm-worker  source-id
----mysql_host       MySQL
----mysql_user       MySQL
----mysql_port       MySQL
----mysql_password   MySQL(dmctl,2.2)
```

**dm-worker**

dm-worker:

```
[tidb@dmmaster dm-ansible]$ ansible-playbook deploy.yml
PLAY RECAP *********************************************************************
alertmanager    : ok=13   changed=7    unreachable=0    failed=0
dm_master       : ok=13   changed=8    unreachable=0    failed=0
dm_portal       : ok=12   changed=5    unreachable=0    failed=0
dm_worker3306   : ok=14   changed=2    unreachable=0    failed=0
dm_worker3307   : ok=14   changed=2    unreachable=0    failed=0
dm_worker3308   : ok=14   changed=2    unreachable=0    failed=0
grafana         : ok=17   changed=10   unreachable=0    failed=0
localhost       : ok=4    changed=3    unreachable=0    failed=0
prometheus      : ok=15   changed=13   unreachable=0    failed=0
#
```

dm-worker:

```
[tidb@dmmaster dm-ansible]$ ansible-playbook start.yml
PLAY RECAP *********************************************************************
alertmanager   : ok=10   changed=1    unreachable=0    failed=0
dm_master      : ok=10   changed=1    unreachable=0    failed=0
dm_portal      : ok=9    changed=1    unreachable=0    failed=0
dm_worker3306  : ok=11   changed=1    unreachable=0    failed=0
dm_worker3307  : ok=11   changed=1    unreachable=0    failed=0
dm_worker3308  : ok=11   changed=1    unreachable=0    failed=0
grafana        : ok=13   changed=1    unreachable=0    failed=0
localhost      : ok=4    changed=0    unreachable=0    failed=0
prometheus     : ok=13   changed=4    unreachable=0    failed=0
# dm  binlog  dm
```

## 4. & task

**TiDB**

| | | | |
|---|---|---|---|
| shard_db01 | shard_tb01 | merge_db | merge_tb |
| shard_db02 | shard_tb02 | | |
| shard_db03 | shard_tb03 | | |
| shard_db04 | shard_tb04 | | |
| shard_db05 | shard_tb05 | | |
| shard_db06 | shard_tb06 | | |

```
CREATE TABLE shard_tb01~06 (
  id bigint(20) NOT NULL AUTO_INCREMENT COMMENT'ID',
  uid bigint(20) NOT NULL COMMENT 'ID',
  uname varchar(10) NOT NULL DEFAULT '' COMMENT '',
  gender tinyint(1) NOT NULL DEFAULT '0' COMMENT ' 0-1-',
  shard varchar(50) NOT NULL DEFAULT '' COMMENT '',
  mobile varchar(15) NOT NULL DEFAULT '' COMMENT '',
  PRIMARY KEY (id)
) ENGINE=InnoDB DEFAULT CHARSET=utf8mb4 COMMENT='';
INSERT INTO shard_db01.shard_tb01
(uid,uname,gender,shard,mobile) VALUES
('10001','tb01001','0','shard_db01_tb01','136******17'),('10002','tb01002','1','shard_db01_tb01','136******17');
INSERT INTO shard_db02.shard_tb02
(uid,uname,gender,shard,mobile) VALUES ('20001','tb02001','1','shard_db02_tb02','136******33'), ('20002','tb02002','0
','shard_db02_tb02','139******63');
INSERT INTO shard_db03.shard_tb03
(uid,uname,gender,shard,mobile) VALUES ('30001','tb03001','0','shard_db03_tb03','135******73'),
('30002','tb03002','0','shard_db03_tb03','139******46');

INSERT INTO shard_db04.shard_tb04
(uid,uname,gender,shard,mobile) VALUES ('40001','tb04001','0','shard_db04_tb04','137******91'),('40002','tb04002','1'
,'shard_db04_tb04','138******91');
INSERT INTO shard_db05.shard_tb05
(uid,uname,gender,shard,mobile) VALUES ('50001','tb05001','1','shard_db05_tb05','158******96'),('50002','tb05002','0'
,'shard_db05_tb05','188******92');
INSERT INTO shard_db06.shard_tb06
(uid,uname,gender,shard,mobile) VALUES ('60001','tb06001','1','shard_db06_tb06','178******98'),('60002','tb06002','1'
,'shard_db06_tb06','175******31');
```

### task yaml

```
[tidb@tidb-dm-4-0-95 task]$ cat shardmysql_to_tidb.yaml
name: "shard_to_tidb"  #task
is-sharding: true      #
task-mode: "all"       # full-incremental-all-+
meta-schema: "tidb_meta"   #
remove-meta: false
target-database:
  host: "192.168.206.28" # TiDB  IP
  port: 4000             #TiDB
  user: "root"           #TiDB
  password: "vLnqQt44rNFHSxA"    # dmctl
mysql-instances:
-
  source-id: "mysql3306"   # inventory.ini  source-id
  route-rules: ["rt000","rt001"]      #
  filter-rules: ["ymdd-filter-rule"]  #
  mydumper-config-name: "global"
  loader-config-name: "global"
  syncer-config-name: "global"
  black-white-list: "br01"       #
  column-mapping-rules: ["cm001"]   #
-
  source-id: "mysql3307"
  route-rules: ["rt000","rt001"]
  filter-rules: ["ymdd-filter-rule"]
  mydumper-config-name: "global"
  loader-config-name: "global"
  syncer-config-name: "global"
  black-white-list: "br01"
  column-mapping-rules: ["cm002"]
-
  source-id: "mysql3308"
  route-rules: ["rt000","rt001"]
  filter-rules: ["ymdd-filter-rule"]
  mydumper-config-name: "global"
  loader-config-name: "global"
  syncer-config-name: "global"
  black-white-list: "br01"
  column-mapping-rules: ["cm003"]
```

```
filters:
  ymdd-filter-rule:
    schema-pattern: "shard_db *"
    # 2  binlog
    events: ["truncate table","delete","drop table","drop database"]
    action: Ignore

routes:
  rt000:
    # shard_db* merge_db
    schema-pattern: "shard_db*"
    target-schema: "merge_db"
  rt001:
    # shard_tb* merge_db  merge_tb
    schema-pattern: "shard_db*"
    table-pattern: "shard_tb??"
    target-schema: "merge_db"
    target-table:  "merge_tb"

#
#
column-mappings:
  cm001:
    schema-pattern: "shard_db*"
    table-pattern: "shard_tb??"
    expression: "partition id"
    source-column: "id"
    target-column: "id"
    arguments: ["1","shard_db","shard_tb"]
  cm002:
    schema-pattern: "shard_db*"
    table-pattern: "shard_tb??"
    expression: "partition id"
    source-column: "id"
    target-column: "id"
    arguments: ["2","shard_db","shard_tb"]
  cm003:
    schema-pattern: "shard_db*"
    table-pattern: "shard_tb??"
    expression: "partition id"
    source-column: "id"
    target-column: "id"
    arguments: ["3","shard_db","shard_tb"]
#
black-white-list:
  br01:
    do-dbs: ["~shard_db*"]  #
    #
    ignore-dbs: ["mysql","performance_schema","information_schema"]
    #
    ignore-tables:
    - db-name: "~shard_db*"
      tbl-name: "~txc_undo_log*"
#
mydumpers:
  global:
    threads:
    chunk-filesize: 64
    skip-tz-utc: true
    extra-args: " --no-locks "
loaders:
  global:
    pool-size: 64
    dir: "./dumped_data"
syncers:
  global:
    worker-count: 6
    batch: 1000
```

```
[tidb@dmmaster dmctl]$ dmctl -master-addr 192.168.128.132:8261
» start-task shard_to_tidb.yaml
» query-status
{
    "result": true,
    "msg": "",
    "tasks": [
        {
            "taskName": "shard_to_tidb",
            "taskStatus": "Running",
            "workers": [
                "192.168.128.133:53306",
                "192.168.128.133:53307",
                "192.168.128.133:53308"
            ]
        }
    ]
}
#
```

**TiDB dm-worker**

```
[root@dmworker dumped_data.shard_to_tidb]# ll |awk '{print $NF}'
metadata
shard_db01-schema-create.sql
shard_db01.shard_tb01-schema.sql
shard_db01.shard_tb01.sql
shard_db02-schema-create.sql
shard_db02.shard_tb02-schema.sql
shard_db02.shard_tb02.sql
```

```
[root@dmworker dumped_data.shard_to_tidb]# ls | grep -v schema | xargs rm -f
[root@dmworker dumped_data.shard_to_tidb]# ls
shard_db01.shard_tb01-schema.sql    shard_db02.shard_tb02-schema.sql
shard_db02-schema-create.sql
```

**merge_db merge_tb**

| id | uid | uname | gender | shard | mobile | |
|---|---|---|---|---|---|---|
| 580981944116838401 | 10001 | tb01001 | 0 | shard_db01_tb01 | 136 | 17 |
| 580981944116838402 | 10002 | tb01002 | 1 | shard_db01_tb01 | 136 | 17 |
| 585503135930253313 | 20001 | tb02001 | 1 | shard_db02_tb02 | 136 | 33 |
| 585503135930253314 | 20002 | tb02002 | 0 | shard_db02_tb02 | 139 | 63 |
| 1166485080047091713 | 30001 | tb03001 | 0 | shard_db03_tb03 | 135 | 73 |
| 1166485080047091714 | 30002 | tb03002 | 0 | shard_db03_tb03 | 139 | 46 |
| 1171006271860506625 | 40001 | tb04001 | 0 | shard_db04_tb04 | 137 | 91 |
| 1171006271860506626 | 40002 | tb04002 | 1 | shard_db04_tb04 | 138 | 91 |
| 1751988215977345025 | 50001 | tb05001 | 1 | shard_db05_tb05 | 158 | 96 |
| 1751988215977345026 | 50002 | tb05002 | 0 | shard_db05_tb05 | 188 | 92 |
| 1756509407790759937 | 60001 | tb06001 | 1 | shard_db06_tb06 | 178 | 98 |
| 1756509407790759938 | 60002 | tb06002 | 1 | shard_db06_tb06 | 175 | 31 |

# 5.1.2.2 DM

## 1. dm-worker

### deploy.yml

```
#inventory.ini
[tidb@dmmaster dm-ansible]$ ansible-playbook deploy.yml
#-l  mysql3306  dm-worker
[tidb@dmmaster dm-ansible]$ ansible-playbook deploy.yml -l mysql3306
# --tags  deploy.yml  dm-worker
[tidb@dmmaster dm-ansible]$ ansible-playbook deploy.yml --tags=dm-worker
```

### dm-worker

```
# dm  MySQL  binlog
# MySQL  Slave_IO_Running
[tidb@dmmaster dm-ansible]$ ansible-playbook start.yml
# dm  MySQL  binlog
[tidb@dmmaster dm-ansible]$ ansible-playbook stop.yml
# dm
[tidb@dmmaster dm-ansible]$ ansible-playbook rolling_update.yml
*yml-l--tags
```

## 2. dm-worker task

### task dmctl help

```
#
[tidb@dmmaster dm-ansible]$ dmctl -master-addr 192.168.128.132:8261
»help
```

### start-task task MySQL Slave_SQL_Running

```
[tidb@dmmaster dm-ansible]$ dmctl -master-addr 192.168.128.132:8261
# task.yaml  dm-worker
»start-task shard_to_tidb.yaml
# shard_to_tidb.yaml  dm-worker
# shard_to_tidb.yaml  192.168.128.133:53307:
»start-task -w '192.168.128.133:53307' shard_to_tidb.yaml
```

### stop-task MySQL Slave_SQL_Running

```
[tidb@dmmaster dm-ansible]$ dmctl -master-addr 192.168.128.132:8261
# shard_to_tidb.yaml  dm-worker
#-w [ -w IP:PORT]
»start-task shard_to_tidb
```

### query-status

```
[tidb@dmmaster dm-ansible]$ dmctl -master-addr 192.168.128.132:8261
# shard_to_tidb
»query-status shard_to_tidb
```

### query-error

```
[tidb@dmmaster dm-ansible]$ dmctl -master-addr 192.168.128.132:8261
# shard_to_tidb
»query-error shard_to_tidb
```

### skip_sql SQL

```
# binlog (failedBinlogPosition)
query-error shard_to_tidb
# binlog
sql-skip --worker=192.168.128.133:53307 --binlog-pos=mysql-bin|000001.000003:737983  shard_to_tidb
#
resume-task --worker=192.168.128.133:53307  shard_to_tidb
#
query-error shard_to_tidb
```

DBA RDBMS NoSQL

TiDB RDBMS NoSQL MySQL TiDB TiDB TiDB TiDB

TiDB OGG Oracle TiDB

# 5.2.1

## 1.

Oracle GoldenGate 12.3.0.1.4 for Oracle on Linux x86-64

Oracle GoldenGate 12.3.0.1.5 for MySQL-compatible DBs on Linux x86-64

Oracle 11G Oracle OGG TiDB

Oracle ZHS16GBK

## 2.

2.1.

Oracle TiDB Navicat

2.2.

OGG initial load Oracle TiDB Oracle initial load Oracle

2.3.

initial load logOGG handlecolisions

## 3. Oracle

- 
- Force logging
- ENABLE_GOLDENGATE_REPLICATION true (11.2.0.4)
- 
  - 
  - Schema
  - 
- 
  - DBA

## 4. TiDB

- set tidb_constraint_check_in_place = 1;

> TiDB commit insert abend OGG session

- lower-case-table-names = 1

> OGG 1tidb

## 5. OGG

DDL

- Oracle

```
create table account (
  account_number      number(10,0),
  account_balance     decimal(38,2),
  account_trans_ts    timestamp(6),
  account_trans_type  varchar2(30),
  primary key (account_number)
  using index
);
```

- TiDB

```
create table account (
  account_number int,
  account_balance decimal(38,2),
  account_trans_ts timestamp,
  account_trans_type varchar(30),
  primary key (account_number));
```

# 5.2.2

## 1. OGG - Oracle

```
$unzip V975837-01.zip
$ ls -l
total 1201820
drwxr-xr-x 3 oracle oinstall      4096 Apr 16  2018 fbo_ggs_Linux_x64_shiphome
-rw-r--r-- 1 oracle oinstall      1396 May 10  2018 OGG-12.3.0.1.4-README.txt
-rw-r--r-- 1 oracle oinstall    293566 May 10  2018 OGG_WinUnix_Rel_Notes_12.3.0.1.4.pdf
```

(1)

```
$vi ./fbo_ggs_Linux_x64_shiphome/Disk1/response/oggcore.rsp
######################################################################
## Copyright(c) Oracle Corporation 2017. All rights reserved.      ##
##                                                                  ##
## Specify values for the variables listed below to customize      ##
## your installation.                                               ##
##                                                                  ##
## Each variable is associated with a comment. The comment         ##
## can help to populate the variables with the appropriate          ##
## values.                                                          ##
##                                                                  ##
## IMPORTANT NOTE: This file should be secured to have read        ##
## permission only by the oracle user or an administrator who      ##
## own this installation to protect any sensitive input values.    ##
##                                                                  ##
######################################################################
#------------------------------------------------------------------------------
# Do not change the following system generated value.
#------------------------------------------------------------------------------
oracle.install.responseFileVersion=/oracle/install/rspfmt_ogginstall_response_schema_v12_1_2

##############################################################################
##                                                                          ##
```

```
## Oracle GoldenGate installation option and details                          ##
##                                                                            ##
##############################################################################
#-----------------------------------------------------------------------------
# Specify the installation option.
# Specify ORA12c for installing Oracle GoldenGate for Oracle Database 12c and
#         ORA11g for installing Oracle GoldenGate for Oracle Database 11g
#-----------------------------------------------------------------------------
INSTALL_OPTION=ORA11g
## Oracle  11.2.0.4 ORA11G 12c  ORA12c
#-----------------------------------------------------------------------------
# Specify a location to install Oracle GoldenGate
#-----------------------------------------------------------------------------
SOFTWARE_LOCATION=/home/oracle/ogg12.3
##
#-----------------------------------------------------------------------------
# Specify true to start the manager after installation.
#-----------------------------------------------------------------------------
START_MANAGER=false
## mgr  false
#-----------------------------------------------------------------------------
# Specify a free port within the valid range for the manager process.
# Required only if START_MANAGER is true.
#-----------------------------------------------------------------------------
MANAGER_PORT=
#-----------------------------------------------------------------------------
# Specify the location of the Oracle Database.
# Required only if START_MANAGER is true.
#-----------------------------------------------------------------------------
DATABASE_LOCATION=

##############################################################################
##                                                                          ##
## Specify details to Create inventory for Oracle installs                  ##
## Required only for the first Oracle product install on a system.          ##
##                                                                          ##
##############################################################################
#-----------------------------------------------------------------------------
# Specify the location which holds the install inventory files.
# This is an optional parameter if installing on
# Windows based Operating System.
#-----------------------------------------------------------------------------
INVENTORY_LOCATION=
#-----------------------------------------------------------------------------
# Unix group to be set for the inventory directory.
# This parameter is not applicable if installing on
# Windows based Operating System.
#-----------------------------------------------------------------------------
UNIX_GROUP_NAME=
```

(2)

fbo_ggs_Linux_x64_shiphome/Disk1/runInstaller

```
$./fbo_ggs_Linux_x64_shiphome/Disk1/runInstaller -silent -responseFile /home/oracle/oggsoft/fbo_ggs_Linux_x64_shiphom
e/Disk1/response/oggcore.rsp
# response
```

successful

```
The installation of Oracle GoldenGate Core was successful
```

OGG

```
$ ls -l
total 225044
-rwxr-xr-x  1 oracle oinstall      426 Oct 15  2010 bcpfmt.tpl
```

```
-rwxr-xr-x  1 oracle oinstall     1725 Oct 15  2010 bcrypt.txt
-rwxrwxr-x  1 oracle oinstall  1612776 Apr 15  2018 cachefiledump
drwxr-xr-x  4 oracle oinstall     4096 Jul 28 14:45 cfgtoollogs
-rwxrwxr-x  1 oracle oinstall  3563576 Apr 15  2018 checkprm
-rw-rw-r--  1 oracle oinstall     1021 Apr 15  2018 chkpt_ora_create.sql
-rwxrwxr-x  1 oracle oinstall  3379568 Apr 15  2018 convchk
-rwxrwxr-x  1 oracle oinstall  4716080 Apr 15  2018 convprm
drwxr-xr-x  2 oracle oinstall     4096 Jul 28 14:45 crypto
-rwxr-xr-x  1 oracle oinstall      159 Oct 15  2010 db2cntl.tpl
-rwxrwxr-x  1 oracle oinstall     9696 Apr 15  2018 db_upgrade
-rw-rw-r--  1 oracle oinstall      455 Apr 15  2018 ddl_cleartrace.sql
-rw-rw-r--  1 oracle oinstall     8414 Apr 15  2018 ddl_create.sql
-rw-rw-r--  1 oracle oinstall     3176 Apr 15  2018 ddl_ddl2file.sql
-rw-rw-r--  1 oracle oinstall       90 Apr 15  2018 ddl_disable.sql
-rw-rw-r--  1 oracle oinstall       88 Apr 15  2018 ddl_enable.sql
-rw-rw-r--  1 oracle oinstall     2036 Apr 15  2018 ddl_filter.sql
-rw-rw-r--  1 oracle oinstall    12220 Apr 15  2018 ddl_ora10.sql
-rw-rw-r--  1 oracle oinstall     1725 Apr 15  2018 ddl_ora10upCommon.sql
-rw-rw-r--  1 oracle oinstall    13539 Apr 15  2018 ddl_ora11.sql
-rw-rw-r--  1 oracle oinstall    12564 Apr 15  2018 ddl_ora9.sql
-rw-rw-r--  1 oracle oinstall      216 Apr 15  2018 ddl_pin.sql
-rw-rw-r--  1 oracle oinstall     3184 Apr 15  2018 ddl_remove.sql
-rw-rw-r--  1 oracle oinstall        1 Apr 15  2018 ddl_session1.sql
-rw-rw-r--  1 oracle oinstall      629 Apr 15  2018 ddl_session.sql
-rw-rw-r--  1 oracle oinstall   287877 Apr 15  2018 ddl_setup.sql
-rw-rw-r--  1 oracle oinstall     8401 Apr 15  2018 ddl_status.sql
-rw-rw-r--  1 oracle oinstall     2122 Apr 15  2018 ddl_staymetadata_off.sql
-rw-rw-r--  1 oracle oinstall     2118 Apr 15  2018 ddl_staymetadata_on.sql
-rw-rw-r--  1 oracle oinstall     2186 Apr 15  2018 ddl_tracelevel.sql
-rw-rw-r--  1 oracle oinstall     2133 Apr 15  2018 ddl_trace_off.sql
-rw-rw-r--  1 oracle oinstall     2383 Apr 15  2018 ddl_trace_on.sql
-rwxrwxr-x  1 oracle oinstall  5037440 Apr 15  2018 defgen
drwxr-xr-x  2 oracle oinstall     4096 Jul 28 14:45 deinstall
-rw-rw-r--  1 oracle oinstall      882 Apr 15  2018 demo_more_ora_create.sql
-rw-rw-r--  1 oracle oinstall      649 Apr 15  2018 demo_more_ora_insert.sql
-rw-rw-r--  1 oracle oinstall      583 Apr 15  2018 demo_ora_create.sql
-rw-rw-r--  1 oracle oinstall      504 Apr 15  2018 demo_ora_insert.sql
-rw-rw-r--  1 oracle oinstall     3597 Apr 15  2018 demo_ora_lob_create.sql
-rw-rw-r--  1 oracle oinstall     1943 Apr 15  2018 demo_ora_misc.sql
-rw-rw-r--  1 oracle oinstall     1056 Apr 15  2018 demo_ora_pk_befores_create.sql
-rw-rw-r--  1 oracle oinstall     1013 Apr 15  2018 demo_ora_pk_befores_insert.sql
-rw-rw-r--  1 oracle oinstall     2305 Apr 15  2018 demo_ora_pk_befores_updates.sql
drwxr-xr-x  3 oracle oinstall     4096 Jul 28 14:45 diagnostics
drwxr-xr-x  3 oracle oinstall     4096 Jul 28 14:45 diretc
drwxr-xr-x  2 oracle oinstall     4096 Jul 28 14:45 dirout
drwxr-xr-x  4 oracle oinstall     4096 Jul 28 14:45 dirsca
-rwxrwxr-x  1 oracle oinstall  4272400 Apr 15  2018 emsclnt
-rwxrwx---  1 oracle oinstall 12545040 Apr 15  2018 extract
-rwxr-xr-x  1 oracle oinstall     1968 Oct 15  2010 freeBSD.txt
-rwxrwxr-x  1 oracle oinstall  4280528 Apr 15  2018 ggcmd
-rwxr-xr-x  1 oracle oinstall  2303056 Apr 15  2018 ggMessage.dat
-rwxr-xr-x  1 oracle oinstall 49675440 Apr 15  2018 ggparam.dat
-rwxrwx---  1 oracle oinstall  9340192 Apr 15  2018 ggsci
drwxr-xr-x  2 oracle oinstall     4096 Jul 28 14:45 healthcheck
-rwxr-xr-x  1 oracle oinstall   299451 Nov 16  2017 help.txt
drwxr-xr-x  3 oracle oinstall     4096 Jul 28 14:45 install
drwxr-x--- 12 oracle oinstall     4096 Jul 28 14:45 inventory
drwxr-xr-x  7 oracle oinstall     4096 Jul 28 14:45 jdk
-rwxrwxr-x  1 oracle oinstall   144496 Apr 15  2018 keygen
-rw-rw-r--  1 oracle oinstall       56 Apr 15  2018 label.sql
-rwxrwx---  1 oracle oinstall   102840 Apr 15  2018 libantlr3c.so
-rwxrwxr-x  1 oracle oinstall    12312 Apr 15  2018 libboost_system-mt.so.1.58.0
-rwxrwx---  1 oracle oinstall  2190856 Apr 15  2018 libdb-6.1.so
-rwxrwx---  1 oracle oinstall  2198136 Apr 15  2018 libgglog.so
-rwxrwx---  1 oracle oinstall 10524064 Apr 15  2018 libggnnzitp.so
-rwxrwx---  1 oracle oinstall 21993240 Apr 15  2018 libggparam.so
-rwxrwx---  1 oracle oinstall   210264 Apr 15  2018 libggperf.so
-rwxrwx---  1 oracle oinstall   779352 Apr 15  2018 libggrepo.so
-rwxrwx---  1 oracle oinstall  1108760 Apr 15  2018 libggssl.so
-rwxrwx---  1 oracle oinstall   125624 Apr 15  2018 libggutil.so
-rwxrwxr-x  1 oracle oinstall 29764432 Apr 15  2018 libicudata.so.56
-rwxrwxr-x  1 oracle oinstall  2909360 Apr 15  2018 libicui18n.so.56
```

```
-rwxrwxr-x  1 oracle oinstall  1995808 Apr 15  2018 libicuuc.so.56
-rwxrwx---  1 oracle oinstall    86960 Apr 15  2018 liblmdb.so
-rwxrwxr-x  1 oracle oinstall   175136 Apr 15  2018 libPocoCrypto.so.48
-rwxrwxr-x  1 oracle oinstall  3079760 Apr 15  2018 libPocoFoundation.so.48
-rwxrwxr-x  1 oracle oinstall   373232 Apr 15  2018 libPocoJSON.so.48
-rwxrwxr-x  1 oracle oinstall  1326504 Apr 15  2018 libPocoNet.so.48
-rwxrwxr-x  1 oracle oinstall   350064 Apr 15  2018 libPocoNetSSL.so.48
-rwxrwxr-x  1 oracle oinstall   520864 Apr 15  2018 libPocoUtil.so.48
-rwxrwxr-x  1 oracle oinstall   680288 Apr 15  2018 libPocoXML.so.48
-rwxrwx---  1 oracle oinstall  1115360 Apr 15  2018 libudt.so
-rwxrwx---  1 oracle oinstall  4782344 Apr 15  2018 libxerces-c-3.1.so
-rwxrwxr-x  1 oracle oinstall  5025840 Apr 15  2018 logdump
-rw-rw-r--  1 oracle oinstall     1553 Apr 15  2018 marker_remove.sql
-rw-rw-r--  1 oracle oinstall     3309 Apr 15  2018 marker_setup.sql
-rw-rw-r--  1 oracle oinstall      675 Apr 15  2018 marker_status.sql
-rwxrwxr-x  1 oracle oinstall  6570480 Apr 15  2018 mgr
-rwxr-xr-x  1 oracle oinstall    41643 Jun 30  2017 notices.txt
-rwxrwxr-x  1 oracle oinstall  1661024 Apr 15  2018 oggerr
drwxr-xr-x 12 oracle oinstall     4096 Jul 28 14:45 OPatch
-rw-r-----  1 oracle oinstall       59 May 30 13:35 oraInst.loc
drwxr-xr-x  8 oracle oinstall     4096 Jul 28 14:45 oui
-rw-rw-r--  1 oracle oinstall     3146 Apr 15  2018 params.sql
-rwxrwxr-x  1 oracle oinstall 11524576 Apr 15  2018 pmsrvr
-rwxr-xr-x  1 oracle oinstall     1272 Dec 28  2010 prvtclkm.plb
-rwxr-xr-x  1 oracle oinstall     9487 May 27  2015 prvtlmpg.plb
-rw-rw-r--  1 oracle oinstall     2724 Apr 15  2018 prvtlmpg_uninstall.sql
-rw-rw-r--  1 oracle oinstall     1532 Apr 15  2018 remove_seq.sql
-rwxrwx---  1 oracle oinstall 10873240 Apr 15  2018 replicat
-rwxrwxr-x  1 oracle oinstall  1656864 Apr 15  2018 retrace
-rw-rw-r--  1 oracle oinstall     3187 Apr 15  2018 role_setup.sql
-rw-rw-r--  1 oracle oinstall    35254 Apr 15  2018 sequence.sql
-rwxrwxr-x  1 oracle oinstall  4659736 Apr 15  2018 server
-rwxr-xr-x  1 oracle oinstall     4917 Jan  5  2017 SQLDataTypes.h
-rwxr-xr-x  1 oracle oinstall      248 Oct 15  2010 sqlldr.tpl
drwxr-xr-x  3 oracle oinstall     4096 Jul 28 14:45 srvm
-rwxrwxr-x  1 oracle oinstall      759 Oct 15  2010 tcperrs
-rwxr-xr-x  1 oracle oinstall    37877 Apr 16  2016 ucharset.h
-rw-rw-r--  1 oracle oinstall     7341 Apr 15  2018 ulg.sql
drwxr-xr-x  7 oracle oinstall     4096 Jul 28 14:45 UserExitExamples
-rwxr-xr-x  1 oracle oinstall    32987 Jun  2  2017 usrdecs.h
-rwxr-xr-x  1 oracle oinstall     1033 Oct 19  2016 zlib.txt
```

(3) .bash_profile

```
export LD_LIBRARY_PATH=$ORACLE_HOME/lib
```

(4)

```
$ ./ggsci
Oracle GoldenGate Command Interpreter for Oracle
Version 12.3.0.1.4 OGGCORE_12.3.0.1.0_PLATFORMS_180415.0359_FBO
Linux, x64, 64bit (optimized), Oracle 11g on Apr 15 2018 21:16:09
Operating system character set identified as UTF-8.
Copyright (C) 1995, 2018, Oracle and/or its affiliates. All rights reserved.


GGSCI ( hostname ) 1> create subdirs
Creating subdirectories under current directory /home/oracle/ogg12.3
Parameter file                 /home/oracle/ogg12.3/dirprm: created.
Report file                    /home/oracle/ogg12.3/dirrpt: created.
Checkpoint file                /home/oracle/ogg12.3/dirchk: created.
Process status files           /home/oracle/ogg12.3/dirpcs: created.
SQL script files               /home/oracle/ogg12.3/dirsql: created.
Database definitions files     /home/oracle/ogg12.3/dirdef: created.
Extract data files             /home/oracle/ogg12.3/dirdat: created.
Temporary files                /home/oracle/ogg12.3/dirtmp: created.
Credential store files         /home/oracle/ogg12.3/dircrd: created.
Masterkey wallet files         /home/oracle/ogg12.3/dirwlt: created.
Dump files                     /home/oracle/ogg12.3/dirdmp: created.
```

Oracle OGG

## 2. OGG - TiDB

(1)

```
$ unzip V978711-01.zip
Archive:  V978711-01.zip
  inflating: ggs_Linux_x64_MySQL_64bit.tar
  inflating: OGG-12.3.0.1-README.txt
  inflating: OGG_WinUnix_Rel_Notes_12.3.0.1.5.pdf
```

(2) ggs_Linux_x64_MySQL_64bit.tar .

```
$tar xvf ./ggs_Linux_x64_MySQL_64bit.tar -C /home/tidb/ogg12.3
```

(3) ggsci

```
$ ./ggsci
Oracle GoldenGate Command Interpreter for MySQL
Version 12.3.0.1.5 OGGCORE_12.3.0.1.0_PLATFORMS_180501.2124
Linux, x64, 64bit (optimized), MySQL Enterprise on May  2 2018 10:58:16
Operating system character set identified as UTF-8.
Copyright (C) 1995, 2018, Oracle and/or its affiliates. All rights reserved.


GGSCI ( hostname ) 1> create subdirs
Creating subdirectories under current directory /home/tidb/ogg12.3
Parameter file                 /home/tidb/ogg12.3/dirprm: created.
Report file                    /home/tidb/ogg12.3/dirrpt: created.
Checkpoint file                /home/tidb/ogg12.3/dirchk: created.
Process status files           /home/tidb/ogg12.3/dirpcs: created.
SQL script files               /home/tidb/ogg12.3/dirsql: created.
Database definitions files     /home/tidb/ogg12.3/dirdef: created.
Extract data files             /home/tidb/ogg12.3/dirdat: created.
Temporary files                /home/tidb/ogg12.3/dirtmp: created.
Credential store files         /home/tidb/ogg12.3/dircrd: created.
Masterkey wallet files         /home/tidb/ogg12.3/dirwlt: created.
Dump files                     /home/tidb/ogg12.3/dirdmp: created.
```

OGG TiDB (OGG For MySQL )

## 3. TiDB

(1) lower-case-table-names 1

```
$grep lower-case-table-names tidb.toml
lower-case-table-names  = 1
```

(2)

```
MySQL [(none)]> show variables like '%lower%';
+------------------------+-------+
| Variable_name          | Value |
+------------------------+-------+
| lower_case_table_names | 1     |
| lower_case_file_system | 1     |
+------------------------+-------+
MySQL [(none)]> show variables like '%place%' ;
+-------------------------------+-------+
| Variable_name                 | Value |
+-------------------------------+-------+
| tidb_constraint_check_in_place | 0     |
+-------------------------------+-------+
```

(3)

```
MySQL [scott]> create user 'tidb' identified by 'tidb';
Query OK, 1 row affected (0.01 sec)
MySQL [scott]> GRANT ALL PRIVILEGES ON scott.* to oggadmin ;
Query OK, 0 rows affected (0.01 sec)
MySQL [scott]> show create user tidb;
+-------------------------------------------------------------------------------------------------------------------------------------
-------------------------------------------------+
| CREATE USER for tidb@%
                                                 |
+-------------------------------------------------------------------------------------------------------------------------------------
-------------------------------------------------+
| CREATE USER 'tidb'@'%' IDENTIFIED WITH 'mysql_native_password' AS '*465D123EE55795DBDBDAE36AFD3DCD9C429B718A' REQUI
RE NONE PASSWORD EXPIRE DEFAULT ACCOUNT UNLOCK |
+-------------------------------------------------------------------------------------------------------------------------------------
-------------------------------------------------+
1 row in set (0.00 sec)
```

(4)

## 4. Oracle

4.1

```
SQL> archive log list;
```

(1)

```
SQL> shutdown immediate;
```

(2) mount

```
SQL> startup mount;
```

(3)

```
SQL> alter database archivelog;
```

(4)

```
SQL> alter database open;
```

(5)

```
SQL> archive log list;
```

4.2

(1)

```
select log_mode,supplemental_log_data_min,force_logging from v$database;
```

(2) force logging

> nolog

```
SQL> ALTER DATABASE FORCE LOGGING;
```

(3)

```
SQL> ALTER DATABASE ADD SUPPLEMENTAL LOG DATA;
SQL> ALTER SYSTEM SWITCH LOGFILE;
```

(4) OGG

```
SQL> alter system set enable_goldengate_replication=true;
```

4.3 ogg

goldengate

```
SQL> create tablespace goldengate datafile '/opt/oracle/data/goldengate001.dbf' size 4G;
SQL> create user goldengate identified by goldengate default tablespace goldengate;
SQL> grant dba to goldengate;
```

## 5. OGG

(1) ggsic

```
./ggsci
create subdirs
add credentialstore
alter credentialstore add user goldengate,password goldengate
```

(2) ogg goldengate

```
dblogin useridalias goldengate
```

## 6. schema

schema schema

(1) 11.2.0.2 Oracle Patch 13794550

> oracle schema
>
> ERROR OGG-06522 Cannot verify existence of table function that is required to ADD schema level supplemental logging, failed.

(2) GGSCI

> 1) dblogin userid goldengate, password goldengate
>
> 2) dblogin useridalias goldengate

(3) schema

> ADD SCHEMATRANDATA schema ALLCOLS

### 7.

> schema

(1) GGSCI

```
dblogin userid goldengate, password goldengate
```

(2) schema

```
ADD TRANDATA schema.tablename NOKEY
```

## 5.2.3 OGG

### 1. OGG

- INITIAL LOAD
- CHANGE SYNCHRONIZATION trail oracle oracle redo log archive log trail

| | |
|---|---|
| /opt/oracle/11.2.0 | ORACLE_HOME |
| ora | Oracle sid |
| ext_ora | |
| tdpm_ora | |
| rep_ora | |
| ./dirdat/sk | |
| /Data/tidb/ogg/dirdat/sk | Replicat |

## 2.

> ADG

Extract pump

Extract redo archive log Data pump

## 2.1 MGR

Manager OGG ExtractPumpReplicat ExtractPumpReplicat Manager

(1)

```
GGSCI (b-db-ps-055) 5> view param mgr

port 9001
DYNAMICPORTLIST 9001-9020
--AUTORESTART ER *,RETRIES 5,WAITMINUTES   7
PURGEOLDEXTRACTS   ./dirdat/*,usecheckpoints, minkeepdays 2
LAGREPORTHOURS 1
LAGINFOMINUTES 30
LAGCRITICALMINUTES 45
```

| | |
|---|---|
| port | |
| DYNAMICPORTLIST | OGG OGG |
| AUTORESTART | |
| PURGEOLDEXTRACTS | trail 2 trail |
| LAGREPORTHOURS | lag 1 |
| LAGINFOMINUTES | |

(2) mgr

```
./ggsci
start mgr
```

## 2.2 Extract

Extract OGG Extract

(1)

```
GGSCI (b-db-ps-055) 2> edit param   ext_ora

EXTRACT ext_ora
SETENV   (ORACLE_HOME="/opt/oracle/11.2.0")
setenv   (NLS_LANG="AMERICAN_AMERICA.AL32UTF8")
setenv (ORACLE_SID="ora")
useridalias goldengate
GETTRUNCATES
REPORTCOUNT EVERY 1 MINUTES, RATE
DISCARDFILE   ./dirrpt/ext_ora.dsc,APPEND,MEGABYTES 1000
WARNLONGTRANS 2h,CHECKINTERVAL 10m
EXTTRAIL ./dirdat/sk
TRANLOGOPTIONS EXCLUDEUSER goldengate
TRANLOGOPTIONS MINEFROMACTIVEDG
DBOPTIONS ALLOWUNUSEDCOLUMN
DYNAMICRESOLUTION
FETCHOPTIONS FETCHPKUPDATECOLS,INCONSISTENTROW ALLOW
ddl include mapped objname hr.*
getupdatebefores
nocompressdeletes
nocompressupdates
table hr.table_name;
```

| | | |:----|:----| | SETENV | | | useridalias | | | GETTRUNCATES | truncate | | REPORTCOUNT | | | WARNLONGTRANS | OGG | | EXTTRAIL | trail | | TRANLOGOPTIONS EXCLUDEUSER | | | TRANLOGOPTIONS MINEFROMACTIVEDG | ADG | | DBOPTIONS ALLOWUNUSEDCOLUMN | | | DYNAMICRESOLUTION | OGG OGG OGG OGG ID FETCHPKUPDATECOLS,INCONSISTENTROW ALLOW | row id () ALLOW |

(2)

```
./ggsci
add extract ext_ora,TRANLOG, begin now
add ExtTrail ./dirdat/sk, Extract ext_ora,   Megabytes 50
```

## 2.3 Pump

Pump Extract Pump Extract Trail Trail

```
GGSCI (b-db-ps-055) 4> edit param   tdpm_ora

EXTRACT tdpm_ora
RMTHOST 31.***.***.***, MGRPORT 9001,   compress
PASSTHRU
RMTTRAIL /Data/tidb/ogg/dirdat/sk
DYNAMICRESOLUTION
--table
table hr.table_name;
```

| | | |:----|:----| | RMTHOST | IP MGR | | PASSTHRU | OGG |

(1) pump

```
./ggsci
add extract tdpm_ora, exttrailsource   ./dirdat/sk
add rmttrail /Data/tidb/ogg/dirdat/sk,   extract tdpm_ora, megabytes 100
```

## 3.

## 3.1 MGR

(1)

```
GGSCI (w-db-ps-082) 2> edit param mgr

port 9001
DYNAMICPORTLIST 9001-9120
ACCESSRULE, PROG *, IPADDR 31.*.*.*,   ALLOW
--AUTORESTART ER *,RETRIES 5,WAITMINUTES   7
PURGEOLDEXTRACTS   ./dirdat/*,usecheckpoints, minkeepdays 10
LAGREPORTHOURS 1
LAGINFOMINUTES 30
LAGCRITICALMINUTES 45
```

(2) mgr

```
./ggsci
start mgr
```

## 3.2 Replicat

Replicat Extract DDL

(1) checkpoint table

```
dblogin sourcedb tidb@31.***.***.***:4000   userid username password user_password
add checkpointtable tidb.checkpoint_table
```

(2) replicat

```
GGSCI (w-db-ps-082) 4> edit param   rep_ora

replicat rep_ora
targetdb tidb@31.***.***.***:4000 userid   username password user_password
SQLEXEC "set tidb_constraint_check_in_place=1"
handlecollisions
MAXTRANSOPS 10000
discardfile /Data/tidb/ogg/dirrpt/repora.dsc,purge
map hr.table_name,target tidb.table_name,keycols(ID);
```

| | | | |:----|:----| | SQLEXEC | tidb_constraint_check_in_place 0 INSERT OGG 1 | | handlecollisions | replicat replicat insertrepliact () |

(3) replicat

```
add replicat rep_ora,exttrail /Data/tidb/ogg/dirdat/sk,checkpointtable tidb.checkpoint_table
```

# 4.

## 4.1

(1)

```
GGSCI (w-db-ps-082) 4>edit param   init_ora

extract init_ora
setenv (NLS_LANG=AMERICAN_AMERICA.AL32UTF8)
setenv (ORACLE_SID="ora")
useridalias goldengate
rmthost 31.***.***.***,mgrport 9001
rmttask replicat,group rnit_ora
table hr.table_name;
```

| | |
|---|---|
| rmttask replicat,group | replicat |

(2)

```
./ggsci
add extract init_ora,sourceistable
```

## 4.2

(1)

```
GGSCI (w-db-ps-082) 4>edit param   rnit_ora

replicat rnit_ora
SETENV (NLS_LANG =   AMERICAN_AMERICA.AL32UTF8)
targetdb tidb@31.***.***.***:4000 userid   username password user_password
discardfile /Data/tidb/ogg/dirrpt/rnit_ora.dsc,purge
map hr.table_name, target   tidb.hr.table_name;
```

(2)

```
./ggsci
add replicat rnit_ora,specialrun
```

# 5.

1. MGR
2. “A ” trail
3. “C ” “A ”
4. “D ”
5. “E ” replicat repliact “C ” “A ” “handlecollisions”

## 5.2.4 OGG

OGG

```
SQL> CREATE TABLE hr.table_name
  2  (
  3  ID          NUMBER              NOT NULL,
  4  CREATED_AT  DATE                DEFAULT sysdate NOT NULL,
  5  CREATED_BY  VARCHAR2(128 BYTE)  DEFAULT 'SYS'   NOT NULL,
  6  UPDATED_AT  DATE                DEFAULT sysdate NOT NULL,
  7  UPDATED_BY  VARCHAR2(128 BYTE)  DEFAULT 'SYS'   NOT NULL
  8  )
  9  ;
SQL> ALTER TABLE hr.table_name ADD   CONSTRAINT PK_table_name;
```

### 1.

1.1

(1)

```
SQL> insert into hr.table_name(id)   values(1);

1 row created.

SQL> commit;

Commit complete.
```

(3) OGG

```
Logdump 12 >ghdr on
Logdump 13 >detail on
Logdump 14 >detail data

Logdump 18 >n
___________________________________________________________________
Hdr-Ind      :     E  (x45)       Partition  :     .    (x0c)
UndoFlag     :     .  (x00)       BeforeAfter:     A    (x41)
RecLength    :    81  (x0051)     IO Time    : 2020/03/06   17:26:30.000.000
IOType       :     5    (x05)     OrigNode   :     255  (xff)
TransInd     :     .  (x03)       FormatType :     R    (x52)
SyskeyLen    :     0  (x00)       Incomplete :     .  (x00)
AuditRBA     :       3539         AuditPos   : 31052304
Continued    :     N    (x00)     RecCount   :     1  (x01)

2020/03/06 17:26:30.000.000 Insert               Len    81 RBA 2014
Name: HR.TABLE_NAME  (TDR Index: 1)
After    Image:                                          Partition 12   G  s
 0000 0005 0000 0001 3100 0100 1500 0032 3032   302d | ........1......2020-
 3033 2d30 363a 3137 3a32 363a 3238 0002 0007   0000 | 03-06:17:26:28......
 0003 5359 5300 0300 1500 0032 3032 302d 3033   2d30 | ..SYS......2020-03-0
 363a 3137 3a32 363a 3238 0004 0007 0000 0003   5359 | 6:17:26:28........SY
 53                                                  | S
Column     0 (x0000), Len     5   (x0005)
 0000 0001 31                                        |   ....1
Column     1 (x0001), Len    21   (x0015)
 0000 3230 3230 2d30 332d 3036 3a31 373a 3236   3a32 | ..2020-03-06:17:26:2
 38                                                  | 8
Column     2 (x0002), Len     7   (x0007)
 0000 0003 5359 53                                   |   ....SYS
Column     3 (x0003), Len    21   (x0015)
 0000 3230 3230 2d30 332d 3036 3a31 373a 3236   3a32 | ..2020-03-06:17:26:2
 38                                                  | 8
Column     4 (x0004), Len     7   (x0007)
 0000 0003 5359 53                                   |   ....SYS
```

> **IOType** 3 delete5 insert10 updatefull >record15 updatecompressed record
>
> **Continued** Y N lobclob > varchar Y N
>
> **BeforeAfter** update before image( B ) >after image A insert after images delete > before images
>
> **FormatType** F >RF fetched from databaseR readable in transaction log

trail

1.2

(1) update

```
SQL> update hr.table_name set   updated_by='aaaaaaa';

1 row updated.

SQL> commit;
```

(2) OGG

```
Logdump 19 >n
___________________________________________________________________
Hdr-Ind      :     E  (x45)       Partition  :     .    (x0c)
UndoFlag     :     .  (x00)       BeforeAfter:     B    (x42)
RecLength    :    19  (x0013)     IO Time    : 2020/03/06   17:26:36.000.000
IOType       :      15  (x0f)     OrigNode   :     255  (xff)
TransInd     :     .  (x00)       FormatType :     R  (x52)
SyskeyLen    :     0  (x00)       Incomplete :     .  (x00)
AuditRBA     :       3539         AuditPos   : 31055376
Continued    :     N  (x00)       RecCount   :     1    (x01)

2020/03/06 17:26:36.000.000   FieldComp            Len    19 RBA 2207
Name: HR.TABLE_NAME  (TDR Index: 1)
Before Image:                                             Partition   12   G    b
 0000 0004 ffff 0000 0004 0007 0000 0003 5359   53 | ................SYS
Column       0 (x0000), Len     4   (x0004)
 ffff 0000                                         |   ....
Column       4 (x0004), Len     7   (x0007)
 0000 0003 5359 53                                 |   ....SYS
Logdump 20 >n
___________________________________________________________________
Hdr-Ind      :     E  (x45)       Partition  :     .    (x0c)
UndoFlag     :     .  (x00)       BeforeAfter:     A  (x41)
RecLength    :    23  (x0017)     IO Time    : 2020/03/06   17:26:36.000.000
IOType       :      15  (x0f)     OrigNode   :     255  (xff)
TransInd     :     .  (x02)       FormatType :     R  (x52)
SyskeyLen    :     0  (x00)       Incomplete :     .  (x00)
AuditRBA     :       3539         AuditPos   : 31055376
Continued    :     N  (x00)       RecCount   :     1    (x01)

2020/03/06 17:26:36.000.000   FieldComp            Len    23 RBA 2334
Name: HR.TABLE_NAME  (TDR Index: 1)
After  Image:                                             Partition   12   G    e
 0000 0004 ffff 0000 0004 000b 0000 0007 6161 6161 | ................aaaa
 6161 61                                           |   aaa
Column       0 (x0000), Len     4   (x0004)
 ffff 0000                                         |   ....
Column       4 (x0004), Len    11   (x000b)
 0000 0007 6161 6161 6161 61                       | ....aaaaaaa
```

trail

replicat “handlecollisions” insert

## 2.

(1) OGG

```
GGSCI (l-db-ps-005) 3> dblogin userid goldengate,   password goldengate
Successfully logged into database.
```

(2)

```
GGSCI (l-db-ps-005 as goldengate@ogg)   4> add trandata   hr.table_name,nokey

2020-03-06 21:13:51  WARNING OGG-01387  Table HR.TABLE_NAME has no valid key   columns, added unconditional supplemen
tal log group for all table columns.

Logging of supplemental redo data enabled   for table HR.TABLE_NAME.
TRANDATA for scheduling columns has been   added on table 'HR.TABLE_NAME'.
TRANDATA for instantiation CSN has been   added on table 'HR.TABLE_NAME'.
```

(3)

```
GGSCI (l-db-ps-005 as goldengate@ogg)   7> info trandata   hr.table_name

Logging   of supplemental redo log data is enabled for table   HR.TABLE_NAME.

Columns supplementally logged for table   HR.TABLE_NAME: ALL.

Prepared CSN for table HR.TABLE_NAME:   57187843
```

ogg

(4)

```
SQL> update hr.table_name set   updated_by='bbb';

1 row updated.

SQL> commit;

Commit complete.
```

(5) ogg

```
Logdump 23 >n
___________________________________________________________________
Hdr-Ind      :     E  (x45)       Partition  :     .    (x0c)
UndoFlag     :     .  (x00)       BeforeAfter:     B  (x42)
RecLength    :    85  (x0055)     IO Time    : 2020/03/06   21:22:21.000.000
IOType       :    15  (x0f)       OrigNode   :   255    (xff)
TransInd     :     .  (x00)       FormatType :     R  (x52)
SyskeyLen    :     0  (x00)       Incomplete :     .  (x00)
AuditRBA     :       3539         AuditPos   : 45237264
Continued    :     N  (x00)       RecCount   :     1    (x01)

2020/03/06 21:22:21.000.000   FieldComp            Len    85 RBA 2437
Name: HR.TABLE_NAME  (TDR Index: 1)
Before Image:                                              Partition 12   G  b
 0000 0005 0000 0001 3100 0100 1500 0032 3032   302d | ........1......2020-
 3033 2d30 363a 3137 3a32 363a 3238 0002 0007   0000 | 03-06:17:26:28......
 0003 5359 5300 0300 1500 0032 3032 302d 3033   2d30 | ..SYS......2020-03-0
 363a 3137 3a32 363a 3238 0004 000b 0000 0007   6161 | 6:17:26:28........aa
 6161 6161 61                                        |   aaaaa
Column     0 (x0000),   Len     5 (x0005)
 0000 0001 31                                        | ....1
Column     1 (x0001),   Len    21 (x0015)
 0000 3230 3230 2d30 332d 3036 3a31 373a 3236   3a32 | ..2020-03-06:17:26:2
 38                                                  | 8
Column     2 (x0002),   Len     7 (x0007)
 0000 0003 5359 53                                   |   ....SYS
Column     3 (x0003),   Len    21 (x0015)
 0000 3230 3230 2d30 332d 3036 3a31 373a 3236   3a32 | ..2020-03-06:17:26:2
 38                                                  | 8
Column     4 (x0004),   Len    11 (x000b)
 0000 0007 6161 6161 6161 61                         | ....aaaaaaa
Logdump 24 >n
___________________________________________________________________
Hdr-Ind      :     E  (x45)       Partition  :     .    (x0c)
UndoFlag     :     .  (x00)       BeforeAfter:     A  (x41)
RecLength    :    81  (x0051)     IO Time    : 2020/03/06   21:22:21.000.000
IOType       :    15  (x0f)       OrigNode   :   255    (xff)
TransInd     :       .  (x02)     FormatType :     R    (x52)
SyskeyLen    :     0  (x00)       Incomplete :     .  (x00)
AuditRBA     :       3539         AuditPos   : 45237264
Continued    :     N  (x00)       RecCount   :     1    (x01)

2020/03/06 21:22:21.000.000   FieldComp            Len    81 RBA 2630
Name: HR.TABLE_NAME  (TDR Index: 1)
After  Image:                                          Partition 12   G  e
 0000 0005 0000 0001 3100 0100 1500 0032 3032   302d | ........1......2020-
 3033 2d30 363a 3137 3a32 363a 3238 0002 0007   0000 | 03-06:17:26:28......
 0003 5359 5300 0300 1500 0032 3032 302d 3033   2d30 | ..SYS......2020-03-0
 363a 3137 3a32 363a 3238 0004 0007 0000 0003   6262 | 6:17:26:28........bb
 62                                                  | b
Column     0 (x0000),   Len     5 (x0005)
 0000 0001 31                                        |   ....1
Column     1 (x0001),   Len    21 (x0015)
 0000 3230 3230 2d30 332d 3036 3a31 373a 3236   3a32 | ..2020-03-06:17:26:2
 38                                                  | 8
Column     2 (x0002),   Len     7 (x0007)
 0000 0003 5359 53                                   |   ....SYS
Column     3 (x0003),   Len    21 (x0015)
 0000 3230 3230 2d30 332d 3036 3a31 373a 3236   3a32 | ..2020-03-06:17:26:2
 38                                                  | 8
Column     4 (x0004),   Len     7 (x0007)
 0000 0003 6262 62                                   |   ....bbb
```

# 5.2.5

## 1.

```
MAXTRANSOPS 100
```

> TiDB OGG 100

```
SQLEXEC "set tidb_constraint_check_in_place = 1 "
```

> OGG TiDB set tidb_constraint_check_in_place = 1 abend

## 2.

GBK report

```
2019-07-28 21:01:10  INFO    OGG-02243  Opened trail file /home/tidb/ogg12.3/dirdat/p1000000002 at 2019-07-28 21:01:1
0.232896.

2019-07-28 21:01:10  INFO    OGG-03506  The source database character set, as determined from the trail file, is zhs1
6gbk.

2019-07-28 21:05:57  INFO    OGG-06505  MAP resolved (entry scott.account): MAP "SCOTT"."ACCOUNT", TARGET "scott"."ac
count".

2019-07-28 21:05:57  INFO    OGG-02756  The definition for table SCOTT.ACCOUNT is obtained from the trail file.

2019-07-28 21:05:57  INFO    OGG-06511  Using following columns in default map by name: account_number, account_balan
ce, account_trans_ts, account_trans_type.

2019-07-28 21:05:57  INFO    OGG-06510  Using the following key columns for target table scott.account: account_numbe
r.

2019-07-28 21:05:57  INFO    OGG-03010  Performing implicit conversion of column data from character set zhs16gbk to
UTF-8.
```

## 3.

OGG OGG TiDB

## 4.

TiDB OGG replicat map

## 5. replicat

OGG RANGE replicat

filter(@RANGE ( , , )) ;

```
EXTRACT initext1

userid oggadmin ,password oggadmin

RMTHOST target-ogg, MGRPORT 7909

RMTTASK replicat, GROUP initrep1

TABLE scott.account, filter(@RANGE(1,2,account)) ;

EXTRACT initext2

userid oggadmin ,password oggadmin

RMTHOST target-ogg, MGRPORT 7909

RMTTASK replicat, GROUP initrep2

TABLE scott.account, filter(@RANGE(2,2,account)) ;
```

# 5.2.6

## 1. OGG-01201 Error reported by MGR : Access denied

This is due to a new security restriction in GoldenGate 12.2. In order to allow access from a remote system the ACCESSRULE parameter must be put into the manager parameter file on the target in order to allow access from the source.

mgr ip

```
(1)  mgr

edit params mgr

(2)

ACCESSRULE, PROG *, IPADDR *, ALLOW
```

## 2. replicat invalid time format

Oracle date TIDB timestmap Oracle TIDB timestamp TIDB 1970-01-01 00:00:01.000000 2038-01-19 03:14:07.999999Oracle 2038

TIDB timestamp datetime OGG replicat abended discard REPERROR (default,discard) OGG

## 3. extract ORA-01801: date format is too long for internal buffer

Oracle OCI Oracle Oracle select * Oracle

to_chardate,’yyyy-mm-dd hh24:mi:ss’Oracle ‘0000-00-00 00:00:00’

```
1

create table t_bak as select * from t where to_char(date1,'yyyy-mm-dd hh24:mi:ss')= '0000-00-00 00:00:00';

2:

delete from t where id in (select id from t_bak);

commit;
```

```
$vi ./fbo_ggs_Linux_x64_shiphome/Disk1/response/oggcore.rsp
######################################################################
## Copyright(c) Oracle Corporation 2017. All rights reserved.     ##
##                                                                ##
## Specify values for the variables listed below to customize     ##
## your installation.                                             ##
##                                                                ##
## Each variable is associated with a comment. The comment        ##
## can help to populate the variables with the appropriate        ##
## values.                                                        ##
##                                                                ##
## IMPORTANT NOTE: This file should be secured to have read       ##
## permission only by the oracle user or an administrator who     ##
## own this installation to protect any sensitive input values.   ##
##                                                                ##
######################################################################
#------------------------------------------------------------------------------
# Do not change the following system generated value.
#------------------------------------------------------------------------------
oracle.install.responseFileVersion=/oracle/install/rspfmt_ogginstall_response_schema_v12_1_2

###############################################################################
##                                                                           ##
## Oracle GoldenGate installation option and details                         ##
##                                                                           ##
###############################################################################
#------------------------------------------------------------------------------
# Specify the installation option.
# Specify ORA12c for installing Oracle GoldenGate for Oracle Database 12c and
#         ORA11g for installing Oracle GoldenGate for Oracle Database 11g
#------------------------------------------------------------------------------
INSTALL_OPTION=ORA11g
## Oracle  11.2.0.4 ORA11G 12c  ORA12c
#------------------------------------------------------------------------------
# Specify a location to install Oracle GoldenGate
#------------------------------------------------------------------------------
SOFTWARE_LOCATION=/home/oracle/ogg12.3
##
#------------------------------------------------------------------------------
# Specify true to start the manager after installation.
#------------------------------------------------------------------------------
START_MANAGER=false
## mgr  false
#------------------------------------------------------------------------------
# Specify a free port within the valid range for the manager process.
# Required only if START_MANAGER is true.
#------------------------------------------------------------------------------
MANAGER_PORT=
#------------------------------------------------------------------------------
# Specify the location of the Oracle Database.
# Required only if START_MANAGER is true.
#------------------------------------------------------------------------------
DATABASE_LOCATION=

###############################################################################
##                                                                           ##
## Specify details to Create inventory for Oracle installs                   ##
## Required only for the first Oracle product install on a system.           ##
##                                                                           ##
###############################################################################
```

```
#-------------------------------------------------------------------------------
# Specify the location which holds the install inventory files.
# This is an optional parameter if installing on
# Windows based Operating System.
#-------------------------------------------------------------------------------
INVENTORY_LOCATION=
#-------------------------------------------------------------------------------
# Unix group to be set for the inventory directory.
# This parameter is not applicable if installing on
# Windows based Operating System.
#-------------------------------------------------------------------------------
UNIX_GROUP_NAME=
```

(2)

fbo_ggs_Linux_x64_shiphome/Disk1/runInstaller

```
$./fbo_ggs_Linux_x64_shiphome/Disk1/runInstaller -silent -responseFile /home/oracle/oggsoft/fbo_ggs_Linux_x64_shiphom
e/Disk1/response/oggcore.rsp
# response
```

successful

```
The installation of Oracle GoldenGate Core was successful
```

OGG

```
$ ls -l
total 225044
-rwxr-xr-x  1 oracle oinstall      426 Oct 15  2010 bcpfmt.tpl
-rwxr-xr-x  1 oracle oinstall     1725 Oct 15  2010 bcrypt.txt
-rwxrwxr-x  1 oracle oinstall  1612776 Apr 15  2018 cachefiledump
drwxr-xr-x  4 oracle oinstall     4096 Jul 28 14:45 cfgtoollogs
-rwxrwxr-x  1 oracle oinstall  3563576 Apr 15  2018 checkprm
-rw-rw-r--  1 oracle oinstall     1021 Apr 15  2018 chkpt_ora_create.sql
-rwxrwxr-x  1 oracle oinstall  3379568 Apr 15  2018 convchk
-rwxrwxr-x  1 oracle oinstall  4716080 Apr 15  2018 convprm
drwxr-xr-x  2 oracle oinstall     4096 Jul 28 14:45 crypto
-rwxr-xr-x  1 oracle oinstall      159 Oct 15  2010 db2cntl.tpl
-rwxrwxr-x  1 oracle oinstall     9696 Apr 15  2018 db_upgrade
-rw-rw-r--  1 oracle oinstall      455 Apr 15  2018 ddl_cleartrace.sql
-rw-rw-r--  1 oracle oinstall     8414 Apr 15  2018 ddl_create.sql
-rw-rw-r--  1 oracle oinstall     3176 Apr 15  2018 ddl_ddl2file.sql
-rw-rw-r--  1 oracle oinstall       90 Apr 15  2018 ddl_disable.sql
-rw-rw-r--  1 oracle oinstall       88 Apr 15  2018 ddl_enable.sql
-rw-rw-r--  1 oracle oinstall     2036 Apr 15  2018 ddl_filter.sql
-rw-rw-r--  1 oracle oinstall    12220 Apr 15  2018 ddl_ora10.sql
-rw-rw-r--  1 oracle oinstall     1725 Apr 15  2018 ddl_ora10upCommon.sql
-rw-rw-r--  1 oracle oinstall    13539 Apr 15  2018 ddl_ora11.sql
-rw-rw-r--  1 oracle oinstall    12564 Apr 15  2018 ddl_ora9.sql
-rw-rw-r--  1 oracle oinstall      216 Apr 15  2018 ddl_pin.sql
-rw-rw-r--  1 oracle oinstall     3184 Apr 15  2018 ddl_remove.sql
-rw-rw-r--  1 oracle oinstall        1 Apr 15  2018 ddl_session1.sql
-rw-rw-r--  1 oracle oinstall      629 Apr 15  2018 ddl_session.sql
-rw-rw-r--  1 oracle oinstall   287877 Apr 15  2018 ddl_setup.sql
-rw-rw-r--  1 oracle oinstall     8401 Apr 15  2018 ddl_status.sql
-rw-rw-r--  1 oracle oinstall     2122 Apr 15  2018 ddl_staymetadata_off.sql
-rw-rw-r--  1 oracle oinstall     2118 Apr 15  2018 ddl_staymetadata_on.sql
-rw-rw-r--  1 oracle oinstall     2186 Apr 15  2018 ddl_tracelevel.sql
-rw-rw-r--  1 oracle oinstall     2133 Apr 15  2018 ddl_trace_off.sql
-rw-rw-r--  1 oracle oinstall     2383 Apr 15  2018 ddl_trace_on.sql
-rwxrwxr-x  1 oracle oinstall  5037440 Apr 15  2018 defgen
drwxr-xr-x  2 oracle oinstall     4096 Jul 28 14:45 deinstall
-rw-rw-r--  1 oracle oinstall      882 Apr 15  2018 demo_more_ora_create.sql
-rw-rw-r--  1 oracle oinstall      649 Apr 15  2018 demo_more_ora_insert.sql
-rw-rw-r--  1 oracle oinstall      583 Apr 15  2018 demo_ora_create.sql
-rw-rw-r--  1 oracle oinstall      504 Apr 15  2018 demo_ora_insert.sql
```

```
-rw-rw-r--  1 oracle oinstall     3597 Apr 15  2018 demo_ora_lob_create.sql
-rw-rw-r--  1 oracle oinstall     1943 Apr 15  2018 demo_ora_misc.sql
-rw-rw-r--  1 oracle oinstall     1056 Apr 15  2018 demo_ora_pk_befores_create.sql
-rw-rw-r--  1 oracle oinstall     1013 Apr 15  2018 demo_ora_pk_befores_insert.sql
-rw-rw-r--  1 oracle oinstall     2305 Apr 15  2018 demo_ora_pk_befores_updates.sql
drwxr-xr-x  3 oracle oinstall     4096 Jul 28 14:45 diagnostics
drwxr-xr-x  3 oracle oinstall     4096 Jul 28 14:45 diretc
drwxr-xr-x  2 oracle oinstall     4096 Jul 28 14:45 dirout
drwxr-xr-x  4 oracle oinstall     4096 Jul 28 14:45 dirsca
-rwxrwxr-x  1 oracle oinstall  4272400 Apr 15  2018 emsclnt
-rwxrwx---  1 oracle oinstall 12545040 Apr 15  2018 extract
-rwxr-xr-x  1 oracle oinstall     1968 Oct 15  2010 freeBSD.txt
-rwxrwxr-x  1 oracle oinstall  4280528 Apr 15  2018 ggcmd
-rwxr-xr-x  1 oracle oinstall  2303056 Apr 15  2018 ggMessage.dat
-rwxr-xr-x  1 oracle oinstall 49675440 Apr 15  2018 ggparam.dat
-rwxrwx---  1 oracle oinstall  9340192 Apr 15  2018 ggsci
drwxr-xr-x  2 oracle oinstall     4096 Jul 28 14:45 healthcheck
-rwxr-xr-x  1 oracle oinstall   299451 Nov 16  2017 help.txt
drwxr-xr-x  3 oracle oinstall     4096 Jul 28 14:45 install
drwxr-x--- 12 oracle oinstall     4096 Jul 28 14:45 inventory
drwxr-xr-x  7 oracle oinstall     4096 Jul 28 14:45 jdk
-rwxrwxr-x  1 oracle oinstall   144496 Apr 15  2018 keygen
-rw-rw-r--  1 oracle oinstall       56 Apr 15  2018 label.sql
-rwxrwx---  1 oracle oinstall   102840 Apr 15  2018 libantlr3c.so
-rwxrwxr-x  1 oracle oinstall    12312 Apr 15  2018 libboost_system-mt.so.1.58.0
-rwxrwx---  1 oracle oinstall  2190856 Apr 15  2018 libdb-6.1.so
-rwxrwx---  1 oracle oinstall  2198136 Apr 15  2018 libgglog.so
-rwxrwx---  1 oracle oinstall 10524064 Apr 15  2018 libggnnzitp.so
-rwxrwx---  1 oracle oinstall 21993240 Apr 15  2018 libggparam.so
-rwxrwx---  1 oracle oinstall   210264 Apr 15  2018 libggperf.so
-rwxrwx---  1 oracle oinstall   779352 Apr 15  2018 libggrepo.so
-rwxrwx---  1 oracle oinstall  1108760 Apr 15  2018 libggssl.so
-rwxrwx---  1 oracle oinstall   125624 Apr 15  2018 libggutil.so
-rwxrwxr-x  1 oracle oinstall 29764432 Apr 15  2018 libicudata.so.56
-rwxrwxr-x  1 oracle oinstall  2909360 Apr 15  2018 libicui18n.so.56
-rwxrwxr-x  1 oracle oinstall  1995808 Apr 15  2018 libicuuc.so.56
-rwxrwx---  1 oracle oinstall    86960 Apr 15  2018 liblmdb.so
-rwxrwxr-x  1 oracle oinstall   175136 Apr 15  2018 libPocoCrypto.so.48
-rwxrwxr-x  1 oracle oinstall  3079760 Apr 15  2018 libPocoFoundation.so.48
-rwxrwxr-x  1 oracle oinstall   373232 Apr 15  2018 libPocoJSON.so.48
-rwxrwxr-x  1 oracle oinstall  1326504 Apr 15  2018 libPocoNet.so.48
-rwxrwxr-x  1 oracle oinstall   350064 Apr 15  2018 libPocoNetSSL.so.48
-rwxrwxr-x  1 oracle oinstall   520864 Apr 15  2018 libPocoUtil.so.48
-rwxrwxr-x  1 oracle oinstall   680288 Apr 15  2018 libPocoXML.so.48
-rwxrwx---  1 oracle oinstall  1115360 Apr 15  2018 libudt.so
-rwxrwx---  1 oracle oinstall  4782344 Apr 15  2018 libxerces-c-3.1.so
-rwxrwxr-x  1 oracle oinstall  5025840 Apr 15  2018 logdump
-rw-rw-r--  1 oracle oinstall     1553 Apr 15  2018 marker_remove.sql
-rw-rw-r--  1 oracle oinstall     3309 Apr 15  2018 marker_setup.sql
-rw-rw-r--  1 oracle oinstall      675 Apr 15  2018 marker_status.sql
-rwxrwxr-x  1 oracle oinstall  6570480 Apr 15  2018 mgr
-rwxr-xr-x  1 oracle oinstall    41643 Jun 30  2017 notices.txt
-rwxrwxr-x  1 oracle oinstall  1661024 Apr 15  2018 oggerr
drwxr-xr-x 12 oracle oinstall     4096 Jul 28 14:45 OPatch
-rw-r-----  1 oracle oinstall       59 May 30 13:35 oraInst.loc
drwxr-xr-x  8 oracle oinstall     4096 Jul 28 14:45 oui
-rw-rw-r--  1 oracle oinstall     3146 Apr 15  2018 params.sql
-rwxrwxr-x  1 oracle oinstall 11524576 Apr 15  2018 pmsrvr
-rwxr-xr-x  1 oracle oinstall     1272 Dec 28  2010 prvtclkm.plb
-rwxr-xr-x  1 oracle oinstall     9487 May 27  2015 prvtlmpg.plb
-rw-rw-r--  1 oracle oinstall     2724 Apr 15  2018 prvtlmpg_uninstall.sql
-rw-rw-r--  1 oracle oinstall     1532 Apr 15  2018 remove_seq.sql
-rwxrwx---  1 oracle oinstall 10873240 Apr 15  2018 replicat
-rwxrwxr-x  1 oracle oinstall  1656864 Apr 15  2018 retrace
-rw-rw-r--  1 oracle oinstall     3187 Apr 15  2018 role_setup.sql
-rw-rw-r--  1 oracle oinstall    35254 Apr 15  2018 sequence.sql
-rwxrwxr-x  1 oracle oinstall  4659736 Apr 15  2018 server
-rwxr-xr-x  1 oracle oinstall     4917 Jan  5  2017 SQLDataTypes.h
-rwxr-xr-x  1 oracle oinstall      248 Oct 15  2010 sqlldr.tpl
drwxr-xr-x  3 oracle oinstall     4096 Jul 28 14:45 srvm
-rwxrwxr-x  1 oracle oinstall      759 Oct 15  2010 tcperrs
-rwxr-xr-x  1 oracle oinstall    37877 Apr 16  2016 ucharset.h
```

```
-rw-rw-r--  1 oracle oinstall     7341 Apr 15  2018 ulg.sql
drwxr-xr-x  7 oracle oinstall     4096 Jul 28 14:45 UserExitExamples
-rwxr-xr-x  1 oracle oinstall    32987 Jun  2  2017 usrdecs.h
-rwxr-xr-x  1 oracle oinstall     1033 Oct 19  2016 zlib.txt
```

(3) .bash_profile

```
export LD_LIBRARY_PATH=$ORACLE_HOME/lib
```

(4)

```
$ ./ggsci
Oracle GoldenGate Command Interpreter for Oracle
Version 12.3.0.1.4 OGGCORE_12.3.0.1.0_PLATFORMS_180415.0359_FBO
Linux, x64, 64bit (optimized), Oracle 11g on Apr 15 2018 21:16:09
Operating system character set identified as UTF-8.
Copyright (C) 1995, 2018, Oracle and/or its affiliates. All rights reserved.


GGSCI ( hostname ) 1> create subdirs
Creating subdirectories under current directory /home/oracle/ogg12.3
Parameter file                 /home/oracle/ogg12.3/dirprm: created.
Report file                    /home/oracle/ogg12.3/dirrpt: created.
Checkpoint file                /home/oracle/ogg12.3/dirchk: created.
Process status files           /home/oracle/ogg12.3/dirpcs: created.
SQL script files               /home/oracle/ogg12.3/dirsql: created.
Database definitions files     /home/oracle/ogg12.3/dirdef: created.
Extract data files             /home/oracle/ogg12.3/dirdat: created.
Temporary files                /home/oracle/ogg12.3/dirtmp: created.
Credential store files         /home/oracle/ogg12.3/dircrd: created.
Masterkey wallet files         /home/oracle/ogg12.3/dirwlt: created.
Dump files                     /home/oracle/ogg12.3/dirdmp: created.
```

Oracle OGG

## 2.2OGG - TiDB

(1)

```
$ unzip V978711-01.zip
Archive:  V978711-01.zip
  inflating: ggs_Linux_x64_MySQL_64bit.tar
  inflating: OGG-12.3.0.1-README.txt
  inflating: OGG_WinUnix_Rel_Notes_12.3.0.1.5.pdf
```

(2) ggs_Linux_x64_MySQL_64bit.tar .

```
$tar xvf ./ggs_Linux_x64_MySQL_64bit.tar -C /home/tidb/ogg12.3
```

(3) ggsci

```
$ ./ggsci
Oracle GoldenGate Command Interpreter for MySQL
Version 12.3.0.1.5 OGGCORE_12.3.0.1.0_PLATFORMS_180501.2124
Linux, x64, 64bit (optimized), MySQL Enterprise on May  2 2018 10:58:16
Operating system character set identified as UTF-8.
Copyright (C) 1995, 2018, Oracle and/or its affiliates. All rights reserved.


GGSCI ( hostname ) 1> create subdirs
Creating subdirectories under current directory /home/tidb/ogg12.3
Parameter file                 /home/tidb/ogg12.3/dirprm: created.
Report file                    /home/tidb/ogg12.3/dirrpt: created.
Checkpoint file                /home/tidb/ogg12.3/dirchk: created.
Process status files           /home/tidb/ogg12.3/dirpcs: created.
SQL script files               /home/tidb/ogg12.3/dirsql: created.
Database definitions files     /home/tidb/ogg12.3/dirdef: created.
Extract data files             /home/tidb/ogg12.3/dirdat: created.
Temporary files                /home/tidb/ogg12.3/dirtmp: created.
Credential store files         /home/tidb/ogg12.3/dircrd: created.
Masterkey wallet files         /home/tidb/ogg12.3/dirwlt: created.
Dump files                     /home/tidb/ogg12.3/dirdmp: created.
```

OGG TiDB (OGG For MySQL )

## 2.3TiDB

(1) lower-case-table-names 1

```
$grep lower-case-table-names tidb.toml
lower-case-table-names  = 1
```

(2)

```
MySQL [(none)]> show variables like '%lower%';
+------------------------+-------+
| Variable_name          | Value |
+------------------------+-------+
| lower_case_table_names | 1     |
| lower_case_file_system | 1     |
+------------------------+-------+
MySQL [(none)]> show variables like '%place%' ;
+--------------------------------+-------+
| Variable_name                  | Value |
+--------------------------------+-------+
| tidb_constraint_check_in_place | 0     |
+--------------------------------+-------+
```

(3)

```
MySQL [scott]> create user 'tidb' identified by 'tidb';
Query OK, 1 row affected (0.01 sec)
MySQL [scott]> GRANT ALL PRIVILEGES ON scott.* to oggadmin ;
Query OK, 0 rows affected (0.01 sec)
MySQL [scott]> show create user tidb;
+-------------------------------------------------------------------------------------------------------------------------------------
--------------------------------------------------+
| CREATE USER for tidb@%
                                                  |
+-------------------------------------------------------------------------------------------------------------------------------------
--------------------------------------------------+
| CREATE USER 'tidb'@'%' IDENTIFIED WITH 'mysql_native_password' AS '*465D123EE55795DBDBDAE36AFD3DCD9C429B718A' REQUI
RE NONE PASSWORD EXPIRE DEFAULT ACCOUNT UNLOCK |
+-------------------------------------------------------------------------------------------------------------------------------------
--------------------------------------------------+
1 row in set (0.00 sec)
```

(4)

## 2.4Oracle

2.4.1

```
SQL> archive log list;
```

(1)

```
SQL> shutdown immediate;
```

(2) mount

```
SQL> startup mount;
```

(3)

```
SQL> alter database archivelog;
```

(4)

```
SQL> alter database open;
```

(5)

```
SQL> archive log list;
```

2.4.2

(1)

```
select log_mode,supplemental_log_data_min,force_logging from v$database;
```

(2) force logging

> nolog

```
SQL> ALTER DATABASE FORCE LOGGING;
```

(3)

```
SQL> ALTER DATABASE ADD SUPPLEMENTAL LOG DATA;
SQL> ALTER SYSTEM SWITCH LOGFILE;
```

(4) OGG

```
SQL> alter system set enable_goldengate_replication=true;
```

2.4.3 ogg

goldengate

```
SQL> create tablespace goldengate datafile '/opt/oracle/data/goldengate001.dbf' size 4G;
SQL> create user goldengate identified by goldengate default tablespace goldengate;
SQL> grant dba to goldengate;
```

## 2.5OGG

(1) ggsic

```
./ggsci
create subdirs
add credentialstore
alter credentialstore add user goldengate,password goldengate
```

(2) ogg goldengate

```
dblogin useridalias goldengate
```

## 2.6 schema

schema schema

(1) 11.2.0.2 Oracle Patch 13794550

> oracle schema
>
> ERROR OGG-06522 Cannot verify existence of table function that is required to ADD schema level supplemental logging, failed.

(2) GGSCI

> 1) dblogin userid goldengate, password goldengate
>
> 2) dblogin useridalias goldengate

(3) schema

> ADD SCHEMATRANDATA schema ALLCOLS

## 2,7

> schema

(1) GGSCI

```
dblogin userid goldengate, password goldengate
```

(2) schema

```
ADD TRANDATA schema.tablename NOKEY
```

# OGG

## 3.1OGG

1. INITIAL LOAD
2. CHANGE SYNCHRONIZATION trail oracle oracle redo log archive log trail

| | |
|---|---|
| /opt/oracle/11.2.0 | ORACLE_HOME |
| ora | Oracle sid |
| ext_ora | |
| tdpm_ora | |
| rep_ora | |
| ./dirdat/sk | |
| /Data/tidb/ogg/dirdat/sk | Replicat |

## 3.2

> ADG

Extract pump

Extract redo archive log Data pump

### 3.2.1 MGR

Manager OGG ExtractPumpReplicat ExtractPumpReplicat Manager

(1)

```
GGSCI (b-db-ps-055) 5> view param mgr

port 9001
DYNAMICPORTLIST 9001-9020
--AUTORESTART ER *,RETRIES 5,WAITMINUTES   7
PURGEOLDEXTRACTS   ./dirdat/*,usecheckpoints, minkeepdays 2
LAGREPORTHOURS 1
LAGINFOMINUTES 30
LAGCRITICALMINUTES 45
```

| | |
|---|---|
| port | |
| DYNAMICPORTLIST | OGG OGG |
| AUTORESTART | |
| PURGEOLDEXTRACTS | trail 2 trail |
| LAGREPORTHOURS | lag 1 |
| LAGINFOMINUTES | |

(2) mgr

```
./ggsci
start mgr
```

## 3.2.2 Extract

Extract OGG Extract

(1)

```
GGSCI (b-db-ps-055) 2> edit param   ext_ora

EXTRACT ext_ora
SETENV   (ORACLE_HOME="/opt/oracle/11.2.0")
setenv   (NLS_LANG="AMERICAN_AMERICA.AL32UTF8")
setenv (ORACLE_SID="ora")
useridalias goldengate
GETTRUNCATES
REPORTCOUNT EVERY 1 MINUTES, RATE
DISCARDFILE   ./dirrpt/ext_ora.dsc,APPEND,MEGABYTES 1000
WARNLONGTRANS 2h,CHECKINTERVAL 10m
EXTTRAIL ./dirdat/sk
TRANLOGOPTIONS EXCLUDEUSER goldengate
TRANLOGOPTIONS MINEFROMACTIVEDG
DBOPTIONS ALLOWUNUSEDCOLUMN
DYNAMICRESOLUTION
FETCHOPTIONS FETCHPKUPDATECOLS,INCONSISTENTROW ALLOW
ddl include mapped objname hr.*
getupdatebefores
nocompressdeletes
nocompressupdates
table hr.table_name;
```

| | | |:----|:----| | SETENV | | | useridalias | | | GETTRUNCATES | truncate | | REPORTCOUNT | | | WARNLONGTRANS | OGG | | EXTTRAIL | trail | | TRANLOGOPTIONS EXCLUDEUSER | | | TRANLOGOPTIONS MINEFROMACTIVEDG | ADG | | DBOPTIONS ALLOWUNUSEDCOLUMN | | |

DYNAMICRESOLUTION | OGG OGG OGG OGG ID
FETCHPKUPDATECOLS,INCONSISTENTROW ALLOW | row id () ALLOW |

(2)

```
./ggsci
add extract ext_ora,TRANLOG, begin now
add ExtTrail ./dirdat/sk, Extract ext_ora,   Megabytes 50
```

### 3.2.3 Pump

Pump Extract Pump Extract Trail Trail

```
GGSCI (b-db-ps-055) 4> edit param   tdpm_ora

EXTRACT tdpm_ora
RMTHOST 31.***.***.***, MGRPORT 9001,   compress
PASSTHRU
RMTTRAIL /Data/tidb/ogg/dirdat/sk
DYNAMICRESOLUTION
--table
table hr.table_name;
```

| | | |:----|:----| | RMTHOST | IP MGR | | PASSTHRU | OGG |

(1) pump

```
./ggsci
add extract tdpm_ora, exttrailsource   ./dirdat/sk
add rmttrail /Data/tidb/ogg/dirdat/sk,   extract tdpm_ora, megabytes 100
```

## 3.3

### 3.3.1 MGR

(1)

```
GGSCI (w-db-ps-082) 2> edit param mgr

port 9001
DYNAMICPORTLIST 9001-9120
ACCESSRULE, PROG *, IPADDR 31.*.*.*,   ALLOW
--AUTORESTART ER *,RETRIES 5,WAITMINUTES   7
PURGEOLDEXTRACTS   ./dirdat/*,usecheckpoints, minkeepdays 10
LAGREPORTHOURS 1
LAGINFOMINUTES 30
LAGCRITICALMINUTES 45
```

(2) mgr

```
./ggsci
start mgr
```

### 3.3.2 Replicat

Replicat

# 5.3 SQL Server TiDB

## 5.3.1

SQL server DAU 1000000000+ SQL server

```
1 SQL Server  100  1000

2 SQL Server
```

SQL Server TiDB SQL Server TiDB

## 5.3.2

| | |
|---|---|
| | 1. SQL Server CDC<br>2. SQL Server<br>3. ETL TiDB<br>4. |
| | 1. CDC TiDB<br>2. |
| | 1. SQL Server<br>2. CDC<br>3. TiDB |

## 5.3.3

### 1.

yugongyugong Oracle https://github.com/alswl/yugong SQL Server

### 2.

**(1) yugong**

```
#  jar
wget https://github.com/alswl/yugong/releases/download/541e5f8/yugong-shaded.jar

#
git git@github.com:alswl/yugong.git
cd yugong
mvn clean package
```

**(2)**

yugong `yugong.properties` `yugong.yaml`

- `yugong.properties`

```
# vi  yugong.properties
vi yugong.properties
```

```
#
yugong.database.source.url=jdbc:sqlserver://192.168.1.88:1433;databaseName=example
yugong.database.source.username=sa
yugong.database.source.password=sa
yugong.database.source.type=SQL_SERVER
yugong.database.source.encode=UTF-8
yugong.database.source.poolSize=200

# TiDB  MySQL
yugong.database.target.url=jdbc:mysql://192.168.1.99:3306/example?autoReconnect=true
yugong.database.target.username=root
yugong.database.target.password=root
yugong.database.target.type=MYSQL
yugong.database.target.encode=UTF-8
yugong.database.target.poolSize=200
yugong.table.batchApply=true
yugong.table.onceCrawNum=1000
yugong.table.tpsLimit=0
#  schema
yugong.table.ignoreSchema=false
# skip Applier Load Db failed data
yugong.table.skipApplierException=false
#
yugong.table.white=user
yugong.table.black=
#
yugong.table.concurrent.enable=true
#
yugong.table.concurrent.size=6
# retry times
yugong.table.retry.times=3
# retry interval or sleep time (ms)
yugong.table.retry.interval=1000
# MARK/FULL/INC/ALL(REC+FULL+INC)/CHECK/CLEAR
# FULL
yugong.table.mode=FULL


# yugong extractor
yugong.extractor.dump=false
yugong.extractor.concurrent.enable=true
yugong.extractor.concurrent.global=false
yugong.extractor.concurrent.size=60
yugong.extractor.noupdate.sleep=1000
yugong.extractor.noupdate.thresold=0
yugong.extractor.once=false

# yugong applier
yugong.applier.concurrent.enable=true
yugong.applier.concurrent.global=false
yugong.applier.concurrent.size=20
yugong.applier.dump=false
# stats
yugong.stat.print.interval=5
yugong.progress.print.interval=1
# alarm email
yugong.alarm.email.host=
yugong.alarm.email.username=
yugong.alarm.email.password=
yugong.alarm.email.stmp.port=
yugong.alarm.email.ssl.support=
```

- `yugong.yaml` translator

```
#  yugong.yaml.sample
wget https://raw.githubusercontent.com/alswl/yugong/feature/sql-server-to-mysql-overview/yugong.yaml.sample

#  yugong.yaml
mv yugong.yaml.sample yugong.yaml
```

### (3) yugong

- yugong

```
# -c yugong.properties
# -y yugong.yaml ETL  translator
#
java -jar yugong-shaded.jar -c yugong.properties -y yugong.yaml
```

-

```
#
2019-12-02 20:49:23.923 [main] INFO  com.taobao.yugong.YugongApp - ## start the YuGong.
#
2019-12-02 20:49:24.000 [main] INFO
com.taobao.yugong.controller.YuGongController - check source database connection ...
2019-12-02 20:49:24.017 [main] INFO  com.taobao.yugong.controller.YuGongController - check source database is ok
2019-12-02 20:49:24.017 [main] INFO  com.taobao.yugong.controller.YuGongController - check target database connection
 ...
2019-12-02 20:49:24.028 [main] INFO  com.taobao.yugong.controller.YuGongController - check target database is ok
2019-12-02 20:49:24.028 [main] INFO  com.taobao.yugong.controller.YuGongController - check source tables read privile
ges ...
#
2019-12-02 20:49:24.071 [main] INFO  com.alibaba.druid.pool.DruidDataSource - {dataSource-1} inited
2019-12-02 20:49:24.277 [main] INFO  com.alibaba.druid.pool.DruidDataSource - {dataSource-2} inited
2019-12-02 20:49:25.418 [main] INFO  com.taobao.yugong.controller.YuGongController - check source tables is ok.
#
2019-12-02 20:49:26.933 [main] INFO  com.taobao.yugong.controller.YuGongController - ## prepare start tables[1] with
concurrent[6]
2019-12-02 20:49:26.959 [main] INFO  com.taobao.yugong.YugongApp - ## the YuGong is running now ......
#
2019-12-02 20:51:08.801 [Thread-7] INFO  com.taobao.yugong.common.stats.ProgressTracer - {:0,:0,:1,:0}
#
2019-12-02 20:51:08.801 [Thread-7] INFO  com.taobao.yugong.common.stats.ProgressTracer - :[example.user]
2019-12-02 20:51:08.805 [Thread-7] INFO  com.alibaba.druid.pool.DruidDataSource - {dataSource-2} closed
2019-12-02 20:51:08.806 [Thread-7] INFO  com.alibaba.druid.pool.DruidDataSource - {dataSource-1} closed
2019-12-02 20:51:08.807 [Thread-7] INFO  com.taobao.yugong.YugongApp - ## YuGong is down.
```

> 

### (4)

- logs

```
logs
├── example.user  #
│   ├── applier.log  #
│   ├── extractor.log  #
│   └── table.log  #
└── yugong
    └── table.log  #
positioner_data
└── example_user.dat #
```

> table.log `ERROR`

## 5.3.4

## 1.

SQL Server CDC SQL Server CDC CDC Change Data CaptureCDC TiDBCapture process transaction log Change Table CDC

## 2.

### (1) SQL Server CDC

```
-- CDC
sys.sp_cdc_enable_db;

--  example CDC
EXEC sys.sp_cdc_enable_table @source_schema = N'dbo', @source_name = N'example', @role_name = NULL;

--  SQL  CDC
-- CDC
SELECT name, is_cdc_enabled from sys.databases where is_cdc_enabled = 1;
```

### (2) CDC `Change Table` `cdc.dbo_example_CT`

```
.schema cdc.dbo_example_CT
name            default  nullable  type          length  indexed
--------------  -------  --------  ------------  ------  -------
__$end_lsn      null     YES       binary        10      NO
__$operation    null     NO        int           4       NO
__$seqval       null     NO        binary        10      NO
__$start_lsn    null     NO        binary        10      YES
__$update_mask  null     YES       varbinary     128     NO
id              null     YES       int           4       NO
name            null     YES       varchar(255)  255     NO
```

> id name example

### (3) CDC

- example CDC

```
--
DECLARE @begin_time datetime, @end_time datetime, @begin_lsn binary(10), @end_lsn binary(10);

--
SET @begin_time = '2020-03-08 10:00:00.000';
SET @end_time   = '2020-03-08 10:10:00.000';

--  lsn
SELECT @begin_lsn = sys.fn_cdc_map_time_to_lsn('smallest greater than', @begin_time);
SELECT @end_lsn = sys.fn_cdc_map_time_to_lsn('largest less than or equal', @end_time);

--  lsn
SELECT * FROM cdc.fn_cdc_get_all_changes_dbo_example(@begin_lsn, @end_lsn, 'all');
```

-

```
__$start_lsn          __$end_lsn  __$seqval             __$operation  __$update_mask  id  name
--------------------  ----------  --------------------  ------------  --------------  --  ------
0000dede0000019f001a  null        0000dede0000019f0018  2             03              1   AAA
0000dede000001ad0004  null        0000dede000001ad0003  2             03              2   BBB
0000dede000001ba0003  null        0000dede000001ba0002  3             02              2   BBB
0000dede000001ba0003  null        0000dede000001ba0002  4             02              2   CCC
0000dede000001c10003  null        0000dede000001c10002  2             03              3   DDD
0000dede000001cc0005  null        0000dede000001cc0002  1             03              3   DDD
```

> __$operation
>
> - 
> - 
> - 
> - 

**(4) CDC**

CDC SQL Change Table `__$operation` SQL TiDB

> 1. `Kafka` `RabbitMQ`
> 2. `Kafka` `Topic` `Partition` `1`
> 3. 
> 4. CDC `insert ignore` SQL

## 5.3.5

ETL

yugong ETL `CHECK` `FULL` `INC` `AUTO` `CHECK` yugong yugong `JDBC`

yugong SQL Server —— `physloc`

5 TiDB

## 5.3.6

1. SQL server DBA SQL server DMV
2. SQL Server TiDBMySQL
3. SQL Server TiDBMySQL
4. 
5. 
6. 

## 5.3.7

TiDB MySQL “” SQL Server TiDB

DataX / MySQLSQL ServerOraclePostgreSQLHDFSHiveHBaseOTSODPS DataX + GitHub

DataX TiDB

TiDB SQL Server DataX TiDB

UpdateTime Where t_sync_record

TiDB SQL Server SQL Server

DataX

```
wget http://datax-opensource.oss-cn-hangzhou.aliyuncs.com/datax.tar.gz
```

```
tar -zxvf datax.tar.gz
```

```
python {YOUR_DATAX_HOME}/bin/datax.py {YOUR_DATAX_HOME}/job/job.json
```

DataX JobJson

1Job

vi full.json

```
{
    "job": {
        "setting": {
            "speed": {
```

```
                #
                "channel": 128
            }
        },
        "content": [{
             #SQL Server
            "reader": {
                "name": "sqlserverreader",
                "parameter": {
                    #
                    "username": "${srcUserName}",
                    #
                    "password": "${srcPassword}",
                     #*
                    "column": ["*"]
                    "connection": [{
                        #
                        "table": ["${tableName}"],
                          jdbc
                        "jdbcUrl": ["${srcUrl}"]
                    }]
                }
        },
        #TiDB
        "writer": {
                "name": "tidbwriter",
                "parameter": {
                    #
                    "username": "${desUserName}",
                     #
                    "password": "${desPassword}",
                     # Replace
                    "writeMode": "replace",
                    #*
                    "column": ["*"],
                    "connection": [{
```

```
                        # jdbc
                        "jdbcUrl": "${desUrl}",
                        #
                        "table": ["${tableName}"]
                    }],
                     #sql-
                    "preSql": [
                       "replace into t_sync_record(table_name,start_date,end_date) values('@table',now(),null)"],
                    # sql-
                    "postSql": [
                       "update t_sync_record set end_date=now() where table_name='@table' " ]
                }
            }
        }]
    }
}
```

2 Job

vi increase.json

```
{
    "job": {
        "setting": {
            "speed": {
                #
                "channel": 128
            }
        },
        "content": [{
             #SQL Server
            "reader": {
                "name": "sqlserverreader",
                "parameter": {
                    #
                    "username": "${srcUserName}",
                    #
                    "password": "${srcPassword}",
```

```
                    #*
                "column": ["*"],
                "connection": [{
                    #
                    "table": ["${tableName}"],
                      jdbc
                    "jdbcUrl": ["${srcUrl}"]
                }],
                #
                "where": "updateTime >= '${syncTime}'"
            }
        },
        #TiDB
        "writer": {
            "name": "tidbwriter",
            "parameter": {
                #
                "username": "${desUserName}",
                 #
                "password": "${desPassword}",
                 # Replace
                "writeMode": "replace",
                #*
                "column": ["*"],
                "connection": [{
                    # jdbc
                    "jdbcUrl": "${desUrl}",
                    #
                    "table": ["${tableName}"]
                }],
                 #sql-
                "preSql": [
                   "replace into t_sync_record(table_name,start_date,end_date) values('@table',now(),null)"],
                # sql-
                "postSql": [
                   "update t_sync_record set end_date=now() where table_name='@table' " ]
```

```
                }
            }
        }]
    }
}
```

3DataX JobShell

vi datax_excute_job.sh

```
#!/bin/bash

source /etc/profile

srcUrl="Reader Sql Server "

srcUserName="Sql Server "

srcPassword="Sql Server "

desUrl="Writer TiDB "

desUserName="TiDB "

desPassword="TiDB "

#

defaultsyncUpdateTime="2020-03-03 18:00:00.000"

# ()

sleepTime="N"

tableName="Table1,Table2,..."

# -1

flg=-1

while [ "$flg" -gt 0 -o "$flg" -eq -1 ]

do

        #

        if [ "" = "$preRunTime" ]; then

                syncTime=$defaultsyncUpdateTime

        else

                syncTime=$preRunTime

        fi

        #

        preRunTime=$(date -d +"%Y-%m-%d %T")".000";

        echo $syncTime

        echo $preRunTime

        echo $flg

        python {YOUR_DATAX_HOME}/bin/datax.py -p "-DsyncTime='${syncTime}' -DtableName='${tableName}' -DsrcUrl='${src
Url}' -DsrcUserName='${srcUserName}' -DsrcPassword='${srcPassword}' -DdesUrl='${desUrl}' -DdesUserName='${desUserName
}' -DdesPassword='${desPassword}'" {YOUR_DATAX_HOME}/job/increase.json

        if [ -1  -lt  "$flg" ]; then

               let "flg-=1"

        fi

        sleep $sleepTime

done
```

4 Shell

```
chmod +x datax_excute_job.sh

nohup ./datax_excute_job.sh > info.file 2>&1 &
```

SQL Server TiDB

# Db2 TiDB CDC

Db2 TiDB Db2 Db2 for LUWDb2 for iAS/400Db2 for z/OSMainframe Db2 for LUW IBM CDC OGG Db2 for i Db2 for z/OS IBM CDC Db2 for i CDC TiDB IBM CDC TiDB

IBM Db2 InfoSphere Data Replication IIDR IIDR Change data capture (CDC) Replication Q Replication SQL Replication Db2 for i TiDB Change data capture (CDC) Replication IBM CDC IIDR

## CDC

- IIDR-CDC CDC

- CDC https://www.ibm.com/support/knowledgecenter/SSTRGZ_11.4.0/com.ibm.cdcdoc.sysreq.doc/concepts/supportedsourceandtargets.html

| Supported source databases | Supported target databases and middleware applications |
|---|---|
| IBM??Db2? for Linux, UNIX and Windows (LUW) | IBM?Db2 for Linux, UNIX and Windows (LUW) |
| IBM?Db2 for i | IBM?Db2 for i |
| IBM?Db2 for z/OS? | IBM?Db2 for z/OS |
| IMS | IBM?InfoSphere? DataStage? |
| Microsoft SQL Server | Microsoft SQL Server |
| Oracle | CDC Replication Engine for FlexRep |
| Sybase?1 | Netezza? |
| Informix??1 | Oracle |
| Db2 on Cloud?(formerly dashDB? for Transactions)?2 | Sybase?1 |
| VSAM | Informix?1 |
| PostgreSQL | CDC Replication Engine for Event Server?1 |
| Db2 Warehouse on Cloud?(formerly dashDB for Analytics)?3 | IBM Cloudant? |
| Db2 Warehouse?(formerly dashDB Local)?3 | Apache? Hadoop |
| MySQL | Apache Kafka |
| | Db2 Warehouse on Cloud?(formerly dashDB for Analytics) |
| | Db2 on Cloud?(formerly dashDB for Transactions)?2 |
| | Db2 Warehouse?(formerly dashDB Local) |
| | IBM MQ for z/OS (using Classic CDC for z/OS) |
| | Teradata |
| | Microsoft Azure SQL Database |
| | Microsoft Azure SQL Database Managed Instance |
| | IBM Integrated Analytics System |

- TiDB  CDC Replication Engine for FlexRep  JDBC  TiDB  MySQL  MySQL  JDBC driver TiDB
- CDC  datastage type FlexRep  JDBC driver  TiDB

Db2 for i  TiDB

IBM OMS IIDR TiDB IIDR

IIDR IIDR TiDB

- IIDR FlexRep

TiDB IIDR **FlexRep**

- MySQL

IIDR MySQL JDBC TiDB MySQL

- IIDR

| | |
|---|---|
| convert_not nullable_column | true |
| events_max_retain | 10000 |
| global_conversion_not_possible_warning | false |
| global_max_batch_size | 25 |
| global_shutdown_after_no_heartbeat_reponse_minute | 10 |
| Implicit_transformation_warning | true |
| jdbc_refresh_commit_after_max_operation | 4000 |
| Mirror_commit_after_max_operations | 4000 |
| Mirror_global_disk_quota_gb | 9223372036854775807 |
| Mirror_interim_commit_threshols | 100 |
| Userexit_max_lob_size_kb | 2097151 |
| Mirror_commit_on_transaction_boundary | False |

-

IIDR TiDB Db2 for i TiDB

| Db2 | TiDB |
| --- | --- |
| L | date |
| T | time |
| Z | timestamp(6) |
| A | varchar |
| P | Decimal |
| S | decimal |
| O | varchar |

- CDC Db2 Db2 TiDB loadalter table xxx activate not logged initially
- CDC datastage type FlexRep TiDB

IIDR Db2 for i TiDB IIDR TiDB

TiDB TiDB TiDB

DataX TiDB TiDB 4.0 CDC

TiDB

DataX

```
wget http://datax-opensource.oss-cn-hangzhou.aliyuncs.com/datax.tar.gz
```

```
tar -zxvf datax.tar.gz
```

```
python {YOUR_DATAX_HOME}/bin/datax.py {YOUR_DATAX_HOME}/job/job.json
```

Job

vi increase.json

```
{
    "job": {
        "setting": {
            "speed": {
                "channel": 128 #Channel
            }
        },
        "content": [{
            "reader": {
                "name": "tidbreader",
```

```
                "parameter": {
                    "username": "${srcUserName}",
                    "password": "${srcPassword}",
                    "column": ["*"],
                    "connection": [{
                        "table": ["${tableName}"],
                        "jdbcUrl": ["${srcUrl}"]
                    }],
                    "where": "updateTime >= '${syncTime}'"
                }
            },
            "writer": {
                "name": "tidbwriter",
                "parameter": {
                    "username": "${desUserName}",
                    "password": "${desPassword}",
                    "writeMode": "replace",
                    "column": ["*"],
                    "connection": [{
                        "jdbcUrl": "${desUrl}",
                        "table": ["${tableName}"]
                    }],
                    "preSql": [
                       "replace into t_sync_record(table_name,start_date,end_date) values('@table',now(),null)"],
                    "postSql": [
                       "update t_sync_record set end_date=now() where table_name='@table' " ]
                }
            }
        }]
    }
}
```

DataX JobShell

vi datax_excute_job.sh

```
#!/bin/bash

source /etc/profile

srcUrl="Reader SourceTiDB "

srcUserName=""

srcPassword=""

desUrl="Writer DestTiDB "

desUserName=""

desPassword=""

#

defaultsyncUpdateTime="2020-03-03 18:00:00.000"

#()

sleepTime="N"

tableName="Table1,Table2,..."

#-1

flg=-1

while [ "$flg" -gt 0 -o "$flg" -eq -1 ]

do

        #

        if [ "" = "$preRunTime" ]; then

                syncTime=$defaultsyncUpdateTime

        else

                syncTime=$preRunTime

        fi

        #

        preRunTime=$(date -d +"%Y-%m-%d %T")".000";

        echo $syncTime

        echo $preRunTime

        echo $flg

        python {YOUR_DATAX_HOME}/bin/datax.py -p "-DsyncTime='${syncTime}' -DtableName='${tableName}' -DsrcUrl='${src
Url}' -DsrcUserName='${srcUserName}' -DsrcPassword='${srcPassword}' -DdesUrl='${desUrl}' -DdesUserName='${desUserName
}' -DdesPassword='${desPassword}'" {YOUR_DATAX_HOME}/job/increase.json

        if [ -1  -lt  "$flg" ]; then

               let "flg-=1"

        fi

        sleep $sleepTime

done
```

Shell

```
chmod +x datax_excute_job.sh

nohup ./datax_excute_job.sh > log.file 2>&1 &
```

DataX Job Shell Supervisor TiDB

TiDB TiDB

DataX TiDB

# 5.7 MongoDB TiDB

## 5.7.1

MongoDB MongoDB

`MongoS` `Oplog` MySQL

`MongoS` AP MongoDB `Kafka` `ClickHouse`

MongoDB TiDB

## 5.7.2 TiDB MongoDB

| MongoDB | TiDB |
| --- | --- |
| 1.<br>2. json<br>3.<br>4. Sharded cluster | 1.<br>2.<br>3.<br>4. |

## 5.7.3 TiDB

Redis Cluster MongoDB TiDB Redis TiDB

Web Service Proxy Redis Cluster TiDB `Transaction too large` Redis Cluster TiDB TiDB TiDB-binlog `Kafka` Redis Cluster

Proxy TiDB Redis Cluster `key-value` Redis TiDB SQL TiDB Spark `Big Key` `Hot Key` Redis `LFU` `key-value` 5 `key-value` Spark 35 TiDB Redis Cluster

Redis TiDB `sleep`

## 5.7.4

## 1.

- 
  - MongoDB MongoDB `_id` TiDB `ID`

    - `uuid` `snowflakes`
    - PK PK TiDB rowid `INSERT` Region `SHARD_ROW_ID_BITS` rowid Region RPC CPU
    - v4.0 TiDB `Auto Random Key` `Auto Random Key` `int`
  - MongoDB TiDB MongoDB TiDB `DATEDATETIME` `TIMESTAMP` `TIME` `YEAR`
- 
- 
- Web Service
- watch
- `uid` `uid`

## 2.

MongoDB java Redis Cluster MongoDB Change Stream Kafka TiDB TiDB TiDB TiDB-binlog Kafka MongoDB TiDB MongoDB TiDB MongoDB TiDB MongoDB MongoDB

> MongoDB v3.6 Change Stream `watch` `MongoCursor`

## 3.

6

**(1)**

`max(uid)` TiDB `max(uid)` TiDB MongoDB TiDB `max(uid)` DML TiDB DML

**(2) Redis**

20 `uid` Redis Cluster Redis log

```
127.0.0.1:6379> KEYS *
1) "migration:data:st"
127.0.0.1:6379> HGETALL "migration:comminfo:st"
 1) "218620068122832 5_238248857777154 0"
 2) "218851395299846 6"
 3) "285966819969142 9_939670410420644 55"
 4) "286116683500851 9"
 5) "248755768403763 3_261230146739508 5"
 6) "248864948769693 8"
 7) "261230146739508 5_265779473046447 5"
 8) "261335227334759 7"
 9) "238248857777154 0_243800281988509 6"
10) "238393360913306 7"
11) "270870639760699 3_285966819969142 9"
12) "270989183444696 3"
13) "265779473046447 5_270870639760699 3"
14) "265890143027311 1"
15) "209421140620084 8_218620068122832 5"
16) "209662855658598 8"
17) "243800281988509 6_248755768403763 3"
18) "243904444701186 8"
```

**(3)**

`UpdateTime` `Change Stream` `UpdatedTime` `insert` `update` `delete` MongoDB `Change Stream` Kafka `Kafka` TIDB

**(4)**

**(5)**

**(6)**

- TiDB MongoDB TiDB TiDB TiDB TiDB
- TiDB MongoDB TiDB TiDB
- TiDB TiDB-binlog Kafka MongoDB

## 5.7.5

### 1.

MongoDB `Change Stream` Kafka TiDB Redis `uid` Kafka `uid` Redis `uid`

```
127.0.0.1:6379> KEYS *
1) "migration:data:st"
127.0.0.1:6379> HGETALL "migration:comminfo:st"
 1) "218620068122832 5_238248857777154 0"
 2) "2188513952998466"
 3) "2859668199691429_9396704104206445 5"
 4) "2861166835008519"
 5) "2487557684037633_2612301467395085"
 6) "2488649487696938"
 7) "2612301467395085_2657794730464475"
 8) "2613352273347597"
 9) "2382488577771540_2438002819885096"
10) "2383933609133067"
11) "2708706397606993_2859668199691429"
12) "2709891834446963"
13) "2657794730464475_2708706397606993"
14) "2658901430273111"
15) "2094211406200848_2186200681228325"
16) "2096628556585988"
17) "2438002819885096_2487557684037633"
18) "2439044447011868"
```

### 2. MongoDB metadata

`Metadata` MongoDB TiDB MongoDB MongoDB `Metadata` `Metadata` TiDB

### 3. TiDB

TiDB MongoDB TiDB SQL

## 5.7.6 -

TiDB MongoDB

1.

TiDB TiDB TiDB-binlog Kafka MongoDB MongoDB

TiDB Web Service MongoDB MongoDB Change Stream Kafka TiDB

1.

“” RPC “” RPC

RPC RPC ”“

```
#
circuitBreaker.requestVolumeThreshold   // 20
circuitBreaker.errorThresholdPercentage // 50%
circuitBreaker.sleepWindowInMilliseconds// 5000 5s
#
 20  50% 5s
```

“”Web Service RPC “”“”

MongoDB TiDB TiDB MongoDB TiDB Kafka

## 5.7.7 SQL

MongoDB SQL TP 99% 15ms99.9% 700ms sum group by TP 99% 15ms99.9% 48ms
SQL

-

-

## 5.7.8

MongoDB TiDB MongoDB change stream TiDB TiDB-binlog Kafka Updatetime RedisMongoDBTiDB MongoDB TiDB

# 6

TiDBHTAP(OLTPOLAP)TiDB

- TiDB
- 
- TiDB + TiSpark
- TiDB
- TiDB  HBaseESDruid
- TiDB  SaikuGrafana
- TiKV

# 6.1

TiDB TiDB

- 
- TiDB
- 
- 
- hint
- SQL
- TiDB + TiSpark

# 6.1.1

3.0.8 TiDB TiDB

- 
- 

- 
- 
- commit

## 6.1.1.1

- Key Key
- Key

TiDB commit

1. TiDB
2. TCC) TiDB

(, , ), , ,

1. , TiDB v3 , ( redis ),
2. , . TiDB ( kafka partition),
3. 

## 6.1.1.2

TiDB (100500 )

1. TiDB OOM
2. 
3. 

TiDB

1. SQL 5000
2. 6MB
3. 300,000
4. 100MB

## 6.1.1.3

prewrite TiKV TiDB

- TiDB TiDB TiKV
- TiKV prewrite TiDB TiDB TiDB TiKV

TiDB

```
txn-local-latches    enable    false
capacity  Hash  slot  2  slot  32 Bytes   1024000
```

capacity key hash hash capacity hash

- capacity
- capacity

TiDB

TiKV TiKV hash

```
scheduler-concurrency  scheduler  key  key hash   2048000
```

TiKV latch

wait duration

## 6.1.1.4 tidb

commit Commit MySQL SQL commit TiDB

- tidb_disable_txn_auto_retry on
- tidb_retry_limit

1. start_ts
2. SQL
3.

tidb_disable_txn_auto_retry = off lost update TiDB tso, region TiDB tidb_disable_txn_auto_retry = off

| | Session A | Session B |
|---|---|---|
| t1 | MySQL [test]> begin;<br>***Query OK, 0 rows affected (0.00 sec)*** | |
| t2 | | MySQL [test]> begin; |

| | | | | | | | | | | |
|---|---|---|---|---|---|---|---|---|---|---|
| t2 | | ***Query OK, 0 rows affected (0.00 sec)*** | | | | | | | | |
| t3 | | MySQL [test]> update tidb set status=0 where id=1;<br>***Query OK, 1 row affected (0.01 sec)***<br>***Rows matched: 1***<br>***Changed: 1***<br>***Warnings: 0*** | | | | | | | | |
| t4 | MySQL [test]> select *from tidb where id=1;*<br>**+------+------+--------+<br>\ | id \ | name<br>\ | status<br>\ | +------+--------+--------+<br>\ | 1<br>\ | tikv<br>\ | 1<br>\ | +------+--------+--------+<br>1 row in set (0.01 sec)* | |
| t5 | | commit;<br>***Query OK, 0 rows affected (0.01 sec)*** | | | | | | | | |
| t6 | update tidb set name='pd' where id =1 and status=1;<br>**Query OK, 1 row affected (0.00 sec)**<br>**Rows matched: 1**<br>**Changed: 1**<br>**Warnings: 0** | | | | | | | | | |
| t7 | MySQL [test]> select *from tidb where id=1;*<br>**+------+------+--------+<br>\ | id \ | name<br>\ | status<br>\ | +------+--------+--------+<br>\ | 1<br>\ | pd<br>\ | 1<br>\ | +------+--------+--------+<br>1 row in set (0.01 sec)* | |
| t8 | MySQL [test]> commit;<br>***Query OK, 0 rows affected (0.01 sec)*** | | | | | | | | | |
| t9 | MySQL [test]> select *from tidb where id=1;*<br>**+------+------+--------+<br>\ | id \ | name<br>\ | status<br>\ | +------+--------+--------+<br>\ | 1<br>\ | tikv<br>\ | 0<br>\ | +------+--------+--------+<br>1 row in set (0.00 sec)* | |

case:

- session B  t2  2t5 session A  1  2 2
-  1 2
- session A  1 tidb  1
  - start_ts  t8’
  - update tidb set name='pd' where id =1 and status=1
    - t8’
    -
- tidb  1
- session A

start_ts ReadRepeatable

SQL TiDB

TiDB TiDB

# 4.6 TiDB

2.1 TiDB

## 4.6.1

>

> TiDB TiDB
>
> 6MB
>
> 300,000
>
> 100MB
>
> SQL 5000

**PingCAP -**

TiDB RocksDB Key-Value 6MB 100MB 30W

## 4.6.2 30W

30W TiKV Key-Value

Key-Value

| Key | Value | Flag |
| --- | --- | --- |
| | | |

- **Insert**

TiKV

(1)

| Key: PK + TSO | Value: Fields | Flag: Put |
| --- | --- | --- |
| | | |

(2)

| Key: Index (UK) + TSO | Value: PK | Flag: Put |
| --- | --- | --- |
| | | |

(3)

| Key: Index + PK + TSO | Value: Null | Flag: Put |
| --- | --- | --- |
| | | |

Insert 30W 1 + ())

- **Delete**

TiKV RocksDB Flag = Del

(1)

| Key: PK + TSO | Value: Null | Flag: Del |
| --- | --- | --- |
| | | |

(2)

| Key: Index (UK) + TSO | Value: Null | Flag: Del |
|---|---|---|
| | | |

(3)

| Key: Index + PK + TSO | Value: Null | Flag: Del |
|---|---|---|
| | | |

Delete 30W (1 + ())

- **Update**

(1)

| Key: PK + TSO | Value: Fields | Flag: Put |
|---|---|---|
| | | |

30W 30W

(1)

| Key: PK + TSO | Value: Fields | Flag: Put |
|---|---|---|
| | | |

(2)

| Key: Index (UK) + TSO | Value: Null | Flag: Del |
|---|---|---|
| | | |

| Key: Index (UK) + TSO | Value: PK | Flag: Put |
|---|---|---|
| | | |

(3)

| Key: Index + PK + TSO | Value: Null | Flag: Del |
|---|---|---|
| | | |

| Key: Index + PK + TSO | Value: Null | Flag: Put |
|---|---|---|
| | | |

30W (1 + * 2)

PK Key

(1)

| Key: PK + TSO | Value: Null | Flag: Del |
|---|---|---|
| | | |

| Key: PK + TSO | Value: Fields | Flag: Put |
|---|---|---|
| | | |

(2)

| Key: Index (UK) + TSO | Value: PK | Flag: Put |
|---|---|---|
| | | |

(3)

| Key: Index + PK + TSO | Value: Null | Flag: Del |
| --- | --- | --- |
| | | |

| Key: Index + PK + TSO | Value: Null | Flag: Put |
| --- | --- | --- |
| | | |

30W ((1 + ) * 2 + ) Update 1 KV 2 KV Key-Value Key UK Value PKUpdate PK Key Put kv
Key PK Update Del kvPut kv

## 4.6.3 30W

||| |:----:|:----:| | Insert | 30W/(1+Idx_Count) | | Delete | 30W/(1+Idx_Count) | | Update_On_PK | 30W/((1+Non_UK)*2+UK*1) Update_non_PK | 30W/(1+Involved_Idx_Count*2) |

CREATE TABLE `t1` (

`id` int(11) NOT Null AUTO_INCREMENT,

`name` char(10) CHARSET utf8mb4 COLLATE utf8mb4_bin DEFAULT Null,

`age` int(11) DEFAULT Null,

PRIMARY Key ( `id` ),

Key `idx_name` ( `name` )

) ENGINE=InnoDB DEFAULT CHARSET=utf8mb4 COLLATE=utf8mb4_bin

1

| | | |
| --- | --- | --- |
| Insert | 30W/(1+1) | 15W |
| Delete | 30W/(1+1) | 15W |
| Update_On_id | 30W/((1+1)*2 + 0) | 7.5W |
| Update_On_name | 30W/(1+1*2) | 10W |
| Update_On_age | 30W/(1+0*2) | 30W |

TiDB int int

CREATE TABLE `t1` (

`id` varchar(11) NOT Null,

`name` char(10) CHARSET utf8mb4 COLLATE utf8mb4_bin DEFAULT Null,

`age` int(11) DEFAULT Null,

PRIMARY Key ( `id` ),

Key `idx_name` ( `name` )

) ENGINE=InnoDB DEFAULT CHARSET=utf8mb4 COLLATE=utf8mb4_bin

1 () 1

| | | |
|---|---|---|
| Insert | 30W/(1+2) | 10W |
| Delete | 30W/(1+2) | 10W |
| Update_On_id | 30W/(1+1*2) | 10W |
| Update_On_name | 30W/(1+1*2) | 10W |
| Update_On_age | 30W/(1+0*2) | 30W |

## 4.6.4

TiDB

(1) stmt-count-limit 5000

> StmtCountLimit limits the max count of statement inside a transaction.

5000 SQL statement TiDB

(2) Insert Into Select

> ERROR 1105 (HY000): BatchInsert failed with error: [try again later]: con:3877 **txn takes too much time**, start: 405023027269206017, commit: 405023312534306817

max-txn-time-use gc_life_time - 10s 590

PingCAP GitHub https://github.com/pingcap/TiDB/blob/master/config/config.toml.example#L240

> # The max time a Txn may use (in seconds) from its startTS to commitTS. # We use it to guarantee GC worker will not influence any active txn. Please make sure that this# Value is less than gc_life_time - 10s.

gc_life_time - 10s gc + TiDB Batch

## 4.6.5

Batch

- tidb_batch_insert

> : SESSION : 0 Autocommit True Batch Batch

- tidb_batch_delete

> : SESSION : 0 Autocommit True Batch Batch

- tidb_dml_batch_size

> : SESSION : 20000 / Batch tidb_batch_insert tidb_batch_delete 20k

Update limit Batch Update

Batch DBA Batch 100 TiDB

# 6.1.3

SequenceTiDB 4.0

## Snowflake

Snowflake  Twitter  ID  uid-generator  leaf uid-generator

uid-generator  64  ID

- sign 1  0 ID
- delta seconds 28  ( "2016-05-20") 28  8.7
- worker node id 22  id ID  ID  Zookeeper worker node id22  420
- sequence 13 13  8192

Snowflake

- delta seconds ,
- delta seconds ,  28  44
- delta seconds
- worker node id  500  TiDB  worker node id TiDB  3  500 / 3 = 166  worker node id  Snowflake

ID | | | | | :---- | :------ | :------ | | SEQ_NAME | varchar(128) | | | MAX_ID | bigint(20) | | | STEP | int(11) | |

ID  TiDB IDbit-reverse ID

# 6.1.4

SQL MySQL `limit` `offset`

```
begin;
update sbtest1 set pad='new_value' where id in (select id from sbtest1 order by id limit 0,10000);
commit;
begin;
update sbtest1 set pad='new_value' where id in (select id from sbtest1 order by id limit 10000,10000);
commit;
begin;
update sbtest1 set pad='new_value' where id in (select id from sbtest1 order by id limit 20000,10000);
commit;
```

SQL TiKV

200 `tmp_loan` 200

```
MySQL [demo]> desc tmp_loan;
+-------------+-------------+------+------+---------+-------+
| Field       | Type        | Null | Key  | Default | Extra |
+-------------+-------------+------+------+---------+-------+
| serialno    | int(11)     | NO   | PRI  | NULL    |       |
| name        | varchar(40) | NO   |      |         |       |
| businesssum | int(10)     | NO   |      | 0       |       |
+-------------+-------------+------+------+---------+-------+

MySQL [demo]> select count(1) from tmp_loan;
+----------+
| count(1) |
+----------+
|  1998985 |
+----------+

MySQL [demo]> select * from tmp_loan limit 10;
+-----------+-----------+-------------+
| serialno  | name      | businesssum |
+-----------+-----------+-------------+
| 200000000 |     |       10000 |
| 200000001 |       |       10000 |
| 200000002 |       |       10000 |
| 200000003 |       |       10000 |
| 200000004 |     |       10000 |
| 200000005 |       |       10000 |
| 200000006 |       |       10000 |
| 200000007 |       |       10000 |
| 200000008 |       |       10000 |
| 200000009 |       |       10000 |
+-----------+-----------+-------------+
```

`row_number()`

```
MySQL [demo]> selecct min(t.serialno) as start_key, max(t.serialno) as end_key, count(*) as page_size from ( select *
, row_number () over (order by serialno) as row_num from tmp_loan ) t group by floor((t.row_num - 1) / 50000) order b
y start_key;
+-----------+-----------+-----------+
| start_key | end_key   | page_size |
+-----------+-----------+-----------+
| 200000000 | 200050001 |     50000 |
| 200050002 | 200100007 |     50000 |
| 200100008 | 200150008 |     50000 |
| 200150009 | 200200013 |     50000 |
| 200200014 | 200250017 |     50000 |
|  ........ |.......... | ........  |
| 201900019 | 201950018 |     50000 |
| 201950019 | 201999003 |     48985 |
+-----------+-----------+-----------+
40 rows in set (1.51 sec)
```

`serialno between start_key and end_key`

```
MySQL [demo]> select serialno from tmp_loan where serialno between 200050002 and 200100007;
+-----------+
| serialno  |
+-----------+
| 200050002 |
| 200050003 |
| 200050004 |
| 200050005 |
| 200050006 |
| ......... |
+-----------+
50000 rows in set (0.070 sec)
```

```
MySQL [demo]> update tmp_loan set businesssum = 6666 where serialno between 200000000 and 200050001;
Query OK, 50000 rows affected (0.89 sec)
Rows matched: 50000  Changed: 50000  Warnings: 0

MySQL [demo]> select * from tmp_loan order by serialno limit 10;
+-----------+-----------+-------------+
| serialno  | name      | businesssum |
+-----------+-----------+-------------+
| 200000000 |     |        6666 |
| 200000001 |       |        6666 |
| 200000002 |       |        6666 |
| 200000003 |       |        6666 |
| 200000004 |     |        6666 |
| 200000005 |       |        6666 |
| 200000006 |       |        6666 |
| 200000007 |       |        6666 |
| 200000008 |       |        6666 |
| 200000009 |       |        6666 |
+-----------+-----------+-------------+
```

# 6.1.5 Hint

hint TiDB MySQL USE INDEXFORCE INDEXIGNORE INDEX TiDB Optimizer Hints MySQL 5.7 comment
/ + *TIDB_XX(t1, t2)* / TiDBhint

| **Hint** | |
|---|---|
| USE INDEX | Index Hint: Choose Index |
| FORCE INDEX | Index Hint: Choose Index |
| IGNORE INDEX | Index Hint: Ignore Index |
| /+ *TIDB_INLJ(t)* / | Join Hint: Nested Index Lookup Join |
| /+ *TIDB_HJ(t)* / | Join Hint: Hash Join |
| /+ *TIDB_SMJ(t)* / | Join Hint: Merge Join |
| /+ *MAX_EXECUTION_TIME(num)* / | Executiom Time Limit |

## 6.1.5.1 USE INDEX,FORCE INDEX,IGNORE INDEX

MySQL , USE INDEX

USE/FORCE INDEX SQL

```
mysql> explain select * from t;
+-----------------------+---------+-----------+---------------+----------------------+
| id                    | estRows | task      | access object | operator info        |
+-----------------------+---------+-----------+---------------+----------------------+
| TableReader_5         | 8193.00 | root      |               | data:TableFullScan_4 |
| └─TableFullScan_4     | 8193.00 | cop[tikv] | table:t       | keep order:false     |
+-----------------------+---------+-----------+---------------+----------------------+
2 rows in set (0.00 sec)

mysql> explain select * from t use index(idx_1);
+------------------------------+---------+-----------+------------------------+------------------+
| id                           | estRows | task      | access object          | operator info    |
+------------------------------+---------+-----------+------------------------+------------------+
| IndexLookUp_6                | 8193.00 | root      |                        |                  |
| ├─IndexFullScan_4(Build)     | 8193.00 | cop[tikv] | table:t, index:idx_1(a) | keep order:false |
| └─TableRowIDScan_5(Probe)    | 8193.00 | cop[tikv] | table:t                | keep order:false |
+------------------------------+---------+-----------+------------------------+------------------+
3 rows in set (0.00 sec)
mysql> explain select * from t force index(idx_1);
+------------------------------+---------+-----------+------------------------+------------------+
| id                           | estRows | task      | access object          | operator info    |
+------------------------------+---------+-----------+------------------------+------------------+
| IndexLookUp_6                | 8193.00 | root      |                        |                  |
| ├─IndexFullScan_4(Build)     | 8193.00 | cop[tikv] | table:t, index:idx_1(a) | keep order:false |
| └─TableRowIDScan_5(Probe)    | 8193.00 | cop[tikv] | table:t                | keep order:false |
+------------------------------+---------+-----------+------------------------+------------------+
3 rows in set (0.00 sec)
```

IGNORE INDEX SQL

```
mysql> explain select a from t where a=2;
+------------------------+---------+-----------+------------------------+-------------------------------+
| id                     | estRows | task      | access object          | operator info                 |
+------------------------+---------+-----------+------------------------+-------------------------------+
| IndexReader_6          | 1.00    | root      |                        | index:IndexRangeScan_5        |
| └─IndexRangeScan_5     | 1.00    | cop[tikv] | table:t, index:idx_1(a) | range:[2,2], keep order:false |
+------------------------+---------+-----------+------------------------+-------------------------------+
2 rows in set (0.00 sec)

mysql> explain select a from t ignore index(idx_1) where a=2 ;
+-------------------------+---------+-----------+-----------------+------------------+
| id                      | estRows | task      | access object   | operator info    |
+-------------------------+---------+-----------+-----------------+------------------+
| TableReader_7           | 1.00    | root      |                 | data:Selection_6 |
| └─Selection_6           | 1.00    | cop[tikv] | eq(test.t.a, 2) |                  |
|   └─TableFullScan_5     | 8193.00 | cop[tikv] | table:t         | keep order:false |
+-------------------------+---------+-----------+-----------------+------------------+
3 rows in set (0.00 sec)
```

MySQL , TiDB USE INDEX FORCE INDEX

USE INDEX TiDB `analyze table` USE INDEX

## 6.1.5.2 MAX_EXECUTION_TIME(N)

SELECT MAX_EXECUTION_TIME(N) N

1

```
SELECT /*+ MAX_EXECUTION_TIME(1000) */  *  FROM t1
```

`MAX_EXECUTION_TIME`

`MAX_EXECUTION_TIME` bug TiDB OLTP 5

MySQL jdbc TiDB KILL tidb-server tidb-server tidb-server KILL `MAX_EXECUTION_TIME`

## 6.1.5.3 JOIN HINT

TiDB Join Sort Merge JoinIndex Nested Loop JoinHash Join join TiDB

## 1. TIDB_SMJ(t1, t2)

```
SELECT /*+ TIDB_SMJ(t1, t2) */ * from t1t2 where t1.id = t2.id;
```

Sort Merge Join Join ,

## 2. TIDB_INLJ(t1, t2)

```
SELECT /*+ TIDB_INLJ(t1, t2) */ * from t1t2 where t1.id = t2.id;
```

Index Nested Loop Join Index Look Up Join WHERE 1 TIDB_INLJ() TIDB_INLJ(t1) t1

## 3. TIDB_HJ(t1, t2)

```
SELECT /*+ TIDB_HJ(t1, t2) */ * from t1t2 where t1.id = t2.id;
```

Hash Join t1 t2 Hash Join Inner Outer

hint / + *TIDB_STREAMAGG()* / / + *TIDB_HASHAGG()* /

Hint SQL SQL SQL

# 6.2 SQL

SQL SQL

count estRows.

## 1 Delete OOM

```
MySQL [db_stat]> explain delete from t_stat where imp_date<='20200202';
+---------------------+--------------+------+-----------------------------------------------------+
| id                  | count        | task | operator info                                       |
+---------------------+--------------+------+-----------------------------------------------------+
| TableReader_6       | 220895815.00 | root | data:Selection_5                                    |
| └─Selection_5       | 220895815.00 | cop  | le(db_stat.t_stat.imp_date, "20200202")             |
|   └─TableScan_4     | 220895815.00 | cop  | table:t_stat, range:[-inf,+inf], keep order:false   |
+---------------------+--------------+------+-----------------------------------------------------+
3 rows in set (0.00 sec)
MySQL [db_stat]> select count(*)  from t_stat where imp_date<='20200202';
+-----------+
| count(*)  |
+-----------+
| 184340473 |
+-----------+
1 row in set (17.88 sec)
```

- TiDB OOM

- imp_date IndexScan Table ScanTiDB TiKV Coprocessor

- TiKV Coprocessor CPU
- Delete TiDB TiDB

- limit N
- 3.0 Range

## 2

```
MySQL [db_stat]> explain SELECT * FROM `tbl_article_check_result` `t` WHERE (articleid = '20190925A0PYT800') ORDER BY
 checkTime desc LIMIT 100 ;
+--------------------------+----------+------+-------------------------------------------------------------------------
-------------------------------------------------------------------------------------------------------------------------
-------------------------------------------------------------------------------------------------------------------------
-------------------------------------------------------------------------+
| id                       | count    | task | operator info                                                           
                                                                          |
+--------------------------+----------+------+-------------------------------------------------------------------------
-------------------------------------------------------------------------------------------------------------------------
-------------------------------------------------------------------------------------------------------------------------
-------------------------------------------------------------------------+
| Projection_7             | 100.00   | root | db_stat.t.type, db_stat.t.articleid, db_stat.t.docid, db_stat.t.versio
n, db_stat.t.checkid, db_stat.t.checkstatus, db_stat.t.seclevel, db_stat.t.t1checkstatus, db_stat.t.t2checkstatus, db
_stat.t.mdaichannel, db_stat.t.mdaisubchannel, db_stat.t.checkuser, db_stat.t.checktime, db_stat.t.addtime, db_stat.t
.havegot, db_stat.t.checkcode                                             |
| └─Limit_12               | 100.00   | root | offset:0, count:100                                                     
                                                                          |
|   └─IndexLookUp_34       | 100.00   | root |                                                                         
                                                                          |
|     ├─IndexScan_31       | 30755.49 | cop  | table:t, index:checkTime, range:[NULL,+inf], keep order:true, desc      
                                                                          |
|     └─Selection_33       | 100.00   | cop  | eq(db_dayu_1.t.articleid, "20190925A0PYT800")                           
                                                                          |
|       └─TableScan_32     | 30755.49 | cop  | table:tbl_article_check_result, keep order:false                        
                                                                          |
+--------------------------+----------+------+-------------------------------------------------------------------------
-------------------------------------------------------------------------------------------------------------------------
-------------------------------------------------------------------------------------------------------------------------
-------------------------------------------------------------------------+
6 rows in set (0.00 sec)
```

- articleid checkTime articleid checkTime

- LIMIT 100 100 checkTime articleid checkTime articleid articleid

- Duration

- analyze table crontab analyze
- auto analyze analyze ratio
  - set global tidb_auto_analyze_ratio=0.2;
  - set global tidb_auto_analyze_start_time='00:00 +0800';
  - set global tidb_auto_analyze_end_time='06:00 +0800';
- SQL force index articleid
- 3.0 SQL create binding force index SQL
- 4.0 SQL Plan Management 1.3

## 3

```
MySQL [db_stat]> explain select * from t_like_list where person_id=1535538061143263;
+---------------------+------------+------+-------------------------------------------------------------------------------
---------+
| id                  | count      | task | operator info
         |
+---------------------+------------+------+-------------------------------------------------------------------------------
---------+
| Selection_5         | 1430690.40 | root | eq(cast(db_stat.t_like_list.person_id), 1.535538061143263e+15)
         |
| └─TableReader_7     | 1788363.00 | root | data:TableScan_6
         |
|   └─TableScan_6     | 1788363.00 | cop  | table:t_like_list, range:[-inf,+inf], keep order:false
         |
+---------------------+------------+------+-------------------------------------------------------------------------------
---------+
3 rows in set (0.00 sec)
```

- person_id IndexScan
- person_id cast
- where

```
MySQL [db_stat]> explain select * from table:t_like_list where person_id='1535538061143263';
+-------------------+-------+------+-------------------------------------------------------------------------------
------------------------------+
| id                | count | task | operator info
                              |
+-------------------+-------+------+-------------------------------------------------------------------------------
------------------------------+
| IndexLookUp_10    | 0.00  | root |
                              |
| ├─IndexScan_8     | 0.00  | cop  | table:t_like_list, index:person_id, range:["1535538061143263","153553806114
3263"], keep order:false      |
| └─TableScan_9     | 0.00  | cop  | table:t_like_list, keep order:false
                              |
+-------------------+-------+------+-------------------------------------------------------------------------------
------------------------------+
3 rows in set (0.00 sec)
```

## 4 SQL

600G TiDB TiDB Query Summary - Duration p99

TiDB KV Duration KV Request Duration 999 by store TiKV Duration

TiKV Coprocessor Overview

Coprocessor CPU

Coprocessor CPU Duration Coprocessor CPU

pt-query-digest TiDB

```
./pt-query-digest tidb_slow_query.log > result
```

TopSQL Process keys Process time Process keys SQL Process time SQL Process keys 22.09MProcess time 51s

```
# Query 26: 0.08 QPS, 0.34x concurrency, ID 0x2AA5E845384665393DC48BB36364AC51 at byte 140924321
# This item is included in the report because it matches --outliers.
# Scores: V/M = 4.20
# Time range: 2019-10-15T12:14:48 to 2019-10-15T14:45:55
# Attribute    pct   total     min     max     avg     95%  stddev  median
# ============ === ======= ======= ======= ======= ======= ======= =======
# Count          0     739
# Exec time      0   3039s   300ms     28s      4s     12s      4s      3s
# Query size     0  22.37k      31      31      31      31       0      31
# Conn ID        0 559.72k      15   7.32k  775.58   4.71k   1.32k  299.03
# Cop proc avg   0   50.76    0.04    0.14    0.07    0.09    0.01    0.07
# Cop proc max   0   50.76    0.04    0.14    0.07    0.09    0.01    0.07
# Cop proc p90   0   50.76    0.04    0.14    0.07    0.09    0.01    0.07
# Cop wait avg   0   2.30k       0   24.03    3.19    8.91    3.15    2.39
# Cop wait max   0   2.30k       0   24.03    3.19    8.91    3.15    2.39
# Cop wait p90   0   2.30k       0   24.03    3.19    8.91    3.15    2.39
# Mem max        0 699.31M 968.95k 969.37k 969.01k 961.27k       0 961.27k
# Num cop task   0     739       1       1       1       1       0       1
# Process keys   0  22.09M     157  32.17k  30.60k  31.59k   6.77k  31.59k
# Process time   0     51s    35ms   138ms    69ms    91ms    15ms    68ms
# Request coun   0     739       1       1       1       1       0       1
# Total keys     0  22.43M     197  32.88k  31.08k  31.59k   6.76k  31.59k
# Txn start ts   0 263.99E 365.80P 365.81P 365.80P   1.25P       0   1.25P
# Wait time      0   2355s     1ms     24s      3s      9s      3s      3s
# String:
# Cop proc add   [redacted].245:20171 (392/53%)... 2 more
# Cop wait add   [redacted].245:20171 (392/53%)... 2 more
# DB             [redacted]
# Digest         769ecfd1640a6a79558c26da1e5b64a2b68d65919b23...
# Is internal    false
# Stats          grp:411858... (100/13%), grp:411859... (95/12%)... 20 more
# Succ           true
```

SQL Process keys 12.68M Process time 142353s

```
# Query 4: 0.36 QPS, 14.84x concurrency, ID 0xF0ECDD453DA544E79C7D0E42506FF4BE at byte 163086266
# This item is included in the report because it matches --limit.
# Scores: V/M = 13.91
# Time range: 2019-10-15T12:13:52 to 2019-10-15T15:20:49
# Attribute    pct   total     min     max     avg     95%  stddev  median
# ============ === ======= ======= ======= ======= ======= ======= =======
# Count          1    3999
# Exec time     11 166406s      3s    170s     42s     80s     24s     39s
# Query size     1 515.50k     132     132     132     132       0     132
# Conn ID        0   2.22M      10   7.32k  583.33   2.06k   1.03k  258.32
# Cop proc avg  32   2.53k    0.17    1.34    0.65    0.99    0.17    0.61
# Cop proc max  35   7.15k    0.45    3.60    1.83    2.76    0.49    1.70
# Cop proc p90  34   6.44k    0.34    3.32    1.65    2.63    0.46    1.62
# Cop wait avg   1   8.10k    0.00    8.48    2.07    4.50    1.41    1.96
# Cop wait max   3  30.67k    0.00   36.06    7.85   16.81    5.21    6.98
# Cop wait p90   1  18.28k    0.00   23.68    4.68    9.83    3.04    4.50
# Mem max       39 119.23G  30.27M  30.54M  30.53M  29.99M       0  29.99M
# Num cop task  18 214.79k      51      55   55.00   54.21    0.08   54.21
# Process keys   0  12.68M   3.18k   3.36k   3.25k   3.19k   57.63   3.19k
# Process time  61 142353s      9s     74s     36s     54s     10s     33s
# Request coun  18 214.79k      51      55   55.00   54.21    0.08   54.21
# Total keys     0  13.00M   3.23k   3.50k   3.33k   3.35k   69.99   3.19k
# Txn start ts   1   1.40Z 365.80P 365.81P 365.80P   1.25P       0   1.25P
# Wait time     24 456039s     6ms    466s    114s    246s     78s    107s
# String:
# Cop proc add          .245:20171 (1814/45%)... 2 more
# Cop wait add          .245:20171 (1835/45%)... 2 more
# DB
# Digest       473bf876de8bb5210bf4b300a6b3d94b0c0210ba1a1e...
# Is internal  false
# Stats        tpl:411850... (202/5%), tpl:411850... (192/4%)... 196 more
# Succ         true
```

Process time SQL 3 slow query

- SQL1

```
select a.a_id, a.b_id,uqm.p_id from a join hsq on a.b_id=hsq.id join uqm on a.a_id=uqm.id;
```

```
id  count   task    operator info   execution info  memory
Projection_9    1878.75 root
time:1m29.290313266s, loops:69, rows:69176  N/A
└IndexJoin_13  1878.75 root    inner join, inner:TableReader_12, outer key:                , inner
key:                  time:1m29.290100131s, loops:69, rows:69176  22.52175521850586 MB
  ├IndexJoin_31    1878.75 root    inner join, inner:IndexLookUp_30, outer key:                inner
  key:                  time:1m11.787661278s, loops:422, rows:429136    7.81768798828125 MB
  │ ├TableReader_44    1503.00 root    data:TableScan_43   time:1.963267ms, loops:3, rows:1503 16.3544921875 KB
  │ │ └TableScan_43    1503.00 cop table:tpl, range:[0,+inf], keep order:false time:1ms, loops:6, rows:1503    N/A
  │ └IndexLookUp_30    284.10  root        time:1m35.454370598s, loops:422, rows:429136    100.359375 KB
  │   ├IndexScan_28    284.10  cop table:        , index:        , range: decided by [eq(                ,
                    )], keep order:false   proc max:470ms, min:36ms, p80:470ms, p95:470ms, rows:429136, iters:428, tasks:2 N/A
  │   └TableScan_29    284.10  cop table:        , keep order:false proc max:1.695s, min:30ms, p80:1.291s, p95:1.525s, rows:429136,
  iters:543, tasks:27 N/A
  └TableReader_12  1.00    root    data:TableScan_11   time:1m9.184965119s, loops:100, rows:64302  N/A
    └TableScan_11  1.00    cop table:    , range: decided by [                , keep order:false   proc max:702ms,
    min:4ms, p80:490ms, p95:627ms, rows:64302, iters:165, tasks:25  N/A
```

- SQL2

```
select distinct g.abc, g.def, g.ghi, h.abcd, hi.jq   from ggg g left join ggg_host gh on g.id = gh.ggg_id left j
oin host h on gh.a_id = h.id left join a_jq hi on h.id = hi.hid   where h.abcd is not null and h.abcd  <>  '' an
d hi.jq is not null and hi.jq  <>  '';
```

```
id  count   task    operator info   execution info  memory
HashAgg_13  80296.47    root    group by:dbl.g.def, dbl.g.abc, dbl.g.ghi, dbl.h.abcd, dbl.hi.jq, funcs:firstrow(dbl.g.abc),
firstrow(dbl.g.def), firstrow(dbl.g.ghi), firstrow(dbl.h.abcd), firstrow(dbl.hi.jq) time:8.646954728s, loops:347, rows:354274   N/A
└IndexJoin_18  80296.47    root    inner join, inner:IndexReader_17, outer key:dbl.h.id, inner key:dbl.hi.hid  time:7.613316688s,
loops:507, rows:517734   257.38256072998047 MB
  ├IndexJoin_47    41156.25    root    inner join, inner:TableReader_46, outer key:dbl.gh.a_id, inner key:dbl.h.id time:2.76087231s,
  loops:656, rows:669536    438.8576126098633 MB
  │ ├IndexJoin_54  41156.25    root    inner join, inner:IndexReader_53, outer key:dbl.g.id, inner key:dbl.gh.ggg_id
  time:1.69100157s, loops:1189, rows:1215334  27.39978790283203 MB
  │ │ ├TableReader_66  32925.00    root    data:TableScan_65   time:75.325365ms, loops:35, rows:32925  4.20347785949707 MB
  │ │ │ └TableScan_65  32925.00    cop table:g, range:[0,+inf], keep order:false   time:52ms, loops:37, rows:32925 N/A
  │ │ └IndexReader_53  0.99    root    index:Selection_52  time:1.898590556s, loops:1202, rows:1215334 15.298088073730469 MB
  │ │   └Selection_52  0.99    cop not(isnull(dbl.gh.ggg_id))  proc max:664ms, min:29ms, p80:317ms, p95:664ms, rows:1215334,
  iters:1218, tasks:10  N/A
  │ │     └IndexScan_51    0.99    cop table:gh, index:ggg_id, a_id, range: decided by [eq(dbl.gh.ggg_id, dbl.g.id)
  not(isnull(dbl.gh.a_id))], keep order:false    proc max:640ms, min:29ms, p80:316ms, p95:640ms, rows:1215334, iters:1218, tasks:10  N/A
  │ └TableReader_46    0.80    root    data:Selection_45   time:3.441797722s, loops:732, rows:666902   N/A
  │   └Selection_45    0.80    cop ne(dbl.h.abcd, ""), not(isnull(dbl.h.id)), not(isnull(dbl.h.abcd))  proc max:206ms, min:0s,
  p80:10ms, p95:30ms, rows:666902, iters:4012, tasks:1487 N/A
  │     └TableScan_44  1.00    cop table:h, range: decided by [dbl.gh.a_id], keep order:false  proc max:204ms, min:0s, p80:10ms,
  p95:30ms, rows:668753, iters:4012, tasks:1487 N/A
  └IndexReader_17  1.20    root    index:Selection_16  time:20.824781527s, loops:545, rows:510094  144.6767578125 KB
    └Selection_16  1.20    cop not(isnull(dbl.hi.hid)) proc max:876ms, min:4ms, p80:728ms, p95:789ms, rows:510094, iters:781, tasks:93
    N/A
      └IndexScan_15    1.20    cop table:hi, index:hid, jq, source, status, range: decided by [eq(dbl.hi.hid, dbl.h.id)
      not(isnull(dbl.hi.jq)) ne(dbl.hi.jq, )], keep order:false  proc max:875ms, min:4ms, p80:728ms, p95:789ms, rows:510094, iters:781,
      tasks:93 N/A
```

- SQL3

```
select tb1.mt, tb2.name from tb2 left join tb1 on tb2.mtId=tb1.id where tb2.type=0 and (tb1.mt is not null and t
b1.mt != '') and (tb2.name is not null or tb2.name != '');
```

```
id  count   task    operator info   execution info  memory
Projection_6    121393.07   root    dbl.tbl.mt, dbl.tb2.name    time:713.605177ms, loops:14, rows:10753 N/A
└HashLeftJoin_11   121393.07   root    inner join, inner:TableReader_26, equal:[eq(dbl.tb2.mtid, dbl.tbl.id)]  time:713.544424ms,
loops:14, rows:10753 2.650096893310547 MB
  ├IndexLookUp_23  121393.07   root        time:621.192752ms, loops:120, rows:121269   2.6519317626953125 MB
  │ ├IndexScan_20  121393.07   cop table:tb2, index:type, range:[0,0], keep order:false    time:69ms, loops:123, rows:121269   N/A
  │ └Selection_22  121393.07   cop or(not(isnull(dbl.tb2.name)), ne(dbl.tb2.name, "")) proc max:390ms, min:9ms, p80:368ms, p95:390ms,
  rows:121269, iters:166, tasks:10 N/A
  │   └TableScan_21    121393.07   cop table:tb2, keep order:false proc max:387ms, min:8ms, p80:366ms, p95:387ms, rows:121269,
  iters:166, tasks:10 N/A
  └TableReader_26  41200.00    root    data:Selection_25   time:171.796012ms, loops:42, rows:41200 2.2558584213256836 MB
    └Selection_25  41200.00    cop ne(dbl.tbl.mt, ""), not(isnull(dbl.tbl.mt)) proc max:156ms, min:11ms, p80:156ms, p95:156ms,
    rows:41200, iters:53, tasks:3   N/A
      └TableScan_24    41200.00    cop table:tbl, range:[-inf,+inf], keep order:false  proc max:152ms, min:11ms, p80:152ms, p95:152ms,
      rows:41200, iters:53, tasks:3   N/A
```

TiDB TiKV

TiKV [slow-query] region

```
more tikv.log.2019-10-16-06\:28\:13 |grep slow-query |awk -F ']' '{print $1}' | awk  '{print $6}' | sort | uniq -c |
sort –n
```

3 region

```
 73 29452
140 33324
757 66625
```

region region region [slow-query] table_id start_ts TiDB table_id 1318start_ts 411837294180565013 SQL

```
more tidb-2019-10-14T16-40-51.728.log | grep '"/[1318/]"' |grep 411837294180565013
```

region split region 66625 x.x.x.x pd

```
pd-ctl –u http://x.x.x.x:2379 operator add split-region 66625
```

PD

```
[2019/10/16 18:22:56.223 +08:00] [INFO] [operator_controller.go:99] ["operator finish"] [region-id=30796] [operator="
\"admin-split-region (kind:admin, region:66625(1668,3), createAt:2019-10-16 18:22:55.888064898 +0800 CST m=+110918.82
3762963, startAt:2019-10-16 18:22:55.888223469 +0800 CST m=+110918.823921524, currentStep:1, steps:[split region with
 policy SCAN]) finished\""]
```

region region slow-query

```
more tikv.log.2019-10-16-06\:28\:13 |grep slow-query  | grep 66625
```

66625 region region region Query Summary - Duration

Duration 18:55 Duration

tikv region leader

```
pd-ctl –u http://x.x.x.x:2379 operator add transfer-leader 1 2 // region1  leader  store2
```

leader TiKV Duration TiKV Duration

region split Duration

SQL TiDB TiKV region region TiKV TiKV SQL 7.2

## 5 SQL

- SQL

- SQL

```
select count(*)
from   tods.bus_jijin_trade_record a, tods.bus_jijin_info b
where   a.fund_code=b.fund_code  and a.type in   ('PURCHASE','APPLY')
and   a.status='CANCEL_SUCCESS' and a.pay_confirm_status = 1
and a.cancel_app_no   is not null and a.id >=    177045000
and a.updated_at   > date_sub(now(), interval 48 hour) ;

 1  3.7s
mysql> select   count(*)
    -> from tods.bus_jijin_trade_record a,   tods.bus_jijin_info b
    -> where a.fund_code=b.fund_code  and a.type in ('PURCHASE','APPLY')
    -> and a.status='CANCEL_SUCCESS' and   a.pay_confirm_status = 1
    -> and a.cancel_app_no is not null and   a.id >=  177045000
    -> and a.updated_at >   date_sub(now(), interval 48 hour) ;
+----------+
| count(*) |
+----------+
|      708 |
+----------+
1   row in set (1 min 3.77 sec)
```

-

| | | |
|---|---|---|
| bus_jijin_trade_record | 176384036 | PRIMARY KEY ( `ID` ) KEY `idx_bus_jijin_trade_record_upt` ( `UPDATED_AT` ) |
| bus_jijin_info | 6442 | PRIMARY KEY ( `ID` ) |

-

```
mysql> explain
    -> select count(*)
    -> from tods.bus_jijin_trade_record a,   tods.bus_jijin_info b
    -> where a.fund_code=b.fund_code  and a.type in ('PURCHASE','APPLY')
    -> and a.status='CANCEL_SUCCESS' and   a.pay_confirm_status = 1
    -> and a.cancel_app_no is not null and   a.id >=  177045000
    -> and a.updated_at >   date_sub(now(), interval 48 hour) ;
+---------------------------+--------------+------+-------------------------------------------------------------
-----------------------------------------------------------------------------------------------+
| id                        | count        | task | operator info
                                                                                                |
+---------------------------+--------------+------+-------------------------------------------------------------
-----------------------------------------------------------------------------------------------+
| StreamAgg_13              | 1.00         | root | funcs:count(1)
                                                                                                |
| └─HashRightJoin_27        | 421.12       | root | inner join, inner:TableReader_18, equal:[eq(a.fund_code, b.fund_
code)]                                                                                          |
|   ├─TableReader_18        | 421.12       | root | data:Selection_17
                                                                                                |
|   | └─Selection_17        | 421.12       | cop  | eq(a.pay_confirm_status, 1), eq(a.status, "CANCEL_SUCCESS"), gt(
a.updated_at, 2020-03-03 22:31:08), in(a.type, "PURCHASE", "APPLY"), not(isnull(a.cancel_app_no)) |
|   |   └─TableScan_16      | 145920790.55 | cop  | table:a, range:[177045000,+inf], keep order:false
                                                                                                |
|   └─TableReader_37        | 6442.00      | root | data:TableScan_36
                                                                                                |
|     └─TableScan_36        | 6442.00      | cop  | table:b, range:[-inf,+inf], keep order:false
                                                                                                |
+---------------------------+--------------+------+-------------------------------------------------------------
-----------------------------------------------------------------------------------------------+

TableScan_16TableScan_36 TiKV  a  b  TableScan_16  1.46
Selection_17 a  where
TableReader_37  b  TiDB
TableReader_18 coprocessor  a  TiDB
HashRightJoin_27 TableReader_37  TableReader_18  hash join
StreamAgg_13
```

a (bus_jijin_trade_record) id >= 177045000 updated_at > date_sub(now(), interval 48 hour) TiDB

```
mysql> SELECT COUNT(*) FROM tods.bus_jijin_trade_record WHERE id >= 177045000 ;
+-----------+
| COUNT(*)  |
+-----------+
| 145917327 |
+-----------+
1 row in set (16.86   sec)

mysql> SELECT COUNT(*) FROM tods.bus_jijin_trade_record WHERE updated_at > date_sub(now(), interval 48 hour)  ;
+-----------+
|  COUNT(*) |
+-----------+
|    713682 |
+-----------+
```

bus_jijin_trade_record  1.7  updated_at

hint 6.27  **63s  6.3s 10**

```
mysql> select   count(*)
    -> from tods.bus_jijin_trade_record a   use index(idx_bus_jijin_trade_record_upt), tods.bus_jijin_info b
    -> where a.fund_code=b.fund_code  and a.type in ('PURCHASE','APPLY')
    -> and a.status='CANCEL_SUCCESS' and   a.pay_confirm_status = 1
    -> and a.cancel_app_no is not null and   a.id >=  177045000
    -> and a.updated_at >   date_sub(now(), interval 48 hour) ;
+----------+
| count(*) |
+----------+
|      709 |
+----------+
1 row in set (6.27   sec)
```

hint

```
mysql> explain
    -> select count(*)
    -> from tods.bus_jijin_trade_record a   use index(idx_bus_jijin_trade_record_upt), tods.bus_jijin_info b
    -> where a.fund_code=b.fund_code  and a.type in ('PURCHASE','APPLY')
    -> and a.status='CANCEL_SUCCESS' and   a.pay_confirm_status = 1
    -> and a.cancel_app_no is not null and   a.id >=  177045000
    -> and a.updated_at >   date_sub(now(), interval 48 hour) ;
+------------------------------+--------------+------+-------------------------------------------------------------
-------------------------------------------------------------+
| id                           | count        | task | operator info
                                                          |
+------------------------------+--------------+------+-------------------------------------------------------------
-------------------------------------------------------------+
| StreamAgg_13                 | 1.00         | root | funcs:count(1)
                                                          |
| └─HashRightJoin_24           | 421.12       | root | inner join, inner:IndexLookUp_20, equal:[eq(a.fund_code, b.fun
d_code)]                                                  |
|   ├─IndexLookUp_20           | 421.12       | root |
                                                          |
|   │ ├─Selection_18           | 146027634.83 | cop  | ge(a.id, 177045000)
                                                          |
|   │ │   └─IndexScan_16       | 176388219.00 | cop  | table:a, index:UPDATED_AT, range:(2020-03-03 23:05:30,+inf], k
eep order:false                                           |
|   │ └─Selection_19           | 421.12       | cop  | eq(a.pay_confirm_status, 1), eq(a.status, "CANCEL_SUCCESS"), i
n(a.type, "PURCHASE", "APPLY"), not(isnull(a.cancel_app_no)) |
|   │   └─TableScan_17         | 146027634.83 | cop  |   table:bus_jijin_trade_record, keep order:false
                                                          |
|   └─TableReader_31           | 6442.00      | root | data:TableScan_30
                                                          |
|     └─TableScan_30           | 6442.00      | cop  | table:b, range:[-inf,+inf], keep order:false
                                                          |
+------------------------------+--------------+------+-------------------------------------------------------------
-------------------------------------------------------------+
```

hint updated_at 176388219

bus_jijin_trade_record

```
mysql> show   stats_meta where table_name like 'bus_jijin_trade_record' and db_name like   'tods';
+---------+------------------------+---------------------+--------------+-----------+
| Db_name | Table_name             | Update_time         | Modify_count | Row_count |
+---------+------------------------+---------------------+--------------+-----------+
| tods    | bus_jijin_trade_record | 2020-03-05 22:04:21 |     10652939 | 176381997 |
+---------+------------------------+---------------------+--------------+-----------+

mysql> show   stats_healthy  where table_name like   'bus_jijin_trade_record' and db_name like 'tods';
+---------+------------------------+---------+
| Db_name | Table_name             | Healthy |
+---------+------------------------+---------+
| tods    | bus_jijin_trade_record |      93 |
+---------+------------------------+---------+
```

bus_jijin_trade_record 176381997 10652939(176381997-10652939)/176381997 *100=93

- 

```
mysql> set   tidb_build_stats_concurrency=10;
Query OK, 0 rows   affected (0.00 sec)

#
mysql> analyze   table tods.bus_jijin_trade_record;
Query OK, 0 rows   affected (3 min 48.74 sec)
```

- hint

```
mysql> explain   select count(*)
  -> from tods.bus_jijin_trade_record a,   tods.bus_jijin_info b
  -> where a.fund_code=b.fund_code  and a.type in ('PURCHASE','APPLY')
  -> and a.status='CANCEL_SUCCESS' and   a.pay_confirm_status = 1
  -> and a.cancel_app_no is not null and   a.id >=  177045000
  -> and a.updated_at >   date_sub(now(), interval 48 hour) ;;
+-----------------------------+-----------+------+-------------------------------------------------------------
-------------------------------------------------------------+
| id                          | count     | task | operator info
                                                              |
+-----------------------------+-----------+------+-------------------------------------------------------------
-------------------------------------------------------------+
| StreamAgg_13                | 1.00      | root | funcs:count(1)
                                                              |
| └─HashRightJoin_27          | 1.99      | root | inner join, inner:IndexLookUp_23, equal:[eq(a.fund_code, b.f
und_code)]                                                    |
|   ├─IndexLookUp_23          | 1.99      | root |
                                                              |
|   | ├─Selection_21          | 626859.65 | cop  | ge(a.id, 177045000)
                                                              |
|   | |   └─IndexScan_19      | 757743.08 | cop  | table:a, index:UPDATED_AT, range:(2020-03-03 23:28:14,+inf],
 keep order:false                                             |
|   | └─Selection_22          | 1.99      | cop  | eq(a.pay_confirm_status, 1), eq(a.status, "CANCEL_SUCCESS"),
 in(a.type, "PURCHASE", "APPLY"), not(isnull(a.cancel_app_no)) |
|   |   └─TableScan_20        | 626859.65 | cop  | table:bus_jijin_trade_record, keep order:false
                                                              |
|   └─TableReader_37          | 6442.00   | root | data:TableScan_36
                                                              |
|     └─TableScan_36          | 6442.00   | cop  | table:b, range:[-inf,+inf], keep order:false
                                                              |
+-----------------------------+-----------+------+-------------------------------------------------------------
-------------------------------------------------------------+
9 rows in set (0.00   sec)
```

**hint 757743**

**1.69s**

```
mysql> select   count(*)
    -> from tods.bus_jijin_trade_record a,   tods.bus_jijin_info b
    -> where a.fund_code=b.fund_code  and a.type in ('PURCHASE','APPLY')
    -> and a.status='CANCEL_SUCCESS' and   a.pay_confirm_status = 1
    -> and a.cancel_app_no is not null and   a.id >=  177045000
    -> and a.updated_at >   date_sub(now(), interval 48 hour) ;
+----------+
| count(*) |
+----------+
|      712 |
+----------+
1 row in set (1.69   sec)
```

SQL

712

# 6.3 TiDB + TiSpark

TiSpark PingCAP OLAP Spark TiKV TiDB TiSpark Spark

## 6.3.1 TiSpark

TiSpark Spark SQL TiDB TiKV OLAP TiSpark

- TiSpark Spark Catalyst , Spark TiKV
- Spark SQL TiDB
- TiSpark+TiDB ETL
- TiSpark TiDB Spark TiSpark ETL TiKV

## 6.3.2

### (1) TiSpark

TiSpark 2.1.8 Spark 2.3.0+ Spark 2.4.0+ TiDB-2.x TiDB-3.x TiSpark GitHub

### (2) Spark

TiDB TiSpark Spark Hadoop

## (3) JDK

TiSpark JDK 1.8+ Scala 2.11Spark2.0+ Scala

---

# 6.3.3 TiSpark

TiSpark YARNMesosStandalone Spark Saprk Standalone Saprk Standalone TiSpark

## (1) spark-env.sh

```
SPARK_EXECUTOR_MEMORY=10g
SPARK_EXECUTOR_CORES=5
SPARK_WORKER_MEMORY=40g
SPARK_WORKER_CORES=20
```

## (2) spark-defaults.conf

```
spark.sql.extensions  org.apache.spark.sql.TiExtensions
spark.tispark.pd.addresses  127.0.0.1:2379
```

PD : PD

## (3) TiSpark

TiSpark Spark Spark --jars TiSpark :

sh spark-shell --jars $TISPARK_FOLDER/tispark-${name_with_version}.jar

TiSpark TiSpark jar Spark jars Spark

${SPARK_HOME}/jars

## (4) TiSpark

Spark Master

```
cd ${SPARK_HOME}
./sbin/start-all.sh
```

master slave log log http://spark-master-hostname:8080 Spark-Master web

---

# 6.3.4

TiSpark Spark-Shell Spark-Submit OLAP

## (1) Spark-Shell

TiSpark 2.0 Spark-Shell Spark SQL TiDB

```
spark.sql("use test")
spark.sql("select count(*) from user").show
```

TiSpark 2.0

```
import org.apache.spark.sql.TiContext
val ti = new TiContext(spark, List("127.0.0.1:2379")
ti.tidbMapDatabase("test")
```

Spark SQL 2.0 TiSpark

# (2) Spark-Submit

Spark-Shell Spark-Submit TiSpark

Maven POM Spark TiSpark Spark Provided

```
<dependencies>
    <dependency>
      <groupId>com.pingcap.tispark</groupId>
      <artifactId>tispark-core</artifactId>
      <version>2.1.8-spark_${spark.version}</version>
      <scope>provided<scope>
    </dependency>

    <dependency>
      <groupId>org.apache.spark</groupId>
      <artifactId>spark-core_2.11</artifactId>
      <version>${spark.version}</version>
      <scope>provided<scope>
    </dependency>

    <dependency>
      <groupId>org.apache.spark</groupId>
      <artifactId>spark-sql_2.11</artifactId>
      <version>${spark.version}</version>
      <scope>provided<scope>
    </dependency>
</dependencies>
```

SparkSession Spark API ScalaPythonJava Java

```
SparkSession sc = SparkSession
      .builder()
      .appName("TiSpark example")
      .master("local")
      .config("spark.sql.extensions","org.apache.spark.sql.TiExtensions")
      .config("spark.tispark.pd.addresses", "127.0.0.1:2379")
      .getOrCreate();
```

TiSpark Spark master TiSpark

TiSpark TiDB Spark JDBC Java

```
sc.read().schema(getStructType())
         .option("delimiter",true)
         .option("header",true)
         .csv(filePath)
         .withColumn("input_time", functions.current_timestamp())
         .repartition(100)
         .write().mode(SaveMode.Append)
         .jdbc(url,tableName,connProperties);


public StructType getStructType(){
        List<StructField> fields=new ArrayList<>();
        StructField transferAccount = DataTypes.createStructField("transferAccount",DataTypes.StringType,false);
        StructField receiveAccount = DataTypes.createStructField("receiveAccount",DataTypes.StringType,false);
        StructField amount = DataTypes.createStructField("amount",DataTypes.createDecimalType(10,2),false);
        fields.add(transferAccount);
        fields.add(receiveAccount);
        fields.add(amount);
        return DataTypes.createStructType(fields);
}
```

TiDB

1. Spark repartition Spark
2. TiDB rewriteBatchedStatements True JDBCOptions.JDBC_BATCH_INSERT_SIZE 150
3. isolationLevel NONE

Java

```
sc.sqlContext()
  .udf()
  .register("convert",newConvertUDF(),DataTypes.createDecimalType(10,2));
sc.sql("select transferAccount,receiveAccount,convert(amount) from tableName where receiveAccount='0001'");
```

0001 convert UDF Job Spark SQL Spark SQL UDF UDAF SQL TiSpark SQL
delete

Spark-Submit Spark

```
cd ${SPARK_HOME}
./bin/spark-submit \
--class Analyze \
--master spark://127.0.0.1:7077 \
/home/tispark/TiSparkExample.jar
```

Spark-Submit Spark

# 6.3.5

TiDB TiSpark TiSpark TiSpark Spark Spark TiSpark TiSpark Spark

TiSpark

Spark-Submit Oozie Azkaban

Spark API Spark Spark API

# 6.4

DELETE Range DDL

# 6.4.1 TiDB

TiDB 2.1 3.0 4.0 Bug

## 6.4.1.1

Range Hash MySQL List Key

Range Range VALUES LESS THAN Range

Hash Hash Hash CREATE TABLE PARTITION BY HASH (expr) PARTITIONS num expr num

## 6.4.1.2

### 1.

Range

```
CREATE TABLE employees_attendance  (
    id INT NOT NULL AUTO_INCREMENT,
    uid INT NOT NULL,
    name VARCHAR(25) NOT NULL,
    login_date date NOT NULL,
    create_time timestamp NOT NULL COMMENT '',
    type tinyint NOT NULL DEFAULT '0' COMMENT '0:1:',
    PRIMARY KEY (`id`,`login_date`),
    UNIQUE KEY `idx_attendance` (`uid`,`login_date`,`type`)
)
PARTITION BY RANGE COLUMNS(login_date)  (
    PARTITION p20200306 VALUES LESS THAN ('20200307'),
    PARTITION p20200307 VALUES LESS THAN ('20200308'),
    PARTITION pmax VALUES LESS THAN MAXVALUE
);
```

login_date

```
> ERROR 1503 (HY000): A (PRIMARY KEY/UNIQUE INDEX) must include all columns in the table's partitioning function
```

### 2.

TiDB Hash Range

Load Data load

```
load local data infile "xxx" into t partition (p1);
```

## 6.4.1.3 TiDB 4.0

TiDB 4.0 Bug

- Bug
- `INFORMATION_SCHEMA.PARTITION`
- 
  - 
  - Range Hash

- Range Partition Expression Expression int Partition Constant Propagate Constant Propagate Pattern Expr Range Partition
- 4.0 Hash Partition Range Partition Hash Partition Range Partition Hash Partition PointGet Hash Partition `partition by hash(id)` id PointGet Hash Partition Hash Partition

# 6.4.2 TiDB

()

- Range TiDB 4.0 DELETE DDL SST
- Hash Hash
- SQL
-
-
  - /TiDB Range 3
  - Range Log
  - BIGINT UID Hash UID Hash Hash

# 6.4.3 TiDB

- DELETE TRUNCATE

  `ALTER TABLE employees_attendance TRUNCATE PARTITION p20200306;`

- TiDB SQL SQL SQL // SQL

  `ALTER TABLE employees_attendance ANALYZE PARTITION p20200306;`

- DBA TiDB UNIX_TIMESTAMP

  `ALTER TABLE ADD PARTITION p20200306 VALUES LESS THAN (UNIX_TIMESTAMP('2020-03-07'))`

  TiDB

- Range MAXVALUE Data Maintance
- Hash Hash Range Hash
- ( TiDB ) UPDATE DROP

# 6.4.4 TiDB

1. TiDB 4.0 Fixed Bug GA

   - 
   - Table Partition

     ```
     create table t (a int) partition by hash(a) partitions 4;
     begin
     insert into t values (0),(1);
     select * from t where a>0;
     +---+
     | a |
     +---+
     | 1 |
     | 0 | -- Bug: filter is a>0
     +---+
     ```

   - INSERT … ON DUPLICATE Table Partition

     ```
     create table t1 (a int,b int,primary key(a,b))
         partition by range(a)
         (partition p0 values less than (100),
          partition p1 values less than (1000)
         );
     insert into t1 set a=1,b=1;
     insert into t1 set a=1,b=1 on duplicate key update a=1,b=1;
     ERROR 1105:can not be duplicated row, due to old row not found. handle 1 not found
     ```

   - Bug
   - LIMIT TiDB Server OOM Kill
   - OR Partition Partition Column CheckScalarFunction OR Partition Column TiDB

# 6.5 TiDB

## 6.5.1

2014 SAN NAS 1PB 2018 3 2017 180 100

180 OracleDB2MySQLGBASE 8aMongodbHIVEHBASE 20

## 6.5.2

5

PB

•

- 

- ;
- 

## 6.5.3

OracleMySQLOracle MySQL

(1) ACID ACID

(2)

(3)

(4) OLTP OLAP PB OLTP OLAP OLTP/OLAP

(5) MySQL

TiDB

(1)

(2)

(3)

MySQL  Oracle MySQL

TiDB

## 6.5.4

TiDB

# 6.6 TiDB HBaseESDruid

TiDB TiDB TiDB HbaseESDruid

## 6.6.1. ES TiDB

ES TiDB Kettle tableinputElasticsearch Query

ES `bmsshakehandsinfo_202003` TiDB `Temp_ETL_Handshake`

### 1. ES

1 ES SQL ES SQL Kettle 2

**1**

**2**

### 2. TiDB

TiDB Kettle `tableout`

#### 2.1

Kettle TiDB Kettle MySQL 3

**3**

### 2.2 TiDB

TiDB 4

- 
  1. TiDB 60-100.
  2. TiDB
- 
  1. 
  2. Kettle /, TiDB on duplicate

**4**

## 3.

Kettle ES TiDB 5 60 60 TiDB

**5**

Kettle 6

**6**

Kettle ES TiDB

## 6.6.2 Hbase TiDB

Hbase TiDB Kettle HbaseInputTableOutPut TiDB TableOutPut ES TiDB

Kettle HBase input , 7, Hbase mapping

7

8

## 6.6.3 Druid TiDB

Druid TiDB Druid TableOutPut TiDB TableOutPut ES TiDB Druid Druid SQL

Druid Query
步骤名称
Druid Query
Druid URL
Druid_DruidPro
Druid Query SQL
select <values> from <table name> where <conditions>
Help
确定(O)
预览(P)
取消(C)

**9**

# 6.7 TiDB

TiDB HTAP TiDB Grafana Saiku

## 6.7.1. TiDB Grafana

Grafana MySQL TiDB

**1**

1 Grafana SQL Grafana

```
1. Grafana  TiDB ,

2. Grafana
```

## 6.7.2 TiDB Saiku

Saiku Web OLAP TiDB + Saiku BI TiDB

```

    Saiku

    TiDB :TiDB  Saiku  Saiku  SQL  TiDB
```

### 6.7.2.1. Schema

Saiku Schema TiDB Schema Schema

```
▼<Schema name="[illegible]">
  ▼<Cube name="[illegible]" caption="[illegible]" cache="true" enabled="true">
    <Table name="[illegible]" alias=""/>
    <!-- 001充电日期-年（字段:RYear） -->
  ▼<Dimension type="StandardDimension" name="001充电日期-年" foreignKey="bizdate">
    ▼<Hierarchy name="" hasAll="true" primaryKey="tday" allLevelName="全部" allMemberCaption="全部">
      <Table name="kms_dt"> </Table>
      <Level name="充电日期-年" column="tyear" type="String" uniqueMembers="true" levelType="Regular"> </Level>
    </Hierarchy>
  </Dimension>
  <!-- 002充电日期-月（字段:RYearMonth）-->
  ▼<Dimension type="StandardDimension" name="002充电日期-月" foreignKey="bizdate">
    ▼<Hierarchy name="" hasAll="true" primaryKey="tday" allLevelName="全部" allMemberCaption="全部">
      <Table name="kms_dt"> </Table>
      <Level name="充电日期-月" column="ymonth" type="String" uniqueMembers="true" levelType="Regular"> </Level>
    </Hierarchy>
  </Dimension>
  ▼<!--
      003充电日期-周（字段:周描述）先把周注释掉，重新修改去除UPPER()逻辑后，再显示该维度。(通过修改sensitive配置，已成功去除Upper)
  -->
  ▼<Dimension type="StandardDimension" name="003充电日期-周" foreignKey="bizdate">
    ▼<Hierarchy name="" hasAll="true" primaryKey="tday" allLevelName="全部" allMemberCaption="全部">
      <Table name="kms_dt"> </Table>
      <Level name="周" column="seqdesc" type="String" uniqueMembers="true" levelType="Regular"> </Level>
    </Hierarchy>
  </Dimension>
  <!-- 004充电日期-日（字段:RBizDate） -->
  ▼<Dimension type="StandardDimension" name="004充电日期-日" foreignKey="bizdate">
    ▼<Hierarchy name="" hasAll="true" primaryKey="tday" allLevelName="全部" allMemberCaption="全部">
      <Table name="kms_dt"> </Table>
      <Level name="充电日期-日" column="tday" type="String" uniqueMembers="true" levelType="Regular"> </Level>
    </Hierarchy>
  </Dimension>
  <!-- 005启动时段(字段:DHour) -->
  ▼<Dimension type="StandardDimension" name="005启动时段">
    ▼<Hierarchy name="" hasAll="true" allLevelName="全部" allMemberCaption="全部">
      <Level name="启动时段" column="dhour" type="String" uniqueMembers="true" levelType="Regular"> </Level>
    </Hierarchy>
  </Dimension>
  <!-- 011省 （字段:省名称）-->
```

**2**

Schema , kms_dt tday bizdate .

```
:
 Schema , TiDB , Schema  Saiku .
```

# 6.7.2.2 TiDB

Saiku 1-3 URL: TiDB Schema: schema jdbcdriver TiDB MySQL MyS
Driver:com.mysql.jdbc.Drive TiDB

**3**

## 2.3

Saiku ,,.

**4**

```
1. Saiku

2. Saiku SQL SQL Saiku Mondrian TiDB TiDb
```

# 7

TiDB 7.1 oncall-map 7.27.37.4 3


- 7.1 Oncall
- 7.2
- 7.3 TiKV is busy
- 7.4 TiDB OOM
- 7.5 TiKV

# 7.1 Oncall

## 1. TiDB

TiDB TiDB FAQ askTUG PingCAP

PingCAP diagnose-map 7

## 2.

https://github.com/pingcap/tidb-map/blob/master/maps/diagnose-map.png TiDB png markdown https://github.com/pingcap/tidb-map/blob/master/maps/diagnose-map.md

## 3.

TiDB TiKV OOM PD latency region is unavailable 1.1.1 4

ONCALL-958 https://github.com/pingcap/tidb-map/tree/master/maps/diagnose-case-study

## 4.

TiDB askTUG

TiDB https://github.com/pingcap/tidb-map issue

# 7.2

```
TiDB

TiDB
```

## 7.2.1

TiDB 3.0 Grafana TiKV-Trouble-Shooting Dashboard Hot Read Hot Write

1. Hot Read
   - *CPU TiKV CPU*
   - *QPS TiKV QPS*
   - *Storage ReadPool CPUReadpool CPU*
   - *Coprocessor CPUcoprocessor CPU*
   - *gRPC poll CPUgRPC CPU 80%*
   - *IO utilization TiKV IO*
2. Hot Write
   - *CPU TiKV CPU*
   - *QPS TiKV QPS*
   - *gRPC poll CPUgRPC CPU 80%*
   - *IO utilization TiKV IO*
   - *Raft store CPUraftstore CPU 80%*
   - *Async apply CPUasync apply CPU 90%*
   - *Scheduler CPUscheduler CPU 80%*

Hot Read Hot Write TiKV

## 7.2.2 /

TiKV TiDB 3.0 SQL information_schema.TIDB_HOT_REGIONS /

```
-- TYPE read write
SQL> select * from information_schema.TIDB_HOT_REGIONS where type = 'read'\G
*************************** 1. row ***************************
      TABLE_ID: 21
      INDEX_ID: NULL
       DB_NAME: mysql
    TABLE_NAME: stats_histograms
    INDEX_NAME: NULL
     REGION_ID: 44
          TYPE: read
MAX_HOT_DEGREE: 17
  REGION_COUNT: 0
    FLOW_BYTES: 248548
1 row in set (0.02 sec)
```

pd-ctl Region

```
$ pd-ctl -u http://{pd}:2379 -d region topread [limit]
$ pd-ctl -u http://{pd}:2379 -d region topwrite [limit]
```

region_id

```
$ pd-ctl -u http://{pd}:2379 -d region topread 1
{
  "as_peer": null,
  "as_leader": {
    "1": {
      "total_flow_bytes": 248535,
      "regions_count": 1,
      "statistics": [
        {
          "region_id": 44,
          "flow_bytes": 248548,
          "hot_degree": 15, --  1 degree+1
          "last_update_time": "2020-03-07T16:14:51.186168306+08:00",
          "AntiCount": 1,
          "Version": 11,
          "Stats": null
        }
      ]
    }
  }
}
```

Region ID

```
$ curl http://{TiDBIP}:10080/regions/{RegionId}
{
 "region_id": 44,
 "start_key": "dIAAAAAAAAAV",
 "end_key": "dIAAAAAAAAAX",
 "frames": [
  {
   "db_name": "mysql",
   "table_name": "stats_histograms",
   "table_id": 21,
   "is_record": false,
   "index_name": "tbl",
   "index_id": 1
  },
  {
   "db_name": "mysql",
   "table_name": "stats_histograms",
   "table_id": 21,
   "is_record": true
  }
 ]
}
```

SQL TiDB 4.0 Key Visualizer ""

## 7.2.3

TiDB TiKV BlockCache TiKV-Details Dashboard RocksDB KV Block cache hit SQL

1. BlockCache BlockCache SQL SQL count(*) SQL " SQL" SQL SQL_NO_CACHE Hints
2. Region Region Region TiKV hash SHOW TABLE REGIONS hash 4

```
SQL> CREATE TABLE t1(
    -> id INT NOT NULL,
    -> name VARCHAR(30),
    -> hired DATE NOT NULL DEFAULT '1970-01-01',
    -> separated DATE NOT NULL DEFAULT '9999-12-31',
    -> store_id INT
    -> )
    -> PARTITION BY HASH(store_id)
    -> PARTITIONS 4;
Query OK, 0 rows affected (1.29 sec)
SQL> show table t1 regions\G
*************************** 1. row ***************************
           REGION_ID: 840
           START_KEY: t_194_
             END_KEY: t_195_
           LEADER_ID: 843
     LEADER_STORE_ID: 9
               PEERS: 841, 842, 843
          SCATTERING: 0
       WRITTEN_BYTES: 35
          READ_BYTES: 0
APPROXIMATE_SIZE(MB): 1
    APPROXIMATE_KEYS: 0
*************************** 2. row ***************************
           REGION_ID: 844
           START_KEY: t_195_
             END_KEY: t_196_
           LEADER_ID: 847
     LEADER_STORE_ID: 9
               PEERS: 845, 846, 847
          SCATTERING: 0
       WRITTEN_BYTES: 35
          READ_BYTES: 0
APPROXIMATE_SIZE(MB): 1
    APPROXIMATE_KEYS: 0
*************************** 3. row ***************************
           REGION_ID: 848
           START_KEY: t_196_
             END_KEY: t_197_
           LEADER_ID: 851
     LEADER_STORE_ID: 9
               PEERS: 849, 850, 851
          SCATTERING: 0
       WRITTEN_BYTES: 35
          READ_BYTES: 0
APPROXIMATE_SIZE(MB): 1
    APPROXIMATE_KEYS: 0
*************************** 4. row ***************************
           REGION_ID: 3
           START_KEY: t_197_
             END_KEY:
           LEADER_ID: 475
     LEADER_STORE_ID: 9
               PEERS: 458, 471, 475
          SCATTERING: 0
       WRITTEN_BYTES: 217
          READ_BYTES: 0
APPROXIMATE_SIZE(MB): 1
    APPROXIMATE_KEYS: 0
4 rows in set (0.05 sec)
```

hash TiDB 3.1 Follower Read TiDB 4.0PD Load Base Splitting Region Region QPS Region""

## 7.2.4

TiDB

1. MySQL TiDB
2. / int /

3.
4.
5.

### 7.2.4.1

MySQL ID TiDB Key Region Region TiDB Region TiKV

MySQL TiDB SHARD_ROW_ID_BITS rowid Region RPC CPU

- SHARD_ROW_ID_BITS = 4 16
- SHARD_ROW_ID_BITS = 6 64
- SHARD_ROW_ID_BITS = 0 1

```
CREATE TABLECREATE TABLE t (c int) SHARD_ROW_ID_BITS = 4;
ALTER TABLEALTER TABLE t SHARD_ROW_ID_BITS = 4;
```

SHARD_ROW_ID_BITS TiDB 4.0 auto_random

### 7.2.4.2

int TiDB _tidb_rowid ID SHARD_ROW_ID_BITS _tidb_rowid INSERT Region

_tidb_rowid SHARD_ROW_ID_BITS PRE_SPLIT_REGIONS SHARD_ROW_ID_BITS _tidb_rowid ID pre_split_regions Split region

> pre_split_regions shard_row_id_bits

```
create table t2 (a int, b int) shard_row_id_bits = 4 pre_split_regions=2;
```

- SHARD_ROW_ID_BITS = 4 tidb_rowid 16 16=2^4
- pre_split_regions=2 4 (2^2) Region

### 7.2.4.2

4.0 Region Region

```
$ pd-ctl -u http://{PDIP}:2379 -i
//  Region 1  Region
> operator add split-region {hotRegionId} --policy=approximate
//  Region 1  Region
> operator add split-region {hotRegionId}1 --policy=scan
```

> Region split-merge-interval split-merge-interval Region split merge split Region merge pd-ctl 1h

hash TiDB 4.0 Region

### 7.2.4.3

ID Region

### 7.2.4.4

TiDB “”TiDB

## 7.2.5 PD

PD PD Region Peer Leader Leader Region Leader

### 7.2.5.1

hot-region-scheduler-limit Store Region Region Region Peer Leader Leader Region Leader

### 7.2.5.2 PD

TiDB 3.0 region-schedule-limit hot-region-schedule-limit hot-region-schedule-limit limit hot-region-cache-hits-threshold PD

```
//  hot-region-schedule-limit
config set hot-region-schedule-limit 8
//  limit
config set merge-schedule-limit 2
config set region-schedule-limit 2
```

### 7.2.5.3 Region

scatter-range-scheduler table Region scatter-range-scheduler

```
curl -X POST http://{TiDBIP}:10080/tables/{db}/{table}/scatter
```

scatter-range-scheduler

```
curl -X POST http://{TiDBIP}:10080/tables/{db}/{table}/stop-scatter
```

## 7.2.6

2 A B A B A 1.5K B AB 2

TiDB 2.1 TiKV raft A A bigint 1 0-9 A 10 A

# 7.3 TiKV is busy

TiDB TiKV Trouble - Shooting - Server Is Busy

TiDB

## 7.3.1 Server is Busy

Server is Busy tikv-server TiDB

# 1.

1. TiDB - Query Summary - Duration
2. TIKV TiKV - Server / Thread CPU / Error
3. TiDB server is busy tidb.log Server is Busy
4.

# 2.

1. 5ms -> 5s
2. TimeoutException
3. DB

Server is Busy Server is busy

## 7.3.2 Server is Busy

### 1. ( write stall )

TiKV 2 RocksDB , RocksDB LSM TreeLSM Tree RocksDB RocksDB

- level0 sst stall
- pending compaction bytes stall IO

- memtable stall

```
1. /
2. rocksdb max-sub-compactions 2~3 level0 level1 compaction compaction
3. level0-slowdown-writes-trigger = 40level0-stop-writes-trigger = 56
```

## 2. scheduler too busy

- latchlatch latch wait duration , TIKV - scheduler prewrite|commit latch wait duration

  scheduler prewrite - latch wait duration | scheduler commit latch wait duration

- TiKV [storage] scheduler-pending-write-threshold = "100MB"

```
1.
2.
3.
```

## 3.

Server Is Busy

(1) tikv.yml

3.0 2 **readpool.storage readpool.coprocessor** TiDB

```
// ,  cpu core  * 80%,  1
high-concurrency
// ,  cpu core  * 80%,  1
normal-concurrency
// ,  cpu core  * 80%,  1
low-concurrency
//
//  2000,  2000
max-tasks-per-worker-high
//
max-tasks-per-worker-normal
//
max-tasks-per-worker-low
```

```
max-tasks-per-worker-high * high-concurrency = 2000 * 4 = 8000
```

(2)  TiDB

- ( TiKV ) CPU
  - 48 Core  1  tikv-server 48
  - **48**
  - **36**
- (TIKV)
  - 48 Core  3  tikv-server 16
  - **16**
  - **12**

(3) 4.0

4.0  readpool.storage  readpool.coprocessor  unified read pool 3

```
[readpool]
# unify-read-pool = true

[readpool.unified]
# min-thread-count = 1
# max-thread-count = 8

## Size of the stack for each thread in the thread pool.
# stack-size = "10MB"

## Max running tasks of each worker, reject if exceeded.
# max-tasks-per-worker = 2000
```

```
1.
2.  TIKV
```

## 4. raftstore is busy

- append log  stall 2
  - [tikv-detail]->[RocksDB - raft]-[Write stall duration]
  - [tikv-detail]->[RocksDB - kv]-[Write stall duration]
  - [tikv-detail]->[Errors]->[Server is busy]
- append log duration  [tikv-detail]->[Raft IO]->[append log duration]
  - append log  IO  [tikv-detail]->[Raft IO]->[Write duration]
  - [raftstore] store-pool-size  [1,5]  [tikv-detail]->[Thread CPU]->[Raft store CPU] [Raft store CPU]  [store-pool-size ] * 70%  store-pool-size

- tikv-server region 5 region raftstore cpu hibernate region

```
[raftstore]
hibernate-regions = true
```

```
**** ****store-pool-size
```

TiKV Server is busy TiDB Server is Busy SQL

## 7.3.3 Server is Busy

### 1. SQL

1. ,
2.
3. tikv

> **SQL SQL SQL 4.0 unified thread pool**

### 2.

tikv is busy

> ****** TiDB v3.0.8 v3.0.8**

### 3. region

TiDB 2.1 TiKV raft region region server is busy

```
1.  3.0  store-pool-size  raftstore
2.  hibernate-regions  region
```

## 7.3.4

1. region id region tikv-server server is busy
2. tikv server is busy

```
 region shard_row_id_bitspre_split_regions
```

## 7.3.5

Server is Busy 99% 6ms , 3s ?

Server is Busy Query Duration tidb.log wait exec

coprocessor 2000 2001 2001

## 7.3.6

1. SQL SQL 4.0  unified thread pool
2. 
3. region shard_row_id_bitspre_split_regions
4. tikv

# 7.4 TiDB OOM

TiDB OOM TiDB-Server TiKV-Server

## 7.4.1 TiDB-Server

### 1. TiDB-Server OOM

- tidb-server "ERROR 2013 (HY000): Lost connection to MySQL server during query"
- TiDB grafana Server Heap Memory Usage

- TiDB service

```
$ systemctl status tidb-4000.service
●tidb-4000.service - tidb-4000 service
Loaded: loaded (/etc/systemd/system/tidb-4000.service; disabled; vendor preset: disabled)
Active: active (running) since Fri 2020-02-21 12:30:04 CST; 5 min ago
```

-
  - /var/log/message&kern “out of memory” "TiDB service was killed"
  - tidb.log grep "Welcome to TiDB" tidb-server
  - tidb_stderr.log grep "fatal error: runtime: out of memory" "cannot allocate memory"

### 2. TiDB-Server OOM

TiDB oom TiDB TiDB

-

SQL root TiDB-Server hash joinUpdate&Delete

- Prometheus
-
- mydumper

### 3. TiDB-Server OOM

- " SQL" SQL
- tidb_mem_quota_query Query 32GB

```
global:
mem-quota-query: 209715200 // 200MB
oom-action: "cancel"  // SQL
```

- max_execution_time SQL

```
set @@GLOBAL.max_execution_time=10000; // SQL  10s
```

- SWAP OOM

```
 IO
```

- 4.0  oom-use-tmp-storage

```
 `true`  SQL  `mem-quota-query`
```

- TiDB

```
TiDB  NUMA TiDB  NUMA
 membind Only allocate memory from nodes.  Allocation will fail when there is not enough memory available on the
se nodes.  nodes may be specified as noted above NUMA NODE NUMA NODES
 preferred Only allocate memory from nodes.  Allocation will fail when there is not enough memory available on t
hese nodes.  nodes may be specified as noted above NUMA NODE
 TiDB
sudo -s numactl --preferred=node
```

- TiDB

```
1 SQL
      TiDB OOM   tidb_slow_query.log  Query_time  Mem_max  SQL
      SQL
      table scan
     hash join  join  index loop join
      delete  tidb_batch_delete
2 TiDB
      SQL  TiDB  TiDB  oom
```

## 7.4.2 TiKV-Server

TiKV-Server OOM

## 1. block-cache

TiKV grafana  instance  RocksDB  block cache size  TiKV  block-cache  45% container  TiKV  container

```
[storage.block-cache]
capacity = "30GB"
```

> 1.
> 2. block-cache

## 2. coprocessor

gRPC  coprocessor  OOM [tikv-detail]->[Coprocessor Overview]->[Total Response Size]  network outbound

> 1.
> 2. " SQL"
> 3. gRPC poll CPU

## 3. Raft apply  raft apply log

Apply  apply channel  oom apply wait duration  apply log duration

- [tikv-detail]->[Raft IO]->[apply log duration]
- [tikv-detail]->[Raft propose]->[apply wait duration]
- [tikv-detail]->[Thread CPU]->[async apply CPU]

> 1. apply cpu  [Async apply CPU]  [apply-pool-size ] * 70%  apply-pool-size
> 2. io

# 7.5 TiKV

```
TiKV  TiDB  SQL  TiKV TiKV
```

## TiKV

- Number files at each levels  TiDB  10G

> TiKV  LSM-Tree  RocksDB  INSERT  UPDATE  DELETE  `max-bytes-for-level-multiplier` RocksDB  10GB  (512MB + 1GB + 10GB) * 3  RocksDB  key  block  LZ4  ZSTD  33.5GB. (512MB L0  SST )

- TiDB  GC ?

> TiDB  MVCC  Snapshot Isolation  DELETE  UPDATE  TiDB  TiDB  TiDB  TiKVTiKV  `GC`

- UPDATE SQL  UPDATE

> UPDATE  TiDB  `tikv_gc_life_time`  10  UPDATE  10  TiKV  GC  UPDATE  GC  UPDATE  TiKV  " 10 + * 1.12". 1.12

- TiKV  1020

> TiKV  GC GC speed  TiKV TiKV  GC  raft leader  follower  TiKV  `gc.max-write-bytes-per-sec`  GC  `128KB` ~ `512KB`  `0KB`

- `DELETE FROM table_xx;`

> GC TiDB  10  RocksDB  RocksDB  `DROP TA`  RocksDB

- TiDB

> MySQL  TiDB TiDB  `SELECT * from mysql.tidb`  `tikv_gc_life_time`  TiDB  10  GC

- GC  RocksDB

> GC  compact  TiKV  CPU RocksDB compact  12%  rocksdb

## Dynamic Level

- TiKV  level-1  level-2  level-3  level-4

> TiKV  RocksDB  Dynamic Level Bytes  `max-bytes-for-level-base` 512MB level-6  level-6  level-1  `max-bytes-for-level-base`  `max-bytes-for-level-base * max-bytes-for-level-multiplier`  level-6  level-2  level-5  level-1 level-0  110

- TiKV

> TiKV  snappyzlibbzip2lz4lz4hczstd  `["no", "no", "lz4", "lz4", "lz4", "zstd", "zstd"]`  dynamic level  500G  RocksDB  4  500G  ZSTD  defaultcf  writecf  `compression-per-level`  `["lz4", "zstd", "zstd", "zstd"]`, 50G  500G  zstd

# 8 TiDB

“” TiDB  TiDBTiKVPD


- 8.1 TiDB
- 8.2 TiKV
- 8.3

# 8.1 TiDB

TiDB TiDB

## 8.1.1 SQL

SQL SQL SQL Kill TiDB SQL

(1)

max_execution_time

- GlOBAL | SESSION | SQL HINT
- 0
- N SQL Hint

SQL Hint:

```
mysql> SELECT /*+ MAX_EXECUTION_TIME(1000) */ * FROM t1 INNER JOIN t2 WHERE ...;
```

(2)

tidb_mem_quota_query

- SESSION
- 32 GB
- TiDB OOMAction oom-action log SQL cancel Kill SQL SQL

```
--10G
mysql> set @@session.tidb_mem_quota_query=10737418240;
Query OK, 0 rows affected (0.00 sec)
mysql> show variables like '%tidb_mem_quota_query%';
+----------------------+-------------+
| Variable_name        | Value       |
+----------------------+-------------+
| tidb_mem_quota_query | 10737418240 |
+----------------------+-------------+
1 row in set (0.00 sec)
```

mem-quota-query

- GLOBAL
- 32GB
- TiDB Global TiDB tidb-ansible conf/tidb.yaml mem-quota-query TiDB OOMAction oom-action log SQL cancel Kill SQL

```
conf/tidb.yaml
---
# default configuration file for TiDB in yaml format

global:
  ...
  # Only print a log when out of memory quota.
  # Valid options: ["log", "cancel"]
  # oom-action: "log"

  # Set the memory quota for a query in bytes. Default: 32GB
  # mem-quota-query: 34359738368
```

## 8.1.2

TiDB 2PC  TiDB

tidb_retry_limit

- SESSION | GLOBAL
- 10
- tidb_retry_limit = 0 SQL

```
--SESSION
mysql> set @@session.tidb_retry_limit=0;
Query OK, 0 rows affected (0.01 sec)

--GLOBAL
mysql> set @@global.tidb_retry_limit=0;
Query OK, 0 rows affected (0.00 sec)

mysql> show variables like '%tidb_retry_limit%';
+------------------+-------+
| Variable_name    | Value |
+------------------+-------+
| tidb_retry_limit | 0     |
+------------------+-------+
```

tidb_disable_txn_auto_retry

- SESSION | GLOBAL
- on
- on  off TiDB  TiDB  tidb_retry_limit SQL

```
--SESSION
mysql> set @@session.tidb_disable_txn_auto_retry=OFF;
Query OK, 0 rows affected (0.00 sec)

--GLOBAL
mysql> set @@global.tidb_disable_txn_auto_retry=OFF;
Query OK, 0 rows affected (0.00 sec)

mysql> show variables like '%tidb_disable_txn_auto_retry%';
+-----------------------------+-------+
| Variable_name               | Value |
+-----------------------------+-------+
| tidb_disable_txn_auto_retry | OFF   |
+-----------------------------+-------+
1 row in set (0.01 sec)
```

## 8.1.3 Join

TiDB  SQL Join  TP | AP  Join  SQL

tidb_distsql_scan_concurrency

- SESSION | GLOBAL
- 15
- scan AP TP  AP  TiKV  CPU SQL

```
--SESSION
mysql> set @@session.tidb_distsql_scan_concurrency=30;
Query OK, 0 rows affected (0.00 sec)

--GLOBAL
mysql> set @@global.tidb_distsql_scan_concurrency=30;
Query OK, 0 rows affected (0.00 sec)

mysql> show variables like '%tidb_distsql_scan_concurrency%';
+------------------------------+-------+
| Variable_name                | Value |
+------------------------------+-------+
| tidb_distsql_scan_concurrency | 30    |
+------------------------------+-------+
1 row in set (0.01 sec)
```

tidb_index_lookup_size

- SESSION | GLOBAL
- 20000
- index lookup batch AP TP SQL

```
--SESSION
mysql> set @@session.tidb_index_lookup_size=40000;
Query OK, 0 rows affected (0.00 sec)

--GLOBAL
mysql> set @@global.tidb_index_lookup_size=40000;
Query OK, 0 rows affected (0.01 sec)

mysql> show variables like '%tidb_index_lookup_size%';
+-----------------------+-------+
| Variable_name         | Value |
+-----------------------+-------+
| tidb_index_lookup_size | 40000 |
+-----------------------+-------+
1 row in set (0.00 sec)
```

tidb_index_lookup_concurrency

- SESSION | GLOBAL
- 4
- index lookup AP TP SQL

```
--SESSION
mysql> set @@session.tidb_index_lookup_concurrency=8;
Query OK, 0 rows affected (0.00 sec)

--GLOBAL
mysql> set @@global.tidb_index_lookup_concurrency=8;
Query OK, 0 rows affected (0.00 sec)

mysql> show variables like '%tidb_index_lookup_concurrency%';
+------------------------------+-------+
| Variable_name                | Value |
+------------------------------+-------+
| tidb_index_lookup_concurrency | 8     |
+------------------------------+-------+
1 row in set (0.00 sec)
```

tidb_index_lookup_join_concurrency

- SESSION | GLOBAL
- 4
- index lookup join SQL

```
--SESSION
mysql> set @@session.tidb_index_lookup_join_concurrency=8;
Query OK, 0 rows affected (0.00 sec)
--GLOBAL
mysql> set @@global.tidb_index_lookup_join_concurrency=8;
Query OK, 0 rows affected (0.01 sec)
mysql> show variables like '%tidb_index_lookup_join_concurrency%';
+-----------------------------------+-------+
| Variable_name                     | Value |
+-----------------------------------+-------+
| tidb_index_lookup_join_concurrency | 8     |
+-----------------------------------+-------+
1 row in set (0.00 sec)
```

tidb_hash_join_concurrency

- SESSION | GLOBAL
- 5
- hash join SQL

```
--SESSION
mysql> set @@session.tidb_hash_join_concurrency=10;
Query OK, 0 rows affected (0.01 sec)

--GLOBAL
mysql> set @@global.tidb_hash_join_concurrency=10;
Query OK, 0 rows affected (0.00 sec)

mysql> show variables like '%tidb_hash_join_concurrency%';
+----------------------------+-------+
| Variable_name              | Value |
+----------------------------+-------+
| tidb_hash_join_concurrency | 10    |
+----------------------------+-------+
1 row in set (0.01 sec)
```

tidb_index_serial_scan_concurrency

- SESSION | GLOBAL
- 1
- scan AP TP SQL

```
--SESSION
mysql> set @@session.tidb_index_serial_scan_concurrency=4;
Query OK, 0 rows affected (0.00 sec)

--GLOBAL
mysql> set @@global.tidb_index_serial_scan_concurrency=4;
Query OK, 0 rows affected (0.01 sec)

mysql> show variables like '%tidb_index_serial_scan_concurrency%';
+-----------------------------------+-------+
| Variable_name                     | Value |
+-----------------------------------+-------+
| tidb_index_serial_scan_concurrency | 4     |
+-----------------------------------+-------+
1 row in set (0.00 sec)
```

## 8.1.4 Mysql

compatible-kill-query

- false
- Kill TiDB Kill sessionID MySQL TiDB TiDB Kill TiDB sessionID compatible-kill-query true TiDB

Ctrl+C MySQL Kill TiDB TiDB Kill Kill compatible-kill-query ,( tidb-ansible conf/tidb.yaml )

```
conf/tidb.yaml
---
# default configuration file for TiDB in yaml format

global:
  ...
  # Make "kill query" behavior compatible with MySQL. It's not recommend to
  # turn on this option when TiDB server is behind a proxy.
  compatible-kill-query: false
```

```
tidb_constraint_check_in_place
* SESSION | GLOBAL
* 0
* TiDB  commit  unique key
```

```
-- tidb_constraint_check_in_place
create table t (i int key);
insert into t values (1);
begin;
insert into t values (1);
Query OK, 1 row affected
commit;   --commit
ERROR 1062 : Duplicate entry '1' for key 'PRIMARY'


-- tidb_constraint_check_in_place
set @@tidb_constraint_check_in_place=1;
begin;
insert into t values (1);
ERROR 1062 : Duplicate entry '1' for key 'PRIMARY'
```

## 8.1.5

prepared-plan-cache txn_local_latches TiDB TiDB tidb-ansible conf/tidb.yaml tidb-server

```
conf/tidb.yaml
--
prepared_plan_cache:
  enabled: true              --  prepare  plan cache, false
  capacity: 100              --
  memory-guard-ratio: 0.1    -- performance.max-memory,  max-proc * (1 - prepared-plan-cache.memory-guard-ratio)  LRU
 , 0 1, 0.1

--
txn_local_latches:
   enabletrue               -- , false
   capacity: 2048000          -- Hash  slot  2  slot  32 Bytes
```

# 8.2 TiKV

TiKV TiKV

TiKV RocksDB TiKV RocksDB TiKV RocksDB RocksDB KV Raft RocksDB RaftDB Raft

TiKV RocksDB `Column Families` (CF)

- RocksDB KV `default` `write` `lock` 3 CF
  - `default` CF `[rocksdb.defaultcf]`
  - `write` CF (MVCC) `[rocksdb.writecf]`
  - `lock` CF
- Raft RocksDB Raft log
  - `default` CF Raft log `[raftdb.defaultcf]`

CF block cache `[storage.block-cache]` `capacity` block cache block cache CF block cache `[storage.block-cache]` `shared=false` CF block cache `[rocksdb.writecf]` `block-cache-size` `write` CF

CF `write-buffer` `write-buffer-size`

## TiKV

`block-cache` `write-buffer`

1. page cache
2. TiKV `select * from ...` TiDB TiKV

## TiKV

1. TiKV CPU 8 32GB
2. 
3. IOPS SSD

TiKV Region TiKV

# 8.2.1 TiKV

TiKV 4.0 gRPCSchedulerUnifyReadPoolStoreApplyRocksDB CPU

● gRPC TiKV

● Scheduler key-value Store Raft

● Raftstore Raft Propose Raft Group Raft Commit Index Apply

● Apply Store key-value RocksDB gRPC

● RocksDB RocksDB Compact Flush RocksDB Compact RocksDB: A Persistent Key-Value Store for Flash a Storage

● UnifyReadPool TiKV 4.0 Coprocessor Storage Read Pool kv getkv batch getraw kv getcoprocessor

[storage]
scheduler-worker-pool-size = 4

Tip: check whether the scheduler wroker CPU has become the bottleneck.

From v3.0, `raftstore` and `apply` work in a multi-threading framework.

[raftstore]
store-pool-size = 2
apply-pool-size = 2

## 1. GRPC

gRPC server.grpc-concurrency **4** gRPC IO CPU 8server.grpc-concurrency 2 TiKV Grafana Thread CPU gRPC poll CPU server.grpc-concurrency 80% server.grpc-concurrency **80%**

## 2. Scheduler

Scheduler (storage.scheduler-worker-pool-size) TiKV CPU 16 8 16 4 key-value **sc** Raft raftstore raft scheduler **50%75%** 8 Grafana Thread CPU scheduler worker CPU 400%

## 3. Raftstore

Raftstore TiKV raftstore.store-pool-size 2 store fsync RocksDB raftstore.sync-log true raftstore.sync-log false IOstore 100% CPU RocksDB CPU **40% 60%** store

● Raft IO append log duration Store Raft Message RocksDB Raft P99 500ms Node Exporter disk latency RocksDB Write Stall RocksDB-raft write stall duration 0 0 write stall

## 4. UnifyReadPool

UnifyReadPool readpool.unified.max-thread-count CPU 80% CPU 60%90%

# 5. RocksDB

RocksDB RocksDB Compact Flush CPU rocksdb.max-background-jobs raftdb.max-background-jobs 4. Write Stall Grafana RocksDB-kv Write Stall Reason 0 pending compaction bytes rocksdb.max-sub-compactions 2 compaction job memtable count max-write-buffer-number 5 level0 file limit

```
rocksdb.defaultcf.level0-slowdown-writes-trigger
rocksdb.writecf.level0-slowdown-writes-trigger
rocksdb.lockcf.level0-slowdown-writes-trigger
```

# 8.2.2 Region

TiDB range key Region TiKV Region TiKV Region

TiKV Raftstore Region

## 1. Raftstore

TiKV RegionRegion Raftstore Raft Region Raft log Raft Region TiKV Raftstore

> 

Raftstore TiDB gRPC storage KV RegionRaftstore Region Region Raftstore Raft Raft Region Raft Region

## 2.

Raftstore Region Region Raftstore Region Raftstore CPU

Raftstore CPU 85% Grafana TiKV Raft Propose propose wait duration

> Raftstore CPU Raftstore Raftstore I/O CPU 100%

Grafana TiKV metrics

Thread-CPU Raft store CPU

raftstore.store-pool-size * 85%

-


Raft Propose Propose wait duration

Propose wait duration Raftstore Raftstore Raftstore append log Raftstore

50-100ms

-


# 3.

- TiKV Region
- Region

## TiKV

I/O CPU TiKV TiKV Region TiKV

## raft-base-tick-interval

Region Region Raftstore TiKV raft-base-tick-interval

```
[raftstore]
raft-base-tick-interval = "2s"
```

raft-base-tick-interval Raftstore Region Raft Raft tick Raftstore tick election timeout heartbeat

```
raft-election-timeout = raft-base-tick-interval * raft-election-timeout-ticks
raft-heartbeat-interval = raft-base-tick-interval * raft-heartbeat-ticks
```

Region Follower raft-election-timeout Leader Leader raft-heartbeat-interval Leader Follower raft-base-tick-interval Raft Raft Leader

## Raftstore

TiKV raftstore.store-pool-size 2 Raftstore

## Hibernate Region

Region Region Region Hibernate Region raft-base-tick Region Raft Region Raft Raftstore

TiDB v4.0Hibernate Region TiKV master Hibernate Region Hibernate Region

## Region Merge

> Region Merge TiDB v4.0

Region Merge Region Region Split Region Merge Region Drop Table/Truncate Table Region Region

pd-ctl Region Merge Region Merge

```
>> pd-ctl config set max-merge-region-size 20
>> pd-ctl config set max-merge-region-keys 200000
>> pd-ctl config set merge-schedule-limit 8
```

Region Merge PD Region Merge PD Region Merge

# 8.2.3

1. Block-cache TiKV RocksDB Column Family (CF) KV RocksDB defaultwritelock 3 CF
2. default CF [rocksdb.defaultcf]
3. write CF MVCC [rocksdb.writecf]
4. lock CF
5. Raft RocksDB Raft logdefault CF Raft log [raftdb.defaultcf]
6. TiDB 3.0 CF Block-cache RocksDB TiDB 2.1 block-cache-size CF Block-cache Block-cache
7. CF Write-buffer write-buffer-size

TiDB 3.0 TiKV conf/tikv.yml block-cache-size capacity

```
storage:
  block-cache:
    capacity: "1GB"
```

> TiKV TiKV capacity = MEM_TOTAL * 0.5 / TiKV

# Sync-log

Raft TiKV 50% ACK sync-log sync-log 30%

conf/tikv.yml raftstore sync-log

```
[raftstore]
sync-log = true
```

# 8.3

TiDB Online DDL TiDB DDL DML

# 8.3.1 TiDB

TiDB DDL Google F1 schema schema TiDB 2.1 DDL (add index job

**:**

1.
2.

**:**

1. TiDB TiDB
2. Job (add index job queue)
3. TiDB Worker Job
4. Worker PD region 256 Job region
5. Job Job (history ddl job)

# 8.3.2

| | | |
|---|---|---|
| tidb_ddl_reorg_worker_cnt | 4 | |
| tidb_ddl_reorg_batch_size | 256 | |
| tidb_ddl_reorg_priority | PRIORITY_LOW | PRIORITY_LOW/PRIORITY_NORMAL/PRIORITY_HIGH |
| tidb_ddl_error_count_limit | 512 | |

`tidb_ddl_reorg_worker_cnt` `tidb_ddl_reorg_batch_size` 4 256 `tidb_ddl_reorg_worker_cnt` `tidb_ddl_reorg_batch_size` `tidb_ddl_reorg_priority` PRIORITY_HIGH OLTP

1. `admin show ddl` RowCount START_TIME DDL r1 t1
2. `show stats_meta` RowCount r0
3. t1/(r1/r2) - t1

1.
2.

# 1 TiDB

## 1.1 TiDB

### 1.1.1 TiDB

TiDB 2015 4 5 5 TiDB 1800 PingCAP 2020 3 TiDB 760 Contributor100 30000+ GitHub Stars 1000+ AskTUG 700+ PingCAP University TiDB 1000

2019 TiDB 94 123 38 Infra Meetup 23 Paper Reading 60000+

2020 TiDB 4.0 GA 5 TiDB

### 1.1.2 TiDB

| | |
|---|---|
| 2015 04 | TiDB |
| 2015 09 | GitHub Star 2700 |
| 2015 12 | TiDB 1.0 Alpha Google F1 |
| 2016 04 | Google Spanner TiKV |
| 2017 10 | TiDB 1.0 GA |
| 2018 04 | TiDB 2.0 GA, TiDB + TiKV 16000+ Stars, 240+ Contributors |
| 2018 08 | TiDB Operator |
| 2018 08 | CNCF TiKV CNCF Sandbox |
| 2018 12 | Talent Plan |
| 2019 01 | TiDB Lightning Toolset & TiDB Data Migration |
| 2019 03 | TiDB PingCAP University |
| 2019 05 | TiDB Binlog |
| 2019 05 | CNCF TiKV CNCF Incubation |
| 2019 06 | TiDB User Group |
| 2019 06 | TiDB 3.0 GATiDB + TiKV 22000+ Stars, 390+ Contributors |
| 2019 06 | TiDB AskTUG |
| 2019 06 | TiDB 2.0 Courses |
| 2019 07 | TiDB Operator 1.0 GA AWS/GCP/ |
| 2019 12 | Chaos Mesh |
| 2020 01 | TiFlash Beta |
| 2020 03 | TiDB Contributor 400 |
| 2020 03 | TiDB 4.0 RC |
| 2020 03 | Talent Plan Courses |
| 2020 05 | TiDB 4.0 GA |

# 1.2 TiDB

## 1.2.1 TiDB

### 1. TiDB

TiDB TiDB SQL SQL SQL Load Balancer TiDB TiDB MySQL Protocol Packet TiI
TiDB TiKV TiDB

### 2. Parser

Parser Yacc MySQL Parser SQL SQL AST

### 3. TiSpark

TiSpark PingCAP OLAP Spark TiKV TiDB HTAP (Hybrid Transactional/Analytical Processing) TiSpark
TiKV Placement Driver (PD) Spark

## 1.2.2 TiKV

### 1. TiKV

TiKV K-V RocksDB Raft Percolator Raft PD K-V ACID TiDB TiKV javac

### 2. PD

PD ( Placement Driver ) TiDB ID TSO PD TiKV client

### 3. grpc-rs

grpc-rs gRPC Core rust SSLTiKV TiDB

### 4. raft-rs

raft-rs Raft rust etcd Raft

### 5. rust-rocksdb

rust-rocksdb Rocksdb rust Rust Rocksdb TiKV

### 6. rust-prometheus

rust-prometheus rust Prometheus instrumentation Rust Prometheus

### 7. pprof-rs

pprof-rs rust profiling TiKV profiling

## 1.2.3 Tools

### 1. TiDB Lightning

TiDB Lightning TiDB DDL DDL TiDB KV TiKV Mydumper CSV MySQL TiDB

### 2. Dumpling

Dumpling Mydumper MySQL Dumpling Mydumper Lightning TiDB Dumpling

### 4.ticdc

ticdc TiDB MySQL, TiDB, Kafka ticdc TiKV KV SQL MySQL TiDB Kafka KV Kafka SQL

### 5. DM

DM MySQL TiDB DM-master, DM-worker dmctl DM-master DM-worker dmctl DM MySQL binlog DM-worker TiDB

### 6. BR

BR TiDB BR SQL BR PD TiKV region leader KV sst TiKV sst Raft

### 7. tidb-binlog

tidb-binlog TiDB binlog TiDB SQL Pump Drainer Pump binlog Tidb Binlog TiDB, MySQL, Kafka SQL

## 1.2.4 Cloud

### TiDB Operator

TiDB Operator Kubernetes TiDB TiDB TiDB TiDB Operator TiDB Kubernetes TiDB Operator Kubernetes TiDB

## 1.2.5

### 1. Chaos Mesh

Chaos Mesh Kubernetes Kubernetes Chaos Mesh Chaos Kubernetes

### 2. tipocket

tipocket Chaos Mesh TiDB TiDB Operator Chaos Mesh Kubernetes TiDB Chaos

### 3. TiDB Ansible

TiDB Ansible TiDB

### 4. docs

docs PingCAP PingCAP https://pingcap.com/docs/

### 5. docs-cn

docs-cn docs PingCAP https://pingcap.com/docs-cn/

# 1.3 TiDB

TiDB  TiDB TiDB  community

PMCDeveloper GroupUser Group  Organization Committee

## 1.3.1 PMC

TiDB  Apache  PMC(Project Management Committee)  TiDB  Roadmap

## 1.3.2 Developer Group

Developer Group ContributorCommitter  Maintainer  Contributor  Committer TiDB  Active Contributor  Reviewer

TiDB TiDB TiKV TiDB :

- Special Interest Group SIG 70 ARPAnet mailing list TiDB SIG TiDB/TiKV Active Contributor Tech Lead CommitterReviwer Active Contributor ReviewerCommitter Maintainer
- Working Group WG SIG SIG

## 1.3.3 User Group

User Group TiDB User GroupTUG TiDB TiDB TUG TUG TiDB

TiDB TiDB TiDB TiDB

## 1.3.4 Organization Committee

Organization Committee Committee Legal / Quality / Marketing

# 1.4 TiDB

TiDB  TiDB

- ICDE  Paper - UniKV: Toward High-Performance and Scalable KV Storage in Mixed Workloads via Unified Indexing
- TiDB  Intel Optane DC persistent memory
-

TiDB

- TiDB  TiDB
- Cloud  TiDB  scan  TiDB 250+ 500+ TB
- TiKV  TiKV  TiKV  KV

TiDB

# 2 TiDB

## 2.1

### 2.1.1 TiDB DevCon

TiDB DevCon PingCAP TiDB 2018 2019 TiDB DevCon TiDB TiDB TiDB DevCon TiDB TiDB

TiDB DevCon 2019 2019 01 19 750+VIPKIDBilibili

TiDB DevCon 2018 2018 01 20 300+Mobike

TiDB DevCon2018

TiDB
DevCon2018

今日头条TiDB实践

## 2.1.2 TiDB TechDay

Get TiDB 2017 PingCAP TiDB TechDay TiDB

TechDay 2017 TiDB Internal, TiSpark, TiDB on Kubernetes

TechDay 2018 TiDB 2.1 Beta Chaos Practice in TiDB

TechDay TiDB TechDay 2019 6 TiDB 3.0 TiDB

TiDB TechDay 2019
join us !
TiDB
NIKE

TiDB TechDay 2019

哪里
OLAP? OLTP? 为什么不能统一?
我们是一个什么样的公司?
我们为世界应该提供什么样的价值?

## 2.1.3 Infra Meetup

### 1.

PingCAP Hackers 2016 3 5 Infra Meetup

### 2.

2015 TiDB Infra Meetup

2020 3 PingCAP Infra Meetup 125 Infra Meetup 100 TiDB TiDB Meetup Meetup

No.125 Infra Meetup

## 2.1.4 TiDB Hackathon

### 1.

Hackathon  Hackathon  18 PingCAP  TiDB Hackathon TiDB  Pizza  TiDB  48

### 2.

PingCAP  TiDB TiDB Hackathon

- TiDB Hackathon  2018  12  1 “TiDB Ecosystem” TiDB 22  6  48  TiDB Batch and Streaming SQL TiDB  CC Region  TiEyeAll diagnosis in SQL  TiQuery Hackathon

- TiDB Hackathon  2019  10  26 “Improve·” Hacking Time 39  7  Demo Show  TiDB TiDB “” bug TiDB~

## 3.

TiDB &TiDB Hackathon

Hackathon PingCAPer TiDB Hackathon

Hackathon ~

## 2.1.5 TUG

TiDB TiDB  TiDB Community  TiDB User Group

TiDB TiDB  11  TiDB TiDB  SaaS

> " TiDB  TiDB "
>
> ""
>
> " TiDB "

TUG  “TUG ”TUG  TUG  TiDB “” Infra Meetup 2.1.3

1. TUG “”“”“Cloud + Database”“”“”
2. TUG
3. TUG
4. TUG TUG PingCAP

TUG  2019  8 ShopeeVIPKIDUCloud 10+  TUG

2020 TUG  TUG  TUG  TUG

# 2.2 TUG (TiDB User Group)

## 2.2.1 TUG

2019 TiDB 1000 TiDB TiDB TUG

TUG 2019 6 TiDB PingCAP 5 Local TUG TUG “”DBA58 Shopee
bilibili 100+ TiDB

TUG TUG TiDB TiDB TUG 2019 TUG 78 78 Talk 5000 TUG TUG

## 2.2.2 TUG

TUG Management) (Professional)

- TUG Management TUG TUG
  - TUG Governance CommitteeTUG TUG TUG TUG
  - TUG Infra Team Leader/Co-Leader TUG
  - TUG Local Leader/Co-Leader TUG TUG Leader Co-leader
- TUG Professional TiDB TiDB MVA TUG
  - TiDB MVAMost Valuable Advocate)TUG TiDB TUG ≥3 TiDB MVA 2019 TUG 29 TiDB MVA

TUG TiDB TUG TUG AmbassadorTUG Ambassador TUG TUG ManagementProfessional TUG

## 2.2.3 TUG

TUG TiDB TUG Talk TUG TUG TUG TUG

## 2.2.4 TUG

2020 TUG  TUG TUG  Go Global  TiDB  TiDB  TUG TUG

# 2.3 Talent Plan: Made for Community, by Community

Talent Plan PingCAP GitHub **3800+** StarTalent Plan TiDB

2018 12 Talent Plan 2020 3 7 **400** 40 4 38 15 Talent Plan PingCAP TiDB Community

## 2.3.1

Talent Plan Talent Plan Rust TiDB/TiKV TiDB

## 1.

4 Open Source Collaboration Programming Language Infrastructure Systems Deep Dive into TiDB Ecosystem

**Series 1: Open Source Collaboration(WIP)**

LinuxApacheCNCF TiDB

**Series 2: Programming Language**

GoRustC++Python

Rust Brian Anderson Rust —— Practical Networked Applications in Rust Rust Key-Value

## Series 3: Infrastructure Systems

- Go TinySQLWIP
- Go Key-Value TinyKVWIP
- Rust Distributed Systems in Rust

TinySQL SQL

- SQL
- SQL Parser
- SQL DML DDL

TinyKV Distributed Systems in Rust MIT 6.824 TiKV 0 1 KV

- LAB1: KV server
- LAB2: Raft KV server
- LAB3: multi-Raft
- LAB4: percolator

TinyKV Raft Percolator TinyKV TiDB + TiKV + PD TiDB/TiKV/PD

**TinySQL TinyKV**

**Series 4: Deep Dive into TiDB Ecosystem**

TiDB TiDBTiKVCloud TiDB

## 2. ——Talent Challenge Program

TiDB 1 **PingCAP Talent Plan PingCAP //Special Offer PingCAP/TiDB Meetup**

4 41 10 38

## 2.3.2

### 1: Distributed Storage Engineer

- Programming Language: "Practical Networked Applications in Rust"
- Infrastructure Systems: "Distributed Key-Value Database Internals(WIP)" &"Distributed Systems in Rust"
- "Deep Dive into TiKV"

### 2: Distributed Relational Database Engineer

- Programming Language: "A Tour of Go"
- Infrastructure Systems: "Distributed Relational Database Internals(WIP)"
- "Deep Dive into TiDB"

### 3: Cloud TiDB Engineer

- Programming Language: "A Tour of Go"
- Container & Container Orchestration (DockerK8s …)
- “Deep Dive into Cloud TiDB(WIP)”

### 4:

- Open Source Collaboration(WIP): “Introduction to Open Source Software” & “Build a Welcoming Community”
- *The Art of Community: Building The New Age Of Participation*, *The Cathedral & the Bazaar: Musings on Linux and Open Source by an Accidental Revolutionary*, *People Powered: How communities can supercharge your business, brand, and teams*

## 2.3.3

> - “ PingCAP Demo TiDB TiDB PingCAP Global Meetup ” ——
> - “ Talent Plan PingCAP PingCAP ” KV | Talent Plan ——
> - “ Talent Plan PingCAP Talent Plan ”——
> - “ Talent Plan fancy work”——
> - “ Talent Plan TiDB PingCAP Cool Geek ”——
> - " Talent Plan TiDB "——

## 2.3.4 Talent Plan

Talent Plan “Made for Community, by Community”

- Talent Plan Talent Plan TiDB TiKV
- Talent Plan TiDB Community Slack Workspace channel: **#wg-talent-plan-courses**“” 2.0

# 2.4 Challenge Program

## 2.4.1

TiDB  TiDB  TiDB TiDB

TiDB PingCAP —— TiDB Challenge Program TiDB  Issue  Issue

2

| season | period |
| --- | --- |
| Challenge Program season 2 | 2020.03~2020.05 |
| Challenge Program season 1 | 2019.11~2020.02 |

## 2.4.2

TiDB Performance Challenge 1  2  3  600

- .* Team15050
- niedhui4300  catror3500
- pingyu2600 Renkai2550  js000701800
- ekalinin1450 mmyj1050 AerysNan750 MaiCw4J650 Rustin-Liu650  koushiro650

TiDB SQL  in/like  TiTan  GC  GC  PD API  PD

## 2.4.3

TiDB Challenge Program TiDB TiDB Usability Challenge

PingCAP AskTUG “ TiDB ” 2019.12.17 2020.01.12 1 20 2020 2 11 2020 2 20 5

2 2020 3 2 2020 05 30 3

10000 8000 6000 (/)*

TiDBTiKVPD TiDB

## 2.4.4

TiDB Challenge Program ->->->->->->“” GitHub

## 2.4.5

PingCAP TiDB TiDB

# 2.5 PingCAP Incubator

PingCAP Incubator CNCF TiDB TiDB TiDB

PingCAP Incubator TiDB TiDB “->->” Feature Project

PingCAP Incubator TiDB TUG TiDB TUG TiDB Community PMC

2020 3 PingCAP Incubator

- TiDB 4.0 TiDB Dashboard( TiDB Key Visualization, )
- TiDB - TiDB In Action48 Book Rush
- TiDB - TiUP
- - Talent Plan Courses(TinySQL/TinyKV)
- AskTUG Discourse PG TiDB
- TiDB - TiDB Wasm

# 2.6 PingCAP University —— Embrace Unlimited Possibilities

PingCAP University PingCAP

PingCAP University

- TiDB DBA PCTAPingCAP Certificated TiDB Associate— PingCAP TiDB PCTPPingCAP Certified TiDB Professional— PingCAP TiDB
- TiDB Talent Plan

PingCAP PingCAP TiDB DBA TiDB TiDB

## 2.6.1 TiDB DBA

### 1.

TiDB DBA 2018 10 2019 1 2020 3 7 2000 11 400 PCTA PCTP TiDB

### 2.

**(1)** TiDB

**(2)** TiDB

**(3)** TiDB NewSQL

**(4)** PCTA PCTP

## 2.6.2 TiDB DBA

TiDB PingCAP University TiDB DBA TiDB DBA 2.0 2019 6

- 2.0
- 2.0
- 2.0 TiDB HTAP TiDB

- 2.0  1.0  Demo show

TiDB DBA  2.0

| 课程类别 | 培训课程 | 培训目标 | 考试认证 |
|---|---|---|---|
| 基础知识 | 一、概述 【2 课时】 | 初级 TiDB DBA<br>需要学习并熟练掌握如下内容：<br>TiDB 概论、架构简介<br>TiDB 集群管理概述及使用实操<br>TiDB SQL 与调优<br>TiDB 对象管理与维护<br>TiDB 同构和异构平台数据迁移解决方案及实操<br>TiDB 备份与恢复原理及实操<br>TiDB 集群监控报警及日志管理<br>TiDB 常见问题处理<br>TiDB 业务开发最佳实践及应用案例介绍<br>TiDB 性能 Benchmark 介绍 | PCTA：<br>PingCAP Certified<br>TiDB Associate |
| | 二、系统安装部署与管理 【3 课时】 | | |
| | 三、使用管理手册 【2 课时】 | | |
| | 四、生态工具 【6.5 课时】 | | |
| | 五、备份恢复 【1 课时】 | | |
| | 六、TiDB 监控与告警 【2 课时】 | | |
| | 七、业务开发优化 【2 课时】 | | |
| | 总结综述 | | |
| 高级进阶 | 八、TiDB 计算内核体系 【4 课时】 | 高级 TiDB DBA<br>需要学习并熟练掌握如下内容：<br>TiDB Server 原理<br>PD 原理<br>TiKV 原理及架构<br>深入 Coprocessor 原理<br>TiDB Server 性能调优<br>TiKV 性能调优<br>TiDB 分布式事务原理<br>TiDB SQL 实现原理<br>TiDB SQL 性能调优<br>TiDB 高可用原理、方案及实战 | PCTP：<br>PingCAP Certified<br>TiDB Professional |
| | 九、TiKV 存储内核体系 【4 课时】 | | |
| | 十、事务 【4 课时】 | | |
| | 十一、系统性能优化 【5 课时】 | | |
| | 十二、SQL 优化 【8.5 课时】 | | |
| | 十三、高可用及容灾 【3 课时】 | | |

## 1.

PingCAP University TiDB DBA  PCTA  TiDB

## 2.

PCTA  PCTP 6*8/=483

11  400  100

> - ——
> - TiDB——
> - —— IT
> - ——
> - Binlog DM ——Mike
> - TiDB ——
> - TiDB ——
> - B TiDB ——
> - PingCAP University ——

## 2.6.3 TiDB DBA

PCTA PCTP DBA TiDB PingCAP

PCTA PingCAP Certified TiDB Associate PingCAP TiDB PCTA PCTA TiDB

PCTPPingCAP Certified TiDB Professional PingCAP TiDB PCTP PCTP TiDB FeatureSQL Trouble Shooting PCTP PCTA

PCTA PCTP TiDB 3.0

- AskTUG
- PingCAP University PCTA 18 20
- PingCAP University PCTA PCTP TiDB
- PCTA PCTP

# 2.7 AskTUG

## 2.7.1 AskTUG

“ TiDB ”TUG TiDB AskTUG 2019 8 TUG “”TiDB TiDB

AskTUG 2019 2 AskTUG 1500+ 1300+ 100+ 100+

## 2.7.2 AskTUG

AskTUG 80% UGC

- AskTUG TiDB AskTUG 100% TiDB
- TiDB
- TiDB TUG AskTUG AskTUG
- AskTUG Weekly

TUG AskTUG “”“” TiDB TiDB

## 2.7.3

> - AskTUG TiDB AskTUG AskTUG
> - AskTUG AskTUG

## 2.7.4 AskTUG

AskTUG “”“” 2020 AskTUG

- PingCAP PingCAP “”
- AskTUG POC SOP Case Study FAQ
- AskTUG UI
- AskTUG “”

TUG AskTUG

# 2.8 Contribution Map

## 2.8.1 Contribution Map

TiDB 2020.3.7 GitHub 22.7K star 400 contributors TiDB TiDB Contribution MapContribution Map contributor

- Contribution Map contributor
- Contribution Map What I Can Contribute contributor
- Contribution Map Learning Materials contributor
- Contribution Map SIGSpecial Interest Group SIG tech-lead mentors SIG TiDB community TiKV community SIG

### 2.8.2 Contribution Map

Contribution Map TiDB MySQL HTAP TiKV KV

# A map that guides what and how contributors can contribute

## Table of Contents


- TiDB is an open-source distributed HTAP database compatible with the MySQL protocol
- TiKV, distributed transactional key-value database
- PD Placement driver for TiKV
- TiKV Clients
- Libraries depended by TiKV
- Ecosystem Tools: DM Data Migration Platform
- Ecosystem Tools - Binlog : A tool used to collect and merge tidb's binlog for real-time data backup and synchronization
- Ecosystem Tools - Lightning: A high-speed data import tool for TiDB
- Ecosystem Tools - BR: A command-line tool for distributed backup and restoration of the TiDB cluster data
- TiDB on K8S/Docker : Creates and manages TiDB clusters running in Kubernetes
- Deployment Tools - tidb-ansible: A tool to capture data change of TiDB cluster
- Chaos-Mesh: A Chaos Engineering Platform for Kubernetes
- Documentation
- AskTUG(CN)
- PingCAP University(CN)
- SIG - Special Interest Group


6 TiKV

## TiKV, distributed transactional key-value database

| *Module* | *Description* | *Code Directory* | *Required Skills* | *Learning Materials* | *What I can Contribute* | *Contributing Tutorials* |
|---|---|---|---|---|---|---|
| Util | Utilities like thread-pool, logger, encoding and decoding, etc. | Utilities, Pipeline batch system | Rust | Rust book, Practical networked applications in Rust, Protocol buffers, TiKV source code reading: service layer(CN), gRPC concepts | Issues want help | Land your first Rust PR in TiKV, Became TiKV Contributor in 30 minutes(CN) |
| Network | Network layer | Server | Rust, Protobuf, gRPC | Ditto | Ditto | Ditto |
| Raw KV API | | API entrance, Storage struct | Rust | Ditto | Ditto | Ditto |
| Transaction KV API | | API entrance, Implementation of Transaction, GC worker, Pessimistic transaction | Rust, 2PC, Percolator transaction model | Two Phase Commit, Percolator paper, TiKV source code reading : storage(CN), TiKV source code reading : distributed transaction(CN), TiKV source code reading MVCC read(CN) | | |
| Multi-raft | | Raftstore | Rust, Raft | Rust book, Practical networked applications in Rust, Raft paper, Raft implementation in etcd | | |
| Engine | | Engine traits, Engine rocks | Rust, RocksDB | | Engine abstraction | |
| Coprocessor | | TiDB query, TiDB query codegen, TiDB query datatype | Rust | TiKV source code reading : Coprocessor Overview(CN), TiKV source code reading : Coprocessor Executor | Coprocessor Issues | |
| Backup | | Backup source code | | | | |

Contribution Map contributors