

Tidy Survey Analysis in R using the `srvyr` Package

Workshop Day 2 - Continuous Data

Stephanie Zimmer, Abt Associates

Rebecca Powell, RTI International

Isabella Velásquez, RStudio

April 22, 2022

Introduction

Overview

- At the end of this workshop series, you should be able to
 - Calculate point estimates and their standard errors with survey data
 - Proportions, totals, and counts
 - Means, quantiles, and ratios
 - Perform t-tests and chi-squared tests
 - Fit regression models
 - Specify a survey design in R to create a survey object
- We will not be going over the following but provide some resources at the end
 - Weighting (calibration, post-stratification, raking, etc.)
 - Survival analysis
 - Nonlinear models

About Us



Stephanie Zimmer
Abt Associates



Rebecca Powell
RTI International



Isabella Velásquez
RStudio

Thank you to our volunteers!

Raphael Nishimura will be assisting during our breakout rooms.

About This Workshop

- Hosted by Midwest Association for Public Opinion Research (MAPOR), a regional chapter of the American Association for Public Opinion Research (AAPOR).
- Originally delivered at AAPOR Conference in May 2021

Midwest Association
for Public Opinion Research



Upcoming Work

- Book on analyzing survey data in R, published by CRC, Taylor & Francis Group
- We would love your help! After each course, we will send out a survey to gather your feedback on the material, organization, etc.
- Keep updated by following our project on GitHub: <https://github.com/tidy-survey-r>

Overview

- Last week we introduced how to do survey analysis in R with categorical data
- Today we focus on continuous data
- At the end of today, you should be able to
 - Calculate means and quantiles with their standard errors
 - Perform t-tests
 - Fit linear regression models
- Next week, we will discuss
 - Specifying a survey design object
 - Creating replicate weights
 - Creating derived/analysis/recoded variables
 - Reproducibility

Overview: Workshop 2 Roadmap

- Quick refresh of RStudio Cloud with a warm-up exercise using the tidyverse
- Introduce the survey data we'll be using today
- Calculate point estimates for continuous data with time for practice
- Significance testing with t-test and linear regression models with time for practice
- Closing

Logistics

- We will be using RStudio Cloud today to ensure everyone has access
- Sign-up for a free RStudio Cloud account (<https://rstudio.cloud/>)
- Access the project and files via link in email and Zoom chat
- Click "START" to open the project and get started
- RStudio Cloud has the same features and appearance as RStudio for ease of use
- All slides and code are available on GitHub: <https://github.com/tidy-survey-r/tidy-survey-short-course>

Intro to RStudio Cloud: Penguins!!

- Using `palmerpenguins` data for warm-up exercises
- Data were collected and made available by Dr. Kristen Gorman and the Palmer Station, Antarctica LTER, a member of the Long Term Ecological Research Network.
- Access data through `palmerpenguins` package <https://github.com/allisonhorst/palmerpenguins/>

If you are using your own RStudio environment:

- Make sure you have `tidyverse`, `here`, and `palmerpenguins` installed

```
# Run package installation if you don't have these packages already
# As a reminder, installing takes package from internet to your computer
# and only needs to be done once, not each session

install.packages(c("tidyverse", "here", "palmerpenguins"))
```

Intro to RStudio Cloud: Penguins!!

- Load `tidyverse`, `here`, and `palmerpenguins`
- Look at the penguins dataset using `glimpse`

```
library(tidyverse) # for tidyverse
library(here) # for file paths
library(palmerpenguins) # for warm-up data
glimpse(penguins)
```

```
## Rows: 344
## Columns: 8
## $ species      <fct> Adelie, Adelie, Adelie, Adelie, Adelie, Adel...
## $ island        <fct> Torgersen, Torgersen, Torgersen, Torgersen, Torgers...
## $ bill_length_mm <dbl> 39.1, 39.5, 40.3, NA, 36.7, 39.3, 38.9, 39.2, 34.1, ...
## $ bill_depth_mm  <dbl> 18.7, 17.4, 18.0, NA, 19.3, 20.6, 17.8, 19.6, 18.1, ...
## $ flipper_length_mm <int> 181, 186, 195, NA, 193, 190, 181, 195, 193, 190, 186...
## $ body_mass_g    <int> 3750, 3800, 3250, NA, 3450, 3650, 3625, 4675, 3475, ...
## $ sex            <fct> male, female, female, NA, female, male, female, male...
## $ year           <int> 2007, 2007, 2007, 2007, 2007, 2007, 2007, 2007, 2007...
```

Warm-up Exercises: WarmUpExercises.Rmd

- Let's open RStudio cloud and do some warm-up examples
- Take 8 minutes to do these exercises in breakout rooms.
- Explore the penguins data
 - What is the mean body mass in grams of all penguins? Hint: use `summarize` and remove missing data
 - What is the mean length of flipper by species? Hint: use `group_by`
 - What is the mean flipper length by species and sex?
 - Fit a simple linear regression between body mass and flipper length.

Ex. 1: What is the mean body mass in grams of all penguins? Hint: use **summarize** and remove missing data

```
penguins %>%
  summarize(
    MeanBodyMass=mean(body_mass_g,
                       na.rm=TRUE))

## # A tibble: 1 × 1
##   MeanBodyMass
##       <dbl>
## 1     4202.
```

Ex. 2: What is the mean length of flipper by species?

Hint: use **group_by**

```
penguins %>%
  group_by(species) %>%
  summarize(
    MeanFlipperLength=mean(flipper_length_mm,
                           na.rm=TRUE))
```

```
## # A tibble: 3 × 2
##   species  MeanFlipperLength
##   <fct>          <dbl>
## 1 Adelie       190.
## 2 Chinstrap    196.
## 3 Gentoo      217.
```

Ex. 3: What is the mean flipper length by species and sex?

```
penguins %>%  
  group_by(species,sex) %>%  
  summarize(  
    MeanFlipperLength=mean(flipper_length_mm,  
                            na.rm=TRUE))
```

```
## # A tibble: 8 × 3  
## # Groups:   species [3]  
##   species   sex   MeanFlipperLength  
##   <fct>     <fct>      <dbl>  
## 1 Adelie    female     188.  
## 2 Adelie    male      192.  
## 3 Adelie    <NA>      186.  
## 4 Chinstrap female     192.  
## 5 Chinstrap male      200.  
## 6 Gentoo   female     213.  
## 7 Gentoo   male      222.  
## 8 Gentoo   <NA>      216.
```

Ex. 4: Fit a simple linear regression between body mass and flipper length.

```
mod1 <- lm(body_mass_g ~ flipper_length_mm, data=penguins)
summary(mod1)

##
## Call:
## lm(formula = body_mass_g ~ flipper_length_mm, data = penguins)
##
## Residuals:
##     Min      1Q  Median      3Q     Max 
## -1058.80  -259.27   -26.88   247.33  1288.69 
##
## Coefficients:
##             Estimate Std. Error t value Pr(>|t|)    
## (Intercept) -5780.831   305.815  -18.90   <2e-16 ***
## flipper_length_mm    49.686     1.518   32.72   <2e-16 ***
## ---
## Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1
##
## Residual standard error: 394.3 on 340 degrees of freedom
##   (2 observations deleted due to missingness)
## Multiple R-squared:  0.759,    Adjusted R-squared:  0.7583 
## F-statistic: 1071 on 1 and 340 DF,  p-value: < 2.2e-16
```

Continuous survey data analysis

Overview of Survey Analysis using `srvyr` Package

1. Create a `tbl_svy` object using: `as_survey_design` or `as_survey_rep`
2. Subset data (if needed) using `filter` (subpopulations)
3. Specify domains of analysis using `group_by`
4. Within `summarize`, specify variables to calculate including means, medians, quantiles and more

Note: We will be teaching this in the reverse order!!!

Dataset: Residential Energy Consumption Survey (RECS) 2015

- Energy consumption/expenditures collected through energy suppliers
- Fielded 14 times between 1950 and 2015
- Topics include appliances, electronics, heating, a/c, temperatures, water heating, lighting, energy bills, respondent demographics, and energy assistance
- Funded by the Energy Information Administration
- **Target Population:** Primary occupied housing units in the US
- **Mode:** In-person, paper, and web interview mode
- **Sample Information:** BRR Replicate weights included for variance estimation

<https://www.eia.gov/consumption/residential/index.php>

Set-up for Analysis

- `srvyr` package uses tidy-syntax but uses the `survey` package behind it to do calculations
- If using your own RStudio environment, install both packages:

```
# Install survey and srvyr packages  
  
remotes::install_github("bschneidr/r-forge-survey-mirror")  
install.packages("srvyr")
```

- First, we will set-up a design object and talk about what it means in Session 3

```
library(survey) # for survey analysis  
library(srvyr) # for tidy survey analysis  
  
recs <- read_rds(here("Data", "recs.rds"))  
  
recs_des <- recs %>%  
  as_survey_rep(weights=NWEIGHT,  
                repweights=starts_with("BRRWT"),  
                type="Fay",  
                rho=0.5,  
                mse=TRUE)
```

Weighted Analysis for Continuous Variables

- Common functions for continuous summaries
 - `survey_mean`
 - `survey_total` (like `sum`)
 - `survey_median`
 - `survey_quantile`
 - `survey_ratio`
- Always call within `summarize/summarise`

survey_mean Syntax

```
survey_mean(  
  x,  
  na.rm = FALSE,  
  vartype = c("se", "ci", "var", "cv"),  
  level = 0.95,  
  proportion = FALSE,  
  deff = FALSE,  
  df = NULL,  
  ...  
)
```

To calculate a survey mean, we use this in `summarize/summarise`

```
survey_design_object %>%  
  summarize(  
    mean_varname=survey_mean(x = continuous_varname)  
  )
```

survey_mean Example 1: On average, how much do US households spend on energy each year?

This is an example using the `recs_des` survey design object and `survey_mean` function defaults

```
recs_des %>%
  summarize(
    TD_mean=survey_mean(x = TOTALDOL)
  )
```

```
## # A tibble: 1 × 2
##   TD_mean  TD_mean_se
##     <dbl>      <dbl>
## 1 1859.       15.6
```

survey_mean Example 2: What is the average temperature US households set their homes to on a summer day?

Run this code. What happens?

```
recs_des %>%
  summarize(
    TD_mean=survey_mean(x = SummerTempDay)
  )
```

survey_mean Example 2: What is the average temperature US households set their homes to on a summer day?

Run this code. What happens?

```
recs_des %>%
  summarize(
    TD_mean=survey_mean(x = SummerTempDay)
  )

## Error in `dplyr::summarise()`:
## ! Problem while computing `TD_mean = survey_mean(x = SummerTempDay)` .
## Caused by error in `svrVar()`:
## ! All replicates contained NAs
```

How do we fix this code?

survey_mean Example 2: Missing data solution

```
recs_des %>%
  summarize(
    TD_mean = survey_mean(
      x = SummerTempDay,
      na.rm = TRUE )
  )
```

```
## # A tibble: 1 × 2
##   TD_mean TD_mean_se
##       <dbl>     <dbl>
## 1     72.4     0.0793
```

survey_median Syntax

```
survey_median(  
  x,  
  na.rm = FALSE,  
  vartype = c("se", "ci"),  
  level = 0.95,  
  df = NULL,  
  ...  
)
```

survey_median Example: What is the median temperature US households set their homes to on a summer day?

```
recs_des %>%  
  summarize(  
    TD_median=survey_median(x=_____,  
                               na.rm=_____)  
  )
```

```
recs_des %>%  
  summarize(  
    TD_median=survey_median(x=SummerTempDay,  
                               na.rm=TRUE)  
  )
```

```
## # A tibble: 1 × 2  
##   TD_median TD_median_se  
##       <dbl>      <dbl>  
## 1        72     0.252
```

survey_quantile Syntax

```
survey_quantile(  
  x,  
  quantiles,  
  na.rm = FALSE,  
  vartype = c("se", "ci", "var", "cv"),  
  level = 0.95,  
  df = NULL,  
  ...  
)
```

survey_quantile Example 1: What are the 1st and 3rd quantile of dollars spent on energy?

```
recs_des %>%
  summarize(
    Spent=survey_quantile(
      x = TOTALDOL,
      quantiles = c(.25, .75))
  )

## # A tibble: 1 × 4
##   Spent_q25  Spent_q75  Spent_q25_se  Spent_q75_se
##     <dbl>     <dbl>       <dbl>       <dbl>
## 1     1153.     2353.       13.9        22.7
```

survey_quantile Example 2: What are the 1st and 3rd quantile of dollars spent on energy with confidence intervals?

```
recs_des %>%
  summarize(
    Spent=survey_quantile(x = TOTALDOL,
                           quantiles = c(.25, .75),
                           vartype = "ci")
  )

## # A tibble: 1 × 6
##   Spent_q25  Spent_q75  Spent_q25_low  Spent_q75_low  Spent_q25_upp  Spent_q75_upp
##   <dbl>      <dbl>       <dbl>        <dbl>       <dbl>        <dbl>
## 1     1153.     2353.      1124.        2310.      1179.        2400.
```

survey_quantile Updated Output

```
recs_des %>%
  summarize(
    Spent=survey_quantile(x = TOTALDOL,
                           quantiles = c(.25, .75),
                           vartype = "ci"
    )
  ) %>%
  pivot_longer(cols=c(Spent_q25:Spent_q75_upp),
               names_to="varname",values_to="value") %>%
  mutate(Quantile=paste0(str_sub(varname,8,9),"th Quantile"),
         type=case_when(str_detect(varname,"_low")~"Lower_Bound",
                        str_detect(varname,"_upp")~"Upper_Bound",
                        TRUE~"Estimate")) %>%
  pivot_wider(id_cols=Quantile,names_from=type,values_from=value)

## # A tibble: 2 × 4
##   Quantile     Estimate Lower_Bound Upper_Bound
##   <chr>        <dbl>      <dbl>      <dbl>
## 1 25th Quantile 1153.      1124.      1179.
## 2 75th Quantile 2353.      2310.      2400.
```

survey_ratio Syntax

- Note this estimates: $\sum x_i / \sum y_i$ not $\sum \frac{x_i}{y_i}$

```
survey_ratio(  
  numerator,  
  denominator,  
  na.rm = FALSE,  
  vartype = c("se", "ci", "var", "cv"),  
  level = 0.95,  
  deff = FALSE,  
  df = NULL,  
  ...  
)
```

survey_ratio Example: What is the average dollar per BTU spent on energy?

```
recs_des %>%
  summarize(
    DolPerBTU=survey_ratio(
      numerator = TOTALDOL,
      denominator = TOTALBTU,
      na.rm = TRUE
    )
  )

## # A tibble: 1 × 2
##   DolPerBTU DolPerBTU_se
##       <dbl>      <dbl>
## 1     0.0241    0.000217
```

Breakout rooms: Practice time

- Open ContinuousExercises.Rmd and work through Part 1
- We will take 15 minutes. Use this time for the exercises and questions.

Weighted Analysis for Continuous Variables: Domain Analysis

- If we want to get estimates by another variable, we need to add a `group_by` statement before doing the analysis.
- Example: What is the average amount of dollars spent on electricity for households that use AC and those that do not use AC?

```
rechs_des %>%  
  group_by(ACUsed) %>%  
  summarize(  
    ElBill=survey_mean(DOLLAREL,  
                        na.rm=TRUE)  
  )
```

```
## # A tibble: 2 × 3  
##   ACUsed   ElBill   ElBill_se  
##   <lgl>     <dbl>     <dbl>  
## 1 FALSE      972.     25.8  
## 2 TRUE       1435.    15.8
```

Domain Analysis: Totals

- If we want the overall average electric bill too, use the `cascade` function instead of `summarize`

```
recs_des %>%
  group_by(ACUsed) %>%
  cascade(
    ElBill=survey_mean(DOLLAREL,
                        na.rm=TRUE)
  )
```

```
## # A tibble: 3 × 3
##   ACUsed   ElBill   ElBill_se
##   <lgl>     <dbl>     <dbl>
## 1 FALSE     972.     25.8
## 2 TRUE      1435.    15.8
## 3 NA        1375.    14.1
```

Note: The overall average electric bill appears as NA

Domain Analysis: Totals

- Also can add sample and pop sizes

```
recs_des %>%
  group_by(ACUsed) %>%
  cascade(
    ElBill=survey_mean(DOLLAREL, na.rm=TRUE),
    N=survey_total(!is.na(DOLLAREL)),
    n=unweighted(sum(!is.na(DOLLAREL)))
  )

## # A tibble: 3 × 6
##   ACUsed  ElBill  ElBill_se          N      N_se     n
##   <lgl>    <dbl>    <dbl>        <dbl>    <dbl> <int>
## 1 FALSE     972.    25.8  15401242.  976901.     737
## 2 TRUE      1435.   15.8  102807008.  976901.    4949
## 3 NA       1375.   14.1  118208250.    0.0320  5686
```

Weighted Analysis for Specific Subpopulations

- filtering (subsetting) the data should be done AFTER specifying the design to ensure accurate standard errors
- Use the `filter` function after creating the survey design object and before summarizing

Wrong way:

```
data %>%
  filter(state=="NC") %>%
  as_survey_design(...) %>%
  summarize(AvgAge=mean(Age))
```

Right way:

```
data %>%
  as_survey_design(...) %>%
  filter(state=="NC") %>%
  summarize(AvgAge=mean(Age))
```

Subpopulation Example: Average electric cost of single family homes

```
recs_des %>%
  filter(HousingUnitType %in% c("Single-family detached",
                                "Single-family attached")) %>%
  summarize(
    ElBill=survey_mean(DOLLAREL,
                        na.rm=TRUE)
  )
```

```
## # A tibble: 1 × 2
##   ElBill  ElBill_se
##     <dbl>      <dbl>
## 1 1542.       17.2
```

Comparisons with t-tests: **svyttest** Syntax

- t-tests are done in the package [survey](#) not [srvyr](#) but you can use the same design object

```
svyttest(formula, # outcome~group for two-sample, outcome~0 for one-sample  
         design,  
         na.rm = FALSE  
         ....)
```

svyttest Syntax with %>%

```
recs_des %>%  
  svyttest(formula=,  
           design=.,  
           na.rm=TRUE)
```

svyttest Syntax with %>%

```
recs_des %>%  
  svyttest(design=.,  
           formula=,  
           na.rm=TRUE)
```

svyttest Example 1: One-sample t-test

- I keep my house at 68 degrees at night during the summer. Is this different from the national average?

```
recs_des %>%
  svyttest(design=.,
            formula=I(SummerTempNight-68)~0,
            na.rm=TRUE)

##
##      Design-based one-sample t-test
##
## data: I(SummerTempNight - 68) ~ 0
## t = 41.013, df = 94, p-value < 2.2e-16
## alternative hypothesis: true mean is not equal to 0
## 95 percent confidence interval:
##  3.424776 3.773247
## sample estimates:
##   mean
## 3.599012
```

svyttest Example 2: Comparing two variables

- Do people keep their house the same temperature at night during the summer and the winter?

```
recs_des %>%
  svyttest(design=.,
            formula=I(SummerTempNight-WinterTempNight)~0,
            na.rm=TRUE)

##
##      Design-based one-sample t-test
##
## data: I(SummerTempNight - WinterTempNight) ~ 0
## t = 29.079, df = 94, p-value < 2.2e-16
## alternative hypothesis: true mean is not equal to 0
## 95 percent confidence interval:
##  2.995084 3.434072
## sample estimates:
##      mean
## 3.214578
```

svyttest Example 3: Two-sample t-test

- Are electric bills different between those with and without A/C?

```
recs_des %>%
  svyttest(design=.,
            formula=DOLLAREL~ACUsed,
            na.rm=TRUE)

##
##      Design-based t-test
##
## data: DOLLAREL ~ ACUsed
## t = 14.772, df = 94, p-value < 2.2e-16
## alternative hypothesis: true difference in mean is not equal to 0
## 95 percent confidence interval:
##  400.6588 525.0903
## sample estimates:
## difference in mean
##                 462.8746
```

Linear Regression or ANOVA: **svyglm** Syntax

- As with t-tests, regressions are done in the package `survey` not `svy` but you can use the same design object
- Syntax is similar between t-test and `glm`

```
svyglm(formula,  
       design,  
       na.action, #default is na.omit  
       ....)
```

svyglm Example: Two-sample

Same example as two-sample t-test: Are electric bills different between those with and without A/C?

t-test:

```
recs_des %>%
  svyttest(design=.,
            formula=DOLLAREL~ACUsed,
            na.rm=TRUE)
```

glm:

```
recs_des %>%
  svyglm(design=.,
          formula=DOLLAREL~ACUsed,
          na.action=na.omit)
```

svyglm Example: Two-sample

Are electric bills different between those with and without A/C?

```
recs_des %>%
  svyglm(design=.,
         formula=DOLLAREL~ACUsed,
         na.action=na.omit) %>%
  summary()

##
## Call:
## svyglm(design = ., formula = DOLLAREL ~ ACUsed, na.action = na.omit)
##
## Survey design:
## Called via srvyr
##
## Coefficients:
##             Estimate Std. Error t value Pr(>|t|)
## (Intercept) 972.09     25.81   37.66  <2e-16 ***
## ACUsedTRUE   462.87     31.33   14.77  <2e-16 ***
## ---
## Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1
##
## Dispersion parameter for gaussian family taken to be 3543220488
##
## Number of Fisher Scoring iterations: 2
```

svyglm Example 1: ANOVA Test

Does temperature of AC at night vary by region?

```
recs_des %>%
  svyglm(design=.,
         formula=SummerTempNight~Region,
         na.action=na.omit) %>%
  summary()

##
## Call:
## svyglm(design = ., formula = SummerTempNight ~ Region, na.action = na.omit)
##
## Survey design:
## Called via srvyr
##
## Coefficients:
##             Estimate Std. Error t value Pr(>|t|)
## (Intercept) 70.4848    0.1968 358.151 < 2e-16 ***
## RegionMidwest 0.8744    0.2526   3.461 0.000818 ***
## RegionSouth  1.4865    0.2306   6.446 5.20e-09 ***
## RegionWest   1.6568    0.3529   4.695 9.27e-06 ***
## ---
## Signif. codes: 0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1
##
## (Dispersion parameter for gaussian family taken to be 119075)
##
## Number of Fisher Scoring iterations: 2
```

svyglm Example 2: Linear Model

- Is there a relationship between square footage and electric bill?
- Let's review the data first with a ggplot. *Note we use the original data and do NOT use the survey design object.*

```
p <- recs %>%
  ggplot(aes(x=TOTSQFT_EN, y=DOLLAREL, weight=NWEIGHT)) +
  geom_hex(color="white") +
  scale_fill_gradient(guide="colourbar", name="Count of Housing Units", labels=comma)
```

svyglm Example 2: Linear Model

svyglm Example 2: Linear Model

```
m_electric_sqft <- recs_des %>%
  svyglm(design=.,
         formula=DOLLAREL~TOTSQFT_EN,
         na.action=na.omit)
summary(m_electric_sqft)

##
## Call:
## svyglm(design = ., formula = DOLLAREL ~ TOTSQFT_EN, na.action = na.omit)
##
## Survey design:
## Called via srvyr
##
## Coefficients:
##             Estimate Std. Error t value Pr(>|t|)
## (Intercept) 879.89542   26.31370   33.44   <2e-16 ***
## TOTSQFT_EN    0.24633    0.01338   18.42   <2e-16 ***
## ---
## Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1
##
## (Dispersion parameter for gaussian family taken to be 3125448288)
##
## Number of Fisher Scoring iterations: 2
```

Breakout rooms: Practice time

- Open ContinuousExercises.Rmd and work through Part 2
- We will take 15 minutes. Use this time for the exercises and questions.

Closing

Resources for more learning

- <https://cran.r-project.org/web/packages/srvyr/vignettes/srvyr-vs-survey.html>
- <https://r-survey.r-forge.r-project.org/survey/>
 - Includes more advanced modeling

Thank You!

We hope you learned a lot in this session!

Please let us know if you have any feedback on this workshop. All feedback is welcome!

Questions?

Sources

- *Residential Energy Consumption Survey: Using the 2015 Microdata File to Compute Estimates and Standard Errors.* U.S. Department of Energy (2017)
https://www.eia.gov/consumption/residential/data/2015/pdf/microdata_v3.pdf
- Horst AM, Hill AP, Gorman KB (2020). palmerpenguins: Palmer Archipelago (Antarctica) penguin data. R package version 0.1.0. <https://allisonhorst.github.io/palmerpenguins/>
- T. Lumley (2020) "survey: analysis of complex survey samples". R package version 4.0. <https://r-survey.r-forge.r-project.org/survey/>
- Greg Freedman Ellis and Ben Schneider (2020). srvyr: 'dplyr'-Like Syntax for Summary Statistics of Survey Data. R package version 1.0.0. <https://CRAN.R-project.org/package=srvyr>
- Hadley Wickham, Romain François, Lionel Henry and Kirill Müller (2021). dplyr: A Grammar of Data Manipulation. R package version 1.0.5. <https://CRAN.R-project.org/package=dplyr>

Session info - platform

```
## setting  value
## version  R version 4.1.2 (2021-11-01)
## os        macOS Big Sur 10.16
## system   x86_64, darwin17.0
## ui        X11
## language (EN)
## collate   en_US.UTF-8
## ctype     en_US.UTF-8
## tz        America/New_York
## date      2022-04-12
## pandoc   2.14.0.3 @ /Applications/RStudio.app/Contents/MacOS/pandoc/ (via rmarkdown)
```

Session info - packages

```
##   package      * version date (UTC) lib source
## dplyr          * 1.0.8   2022-02-08 [1] CRAN (R 4.1.2)
## forcats        * 0.5.1   2021-01-27 [1] CRAN (R 4.1.0)
## ggplot2        * 3.3.5   2021-06-25 [1] CRAN (R 4.1.0)
## here           * 1.0.1   2020-12-13 [1] CRAN (R 4.1.0)
## hexbin         * 1.28.2  2021-01-08 [1] CRAN (R 4.1.0)
## knitr          * 1.38    2022-03-25 [1] CRAN (R 4.1.2)
## Matrix          * 1.4-0   2021-12-08 [1] CRAN (R 4.1.0)
## palmerpenguins * 0.1.0   2020-07-23 [1] CRAN (R 4.1.0)
## purrr          * 0.3.4   2020-04-17 [1] CRAN (R 4.1.0)
## readr           * 2.1.2   2022-01-30 [1] CRAN (R 4.1.2)
## remotes         * 2.4.2   2021-11-30 [1] CRAN (R 4.1.0)
## scales          * 1.1.1   2020-05-11 [1] CRAN (R 4.1.0)
## srvyr          * 1.1.1   2022-02-20 [1] CRAN (R 4.1.2)
## stringr         * 1.4.0   2019-02-10 [1] CRAN (R 4.1.0)
## survey          * 4.1-1   2021-07-19 [1] CRAN (R 4.1.0)
## survival        * 3.2-13  2021-08-24 [1] CRAN (R 4.1.2)
## tibble          * 3.1.6   2021-11-07 [1] CRAN (R 4.1.0)
## tidyverse        * 1.3.1   2021-04-15 [1] CRAN (R 4.1.0)
## xaringan        * 0.22    2021-06-23 [1] CRAN (R 4.1.0)
##
## [1] /Library/Frameworks/R.framework/Versions/4.1/Resources/library
```