

Send MSG File API

Accept a booking .msg file plus a category. When category is "HubSpot deal", forwards the .msg to the email-to-deal/msg endpoint.

URL

```
https://tidystack-app.vercel.app/api/send-msg-file
```

Local: `http://localhost:3000/api/send-msg-file`

Method

POST

3 ways to send the .msg file

Every request also needs a category (string). Supported value today: "HubSpot deal".

Option 1: File upload (recommended)

Best for Postman, Zapier, and most no-code tools.

- Content-Type: multipart/form-data
- Field name: msg (File) - the .msg file. Also accepted: file, email
- Field name: json (Text) - e.g. {"category": "HubSpot deal"}

Also accepted for category: multipart fields data / info / payload (JSON), or a plain category text field.

Postman

1. Method: POST
2. Body -> form-data
3. Key: msg -> change type to File -> pick your .msg
4. Key: json -> Text -> {"category": "HubSpot deal"}

Zapier (Webhooks by Zapier)

1. Action: POST
2. Payload type: form
3. Field: msg = attachment file from the previous step
4. Field: json = {"category": "HubSpot deal"}

curl

```
curl -X POST "https://tidystack-app.vercel.app/api/send-msg-file" \
  -F "msg=@/path/to/booking.msg" \
  -F "json={\"category\": \"HubSpot deal\"}"
```

Option 2: Raw .msg as the request body

Put the entire .msg file bytes in the request body (not JSON, not a form).

- Content-Type: application/vnd.ms-outlook (preferred)
- Content-Type: application/octet-stream
- Content-Type: application/x-ole-storage

Because the body is only the file, pass category with a header or query param:

- Header: X-Category: HubSpot deal
- Or query: ?category=HubSpot%20deal

Postman

1. Method: POST
2. Headers -> X-Category = HubSpot deal
3. Body -> binary -> Select File -> pick your .msg
4. Also set Content-Type header to application/vnd.ms-outlook (or application/octet-stream)

curl

```
curl -X POST "https://tidystack-app.vercel.app/api/send-msg-file" \
  -H "Content-Type: application/vnd.ms-outlook" \
  -H "X-Category: HubSpot deal" \
  --data-binary "@/path/to/booking.msg"
```

Option 3: JSON body

Best when you have the email as base64 or a download URL.

- Content-Type: application/json

Base64-encoded .msg

```
{
  "category": "HubSpot deal",
  "msg": "<base64-string>"
}
```

URL to download the .msg (must be publicly reachable)

```
{
  "category": "HubSpot deal",
  "msgUrl": "https://example.com/path/to/booking.msg"
}
```

Other accepted JSON field names for the file: file, email, attachment, url

Postman

1. Method: POST
2. Body -> raw -> JSON
3. Paste one of the JSON examples above

curl (URL example)

```
curl -X POST "https://tidystack-app.vercel.app/api/send-msg-file" \
  -H "Content-Type: application/json" \
  -d '{"category": "HubSpot deal", "msgUrl": "https://example.com/booking.msg"}'
```

Zapier: use Webhooks -> POST -> Payload type json. Easiest is msgUrl if you have a public file URL.

What happens

If category is "HubSpot deal", this route POSTs the .msg file to:

```
/api/highviewtravel/email-to-deal/msg
```

and returns that endpoint's response (same status code and JSON body).

Success response

When HubSpot create is disabled for Outlook testing, email-to-deal/msg returns a stub deal. Example of what is returned:

```
{
  "success": true,
  "hubspotDisabled": true,
  "passengerName": "Kristen Fung",
  "departureAirport": "LAX",
  "arrivalAirport": "KEF",
  "outboundDate": "17AUG",
  "returnDate": "02SEP",
  "cabinClass": "Business",
  "route": "International",
  "passengers": 1,
  "departureRegion": "US",
  "dealId": "TEST_DEAL_ID",
  "dealName": "Kristen Fung LAX KEF 17AUG/02SEP",
  "contactId": null,
  "contactEmail": "sender@example.com",
  "contactAssociated": false,
  "ownerId": null,
  "ownerEmail": null,
  "ownerAssigned": false
}
```

- hubspotDisabled: true means HubSpot deal creation is currently stubbed in email-to-deal/msg.
- dealId: "TEST_DEAL_ID" is the stub id while HubSpot create is disabled.
- When HubSpot is re-enabled, dealId / contactId / owner fields will be real HubSpot IDs.

Error responses

Missing file or category:

```
{
  "error": "Failed to process .msg file",
  "details": "Missing category..."
}
```

Unsupported category:

```
{
  "error": "Unsupported category: Something else",
  "supportedCategories": ["HubSpot deal"]
}
```

Upstream email-to-deal/msg failure (forwarded as-is):

```
{
  "error": "Failed to process .msg email and create HubSpot deal",
  "details": "..."
}
```