

Neural Exception Handling Recommender for Code Snippets

Anonymous Author(s)

ABSTRACT

With practical code reuse, the code fragments from developer forums often migrate to applications. Owing to the incomplete nature of such fragments, they often lack the details on exception handling. The adaptation for exception handling to the codebase is not trivial as developers must learn and memorize what API methods could cause exceptions and what exceptions need to be handled. We propose NEUREX, an exception handling recommender that learns from complete code, and accepts a given Java code snippet and recommends 1) if a try-catch block is needed, 2) what statements need to be placed in a try-catch block, and 3) what exception types need to be caught in the catch clause. Inspired by the sequence chunking techniques in natural language processing, we design NEUREX via a multi-tasking model with the fine-tuning of the large language model CodeBERT for the three above exception handling recommending tasks. Via the large language model, we enable NEUREX to learn the surrounding context, leading to better learning the identities of the APIs, and the relations between the statements and the corresponding exception types needed to be handled.

Our empirical evaluation shows that NEUREX correctly performs all three exception handling recommendation tasks with an F1-score of **XX.X%** (an relative improvement of up to **XX.X%** over the baselines). It achieves high F1-score from 98.2%–99.7% in try-catch block necessity checking (an relative improvement of up to 55.9% over the baselines). Moreover, it can correctly decide both the need of try-catch block(s) and the statements to be placed in such blocks with the accuracies of 74.7% and 87.1% at the instance and statement levels, an improvement of 128.7% and 44.9% over the baseline, respectively. Our extrinsic evaluation also shows that NEUREX relatively improves over the baseline by **9.6%** in F-score in detecting exception-related bugs in incomplete StackOverflow code snippets.

1 INTRODUCTION

The online question and answering (Q&A) forums, e.g., StackOverflow (S/O) provide important resources for developers to learn how to use software libraries and frameworks. While the code snippets in an S/O answer are good starting points, they are often incomplete with several missing details, even with ambiguous references, etc. Zhang *et al.* [15] have conducted a large-scale empirical study on the nature and extent of manual adaptations of the S/O code snippets by developers into their Github repositories. They reported that the adaptations from S/O code examples to their Github counterpart projects are prevalent. They qualitatively inspected all the adaptation cases and classified them into 24 different adaptation types. They highlighted several adaptation types including *type conversion*, *handling potential exceptions*, and *adding if checks* [15]. Among them, adding a try-catch block to wrap the code snippet and listing the handled exceptions in the catch clause are frequently performed, yet not automated by existing tools.

The adaptation process for exception handling is not trivial as Nguyen *et al.* [10] have reported that it is challenging for developers to learn and memorize what API methods could cause exceptions

and what exceptions need to be handled. Kechagia *et al.* [8] found that 19% of the crashes in Android applications could have been caused by insufficient documented exceptions in Android APIs. Thus, it is desirable to have an automated tool to recommend proper exception handling for the adaptation of online code snippets.

There exist several approaches to automatic recommendation of exception handling [2–4, 10, 13, 16]. They can be classified into four categories. The first category of approaches relies on a few *program analysis heuristics* on exception types, API calls, and variable types to recommend exception handling code [3]. These heuristic-based approaches do not always work in all cases due to incomplete code. The second category utilized *exception handling policies*, which are enforced in all cases [4, 9]. However, the policies need to be pre-defined and encoded within the recommending tools. This is not an ideal solution considering the fast evolution of software libraries. To enable more flexibility than policy enforcement, the third category leverages *mining algorithms* that derive similar exception handling for two similar code fragments [13]. While avoiding hard-coding of the rules, these mining approaches suffer the issue of how much similar for two fragments to be considered as having similar exception handling. For the mining approaches, deterministically setting a threshold for frequent occurrences is also challenging.

To provide more flexibility in code matching, the fourth category follows *information retrieval* (IR) [10]. XRank [10] takes as input source code and recommends a ranked list of API method calls in the code that are potentially involved in the exceptions in a catch-try block. XHand [10] recommends the exception handling code in a catch block for a given code. Both use a fuzzy set technique to compute the associations between the API calls (e.g., `newBufferedReader`) and the exceptions (e.g., `IOException`).

While the IR-based approach achieves higher accuracy than the others [10], it has key limitations. First, it is not trivial to **pre-define a threshold** for feature matching for a retrieval of an exception type or an API element. The effectiveness of those IR techniques depends much on the correct value of such pre-defined threshold. Second, the IR-based techniques rely on the lexical values of the code tokens and API elements, whose names can be *ambiguous* in an incomplete code snippet. For example, the `Document` class in `org.w3c.dom` of the W3C library has the same simple name as the `Document` class in `com.google.gwt.dom.client` of Google Web Toolkit library (GWT). An API method to open/write/read a `Document` in the W3C library might need to catch a different set of exceptions than the one in GWT. Those IR-based techniques are not sufficiently flexible to handle such **ambiguous names**. Third, the IR techniques *do not consider the context of surrounding code*, thus, cannot leverage the *dependencies* among API elements to resolve the ambiguity of the names of the APIs and exceptions in an incomplete snippet.

In this paper, we propose NEUREX, a learning-based exception handling recommender, which accepts a given Java code snippet and recommends 1) *whether a try-catch block is needed for the snippet* (XBLOCK), 2) *what statements need to be placed in a try-catch block* (XSTATE) and 3) *what exception types need to be caught in the*

catch *clause* (XTYPE). We find a motivation for such a data-driven, learning-based approach from the previous studies reporting that exception handling for the API elements is frequently repeated across different projects [13, 17]. The rationale is that the designers of a software library have the intents for users to use certain API elements with corresponding exception types. Thus, we design NEUREX to learn from the statements in try-catch blocks and the exception types retrieved from *complete source code* in a large code corpus, and derive the above exception handling suggestions for the (partial) code snippet under study.

We leverage and fine-tune the large language model CodeBERT [7] to capture the surrounding **context** with the dependencies among the API elements. Capturing such contextual information and the dependencies enable NEUREX to realize the idea “Tell Me Your Friends, I’ll Tell You Who You Are” to learn the **dependencies among statements with APIs** in a given (in)complete code, leading to better learning in XBLOCK, XSTATE and XTYPE. Inspired by sequence chunking in natural language processing (NLP), we formulate our problem as detecting one or multiple chunks of consecutive statements that need try-catch blocks. NEUREX also has the three tasks in a **multi-tasking** mechanism to enable the mutual impact among the learning, leading to better performance in all three tasks.

Our aforementioned idea gives NEUREX three advantages over the state-of-the-art IR approach. First, with the learning-based approach, NEUREX does not rely on a pre-defined threshold for explicit feature matching for the retrieval of the API elements or exception types. Second, instead of learning only the associations between the API elements and corresponding exception types, NEUREX has advantages in both predicting and training. During predicting, for a given incomplete code, the context enables NEUREX to *learn the identities of the API elements via the dependencies/relations* among them in the context, thus, avoiding the name ambiguity. Let us call it *dependency context*. During training, the complete code enables the identifications (i.e., the fully-qualified names) of the API elements. Third, the context of surrounding code also helps the model implicitly learn the important features to connect between the API elements and the corresponding exception types.

We have conducted several experiments to evaluate NEUREX. We have collected a large dataset of 5,726 projects from Github with 307,646 code snippets (half of them have try-catch blocks). Our empirical evaluation shows that NEUREX correctly performs all three exception handling recommendation tasks with an F1-score of **XX.X%** (an relative improvement of up to **XX.X%** over the baselines). It achieves high F1-score from 98.2%–99.7% in try-catch block necessity checking (an relative improvement of up to 55.9% over the baselines). Moreover, it can correctly decide both the need of try-catch block(s) and the statements to be placed in such blocks with the accuracies of 74.7% and 87.1% at the instance and statement levels, an improvement of 128.7% and 44.9% over the baseline, respectively. Our extrinsic evaluation also shows that NEUREX relatively improves over the baseline by **9.6%** in F-score in detecting exception-related bugs in incomplete StackOverflow code snippets.

In brief, this paper makes the following major contributions:

1. **[Neural Network-based Automated Exception Handling Recommendation]**. NEUREX is the first neural network approach to automated exception handling recommendation in three above tasks. NEUREX works for either complete or *incomplete* code.

```

1 public static void addLibraryPath(String pathToAdd) throws Exception {
2     final Field usrPathsField =
3         ClassLoader.class.getDeclaredField("usr_paths");
4     usrPathsField.setAccessible(true);
5
6     //get array of paths
7     final String[] paths = (String[])usrPathsField.get(null);
8
9     //check if the path to add is already present
10    for(String path : paths) {
11        if(path.equals(pathToAdd)) {
12            return;
13        }
14    }
15
16    //add the new path
17    final String[] newPaths = Arrays.copyOf(paths, paths.length + 1);
18    newPaths[newPaths.length-1] = pathToAdd;
19    usrPathsField.set(null, newPaths);
20 }

```

Figure 1: StackOverflow post #15409223 on adding new paths for native libraries at runtime in Java

2. **[Multi-tasking among three Exception Handling Recommendations]** We formulate the problem as sequence chunking with a multi-tasking mechanism to learn for three above tasks.
3. **[Empirical Evaluation]**. Our evaluation shows NEUREX’s high accuracy in exception handling recommendation as well as in exception-related bug detection. Data and code is available at [6].

2 MOTIVATION

2.1 Motivating Examples

Let us use a few real-world examples to explain the problem and motivate our approach. Figure 1 displays a code snippet in an answer to the StackOverflow (S/O) question 15409223 on how to “*add new paths for native libraries at runtime in Java*”. The code snippet serves as an illustration in the S/O post, thus, does not contain all the details on what exceptions that need to be handled. It contains only a throw of a generic Exception in the method header (addLibraryPath). From Zhang *et al.*’s study [15], this code snippet was adopted by developers into their Github project named *armint* (Figure 2). *armint*’s developers handle in a try-catch block several exceptions caused by `java.lang.Class.getDeclaredField(...)` (line 7) according to JDK’s documentation, e.g., `NoSuchFieldException`, `SecurityException`, `IllegalArgumentException`, and `IllegalAccessException` (line 24, Figure 2).

The manual adaptation on exception handling by inserting a try-catch block is quite popular, yet not automated by any tools [15]. Such manual adaptation for a code snippet could lead to exception-related bugs, which could cause serious issues including crashes or unstable states. Thus, it is desirable to have an automated tool to recommend proper exception handling for such adaptation.

OBSERVATION 1 (Exception Handling Recommendation). *Automated recommendation to handle exceptions is desirable to assist developers in adapting incomplete code snippets into their codebases.*

As explained in Section 1, four categories of automated approaches have been proposed to recommend exception handling [2–4, 10, 13]. However, the state-of-the-art, IR-based approaches [10], which have been shown to outperform others, still have the limitations. First, it is not trivial to pre-define a threshold for feature

```

1  /** ...
2  * taken from http://stackoverflow.com/questions/15409223/
3  * adding-new-paths-for-native-libraries-at-runtime-in-java
4  */
5  private static void addLibraryPath(String pathToAdd) {
6      try {
7          final Field usrPathsField =
8              ClassLoader.class.getDeclaredField("usr_paths");
9          usrPathsField.setAccessible(true);
10
11         // get array of paths
12         final String[] paths = (String[]) usrPathsField.get(null);
13
14         // check if the path to add is already present
15         for (String path : paths) {
16             if (path.equals(pathToAdd)) {
17                 return;
18             }
19         }
20
21         // add the new path
22         final String[] newPaths = Arrays.copyOf(paths, paths.length + 1);
23         newPaths[newPaths.length - 1] = pathToAdd;
24         usrPathsField.set(null, newPaths);
25     } catch (NoSuchFieldException | SecurityException |
26             IllegalArgumentException | IllegalAccessException e) {
27         throw new RuntimeException(e);
28     }
29 }

```

Figure 2: GitHub project armint adapts SO post in Figure 1

matching for a retrieval, e.g., the threshold to determine the associations between an API call (e.g., `getDeclaredField`) and an exception type (e.g., `NoSuchFieldException`). Thus, the pre-defined threshold affects much their effectiveness. Second, relying on the lexical values of API elements' names, they suffer the issue of ambiguous names of the APIs or exceptions in an incomplete code snippet (e.g., the API method `get` at line 6 of Figure 1 occurs in multiple libraries), which might not be parseable for fully-qualified name resolution. Thus, this reduces effectiveness. Finally, they consider only the associations between an API method and an exception type, and discard the surrounding context. For example, they compute the association between the names of the API call (e.g., `getDeclaredField`) and the exceptions to be handled (e.g., `NoSuchFieldException`, `SecurityException`, etc.). Without the context, it is challenging to decide the identities of the APIs and their exceptions via only simple names.

```

1  public Object readField(Class<?> clazz, String name, Object instance) {
2      try {
3          Field field = clazz.getDeclaredField(name);
4          if (!field.isAccessible()) {
5              field.setAccessible(true);
6          }
7          return field.get(instance);
8      } catch (NoSuchFieldException | SecurityException |
9              IllegalArgumentException | IllegalAccessException e) {
10         throw new RuntimeException("Cannot read field value: " + clazz.getName()
11             + " #" + name, e);
12     }
13 }

```

Figure 3: Project quarkus with same exception handling

Now, consider the complete code example in Figure 3 from the Github project named `quarkus`. While there are differences between the complete code in Figure 3 and the adapted code in Figure 2, the lists of the handled exceptions are the same (line 8 in Figure 3 and line 24 in Figure 2) due to the presence of the API call to `getDeclaredField` in both code. This is expected because the designers of the

```

1  Charset charset = Charset.forName("US-ASCII");
2  try {
3      BufferedReader reader = Files.newBufferedReader(file, charset);
4      String line = null;
5      while ((line = reader.readLine()) != null) {
6          System.out.println(line);
7      }
8  } catch (IOException x) {
9      System.err.format("IOException: %s\n", x);
10 }

```

Figure 4: Using `newBufferedReader` to read from a file

JDK library have the intent for developers to use the API method `getDeclaredField` within a try-catch block and to handle the list of exceptions as in line 8 of Figure 3. Thus, to adapt the incomplete code snippet in Figure 1, a model could learn from the public repositories with complete code to suggest proper exception handling.

OBSERVATION 2 (Regularity of Exception Handling). *Finding the patterns from complete code in existing code corpora could be a good strategy for a model to learn to properly handle the exceptions in adapting an (incomplete) code snippet into a codebase.*

OBSERVATION 3 (Relations between API methods and Exceptions). *The presence of certain API elements helps decide the exceptions that need to be handled.*

For example, the relation between `java.lang.Class.getDeclaredField` and the exceptions `NoSuchFieldException`, `SecurityException`, `IllegalArgumentException`, and `IllegalAccessException` can be learned from the code corpora. Thus, a model can learn to recommend those exceptions for an incomplete code snippet involving `getDeclaredField`.

OBSERVATION 4 (Surrounding Context help resolve name ambiguity). *The surrounding code context can help resolve the ambiguity of the names of those elements in incomplete code snippets, leading to better prediction of the handled exceptions.*

For an incomplete code snippet, as explained earlier, the simple names of the API elements (methods, fields, classes) could be ambiguous. However, if a model can learn from the complete code the fully-qualified names of the API elements, the surrounding context consisting of those API elements and their program dependencies can help a model decide the correct identities of the API elements.

In Figure 1, to derive the identities of `Field` (line 2), `getDeclaredField` (line 2), `setAccessible` (line 3), `get` (line 6), etc., a model could rely on the dependencies among them in the surrounding context. For example, the return type of `getDeclaredField` is `Field` (thanks to line 2), which has an API method named `setAccessible` (thanks to line 3) and another API method named `get` (thanks to line 6). Considering all those dependencies among the API elements in the context and with the knowledge learned from the complete code, a model could decide that in the code snippet, the identity of `Field` is `java.lang.Class.Field`, that of `setAccessible` is `java.lang.Class.Field.setAccessible`, and that of `get` at line 6 is `java.lang.Class.Field.get`. The rationale is that a model could see such dependencies among those API elements before in a complete code in training.

For the list of statements in an incomplete code, not all of them needs to be wrapped around in a try-catch block. For example, considering the example of using `newBufferedReader` in Figure 4. While the API call `java.nio.file.newBufferedReader` needs to be within a




Figure 5: NEUREX: Architecture Overview

try-catch block, the statement at line 1 to retrieve the character set does not. Moreover, the statement at line 5 with the API call to `readLine` needs to be wrapped in a try-catch block as well.

OBSERVATION 5 (Learn to decide what statements to be in a Try-Catch block). *A model can learn from the code corpora what statements need to be placed within a try-catch block or not.*

2.2 Key Ideas

We introduce NEUREX with three functionalities for exception handling recommendation: given a Java code snippet, it will

- 1) predict if a try-catch block is required (XBLOCK),
- 2) point out which statements in the code snippet need to be placed in a try-catch block (XSTATE), and
- 3) suggest the exception types to be in the catch clause (XTYPE).

From Observations, we design NEUREX with the following ideas:

2.2.1 [Key Idea 1] Neural Network-based approach to Exception Handling Recommendation by Learning from Complete Code. Instead of deterministically deriving the exceptions to be handled for a given (incomplete) code snippet, following Observation 2, we follow a learning-based approach to learn to properly handle the exceptions in the three above tasks. By learning from the try-catch blocks of the complete code in the open-source projects in the training process, our model can help the adaptation tasks.

2.2.2 [Key Idea 2] Leveraging Language Model to learn Context to avoid name ambiguity and Learning the Relations between API elements and Exception types. Instead of learning only the associations between an API element and exception types as in IR-based approaches, we leverage as the context the complete code in the training corpus, which are parsable and provide the identities (i.e., FQNs) of the API elements. In predicting for a code snippet, NEUREX will also leverage the context and dependencies among the API elements to learn their identities implicitly (see Observation 4). Importantly, that leads to the learning of the relations between the key API elements in the context and the handled exception types (Observation 3).

2.2.3 [Key Idea 3] Leveraging Sequence Chunking with a Language Model and Multi-tasking. Inspired by the sequence chunking techniques [1] in NLP, we formulate our problem as identifying one or multiple chunks of consecutive statements that

need to be placed within try-catch blocks. We leverage and fine-tune the language model CodeBERT [7] to learn to the relations among statements with the API elements. We also leverage the multi-tasking framework for all three tasks XBLOCK, XSTATE, and XTYPE because the learning for one task can benefit for another.

3 NEUREX OVERVIEW

Figure 5 displays the overview architecture of NEUREX. Generally, it has three main components dedicated to the three tasks: for a given (in)complete code snippet, 1) XBLOCK aims to check the necessity of try-catch blocks, 2) XSTATE aims to detect which statements need to be in a try-catch block, and 3) XTYPE aims to detect the exception types need to be caught in the catch clauses. We support the detection of one or multiple try-catch blocks if any.

During training, the code snippets with try-catch blocks are used as the positive samples and the ones without them as the negative samples. For a positive sample, the statements inside the try blocks and the exception types in the catch clauses are used as the labels for training. The negative samples are labeled as not needing a try-catch block. In prediction, NEUREX accepts as input any incomplete or complete code snippet without a try-catch block, and predicts the results for those tasks. The predicted results from XSTATE and XTYPE are considered only when XBLOCK predicts Yes, i.e., a need of a try-catch block for the given code snippet.

The input code is used as the input of a large language model to act as the code representation learning model to produce the vector representations for the (sub)tokens and statements in the source code. We use CodeBERT [7] as it is capable of producing embeddings that capture both the syntactic and semantic information.

The vectors are used as the inputs for three components. The prediction is made on the vectors that are attained by composing the embeddings of individual (sub)tokens into the ones for a statement and for a block of statements. First, XBLOCK is modeled as a binary classifier on deciding whether the input code needs at least one try-catch block. Second, inspired by the sequence chunking techniques [1] in NLP, we model the second task, XSTATE, as learning to tag/label each statement in the code snippet with either 0 (i.e., the statement is outside of a try-catch block), B-try (i.e., it is the beginning of a try-catch block), or I-try (i.e., it is inside of such a block). During training, the statements within or outside of the try-catch blocks enable us to build the tags/labels for them.




Figure 6: Try-catch Necessity Checker (XBLOCK)

The last task, XTYPE, is modeled as a set of binary classifiers, each is responsible for deciding whether an exception type of interest needs to be caught in the catch clause. An *Yes* outcome indicates the need to catch a specific exception type of interest in the set of libraries under consideration. An *No* outcome indicates otherwise. During training, the exception types for each try-catch block in the positive samples are used as labels. During prediction, for each predicted block from XSTATE (starting from a statement with *B-try* to the last respective *I-try*), XTYPE uses the embeddings for those statements to predict the corresponding exception types. Finally, from the results in all three tasks, NEUREX forms the final output.

4 XBLOCK: TRY-CATCH BLOCK CHECKER

Given an input code snippet, we first split it into the statements. Each statement is then tokenized into sub-tokens using the CodeBERT tokenizer. We use a special separator token [SEP] to concatenate the tokenized statements, and add a [CLS] token at the beginning. As in CodeBERT, we take the [CLS] token to be the representation of the entire code snippet.

We fine-tune a CodeBERT(MLM) for this problem. Given the good performance of CodeBERT on many code-related downstream tasks (<https://github.com/microsoft/CodeXGLUE>), we expect it to be able to learn the correlation between important code tokens that would signal the need of exception handling. Importantly, by providing the code snippet, we expect to leverage the code context in which the API elements are used with regard to one another. For example, in Figure 5, CodeBERT is expected to learn that the APIs `newBufferedReader` of the class `Files` and `readLine` of the class `BufferedReader` are used often together in API usages and they require `IOException`. For the input incomplete code snippet, CodeBERT is expected to learn such relations/connections to avoid name ambiguity and to connect them with the exception types.

During training, as we use exactly one CodeBERT, all three modules (Sections 5 and 6) contribute to the signal for updating the CodeBERT parameters. In XBLOCK, we feed the vector representation of the [CLS] token to a linear layer (Feed-forward neural network - FFNN) and use a softmax function to learn the decision as to whether the input code needs to handle any exceptions.




Figure 7: Try-catch Statement Detector (XSTATE)

5 XSTATE: TRY-CATCH STATEMENT DETECTOR

The goal of XSTATE (Figure 7) is to decide if a statement in the given code snippet needs to be in a try-catch block or not. For code representation learning, we use one single CodeBERT [7] model as in XBLOCK (see Figure 6) to produce the embedding for code (sub)-tokens. For the input code, each [SEP] token represents the statement preceding it. Note that semicolon would not be as consistent as our explicit separator, because some statements might not end with a semicolon. A semicolon also could appear inside string literals and for-loop conditions.

The advantage in using CodeBERT on the entire code snippet has two folds. First, as in Key idea 2, the context of the entire code facilitates our model to learn the identities of the API elements, thus, making the connections between the APIs and the presence of try-catch blocks. For example, `write` in the statement 1 could be determined to belong to `OutputStream` in `JDK`. Thus, that leads to better learning to place that statement inside a try-catch block. Second, we expect that CodeBERT would learn *the data and control dependencies among the consecutive statements* separated by the special tokens [SEP]. Those dependencies would help the model better decide whether some consecutive statements need to be placed together in a try-catch block. For example, in Figure 5, the statements at lines 2–5 have data dependencies, thus, they should be in the same try-catch block.

We take the embedding produced by CodeBERT for each [SEP] token as the statement embedding and feed it to a layer with Feed-forward neural network (FFNN). We then use a softmax function to learn to label each corresponding statement with one of three tags: 0 tag means that the statement is outside of any try-catch blocks; *B-Try* tag means that the statement begins a try-catch block; and *I-Try* tag means that the statement is inside a try-catch block and is not the first line of that block. For example, in Figure 7, the embedding computed by CodeBERT for the first [SEP], which represents the statement `out.write(...)`, is classified by the first FFNN+Softmax layer into the *B-Try* category/label because it is the first statement of a try-catch block. However, the embedding for the second [SEP], representing `print(node.getBody(...))`, is labeled as *I-Try* because it is the second statement of the try-catch block. Finally, the embedding of the third [SEP], is labeled as 0 because the statement `return null;` does not need to be in the try-catch block. With this tag encoding, we can support multiple try-catch blocks in which the statement




Figure 8: Exception Type Recommendation (XTYPE)

with the B-Try tag is the start of a try-catch block and the statement with the last respective I-Try tag is the end of that block. A new block will be formed with another statement having a B-Try tag.

During training, the labels for all the statements are known from the code. During prediction, our model will assign the labels to the statements, from which we can derive the try-catch blocks and what statements belonging to each block.

6 XTYPE: EXCEPTION TYPE RECOMMENDER

The goal of XTYPE (Figure 8) is to predict what exception types need to be placed in the catch clause of each of the predicted try-catch block(s) for the given input code snippet. We use one single CodeBERT [7] model as in XBLOCK to produce the embedding for code (sub)-tokens. We expect CodeBERT to learn the connection between the statements in a try-catch block and the corresponding exception types that need to be caught. From Key idea 2, we expect that via context, CodeBERT could learn the identities of the API elements, thus, leading to better learning of the exception types to be caught.

During training, we know all the labels of the statements in a code snippet. For each try-catch block, we identify the statements at the beginning (with the B-Try label) and at the end of the block (with the last respective I-Try label). We consider the embeddings from CodeBERT for the [SEP] tokens corresponding to the statements from the beginning to the end of the block. We add them together to get the embedding for the entire try-catch block, and feed it into a linear layer. We use a sigmoid function to perform binary classifications for the exception types in the libraries of interest.

During prediction, we use the predicted tags for the given statements in the code snippet. From the predicted tags, we obtain the statements in a predicted try-catch block. From there, the embeddings computed by CodeBERT are used in the same way as in training. For example, in Figure 8, the model predicts the try-catch block from the statement `out.write` to the statement `print(node.getBody(...))`. The embeddings of all the statements in the block are used and the output of `IOException` is predicted with the highest probability.

7 MULTI-TASK LEARNING

The learning on the three tasks, XBLOCK, XSTATE, and XTYPE can benefit to one another. If a model decides the need of a try-catch block, there must be some statements in the code snippet that will be placed in such a block. If a model learns the statements to be placed in a try-catch block, it can decide that the code snippet needs such a block and make the connections to what exception types to be caught. The knowledge on the exception types can help a model decide better what important statements need to be in a try-catch block. Thus, we put the three tasks in a multi-task learning fashion.

We calculate the training loss by combining the losses from the three modules. $Loss_{XBLOCK}$ is the Binary Cross Entropy loss for the decision as to whether try-catch blocks exist in the input. To calculate $Loss_{XSTATE}$, we first get the classification loss for each statement ($loss_{stmt}$) in the input, and sum them together. $loss_{stmt}$ is the Cross Entropy loss calculated from the distribution for the three tags – 0, B-Try, I-Try – and the ground-truth tag. Finally, in XTYPE, several try-catch blocks might be present, so $Loss_{XTYPE}$ comes from the summation of the exception prediction losses from all the try-catch blocks. For each try-catch block, the $loss_{try-block}$ is calculated by adding the Binary Cross Entropy loss for the prediction of each exception that we considered.

The overall training loss is calculated as follows. If the input does not contain any try-catch block, the loss will be only the $Loss_{XBLOCK}$. If the input contains a try-catch block, the overall loss will be the summation of the losses from all three tasks (1).

$$Loss_{overall} = \begin{cases} Loss_{XBLOCK}, & \text{no try-catch} \\ Loss_{XBLOCK} + Loss_{XSTATE} + Loss_{XTYPE}, & \text{otherwise.} \end{cases} \quad (1)$$

8 EMPIRICAL EVALUATION

8.1 Research Questions

We conducted several experiments to evaluate NEUREX. We seek to answer the following questions:

RQ1. [Effectiveness on Try-Catch Necessity Checking] How accurate is NEUREX in predicting whether a given code snippet needs to have a try-catch block?

RQ2. [Effectiveness on Try-Catch Statement Detection]. How accurate is NEUREX in predicting which statements in a given code snippet needs to be placed in a try-catch block?

RQ3. [Effectiveness on Exception Type Recommendation]. How accurate is NEUREX in recommending what exception types need to be handled in the catch clause of a try-catch block?

RQ4. [Dependency Probing]. How well NEUREX learn the dependencies among statements for grouping them into a try-catch blocks

RQ5. [Extrinsic Evaluation on Exception-related Bug Detection]. How well does NEUREX detect exception-related bugs?

RQ6. [Ablation Study]. How does fine-tuning improve NEUREX?

8.2 Empirical Methodology

8.2.1 Datasets. We conducted experiments on two datasets: 1) *Github dataset* for intrinsic evaluation on exception handling recommendation tasks (XBLOCK, XSTATE, XTYPE), and 2) *FuzzyCatch*

dataset [10] for extrinsic evaluation on exception-related bug detection. We collected the Github dataset as follows. We first chose in Github 5,726 Java projects with the highest ratings that use the following libraries: jodatetime, JDK, Android, xstream, GWT, and Hibernate. These are the well-established libraries that have been used in several prior research on the topics related to APIs [12, 14]. We then selected the methods with at least one try-catch block, which was not part of any fix in a later version. In total, we have 153,823 code snippets containing try-catch blocks as positive samples. We also randomly selected from the same Github projects the same amount of code snippets that do not have any try-catch block as the negative samples.

For extrinsic evaluation, we used FuzzyCatch dataset, provided by the authors of XRank/XHand [10], which contains 750 samples of methods with exception-related bugs (missing try-catch blocks or missing catching some exceptions). We also randomly selected from the projects in FuzzyCatch dataset the same amount of code snippets with no exception-related bugs as the negative samples.

8.2.2 RQ1. Effectiveness on Try-Catch Necessity Checking.

Baselines. We compared XBLOCK with GPT-3.5 in ChatGPT [5]. Due to cost of using ChatGPT-3.5 on OpenAI, we performed sampling on the Github dataset of 30,764 snippets. To obtain the confidence level of 95%, we randomly selected 380 code snippets in which 190 are negative samples (no try-catch block), and 190 are positive samples (at least one try-catch block). We trained on Github dataset and compared with GPT-3.5 on this sampled test set.

We also compared XBLOCK with XRank [10] (XRank is part of FuzzyCatch tool) on the entire Github dataset. XRank computed the exception risk score for each API call. If a score of a call in the snippet is higher than a threshold, we consider it as needing a try-catch block.

Procedure. We randomly split both the positive and negative sets in the corresponding dataset into 80%, 10%, and 10% of the code snippets for training, tuning, and testing. Meanwhile, we make sure that each partition contains the equal amount of positive samples and negative samples; and the training and tuning partitions do not contain any duplicates.

To request responses from ChatGPT, we construct prompt with the format "question + code", where the question we pose is "Does the code below need to catch any exceptions?\n\n". Considering that the answers from ChatGPT for the same prompt may vary, for each code snippet, we send the prompt three times through the Chat Completions API (<https://platform.openai.com/docs/guides/gpt/chat-completions-api>). Labelling the responses has three steps. Firstly, we check whether the first word in each response is Yes or No. If it is Yes, we assign a positive label; If it is No, we assign a negative label. Secondly, for the responses that do not start with Yes or No, we read each response and manually assign labels to them. However, there are some cases that we cannot, based on the response, easily determine whether or not the code needs any try-catch blocks. The common reasons are (1) the response is not informative enough in that it only relays some general advice about exception handling, (2) In the text, it states that it is uncertain about the case, or (3) the decision depends on background knowledge about either the project structure or certain method specifications. Therefore, in evaluating the performance of ChatGPT, for each metrics, we calculate the lower and upper bound. In the upper bound, all such

uncertain cases are considered as correct, in the lower bound, all such cases are considered as incorrect. Lastly, we assign the final label for each instance from the majority vote from three tries.

Tuning. We trained NEUREX for 15 epochs with the following key hyper-parameters: (1) Batch size is set to 32; (2) Learning rate is set to 0.000006; (3) Weight decay is set to 0.01. We select the model with the lowest overall loss.

Metrics. We use **Recall**, **Precision**, and **F-score** to evaluate the performance of the approaches. They are calculated as $Recall = \frac{TP}{TP+FN}$, $Precision = \frac{TP}{TP+FP}$, $F\text{-score} = \frac{2*Recall*Precision}{Recall+Precision}$. TP : true positive, FN : false negative, and FP : false positive.

8.2.3 RQ2. Effectiveness on Try-Catch Statement Detection.

Baselines. We compared XSTATE against GPT-3.5 as in RQ1.

Procedure. We used the same procedure as in RQ1.

Tuning. We used the same tuning as in RQ1.

Metrics. We used the same metrics as in RQ1 at the instance (snippet) level. At the statement level, we use *Accuracy*, which is the ratio between the number of correct tagging of statements over the total number of statements. We computed Recall, Precision, and F-score in two ways. First, we evaluated XSTATE in connection with XBLOCK. That is, we consider a correct case if XBLOCK gives a correct prediction on whether try-catch blocks are needed, and XSTATE produces correct tags for all the statements when there exists a try-catch block. Second, we evaluated XSTATE as individual. We assumed that XBLOCK predicts correctly whether a code snippet needs try-catch block(s). We used XSTATE to predict the groupings of statements for the blocks in those snippets and compared against the statements in one or multiple blocks in the oracle (via the encoded vector [O, B-Try, I-Try]). We also computed the accuracy at the statement level on if a statement needs a try-catch block.

8.2.4 RQ3. Effectiveness on Exception Type Recommendation.

Baselines. We compared XTYPE against GPT-3.5 as in RQ1.

Procedure. We used the same procedure as in RQ1.

Tuning. We used the same tuning as in RQ1.

Metrics. We used 1) Precision (defined as the ratio between the size of the overlapping set between the predicted and oracle sets over the size of the predicted one), 2) Recall (defined as the ratio between the size of the overlapping set and the size of the oracle set), and 3) F-score (a harmonious mean). We computed those metrics in two ways. First, we evaluate XTYPE in connection with XBLOCK and XSTATE. We consider a correct case if XBLOCK gives a correct prediction on whether try-catch blocks are needed, XSTATE produces correct tags for all the statements, and XTYPE predicted correctly on the exceptions that need to be caught for all the try-catch blocks. Second, we evaluate XTYPE as individual: we assumed that both XBLOCK and XSTATE have given 100% correct predictions for their own tasks. To do so, we put the code snippets that need try-catch blocks with statements correctly labeled in the oracle and used XTYPE to predict the exception types for all such blocks.

8.2.5 RQ4.

8.2.6 RQ5. Extrinsic Evaluation on Exception-related Bug Detection.

Baselines. FuzzyCatch [10] leverages XRank to detect the exception-related bugs, which are the StackOverflow code snippets that were supposed to handle exceptions, but missed try-catch blocks and/or exceptions.

Table 1: Try-Catch Block Comparison with XRank (RQ1)

Github dataset	Precision	Recall	F1-score
XRank	0.810	0.530	0.630
NEUREX	0.981	0.984	0.982

Table 2: Try-Catch Block Comparison with GPT-3.5 (RQ1)

Small dataset	Precision	Recall	F1-score
GPT-3.5	0.666–0.804	0.726–0.778	0.695–0.791
NEUREX	0.994	1.0	0.997

Procedure. We trained NEUREX on the Github dataset and detected the exception-related bugs in FuzzyCatch bug dataset via XBLOCK.

Metrics. We compared the result against the oracle in FuzzyCatch dataset. If XBLOCK correctly detects a buggy snippet (missing a try-catch block or exceptions), we consider it as correct. Otherwise, it is a miss. We use **Recall**, **Precision**, and **F-score** as in RQ1.

8.2.7 RQ6. Ablation Study.

We aim to evaluate the contribution of fine-tuning in NEUREX. We compared NEUREX against CodeBERT without fine-tuning.

9 EMPIRICAL RESULTS

9.1 Comparison on Try-Catch Necessity Checking Effectiveness (RQ1)

As seen in Table 1, NEUREX achieves very high Precision, Recall and F-score on the Github dataset—all above 98%. In comparison, NEUREX relatively improves over XRank 21%, 85.7%, and 55.9% in Precision, Recall, and F1-score, respectively.

Examining the result, we reported the following. First, precision is just marginally better than a coin toss (0.53) in our balanced dataset. In XRank, if the association score of *only one API method* in the snippet and *one exception* is higher than a threshold, it decides that a try-catch block is needed. Second, the decisions on the necessity of a try-catch block or the exception types depend on the pre-defined thresholds in XRank on those association scores. Thus, those pre-defined thresholds might not be suitable across the libraries. Third, for the incomplete code snippets in which the names of the API methods in different packages or libraries are the same (e.g., `toString` or `getText` in various JDK packages), XRank cannot distinguish them and use one entry in the dictionary for them due to its IR approach, leading to mistakenly considering them the same. Unlike XRank, which considers only the API method calls in a try-catch block, NEUREX considers the code in the block as the context to learn the relations among the names of those API elements, thus, better deciding the need of try-catch blocks.

As seen in Table 2, NEUREX relatively improves over GPT-3.5 from 23.6%–49.3%, 28.5%–37.7%, and 26%–43.5%, in Precision, Recall, and F1-score, respectively. Examining GPT-3.5’s results, we found that it detected well only the popular APIs and corresponding exception types because it was not trained specifically for the exception handling task. Moreover, for the un-popular API names, GPT-3.5 often resorted to another API with similar name, and predicts that the given code snippet needs a try-catch block because that API requires such a block. For example, in an instance containing a method call to `interval.parseWithOffset`, which is specific to a project, GPT-3.5 incorrectly considered it to have a try-catch block.

```
protected Class << ? > loadClass(String name, boolean resolve) throws ClassNotFoundException {
    if (name.startsWith(Test.class.getName())) {
        Class << ? > c = findLoadedClass(name);
        if (c != null) {
            return c;
        }
        try {
            COUNTER++;
            InputStream in = getSystemResourceAsStream(name.replace('.', File.separatorChar) + ".class");
            byte[] buf = in.readAllBytes();
            return defineClass(name, buf, 0, buf.length);
        } catch (IOException e) {
            throw new ClassNotFoundException(name);
        }
    }
    return super.loadClass(name, resolve);
}
```

Figure 9: XBLOCK Puts Attention on the Right Tokens**Table 3: Try-Catch Necessity Checking Evaluated on Test Partitions by the Number Of Try-Catch Blocks (RQ1)**

	Number of Try-Catch Blocks (Github dataset)					
	Zero	One	Two	Three	Four	Five
Precision	0.0	1.0	1.0	1.0	1.0	1.0
Recall	0.0	0.983	0.9988	1.0	0.9861	1.0
F1	0.0	0.9914	0.9994	1.0	0.993	1.0

GPT-3.5 explained that it is similar to parse in a compiler project, which needs to handle `InvalidInputException`. Thus, it incorrectly considers `parseVals` needs to handle that exception.

Attribution Scores. To illustrate how XBLOCK makes the prediction, in Figure 9, we shows a code snippet that catches an `IOException` thrown by the `readAllBytes` API call on an `InputStream` object. CodeBERT produces as a by-product an *attribution score* for each code sub-token in the input. The higher the score of a token the higher attention that the model pays to that token, contributing to the prediction result. In Figure 9, for each statement, we show the statement attribution score, which is calculated by averaging the attribution scores of all the sub-tokens in the statement. A positive attribution score means that the statement contributes positively to the model’s predicted class, while a negative score means the statement contributes negatively to the predicted class. As seen, the two statements that receive the highest scores are the statement that defines the `InputStream` variable and the statement that invokes the `readAllBytes` method call on the `InputStream` object. This example illustrates that NEUREX is able to put the attention on the right (sub)tokens of those statements including `InputStream`, `in`, `get`, `System`, `name`, `replace`, etc., leading to its correct prediction.

In addition, we partitioned the test dataset according to the number of try-catch blocks, and evaluated XBLOCK on each partition. As seen in Table 3, XBLOCK gives 100% correct prediction on the partitions with zero, three and five try-catch blocks. Moreover, it achieves 100% precision and above 0.99 F1-score across all the partitions, showing that XBLOCK’s prediction ability remains strong regardless of the number of try-catch blocks in a code snippet.

9.2 Try-Catch Statement Detection (RQ2)

Table 4 shows the result when we evaluated XSTATE in connection with XBLOCK. That is, both individual results from XBLOCK and XSTATE must be correct for the instance to be considered correct.

Table 4: Try-Catch Statement Detecting Comparison (XBLOCK+XSTATE, Instance Level) (RQ2)

Small dataset	Precision	Recall	F1-score
GPT-3.5	0.550	0.232	0.326
XBLOCK + XSTATE	0.969	0.607	0.747

Table 5: Try-Catch Statement Detecting Result (XSTATE as Individual, Instance Level) (RQ2)

Github dataset	Precision	Recall	F1-score
XSTATE	1.0	0.6198	0.7652

Table 6: Try-Catch Statement Detecting Comparison (XBLOCK+XSTATE, Statement Level, Small Dataset) (RQ2)

Statement Level	Accuracy
GPT-3.5	60.1%
XBLOCK + XSTATE	87.1%

Table 7: Try-Catch Statement Detecting Result (XSTATE as Individual, Statement Level, Github Dataset) (RQ2)

Statement Level	Accuracy
XSTATE	87.4%

NEUREX achieves a very high precision (96.88%) and predicts correctly *all the statements in all try-catch blocks* (could have multiple blocks) for 62% of the positive code snippets. It improves relatively over GPT-3.5 **76.1%**, **161.7%**, and **128.7%** in Precision, Recall, and F1-score. Examining the results, we found that GPT-3.5 did not work well for the code snippets that have more than one try-catch blocks. It also does not recognize well multiple statements with dependencies that need to be placed in the same block. NEUREX recognizes/captures well the dependencies among statements (see RQ4), thus, better grouping them into a try-catch block.

Table 5 displays the result when we evaluated XSTATE individually (i.e., assuming XBLOCK correctly predicts the presence of try-catch blocks). As seen, the numbers are slightly higher than those for XBLOCK+XSTATE because there is no impact from XBLOCK’s result. In other words, XSTATE manages to achieve a 100% precision, showing that XSTATE is capable of giving correct predictions for those false negatives from XBLOCK.

Table 6 displays the result at the statement level (i.e., whether a statement needs to be inside a try-catch block or not). As seen, XBLOCK+XSTATE improves relatively over GPT-3.5 **44.9%** in accuracy at the statement level. As seen in Table 7, NEUREX also achieves high numbers in accuracy at the statement level as individual. As expected, it has a slightly higher accuracy than XBLOCK +XSTATE.

9.3 Exception Type Recommendation (RQ3)

9.4 Dependency Probing (RQ4)

9.5 Exception-Related Bug Detection (RQ5)

Has seen in Table 8, NEUREX can be used to detect well real-world exception-related bugs in which a code snippet needs but did not have a try-catch block or miss some exceptions. In comparison, NEUREX improves relatively over FuzzyCatch [10] 14.8% in Precision

Table 8: Exception-Related Bug Detection (RQ5)

	FuzzyCatch Dataset	
	NEUREX	FuzzyCatch [10]
Recall	0.75	0.76
Precision	0.62	0.54
F-score	0.68	0.62

```

1 public void onCreate(Bundle state) {
2     requestWindowFeature(Window.FEATURE_NO_TITLE);
3     + try {
4         final WindowManager.LayoutParams attrs = getWindow().getAttributes();
5         final Class<?> cls = attrs.getClass();
6         final Field fld = cls.getField("buttonBrightness");
7         if (fld != null && "float".equals(fld.getType().toString())) {
8             fld.setFloat(attrs, 0);
9         }
10    } catch (NoSuchFieldException e) {
11    } catch (IllegalAccessException e) {
12    } ...
13 }

```

Figure 10: Exception-related Bug #106 in FuzzyCatch dataset (missing try-catch) (detected by NEUREX)

and 9.8% in F-score. While the recall values between two models are almost the same, FuzzyCatch has lower precision. It tends to predict “Yes” (buggy) for all code snippets. That is because if there is an association score between *only* one API method call in the code snippet and one exception type higher than the threshold, it will decide that the snippet is buggy. Figure 10 shows a bug detected by NEUREX, and its fix (adding a try-catch block). All buggy code and fixes are available in FuzzyCatch’s repository: ebrand.ly/ExDataset.

9.6 Impact of Fine-Tuning (RQ6)

Table 9: Impact of Fine-Tuning in NEUREX (RQ6)

Github dataset (XBlock)	Precision	Recall	F1-score
CodeBERT w/o fine-tuning	0.497	0.972	0.657
NEUREX	0.981	0.984	0.982

As seen in Table 9, fine-tuning contributes much to NEUREX in much improving Precision (almost twice) and slightly improving in Recall (1%), and much improving in F1-score (relatively 49.5%). Without fine-tuning, the model overwhelmingly predicts that the input code snippet contains a try-catch block: in our balanced test dataset that contains 30,764 samples, only 236 samples receives the negative label (i.e., no try-catch) from CodeBERT.

Limitations and Threats to Validity. First, NEUREX can not handle the code with multiple try-catch blocks. Second, it cannot generate new exception types that were not in the training corpus. Third, it does not support the generation of exception handling code inside the body of catch. Finally, NEUREX needs training data, thus, does not work for a new library without any API usage yet.

Our solution is specifically for Java. Our collected data might not be representative. However, we use well-established open-source projects with well-known libraries.

10 RELATED WORK

The automated approaches to recommend exception handling can be classified into four categories as presented in Section 1. The

closest work to NEUREX is the state-of-the-art *information retrieval* (IR) approaches [10], which provides more flexibility than the others. XRank [10] recommends a ranked list of API calls that might need exception handling and XHand [10] recommends exception handling code. Both leverages fuzzy set theory to compute the associations between API method calls and the exception types. This direction has three key limitations. First, one needs to pre-define a threshold for feature matching for the retrieval of API elements or exception types. Second, the IR techniques are not flexible as the ML approaches because they use the lexical values of API simple names. Thus, they suffer the ambiguity in the names of API elements in incomplete code snippets. Lastly, XRank/XHand considers only pairwise associations between the API method calls and exceptions. It disregards the surrounding code context and the dependencies/relations. XRank/XHand simply uses Groum [11], a dependency graph among API elements, to collect the API calls, but did not use dependencies in computing the association scores.

In addition to exception handling recommendation research, ThEx [16] predict which exception(s) shall be thrown under a given programming context. ThEx learns a classification model from existing thrown exceptions in different contexts.

11 CONCLUSION

NEUREX is the first neural-network model to automated exception handling recommendation in three tasks for (in)complete code. It is designed to capture the basic insights to overcome key limitations of the state-of-the-art IR approaches. With the learning-based approach, it does not rely on a pre-defined threshold for explicit feature matching. The dependencies and context help NEUREX learn the identities of API elements to avoid name ambiguity and to learn their relations with the exception types. Our evaluation shows that NEUREX improves over the state-of-the-art approaches in both intrinsic task and extrinsic one in exception-related bug detection.

REFERENCES

- [1] [n. d.].
- [2] Eiji Adachi Barbosa and Alessandro Garcia. 2018. Global-Aware Recommendations for Repairing Violations in Exception Handling. *IEEE Transactions on Software Engineering* 44, 9 (2018), 855–873. <https://doi.org/10.1109/TSE.2017.2716925>
- [3] Eiji Adachi Barbosa, Alessandro Garcia, and Mira Mezini. 2012. Heuristic Strategies for Recommendation of Exception Handling Code. In *2012 26th Brazilian Symposium on Software Engineering*. 171–180. <https://doi.org/10.1109/SBES.2012.22>
- [4] Eiji Adachi Barbosa, Alessandro Garcia, Martin P. Robillard, and Benjamin Jakobus. 2016. Enforcing Exception Handling Policies with a Domain-Specific Language. *IEEE Transactions on Software Engineering* 42, 6 (2016), 559–584. <https://doi.org/10.1109/TSE.2015.2506164>
- [5] ChatGPT [n. d.]. OpenAI. <https://openai.com/>.
- [6] DeepEx [n. d.]. DeepEx. https://github.com/trycatchresearch/try_catch_research.
- [7] Zhangyin Feng, Daya Guo, Duyu Tang, Nan Duan, Xiaocheng Feng, Ming Gong, Linjun Shou, Bing Qin, Ting Liu, Daxin Jiang, and Ming Zhou. 2020. CodeBERT: A Pre-Trained Model for Programming and Natural Languages. In *Findings of the Association for Computational Linguistics: EMNLP 2020, Online Event, 16-20 November 2020 (Findings of ACL, Vol. EMNLP 2020)*, Trevor Cohn, Yulan He, and Yang Liu (Eds.). Association for Computational Linguistics, 1536–1547. <https://doi.org/10.18653/v1/2020.findings-emnlp.139>
- [8] Maria Kechagia and Diomidis Spinellis. 2014. Undocumented and Unchecked: Exceptions That Spell Trouble. In *Proceedings of the 11th Working Conference on Mining Software Repositories (Hyderabad, India) (MSR 2014)*. Association for Computing Machinery, New York, NY, USA, 312–315. <https://doi.org/10.1145/2597073.2597089>
- [9] Taiza Montenegro, Hugo Melo, Roberta Coelho, and Eiji Barbosa. 2018. Improving developers awareness of the exception handling policy. In *2018 IEEE 25th International Conference on Software Analysis, Evolution and Reengineering (SANER)*. 413–422. <https://doi.org/10.1109/SANER.2018.8330228>
- [10] Tam Nguyen, Phong Vu, and Tung Nguyen. 2020. Code Recommendation for Exception Handling. In *Proceedings of the 28th ACM Joint Meeting on European Software Engineering Conference and Symposium on the Foundations of Software Engineering (Virtual Event, USA) (ESEC/FSE 2020)*. Association for Computing Machinery, New York, NY, USA, 1027–1038. <https://doi.org/10.1145/3368089.3409690>
- [11] Tung Thanh Nguyen, Hoan Anh Nguyen, Nam H. Pham, Jafar M. Al-Kofahi, and Tien N. Nguyen. 2009. Graph-based Mining of Multiple Object Usage Patterns. In *Proceedings of Conference on the Foundations of Software Engineering (ESEC/FSE '09)*. ACM, 383–392.
- [12] Hung Phan, Hoan Anh Nguyen, Ngoc M. Tran, Linh H. Truong, Anh Tuan Nguyen, and Tien N. Nguyen. 2018. Statistical Learning of API Fully Qualified Names in Code Snippets of Online Forums. In *Proceedings of the 40th International Conference on Software Engineering (ICSE '18)*. Association for Computing Machinery, New York, NY, USA, 632–642. <https://doi.org/10.1145/3180155.3180230>
- [13] Mohammad Masudur Rahman and Chanchal K. Roy. 2014. On the Use of Context in Recommending Exception Handling Code Examples. In *2014 IEEE 14th International Working Conference on Source Code Analysis and Manipulation*. 285–294. <https://doi.org/10.1109/SCAM.2014.15>
- [14] Siddharth Subramanian, Laura Inozemtseva, and Reid Holmes. 2014. Live API Documentation. In *Proceedings of the 36th International Conference on Software Engineering (Hyderabad, India) (ICSE '14)*. ACM, 643–652. <https://doi.org/10.1145/2568225.2568313>
- [15] Tianyi Zhang, Di Yang, Crista Lopes, and Miryung Kim. 2019. Analyzing and Supporting Adaptation of Online Code Examples. In *Proceedings of the 41st International Conference on Software Engineering (ICSE '19)*. IEEE Press, 316–327. <https://doi.org/10.1109/ICSE.2019.00046>
- [16] Hao Zhong. 2023. Which Exception Shall We Throw?. In *Proceedings of the 37th IEEE/ACM International Conference on Automated Software Engineering (ASE '22)*. Association for Computing Machinery, New York, NY, USA, Article 116, 12 pages. <https://doi.org/10.1145/3551349.3556895>
- [17] Hao Zhong and Hong Mei. 2018. Mining repair model for exception-related bug. *Journal of Systems and Software* 141 (2018), 16–31. <https://doi.org/10.1016/j.jss.2018.03.046>