

**CS 2021: Practice Exam 2**

Spring 2019

University of Minnesota

Exam period: 20 minutes

Points available: 40

**Problem 1 (15 pts):** Nearby is a C function `col_update()` with associated data and documentation. **Re-implement this function in x86-64 assembly** according to the documentation given. Follow the same flow provided in the C implementation. The comments below the `colinfo_t` struct give information about how it lays out in memory and as a packed argument.

**Indicate which registers correspond to which C variables.**

```
.text
.globl      col_update
# YOUR CODE BELOW
col_update:
```

```
1 typedef struct{
2     int cur;
3     int step;
4 } colinfo_t;
5 // |           | Byte |   Byte | Packed |
6 // | Field | Size | Offset | Bits |
7 // |-----+-----+-----+-----|
8 // | cur   |   4 |    +0 | 0-31 |
9 // | step  |   4 |    +4 | 32-64 |
10
11 int col_update(colinfo_t *info){
12     // Updates current value and step in
13     // colinfo_t pointed by param info. If
14     // info->cur is invalid, makes no changes
15     // and returns 1 to indicate an
16     // error. Otherwise performs odd or even
17     // update on cur and increments step
18     // returning 0 for success.
19
20     int cur = info->cur;
21     int step = info->step;
22     if(cur <= 0){
23         return 1;
24     }
25     step++;
26     if(cur % 2 == 1){
27         cur = cur*3+1;
28     }
29     else{
30         cur = cur / 2;
31     }
32     info->cur = cur;
33     info->step = step;
34     return 0;
35 }
36
```

**Problem 2 (15 pts):** Below is an initial register/memory configuration along with snippets of assembly code. Each snippet is followed by a blank register/memory configuration which should be filled in with the values to reflect changes made by the preceding assembly. The code is continuous so that POS A is followed by POS B.

INITIAL			addl %edi, %esi subq \$8, %rsp movl \$100, 4(%rsp) movl \$300, 0(%rsp) addl (%rsp), %eax # POS A			movq \$1, %rdi addl %rsi, (%rsp,%rdi,4) leaq 8(%rsp), %rdi addl (%rdi), %rax # POS B		
REG	Value		REG	Value		REG	Value	
rax	10		rax			rax		
rdi	20		rdi			rdi		
rsi	30		rsi			rsi		
rsp	#3032		rsp			rsp		
MEM	Value		MEM	Value		MEM	Value	
#3032	250		#3032			#3032		
#3028	1		#3028			#3028		
#3024	2		#3024			#3024		
#3020	3		#3020			#3020		

**Problem 3 (10 pts):** Rover Witer is writing an assembly function called `compval` which he will use in C programs. He writes a short C `main()` function to test `compval` but is shocked by the results which seem to defy the C and assembly code. Valgrind provides no insight for him. **Identify why** Rover's code is behaving so strangely and fix `compval` so it behaves correctly.

#### Sample Compile / Run:

```
> gcc compval_main.c compval_asm.s
> a.out
expect: 0
actual: 19
expect: 0
actual: 50
```

```
1 // compval_main.c
2 #include <stdio.h>
3
4 void compval(int x, int y, int *val);
5 // compute something based on x and y
6 // store result at int pointed to by val
7
8 int main(){
9     int expect, actual;
10
11     expect = 7 * 2 + 5;    // expected value
12     compval(7, 2, &actual); // actual result
13     printf("expect: %d\n", expect);
14     printf("actual: %d\n", actual);
15
16     expect = 5 * 9 + 5;    // expected value
17     compval(5, 9, &actual); // actual result
18     printf("expect: %d\n", expect);
19     printf("actual: %d\n", actual);
20
21     return 0;
22 }
```

```
1 # compval_asm.s
2 .text
3 .global compval
4 compval:
5     imulq    %rdi,%rsi
6     addq     $5,%rsi
7     movq     %rsi, (%rdx)
8     ret
```