≔ Articles > 100. Same Tree ▼

♦ Previous (/articles/sliding-window-maximum/) Next ♦ (/articles/gas-station/)

100. Same Tree [☑] (/problems/same-tree/)

March 7, 2019 | 104K views

Average Rating: 4.41 (54 votes)


Given two binary trees, write a function to check if they are the same or not.

Two binary trees are considered the same if they are structurally identical and the nodes have the same value.

Example 1:

Example 2:

Example 3:




Solution

Approach 1: Recursion

Intuition

The simplest strategy here is to use recursion. Check if p and q nodes are not None, and their values are equal. If all checks are OK, do the same for the child nodes recursively.

Implementation



```
    Articles > 100 Same Tree ▼
Java
       Python
    class Solution:
2
        def isSameTree(self, p, q):
3
4
            :type p: TreeNode
5
            :type q: TreeNode
6
            :rtype: bool
7
8
            # p and q are both None
9
            if not p and not q:
10
                return True
11
            # one of p and q is None
12
            if not q or not p:
13
                return False
14
            if p.val != q.val:
15
                return False
16
            return self.isSameTree(p.right, q.right) and \
17
                   self.isSameTree(p.left, q.left)
```

Complexity Analysis

- ullet Time complexity : $\mathcal{O}(N)$, where N is a number of nodes in the tree, since one visits each node exactly once.
- Space complexity : $\mathcal{O}(\log(N))$ in the best case of completely balanced tree and $\mathcal{O}(N)$ in the worst case of completely unbalanced tree, to keep a recursion stack.

Approach 2: Iteration

Intuition

Start from the root and then at each iteration pop the current node out of the deque. Then do the same checks as in the approach 1:

- p and p are not None,
- p.val is equal to q.val,

and if checks are OK, push the child nodes.


Implementation

```
    Articles > 100 Same Tree ▼
Java
       Python
    from collections import deque
 2
    class Solution:
 3
        def isSameTree(self, p, q):
 4
 5
             :type p: TreeNode
 6
             :type q: TreeNode
 7
             :rtype: bool
 8
9
            def check(p, q):
10
                 # if both are None
                 if not p and not q:
11
12
                    return True
13
                 # one of p and q is None
14
                 if not q or not p:
15
                     return False
16
                 if p.val != q.val:
17
                     return False
                 return True
18
19
2.0
            deq = deque([(p, q),])
21
            while deq:
22
                 p, q = deq.popleft()
23
                 if not check(p, q):
24
                     return False
25
                 if p:
26
27
                     deq.append((p.left, q.left))
28
                     deq.append((p.right, q.right))
29
30
             return True
```

Complexity Analysis

- ullet Time complexity : $\mathcal{O}(N)$ since each node is visited exactly once.
- Space complexity : $\mathcal{O}(\log(N))$ in the best case of completely balanced tree and $\mathcal{O}(N)$ in the worst case of completely unbalanced tree, to keep a deque.

Rate this article:





none0 (/none0) ★ 321 ② June 6, 2019 7:21 PM

≡ Articles > 100. Same Tree ▼



An easier and intuitive iterative solution (beats 100% both):

The idea is to store both the root values in a queue, and later dequeue both two compare them.



SHOW 9 REPLIES



kevinhynes (/kevinhynes) ★ 295 ② June 28, 2019 9:02 AM

Many comments here are questioning the space complexity of the iterative approach, and I agree this should be reviewed by the experts. I believe the space complexity is dependent on using an iterative DFS (stack) vs BFS (queue). Here's what I think, with code samples/test cases below:





mengmengli100 (/mengmengli100) ★ 22 ② April 19, 2019 9:49 PM

A question regards the space complexity of the iterative solution:

Why is O(log(N)) in the best case? I thought it was also O(N).

I tried myself and found that the ArrayDeque "deqP" always keeps N/2's items in the best case of completely balanced tree. Because in every while loop, we remove one item from and add two items (left and right) into deaP.

Read More

SHOW 8 REPLIES



terrible_whiteboard (/terrible_whiteboard) ★ 629 ② May 19, 2020 8:51 AM

I made a video if anyone is having trouble understanding the solution (clickable link) https://youtu.be/G9wwY-cmuiE (https://youtu.be/G9wwY-cmuiE)





lxnn (/lxnn) ★ 286 ② October 3, 2019 8:24 PM

It isn't necessary to use a queue in the iterative implementation. In fact the two solutions are the same except that we use the call stack in one and make our own stack in the other.

Read More

Share

SHOW 1 REPLY **≡** Articles > 100. Same Tree ▼ mohanmunisifreddy (/mohanmunisifreddy) ★ 6 ② July 22, 2019 7:46 PM class Solution { public boolean isSameTree(TreeNode p, TreeNode q) { (/mohanmunisifreddy) if(p==null || q==null) return p==q; return p.val==q.val && isSameTree(p.left, q.left) && isSameTree(p.right, q.right); } Read More 🗗 Share ♠ Reply **SHOW 2 REPLIES** shAdow2654 (/shadow2654) ★ 12 ② October 2, 2019 9:45 AM Can anyone please explain the space complexity in both the recursive and iterative case please!!! (/shadow2654) SHOW 1 REPLY JAMESJJ78 (/jamesjj78) ★ 207 ② April 10, 2019 10:15 AM Yessirr 3 ∧ ∨ ☐ Share ¬ Reply (/jamesjj78) SHOW 1 REPLY Marinebattery (/marinebattery) ★ 3 ② March 22, 2019 11:36 AM beauty 3 ∧ ∨ ☐ Share ¬ Reply (/marinebattery) chenmengjie (/chenmengjie) ★ 2 ② March 28, 2019 12:09 PM great C Share (/chenmengjie) ((1) (2) (3) (4) (>)

Copyright © 2020 LeetCode

Help Center (/support/) | Terms (/terms/) | Privacy (/privacy/)

United States (/region/)