

z/OS  
2.5

*Bulk Data Transfer Diagnosis Reference*



**Note**

Before using this information and the product it supports, read the information in [“Notices” on page 157.](#)

This edition applies to Version 2 Release 5 of z/OS® (5650-ZOS) and to all subsequent releases and modifications until otherwise indicated in new editions.

Last updated: 2021-09-30

© **Copyright International Business Machines Corporation 1986, 2021.**

US Government Users Restricted Rights – Use, duplication or disclosure restricted by GSA ADP Schedule Contract with IBM Corp.

---

# Contents

<b>Figures.....</b>	<b>v</b>
<b>Tables.....</b>	<b>vii</b>
<b>About This Book.....</b>	<b>ix</b>
Who Should Read This Book.....	ix
How to Use This Book.....	ix
Related Reading.....	ix
<b>How to send your comments to IBM.....</b>	<b>xi</b>
If you have a technical problem.....	xi
<b>Summary of changes.....</b>	<b>xiii</b>
Summary of changes for z/OS BDT Diagnosis Reference for Version 2 Release 5 (V2R5).....	xiii
Summary of changes for z/OS BDT Diagnosis Reference for Version 2 Release 4 (V2R4) and its updates.....	xiii
Summary of changes for z/OS BDT Diagnosis Reference for Version 2 Release 3 (V2R3) and its updates.....	xiii
<b>Chapter 1. The BDT Formatted Dump.....</b>	<b>1</b>
Purpose of the BDT Formatted Dump.....	1
How to Request the BDT Formatted Dump.....	1
Contents of the Formatted Dump.....	1
Dump Title Page.....	2
Map of BDT Nucleus (BDTNUC).....	3
Transfer Vector Table (TVT).....	4
Function Control Table (FCT).....	25
Job Queue Element (JQE).....	28
Resident Logical Units Table (RLT).....	29
Logical Unit Control Table (LCT).....	30
BDT SNA Line and Node Variable Entries.....	31
Structure of the BDT SNA control blocks.....	33
Cell Pool Directory (CPD) and Cell Pool Control Block (CPB).....	33
Contents of BDT Nucleus (BDTNUC).....	36
<b>Chapter 2. The MVS SVC Dump.....</b>	<b>37</b>
Purpose of the SVC Dump.....	37
How to Request the SVC Dump.....	37
How to Access the SVC Dump.....	37
Formatting and Printing the SVC Dump.....	37
Transmitting the SVC Dump to Another Node.....	38
Contents of the SVC Dump.....	38
Title Page of the SVC Dump.....	38
BDT Trace Table.....	40
Contents of the Trace Table.....	40
Locating the Trace Table.....	42
<b>Chapter 3. BDT Data Areas.....</b>	<b>45</b>
Location of BDT Control Blocks.....	45

Control Blocks after BDT and BDT SNA Manager Initialization.....	46
Control blocks during a file-to-file transaction.....	46
Control Blocks during an NJE Transaction.....	48
Relationships among BDT control blocks.....	51
Data Areas — Summaries and Layouts.....	55
BDT Subsystem Interface Data Area — BSID.....	56
<b>Chapter 4. Generalized Subtask Directory — GSD.....</b>	<b>63</b>
<b>Chapter 5. Initialization Data CSECT — INT.....</b>	<b>69</b>
<b>Chapter 6. Job Control Table — JCT.....</b>	<b>83</b>
<b>Chapter 7. Job Queue Element — JQE.....</b>	<b>89</b>
<b>Chapter 8. JQE/JCT Access Control Table — JQX.....</b>	<b>91</b>
<b>Chapter 9. Logical Unit Control Table — LCT and LCTLU.....</b>	<b>93</b>
<b>Chapter 10. Master Job Definition — MJD.....</b>	<b>99</b>
<b>Chapter 11. Resident Logical Units Table — RLT.....</b>	<b>107</b>
<b>Chapter 12. Sequential Transfer Data Area — SEQ.....</b>	<b>109</b>
Scheduler Interface Control Area CSECT — SICA.....	120
SNA Buffer Pool Control Block — SNBP.....	121
<b>Chapter 13. Transfer Vector Table — TVT.....</b>	<b>123</b>
<b>Chapter 14. Trace Work Area — TWA.....</b>	<b>149</b>
<b>Chapter 15. Transaction Origin Data Area — XOID.....</b>	<b>151</b>
<b>Appendix A. Accessibility.....</b>	<b>153</b>
Accessibility features.....	153
Consult assistive technologies.....	153
Keyboard navigation of the user interface.....	153
Dotted decimal syntax diagrams.....	153
<b>Notices.....</b>	<b>157</b>
Terms and conditions for product documentation.....	158
IBM Online Privacy Statement.....	159
Policy for unsupported hardware.....	159
Minimum supported hardware.....	159
Programming Interface Information.....	160
Trademarks.....	160
<b>GLOSSARY.....</b>	<b>161</b>
<b>Index.....</b>	<b>165</b>

---

# Figures

1. Title Page of the Formatted Dump.....	2
2. BDT TVT in the Formatted Dump.....	5
3. BDT FCT in the Formatted Dump — Resident Functions.....	26
4. BDT FCT in the Formatted Dump — Nonresident Functions.....	28
5. BDT JQE in the Formatted Dump.....	28
6. BDT RLT in the Formatted Dump.....	29
7. BDT LCT in the Formatted Dump.....	30
8. BDT SNA Line and Node Variable Entries in the Formatted Dump.....	31
9. Structure of the BDT SNA control blocks.....	33
10. BDT CPD and CPB in the Formatted Dump.....	34
11. Contents of BDTNUC in the Formatted Dump.....	36
12. Example of a BDT Trace Table.....	41
13. BDT control blocks at file-to-file nodes after a transaction is submitted.....	46
14. BDT control blocks at file-to-file nodes after the job is scheduled.....	47
15. BDT control blocks at file-to-file nodes after the job is purged.....	48
16. BDT control blocks at nje nodes after a transaction is submitted.....	49
17. BDT control blocks at nje nodes after the job is scheduled.....	50
18. BDT control blocks after the job is purged.....	51
19. BDT storage management control blocks.....	52
20. BDT session-related control blocks.....	53
21. BDT job scheduling and dispatching control blocks.....	54
22. BDT SNA buffer management control blocks.....	55



---

# Tables

1. RPL Request Types..... 32

2. BDTDATR Data Area..... 42





## About This Book

---

This book is a reference for diagnosing problems with the Bulk Data Transfer (BDT) licensed program. It describes the dumps, trace facility, and data areas you will need to identify the part of BDT that is causing a problem, and to gather information to report a problem to IBM.

In addition, this book is a reference for writing and testing user exit routines. For this purpose, use Chapter 3, “BDT Data Areas,” on page 45, along with [\*z/OS BDT Installation\*](#).

## Who Should Read This Book

---

This book is for system programmers responsible for detecting and solving BDT problems or coding and testing user exit routines.

## How to Use This Book

---

If you are new to BDT, use the index or table of contents to help you find what you need.

This book contains three chapters and a glossary:

- Chapter 1, “[The BDT Formatted Dump](#),” on page 1 explains how to request and use the BDT formatted dump.
- Chapter 2, “[The MVS SVC Dump](#),” on page 37 explains how to request and use the MVS SVC dump, which includes the BDT trace table.
- Chapter 3, “[BDT Data Areas](#),” on page 45 contains descriptions and layouts of BDT data areas.

## Related Reading

---

Where necessary, this book references information in other books, using shortened versions of the book title. For complete titles and order numbers of the information for all products that are part of z/OS, see [\*z/OS Information Roadmap\*](#).



## How to send your comments to IBM

---

We invite you to submit comments about the z/OS product documentation. Your valuable feedback helps to ensure accurate and high-quality information.

**Important:** If your comment regards a technical question or problem, see instead [“If you have a technical problem”](#) on page xi.

Submit your feedback by using the appropriate method for your type of comment or question:

### **Feedback on z/OS function**

If your comment or question is about z/OS itself, submit a request through the [IBM RFE Community](#) ([www.ibm.com/developerworks/rfe/](http://www.ibm.com/developerworks/rfe/)).

### **Feedback on IBM® Documentation function**

If your comment or question is about the IBM Documentation functionality, for example search capabilities or how to arrange the browser view, send a detailed email to IBM Documentation Support at [ibmdocs@us.ibm.com](mailto:ibmdocs@us.ibm.com).

### **Feedback on the z/OS product documentation and content**

If your comment is about the information that is provided in the z/OS product documentation library, send a detailed email to [mhvrcfs@us.ibm.com](mailto:mhvrcfs@us.ibm.com). We welcome any feedback that you have, including comments on the clarity, accuracy, or completeness of the information.

To help us better process your submission, include the following information:

- Your name, company/university/institution name, and email address
- The following deliverable title and order number: z/OS BDT Diagnosis Reference, SC14-7586-50
- The section title of the specific information to which your comment relates
- The text of your comment.

When you send comments to IBM, you grant IBM a nonexclusive authority to use or distribute the comments in any way appropriate without incurring any obligation to you.

IBM or any other organizations use the personal information that you supply to contact you only about the issues that you submit.

## If you have a technical problem

---

If you have a technical problem or question, do not use the feedback methods that are provided for sending documentation comments. Instead, take one or more of the following actions:

- Go to the [IBM Support Portal](#) ([support.ibm.com](http://support.ibm.com)).
- Contact your IBM service representative.
- Call IBM technical support.



## Summary of changes

---

This information includes terminology, maintenance, and editorial changes. Technical changes or additions to the text and illustrations for the current edition are indicated by a vertical line to the left of the change.

**Note:** IBM z/OS policy for the integration of service information into the z/OS product documentation library is documented on the z/OS Internet Library under [IBM z/OS Product Documentation Update Policy \(www-01.ibm.com/servers/resourcelink/svc00100.nsf/pages/ibm-zos-doc-update-policy?OpenDocument\)](http://www-01.ibm.com/servers/resourcelink/svc00100.nsf/pages/ibm-zos-doc-update-policy?OpenDocument).

## Summary of changes for z/OS BDT Diagnosis Reference for Version 2 Release 5 (V2R5)

---

This information contains no technical changes for this release.

## Summary of changes for z/OS BDT Diagnosis Reference for Version 2 Release 4 (V2R4) and its updates

---

This information contains no technical changes for this release.

## Summary of changes for z/OS BDT Diagnosis Reference for Version 2 Release 3 (V2R3) and its updates

---

This information contains no technical changes for this release.



---

# Chapter 1. The BDT Formatted Dump

This chapter discusses the BDT formatted dump. It explains:

- The purpose of the BDT formatted dump
- How to request the BDT formatted dump
- The contents of the BDT formatted dump

---

## Purpose of the BDT Formatted Dump

The BDT formatted dump is a good place to start analyzing your BDT subsystem problems. It contains information about the failing module, resident modules in the BDT nucleus, and BDT control blocks. Use this dump together with the MVS SVC dump, which is described in Chapter 2.

---

## How to Request the BDT Formatted Dump

The BDT initialization stream and BDT commands allow you to request that a BDT formatted dump be taken during normal processing, or when an abend occurs.

- During normal processing, you can request a BDT formatted dump with the DUMP command. When you issue the DUMP command, an MVS SNAP dump appears in the BDT formatted dump before the contents of BDTNUC. You also receive an SVC dump. The format of the DUMP command is `DUMP,TITLE='dump-title'`, where *dump-title* is a title you assign to the dump. For more information, see [z/OS BDT Commands](#).
- When an abend occurs, BDT can either take a formatted dump, not take a formatted dump, or ask if a formatted dump is to be taken. You specify which option you want with the WANTDUMP parameter of the OPTIONS statement in the initialization stream. For more information on coding the OPTIONS statement, see [z/OS BDT Installation](#). The MODIFY,DUMP command allows you to change the option specified in the WANTDUMP parameter. `MODIFY,DUMP,YES` requests that when an abend occurs, BDT is to take a formatted dump. `MODIFY,DUMP,ASK` requests that when an abend occurs, BDT is to ask if a formatted dump is to be taken. For more information on this command, see [z/OS BDT Commands](#).

---

## Contents of the Formatted Dump

The BDT formatted dump contains:

- A title page. This gives summary information about the failing module.
- A map of BDTNUC (the BDT nucleus). This lists resident modules and data areas and their corresponding addresses.
- Fields for these BDT control blocks:
  - The transfer vector table (TVT)
  - The function control table (FCT) — a page for each resident function and each active job
  - The job queue element (JQE)
  - The resident logical units table (RLT)
  - The logical unit control tables (LCTs)
  - The BDT SNA line and node variable entries, including the logical unit control blocks (LCBs), ACF/VTAM's request parameter list (RPL), and LCTs for logical units (LCTLUs).
  - The cell pool directory (CPD)
  - The cell pool control block (CPB)
- The hexadecimal contents of BDTNUC.

The rest of this chapter describes the sections of the BDT formatted dump. The sections are described in the order in which they appear in an actual dump.

Each section begins a new page in this chapter, and each section is illustrated with an example from a dump. Parts of the examples are identified with numbers. These numbers point you to the text that follows the examples — an area marked with a **1** in the dump is described under **1** in the text.

The examples in this chapter may not, field-for-field, match the contents of your dump.

## Dump Title Page

The first page of the BDT formatted dump is a title page that describes the failing module.

```

1 BDT FORMATTED DUMP:  SOC1 IN LOW-MEM      SYSID=SYSA1      DATE=85211 TIME= 7:58:30 PAGE=001

2      SOC1 ABEND AT 00000000 (LOW-MEM +00000000)

3 PSW AT TIME OF INTERRUPT: 078C0000 00000002  4 ILC-02  5 INTC=0001

6 THE INTERRUPTING INSTRUCTION IS: 0008

7 REGISTER CONTENTS AT TIME OF INTERRUPT:

R0 =00000014  R1 =001EAC48  R2 =001EAD08  R3 =00000158  R4 =001CD038  R5 =00236554  R6 =001EACF4  R7 =0029A460
R8 =0029C3E8  R9 =00236554  R10=0029C3E8  R11=001DE2D8  R12=00197000  R13=00201700  R14=4019D674  R15=00000000

8 THE ACTIVE FCT IS NJS      (00236554); JOB IS 0003 (JOBA )

```

Figure 1. Title Page of the Formatted Dump

- **1** This line is the dump heading. It identifies each page of the BDT formatted dump. In the heading:
  - **BDT FORMATTED DUMP** is the dump name. The dump name identifies the completion, or abend, code (SOC1), and the name of the failing module (LOW-MEM). There are three possible completion code prefixes:
    - S is the MVS system completion code.
    - U is the initialization completion code.
    - BD is the BDT completion code.
  - See [z/OS BDT Messages and Codes](#) for more information on completion codes.
- **SYSID** is the name of the BDT node.
- **DATE** is the date (yyddd) when the dump began processing.
- **TIME** is the hour, minute, and second when the dump began processing.
- **PAGE** is the dump page number.
- **2** This line contains abend information:
  - **SOC1** is the completion code.
  - **00000000** is the virtual address of the failing instruction. **Do not adjust this address for the length of the failing instruction.**
  - **(LOW-MEM +00000000)** is the relative address of the failing instruction — module name and displacement.
- **3 PSW AT TIME OF INTERRUPT** is the PSW for the program when the abend occurred, or when the request for a dump was made.
- **4 ILC** is the hexadecimal instruction length code.
- **5 INTC** is the hexadecimal interrupt code or SVC number.



- **6 INTERRUPTING INSTRUCTION** is the object code of the failing instruction.
- **7 REGISTER CONTENTS** is the contents of general registers 0-15.
- **8 ACTIVE FCT** is the name of the BDT function in control when the abend occurred, and the address of the abending FCT entry.

**Note:** If the abending module is not a resident function, the title page will show the job number and job name in addition to the fields described.

## Map of BDT Nucleus (BDTNUC)

The map of the BDT nucleus is a list of the names and virtual addresses of all modules, service routines, and data areas that reside in BDTNUC. Modules that reside in BDTNUC are called *resident functions*.

BDTNUC is located in the BDT address space at the low end of the private area. It is a non-reusable load module, loaded during BDT initialization by BDTINTK.

### Map of BDTNUC in the Formatted Dump

BDT FORMATTED DUMP:    SOC1 IN LOW-MEM                    SYSID=SYSA1    DATE=85211    TIME= 7:58:30  
PAGE=002

#### MAP OF BDT NUCLEUS

00197000	TVT	
001977C6	BDTGRVT	TRANSTAB
00198668	BDTGRPT	
00198698	BDTGRPT	FCTTOP
0019B878	BDTGRPT	BDTXEXL
0019BC78	BDTGRCPD	
0019BCA4	BDTGRCPD	CPDTABLE
0019BE00	BDTGRQC	
0019BE2C	BDTGRQC	BDTXBPL
0019C590	BDTGRQC	BDTXGCL
0019CB32	BDTGRQC	BDTXRCL
0019D064	BDTGRQC	BDTXDPL
0019D42C	BDTGRQC	BDTXCPD
0019D550	BDTGRSV	
0019D57C	BDTGRSV	ASAVEYES
0019D674	BDTGRSV	ASARETRN
0019D810	BDTGRTX	
0019DB6C	BDTGRTX	ATRSTART
0019DB6C	TRACEHDR	
0019E0E8	BDTIFCM	
0019F318	BDTIFCS	
0019F750	BDTLAMB	BDTLOPN
0019F9DA	BDTLAMB	BDTLCLS
0019FCB0	BDTLAMB	BDTLPUT
0019FE38	BDTLAMB	BDTLGET

001A004C	BDTLAMB	BDTLRD
001A0094	BDTLAMB	BDTLWRT
-----		
-----		
001C3360	BDTABLG	
001C49D0	BDTABMN	
001C4BF8	BDTABMN	BDTMODUP
001C4DAE	BDTABMN	FAILDAPX
001C5024	BDTABMN	ABSERV2
001C572E	BDTABMN	ABSERV1
001C6098	BDTABNO	
001C6D8C	BDTABNO	ABNCORE
001C70C4	BDTABNO	ABNDCB
001C72D0	BDTDJNR	
001C7A68	BDTTQDRV	
001C82C8	BDTTQINI	
001C8B08	BDTTQSUB	
001C98C0	BDTTQRCV	
001CA048	BDTTQCMD	
001CA410	BDTTQACK	
001CA860	BDTTQDAT	
001CB430	BDTGRCP	CKPTDATA
001CB430	CKPTDATA	

## Transfer Vector Table (TVT)

The BDT transfer vector table (TVT) is the primary control block of BDT. It includes pointers to the beginnings of control block chains, addresses of general BDT routines, constants, and initialization parameters from the OPTIONS statement. It is located at CSECT BDTGRVT at the beginning of BDTNUC.

The TVT entries occupy three pages in the BDT formatted dump. The entries are described in the pages that follow. A sentence at the beginning of each page tells which portion of which TVT page in the BDT formatted dump is being described.

A layout of the TVT, with an alphabetical cross-reference of the fields in the TVT, is included in [Chapter 3, "BDT Data Areas,"](#) on page 45.

BDT FORMATTED DUMP: SOC1 IN LOW-MEM

SYSID=SYSA1

DATE=85211

TIME= 7:58:30 PAGE=005

## TRANSFER VECTOR TABLE (BDTDTV) - VERSION 2 RELEASE 1

OFFSET	LABEL	DATA	LABEL	DATA	LABEL	DATA	LABEL	DATA
0000	TVTID	E3E5E340	TVTVERS	F1F0F0F0	TVTLNGTH	0538	TVTINDAT	0085211F
0010	TVTINTIM	07491325	TVTRELNR	F2F0F0F0	TVTASAVE	0019D57C	TVTASVRT	0019D674
0020	TVTADEQ	001BE3B0	TVTAPTMN	001BE088	TVTAGTMN	001BDD04	TVTALLOC	001BCA38
0030	TVTXBPL	0019BE2C	TVTXCPD	0019D42C	TVTXGCL	0019C590	TVTXRCL	0019CB32
0040	TVTXDPL	0019D064	TVTAWAIT	80	TVTAWTA	1B	TVTAWTL	81
0049	TVTAWTLA	1B	TVTAWTOF	50	TVTAWTOA	1B	TVTAWTOL	51
0051	TVTWTOLA	1B	TVTAWTE	FF	TVTAWTEA	1B	TVTABMNO	001C49D0
005C	TVTABND0	001C6098	TVTABSRV	001C5024	TVTFLDAP	001C4DAE	TVTGSDAX	001C572E
006C	TVTCSCEF	00	TVTCSRQR	001C3060	TVTCSRCP	00233EC0	TVTADFCT	001C26B2
0078	TVTDLFCT		TVTFNFCT	001C284A	TVTGTFCF	001C257C	TVTPTFCT	001C27CE
-----								
0698	TVTAPLNJ+4	C1F1D540	TVTASRIM	00001770	TVT			4040
06B6	TVTRSJCT	0064	TVTSYSID	E2E8E2C1	TVTSYSID+4	F1404040	TVTNJEID	E2E8E2C1
06C4	TVTNJEID+4	F1D54040	TVTTQITD	00000BB8	TVTFSFG1	01	TVTFSFG2	03
06CE	TVTOPTNS	C8	TVTQIDFG	00	TVTSYSLG	801C9670	TVTJES	F3
06D5	TVTSLOGC	F2	TVTJSXMX	0040	TVTSLOGL	00001770	TVTSLOGP	0000003C
06E0	TVTSYSN	E2E8E2C1	TVTSYSN+4	F3F0F8F1	TVTRSD29	00000000	TVTRSD30	00000000
06F0	TVTRSD31	00000000	TVTRSD32	00000000	TVTRSS30	00000000	TVTRSS31	00000000
0700	TVTRSS32	00000000	TVTRSS33	00000000	TVTRSS34	00000000	TVTRSS35	00000000
0710	TVTRSU01	00000000	TVTRSU02	00000000	TVTRSU03	00000000	TVTRSU04	00000000
0720	TVTSXHDR	E7D6C9C4	TVTSXREL	F1F0F0F0	TVTSXLEN	003C	TVTSXBS1	E2E8E2C1
072E	TVTSXBS1+4	F1404040	TVTSXBSN	E2E8E2C1	TVTSXBSN+4	F3F0F8F1	TVTSXTYP	07
073B	TVTSXFL1	00	TVTSDDRS	00000000	TVTSDDRS+4	00000000	TVTSXRD2	00000000
0748	TVTSXRD3	00000000	TVTSXRS1	00000000	TVTSXRS2	00000000	TVTSXRU1	00000000

Figure 2. BDT TVT in the Formatted Dump

This page describes the upper-left quarter of the first TVT page in the dump.

**TVTID**

is the control block acronym.

**TVTVERS**

is the TVT version ID.

**TVTINTIM**

is the time BDT started — hhmmsssth.

**TVTRELNR**

is the BDT release number.

**TVTADEQ**

indicates resource management.

**TVTAPTMN**

is the FREEMAIN address.

**TVTXBPL**

is the quik cell SVCS-build pool.

**TVTXCPD**

is the quik cell SVCS-CPD access.

**TVTXDPL**

is the quik cell SVCS-DEL pool.

**TVTAWAIT**

is the await condition code.

**TVTAWTLA**

is MFM await processing.

**TVTAWTOF**

is the await-off condition code.

**TVTWTOLA**

is MFM await processing.

**TVTAWTE**

is the await exit condition code.

**TVTABNDO**

is the formatted dump router.

**TVTABSRV**

is the ESTAE recovery abend SVC.

**TVTCSECF**

is the common subtask request ECF.

**TVTCSRQR**

is the common subtask request queue routine.

**TVTDLFCT**

is the delete FCT routine.

**TVTENFCT**

is the ENQ/DEQ FCT routine.

**TVTIFECF**

is the interfunction communication manager ECF.

**TVTIFSND**

is the interfunction communication send routine.

**TVTJNUMR**

is the return-a-job-number routine.

**TVTJSSRT**

is the DAP return point to BDTGRJR.

**TVTGETLU**

is the LU “put”.

**TVTPUTLU**

is the “put” LU.

**TVTLPUTO**

is the LU “get”.

**TVTLGETO**

is the LU “put”.

**TVTXTRC**

is the trace routine entry point.

**TVTVATR**

is the trace routine control area.

**TVTRSD02**

is reserved.

**TVTRFMT0**

is the RBAM format queue.

**TVTOPNO**

is the open RBAM file.

**TVTRPRGO**

indicates return blocks.

**TVTSNOPN**

is the SNA BDTXLOPN extension.

**TVTSNCLS**

is the SNA BDTXLCLS extension.

**TVTSCDTA**

is the BDT SNA manager data area.

**TVTSNRD**

is the SNA BDTXLWRD extension.

**TVTRQTBA**

is the RESQUEUE table address.

**TVTRQTB**

is the RESQUEUE table delete character.

**TVTXJQE**

is the JQE access routine.

**TVTXCOMP**

is the SCNBLNK compression routine.

**TVTCKPNT**

is the checkpoint.

**TVTABNGT**

is the virtual address validation routine.

**TVTRSD51**

is reserved.

**TVTMDLK**

is the module name look-up routine.

**TVTMFMPE**

is the emulation program for the multi-function monitor.

**TVTSUPC**

is the superscan routine entry point.

**TVTXOIDF**

is the XOID formatting routine.

**TVTXTIME**

is the timing services routine.

This page describes the upper-right quarter of the first TVT page in the dump.

**TVTLNGTH**

is the TVT length.

**TVTINDAT**

is the date BDT started — 00yydddf.

**TVTASAVE**

is the ASAVE processing routine.

**TVTASVRT**

is the ASAVE processing return.

**TVTAGTMN**

is the GETMAIN address.

**TVTALLOC**

is the address of the dynamic allocation routine.

**TVTXGCL**

is the quik cell SVCS “get” cell.

**TVTXRCL**

is the quik cell SVCS-return cell.

**TVTAWTA**

indicates MFM await processing.

**TVTAWTL**

is the await-list condition code.

**TVTAWTOA**

indicates MFM await processing.

**TVTAWTOL**

is the awaitoff-list condition code.

**TVTAWTEA**

is MFM await processing.

**TVTABMNO**

is the BDT ESTAE routine.

**TVTFLDAP**

is the fail-a-DAP routine.

**TVTGSDAX**

is the ESTAE exit abend SVC routine.

**TVTCSRCP**

is the common subtask request cell pool.

**TVTADFCT**

is the “add” FCT routine.

**TVTGTFCT**

is the “get” FCT routine.

**TVTPTFCT**

is the “put” FCT routine.

**TVTFDJNR**

is the find-a-job-number routine.

**TVTJOBNR**

is the job number.

**TVTSSNJ**

is the DAP return point to BDTGRNJ.

**TVTXCKPT**

is the DAP checkpoint routine.

**TVTLOPNO**

is the LU open routine.

**TVTLCLS0**

is the close-RBAM-file routine.

**TVTLRDO**

is the LREAD routine emulation program.

**TVTLWRT0**

is the LWRITE routine emulation program.

**TVTLGREC**

is the logical record suppression routine.

**TVTRSD01**

is reserved.

**TVTRALC0**

indicates allocation blocks (RBNS).

**TVTRCLS0**

is the LU close routine.

**TVTRREDO**

is the read data routine.

**TVTRWRT0**

is the write data routine.

**TVTSNGET**

is set by the SNA BDTXLGET extension.

**TVTSNPUT**

is set by the SNA BDTXLPUT extension.

**TVTSNWRT**

is set by the BDTXLWRT extension.

**TVTDQMSG**

is the BDTXDQMS service routine.

**TVTRQTBP**

is the RESQUEUE table “put” routine.

**TVTXJCT**

is the JCT access routine.

**TVTXDCMP**

is the data compress/decompress routine.

**TVTBDKEY**

is the BDT storage protect key.

**TVTCSF**

is the call subtask function routine.

**TVTDJNR**

is DJC net release processing.

**TVTMESAG**

is the console message.

**TVTNMSG**

is message handler support.

**TVTTUAM**

is the MJD text unit access method.

**TVTRSD05**

is reserved.

**TVTRSD06**

is reserved.

**TVTXACC**

is the BDT accounting STIMER routine.

This page describes the lower-left quarter of the first TVT page in the dump.

**TVTXLOG**

is the BDT log manager.

**TVTSLACB**

is the access method CB pointer.

**TVTRSD10**

is reserved.

**TVTEXL**

is the user exit routine address list.

**TVTRSD13**

is reserved.

**TVTRSD14**

is reserved.

**TVTRSS06**

is reserved.

**TVTRS07**

is reserved.

**TVTRSS10**

is reserved.

**TVTRSS11**

is reserved.

**TVTRSS14**

is reserved.

**TVTRSS15**

is reserved.

**TVTINITF**

is the BDT initialization flag.

**TVTINDTA**

is the pointer to the initialization data CSECT.

**TVTICMCP**

is the address of the ICMB cell pool CPB.

**TVTIFCCP**

is the address of the IFC cell pool CPB.

**TVTJMLCP**

is the address of the JML cell pool CPB

**TVTNUMAP**

is the map of the BDTNUC CSECTs.

**TVTSVCPB**

is the address of the save area cell pool CPB.

**TVTTQECF**

is the address of the TQE cell pool CPB.

**TVTLCTUN**

is set by the BDTINGN logical units table.

**TVTRSTPU**

is the first physical entry in restabilization.

**TVTSNLTP**

is the BDT SNA line LCTUNITS chain.

**TVTXFER**

is the start of transfer LCTs.

**TVTRSD18**

is reserved.

**TVTRSS16**

is reserved.

**TVTXDQUE**

is the transaction driver queue.

**TVTADFQE**

is the address of the first queue entry.

**TVTXDQLO**

is the transaction driver low watermark.

**TVTXMQUE**

is the cross-memory queue.

**TVTXMQHI**

is the cross-memory high watermark.

**TVTXMQLO**

is the cross-memory low watermark.



**TVTRSV02**

is reserved.

**TVTRSV03**

is reserved.

**TVTNRDAP**

is the dynamic DAP counter.

**TVTCLDAP**

is the called DAP counter.

**TVTRSV05**

is reserved.

**TVTRSV06**

is reserved.

**TVTRSS19**

is reserved.

**TVTRSS20**

is reserved.

**TVTMTECB**

is the BDT master ECB flag.

**TVTAMECB**

is the address of the master ECB.

**TVTNUECB**

is the ECB that BDTINTK waits on.

**TVTAMQUE**

is the BDT action message queue.

**TVTCMTCB**

is the TCB for BDTCMDV.

**TVTCSRQU**

is the common subtask request queue.

**TVTFCTTP**

is the first FCT entry.

**TVTMSGQU**

is the OCMB queue for BDTMSDV.

**TVTJQX**

is the address of the JQX.

**TVTJSSFC**

is the BDTGRJS FCT.

This page describes the lower-right quarter of the first TVT page in the dump.

**TVTSLEXL**

is an access method CB pointer.

**TVTSLRPL**

is an access method CB pointer.

**TVTRSD11**

is reserved.

**TVTRSD12**

is reserved.

**TVTRSD15**

is reserved.

**TVTRSS05**

is reserved.

**TVTRSS08**

is reserved.

**TVTRSS09**

is reserved.

**TVTRSS12**

is reserved.

**TVTRSS13**

is reserved.

**TVTEPE**

is the end of entry points.

**TVTABDCB**

is the abend DCB.

**TVTMSTCB**

is the BDT master TCB.

**TVTFCTCP**

is the address of the FCT cell pool CPB.

**TVTIFNCP**

is the address of the NJE IFC cell pool CPB.

**TVTJCBCP**

is the address of the JCT buffer cell pool CPB.

**TVTOCMCP**

is the address of the OCMB cell pool CPB.

**TVTSCPD**

is the BDT system cell pool directory.

**TVTTQICP**

is the address of the TQI cell pool CPB.

**TVTIFC**

is the start of the IFC LCTs.

**TVTRLTTB**

is the resident RLT table.

**TVTSNBP**

is the BDT SNA buffer pool.

**TVTMSGDV**

is the address of the first MSGD data area.

**TVTRSD17**

is reserved.

**TVTRSS17**

is reserved.

**TVTRSS18**

is reserved.

**TVTXDQCT**

is the number of elements queued.

**TVTXDQHI**

is the high watermark.

**TVTXMQ**

is the BDTCMDV cross-memory queue.

**TVTXMQCT**

is the number of elements on the queue.

**TVTXDECF**

is the transaction driver ECF.

**TVTRSV01**

is reserved.

**TVTRSV04**

is reserved.

**TVTRSDAP**

is the resident DAP counter.

**TVTPFLG1**

is the BDT termination flag 1.

**TVTPFLG2**

is the BDT termination flag 2.

**TVTRSV07**

is reserved.

**TVTRSV08**

is reserved.

**TVTRSS21**

is reserved.

**TVTITECB**

is the ECB for BDTINIT to wait on.

**TVTMCECB**

is the MCS console command ECB.

**TVTMSECB**

is the BDT master ECB.

**TVBTAB**

is the RBAM bit table.

**TVTCKPAR**

is the checkpoint area.

**TVTEFTOP**

is the top of the RESQUEUE ending function.

**TVTNETOP**

is the NJE ending function queue.

**TVTITKPM**

is the address of the BDTINTK parameters list.

**TVTJNM**

is the address of the job number table.

**TVTLBDCB**

is the BDTLIB DCB pointer.

**TVTRSD19**

is reserved.

This page describes the upper-left quarter of the second TVT page in the dump.

**TVTSTGLS**

is the start of the nucleus.

**TVTNUCND**

is the end-of-nucleus flag.

**TVTRSTBL**

is the resource management table.

**TVTTRTAB**

is the system-translate table.

**TVTSSCVT**

is the pointer to the BDT SSCVT.

**TVTWFACT**

is the “wait” FCT address.

**TVTRSD22**

is reserved.

**TVTRSD23**

is reserved.

**TVTRSS24**

is reserved.

**TVTRSS25**

is reserved.

**TVTRSS28**

is reserved.

**TVTRSS29**

is reserved.

**TVTDDBRQ+8**

is the master DDBFX, bytes 9-12.

**TVTDDBFX**

is the master DDBFX.

**TVTSZBUX**

is the initialization flag, first halfword.

**TVTBUFSZ**

is the size of the buffer — halfword.

**TVTIFCGM**

is the current storage being used for IFC buffers obtained by GETMAIN.

**TVTIFCCT**

is the current count of IFC buffers obtained by GETMAIN.

**TVTRSU05**

is reserved.

**TVTRSU06**

is reserved.

**TVTRSD56**

is reserved.

**TVTRSD57**

is reserved.

**TVTRSD60**

is reserved.

**TVTJSCMX**

indicates the currently scheduled transfers.

**TVTRSD36**

is reserved.

**TVTRSD37**

is reserved.

**TVTRSD40**

is reserved.

**TVTRSD41**

is reserved.

**TVTRSS42**

is reserved.

**TVTRSS43**

is reserved.

**TVTACECF**

is the accounting ECF.

**TVTRSD44**

is reserved.

**TVTRSTFL**

is the BDT start flag.

**TVTSTATE**

is the BDT connection state machine.

**TVTTQECF**

is the TQI ECF.

**TVTTQIOF**

is the TQI-inoperative flag.

**TVTCPSD2**

is group 2 of the slow-down flags.

**TVTCDECf**

is the communications driver ECF.

**TVTRSD47**

is reserved.

**TVTRSD53**

is reserved.

**TVTRSS49**

is reserved.

**TVTRSS50**

is reserved.

**TVTRSS53**

is reserved.

**TVTRSS54**

is reserved.

**TVTBDTPL**

is used by BDTXGMPM for the default subpool.

**TVTBLANK**

indicates constant blanks.

**TVTHXCHR**

indicates hexadecimal characters.

**TVTRSD26**

is reserved.

**TVTSNSET**

is the total of SNA sessions for file-to-file.

**TVTSNSTN**

is the total of SNA sessions for NJE.

**TVTRSD55**

is reserved.

**TVTJMLWA**

is the JML work area, bytes 1-4.

**TVTJMLWA+12**

is the JML work area, bytes 13-16.

**TVTCID**

is the component ID, bytes 1-4.

This page describes the upper-right quarter of the second TVT page in the dump.

**TVTNUCNA**

is the end of nucleus address.

**TVTOCMQU**

is the output console message queue.

**TVTSCAN**

is the scan/validate/translate table.

**TVTSPDCB**

is the spool DCB.

**TVTRSD20**

is reserved.

**TVTRSD21**

is reserved.

**TVTRSD24**

is reserved.

**TVTRSS23**

is reserved.

**TVTRSS26**

is reserved.

**TVTRSS27**

is reserved.

**TVTDDBRQ**

is the master DDBFX, bytes 1-4.

**TVTDDBRQ+4**

is the master DDBFX, bytes 5-8.

**TVTDDBFX+4**

is the master DDBFX, bytes 1-4.

**TVTRSD33**

is reserved.

**TVTRSD34**

is reserved.

**TVTCPUID**

is the CPU ID.

**TVTIFCGH**

is the high watermark for the IFC.

**TVTIFCCH**

is the high watermark for the number of IFC buffers obtained by GETMAIN.

**TVTRSU07**

is reserved.

**TVTRSU08**

is reserved.

**TVTRSD58**

is reserved.

**TVTRSD59**

is reserved.

**TVTLNOHI**

is the TQI high watermark for the LCTOUT queue.

**TVTLNOLO**

is the TQI low watermark for the LCTOUT queue.

**TVTRSD38**

is reserved.

**TVTRSD39**

is reserved.

**TVTRSS40**

is reserved.

**TVTRSS41**

is reserved.

**TVTRSS44**

is reserved.

**TVTRSS45**

is reserved.

**TVTJSFL1**

is a JSS flag byte.

**TVTJSFL2**

is a JSS flag byte.

**TVTSTFLG**

is the BDT connect state machine flag.

**TVTSNECF**

is the BDT SNA manager ECF.

**TVTTQIFG**

is the TQI control flag.

**TVTCPSD1**

is group 1 of the slowdown flags.

**TVTCDECX**

is the communication driver ECF extension.

**TVTMSGCF**

is the message data set driver ECF.

**TVTRSD54**

is reserved.

**TVTRSS48**

is reserved.

**TVTRSS51**

is reserved.

**TVTRSS52**

is reserved.

**TVTRSS55**

is reserved.

**TVTADMSK**

is the constant for the address mask.

**TVTCPUF**

is the CPU factor.

**TVTDFACT**

indicates default accounting.

**TVTRMFF**

is the hexadecimal constant FF.

**TVTRM7F**

is the hexadecimal constant 7F.

**TVTSNSEL**

is the session limit.

**TVTZERO**

is the zero constant.

**TVTJMLWA+4**

is bytes 5-8 of the JML work area.

**TVTJMLWA+8**

is bytes 9-12 of the JML work area.

**TVTCID+4**

is bytes 5-8 of the component ID.

**TVTCIDB**

is the component ID base.

This page describes the lower-left quarter of the second TVT page in the dump.

**TVTRSS56**

is reserved.

**TVTRSS57**

is reserved.

**TVTEBCOM**

is the NJE communications VLU name (external).

**TVTEBCS1**

is the an NJE VLU name (external).

**TVTEBCS1+9**

is an NJE VLU name (external).

**TVTEBCS2**

is an NJE VLU name (external).

**TVTEBCS2+9**

is an NJE VLU name (external).

**TVTEBCS3**

is an NJE VLU name (external).

**TVTEBCS3+9**

is an NJE VLU name (external).

**TVTEBCS4**

is an NJE VLU name (external).

**TVTEBCS4+9**

is an NJE VLU name (external).

**TVTEBCS5**

is an NJE VLU name (external).

**TVTEBCS5+9**

is an NJE VLU name (external).

**TVTEBCS6**

is an NJE VLU name (external).

**TVTEBCS6+9**

is an NJE VLU name (external).

**TVTEBCS7**

is an NJE VLU name (external).

**TVTEBCS7+9**

is an NJE VLU name (external).

**TVTSTCOM**

is the NJE communications VLU name (internal).

**TVTSTID1+2**

is an NJE VLU name (internal).

**TVTSTID1+3**

is an NJE VLU name (internal).



**TVTSTID2+2**

is the an NJE VLU name (internal).

**TVTSTID2+3**

is the an NJE VLU name (internal).

**TVTSTID3+2**

is an NJE VLU name (internal).

**TVTSTID3+3**

is an NJE VLU name (internal).

**TVTSTID4+2**

is an NJE VLU name (internal).

**TVTSTID4+3**

is an NJE VLU name (internal).

**TVTSTID5+2**

is an NJE VLU name (internal).

**TVTSTID5+3**

is an NJE VLU name (internal).

**TVTSTID6+2**

is an NJE VLU name (internal).

**TVTSTID6+3**

is an NJE VLU name (internal).

**TVTSTID7+2**

is an NJE VLU name (internal).

**TVTSTID7+3**

is an NJE VLU name (internal).

**TVTCICDYN**

is the DYNALLOC card, bytes 1-4.

**TVTCICDYN+4**

is the DYNALLOC card, bytes 5-8.

**TVTCIDYX+4**

is bytes 5-8 of TVTCIDYX.

**TVTCIDYX+8**

is bytes 9-12 of TVTCIDYX.

**TVTCIDAT**

is the initialization checkpoint data, bytes 1-4.

**TVTCIDAT+4**

is the initialization checkpoint data, bytes 5-8.

**TVTCIDAX+4**

is bytes 5-8 of TVTCIDAX.

**TVTCIDAX+8**

is bytes 9-12 of TVTCIDAX.

**TVTCIDAX+20**

is bytes 21-24 of TVTCIDAX.

**TVTCIDAX+24**

is bytes 25-28 of TVTCIDAX.

**TVTCIDAX+36**

is bytes 37-40 of TVTCIDAX.

**TVTCICK1**

is checkpoint record 1, bytes 1-4.

**TVTCICKX**

is 5 extent entries, bytes 1-4.

**TVTCICKX+4**

is 5 extent entries, bytes 5-8.

**TVTCICKX+16**

is 5 extent entries, bytes 16-19.

**TVTCICK2**

is checkpoint record 2, bytes 1-4.

**TVTCICKY**

is 5 extent entries, bytes 1-4.

**TVTCICKY+4**

is 5 extent entries, bytes 5-8.

**TVTCICKY+16**

is 5 extent entries, bytes 16-19.

**TVTCIJCT**

is the JCT DDB fixed area.

**TVTCIJCX**

is 10 extent entries, bytes 1-4.

**TVTCIJCX+4**

is 10 extent entries, bytes 5-8.

This page describes the lower-right quarter of the second TVT page in the dump.

**TVTRSS58**

is reserved.

**TVTRSS59**

is reserved.

**TVTEBCS1+3**

is an NJE VLU name (external).

**TVTEBCS1+6**

is an NJE VLU name (external).

**TVTEBCS2+3**

is an NJE VLU name (external).

**TVTEBCS2+6**

is an NJE VLU name (external).

**TVTEBCS3+3**

is an NJE VLU name (external).

**TVTENCS3+6**

is an NJE VLU name (external).

**TVTEBCS4+3**

is an NJE VLU name (external).

**TVTEBCS4+6**

is an NJE VLU name (external).

**TVTEBCS5+3**

is an NJE VLU name (external).

**TVTEBCS5+6**

is an NJE VLU name (external).

**TVTEBCS6+3**

is an NJE VLU name (external).

**TVTEBCS6+6**

is an NJE VLU name (external).

**TVTEBCS7+3**

is an NJE VLU name (external).

**TVTEBCS7+6**

is an NJE VLU name (external).

**TVTSTID1**

is an NJE VLU name (internal).

**TVTSTID1+1**

is an NJE VLU name (internal).

**TVTSTID2**

is an NJE VLU name (internal).

**TVTSTID2+1**

is an NJE VLU name (internal).

**TVTSTID3**

is an NJE VLU name (internal).

**TVTSTID3+1**

is an NJE VLU name (internal).

**TVTSTID4**

is an NJE VLU name (internal).

**TVTSTID4+1**

is an NJE VLU name (internal).

**TVTSTID5**

is an NJE VLU name (internal).

**TVTSTID5+1**

is an NJE VLU name (internal).

**TVTSTID6**

is an NJE VLU name (internal).

**TVTSTID6+1**

is NJE VLU name (internal).

**TVTSTID7**

is an NJE VLU name (internal).

**TVTSTID7+1**

is an NJE VLU name (internal).

**TVTABTIM**

is the BDTINCD recursiveabend time delay.

**TVTABMAX**

indicates the BDTINCD recursiveabend, maximum abends.

**TVTCIDYN+8**

is bytes 9-12 of the DYNALLOC card.

**TVTCIDYX**

is 5 extent entries, bytes 1-4.

**TVTCIDYX+12**

is 5 extent entries, bytes 13-16.

**TVTCIDYX+16**

is 5 extent entries, bytes 17-20.

**TVTCIDAT+8**

is the initialization checkpoint data, bytes 9-12.

**TVTCIDAX**

is 10 extent entries, bytes 1-4.

**TVTCIDAX+12**

is 10 extent entries, bytes 13-16.

**TVTCIDAX+16**

is 10 extent entries, bytes 17-20.

**TVTCIDAX+28**

is 10 extent entries, bytes 29-32.

**TVTCIDAX+32**

is 10 extent entries, bytes 33-36.

**TVTCICK1+4**

is checkpoint record 1, bytes 5-8.

**TVTCICK1+8**

is checkpoint record 1, bytes 9-12.

**TVTCICKX+8**

is 5 extent entries, bytes 9-12.

**TVTCICKX+12**

is 5 extent entries, bytes 13-16.

**TVTCICK2+4**

is checkpoint record 2, bytes 5-8.

**TVTCICK2+8**

is checkpoint record 2, bytes 9-12.

**TVTCICKY+8**

is 5 extent records, bytes 9-12.

**TVTCICKY+12**

is 5 extent records, bytes 13-16.

**TVTCIJCT+4**

is the JCT DDB fixed area, bytes 5-8.

**TVTCIJCT+8**

is the JCT DDB fixed area, bytes 9-12.

**TVTCIJCX+8**

is 10 extent entries, bytes 9-12.

**TVTCIJCX+12**

is 10 extent entries, bytes 13-16.

This page describes the upper-left quarter of the third TVT page in the dump.

**TVTCIJCX+16**

is 10 extent entries, bytes 17-20.

**TVTCIJCX+20**

is 10 extent entries, bytes 21-24.

**TVTCIJCX+32**

is 10 extent entries, bytes 33-36.

**TVTCIJCX+36**

is 10 extent entries, bytes 37-40.

**TVTDDR3**

is reserved.

**TVTDDR4**

is reserved.

**TVTJBNTL**

is the default job execution time.

**TVTAPLID**

is the application ID for the open ACB.

**TVTAPLNJ+4**

is the application ID for the NJE ACB, bytes 5-8.

**TVTASRTM**

is the ASR time delay.

**TVTRSJCT**

is the resident JCT maximum count.

**TVTSYSID**

is the BDT system ID for file-to-file.

**TVTNJEID+4**

is the BDT system ID for NJE, bytes 5-8.

**TVTTQITD**

is the TQI time delay — 30 seconds.

**TVTOPTNS**

is the BDT options flag.

**TVTQIDFG**

is the auto disable flag for TQI.

**TVTSLOGC**

is the default BDT SYSLOG class.

**TVTJSXMX**

is the maximum number of scheduled transfers.

**TVTSYSN**

is the SYSNAME for the proc BDT is on, bytes 1-4.

**TVTSYSN+4**

is the SYSNAME for the proc BDT is on, bytes 5-8.

**TVTRSD31**

is reserved.

**TVTRSD32**

is reserved.

**TVTRSS32**

is reserved.

**TVTRSS33**

is reserved.

**TVTRSU01**

is reserved.

**TVTRSU02**

is reserved.

**TVTSXHDR**

is the control block acronym.

**TVTSXREL**

is the version ID.

**TVTSXBSI+4**

is the transaction origin — BDT SYSID.

**TVTSXBSN**

is the transaction origin — BDT SYSNAME.

**TVTSXFL1**

is the XOID flag 1.

**TVTSDDRS**

is the DDNAME.

**TVTSXRD3**

is reserved.

**TVTSXRS1**

is reserved.

**TVTSXRU2**

is reserved.

This page describes the upper-right quarter of the third TVT page in the dump.

**TVTCIJCX+24**

is 10 extent entries, bytes 25-28.

**TVTCIJCX+28**

is 10 extent entries, bytes 29-32.

**TVTDDBR1**

is reserved.

**TVTDDBR2**

is reserved.

**TVTACNTL**

is the accounting timing interval — .01 seconds.

**TVTJBPTY**

is the default job priority.

**TVTAPLID+4**

is the application ID for the open ACB, bytes 5-8.

**TVTAPLNJ**

is the application ID for the NJE ACB.

**TVTJBRPD**

is the job retention period (days).

**TVTRSD25**

is reserved.

**TVTSYSID+4**

is the BDT system ID for FTF, bytes 5-8.

**TVTNJEID**

is the BDT system ID for NJE.

**TVTFSG1**

is the fail-soft flag 1.

**TVTFSG2**

is the fail-soft flag 2.

**TVTSYSLG**

is the SYSLOG flag.

**TVTJES**

is the JES identifier.

**TVTSLOGL**

is the default BDT SYSLOG line limit.

**TVTSLOGP**

is the default BDT SYSLOG page length.

**TVTRSD29**

is reserved.

**TVTRSD30**

is reserved.

**TVTRSS30**

is reserved.

**TVTRSS31**

is reserved.

**TVTRSS34**

is reserved.

**TVTRSS35**

is reserved.

**TVTRSU03**

is reserved.

**TVTRSU04**

is reserved.

**TVTSXLEN**

is the XOID length.

**TVTSXBSI**

is the transaction origin — BDT SYSID.

**TVTSXBSN+4**

is the transaction origin — BDT SYSNAME.

**TVTSXTYP**

is the transaction origin — type.

**TVTSDDRS+4**

is the DDNAME, bytes 5-8.

**TVTSXRD2**

is reserved.

**TVTSXRS2**

is reserved.

**TVTSXRU1**

is reserved.

## Function Control Table (FCT)

---

A function control table (FCT) contains an entry for each resident BDT function and an entry for each nonresident BDT function. The nonresident functions are the dynamic application programs (DAPs) that copy data. The formatted dump produces one page for each FCT entry. The order of the FCT entries indicates their priority at the time the dump is taken.

Figure 3 on page 26 is an example of the page for a *resident* BDT function.

See Figure 4 on page 28 for an example of the page for a nonresident BDT function.

BDT FORMATTED DUMP: SOC1 IN LOW-MEM

SYSID=SYSA1 DATE=85211 TIME= 7:58:30 PAGE=008

## FUNCTION CONTROL TABLES

```

1      2      3
00198698  TCB ADDRESS IS 0077E990  PROGRAM NAME IS TIMER

4  ECF OF X'CO' AT 001B8FCC IS NOT POSTED  5  AWAIT RETURN IS 501B877A

6  ID      VER      LEN
C6C3E340  F1F0F0F0  0190

7  REG 0- 7  800000C0  001B8FCC  001988A8  00244024  00000000  00000005  000001F4  801B89A6
    REG 8-15  001988A8  0077E990  001B86C0  00198698  00197000  00201000  501B877A  00198698

8  SAVCH    PRTY    9  SESEQ    RSD01  10 RSD02    RQAD  11 GSD      GLIST
00198828    FA      00      00      00      00000000  001988A8  00198A9C

    DAPDC     DATAC   DRVRC   LOGINM   LOGINA   ICMQ     IFCM     IFCA     IFCQU
001CB948    00000000  00000000  00000000  00000000  00000000  00000000  00000000  00000000

    JSRSH     RSD04   GETSZ   RSCNT   JCTC    ABECF   ABCNT   RSD05   RSD06
00000000    00000000  0000     0000     0000    FF      00      00      00

    FLAG1     FLAG2   FLAG3   FLAG4   FSFLG   CSRFG   TSFLG   ABCDE
00          00      C0      00      00      00      D0

    RSD07     RSD08   RSD09   RSD10   RSD11   RSD12   RSD13   RSD14
00000000    00000000  00000000  00000000  00      00      00      00

    RSS01     RSS02   RSS03   RSS04   RSS05   RSS06
00000000    00000000  00      00      00      00

    RSU01     RSU02   RSU03   RSU04   RSU05   RSS06
00000000    00000000  00      00      00      00

12 GETUNIT LIST -      NUMBER  GLLUDDNM  GLADDR
                        1          *****

13 CALLING SEQUENCE AND ACTIVE SAVE AREA CHAIN

00198828      SAVWORK-----00000000  SAVBACHN----00194ED8  SAVFOCHN----00201000  SAVRETN-----601DFC63

    REG 0- 7  00000100  00000080  001988A8  00000000  001974CC  00000005  00196B7C  001C49D0
    REG 8-15  001988A8  0077E990  001DFBA8  00198698  00197000  00198698  601DFC6E  001B86C0
    SAVFCT----00198698  SAVRSD01---00000000  D1-00000000  00000000  D2-00000000  00000000
    D3-00000000  00000000  D4-00000000  00000000  D5-00000000  00000000  D6-00000000  00000000

    EP BDTGRTS LOCATED AT 001B86C0 (BDTGRTS +00000000) CALLED FROM 601DFC6C (BDTGSC1 +000000C4)

00201000      SAVWORK-----00000000  SAVBACHN----00198828  SAVFOCHN----00000000  SAVRETN-----13000000

    REG 0- 7  131B8E90  001B8FA4  001988A8  00244024  00000000  00000005  000001F4  801B89A6
    REG 8-15  001988A8  0077E990  001B86C0  00198698  00197000  00198698  13000000  00000000
    SAVFCT----00198698  SAVRSD01---00000000  D1-00000000  00000000  D2-00000000  00000000
    D3-00000000  00000000  D4-00000000  00000000  D5-00000000  00000000  D6-00000000  00000000

```

Figure 3. BDT FCT in the Formatted Dump — Resident Functions

**1** **00198698** is the hexadecimal address of the FCT entry.

**2** **TCB ADDRESS** is the address of the task control block (TCB).

**3** **PROGRAM NAME** is the name of the FCT.

**4** **ECF OF X'CO'** indicates the ECF mask currently outstanding, its address, and whether the ECF is posted.

**5** **AWAIT RETURN** indicates the hexadecimal address to which the AWAIT routine will return when the ECF is posted.

**6** **ID** is the control block ID.

**VER** is the FCT version number.

**LEN** is the length of the FCT.

**7** **REG 0-15** is the FCT register save area, used to save registers over a BDT XWAIT macro service.

**8** **SAVCH** is the address of the active save area chain.

**PRTY** is the function priority.

**DAPDC** is the address of the DAP dictionary entry.



**DATA** is the address of the DAP data CSECT.

**JRSRSH** is the job scheduler requeue request.

**RSD04** is reserved.

**FLAG1** is a flag. See flag byte FCTFLAG1 in a listing of the FCT.

**FLAG2** is a flag. See flag byte FCTFLAG2 in a listing of the FCT.

**RS** fields are reserved.

**9 SESEQ** is the scheduler element (SE) sequence number of this function.

**RSD01** is reserved.

**DRVRC** is the address of the DAP driver CSECT.

**LOGINM** is the LOGIN ECF mask.

**GETSZ** is the size of gotten storage for this entry.

**RSCNT** is the number of resources enqueued.

**FLAG3** is a flag. See flag byte FCTFLAG3 in a listing of the FCT.

**FLAG4** is a flag. See flag byte FCTFLAG4 in a listing of the FCT.

**RS** fields are reserved.

**10 RSD02** is reserved.

**RQAD** is the address of the resident job queue entry.

**LOGINA** is the login ECF address.

**ICMQ** is the input console message queue.

**JCTC** is the system ID of the cancel JCTC function.

**ABECF** is the recursive abend ECF.

**FSFLG** is the DAP fail-soft flag.

**CSRFG** is the common subtask request flag.

**RS** fields are reserved.

**11 GSD** is the address of the GSD.

**GLIST** is the address of the GETUNIT list.

**IFCM** is the IFC ECF mask.

**IFCA** is the IFC ECF address.

**ABCNT** is the recursive abend count.

**RSD05** is reserved.

**TSFLG** is the timing services flag.

**ABCDE** is the formatted job completion code. **RS** fields are reserved.

**12 GETUNIT LIST** contains this information:

**NUMBER** is the number of the GETUNIT list entry for that FCT.

**GLLUDDNM** is the DDNAME of the GETUNIT list entry. (Asterisks indicate that this field is not applicable.)

**GLADDR** is the address of the LCTUNITS table. (Asterisks indicate that this field is not applicable.)

**13 CALLING SEQUENCE AND ACTIVE SAVE AREA CHAIN** is the current save area chained off the FCT entry.

Figure 4 on page 28 is an example of a page for a *nonresident* BDT function. It shows lines describing the DAP that processes the job.

```

BDT FORMATTED DUMP:  SOC1 IN LOW-MEM                      SYSID=SYSA1    DATE=85211    TIME= 7:58:30    PAGE=019
1 00236000 2 TCB ADDRESS IS 00782D90 3 DAP NAME IS SNA 4 JOB NUMBER IS 1 5 JOB PRIORITY IS 15
6 MODULE NAME IS BDTSNA 7 MODULE BASE IS 00289DA0 8 SE SEQUENCE IS 1

ECF OF X'7A' AT 001973A5 IS NOT POSTED AWAIT RETURN IS 5028CFC4

ID      VER      LEN
C6C3E340 F1F0F0F0 0190

REG 0- 7 8000007A 001973A5 001CB430 00000000 001E0FAC A028CE72 00236438 0028ADA0
REG 8-15 0028CE0A 001C1408 0028CB70 00289DA0 00197000 00201400 5028CFC4 00236000

SAVCH    PRTY    SESEQ    RSD01    RSD02    RQAD    GSD    GLIST
00236384 0F      01      00      00      00236438 00236190 00236510

```

Figure 4. BDT FCT in the Formatted Dump — Nonresident Functions

- 1 **00236000** is the hexadecimal address of the DAP.
- 2 **TCB ADDRESS** is the address of the task control block (TCB).
- 3 **DAP NAME** is the name of the DAP.
- 4 **JOB NUMBER** is the number of the job that the DAP represents.
- 5 **JOB PRIORITY** is the priority of the job.
- 6 **MODULE NAME** is the name of the module that represents the DAP (may not be retrievable).
- 7 **MODULE BASE** is the base address of the module that represents the DAP (may not be retrievable).
- 8 **SE** is the sequence number of the DAP being executed (always 1).

## Job Queue Element (JQE)

A job queue element (JQE) contains basic information about an active job.

```

BDT FORMATTED DUMP:  SOC1 IN LOW-MEM                      SYSID=SYSA1    DATE=85211    TIME= 7:58:30    PAGE=024
BDT JOB QUEUE ELEMENTS
1 00257460 2 JOBNAME 3 ID 4 JCTDDB1 JCTDDB2 JCTDDB3 5 NETID 6 JBNO 7 PREV 8 NEXT 9 PRTY 10 UCNT
00000000 - JQE 00000000 00000000 00000100 1 0 0 15 0

11 JQERW 12 FCT ADDR 13 JML LOCK 14 FCT ADDR 15 JML 16 JQEDATE 17 JQELOC 18 JQJGID 19 JQJJOBN 20 JQJJJNO 21 J1 J2 J3 S2 F1 F5
00000000 0019B028 00000000 00000000 00000000 00000000 SYSA1 JQJGID SNSNA JQJJJNO 40 00 00 70 80

```

Figure 5. BDT JQE in the Formatted Dump

- 1 **00257460** is the address of the JQE entry.
- 2 **JOBNAME** is the job name.
- 3 **ID** is the control block acronym.
- 4 **JCTDDB1-3** indicates the data definition block (DDB) for JCT entries.
- 5 **NETID** is the network ID.
- 6 **JBNO** is the job number.
- 7 **PREV** is the job number of the previous job of this priority.
- 8 **NEXT** is the job number of the next job of this priority.
- 9 **PRTY** is the job priority.
- 10 **UCNT** is the number of read-only users for this JCT entry.
- 11 **JQERW** is the read/write enqueue byte or read/write FCT address.
- 12 **FCT ADDRESS** is the FCT address.
- 13 **JML LOCK** is the job message log (JML) lock.
- 14 **FCT ADDRESS** is the FCT address.
- 15 **JML** is the job message log control block.
- 16 **JQEDATE** is the date that the job entered the system.

**17 JQELOC** is the CPU ID.

**18 JQEJGID** is the JES3 group ID.

**19 JQEJOB** is the job name.

**20 JQEJJNO** is the JES3 job ID.

**21** Flags:

**J1** is a flag. See either flag byte JCTFL1 in a listing of the JCT, or flag byte JQEFL1 in a listing of the JQE.

**J2** is a flag. See either flag byte JCTFL2 in a listing of the JCT, or flag byte JQEFL2 in a listing of the JQE.

**J3** is a flag. See flag byte JQEFL3 in a listing of the JQE.

**S2** is a flag. See flag byte JQESTAT2 in a listing of the JQE.

**F1** is a flag. See flag byte JQEFLG1 in a listing of the JQE.

Layouts for both the JCT and the JQE, which include the flag bytes previously listed, appear in [Chapter 3](#), “BDT Data Areas,” on page 45.

## Resident Logical Units Table (RLT)

A resident logical units table (RLT) contains information about a BDT node or about a SNA session, or *line*, that you coded in the BDTNODE statements. There is a *node* RLT for each BDT node, and a *line* RLT for each SNA session. Because you do not establish a session with your own node, you have a node RLT for your node but no corresponding line RLT. The following is an example of a line RLT.

BDT FORMATTED DUMP:		SOC1 IN LOW-MEM		SYSID=SYSA1 DATE=85211 TIME= 7:58:30 PAGE=025					
RESIDENT LOGICAL UNITS TABLE									
1	2	3		4		5		6	
001E0C10	TYPE LINE	ID RLT	VER 2000	LEN 0054	RSVD4 0000	NAME APPLA2	NODE SYSA2	LMODE	LCTAD 001EC950
		NLU 000	COMLU 000	ACTLU 0	SF 00000000	BLK 01024	FLAG1 10	FLAG2 00	CKPT 00000K
		CSOPT 00	ASRFG 80	LIMIT 00000	LUTO 000	LUFR 000	TOCNT 000	FRCNT 000	RSVD5 00000000

Figure 6. BDT RLT in the Formatted Dump

**1 001E0C10** is the address of the RLT.

**2 TYPE** is the type of logical unit (LU), either LINE or NODE.

**3 ID** is the control block acronym.

**VER** is the version release ID.

**NLU** is the total number of LUs (from LU on the BDTNODE statement).

**COMLU** is the number of communication LUs.

**CSOPT** is the compression option flag.

**ASRFG** is the ASR flag byte. See RLTAASRFG in a listing of the RLT.

**4 LEN** is the length of the RLT section.

**RSVD4** is reserved.

**ACTLU** is the active VLU count.

**SF** indicates BDT selectable features.

**LIMIT** is the restart limit.

**LUTO** is the number of LUs fenced “to”.

**5 NAME** is the node name in a node RLT entry, and the LU name in a line RLT entry.

**NODE** is the corresponding node name for line entries; it is empty for node entries.

**BLK** is the buffer size (from BUFSZ on the BDTNODE statement).

**FLAG1** is an entry flag byte. See RLTF1AG1 in a listing of the RLT.

**LUFR** is the number of LUs fenced “from”.

**TOCNT** is the “to” LU count.

**6 LMODE** is the log mode entry name.

**LCTAD** is the address of the LCT.

**FLAG2** is an entry flag byte. See RLTF1AG2 in a listing of the RLT.

**CKPT** is the checkpoint interval (from CKPT on the BDTNODE statement).

**FRCNT** is the “from” LU count.

**RSVD5** is reserved.

A layout of the RLT, which shows the flag bytes previously listed, is included in [Chapter 3, “BDT Data Areas,”](#) on page 45.

## Logical Unit Control Table (LCT)

A logical unit control table (LCT) describes a SNA session or a virtual logical unit (VLU) associated with a BDT node. Some fields in an LCT have one meaning for a session and a different meaning for a node. Many fields are unused because an LCT for a session does not contain node information, and an LCT for a node does not contain session information.

BDT FORMATTED DUMP: SOC1 IN LOW-MEM										SYSID=SYSA1 DATE=85211 TIME= 7:58:30 PAGE=027				LOGICAL UNITS CONTROL TABLE - VERSION 2 RELEASE 1	
1	2	3	4							5	6	7	8	9	10
LOC	TYPE	LUNAME	FX	F1	F2	F3	F4	STREAM ID	FCT	VLUNO	OUTQU	LGETA	LPUTA		
001EC950	VTAM	APPLA2	00	80	80	00	00	00	00000000	000	000000	00000000	00000000		
001EC9D4	VTAM	APPLA3	00	80	88	00	00	00	00000000	000	000000	00000000	00000000		
001ECA58	VTAM	APPLA2N	00	80	90	00	00	00	00000000	000	000000	00000000	00000000		
001ECADC	VTAM	APPLA5N	00	80	90	00	00	00	00000000	000	000000	00000000	00000000		
001ECB60	VTAM	APPLA3N	00	80	90	00	00	00	00000000	000	000000	00000000	00000000		
001ECBE4	COMM	SYSA1	001	00	20	20	00	00	00000000	F0F	000000	00000000	00000000		
001ECC68	XFER	SYSA1	002	00	00	40	00	00	00000000	F0F	000000	00000000	00000000		
001ECC6C	XFER	SYSA1	003	00	00	40	00	00	00000000	F0F	000000	00000000	00000000		
001ECD70	XFER	SYSA1	004	00	00	40	00	00	00000000	F0F	000000	00000000	00000000		
001ECD74	COMM	SYSA2	001	00	80	20	00	00	00000000	F0F	000000	00000000	00000000		
001ECE78	XFER	SYSA2	002	00	80	40	00	00	00000000	F0F	000000	00000000	00000000		
001ECEFC	XFER	SYSA2	003	00	80	40	00	00	00000000	F0F	000000	00000000	00000000		
001ECF80	XFER	SYSA2	004	00	80	40	00	00	00000000	F0F	000000	00000000	00000000		
001ED004	XFER	SYSA2	005	00	80	40	00	00	00000000	F0F	000000	00000000	00000000		
001ED088	XFER	SYSA2	006	00	80	40	00	00	00000000	F0F	000000	00000000	00000000		
001ED10C	XFER	SYSA2	007	00	80	40	00	00	00000000	F0F	000000	00000000	00000000		

Figure 7. BDT LCT in the Formatted Dump

- **1 LOC** is the address of the LCT.
- **2 TYPE** indicates the type of LCT:
  - **VTAM** indicates an LCT for a session. There is one for each SNA session.
  - **COMM** indicates an LCT for the communication VLU associated with a node. The communication VLU carries commands, messages, status, and control information for other VLUs.
  - **XFER** indicates an LCT for a transfer VLU associated with a node. There is one transfer VLU for each data transfer at each node.
- **3 LUNAME** is the node name and VLU number in a node LCT, or the LU name in a session LCT.
- **4 Flags:**
  - **FX** is the buffer status flag. See LCTFLAGX in a listing of the LCT.
  - **F1** is the VLU status flag. See LCTFLAG1 in a listing of the LCT.
  - **F2** is the VLU type flag. See LCTFLAG2 in a listing of the LCT.

- **F3** is the VLU control flag. See LCTFLAG3 in a listing of the LCT.
- **F4** is a flag. See LCTFLAG4 in a listing of the LCT.

A layout of the LCT, which shows the LCT flag fields previously listed, appears in [Chapter 3, “BDT Data Areas,”](#) on page 45.

- **5 STREAM ID** indicates the stream ID. The left column is for file-to-file and the right column is for NJE.
- **6 FCT** is the address of the FCT that is using the VLU.
- **7 VLUNO** is the VLU number.
- **8 OUTQU** is the interfunction communication output queue.
- **9 LGETA** is the address of the LGET area on the communication VLU.
- **10 LPUTA** is the address of the LPUT area on the communication VLU.

## BDT SNA Line and Node Variable Entries

The SNA line and node variable entries in the BDT formatted dump contain fields from three control blocks: the logical unit control block (LCB), ACF/VTAM’s request parameter list (RPL), and the LCT for logical units (LCTLU).

BDT FORMATTED DUMP: SOC1 IN LOW-MEM										SYSID=SYSA1 DATE=85211 TIME= 7:58:30 PAGE=029									
										BDT SNA LINE AND NODE VARIABLE ENTRIES VERSION 2 RELEASE 1									
		APPLID	LCBLCT	LCTLU	INPUT	NXLUO	LCBSEB	LCBACB	SNDCT	RCVCT	CID	VLUS	OX	OY	WR	F			
1 2	00298100	APPLA2	001EC950	00298DE0	00000000	00298DE0	00000000	00298000	00000000	00000000	00000000	000	000	000	00	0			
	002981D4	SEND	REQ-00	ACTIV-00	RTNCD-00	FDB2-00	FDB3-00	FDBK2---	00000000	0SENS--	00000000								
	0029824C	RECV	REQ-00	ACTIV-00	RTNCD-00	FDB2-00	FDB3-00	FDBK2---	00000000	0SENS--	00000000								
	002982C4	SESS	REQ-00	ACTIV-00	RTNCD-00	FDB2-00	FDB3-00	FDBK2---	00000000	0SENS--	00000000								
		VLUNO	LULIN	LUIBE	LUIBQ	LUIBF	LUOBQ	LUOBS	LUREC	LUMAX	LUSIZ	ACK	SNT	BFN	ISQ	OSQ	F2	F3	
3	00298DE0	SYSA2	001	00298100	00000000	00000000	00000000	00000000	00000000	01024	01024	000	000	010	000	000	00	00	
	00298E70	SYSA2	002	00298100	00000000	00000000	00000000	00000000	00000000	00000	01024	01024	000	000	010	000	000	00	
	00298F00	SYSA2	003	00298100	00000000	00000000	00000000	00000000	00000000	00000	01024	01024	000	000	010	000	000	00	
	00298T90	SYSA2	004	00298100	00000000	00000000	00000000	00000000	00000000	00000	01024	01024	000	000	010	000	000	00	
	00299020	SYSA2	005	00298100	00000000	00000000	00000000	00000000	00000000	00000	01024	01024	000	000	010	000	000	00	
	002990B0	SYSA2	006	00298100	00000000	00000000	00000000	00000000	00000000	00000	01024	01024	000	000	010	000	000	00	
	00299140	SYSA2	007	00298100	00000000	00000000	00000000	00000000	00000000	00000	01024	01024	000	000	010	000	000	00	

Figure 8. BDT SNA Line and Node Variable Entries in the Formatted Dump

- The LCB contains information about a SNA session. The LCB fields are as follows:  
**00298100** is the hexadecimal address of the LCB.  
**APPLID** is the logical unit (LU) name. It is the same as LUNAME in the session RLT and LUNAME in the LCT.  
**LCBLCT** is the address of the related LCT.  
**LCTLU** is the address of the first LCTLU for the node.  
**INPUT** is the address of the input buffer for the receive area.  
**NXLUO** is the address of the next output LCTLU.  
**LCBSEB** is the LCB session-establishment block.  
**LCBACB** is the pointer to the access control block (ACB) for this node.  
**SNDCT** is the send record unit (RU) count.  
**RCVCT** is the receive RU count.  
**CID** is the network address.  
**VLUS** is the number of VLUs per session.  
**OX** is the output VLU identification.  
**OY** is the output VLU sequence number.  
**WR** is the BDT SNA manager work queue request flag.  
**F** is a flag.
- The RPL is a communication area for ACF/VTAM and its applications. It describes the macro BDT is requesting of ACF/VTAM. The RPL fields are as follows:  
**002981D4** is the hexadecimal address of the RPL entry.  
**SEND** indicates the type of RPL (send, receive, or session-related).  
**REQ** indicates the RPL request type (ACF/VTAM macro), as described in [Table 1 on page 32](#).

Table 1. RPL Request Types		
Code	Request Type	Function
00	GET	
15	SETLOGON	Modifies an application program's capability to establish sessions.
16	SIMLOGON	Initiates a session in which the application program will act as the primary LU.
17	OPNDST	Establishes sessions in which the application program will act as the primary LU.
1A	INQUIRE	Obtains LU information or application program status.
1F	CLSDST	Terminates sessions in which the application program is acting as the primary LU.
21	CLOSE	Closes one or more ACBs.
23	RECEIVE	Receives input on a session.
25	SESSIONC	Sends a session-control request or response.
27	SEND	Sends output on a session.
29	REQSESS	Initiates a session in which the application program will act as the secondary LU.
2A	OPNSEC	Establishes a session in which the application program will act as the secondary LU.
2C	TERMSESS	Requests termination of a session in which the application program acts as the secondary LU.

- **ACTIV** is the activity code:
    - Hex FF — ACF/VTAM was processing this request at the time of the dump.
    - Hex 00 — ACF/VTAM completed processing of this request before the dump was taken.
  - **RTNCD** is the RPL return code. This field is dumped from RPLRTNCD, which is at offset hex D in the RPL.
  - **FDB2** is the ACF/VTAM reason code. This field is dumped from RPLFDB2, which is at offset hex E in the RPL.
  - **FDB3** indicates the ACF/VTAM data flags. This field is dumped from RPLFDB3, which is at offset hex F in the RPL.
- Note:** For information on the RTNCD, FDB2, and FDB3 fields, see the ACF/VTAM programming manual.
- **FDBK2** indicates SNA sense received by BDT. This field is dumped from two RPL fields: RPLSSEI at offset hex 58, and RPLSSMI at offset hex 59.
  - **OSENS** indicates SNA sense sent by BDT. This field is dumped from two RPL fields: RPLSSEO at offset hex 64, and RPLSSMO at offset hex 65.
- Note:** For information on the FDBK2 and OSENS fields, see the SNA format and protocol manual.
- **3** The LCTLU fields are as follows:
    - **00298DE0** is the hexadecimal address of the LCTLU.
    - **VLU** is the name of the node and the VLU number.
    - **LULIN** is the address of the line LCTLN segment.
    - **LUIBE**, is the address of the input buffer being emptied.
    - **LUIBQ** is the address of the input buffer queue.

- **LUOBF** is the address of the output buffer being filled.
- **LUOBQ** is the address of the output buffer queue.
- **LUOBS** is the address of the output buffer sent.
- **LUREC** is the size of the given record.
- **LUMAX** is the maximum record size.
- **LUSIZ** is the node buffer size.
- **ACK** is the number of pending acknowledgements for input buffers.
- **SNT** is the number of pending acknowledgements for output buffers.
- **BFN** is the number of buffers.
- **ISQ** is the input buffer sequence counter.
- **OSQ** is the output buffer sequence counter.
- **F2** is the sequence number updated (01 = yes, 00 = no).
- **F3** is not presently supported.

## Structure of the BDT SNA control blocks

The RLT, LCT, LCB, RPL, and LCTLU control blocks, described in the preceding sections, all contain information about SNA sessions and BDT nodes. Figure 9 on page 33 shows the relationships among the SNA-related control blocks and identifies the figure in this chapter that contains the corresponding example from the dump.




Figure 9. Structure of the BDT SNA control blocks

## Cell Pool Directory (CPD) and Cell Pool Control Block (CPB)

The cell pool directory (CPD) in BDTNUC contains information you need to locate cell pools in the BDT address space. There is one CPD and one cell pool control block (CPB) entry for every cell pool defined with a CELLPOOL statement in the BDT initialization stream. (See Figure 19 on page 52 for an illustration of the relationships among CPD, CPB, and TVT entries.)

Figure 10 on page 34 shows the BDT formatted dump for one cell pool.

BDT FORMATTED DUMP: SOC1 IN LOW-MEM				SYSID=SYSA1		DATE=85211		TIME= 7:58:30	
PAGE=035				*** CELL POOL CONTROL BLOCKS ***					
1	0019BCA4	CPD ----	SAVE						
		CPID	E2C1E5C5	CSIZE	00000080	CPB	00200EC0		
		SUBID	010	RSVD1	00	RSVD2	00	RSVD3	00
		RSVD4	00000000	RSVS1	00000000	RSVS2	00000000		
2	00200EC0	3	CPB			4			
		ID	C3D7C240	5	REL	F1F0F0F0	LEN	013C	RSD01 0000
HIADD	00205000	NXCPB	00000000	CPRT	00200EA8	CPAT	00200EB0	LOWAD	00201000
		RSD02	00	SUBID	010	CELSZ	0128	CELPG	0032
DPLTD	000000	TOTEX	0000	MAXEX	0015	HWMEX	0000	WASTE	0000
SEXSZ	00004096	SDCNT	00000	RSD03	0000	CTR	00000001	EXSIZ	00016384
LWMAV	00000106	AVLCL	00000111	TOTAV	00000111	TOTCE	00000128	HWMCE	00000128
		HWMUS	00000022	CELMN	00000128	SELCX	00000032		
CPRTZ	00000008	SELPG	00000000	SPATZ	00000004	SPRTZ	00000002	CPATZ	00000016
		LOCKB	00	LOCKBRV	000000	LOCKF	00198EE8		
		RSD04	00000000	RSD05	00000000	RSD06	00000000	RSD07	00000000
		RSVS1	00000000	RSVS2	00000000	RSVS3	00000000	USER	00000000
		FLAG1	E0	FLAG2	00	KEY	80	RSD08	00
		PARM	001E0B20	PARMD	00000000	PARMD+4	00000000	PARMD+8	00000000
		6	SAVEAR00	00201800	SAVEAR01	00200EC0	SAVEAR02	00000004	SAVEAR03 00201800
			SAVEAR04	00244000	SAVEAR05	00000033	SAVEAR06	00284140	SAVEAR07 001B89E2
			SAVEAR08	00227100	SAVEAR09	001A6778	SAVEAR10	0019D57C	SAVEAR11 00198EE8
			SAVEAR12	00197000	SAVEAR13	00201100	SAVEAR14	4019D6B8	SAVEAR15 0019CB32
			SAVEWORK	00000000	SAVEBCHN	00000000	SAVEFCHN	00000000	
			SAVER14	00000000	SAVER15	00000000	SAVER00	00000000	SAVER01 00000000
			SAVER02	00000000	SAVER03	00000000	SAVER04	00000000	SAVER05 00000000
			SAVER06	00000000	SAVER07	00000000	SAVER08	00000000	SAVER09 00000000
			SAVER10	00000000	SAVER11	00000000	SAVER12	00000000	

Figure 10. BDT CPD and CPB in the Formatted Dump

**1** The CPD fields are as follows:

**0019BCA4** is the address of the cell pool.

**CPD -----** indicates the name (SAVE) of the cell pool.

**CPID** is the hexadecimal name of the cell pool (ID on the CELLPOOL statement).

**CSIZE** is the size, in bytes, of one cell in this cell pool.

**CPB** is the address of the corresponding CPB primary extent.

**SUBID** is the subsystem ID.

**RS** fields are reserved fields.

**2 00200EC0** is the address of the corresponding CPB primary extent.

**3 ID** is the control block identification.

**REL** is the release number.

**NXCPB** is the address of the next CPB, if one exists.



**CPRT** is the address of the cell pool page release table.

**RSD02** is reserved.

**SUBID** is the subsystem ID.

**TOTEX** is the current number of extents.

**MAXEX** is the maximum number of extents allowed.

**SDCNT** is the number of times the cell pool has entered slowdown.

**RSD03** is reserved.

**AVLCL** is the number of unused cells in the extent.

**TOTAV** is the total number of cells available in the pool.

**HWMUS** is the high watermark — the number of cells in use.

**CELNM** is the number of cells in the primary extent.

**SELPG** is the number of pages in the secondary extent.

**SPATZ** is the size of the secondary allocation table.

**LOCKB** is the cell pool lock byte.

**LOCKBRVS** is reserved.

**RSD** fields are reserved.

**RSVS** fields are reserved.

**FLAG1** is a flag. See CPBFLAG1 in a listing of the CPB.

**FLAG2** is a flag. See CPBFLAG2 in a listing of the CPB.

**PARM** is the address of the XBPL/XDPL PARM list.

**PARMD** is the first 4 bytes of the address of the XBPL/XDPL PARM list for BDTGRCP internal calls.

**4 LEN** is the length of the control block.

**RSD01** is reserved.

**CPAT** is the address of the cell pool allocation table.

**LOWAD** is the address of the beginning of the cell pool for this extent.

**CELSZ** is the size of the cell.

**CELPG** is the number of cells per page.

**HWMEX** is the maximum number of extents of this cell pool since last initialization.

**WASTE** is the wasted space due to records that were not spanned.

**CTR** is the total number of extents created.

**EXSIZ** is the size, in bytes, of the primary extent.

**TOTCE** is the total number of cells in the pool.

**HWMCE** is the high watermark — the number of cells in the pool.

**SECLX** is the number of cells in the secondary extent.

**SPRTZ** is the size of the secondary page release table.

**CPATZ** is the size of the page release table for this extent.

**LOCKF** is the cell pool lock FCT address.

**RS** fields are reserved.

**USER** is reserved.

**KEY** is the storage key for GETMAINS.

**RSD08** is reserved.

**PARMD+4** is bytes 5-8 of the PARMD address.

**PARMD+8** is bytes 9-12 of the PARMD address.

**5 HIADD** is the address of the end of the cell pool for this extent.

**DPLTD** is the number of times the cell pool was depleted.

**SEXSZ** is the size, in bytes, of the secondary event.

**LWMAV** is the low watermark — the number of cells available.

**CPRTZ** is the size of the allocation table for this extent.

**6** Save areas:

**SAVEAR00-15** is the save area for the GET and RETURN cell.

**SAVER00-14** is the save area for BPL and DLP requests.

## Contents of BDT Nucleus (BDTNUC)

This section of the BDT formatted dump displays the contents of the BDT nucleus (BDTNUC) in hexadecimal form.

JOB	BDTA1	STEP	A1	TIME	080035	DATE=85211	CPUID = FF0232523081	PAGE 0001
*** BDT NUCLEUS ***								
197000	E3E5E340	F1F0F0F0	05380000	0085211F	07491325	F2F0F0F0	0019D57C	0019D674
197020	001BE3B0	001BE088	001BDD04	001BCA38	0019BE2C	0019D42C	0019C590	0019CB32
197040	0019D064	801B83CC	811B83CC	501B83CC	511B83CC	FF1B83CC	001C49D0	001C6098
197060	001C5024	001C4DAE	001C572E	001C3060	00233EC0	001C26B2	001C274C	001C284A
197080	001C257C	001C27CE	0019F318	001BC7CC	001BC694	001BC80C	001C1024	001B5870
1970A0	001C1F80	001C22A0	0019F750	0019F9DA	0019FCB0	0019FE38	001A004C	001A0094
1970C0	0019D810	0019DB6C	00000000	00000000	00000000	001B46E4	001B4BE4	001B4AAE
1970E0	001B492E	001B4BAC	001B4B3C	001B4B74	002933C0	0028D738	00292AB8	00293530
197100	00289DA0	0028D548	00297D30	001BA77E	00000000	00000000	00000000	001AE134
197120	001ADDF0	001BA910	001A904C	801B557C	001C6D8C	001C0168	001C72D0	00000000
197140	001C4BF8	001BA4B4	001A7810	001B84CE	001B9010	001BD720	00000000	001AB718
197160	001B89E2	00000000	001C2D40	001BAA60	0000004C	00000028	0000004C	00000000
197180	0019B878	00000000	00000000	00000000	00000000	00000000	00000000	00000000
1971A0	00000000	00000000	00000000	00000000	00000000	00000000	00000000	00000000
1971C0	00000000	001C70C4	80000000	00000000	0077F0E0	00235EC0	0022EEC0	001F3EC0
1971E0	001FEEC0	00205EC0	00245EC0	001978C8	00226EC0	0019BCA4	00200EC0	00243EC0
197200	001F1EC0	001ECBE4	001EC950	001E0D84	001E0C10	0027D310	001EC950	001ECC68
197220	00284000	00000000	00000000	00000000	00000000	00000000	00000000	00000000
197240	0014000A	00000000	00000000	00000000	0014000A	00000000	00000000	00000000
197260	00000000	00000000	00000000	00000000	00000000	00000000	00000000	00000000
197280	00000000	40000000	00197290	80FDD1A0	8077F030	807831F1	00000000	001EA350
1972A0	001CB430	0077E260	00000000	00000000	00000000	00198698	00000000	00196B7C
1972C0	00194B60	001AEC70	0019B028	00000000	00000000	00197000	881CBBB8	00000000
1972E0	001BE580	001977C6	001BFB60	001B528C	00A16800	0019B450	00000000	00000000
197300	00000000	00000000	00000000	00000000	00000000	00000000	00000000	00000000
197320	00000000	00000000	00197538	00000000	00000130	01000130	01000052	00000000
197340	00000800	00000000	FF023252	00000000	00000000	00000000	00000000	00000000
197360	00000000	00000000	00000000	00000000	00000000	00000000	00000000	00000000
197380	00010028	00140000	00000000	00000000	00000000	00000000	00000000	00000000
1973A0	00008020	00840000	00000000	00000000	00000000	00000000	00000000	00FFFFFF

Figure 11. Contents of BDTNUC in the Formatted Dump

---

## Chapter 2. The MVS SVC Dump

This chapter is a brief introduction to the MVS supervisor call (SVC) dump. It discusses aspects of the SVC dump that are of particular importance to diagnosing problems in BDT. For a detailed explanation of how to use the SVC dump, see the MVS system programming library service aids manual that is appropriate for your installation.

This chapter explains:

- The purpose of the SVC dump in diagnosing problems in BDT
- How to request the SVC dump
- How to access the SVC dump
- The contents of the SVC dump
- The title page of the SVC dump
- The BDT trace table in the SVC dump.

---

### Purpose of the SVC Dump

Use the SVC dump to get a detailed picture of the system, including, in the BDT trace table, a record of the internal program flow within the BDT address space prior to a failure.

---

### How to Request the SVC Dump

The SVC dump is invoked automatically when an abend occurs in the BDT or TQI address space.

The SVC dump can be requested during normal processing with the DUMP command. The DUMP command will give you an SVC dump along with a BDT formatted dump. The format of the DUMP command is `DUMP,TITLE=dump-title`, where *dump-title* is a title you assign to the dump. See [z/OS BDT Commands](#) for more information.

Often a message or reason code explains the cause of an abend and substitutes for the SVC dump.

---

### How to Access the SVC Dump

If BDT takes an SVC dump, it issues the dump to the SYS1.DUMP data set. You can then access the data set directly, format and print the data set, or send the data set to another node for analysis.

If BDT is unable to take an SVC dump, it issues a dump to the SYSABEND, SYSUDUMP, or SYSMDUMP data set, depending on which is specified in the BDT start procedure. You can then access that data set.

---

### Formatting and Printing the SVC Dump

For complete information on formatting and printing the dump, see the service aids manual that is appropriate for your installation. The following is only an introduction.

To format and print an SVC dump you must first create an entry in the exit control table (ECT). This entry defines a BDT exit module to the print dump service aid, AMDPRDMP. To create the entry, use the SPZAP service aid. You must provide three control statements for the SPZAP service aid. Code the statements as shown:

```
NAME AMDPRECT
VER offset 40404040,40404040,40404040,40404040,40404040
REP offset C2C4E3C1,C2D7D940,80000000,C2C4E340,40404040
```

The variable *offset* refers to the offset in the ECT table where you added your entry.

## Transmitting the SVC Dump to Another Node

The SVC dump is most useful in a network where problem analysis is done at only one node. If your node is part of such a network you may want to transmit your dumps to another node. To do this you can submit a BDT transaction.

The following is an example of a transaction submitted at a TSO terminal to transmit a dump data set from node SYSA1 to node SYSA2.

```
BDT Q JOB(DUMPSND) FROM LOC(SYSA1)
DAP(SEQ) DSN(SYS1.DUMP00) VOL(BDTRES)
DSORG(PS) RECFM(F) LRECL(4104) BLKSIZE(4104)
UNIT(3330-1) SHR
TO LOC(SYSA2) DSN(SYS1.DUMP01) VOL(BDTRES)
DSORG(PS) RECFM(F) LRECL(4104) BLKSIZE(4104)
UNIT(3330-1) OLD
```

For an explanation of how to write a BDT transaction, see [z/OS BDT File-to-File Transaction Guide](#).

After you have transmitted the dump you should clear the SYS1.DUMP data set so that it can be reused.

## Contents of the SVC Dump

---

The SVC dump includes a title page, a summary dump, the BDT trace table, and the following areas from the BDT address space:

- The system queue area (SQA)
- All prefixed storage areas (PSAs) in the system
- The generalized trace facility (GTF) trace buffers and system trace table
- The local system queue area (LSQA)
- The private user area
- The common service area (CSA), which includes:
  - The subsystem vector table (SSVT) for BDT
  - The SSVT extension (USVT) for BDT
  - The configuration control block for TQI
  - The program call table for the BDT address space
  - The program call table for the MVS/TQI address space

A table of contents appears on the last page of the SVC dump.

## Title Page of the SVC Dump

---

The following is a portion of an SVC dump title page.

**1**  
 TITLE FROM DUMP: ABEND=BD008,REASON= ,ISSUER=BDTCMDV -ESTAEXIT,  
 COMPON=BDT - COMMUNICATIONS ,COMPID=30201

**2**

#### SYMPTOMS FOR THIS DUMP

ABEND COMPLETION CODE  
 ABEND REASON CODE  
 COMPONENT ID INVOLVED  
 LOAD MODULE  
 ASSEMBLY MOD (CSECT)  
 RECOVERY ROUTINE  
 REG/PSW DIFFERENCES  
 (REG-OFFSET)

USER 0008  
 \*\*NOT SUPPLIED\*\*  
 5665-30201  
 BDTNUC  
 BDTCMDV  
 BDTCMDV  
 E-040  
 A-372

#### APAR DATA BASE FORMAT

AB/U0008  
 PRCS/  
 PIDS/566530201  
 RIDS/BDTNUC #L  
 RIDS/BDTCMDV  
 RIDS/BDTCMDV #R  
 REGS/0E040  
 REGS/0A372

**3**

#### CLUES FOR THIS DUMP

ABENDING PROGRAM  
 ASSEMBLY MOD LEVEL  
 COMPONENT/SUBCOMPON/  
 SUBFUNCTION  
 RECOVERY RTN LABEL

BDTGSC1  
 06/18/86 HBD1202  
 BDT - GENERAL ROUTINES  
 ESTAEXIT

- **1 TITLE FROM DUMP** describes the failing module:
- **ABEND** indicates the completion (or abend) code. There are three possible completion codes:
  - **S** is the MVS system completion code
  - **U** is the initialization completion code. This code is issued during BDT initialization. See [z/OS BDT Messages and Codes](#)
  - **BD** is the BDT completion code. See [z/OS BDT Messages and Codes](#)
- **REASON** is the reason code. See [z/OS BDT Messages and Codes](#) If the failing module is in the TQI address space, this field will not appear in the dump title.
- **ISSUER** is the name of the module containing the recovery routine, and the label of that routine.
- **COMPON** is the component name (BDT) and the subcomponent name, if any.
- **COMPID** is the BDT identification number.
- **2 SYMPTOMS FOR THIS DUMP** include information from the fields in the system-defined work area (SDWA):
- **ABEND COMPLETION CODE** is the completion code. See **ABEND** under **1**.
- **ABEND REASON CODE** is the abend reason code. See **REASON** under **1**. This comes from the SDWA field SDWAHRC.
- **COMPONENT ID INVOLVED** is the component ID. This comes from the SDWA field SDWACID/SDWACIDB.
- **LOAD MODULE** is the load module name at the time of the error. This comes from the SDWA field SDWAMODN.
- **ASSEMBLY MOD (CSECT)** is the assembly module name at the time of the error. This comes from the SDWA field SDWACSCT.
- **RECOVERY ROUTINE** is the recovery routine module name. This comes from the SDWA field SDWAREXN.
- **REG/PSW DIFFERENCES** is the difference between the address of the base register and the PSW.
- **(REG-OFFSET)** is the register offset.
- **3 CLUES FOR THIS DUMP** includes information from the fields in the SDWA:
- **ABENDING PROGRAM** is the name of the abending program.

- **ASSEMBLY MOD LEVEL** is the level of the failing module: assembly date and release/PTF level. This comes from the SDWA field SDWAMLVL.
- **COMPONENT/SUBCOMPON/SUBFUNCTION** is the component/subcomponent/subfunction. This comes from the SDWA field SDWASC.
- **RECOVERY RTN LABEL** is the recovery routine label, if it is not equal to SDWAREXN. This comes from the SDWA field SDWAARRL.

## BDT Trace Table

---

The BDT trace table displays a record of the internal program flow within the BDT address space prior to the failure. The trace table is a wraparound table that is printed unformatted in the SVC dump.

You can control the contents of the trace table. You do this by including the BDT trace macro, BDTXTRC, in user exit routines. For information on the BDTXTRC macro, see *BDT Installation*

You can also control the size of the trace table. You do this by coding the TRACE parameter in the BDT start procedure. For information on coding the TRACE parameter, see *BDT Installation*

The following pages describe the contents and location of the trace table.

### Contents of the Trace Table

The trace table is a series of “snapshots” of the BDT address space. BDT takes a snapshot, or makes an entry in the trace table, each time the BDTXTRC macro is invoked. The BDTXTRC macro is invoked by:

- Entering or exiting the ASAVE/ARETURN linkage module, BDTGRSV. (Note, however, that not all ASAVE and ARETURN calls are included in the trace table.)
- Branching to a user exit routine that contains the BDTXTRC macro.

The entries BDT makes in the trace table do not include all activity in the BDT address space. However, they always include:

- The name of the module that caused the trace entry
- An identifier for the entry
- Information about the calling module
- Information about the called module
- The contents of registers 0, 1, 10, 11, 14, and 15 at the time the trace entry was made
- The address of the task control block (TCB) under which the trace entry was created
- The time of day when the trace entry was made.

Each entry in the trace table consists of 64 decimal (hex 40) bytes of data that reflect the parameters coded on the BDTXTRC macro.

Figure 12 on page 41 is a sample of part of a BDT trace table. In the sample, each trace table entry occupies two printed lines, beginning in the third column.

An entry for an ASAVE call has been marked in the sample with numbers 1 through 11. Numbers 1 through 8 mark the fields under them; numbers 9 through 11 mark the fields over them.

An entry for an ARETURN call has been marked in the sample with numbers 12 through 22. Numbers 12 through 19 mark the fields under them; numbers 20 through 22 mark the fields over them.

00193820	88	00000000	00000000	0016A92C	00191140	4016AADE	00166EB8	007A2810	3E3BA7F8	*.....8*
00193840	88	C7D9E2E5	00E2003C	C9D5C7D3	701A5B82	C7D9D8C3	0017B924	C2C4E3E7	C2D7C440	*GRSV.S..INGL...GRQC...BDTXCPD *
00193860	88	001A5CD8	001A6E27	0016A92C	00191140	701A5B82	00166EB8	007A2810	3E471DDC	*...Q.....*
00193880	88	C7D9E2E5	00D901E6	C9D5C7D3	701A5B82	C7D9D8C3	00000000	C2C4E3E7	C3D7C440	*GRSV.R.WINGL...GRQC...BDTXCPD *
001938A0	88	00000000	00000000	0016A92C	00191140	4016AADE	00166EB8	007A2810	3E4721DA	*.....*
001938C0	88	C7D9E2E5	00E2003C	C9D5C7D3	701A5B82	C7D9D8C3	0017B924	C2C4E3E7	C3D7C440	*GRSV.S..INGL...GRQC...BDTXCPD *
001938E0	88	001A5CD8	001A6E29	0016A92C	00191140	701A5B82	00166EB8	007A2810	3E6A53E0	*...Q.....*
00193900	88	C7D9E2E5	00D901E6	C9D5C7D3	701A5B82	C7D9D8C3	00000000	C2C4E3E7	C3D7C440	*GRSV.R.WINGL...GRQC...BDTXCPD *
00193920	88	00000000	00000000	0016A92C	00191140	4016AADE	00166EB8	007A2810	3E6A5808	*.....*
00193940	88	C7D9E2E5	00E2003C	C9D5C7D3	501A5ECE	D9C2C1D4	801775BC	D9C1D3D3	D6C34040	*GRSV.S..INGL...RBAM...RALLOC *
00193960	88	00167320	00167314	0016A92C	00191140	501A5ECE	00166EB8	007A2810	40FE93BE	*.....*
1 2 3 4 5										
001939C0	88	C7D9E2E5	00E2003C	D9C2C1D4	50177712	D9C2C1D4	801775BC	D9C1D3D3	D6C34040	*GRSV.S..RBAM...RBAM...RALLOC *
001939E0	88	00164264	00164258	0016A92C	FFFFFDC0	50177712	00166EB8	007A2810	40FE9C18	*.....*
6 7 8 9 10 11										
00193A40	88	C7D9E2E5	00D901E6	D9C2C1D4	501778BA	D9C2C1D4	00000000	D9E6D9C9	E3C54040	*GRSV.R.WRBAM...RBAM...RWRITE *
00193A60	88	00000000	00000000	0016A92C	001648BC	4016AADE	001648BC	007A2810	4132EA88	*.....*
00193A80	88	C7D9E2E5	00D901E6	C9D5C7D3	501A5ECE	D9C2C1D4	00000000	D9C1D3D3	D6C34040	*GRSV.R.WINGL...RBAM...RALLOC *
00193AA0	88	00000000	00000000	0016A92C	FFFFFDC0	4016AADE	00166EB8	007A2810	4132EC40	*.....*
00193AC0	88	C7D9E2E5	00E2003C	C9D5C7D3	501A5EF2	D9C2C1D4	80177554	D9E6D9C9	E3C54040	*GRSV.S..INGL...2RBAM...RWRITE *
00193AE0	88	00167320	00156314	0016A92C	00191140	501A5EF2	00166EB8	007A2810	4232ED4A	*.....2.....*
00193B00	88	C7D9E2E5	00E2003C	D9C2C1D4	50177712	D9C2C1D4	801775BC	D9C1D3D3	D6C34040	*GRSV.S..RBAM...RBAM...RALLOC *
00193B20	88	00167320	00167314	0016A92C	00191140	50177712	00166EB8	007A2810	4132EF4C	*.....*
00193B40	88	C7D9E2E5	00D901E6	D9C2C1D4	50177712	D9C2C1D4	00000000	D9C1D3D3	D6C34040	*GRSV.R.WRBAM...RBAM...RALLOC *
00193B60	88	00000000	00000000	0016A92C	000003C0	4016AADE	00166EB8	007A2810	4132F19E	*.....1.....*
00193B80	88	C7D9E2E5	00D901E6	C9D5C7D3	501A5EF2	D9C2C1D4	00000000	D9E6D9C9	E3C54040	*GRSV.R.WINGL...2RBAM...RWRITE *
00193BA0	88	00000000	00000000	0016A92C	001648BC	4016AADE	00166EB8	007A2810	418CD1EE	*.....J.....*
00193BC0	88	C7D9E2E5	00D901E6	C9D5E3D2	4016612C	C9D5C7D3	00000000	40404040	40404040	*GRSV.R.WINTK ...INGL... *
00193BE0	88	00000000	00000000	0016A92C	00191140	4016AADE	00166EB8	007A2810	419043DA	*.....*
00193C00	88	C7D9E2E5	00E2003C	C9D5E3D2	40166166	C7D9D8C3	0017B924	C2C4E3E7	C3D7C440	*GRSV.S..INTK ...GRQC...BDTXCPD *
00193C20	88	00166AB0	00000000	0016A92C	00191140	40166166	00166EB8	007A2810	4191D34E	*.....L.....*
00193C40	88	C7D9E2E5	00D901E6	C9D5E3D2	40166166	C7D9D8C3	00000000	C2C4E3E7	C3D7C440	*GRSV.R.WINTK ...GRQC...BDTXCPD *
12 13 14 15 16 17 18 19 20 21 22										
00193CC0	88	C7D9E2E5	00D901E6	C9D5C9E8	401909F4	C9D5C9E7	00000000	40404040	40404040	*GRSV.R.WINIT ...4INIX... *
00193CE0	88	00000000	00000000	0016A92C	00191140	4016AADE	0016A470	0079F160	44AD40E4	*.....1... U*
20 21 22										
00193D40	88	C7D9E2E5	00E2003C	C9D5C9C3	501A32D6	C9D5D9D5	00192BE4	C3C1D9C4	D9C5C1C4	*GRSV.S..INIC...OINRN...UCARDREAD*
00193D60	88	001A32C0	00000000	0016A92C	00191140	501A32D6	0016A470	0079F160	45175040	*.....0.....1.....*
00193D80	88	C7D9E2E5	00D901E6	C9D5C9C3	501A32D6	C9D5D9D5	12A769E0	C3C1D9C4	D9C5C1C4	*GRSV.R.WINIC...OINRN...CARDREAD*
00193DA0	88	00000000	00000000	0016A92C	00191140	4016AADE	0016A470	0079F160	451F65B4	*.....1.....*
00193DC0	88	C7D9E2E5	00E2003C	C9D5C9C3	401A3304	C9D5D9D5	00192594	E2C3C1D5	F1404040	*GRSV.S..INIC ...INRN...SCAN1 *
00193DE0	88	00000001	00191258	0016A92C	00191140	401A3304	0016A470	0079F16C	451F66DA	*.....1.....*
00193E00	88	C7D9E2E5	00D901E6	C9D5C9C3	401A3304	C9D5D9D5	00000004	E2C3C1D5	F1404040	*GRSV.R.WINIC ...INRN...SCAN1 *
00193E20	88	00000000	00000000	0016A92C	00191140	4016AADE	0016A470	0079F160	451F6AC6	*.....1.....*
00193E40	88	C7D9E2E5	00E2003C	C9D5C9C3	401A32D6	C9D5D9D5	00192BE4	C3C1D9C4	D9C5C1C4	*GRSV.S..INIC ...OINRN...UCARDREAD*
00193E60	88	00000001	00191260	0016A92C	00191140	401A32D6	0016A470	0079F160	451F6BA6	*.....0.....1.....*
00193E80	88	C7D9E2E5	00D901E6	C9D5C9C3	401A32D6	C9D5D9D5	12A769E0	C3C1D9C4	D9C5C1C4	*GRSV.R.WINIC ...OINRN...CARDREAD*
00193EA0	88	00000000	00000000	0016A92C	00191140	4016AADE	0016A470	0079F160	451F6F92	*.....1.....*
00193EC0	88	C7D9E2E5	00E2003C	C9D5C9C3	401A3304	C9D5D9D5	00192594	E2C3C1D5	F1404040	*GRSV.S..INIC ...INRN...SCAN1 *
00193EE0	88	00000001	00191258	0016A92C	00191140	401A3304	0016A470	0079F160	451F7056	*.....1.....*
00193F00	88	C7D9E2E5	00D901E6	C9D5C9C3	401A3304	C9D5D9D5	00000004	E2C3C1D5	F1404040	*GRSV.R.WINIC ...INRN...SCAN1 *

Figure 12. Example of a BDT Trace Table

In Figure 12 on page 41, numbers 1 through 8 and 12 through 19 mark the fields under them; numbers 9 through 11 and 20 through 22 mark the fields over them.

Entry for an ASAVE call:

	Offset	Description
1	0	Bytes 4-7 of the module name BDTGRSV
	4	Reserved
2	5	Entry identifier — S for ASAVE
3	6	Offset of the BDTXTRC macro within BDTGRSV (3C)
4	8	Characters 4-7 of the calling module name
5	C	Return address of the calling module
6	10	Characters 4-7 of the called module name
7	14	Entry point address of the called module
8	18	Characters 1-8 of the called module entry point address
9	20	Contents of registers 0, 1, 10, 11, 14, and 15

	Offset	Description
<b>10</b>	38	Address of the TCB of the task issuing BDTXTRC
<b>11</b>	3C	Time when the entry was created (bytes 3-6 of STCK instruction)

Entry for an ARETURN call:

	Offset	Description
<b>12</b>	0	Bytes 4-7 of the module name BDTGRSV
	4	Reserved
<b>13</b>	5	Entry identifier — R for ARETURN
<b>14</b>	6	Offset of the BDTXTRC macro within BDTGRSV (E6)
<b>15</b>	8	Characters 4-7 of the called module name
<b>16</b>	C	Return address of the calling module
<b>17</b>	10	Characters 4-7 of the calling module name
<b>18</b>	14	Return code of the called module
<b>19</b>	18	Characters 1-8 of the calling module entry point address
<b>20</b>	20	Contents of registers 0, 1, 10, 11, 14, and 15
<b>21</b>	38	Address of the TCB of the task issuing BDTXTRC
<b>22</b>	3C	Time when entry was created (bytes 3-6 of STCK instruction)

## Locating the Trace Table

The BDT trace table resides in the SVC dump in subpool 127. To find the table, follow a pointer from TVTVATR in the BDT TVT to BDTDATR. The BDTDATR data area includes addresses that help you locate the trace table. The most important addresses are:

- The beginning of the table — pointed to by ATRBEGIN
- The end of the trace table — pointed to by ATREND1
- The most recent entry in the trace table — pointed to by ATRCURNT.

The complete contents of the BDTDATR data area are listed:

*Table 2. BDTDATR Data Area*

OFFSET	LENGTH	NAME	DESCRIPTION
0	4 bytes	ATRCBID	Control block ID ATR
4	4 bytes	ATRREL	Version release ID
8	2 bytes	ATRLLEN	Size of control block
C	4 bytes	ATRCURNT	Address of current entry
10	4 bytes	ATRBEGIN	Address of trace table start
14	4 bytes	ATREND1	Address of trace table end
18	12 bytes		Reserved for development
24	12 bytes		Reserved for service
30	4 bytes	ATRTIME	Time trace table last wrapped
34	8 bytes	ATRSTCK	Store clock work area



Table 2. BDTDATR Data Area (continued)

OFFSET	LENGTH	NAME	DESCRIPTION
3C	1 byte	ATRFLAG	Trace routine flag: X'80' = Trace inactive X'20' = A BDT subtask is abending X'10' = Trace entries lost



---

## Chapter 3. BDT Data Areas

This chapter discusses data areas, including control blocks and work areas, that are involved with BDT processing. It includes:

- Diagrams showing the locations of control blocks
- Diagrams showing the relationships of control blocks
- Brief descriptions of the following data areas:
  - ACB — Access control block
  - CPB — Cell pool control block
  - CPD — Cell pool directory
  - DAP Dictionary — Dynamic application program dictionary
  - DAP Data Areas for SNA NJE — Dynamic application program data areas for SNA network job entry
  - DCL — Data compression list
  - DDB — Data description block
  - DSWA — Data support work area
  - EXLIST — Exit list
  - FCT — Function control table
  - GETUNIT list
  - JML — Job message log
  - LCB — Logical unit control block
  - RESQUEUE — Resident job queue entry
  - SMF — System management facility
  - SSOB, SSIB, BSIW — Subsystem interface options block, subsystem interface identification block, and subsystem interface work area.
- Summary information and layouts for the following data areas:
  - BSID — BDT subsystem interface data area
  - GSD — Generalized subtask directory
  - INT — Initialization data CSECT
  - JCT — Job control table
  - JQE — Job queue element
  - JQX — JQE/JCT access control table
  - LCT — Logical units control table
  - LCTLU — LCT extension for logical units (VLUs)
  - MJD — Master job definition
  - RLT — Resident logical units table
  - SEQ — Sequential transfer data area
  - SNBP — SNA buffer pool control block
  - TVT — Transfer vector table
  - TWA — Trace work area
  - XOID — Transaction origin data area

---

### Location of BDT Control Blocks

The following pages describe the locations of BDT control blocks — when they are created and where they reside. The diagrams show BDT control blocks after BDT initialization, at three stages of a file-to-file (FTF) transaction, and at three stages of a network job entry (NJE) transaction.

## Control Blocks after BDT and BDT SNA Manager Initialization

BDT initializes all control blocks during initialization except the task control block (TCB), which is initialized by MVS. The control blocks after BDT SNA initialization are the same for file-to-file and NJE nodes.

### Control blocks during a file-to-file transaction

**Stage 1 – File-to-File. A transaction is submitted from node B requesting transfer of data to node A.** Node A is global to node B.

- BDT builds certain job-related control blocks at the global node (node A).
- The JCT and MJD are written to the work queue at the global node (node A), and the JQE is allocated in the JQX in the address space. The JQX is the access table for the JQE and includes the JQE.
- The BSID is built in the address space of the requesting node (node B).
- The *transaction* becomes a BDT *job* (job 1, in the illustration).




Figure 13. BDT control blocks at file-to-file nodes after a transaction is submitted

**Stage 2 – File-to-File. The job is scheduled.**

- The dispatching control blocks for job 1 are built in the FCT subpools at both nodes. These control blocks are the FCT, the GSD, the TWA, and the GETUNIT list.
- The MJD is written from the work queue at the global node (node A) to the address space.
- The TCB and the RESQUEUE for job 1 are built in both address spaces.
- Once the job is dispatched, the data is transferred.




Figure 14. BDT control blocks at file-to-file nodes after the job is scheduled

### Stage 3 – File-to-File. The job is purged.

- All the control blocks that are related to the job are removed from the address spaces, except the JQE.
- The accounting driver uses the JQE in the address space and the MJD and JCT on the work queue to write the SMF record.




Figure 15. BDT control blocks at file-to-file nodes after the job is purged

## Control Blocks during an NJE Transaction

**Stage 1 – NJE. A transaction is submitted at node A requesting transfer of data to node B.** In NJE processing involving BDT, only one node, either the sending or receiving node, must be a BDT node. The other node might be JES2, RSCS, or VSE/POWER. However, for purposes of illustration, these diagrams show the processing of an NJE transaction for which both the sending and receiving nodes are BDT nodes.

Notice that, in the diagrams in this chapter, the NJE transaction is submitted at node A while the file-to-file transaction is submitted at node B. With the exception of the BSID, the control blocks at the submitting node in the NJE transaction correspond to the control blocks at the *global* (not submitting) node in the file-to-file transaction.

- BDT builds certain job-related control blocks at the node which submits the transaction (node A).
- The JCT and MJD are written to the work queue at the node submitting the transaction (node A), and the JQE is allocated in the JQX in the address space. The JQX is the access table for the JQE and includes the JQE.
- The BSID is built in the address space of the node submitting the transaction (node A).
- The *transaction* becomes a BDT *job* (job 1 in the illustration).




Figure 16. BDT control blocks at nje nodes after a transaction is submitted

### Stage 2 – NJE. The job is scheduled.

- The dispatching control blocks for job 1 are built in the FCT subpools at both nodes. These control blocks are the FCT, the GSD, the TWA, and the GETUNIT list.
- The MJD is written from the work queue at the submitting node (node A) to the address space.
- The TCB for job 1 is built in both address spaces.
- The RESQUEUE for job 1 is built in the address space of the submitting node (node A).
- Once the job is dispatched, the data transfer occurs.




Figure 17. BDT control blocks at nje nodes after the job is scheduled

### Stage 3 – NJE. The job is purged.

- All the control blocks that are related to the job are removed from the address spaces, except the JQE.
- The accounting driver uses the JQE in the address space and the MJD and JCT on the work queue to write the SMF record.






Figure 18. BDT control blocks after the job is purged

## Relationships among BDT control blocks

The diagrams in this section show the relationships between BDT control blocks.




Figure 19. BDT storage management control blocks





Figure 20. BDT session-related control blocks

## Job Scheduling



## Job Dispatching




Figure 21. BDT job scheduling and dispatching control blocks



**DDB**

The data description block (DDB) contains information about the DDB request area, fixed area, and extent entry, such as the address of the area, length of the data, end of the entry, and size of the entry. The DDB is used by RBAM to read and write to a disk.

**DSWA**

The data support work area (DSWA) contains processing flags, a message buffer area, data areas and constants for user exits, and information about dynamic allocation text units and checkpoints. The DSWA is used for allocating and deallocating data sets. It is created by BDTGRJR before the appropriate DAP driver module is loaded.

**EXLST**

The exit list (EXLST) contains the addresses of the ACF/VTAM exits used by the BDT SNA manager. It is created by BDTSCINT when the BDT SNA manager is initialized.

**FCT**

The function control table (FCT) represents the dispatchable units of work in BDT. Resident FCT entries are part of BDTNUC, in CSECT BDTGRPT. FCT entries for BDT jobs are dynamically allocated from a cell pool defined in the initialization stream.

**GETUNIT list**

The GETUNIT list contains flags and pointers to the VLU/LCT that the DAP is using to copy data.

**JML**

The job message log (JML) contains messages related to the progress of a job and codes associated with the messages. There is one JML for each job that results from a transaction that included the MSGCLASS(LOG) parameter.

**LCB**

The logical unit control block (LCB) is an extension of the session LCT and is used for session control. It contains such information as the request parameter lists (RPLs) used to communicate with ACF/VTAM, bind parameters, counters for SEND/RECEIVE statistics, and buffer pool information. There is one LCB per session, and it is built during BDT SNA initialization.

**RESQUEUE**

A resident job queue entry (RESQUEUE) contains most job-related information, such as the job name, the job number in EBCDIC and binary, the source and destination data set DDNAMES, pointers to the displacement in the MJD where the addresses of the data transfer checkpoint areas can be found, and the time limit for the job. It is an in-storage version of the JCT when the BDT job is active.

**SMF**

The system management facilities (SMF) record accounting data about jobs. The SMF record type 59 contains information about BDT transactions such as the programmer, department, job number, bytes transferred, job entry time, node name, transaction source, transaction type, and job name. It is created by BDTACMN and is written out to spool when the job completes. For more information, see the system management facilities (SMF) manual that is appropriate for your installation.

**SSOB, SSIB, BSIW**

The subsystem interface options block (SSOB) contains the addresses of the subsystem interface identification block (SSIB) and the subsystem interface work area (BSIW). The SSIB contains the subsystem name and the job identifier. The BSIW contains the address of the BSID, the address of the response ECB, the pointer to the register save area, the service entrance list (SEL), and the address of the response exit. The SSOB, SSIB, and BSIW are mapped by BDTDBSI. BDTCMDV obtains storage for these control blocks at initialization.

## BDT Subsystem Interface Data Area – BSID

---

The BDT subsystem interface data area (BSID) is a control block made up of a fixed area containing information about the type of BSID (transaction, command, or message), the transaction origin ID (XOID), the BDT subsystem ID, and the unique transaction identifier (UTI). The BSID also contains a variable area containing the command, message, or a master job definition (MJD) when the BSID represents a transaction.

<b>Function:</b>	The BSID provides basic information about the transaction, message, or command to BDT.
<b>Macro ID:</b>	BDTDBSID
<b>DSECT name:</b>	BSID
<b>Created by:</b>	BDTLP
<b>Size:</b>	Fixed area contains hex C0 bytes
<b>Pointed to by:</b>	TVTXDQUE
<b>Location:</b>	May originate in a user address space, such asTSO, JES, or other, in the case of a batch job. It is then passed to the BDT address space by the SSI. May also originate in the BDT address space.

OFFSETS	TYPE	LENGTH	NAME	DESCRIPTION
BDT SUBSYSTEM INTERFACE DATA AREA(BSID)				
FIXED PART OF THE BSID				
0	(0) FIXED	2	BSIDTOTL	TOTAL LENGTH OF BSID
2	(2) CHARACTER	4	BSIDID	CONTROL BLOCK IDENTIFIER
6	(6) CHARACTER	4	BSIDVER#	BDT VERSION NUMBER
10	(A) ADDRESS	2	BSIDFXDL	LENGTH OF FIXED PART OF BSID
12	(C) BITSTRING	1	BSIDMOD	MODIFIER CODE
	.... .1		BSIDSHTL	"1" SHUTTLE STAGING AREA
	.... .1.		BSIDMSG	"2" BDT MESSAGE
	.... .11		BSIDXACT	"3" BDT TRANSACTION
	.... .1..		BSIDCMND	"4" BDT COMMAND
	.... .1.1		BSIDJCMD	"5" JES COMMAND
	.... .11.		BSIDOFFL	"6" BDT/JES3 INTERFACE OFF LINE
	.... .111		BSIDREJT	"7" BDT/JES3 CONNECT OFF REJECTED
	.... 1...		BSIDJMSG	"8" BDT/JES3 JES3 CONSOLE MSG
	.... 1..1		BSIDNATV	"9" NATIVE BDT TRANSACTION
	.... 1.1.		BSIDTQIP	"10" TQI POST MESSAGE
	.... 1.11		BSIDTQID	"11" TQI AUTO DISABLE MESSAGE
	.... 11..		BSIDBDEV	"12" BEGIN RES FOR DEV MOD CODES
	.... 11.1		BSIDRES1	"13" RESERVED
	.... 111.		BSIDNTRA	"14" RESERVED
	.... 1111		BSIDNOTE	"15" NJE TRANSACTION NOTIFICATION
	...1 ....		BSIDRES2	"16" RESERVED
	...1 ...1		BSIDRES3	"17" RESERVED
	...1 .1.		BSIDRES4	"18" RESERVED
	...1 .11		BSIDCONT	"19" BDT CONNECT REQUEST
	...1 .1..		BSIDSPND	"20" BDT SUSPEND REQUEST
	...1 .1.1		BSIDRES5	"21" RESERVED
	...1 .11.		BSIDRSUM	"22" BDT RESUME REQUEST
	...1 .111		BSIDRES6	"23" RESERVED
	...1 1...		BSIDRES7	"24" RESERVED
	...1 1..1		BSIDRES8	"25" RESERVED
	...1 1.1.		BSIDRES9	"26" RESERVED
	...1 1.11		BSIDRS10	"27" RESERVED
	...1 11..		BSIDRS11	"28" RESERVED
	...1 11.1		BSIDRS12	"29" RESERVED
	...1 111.		BSIDNMR	"30" NJE NODAL MESSAGE RECORD REQ
	...1 1111		BSIDNMRR	"31" RETURN NMR TO JES3
	.1.1 ...1		BSIDNJET	"81" X'51' NJE TRANSACTION
	1... ....		BSIDUSE1	"128" BEGIN RES FOR USER MOD CODES
MESSAGE CLASS DEFINITION				
13	(D) BITSTRING	1	BSIDMCLS	MESSAGE CLASS
	1... ....		BSIDBDT	"BIT0" CLASS=BDT
	.1.. ....		BSIDBAT	"BIT1" CLASS=BATCH
	.1. ....		BSIDSYS	"BIT2" CLASS=SYSTEM
	...1 ....		BSIDNLOG	"BIT3" CLASS=NOLOG

		.... 1...		BSIDSUPP	"BIT4" CLASS=SUPPRESS
		.... .1..		BSIDMCR1	"BIT5" RESERVED
		.... ..1.		BSIDMCR2	"BIT6" RESERVED
		.... ...1		BSIDMCR3	"BIT7" RESERVED
14	FLAG 1 (E)	DEFINITION BITSTRING	1	BSIDFLG1	BSID FLAG 1
		1... ....		BSIDSEND	"BIT0" BDT SYSTEM 'SEND' COMMAND
		.1.. ....		BSIDIDUS	"BIT1" SYSID IS USER SPECIFIED
		..1. ....		BSIDWAIT	"BIT2" SYNCHRONOUS RESP REQUIRED
		...1 ....		BSIDRPLY	"BIT3" ASYNCHRONOUS RESP EXPECTED
		.... 1...		BSIDACK	"BIT4" SYNCHRONOUS ACKLDGD REQUIRED
		.... .1..		BSIDNOLG	"BIT5" SUPPRESS COMMAND DGD LOGGING REQUIRED
		.... ..1.		BSIDF1R1	"BIT6" RESERVED
		.... ...1		BSIDF1R2	"BIT7" RESERVED
15	FLAG 2 (F)	DEFINITION BITSTRING	1	BSIDFLG2	BSID FLAG 2
		1... ....		BSIDINMR	"BIT0" INBOUND NODAL MESSAGE RECORD
		.1.. ....		BSIDPRI	"BIT1" PRIORITY TRANSACTION
		..1. ....		BSIDPTMN	"BIT2" BSID FREEMAIN TYPE
		...1 ....		BSIDFILL	"BIT3" JES SHOULD FILL IN JOB NUM
		.... 1...		BSIDSSNW	"BIT4" WAIT FOR TQI CKPT OF CMD OR TRANS
		.... .1..		BSIDJOBT	"BIT5" NJE JOB TRANSACTION
		.... ..1.		BSIDSSOT	"BIT6" NJE SYSOUT TRANSACTION
		.... ...1		BSIDJBSI	"BIT7" BSID GOTTEN BY JES3
16	FLAG 3 (10)	DEFINITION BITSTRING	1	BSIDFLG3	BSID FLAG 3
17	FLAG 4 (11)	DEFINITION BITSTRING	1	BSIDFLG4	BSID FLAG 4
18	(12)	CHARACTER	4	BSIDXHDR	CONTROL BLOCK ACRONYM
22	(16)	CHARACTER	4	BSIDXREL	VERSION ID
26	(1A)	ADDRESS	2	BSIDXLEN	XOID LENGTH
28	(1C)	BITSTRING	8	BSIDXBSI	XACTION ORIGIN BDT SYS ID
36	(24)	BITSTRING	8	BSIDXBSN	XACTION ORIGIN BDT SYS NAME
44	TRANSACTION ORIGIN (2C)	TYPE BITSTRING	1	BSIDXTYP	XACTION ORIGIN TYPE
		.... ...1		BSIDTSO	"1" TSO USER
		.... ..1.		BSIDJES	"2" JES CONSOLE
		.... ...11		BSIDBTCH	"3" BATCH JOB
		.... .1..		BSIDMCS	"4" MCS CONSOLE
		.... .1.1		BSIDLOG	"5" JOB MESSAGE LOG
		.... ..11.		BSIDFCT	"6" BDT FCT
		.... .111		BSIDJMC	"7" JES MESSAGE CLASS
		.... 1...		BSIDRDEV	"8" BEGIN DEVELOPMENT DEFINED XOIDXTYP
		1... ....		BSIDUSER	"128" BEGIN USER DEFINED XOIDXTYP
45	FLAG 1 (2D)	DEFINITION BITSTRING	1	BSIDXFL1	XOID FLAG 1
		1... ....		BSIDXMCL	"BIT0" SUPPRESSION OF MESSAGE CLASS
		.1.. ....		BSIDX1R1	"BIT1" RESERVED
		..1. ....		BSIDX1R2	"BIT2" RESERVED
		...1 ....		BSIDX1R3	"BIT3" RESERVED
		.... 1...		BSIDX1R4	"BIT4" RESERVED
		.... .1..		BSIDX1R5	"BIT5" RESERVED



	....	..1.		BSIDX1R6	"BIT6" RESERVED
	....	...1		BSIDX1R7	"BIT7" RESERVED
MISCELLANEOUS INFORMATION					
46	(2E)	CHARACTER	8	BSIDXDDN	TRANSACTION ORIGIN DDNAME
46	(2E)	CHARACTER	8	BSIDUSID	TSO USERID
46	(2E)	CHARACTER	8	BSIDCNDD	JES CONSOLE DDNAME
46	(2E)	CHARACTER	8	BSIDJCLS	JES MESSAGE CLASS
46	(2E)	CHARACTER	8	BSIDBJNM	BATCH JOB NAME
46	(2E)	ADDRESS	1	BSIDMCSI	MCS CONSOLE ID
46	(2E)	BITSTRING	2	BSIDBJNO	BDT JOB NUMBER
46	(2E)	BITSTRING	8	BSIDDDRS	DDNAME
RESERVED FIELDS					
54	(36)	BITSTRING	4	BSIDXRDR	RESERVED
58	(3A)	BITSTRING	4	BSIDXR03	RESERVED
62	(3E)	BITSTRING	4	BSIDXRS1	RESERVED
66	(42)	BITSTRING	4	BSIDXRS2	RESERVED
70	(46)	BITSTRING	4	BSIDXRU1	RESERVED
74	(4A)	BITSTRING	4	BSIDXRU2	RESERVED
	..1.	1111		BSIDMCSA	MCS CONSOLE UX28 AUTH
	.1..	111.		BSIDXEND	END OF XOID
	...1	..1.		BSIDXOID	XOID EQUATE
	...1	11..		BSIDXALL	BSI EQUATE
78	(4E)	CHARACTER	8	BSIDDEST	DESTINATION
78	(4E)	CHARACTER	8	BSIDORG	ORIGIN
78	(4E)	CHARACTER	8	BSIDSYSI	BDT SYSTEM ID
86	(56)	ADDRESS	2	BSIDJNUM	JES JOB NUMBER OF BDT SYSTEM
TQI UNIQUE IDENTIFIER MAPPING MACRO					
88	(58)	FIXED	4	BSIUTI	
88	(58)	BITSTRING	1	BSIRECS	NUMBER OF RECORDS REQUIRED
	1...	....		BSIREXMT	"BIT0" RETRANSMISSION FLAG
	1...	....		BSIPNDFG	"BIT0" TQI PENDING FLAG
89	(59)	CHARACTER	3	BSICPUID	CPU ID CHARACTERS
92	(5C)	FIXED	4	BSIRNWD	ALIGNMENT
92	(5C)	FIXED	2	BSIRUD1	RESERVED FOR DEVELOPMENT
94	(5E)	FIXED	2	BSIRNUM	RELATIVE RECORD NUMBER
96	(60)	CHARACTER	8	BSIDTTM	DATE TIME STAMP
104	(68)	CHARACTER	8	BSIXMTTM	TIME OF SUBMISSION
112	(70)	FIXED	4	BSIEND	END OF UTI
	...1	1...		BSISIZE	LENGTH OF UTI
	.1.1	1...		BSIENTRY	UTI EQUATE
112	(70)	ADDRESS	4	BSIDTQI1	TQI UTILITY FIELD
116	(74)	ADDRESS	4	BSIDTQI2	TQI UTILITY FIELD
120	(78)	ADDRESS	4	BSIDJES3	JES3 USE
124	(7C)	ADDRESS	2	BSIDVRDL	LENGTH OF VARIABLE PART OF BSID
126	(7E)	ADDRESS	2	BSIDRSD2	RESERVED
128	(80)	ADDRESS	4	BSIDRSD3	RESERVED
132	(84)	ADDRESS	4	BSIDRSD4	RESERVED
136	(88)	ADDRESS	4	BSIDRSD5	RESERVED
140	(8C)	ADDRESS	4	BSIDRSD6	RESERVED
144	(90)	ADDRESS	4	BSIDRSD7	RESERVED
148	(94)	ADDRESS	4	BSIDRSD8	RESERVED
152	(98)	CHARACTER	8	BSIDRSD9	RESERVED
160	(A0)	CHARACTER	8	BSIDRSDA	RESERVED
168	(A8)	ADDRESS	4	BSIDRSS1	RESERVED
172	(AC)	ADDRESS	4	BSIDRSS2	RESERVED
176	(B0)	ADDRESS	4	BSIDRSS3	RESERVED
180	(B4)	ADDRESS	4	BSIDRSS4	RESERVED
184	(B8)	ADDRESS	4	BSIDRSU1	RESERVED
188	(BC)	ADDRESS	4	BSIDRSU2	RESERVED
192	(C0)	FIXED	2	BSIDFEND	ALIGN TO FULLWORD
	....	....		BSIDFIXD	FIXED LENGTH OF BSID
	11..	....		BSIDMINL	MINIMUM LENGTH OF BSID
192	(C0)	FIXED		BSIDMAXL	"3584" MAXIMUM LENGTH OF BSID
192	(C0)	FIXED	2	BSIDDATA	BEGINNING OF VARIABLE DATA

VARIABLE PART OF THE BSID					
BSID EXTENSION FOR NJE					
192	(C0)	FIXED	2	BSIDNJE	BDT EXTENSION FOR NJE
192	(C0)	CHARACTER	1	BSIDEVNT	BDT EVENT FIELD
		....	...1	BSIDTRNQ	"1" TRANSACTION QUEUED
		....	..1.	BSIDABNR	"2" TRANSACTION ABNORMAL COMPLETION
		....	..11	BSIDCANC	"3" TRANSACTION CANCELLED BY OPER
		....	.1..	BSIDDUPE	"4" TRANSACTION IS A DUPLICATE
		....	.1.1	BSIDOPRC	"5" TRANSACTION NOT QUEUED
		....	.11.	BSIDOPRX	NODE IS NOT AN NJE NODE.
					"6" TRANSACTION REMOVED FROM QUEUE NODE HAS BEEN REMOVED.
		....	.111	BSIDNCAN	"7" JES3 CANCEL REJECTED
		....	1...	BSIDNEV2	"8" RESERVED
		....	1..1	BSIDNEV3	"9" RESERVED
		....	1.1.	BSIDNJOB	"10" JOB NOT FOUND
		....	1.11	BSIDNEV4	"11" RESERVED
		....	11..	BSIDNEV5	"12" RESERVED
		....	11.1	BSIDNEV6	"13" RESERVED
		....	111.	BSIDNEV7	"14" RESERVED
		....	1111	BSIDNEV8	"15" RESERVED
		...1	....	BSIDNEV9	"16" RESERVED
		...1	...1	BSIDNE10	"17" RESERVED
		...1	.1.	BSIDNE11	"18" RESERVED
		...1	..11	BSIDNE12	"19" RESERVED
		...1	.1..	BSIDNORC	"20" NORMAL CONNECT REQUESTED
		...1	.1.1	BSIDABNC	"21" ABNORMAL CONNECT REQUESTED
193	(C1)	CHARACTER	1	BSIDDT1	RESERVED
194	(C2)	CHARACTER	8	BSIDJGID	JES3 GROUP ID
202	(CA)	FIXED	2	BSIDBJOB	BDT JOB NUMBER
204	(CC)	CHARACTER	8	BSIDJOBN	JES3 JOB NAME
212	(D4)	CHARACTER	8	BSIDJJOB	JES3 JOB NUMBER
220	(DC)	FIXED	4	BSIDVEND	END OF VARIABLE DATA
		.1..	111.	BSIDDNOD	"BSIDDEST" DESTINATION NODE NAME
		11..	....	BSIDVARL	VARIABLE LENGTH          NODE

CROSS REFERENCE			
NAME	HEX OFFSET	HEX VALUE	LEVEL
BSICPUID	59	4040	2
BSIDABNC	C0	15	2
BSIDABNR	C0	2	2
BSIDACK	E	8	2
BSIDBAT	D	40	2
BSIDBDEV	C	C	2
BSIDBDT	D	80	2
BSIDBJNM	2E		2
BSIDBJNO	2E		2
BSIDBJOB	CA		2
BSIDBTCH	2C	3	2
BSIDCANC	C0	3	2
BSIDCMND	C	4	2
BSIDCNDD	2E		2
BSIDCONT	C	13	2
BSIDDATA	C0		2
BSIDDDRS	2E	0	2
BSIDDEST	4E		2
BSIDDNOD	DC	4E	2
BSIDDT1	C1		2
BSIDDUPE	C0	4	2
BSIDEVNT	C0		2
BSIDFCT	2C	6	2
BSIDFEND	C0		2
BSIDFILL	F	10	2
BSIDFIXD	C0	0	2
BSIDFLG1	E		2
BSIDFLG2	F		2
BSIDFLG3	10		2
BSIDFLG4	11		2

BSIDFXDL	A	C0	2
BSIDF1R1	E	2	2
BSIDF1R2	E	1	2
BSIDID	2	C2E2	2
BSIDIDUS	E	40	2
BSIDINMR	F	80	2
BSIDJBSI	F	1	2
BSIDJCLS	2E		2
BSIDJCMD	C	5	2
BSIDJES	2C	2	2
BSIDJES3	78		2
BSIDJGID	C2		2
BSIDJJOB	D4		2
BSIDJMC	2C	7	2
BSIDJMSG	C	8	2
BSIDJNUM	56		2
BSIDJOBN	CC		2
BSIDJOBT	F	4	2
BSIDLOG	2C	5	2
BSIDMAXL	C0	E00	2
BSIDMCLS	D		2
BSIDMCR1	D	4	2
BSIDMCR2	D	2	2
BSIDMCR3	D	1	2
BSIDMCS	2C	4	2
BSIDMCSA	4A	2F	2
BSIDMCSI	2E		2
BSIDMESG	C	2	2
BSIDMINL	C0	C0	2
BSIDMOD	C	0	2
BSIDNATV	C	9	2
BSIDNCAN	C0	7	2
BSIDNEV2	C0	8	2
BSIDNEV3	C0	9	2
BSIDNEV4	C0	B	2
BSIDNEV5	C0	C	2
BSIDNEV6	C0	D	2
BSIDNEV7	C0	E	2
BSIDNEV8	C0	F	2
BSIDNEV9	C0	10	2
BSIDNE10	C0	11	2
BSIDNE11	C0	12	2
BSIDNE12	C0	13	2
BSIDNJE	C0		2
BSIDNJET	C	51	2
BSIDNJOB	C0	A	2
BSIDNLOG	D	10	2
BSIDNMRR	C	1F	2
BSIDNNMR	C	1E	2
BSIDNOLG	E	4	2
BSIDNORC	C0	14	2
BSIDNOTE	C	F	2
BSIDNTRA	C	E	2
BSIDOFFL	C	6	2
BSIDOPRC	C0	5	2
BSIDOPRX	C0	6	2
BSIDORG	4E		2
BSIDPRI	F	40	2
BSIDPTMN	F	20	2
BSIDRDEV	2C	8	2
BSIDREJT	C	7	2
BSIDRES1	C	D	2
BSIDRES2	C	10	2
BSIDRES3	C	11	2
BSIDRES4	C	12	2
BSIDRES5	C	15	2
BSIDRES6	C	17	2
BSIDRES7	C	18	2
BSIDRES8	C	19	2
BSIDRES9	C	1A	2
BSIDRPLY	E	10	2
BSIDRSDA	A0	4040	2
BSIDRSD2	7E		2
BSIDRSD3	80		2
BSIDRSD4	84		2
BSIDRSD5	88		2
BSIDRSD6	8C		2
BSIDRSD7	90		2
BSIDRSD8	94		2
BSIDRSD9	98	4040	2
BSIDRSS1	A8		2
BSIDRSS2	AC		2

BSIDRSS3	B0		2
BSIDRSS4	B4		2
BSIDRSUM	C	16	2
BSIDRSU1	B8		2
BSIDRSU2	BC		2
BSIDRS10	C	1B	2
BSIDRS11	C	1C	2
BSIDRS12	C	1D	2
BSIDSEND	E	80	2
BSIDSHTL	C	1	2
BSIDSPND	C	14	2
BSIDSSNW	F	8	2
BSIDSSOT	F	2	2
BSIDSUPP	D	8	2
BSIDSYS	D	20	2
BSIDSYSI	4E	4040	2
BSIDTOTL	0	0	2
BSIDTQID	C	B	2
BSIDTQIP	C	A	2
BSIDTQI1	70		2
BSIDTQI2	74		2
BSIDTRNQ	C0	1	2
BSIDTSO	2C	1	2
BSIDTTM	60	4040	2
BSIDUSER	2C	80	2
BSIDUSE1	C	80	2
BSIDUSID	2E		2
BSIDVARL	DC	C0	2
BSIDVEND	DC		2
BSIDVER#	6	F2F0	2
BSIDVRDL	7C	1C	2
BSIDWAIT	E	20	2
BSIDXACT	C	3	2
BSIDXALL	4A	1C	2
BSIDXBSI	1C	0	2
BSIDXBSN	24	0	2
BSIDXDDN	2E		2
BSIDXEND	4A	4E	2
BSIDXFL1	2D	0	2
BSIDXHDR	12	E7D6	2
BSIDXLEN	1A	3C	2
BSIDXMCL	2D	80	2
BSIDXOID	4A	12	2
BSIDXRD2	36	0	2
BSIDXRD3	3A	0	2
BSIDXREL	16	F1F0	2
BSIDXRS1	3E	0	2
BSIDXRS2	42	0	2
BSIDXRU1	46	0	2
BSIDXRU2	4A	0	2
BSIDXTYP	2C	0	2
BSIDX1R1	2D	40	2
BSIDX1R2	2D	20	2
BSIDX1R3	2D	10	2
BSIDX1R4	2D	8	2
BSIDX1R5	2D	4	2
BSIDX1R6	2D	2	2
BSIDX1R7	2D	1	2
BSIEND	70		2
BSIENTRY	70	58	2
BSIPNDFG	58	80	2
BSIRECS	58	0	2
BSIREXMT	58	80	2
BSIRNUM	5E	0	2
BSIRNWD	5C		2
BSIRUD1	5C	0	2
BSISIZE	70	18	2
BSIUTI	58		2
BSIXMTTM	68	4040	2

## Chapter 4. Generalized Subtask Directory – GSD

The generalized subtask directory (GSD) contains one entry for each resident function and each scheduled job. It also contains the address of the MVS TCB, which is needed for dispatching the BDT task that is associated with each resident function or job.

The GSD is used by abend and recovery functions and by the multifunction monitor, BDTGRCT.

**Macro ID:** BDTDGSD

**DSECT name:** GSDSTART

**Created by:** BDTGRJS via BDTGRFC

**Size:** Hex 1F4 bytes

**Pointed to by:** JMLGSD, FCTGSD, TCBBDT

**Location:** GSDs for resident functions reside permanently in BDTGRPT in BDTNUC. The GSDs for jobs are dynamically allocated in cell pool FCTs when the transaction is scheduled, and released when the job is purged.

OFFSETS	TYPE		LENGTH	NAME	DESCRIPTION
	GENERALIZED SUBTASK DIRECTORY PREFIX				
	MACDATE = 04/12/82				
	THE VALUE OF SPLEVEL IS NOW 1				
	GENERALIZED SUBTASK DIRECTORY PREFIX				
0	(0)	CHARACTER	4	GSDID	CONTROL BLOCK ID
4	(4)	CHARACTER	4	GSDREL	VERSION RELEASE ID
8	(8)	ADDRESS	2	GSDLEN	CONTROL BLOCK SIZE
10	(A)	ADDRESS	2	GSDURSV1	RESERVED
12	(C)	FIXED	4	GSDECB	ADDRESS OF SUBTASK ECB
16	(10)	FIXED	4	GSDTMDT	TIME AND DATE OF ABEND
16	(10)	FIXED	4	GSDTIME	TIME OF ABEND
20	(14)	FIXED	4	GSDDATE	DATE OF ABEND
24	(18)	BITSTRING	1	GSDILC1	INSTRUCTION LENGTH CODE
25	(19)	BITSTRING	2	GSDINC1	INTERRUPT CODE
27	DEFINITION OF GSDFLG2 (1B)		1	GSDFLG2	FLAG2
	1...	....		GSDRCVLD	"BIT0" REASON CODE IS VALID
	.1..	....		GSDSVDM	"BIT1" SVC DUMP TAKEN
	..1.	....		GSDSYNC	"BIT2" SYNCHRONOUS ABEND REQUESTED
	...1	....		GSDNOLST	"BIT3" NO LIST PRESENT IN SDTLIST
	....	1...		GSDGET1	"BIT4" PARMLIST STORAGE OBTAINED
	....	.1..		GSDGET2	"BIT5" SDUMP TITLE STG OBTAINED
	....	..1.		GSDCCRC	"BIT6" COMPL CODE HAS BEEN RECORDED
	....	...1		GSDFL2R2	"BIT7" RESERVED
28	(1C)	FIXED	4	GSDNXT1	ADDRESS OF NEXT INSTRUCTION
32	(20)	FIXED	4	GSDDRSV1	RESERVED
36	(24)	ADDRESS	4	GSDDUMPT	ADDRESS OF DUMP TITLE TEXT
40	SUBTASK REGISTER SAVE AREA (28)		4	GSDSUBSV	SUBTASK REGISTERS R3 R10

72	(48)	FIXED	4	GSDFACT	SUBTASK REGISTER R11
76	(4C)	FIXED	4	GSDTVT	SUBTASK REGISTER R12
80	(50)	FIXED	4	GSDR13	SUBTASK REGISTER R13
84	ESTAE (54)	EXIT REGISTER SAVE AREA FIXED	4	GDESTAE	ESTAE EXIT REGISTER SAVE AREA
148	REGISTER SAVE AREA (94)	AT TIME OF ABEND FIXED	4	GSDERREG	CONTENTS OF R0 R15 AT TIME OF ABEND
212	(D4)	FIXED	4	GSDPSW	ABEND PSW
220	(DC)	FIXED	4	GSDABCC	ABEND COMPLETION CODE
224	(E0)	BITSTRING	1	GSDLOCK	SUBTASK LOCK
225	(E1)	BITSTRING	1	GSDCEF	SUBTASK ECF
226	DEFINITION OF GSDFLG1 (E2)	BITSTRING	1	GSDFLG1	FLAG1
	1...	....		GSDFAILD	"BIT0" FAILDAP ISSUED
	.1...	....		GSDNODMP	"BIT1" SUPPRESS BDT FORMATTED DUMP
	..1.	....		GSDRTM	"BIT2" TASK TERMINATED BY RTM
	...1	....		GSDREST	"BIT3" RESTART REQUESTED
	....	1...		GSDNOREC	"BIT4" NO RECOVERY PERMITTED
	....	.1..		GSDCANCL	"BIT5" JOB CANCELLED
	....	..1.		GSDBD322	"BIT6" JOB EXCEEDED TIME LIMIT
	....	...1		GSDABEND	"BIT7" ABEND IN PROGRESS
227	DEFINITION OF SUBTASK RETURN CODES (E3)	BITSTRING	1	GSDRC	SUBTASK RETURN CODE
	....	....		GSDNORM	"X'00'" NORMAL RETURN
	....	.1..		GSDABND	"X'04'" FUNCTION ABENDED
228	(E4)	FIXED	4	GSDTCB	ADDRESS OF SUBTASK TCB
232	(E8)	FIXED	4	GSDRSD01	RESERVED
236	(EC)	FIXED	4	GSDRSD02	RESERVED
240	(F0)	FIXED	4	GSDRSD03	RESERVED
244	(F4)	FIXED	4	GSDSTRAD	ADDRESS OF GETMAIN'ED AREA
248	(F8)		8	GSDWORK	WORK AREA
256	(100)	CHARACTER	8	GSDRCVMD	RECOVERY ROUTINE MODULE NAME
264	(108)	CHARACTER	8	GSDRCVLB	RECOVERY ROUTINE LABEL
ESTAE ,PURGE=QUIESCE,ASYNCH=NO,TERM=TES,RECORD=YES,MF=L					
MACDATE 80247					
272	(110)	FIXED	4		
272	(110)	ADDRESS	1	GDESTAL	FLAGS FOR TCB,PURGE,ASYNCH
273	(111)	ADDRESS	3		EXIT ADDR. NOT SPECIFIED
276	(114)	ADDRESS	4		PARM. LIST ADDR. NOT SPECIFIED
280	(118)	ADDRESS	4		TCB NOT SPECIFIED
284	(11C)	ADDRESS	1		FLAGS
285	(11D)	ADDRESS	3		RESERVED
288	(120)	ADDRESS	4		TOKEN VALUE AREA
292	(124)	FIXED	2	GDESTND	
296)	(128)		8	GSDTWA	GSD TRACE WORK AREA
TRACE WORK AREA					
296	(128)		8		
296	(128)	CHARACTER	4		DIRECTORY ID
300	(12C)	CHARACTER	4		VERSION RELEASE ID
304	(130)	ADDRESS	2		CONTROL BLOCK SIZE
306	(132)	BITSTRING	1		GENERIC FOR TWA WORK AREA
306	(132)	CHARACTER	4		CHARS 4 7 OF MODULE NAME
310	(136)	BITSTRING	1		RESERVED FOR DEV
311	(137)	CHARACTER	1		ID FOR THIS TRACE ENTRY
312	(138)	ADDRESS	2		OFFSET IN MOD FOR BDTXTRC
316	(13C)	FIXED	4		GENERIC FOR ALL TWATW WORDS
316	(13C)	ADDRESS	4		TRC ENT BDTXTRC ENTRY WORD 1
320	(140)	ADDRESS	4		TRC ENT BDTXTRC ENTRY WORD 2
324	(144)	ADDRESS	4		TRC ENT BDTXTRC ENTRY WORD 3
328	(148)	ADDRESS	4		TRC ENT BDTXTRC ENTRY WORD 4
332	(14C)	ADDRESS	4		TRC ENT BDTXTRC ENTRY WORD 5

336	(150)	ADDRESS	4	TRC ENT BDTXTRC ENTRY WORD 6
340	(154)	BITSTRING	1	GENERIC FOR ALL TWATW WORDS
340	(154)	BITSTRING	1	TRC ENT REG SAVE AREA
340	(154)	ADDRESS	4	TRC ENT REG 00
344	(158)	ADDRESS	4	TRC ENT REG 01
348	(15C)	ADDRESS	4	TRC ENT REG 02
352	(160)	ADDRESS	4	TRC ENT REG 03
356	(164)	ADDRESS	4	TRC ENT REG 04
360	(168)	ADDRESS	4	TRC ENT REG 05
364	(16C)	ADDRESS	4	TRC ENT REG 06
368	(170)	ADDRESS	4	TRC ENT REG 07
372	(174)	ADDRESS	4	TRC ENT REG 08
376	(178)	ADDRESS	4	TRC ENT REG 09
380	(17C)	ADDRESS	4	TRC ENT REG 10
384	(180)	ADDRESS	4	TRC ENT REG 11
388	(184)	ADDRESS	4	TRC ENT REG 12
392	(188)	ADDRESS	4	TRC ENT REG 13
396	(18C)	ADDRESS	4	TRC ENT REG 14
400	(190)	ADDRESS	4	TRC ENT REG 15
404	(194)	ADDRESS	4	BDTXTRC REG SAVE AREA
472	(1D8)		8	TRC ENT TIME FIELD
480	(1E0)	ADDRESS	4	RC FROM LAST GRTX CALL
484	(1E4)	ADDRESS	4	RES FOR DESIGN
488	(1E8)	ADDRESS	4	RES FOR DESIGN
492	(1EC)	ADDRESS	4	RES FOR SERVICE
496	(1F0)	ADDRESS	4	RES FOR SERVICE
500	(1F4)	BITSTRING	1	END OF TWA
500	(1F4)		GSDEND	END OF GSD
500	(1F4)		GSDSIZE	LENGTH OF GSD

	TRACE	WORK AREA			
0	(0)	CHARACTER	4	TWACBID	CONTROL BLOCK ID
4	(4)	CHARACTER	4	TWAREL	VERSION RELEASE ID
8	(8)	ADDRESS	2	TWAKLEN	CONTROL BLOCK SIZE
10	(A)	BITSTRING	1	TWAWORK	GENERIC FOR TWA WORK AREA
10	(A)	CHARACTER	4	TWANAME	CHARS 4 7 OF MODULE NAME
14	(E)	BITSTRING	1	TWARES	RESERVED FOR DEV
15	(F)	CHARACTER	1	TWAID	ID FOR THIS TRACE ENTRY
16	(10)	ADDRESS	2	TWAOFF	OFFSET IN MOD FOR BDTXTRC
20	(14)	FIXED	4	TWATW	GENERIC FOR ALL TWATW WORDS
20	(14)	ADDRESS	4	TWATW1	TRC ENT BDTXTRC ENTRY WORD 1
24	(18)	ADDRESS	4	TWATW2	TRC ENT BDTXTRC ENTRY WORD 2
28	(1C)	ADDRESS	4	TWATW3	TRC ENT BDTXTRC ENTRY WORD 3
32	(20)	ADDRESS	4	TWATW4	TRC ENT BDTXTRC ENTRY WORD 4
36	(24)	ADDRESS	4	TWATW5	TRC ENT BDTXTRC ENTRY WORD 5
40	(28)	ADDRESS	4	TWATW6	TRC ENT BDTXTRC ENTRY WORD 6
44	(2C)	BITSTRING	1	TWATWEND	GENERIC FOR ALL TWATW WORDS
44	(2C)	BITSTRING	1	TWAREGS	TRC ENT REG SAVE AREA
44	(2C)	ADDRESS	4	TWAR00	TRC ENT REG 00
48	(30)	ADDRESS	4	TWAR01	TRC ENT REG 01
52	(34)	ADDRESS	4	TWAR02	TRC ENT REG 02
56	(38)	ADDRESS	4	TWAR03	TRC ENT REG 03
60	(3C)	ADDRESS	4	TWAR04	TRC ENT REG 04
64	(40)	ADDRESS	4	TWAR05	TRC ENT REG 05
68	(44)	ADDRESS	4	TWAR06	TRC ENT REG 06
72	(48)	ADDRESS	4	TWAR07	TRC ENT REG 07
76	(4C)	ADDRESS	4	TWAR08	TRC ENT REG 08
80	(50)	ADDRESS	4	TWAR09	TRC ENT REG 09
84	(54)	ADDRESS	4	TWAR10	TRC ENT REG 10
88	(58)	ADDRESS	4	TWAR11	TRC ENT REG 11
92	(5C)	ADDRESS	4	TWAR12	TRC ENT REG 12
96	(60)	ADDRESS	4	TWAR13	TRC ENT REG 13
100	(64)	ADDRESS	4	TWAR14	TRC ENT REG 14
104	(68)	ADDRESS	4	TWAR15	TRC ENT REG 15
108	(6C)	ADDRESS	4	TWASAVE	BDTXTRC REG SAVE AREA
176	(B0)		8	TWASTCK	TRC ENT TIME FIELD
184	(B8)	ADDRESS	4	TWARETC	RC FROM LAST GRTX CALL
188	(BC)	ADDRESS	4	TWARES1	RES FOR DESIGN
192	(C0)	ADDRESS	4	TWARES2	RES FOR DESIGN
196	(C4)	ADDRESS	4	TWARES3	RES FOR SERVICE
200	(C8)	ADDRESS	4	TWARES4	RES FOR SERVICE
204	(CC)	BITSTRING	1	TWAEND	END OF TWA
	11..	11..		TWASIZE	LENGTH OF TWA
	11..	..1.		TWAWORKL	LENGTH OF TWA WORK AREA
	...1	1...		TWATWL	LTH FOR GENERIC TWATW WORDS

CROSS REFERENCE  
HEX HEX

NAME	OFFSET	VALUE	
GSDABCC	DC	0	2
GSDABEND	E2	1	2
GSDABND	E3	4	2
GSDBD322	E2	2	2
GSDCANCL	E2	4	2
GSDCCRCO	1B	2	2
GSDDATE	14	0	2
GSDDRSV1	20	0	2
GSDDUMPT	24		2
GSDDWORK	F8	0	2
GSDECB	C	0	2
GSDECF	E1	0	2
GSDEND	1F4	1F4	2
GSDERREG	94	0	2
GSESTAE	54	0	2
GSESTAL	110		2
GSESTND	124		2
GSDFAILD	E2	80	2
GSDFACT	48	0	2
GSDFLG1	E2	0	2
GSDFLG2	1B	0	2
GSDFL2R2	1B	1	2
GSDGET1	1B	8	2
GSDGET2	1B	4	2
GSDID	0	C7E2	2
GSDILC1	18	0	2
GSDINC1	19	0	2
GSDLEN	8		2
GSDLOCK	E0	0	2
GSDNODMP	E2	40	2
GSDNOLST	1B	10	2
GSDNOREC	E2	8	2
GSDNORM	E3	0	2
GSDNXT1	1C	0	2
GSDPSW	D4	0	2
GSDRC	E3	0	2
GSDRCVLB	108	4040	2
GSDRCVLD	1B	80	2
GSDRCVMD	100	4040	2
GSDREL	4	F2F0	2
GSDREST	E2	10	2
GSDRSD01	E8	0	2
GSDRSD02	EC	0	2
GSDRSD03	F0	0	2
GSDRTM	E2	20	2
GSDR13	50	0	2
GSDSIZE	1F4	1F4	2
GSDSTRAD	F4	0	2
GSDSUBSV	28	0	2
GSDSVDMF	1B	40	2
GSDSYNC	1B	20	2
GSDTCB	E4	0	2
GSDTIME	10	0	2
GSDTMDT	10		2
GSDTVT	4C	0	2
GSDTWA	128		2
GSDURSV1	A		2
TWACBID	0	E3E6	2
TWAEND	CC		2
TWAID	F	40	2
TWALEN	8		2
TWANAME	A	4040	2
TWAOFF	10		2
TWAREGS	2C		2
TWAREL	4	F2F0	2
TWARES	E	0	2
TWARES1	BC		2
TWARES2	C0		2
TWARES3	C4		2
TWARES4	C8		2
TWARETC	B8		2
TWAR00	2C		2
TWAR01	30		2
TWAR02	34		2
TWAR03	38		2
TWAR04	3C		2
TWAR05	40		2
TWAR06	44		2
TWAR07	48		2
TWAR08	4C		2



TWAR09	50		2
TWAR10	54		2
TWAR11	58		2
TWAR12	5C		2
TWAR13	60		2
TWAR14	64		2
TWAR15	68		2
TWASAVE	6C		2
TWASIZE	CC	CC	2
TWASTCK	B0	0	2
TWATW	14		2
TWATWEND	2C		2
TWATWL	CC	18	2
TWATW1	14		2
TWATW2	18		2
TWATW3	1C		2
TWATW4	20		2
TWATW5	24		2
TWATW6	28		2
TWAWORK	A		2
TWAWORKL	CC	C2	2



## Chapter 5. Initialization Data CSECT – INT

The INT is a work area that contains addresses of the macros that reside in BDTINRN. Used by initialization modules, these macros perform such basic services as parsing, scanning, character conversion, and spool reading and writing.

<b>Function:</b>	The INT defines the data areas used by the initialization modules. It contains the entry points for error processing and produces error messages.
<b>Macro ID:</b>	BDTDINT
<b>DSECT name:</b>	BDTSTART
<b>Created by:</b>	BDTINDT
<b>Size:</b>	Hex F07 bytes
<b>Location:</b>	Subpool 251

OFFSETS	TYPE	LENGTH	NAME	DESCRIPTION
0	GENERATE BDT INITIALIZATION (0)	8	INTPKARA	ZONED TO PACKED DIGITS AREA
	.... .1..		INTCNANS	CONVERSION RESULT
8	(8) FIXED	4	INTOBSA	OS BSAM SAVE AREA
NOTE - ABOVE 3 STATEMENTS MUST BE FIRST				
72	(48) CHARACTER	4	INTHDR	CONTROL BLOCK ACRONYM
76	(4C) CHARACTER	4	INTREL	VERSION RELEASE ID
80	(50) ADDRESS	2	INTLNTH	CONTROL BLOCK LENGTH
82	(52) FIXED	2	INTRSVDZ	RESERVED
	.... 1....		INTMNJMX	"8" MAX NO. OF BDT MAINS ALLOWED
84	(54) CHARACTER	8	INTGLBNM	NAME OF GLOBAL PROCESSOR
92	(5C) CHARACTER	8	INTOGLBL	IF IN DSI, NAME OF EX GLOBAL
100	(64) CHARACTER	8	INTMNNAM	BDT NAME OF THIS PROCESSOR
108	(6C) ADDRESS	4	INTBSES	SAVED BASES, FOR INIC,CD,RN
116	(74) ADDRESS	4	INTBAS3	THIRD BASE FOR INCD
120	(78) ADDRESS	4	INTRTN	R14 RETURN POINT TO BDTINIT
124	(7C) ADDRESS	4	INTSVBS	REG SAVE AREA FOR BDTINRN
128	(80) ADDRESS	4	INTACDRD	ADDRESS TO RETURN TO READ STMTS
132	(84) ADDRESS	4	INTERTN	STMT SCAN ERROR RETURN ADDRESS
136	(88) ADDRESS	4	INTCKARE	INITCHK DATA AREA
140	(8C) ADDRESS	4	INTINECB	INIT COMPLETION WAIT ECB
ENTRY POINT ADDRESSES				
144	(90) ADDRESS	4	INTIIADR	ADDR BDTINII ENTRY POINT
148	(94) ADDRESS	4	INTMDADR	ADDR BDTINMD ENTRY POINT
152	(98) ADDRESS	4	INTPKADR	ADDR BDTINPK ENTRY POINT
156	(9C) ADDRESS	4	INTCTADR	ADDR BDTINCT ENTRY POINT
160	(A0) ADDRESS	4	INTINR2	ADDR BDTINR1/BDTINR2 EP
ECB FOR POSTING BDTINTK				
164	(A4) ADDRESS	4	INTUXECB	ECB FOR POSTING BDTINTK TO CALL USER EXIT 01
168	(A8) ADDRESS	4	INTRSVD2	RESERVED
172	(AC) ADDRESS	4	INTIOPRM	BASE OF TRACK/FORMAT STMT TABLE
176	(B0) ADDRESS	4	INTNBDTK	NEXT BAD TRACK TABLE ENTRY
180	(B4) ADDRESS	4	INTTBUF	BUFFER FOR TABLE DDBS
184	(B8) ADDRESS	4	INTUXLAD	ADDRESS OF USER EXIT
188	(BC) FIXED	4	INTRSVD3	RESERVED
204	(CC) FIXED	4	INTRSVU1	RESERVED

212	(D4)	FIXED	2	INTMXBTS	MAX BAD TRK ENTRIES (1 PAGE)
214	(D6)	FIXED	2	INTMAXQS	MAX BDT QUEUE PACKS

SNA - BDT COMMDEFN DATA AREA					
216	(D8)	CHARACTER	8	INTSTCTB	DEFAULT CTE/CTAB NAME
224	(E0)	ADDRESS	4	INTSTPTR	GETMAIN CORE FOR CB'S
228	(E4)	ADDRESS	4	INTINPTR	STARTING COLUMN FOR SCAN
232	(E8)	FIXED	2	INTPAREN	COUNT UNCLOSED PARENTHESES
234	(EA)	FIXED	2	INTLOPER	LENGTH OF OPERAND
236	(EC)	CHARACTER	16	INTSPARM	PARAMETER WORK STORAGE
252	(FC)	CHARACTER	16	INTSOPER	OPERAND WORD STORAGE
268	(10C)	ADDRESS	2	INTTEXT	OUTPUT AREA
280	(118)	CHARACTER	80	INTINARE	INIT CONTROL STMT BUFFER
280	(118)			INTINA72	CONTINUE' COLUMN
360	(168)	FIXED	4	INTRSVDD	RESERVED
380	(17C)	FIXED	4	INTRSVU9	RESERVED
380	(17C)			INTINEND	END OF THIS SECTION

ADDRESSES OF SUBROUTINES IN BDTINRN - SEQ DEPEND LIST					
388	(184)	ADDRESS	4	INTICRD	ROUTINE 'CARDREAD' INIT CONTROL STMT READ ROUTINE
392	(188)	ADDRESS	4	INTICRD2	ROUTINE 'CARDRD2' SECOND ENTRY TO CARDREAD
396	(18C)	ADDRESS	4	INTCNBIN	ROUTINE 'CONVERT' DECIMAL TO BINARY CONVERT ROUTINE
400	(190)	ADDRESS	4	INTRSVD4	RESERVED
404	(194)	ADDRESS	4	INTMWLE	ROUTINE 'INITEMEN' ROUTINE TO FILL IN THE VARIABLE PART OF MESSAGES
408	(198)	ADDRESS	4	INTISCN1	ROUTINE 'SCAN1' CONTROL STATEMENT SCAN ROUTINE
412	(19C)	ADDRESS	4	INTISCN2	ROUTINE 'SCAN2' MULTIPLE OPERAND ENTRY SCAN ROUTINE
416	(1A0)	ADDRESS	4	INTITRD	ROUTINE 'TREAD' INTERMEDIATE SPOOL RECORD READ ROUTINE
420	(1A4)	ADDRESS	4	INTITWRT	ROUTINE 'TWRITE' INTERMEDIATE SPOOL RECORD WRITE ROUTINE
424	(1A8)	ADDRESS	4	INTIWOUT	ROUTINE 'WBDTOUT' ROUTINE TO WRITE ERROR MSGS TO PRINT
428	(1AC)	ADDRESS	4	INTIEOF2	ROUTINE 'INEOF2' ROUTINE FOR END OF FILE FOR BDTIN
432	(1B0)	ADDRESS	4	INTNOGMN	ROUTINE 'NOMAIN' BDTXGTMM FAILURE IN INITIALIZATION ROUTINE
436	(1B4)	ADDRESS	4	INTINRN	RESERVED
448	(1C0)	ADDRESS	4	INTRSVDC	RESERVED
460	(1CC)	ADDRESS	4	INTRSVU8	RESERVED

TITLE ERROR HANDLING OF INITIALIZATION ERRORS					
464	(1D0)	CODE	396	INTEBKW	

TITLE SNA - BDT MESSAGE ROUTINES FOR RELEASE 2					
860	(35C)	CHARACTER	9	MSGCD9I	
869	(365)	CHARACTER	9	MSGR17I	

TITLE MESSAGES USED BY THE INITIALIZATION MODULES					
878	(36E)	ADDRESS	2	INTEBLKL	ASA + MIN TAPE REC
878	(36E)			INTEBLKE	
906	(38A)	ADDRESS	2	INGL3053	
942	(3AE)	CHARACTER	8	INGL53NM	
942	(3AE)			IGL53E	
950	(3B6)	ADDRESS	2	INGL3042	
983	(3D7)	CHARACTER	28		
983	(3D7)			INGL42E	
1012	(3F4)	ADDRESS	2	INGL3048	
1029	(405)	CHARACTER	36		
1029	(405)			INGL48E	
1066	(42A)	ADDRESS	2	INTEPRND	
1102	(44E)	CHARACTER	2		
1104	(450)	CHARACTER	11	INTEILD	
1104	(450)			INTEPDEN	
1116	(45C)	ADDRESS	2	INTECOMB	
1133	(46D)	CHARACTER	39		
1133	(46D)			INTECEN1	
1172	(494)	ADDRESS	2	INTECARD	
1189	(4A5)	CHARACTER	8	INTECSPR	
1198	(4AE)	CHARACTER	8	INTECSOP	

1198	(4AE)			INTECEND	
1232	(4D0)	ADDRESS	2	INTEBDCD	
1262	(4EE)	CHARACTER	11	INTEBDKW	
1262	(4EE)			INTEBDCE	
1274	(4FA)	ADDRESS	2	INTEORKY	
1300	(514)	CHARACTER	11	INTEOKEY	
1300	(514)			INTEOEND	
1328	(530)	ADDRESS	2	INTESOPR	
1354	(54A)	CHARACTER	11	INTESOP1	
1365	(555)	CHARACTER	17	INTESOP2	
1382	(566)	CHARACTER	8	INTEBDPA	
1382	(566)			INTEBDSN	
1392	(570)	ADDRESS	2	INTETBIG	
1410	(582)	CHARACTER	15	INTETBPR	
1410	(582)			INTETBEN	
1462	(5B6)	ADDRESS	2	INTEMPR1	
1479	(5C7)	CHARACTER	5	INTEMPR2	
1484	(5CC)	CHARACTER	27		OR 'LEFT'
1511	(5E7)	CHARACTER	11	INTEMPRM	
1511	(5E7)			INTEMPEN	
1524	(5F4)	ADDRESS	2	INTEREQP	
1559	(617)	CHARACTER	11	INTEREKW	
1572	(624)	CHARACTER	7		
1572	(624)			INTERPEN	
1580	(62C)	ADDRESS	2	INTERPKY	
1597	(63D)	CHARACTER	32		
1629	(65D)	CHARACTER	11	INTEREQK	
1629	(65D)			INTERKEN	
1650	(672)	ADDRESS	2	INTECOTC	
1667	(683)	CHARACTER	31		
1667	(683)			INTECOEN	
1698	(6A2)	ADDRESS	2	INTEILKY	
1728	(6C0)	CHARACTER	11	INTEIKYW	
1728	(6C0)			INTEIKEN	
1752	(6D8)	ADDRESS	2	INTEIBLK	
1769	(6E9)	CHARACTER	37		
1769	(6E9)			INTEIBEN	
1806	(70E)	ADDRESS	2	INTEMSCM	
1823	(71F)	CHARACTER	53	INTEMSC2	
1830	(726)	CHARACTER	26		OR 'MISSING'
1830	(726)			INTEMCEN	
1856	(740)	ADDRESS	2	INTEICHR	
1873	(751)	CHARACTER	37		
1873	(751)			INTEICEN	
1910	(776)	ADDRESS	2	INTECMDF	
1927	(787)	CHARACTER	35		
1927	(787)			INTECMEN	
1962	(7AA)	ADDRESS	2	INTENSNA	
1979	(7BB)	CHARACTER	3		
1982	(7BE)	CHARACTER	8	INTENNM	
1990	(7C6)	CHARACTER	22		
1990	(7C6)			INTENSEN	
2012	(7DC)	ADDRESS	2	INTEDTCT	
2029	(7ED)	CHARACTER	10		
2039	(7F7)	CHARACTER	7	INTEDST	STATEMENT TYPE
2046	(7FE)	CHARACTER	20		
2046	(7FE)			INTEDTEN	
2066	(812)	ADDRESS	2	INTECCNP	
2083	(823)	CHARACTER	9		
2092	(82C)	CHARACTER	7	INTECST	STATEMENT TYPE
2099	(833)	CHARACTER	21		
2099	(833)			INTECCEN	
2120	(848)	ADDRESS	2	INTECHSP	
2137	(859)	CHARACTER	42		
2179	(883)	CHARACTER	8	INTEBDNM	
2179	(883)			INTECSN	
2190	(88E)	ADDRESS	2	INTECTBN	
2198	(896)	CHARACTER	9	INTECTNO	
2207	(89F)	CHARACTER	8	INTESTMT	
2215	(8A7)	CHARACTER	20		
2235	(8BB)	CHARACTER	8	INTENODE	
2243	(8C3)	CHARACTER	20		
2243	(8C3)			INTECBEN	
2264	(8D8)	ADDRESS	2	INTETCHR	
2281	(8E9)	CHARACTER	40		
2321	(911)	CHARACTER	10		
2321	(911)			INTETCEN	
2332	(91C)	ADDRESS	2	INTEIERR	
2366	(93E)	CHARACTER	9		
2375	(947)	CHARACTER	12	INTEIETB	
2407	(967)	CHARACTER	10	INTEIEAC	
2407	(967)			INTEIEZ	

2417	(971)	CHARACTER	10	INTEIEDS	
2427	(97B)	CHARACTER	10	INTEIEIN	
2440	(988)	FIXED	4		
2440	(988)	ADDRESS	2	INT3001B	
2477	(9AD)	CHARACTER	24		
2477	(9AD)			INT001BE	
2502	(9C6)	ADDRESS	2	INT3001C	
2536	(9E8)	CHARACTER	20		
2536	(9E8)			INT001CE	
2556	(9FC)	ADDRESS	2	INTEATCH	
2590	(A1E)	CHARACTER	15		
2590	(A1E)			INTEATCE	
2608	(A30)	FIXED	4	INTSAVE	INIT SAVE STARTING POINT

SPOOL ENTRIES					
INTXXXX BDTDSPL,PREFIX=INTXXX (SAMPLE ENTRY)					
2608	(A30)	FIXED	4		
2608	(A30)	ADDRESS	2	INTLCTID	INTERNAL TABLE ID
2610	(A32)	ADDRESS	2	INTLCTEL	ENTRY LENGTH
2612	(A34)	ADDRESS	4	INTLCTEA	ENTRY ADDRESS
2616	(A38)	ADDRESS	4	INTLCTSZ	TABLE SIZE
2620	(A3C)	BITSTRING	12	INTLCTDB	DDBRQ
2632	(A48)	ADDRESS	1		DDBFXENO
2633	(A49)	BITSTRING	3		DDBFXLEN
2636	(A4C)	BITSTRING	20		DDBEX
2656	(A60)	ADDRESS	2	INTMNID	INTERNAL TABLE ID
2658	(A62)	ADDRESS	2	INTMNEL	ENTRY LENGTH
2660	(A64)	ADDRESS	4	INTMNEA	ENTRY ADDRESS
2664	(A68)	ADDRESS	4	INTMNSZ	TABLE SIZE
2668	(A6C)	BITSTRING	12	INTMNDB	DDBRQ
2680	(A78)	ADDRESS	1		DDBFXENO
2681	(A79)	BITSTRING	3		DDBFXLEN
2684	(A7C)	BITSTRING	20		DDBEX
2704	(A90)	ADDRESS	2	INTBUFID	INTERNAL TABLE ID
2706	(A92)	ADDRESS	2	INTBUFEL	ENTRY LENGTH
2708	(A94)	ADDRESS	4	INTBUFEA	ENTRY ADDRESS
2712	(A98)	ADDRESS	4	INTBUFSZ	TABLE SIZE
2716	(A9C)	BITSTRING	12	INTBUFDB	DDBRQ
2728	(AA8)	ADDRESS	1		DDBFXENO
2729	(AA9)	BITSTRING	3		DDBFXLEN
2732	(AAC)	BITSTRING	20		DDBEX
2752	(AC0)	ADDRESS	2	INTCTBID	INTERNAL TABLE ID
2754	(AC2)	ADDRESS	2	INTCTBEL	ENTRY LENGTH
2756	(AC4)	ADDRESS	4	INTCTBEA	ENTRY ADDRESS
2760	(AC8)	ADDRESS	4	INTCTBSZ	TABLE SIZE
2764	(ACC)	BITSTRING	12	INTCTBDB	DDBRQ
2776	(AD8)	ADDRESS	1		DDBFXENO
2777	(AD9)	BITSTRING	3		DDBFXLEN
2780	(ADC)	BITSTRING	20		DDBEX
2800	(AF0)	ADDRESS	2	INTSRJID	INTERNAL TABLE ID
2802	(AF2)	ADDRESS	2	INTSRJEL	ENTRY LENGTH
2804	(AF4)	ADDRESS	4	INTSRJEA	ENTRY ADDRESS
2808	(AF8)	ADDRESS	4	INTSRJSZ	TABLE SIZE
2812	(AFC)	BITSTRING	12	INTSRJDB	DDBRQ
2824	(B08)	ADDRESS	1		DDBFXENO
2825	(B09)	BITSTRING	3		DDBFXLEN
2828	(B0C)	BITSTRING	20		DDBEX
2848	(B20)	ADDRESS	2	INTYYYYY	INTERNAL TABLE ID
2850	(B22)	ADDRESS	2	INTYYYEL	ENTRY LENGTH
2852	(B24)	ADDRESS	4	INTYYYEA	ENTRY ADDRESS
2856	(B28)	ADDRESS	4	INTYYYSZ	TABLE SIZE
2860	(B2C)	BITSTRING	12	INTYYYDB	DDBRQ
2872	(B38)	ADDRESS	1		DDBFXENO
2873	(B39)	BITSTRING	3		DDBFXLEN
2876	(B3C)	BITSTRING	24		DDBEX
2900	(B54)	ADDRESS	2	INTZZZZZ	INTERNAL TABLE ID
2902	(B56)	ADDRESS	2	INTZZZEL	ENTRY LENGTH
2904	(B58)	ADDRESS	4	INTZZZEA	ENTRY ADDRESS
2908	(B5C)	ADDRESS	4	INTZZZSZ	TABLE SIZE
2912	(B60)	BITSTRING	12	INTZZZDB	DDBRQ
2924	(B6C)	ADDRESS	1		DDBFXENO
2925	(B6D)	BITSTRING	3		DDBFXLEN
2928	(B70)	BITSTRING	24		DDBEX
2952	(B88)	FIXED	4	INTRSVD5	RESERVED
2960	(B90)	FIXED	4	INTRSVU2	RESERVED

2964	FLAG1	DEFINITION	1	INTFLG1	FLAG BYTE
	(B94)	BITSTRING			
	1...	....		INTFTERM	"BIT0" SET TO TERMINATE

		.1.. ....		INTPROB	AFTER INIT "BIT1" PROBABLE DAMAGE, SYSTEM TERMINAT
		..1. ....		INTWARN	"BIT2" WARNING MSG, SYSTEM TERMINATES
		...1 ....		INTIGCON	"BIT3" IGNORE NEXT STMT, LAST WAS CONTI
		.... 1...		INTPARM	"BIT4" PARAMETER ERROR IN MULTIPLE PARMS
		.... .1..		INTEBUFF	"BIT5" RESERVED
		.... ..1.		INTETRF	"BIT6" ERROR ON TRACK/FORMAT STMT
		.... ...1		INTBDTIO	"BIT7" JSAM INITIALIZED
2965	FLG2 DEFINITION (B95) BITSTRING	1		INTFLG2	FLAG BYTE
		1... ....		INTFORMT	"BIT0" FORMATTING OF QUEUES REQUIRED
		.1.. ....		INTHOME	"BIT1" BDTNODE/SYSID MATCH FOUND
		..1. ....		INTCPON	"BIT2" MAINPROC,CPUID=ONLY GIVEN
		...1 ....		INTJBLS	"BIT3" SOME JOBS LOST
		.... 1...		INTJSMI	"BIT4" SYMSG INTERCEPT FUNCTION WANTED
		.... .1..		INTPCRD	"BIT5" BDTIN IS NOT A CARD RDR AND BDTINRN SHOULD NOT PRINT STMTS PROCESSED BY BDTINGL
		.... ..1.		INTNJHO	"BIT6" NJENODE/SYSID MATCH FOUND
		.... ...1		INTFL2R1	"BIT7" RESERVED
2966	MNFLG DEFINITION (B96) BITSTRING	1		INTMNFLG	INITMAIN FLAGS
		1... ....		INTMNONE	"BIT0" BDTINM1 HAS BEEN USED
		.1.. ....		INTMDEF	"BIT1" GENERATE CLASS AND GROUP DEFAULT
		..1. ....		INTMNDCL	"BIT2" DEFAULT CLASS HAS BEEN DEFINED
		...1 ....		INTMNDGR	"BIT3" DEFAULT GROUP HAS BEEN DEFINED
		.... 1...		INTMNBGR	"BIT4" BATCH INITBDTOR DEFAULT GROUP USE
		.... .1..		INTMNAFL	"BIT5" JOB BATCH CLASS DEFINED
		.... ..1.		INTMNAGR	"BIT6" JOB BATCH GROUP DEFINED
		.... ...1		INTMNDL	"BIT7" DEFAULT SELECT MODE DEFINED
2967	SCFLG DEFINITION (B97) BITSTRING	1		INTSCFLG	SCAN PARAMETERS FLAGS
		1... ....		INTSCKWD	"BIT0" SCAN IS FOR KEYWORDS
		.1.. ....		INTSCKWF	"BIT1" KEYWORD FOUND IF ON
		..1. ....		INTSCLPA	"BIT2" LEFT PAREN FOUND
		...1 ....		INTSCDUP	"BIT3" SCAN FOR ) WHEN DUPLICATE PARM
		.... 1...		INTSCMLP	"BIT4" MULTIPLE PARAMETER FLAG
		.... .1..		INTSCBMK	"BIT5" BAD KEYWORD ON A MULTI KEYWORD
		.... ..1.		INTSCTRM	"BIT6" SET TO TERMINATE SCAN
		.... ...1		INTSCFG1	"BIT7" RESERVED
2968	SCFL1 DEFINITION (B98) BITSTRING	1		INTSCFL1	FLAG FOR SCAN ROUTINE IN INITRTNS
		1... ....		INTS1NOT	"BIT0" CHARACTER / USED TO SIGNIFY 'NOT'
		.1.. ....		INTSCFR1	"BIT1" RESERVED
		..1. ....		INTSCFR2	"BIT2" RESERVED

	...1	....		INTSCFR3	"BIT3" RESERVED
	....	1...		INTSCFR4	"BIT4" RESERVED
	....	.1..		INTSCFR5	"BIT5" RESERVED
	....	..1.		INTSCFR6	"BIT6" RESERVED
	....	...1		INTSCFR7	"BIT7" RESERVED
RESERVED FIELDS					
2969	(B99)	BITSTRING	1	INTRSVDB	RESERVED
2973	(B9D)	BITSTRING	1	INTRSVU7	RESERVED
SNA SCAN FLAG SETTINGS					
2975	(B9F)	BITSTRING	1	INTSCFL2	SNA BDT CONFIGURATION
		1... ..		INTS2CMD	"BIT0" SYSID STATEMENT FOUND
		.1.. ....		INTS2SNA	"BIT1" BDTNODE SPECIFIED
		..1. ....		INTS2CTB	"BIT2" COMPACTION SPECIFIED
		...1 ....		INTS2SYS	"BIT3" SYSID STMT PROCESSED
		.... 1...		INTS2NSN	"BIT4" NO SNA BDT SUPPORT
		.... .1..		INTS2PH2	"BIT5" PHASE 2 STARTED FLAG
		.... ..1.		INTS2CTD	"BIT6" DEFAULT CLASS CTAB SPECIFIED
		.... ...1		INTS2RS1	"BIT7" RESERVED
		.... ...1		SSNRECB	"X'01'" RECURSIVE ABEND CARD PROCESS
2976	(BA0)	BITSTRING	1	INTCNDFL	CONSOLE DEVICE FLAG
SUBPOOL INFORMATION					
2977	(BA1)	BITSTRING	1	INTSNASP	SNA BUF SUBPOOL SUBPOOL ID
		.... .1.1		INTSNAMX	"5" SNA BUF MAX SUBPOOL ID
		.... ...1		INTSNACB	"1" SNA CNTL BLOCKS SUBPOOL ID
2978	(BA2)	BITSTRING	1	INTRSVD7	RESERVED
2981	(BA5)	BITSTRING	1	INTRSVU3	RESERVED
REASON CODES					
		.... .1..		INTRC04	"4" REASON CODE 4
		.... 1...		INTRC08	"8" REASON CODE 8
		.... 11..		INTRC12	"12" REASON CODE 12
		...1 ....		INTRC16	"16" REASON CODE 16
		...1 .1..		INTRC20	"20" REASON CODE 20
		...1 1...		INTRC24	"24" REASON CODE 24
		...1 11..		INTRC28	"28" REASON CODE 28
		..1. ....		INTRC32	"32" REASON CODE 32
		..1. .1..		INTRC36	"36" REASON CODE 36
		..1. 1...		INTRC40	"40" REASON CODE 40
		..1. 11..		INTRC44	"44" REASON CODE 44
		..11 ....		INTRC48	"48" REASON CODE 48
WORK FIELDS AND DATA AREAS					
2984	(BA8)	FIXED	4	INTTRDDB	JBTAT DDB USED BY INITIALIZATION
2990	(BAE)	FIXED	2	INTNTBUF	NO. OF DDB BUFFERS
2992	(BB0)	FIXED	4	INTRSVD8	RESERVED
3004	(BBC)	FIXED	4	INTRSVU4	RESERVED
3008	(BC0)	ADDRESS	4	INTSTSR	PRT TO INTERNAL MAIN DEVICE TABL
3012	(BC4)	FIXED	2	INTSTCNT	NUMBER OF MAIN DEVICES
3014	(BC6)	FIXED	2	INTSTSIZ	LENGTH OF ENTRY (SET BY INITMDS)
3016	(BC8)	FIXED	2	INTSTKYN	ONE SORT KEY (TWO IF ADDR SORT=NO)
3018	(BCA)	FIXED	2	INTPKEY1	POSITION OF KEY 1
3020	(BCC)	FIXED	2	INTSTKYL	LENGTH OF KEY 1 (9 IF ADDR SORT=NO)
3022	(BCE)	FIXED	2	INTPKEY2	POSITION OF KEY 2
3024	(BD0)	FIXED	2	INTLKEY2	LENGTH OF KEY 2
3026	(BD2)	FIXED	2	INTBDCNT	BAD TRACK STMT COUNT
3032	(BD8)	FIXED	2	INTNOENT	NUMBER OF ENTRIES
3034	(BDA)	FIXED	2	INTLNENT	LENGTH OF ENTRY
3036	(BDC)	FIXED	2	INTNOKEY	NUMBER OF KEYS
3038	(BDE)	FIXED	2	INTPOKEY	POSITION OF KEY
3040	(BE0)	FIXED	2	INTLNKEY	LENGTH OF KEY
3044	(BE4)	FIXED	4	INTRSVDE	RESERVED



3056	(BF0)	FIXED	4	INTRSVUB	RESERVED
3060	(BF4)	FIXED	2	INTSTCNB	STANDARDS,CONSBUF=
3062	(BF6)	FIXED	2	INTBFSZC	BDT BUFR SIZE FROM BUFFER CD
3064	(BF8)	FIXED	2	INTBFPAG	BUFFER,PAGES=
3066	(BFA)	FIXED	2	INTNQMOD	NO. OF QUEUE MODULES
3068	(BFC)	FIXED	2	INTDLTCT	DLT ENTRY COUNT
3070	(BFE)	FIXED	2	INTDFDNO	DEFAULT NUMBER OF FD ENTRIES
3072	(C00)	FIXED	2	INTIOTLN	LENGTH OF BDTIO TABLE
3074	(C02)	FIXED	2	INTMNCNT	COUNT OF MAINPROC CONTROL
					STMTS
3076	(C04)	FIXED	2	INTMNJCN	NO OF BDT MAINS DEFINED
3078	(C06)	FIXED	2	INTMXVLP	MAX VLU PACING WINDOW
3080	(C08)	FIXED	2	INTMXSIO	MAX SNA I/O BUFFER SIZE
3082	(C0A)	FIXED	2	INTMNSIO	MIN SNA I/O BUFFER SIZE
3084	(C0C)	FIXED	2	INTMXSVL	MAX VLUS PER SESSION
3086	(C0E)	FIXED	2	INTMNVLP	MIN VLU PACING WINDOW
3088	(C10)	FIXED	2	INTMNVLS	MINIMUM VLUS PER SESSION
3090	(C12)	FIXED	2	INTNXSYS	DEVICE STMT INDEX

					NUMBER AND COUNTS
3092	(C14)	FIXED	2	INTLNCNT	NUMBER OF LINES
3094	(C16)	FIXED	2	INTNJPTN	NUMBER OF NJP TERMINALS
3096	(C18)	FIXED	2	INTNDTST	NUMBER OF READER INTERPRETER
					DSNAMES
3098	(C1A)	FIXED	2	INTPAFCT	COUNT OF PREALLOCATED FCT'S
3100	(C1C)	FIXED	2	INTPARQE	COUNT OF PREALLOCATED RQ'S
3102	(C1E)	FIXED	2	INTHWNMS	NUMBER OF HWSNAME ENTRIES
3104	(C20)	FIXED	2	INTPRNMS	NUMBER OF PROCEDURE NAMESS
					(R/I)
3106	(C22)	FIXED	2	INTPRCNT	NUMBER OF R/I PARM LISTS S

					COUNTS
3108	(C24)	FIXED	2	INTRJCNT	COUNT OF SNALINE STMTS FOUND
3110	(C26)	FIXED	2	INTBCCNT	COUNT OF BDTNODE STMTS FOUND
3112	(C28)	FIXED	2	INTSLCNT	COUNT OF SELECT CONTROL STMTS
3114	(C2A)	FIXED	2	INTSNCNT	COUNT OF SETNAMES STMTS NAMES
3116	(C2C)	FIXED	2	INTLRTDO	NO OF LINE RECORDS TO PROCESS
3118	(C2E)	FIXED	2	INTNRTDO	NO OF NODE RECORDS TO PROCESS
3120	(C30)	CHARACTER	8	INTACDEF	APPLID/COMMDEFN STMT
3128	(C38)	CHARACTER	8	INTPSCDC	PASSWD/COMMDEFN STMT
3136	(C40)	FIXED	4	INTMXNSE	MAX. NO. OF SESSIONS
3140	(C44)	FIXED	4	INTRSVDF	RESERVED
3156	(C54)	FIXED	4	INTRSVUA	RESERVED

					SNA BDT COUNTS
3164	(C5C)	FIXED	2	INTNOWST	NO. OF WORKSTATIONS
3166	(C5E)	FIXED	2	INTCNTDV	NO. OF DEVS PER WORKSTATION
3168	(C60)	FIXED	2	INTCNTCT	NO. OF CTAB'S SPECIFIED
3170	(C62)	FIXED	2	INTCNTCH	NO. OF CHARS SPECIFIED
3172	(C64)	FIXED	2	INTJCTSZ	JCT MAXIMUM SIZE
3174	(C66)	FIXED	2	INTRSVDP9	RESERVED
3184	(C70)	FIXED	2	INTRSVU5	RESERVED
3192	(C78)	FIXED	4	INTMNLS	CL8,A NAME,LCTUN LNG FOR
					GLBLS

					TABLE OF N= (NODE NAME) PARMS FROM BDTNODE STMTS
3288	(CD8)	FIXED	4	INTTNT1	FIRST ENTRY
3292	(CDC)	FIXED	4	INTTNT1C	CURRENT ENTRY
3296	(CE0)	FIXED	4	INTTNT1E	LAST NODE TABLE ENTRY

					TABLE OF NODE= (NODE NAME) PARMS FROM SNALINE STMTS
3300	(CE4)	FIXED	4	INTTNT2	FIRST ENTRY
3304	(CE8)	FIXED	4	INTTNT2C	CURRENT ENTRY
3308	(CEC)	FIXED	4	INTTNT2E	LAST NODE TABLE ENTRY
3312	(CF0)	ADDRESS	2	INTTNTLN	NODE TABLE ENTRY LENGTH
3314	(CF2)	ADDRESS	2	INTTNTL2	LINE TABLE ENTRY LENGTH
3316	(CF4)	ADDRESS	2	INTTNTL3	DELETE TABLE ENTRY LENGTH
3318	(CF6)	FIXED	2	INTTNTNM	NODE TABLE NUMBER OF ENTRIES

					TABLE OF N= (NODE NAME) PARMS FOR DELETE LIST
3320	(CF8)	FIXED	4	INTTNT3	FIRST ENTRY
3324	(CFC)	FIXED	4	INTTNT3C	CURRENT ENTRY
3328	(D00)	FIXED	4	INTTNT3E	LAST DELETE TABLE ENTRY

SP00L ENTRIES FOR BDTNODE AND SNALINE STMTS  
 3332 (D04) FIXED 4 ALIGN

INTRJLID BDTDSPL EXTENTS=30,PREFIX=INTRJT MAX 853 BDTNODE STMTS  
 3332 (D04) ADDRESS 2 INTRJTID INTERNAL TABLE ID  
 3334 (D06) ADDRESS 2 INTRJTEL ENTRY LENGTH  
 3336 (D08) ADDRESS 4 INTRJTEA ENTRY ADDRESS  
 3340 (D0C) ADDRESS 4 INTRJTSZ TABLE SIZE  
 3344 (D10) BITSTRING 12 INTRJTDB DDBRQ  
 3356 (D1C) ADDRESS 1 DDBFXENO  
 3357 (D1D) BITSTRING 3 DDBFXLEN  
 3360 (D20) BITSTRING 1 DDBEX

INTRJLID BDTDSPL EXTENTS=24,PREFIX=INTRJL MAX 877 SNALINE STMTS  
 3480 (D98) ADDRESS 2 INTRJLID INTERNAL TABLE ID  
 3482 (D9A) ADDRESS 2 INTRJLEL ENTRY LENGTH  
 3484 (D9C) ADDRESS 4 INTRJLEA ENTRY ADDRESS  
 3488 (DA0) ADDRESS 4 INTRJLSZ TABLE SIZE  
 3492 (DA4) BITSTRING 12 INTRJLDB DDBRQ  
 3504 (DB0) ADDRESS 1 DDBFXENO  
 3505 (DB1) BITSTRING 3 DDBFXLEN  
 3508 (DB4) BITSTRING 1 DDBEX

INTRJDID BDTDSPL EXTENTS=6,PREFIX=INTRJD MAX DELETE NAMES  
 3604 (E14) ADDRESS 2 INTRJDID INTERNAL TABLE ID  
 3606 (E16) ADDRESS 2 INTRJDEL ENTRY LENGTH  
 3608 (E18) ADDRESS 4 INTRJDEA ENTRY ADDRESS  
 3612 (E1C) ADDRESS 4 INTRJDSZ TABLE SIZE  
 3616 (E20) BITSTRING 12 INTRJDDB DDBRQ  
 3628 (E2C) ADDRESS 1 DDBFXENO  
 3629 (E2D) BITSTRING 3 DDBFXLEN  
 3632 (E30) BITSTRING 24 DDBEX  
 3656 (E48) 8 INTDTEND PAD TO DOUBLE WORD

DCB'S  
 DCB DDNAME=BDTIN,DSORG=PS,MACRF=(GM),RECFM=FB,  
 BUFNO=2,LRECL=80  
 DATA CONTROL BLOCK  
 3656 (E48) FIXED 4 INTBDTIN ORIGIN ON WORD BOUNDARY  
 DIRECT ACCESS DEVICE  
 INTERFACE  
 3656 (E48) BITSTRING 16 FADAD,DVTBL  
 3672 (E58) ADDRESS 4 KEYLE,DEV,TRBAL COMMON ACCESS  
 METHOD INTERFACE  
 3676 (E5C) ADDRESS 1 BUFNO  
 3677 (E5D) ADDRESS 3 BUFCB  
 3680 (E60) ADDRESS 2 BUFL  
 3682 (E62) BITSTRING 2 DSORG  
 3684 (E64) ADDRESS 4 IOBAD FOUNDATION EXTENSION  
 3688 (E68) BITSTRING 1 BFTEK,BFLN,HIARCHY  
 3689 (E69) ADDRESS 3 EODAD  
 3692 (E6C) BITSTRING 1 RECFM  
 3693 (E6D) ADDRESS 3 EXLST FOUNDATION BLOCK  
 3696 (E70) CHARACTER 8 DDNAME  
 3704 (E78) BITSTRING 1 OFLGS  
 3705 (E79) BITSTRING 1 IFLG  
 3706 (E7A) BITSTRING 2 MACR BSAM BPAM QSAM INTERFACE  
 3708 (E7C) BITSTRING 1 RER1  
 3709 (E7D) ADDRESS 3 CHECK, GERR, PERR  
 3712 (E80) ADDRESS 4 SYNAD  
 3716 (E84) FIXED 2 CIND1, CIND2  
 3718 (E86) ADDRESS 2 BLKSIZE  
 3720 (E88) FIXED 4 WCPO, WCPL, OFFSR, OFFSW  
 3724 (E8C) ADDRESS 4 IOBA  
 3728 (E90) ADDRESS 1 NCP  
 3729 (E91) ADDRESS 3 EOBR, EOBAQ QSAM INTERFACE  
 3732 (E94) ADDRESS 4 RECAD  
 3736 (E98) FIXED 2 QSWs  
 3738 (E9A) ADDRESS 2 LRECL  
 3740 (E9C) BITSTRING 1 EROPT  
 3741 (E9D) ADDRESS 3 CNTRL  
 3744 (EA0) FIXED 4 PRECL  
 3748 (EA4) ADDRESS 4 EOB

DCB DDNAME=BDTOUT,DEV=DA,DSORG=PS,MACRF=(W),RECFM=VBA,  
 LRECL=125,BLKSIZE=129,SYNAD=INTBR14

DATA CONTROL BLOCK					
3752	(EA8)	FIXED	4	INTDCBPR	ORIGIN ON WORD BOUNDARY DIRECT ACCESS DEVICE INTERFACE
3752	(EA8)	BITSTRING	16		FDAD,DVTBL
3768	(EB8)	ADDRESS	4		KEYLE,DEVT,TRBAL COMMON ACCESS METHOD INTERFACE
3772	(EBC)	ADDRESS	1		BUFNO
3773	(EBD)	ADDRESS	3		BUFCB
3776	(EC0)	ADDRESS	2		BUFL
3778	(EC2)	BITSTRING	2		DSORG
3780	(EC4)	ADDRESS	4		IOBAD FOUNDATION EXTENSION
3784	(EC8)	BITSTRING	1		BFTEK,BFLN,HIARCHY
3785	(EC9)	ADDRESS	3		EODAD
3788	(ECC)	BITSTRING	1		RECFM
3789	(ECD)	ADDRESS	3		EXLST FOUNDATION BLOCK
3792	(ED0)	CHARACTER	8		DDNAME
3800	(ED8)	BITSTRING	1		OFLGS
3801	(ED9)	BITSTRING	1		IFLG
3802	(EDA)	BITSTRING	2		MACR BSAM BPAM QSAM INTERFACE
3804	(EDC)	BITSTRING	1		RER1
3805	(EDD)	ADDRESS	3		CHECK, GERR, PERR
3808	(EE0)	ADDRESS	4		SYNAD
3812	(EE4)	FIXED	2		CIND1, CIND2
3814	(EE6)	ADDRESS	2		BLKSIZE
3816	(EE8)	FIXED	4		WCPO, WCPL, OFFSR, OFFSW
3820	(EEC)	ADDRESS	4		IOBA
3824	(EF0)	ADDRESS	1		NCP
3825	(EF1)	ADDRESS	3		EOBR, EOBA BSAM BPAM INTERFACE
3828	(EF4)	ADDRESS	4		EOBW
3832	(EF8)	FIXED	2		DIRECT
3834	(EFA)	ADDRESS	2		LRECL
3836	(EFC)	ADDRESS	4		CNTRL, NOTE, POINT

GLOBALS LIST FORMAT - FOR LCTUNITS BUILD					
0	(0)	CHARACTER	8	INTGBNM	NAME OF MAIN PROCESSOR
8	(8)	FIXED	4	INTGBSZ	LCTUNITS SIZE FOR THIS CPU
		.... 1...		INTGBFLG	"INTGBSZ,1,C'X'" FLAGS
		1.... ....		INTGBTAG	"BIT0" MULTI USE FLAG
12	(C)	FIXED	4	INTGRVDA	RESERVED
24	(18)	FIXED	4	INTGRVU6	RESERVED
28	(1C)	BITSTRING	1	INTGBEND	END OF DESCRIBED AREA

DSECTS FOR NODE TABLE ENTRIES AND LINE TABLE ENTRIES AND FOR DELETE TABLE ENTRIES					
0	(0)	CHARACTER	8	INNODNAM	NODE NAME
8	(8)	BITSTRING	1	INNODFLG	NODE ENTRY FLAG
		.... 1..1		INNODEND	"*" END OF NODE TABLE ENTRY
		.... ...1		INNODNJE	"1" CONSTANT TO INDICATE NJE NODE
0	(0)	CHARACTER	8	INLINNAM	LINE ENTRY NAME
8	(8)	BITSTRING	1	INLINFLG	LINE ENTRY FLAG
		.... 1..1		INLINEND	"*" END OF LINE TABLE ENTRY
		.... ...1		INMATCH	"1" CONSTANT TO INDICATE MATCH
		.... 1...		INLINNDC	"8" CONSTANT TO INDICATE LN FM NODE
0	(0)	CHARACTER	8	INDELNAM	NODE NAME TO DELETE
		.... 1...		INDELEND	"*" END OF DELETE TABLE ENTRY

CROSS REFERENCE				
NAME	HEX OFFSET	HEX VALUE	LEVEL	
IGL53E	3AE	3B6	2	
INDELEND	0	8	2	
INDELNAM	0		2	
INGL3042	3B6	3D	2	
INGL3048	3F4	35	2	
INGL3053	38A	2C	2	

INGL42E	3D7	3F3	2
INGL48E	405	429	2
INGL53NM	3AE	4040	2
INLINEND	8	9	2
INLINFLG	8		2
INLINNAM	0		2
INLINNDC	8	8	2
INMATCH	8	1	2
INNODEND	8	9	2
INNODFLG	8		2
INNODNAM	0		2
INNODNJE	8	1	2
INTACDEF	C30	C2C4	2
INTACDRD	80		2
INTBAS3	74		2
INTBCCNT	C26	0	2
INTBDCNT	BD2	0	2
INTBDTIN	E48		2
INTBDTIO	B94	1	2
INTBFPAAG	BF8	40	2
INTBFSZC	BF6	4E0	2
INTBSES	6C		2
INTBTBLA	BD4		2
INTBUFDB	A9C	0	2
INTBUFEA	A94		2
INTBUFEL	A92		2
INTBUFID	A90		2
INTBUFSZ	A98		2
INTCKARE	88		2
INTCNANS	0	4	2
INTCNBIN	18C		2
INTCNDFL	BA0	0	2
INTCNTCH	C62	0	2
INTCNTCT	C60	0	2
INTCNTDV	C5E	0	2
INTCPON	B95	20	2
INTCTADR	9C		2
INTCTBDB	ACC	0	2
INTCTBEA	AC4		2
INTCTBEL	AC2		2
INTCTBID	AC0		2
INTCTBSZ	AC8		2
INTDCBPR	EA8		2
INTDFDNO	BFE	80	2
INTDLTCT	BFC	0	2
INTDTEND	E48		2
INTEATCE	A1E	A2D	2
INTEATCH	9FC	31	2
INTEBDCE	4D0	2A	2
INTEBDKW	4DD	4FA	2
INTEBDNM	4EE	4040	2
INTEBDPA	883	4040	2
INTEBDSA	566	4040	2
INTEBDSN	566	570	2
INTEBKW	1D0		2
INTEBLKE	36E	38A	2
INTEBLKL	36E	1C	2
INTEBUFF	B94	4	2
INTECARD	494	3C	2
INTECBEN	8C3	8D7	2
INTECCEN	833	848	2
INTECCNP	812	36	2
INTECEND	4AE	4D0	2
INTECEN1	46D	494	2
INTECHSP	848	45	2
INTECMDF	776	34	2
INTECMEN	787	7AA	2
INTECOEN	683	6A2	2
INTECOMB	45C	38	2
INTECOTC	672	30	2
INTECSEN	883	88D	2
INTECSOP	4AE	4040	2
INTECSPR	4A5	4040	2
INTECST	82C	4040	2
INTECTBN	88E	49	2
INTECTNO	896	4040	2
INTEDST	7F7	4040	2
INTEDTCT	7DC	36	2
INTEDTEN	7FE	812	2
INTEIBEN	6E9	70E	2
INTEIBLK	6D8	36	2
INTEICEN	751	776	2

INTEICHR	740	36	2
INTEIEAC	967	4040	2
INTEIEDS	971	C4C9	2
INTEIEIN	97B	C9D5	2
INTEIERR	91C	55	2
INTEIETB	947	4040	2
INTEIEZ	967	971	2
INTEIKEN	6C0	6D8	2
INTEIKYW	6C0	4040	2
INTEILDP	450	4040	2
INTEILKY	6A2	36	2
INTEMCEN	726	740	2
INTEMPEN	5E7	5F3	2
INTEMPRM	5E7	4040	2
INTEMPR1	5B6	3D	2
INTEMPR2	5C7	D9C9	2
INTEMSCM	70E	32	2
INTEMSC2	71F	C9D3	2
INTENNM	7BE	4040	2
INTENODE	8BB	4040	2
INTENSEN	7C6	7DC	2
INTENSNA	7AA	32	2
INTEOEND	514	530	2
INTEOKEY	514	4040	2
INTEORKY	4FA	36	2
INTEPDEN	450	45C	2
INTEPRND	42A	32	2
INTEREKW	617	4040	2
INTEREQK	65D	4040	2
INTEREQP	5F4	37	2
INTERKEN	65D	672	2
INTERPEN	624	62B	2
INTERPKY	62C	46	2
INTERTN	84		2
INTESOPR	530	40	2
INTESOP1	54A	4040	2
INTESOP2	555	5D40	2
INTESTMT	89F	4040	2
INTETBEN	582	5B6	2
INTETBIG	570	46	2
INTETBPR	582	4040	2
INTETCEN	911	91B	2
INTETCHR	8D8	43	2
INTETRKF	B94	2	2
INTFLG1	B94	0	2
INTFLG2	B95	0	2
INTFL2R1	B95	1	2
INTFORMT	B95	80	2
INTFTERM	B94	80	2
INTGBEND	1C		2
INTGBFLG	8	8	2
INTGBNM	0		2
INTGBSZ	8		2
INTGBTAG	8	80	2
INTGLBNM	54	4040	2
INTGRVDA	C	0	2
INTGRVU6	18	0	2
INTHDR	48	C9D5	2
INTHOME	B95	40	2
INTHWNMS	C1E	0	2
INTICRD	184		2
INTICRD2	188		2
INTIEOF2	1AC		2
INTIGCON	B94	10	2
INTIIADR	90		2
INTINARE	118	4040	2
INTINA72	118	15F	2
INTINECB	8C		2
INTINEND	17C	184	2
INTINPTR	E4		2
INTINRN	1B4		2
INTINR2	A0		2
INTIOPRM	AC		2
INTIOTLN	C00	0	2
INTISCN1	198		2
INTISCN2	19C		2
INTITRD	1A0		2
INTITWRT	1A4		2
INTIWOUT	1A8		2
INTJBL5	B95	10	2
INTJCTSZ	C64	0	2
INTJSMI	B95	8	2

INTLCTDB	A3C	0	2
INTLCTEA	A34		2
INTLCTEL	A32		2
INTLCTID	A30		2
INTLCTSZ	A38		2
INTLKEY2	BD0	2	2
INTLNCNT	C14	0	2
INTLNENT	BDA	C	2
INTLNTH	50	E48	2
INTLNKEY	BE0	C	2
INTLOPER	EA	0	2
INTLRTDO	C2C	0	2
INTMAXQS	D6	1F	2
INTMDADR	94		2
INTMNAEL	B96	4	2
INTMNAGR	B96	2	2
INTMNBGR	B96	8	2
INTMNCNT	C02	0	2
INTMNDB	A6C	0	2
INTMNDCL	B96	20	2
INTMNDEF	B96	40	2
INTMNDGR	B96	10	2
INTMNDSL	B96	1	2
INTMNEA	A64		2
INTMNEL	A62		2
INTMNFLG	B96	0	2
INTMNID	A60		2
INTMNJCN	C04	0	2
INTMNJMX	52	8	2
INTMNLS	C78	0	2
INTMNNAM	64	4040	2
INTMNONE	B96	80	2
INTMNSIO	C0A	12C	2
INTMNSZ	A68		2
INTMNVLP	C0E	1	2
INTMNVLS	C10	1	2
INTMWLE	194		2
INTMXBTS	D4	154	2
INTMXNSE	C40	0	2
INTMXSIO	C08	1000	2
INTMXSVL	C0C	FF	2
INTMXVLP	C06	FF	2
INTNBDTK	B0		2
INTNDTST	C18	0	2
INTNJHO	B95	2	2
INTNJPTN	C16	0	2
INTNOENT	BD8	0	2
INTNOGMN	1B0		2
INTNOKEY	BDC	1	2
INTNOWST	C5C	0	2
INTNQMOD	BFA	0	2
INTNRTDO	C2E	0	2
INTNTBUF	BAE	0	2
INTNXSYS	C12	1	2
INTOBSA	8	0	2
INTOGLBL	5C	4040	2
INTPAFCT	C1A	0	2
INTPAREN	E8	0	2
INTPARM	B94	8	2
INTPARQE	C1C	0	2
INTPCRD	B95	4	2
INTPKADR	98		2
INTPKARA	0	0	2
INTPKEY1	BCA	1	2
INTPKEY2	BCE	D	2
INTPOKEY	BDE	1	2
INTPRCNT	C22	0	2
INTPRNMS	C20	0	2
INTPROB	B94	40	2
INTPSCDC	C38	4040	2
INTRC04	BA5	4	2
INTRC08	BA5	8	2
INTRC12	BA5	C	2
INTRC16	BA5	10	2
INTRC20	BA5	14	2
INTRC24	BA5	18	2
INTRC28	BA5	1C	2
INTRC32	BA5	20	2
INTRC36	BA5	24	2
INTRC40	BA5	28	2
INTRC44	BA5	2C	2
INTRC48	BA5	30	2

INTREL	4C	F2F0	2
INTRJCNT	C24	0	2
INTRJDDB	E20	0	2
INTRJDEA	E18		2
INTRJDEL	E16		2
INTRJDID	E14		2
INTRJDSZ	E1C		2
INTRJLDB	DA4	0	2
INTRJLEA	D9C		2
INTRJLEL	D9A		2
INTRJLID	D98		2
INTRJLSZ	DA0		2
INTRJTDB	D10	0	2
INTRJTEA	D08		2
INTRJTEL	D06		2
INTRJTID	D04		2
INTRJTSZ	D0C		2
INTRSVDB	B99	0	2
INTRSVDC	1C0		2
INTRSVDD	168	0	2
INTRSVDE	BE4	0	2
INTRSVDF	C44	0	2
INTRSDVZ	52	0	2
INTRSDV2	A8		2
INTRSDV3	BC	0	2
INTRSDV4	190		2
INTRSDV5	B88	0	2
INTRSDV7	BA2	0	2
INTRSDV8	BB0	0	2
INTRSDV9	C66	0	2
INTRSVUA	C54	0	2
INTRSVUB	BF0	0	2
INTRSVU1	CC	0	2
INTRSVU2	B90	0	2
INTRSVU3	BA5	0	2
INTRSVU4	BBC	0	2
INTRSVU5	C70	0	2
INTRSVU7	B9D	0	2
INTRSVU8	1CC		2
INTRSVU9	17C	0	2
INTRTN	78		2
INTSAVE	A30		2
INTSCBMK	B97	4	2
INTSCDUP	B97	10	2
INTSCFG1	B97	1	2
INTSCFLG	B97	0	2
INTSCFL1	B98	0	2
INTSCFL2	B9F	0	2
INTSCFR1	B98	40	2
INTSCFR2	B98	20	2
INTSCFR3	B98	10	2
INTSCFR4	B98	8	2
INTSCFR5	B98	4	2
INTSCFR6	B98	2	2
INTSCFR7	B98	1	2
INTSCKWD	B97	80	2
INTSCKWF	B97	40	2
INTSCLPA	B97	20	2
INTSCMLP	B97	8	2
INTSCTRM	B97	2	2
INTSLCNT	C28	0	2
INTSNACB	BA1	1	2
INTSNAMX	BA1	5	2
INTSNASP	BA1	2	2
INTSNCNT	C2A	0	2
INTSOPER	FC	4040	2
INTSPARM	EC	4040	2
INTSRJDB	AFC	0	2
INTSRJEA	AF4		2
INTSRJEL	AF2		2
INTSRJID	AF0		2
INTSRJSZ	AF8		2
INTSTCNB	BF4	32	2
INTSTCNT	BC4	0	2
INTSTCTB	D8	4040	2
INTSTKYL	BCC	C	2
INTSTKYN	BC8	1	2
INTSTPTR	E0		2
INTSTSIZ	BC6	0	2
INTSTSRT	BC0		2
INTSVBS	7C		2
INTS1NOT	B98	80	2

INTS2CMD	B9F	80	2
INTS2CTB	B9F	20	2
INTS2CTD	B9F	2	2
INTS2NSN	B9F	8	2
INTS2PH2	B9F	4	2
INTS2RS1	B9F	1	2
INTS2SNA	B9F	40	2
INTS2SYS	B9F	10	2
INTTBUF	B4		2
INTTEXT	10C	78	2
INTTNTLN	CF0	9	2
INTTNTL2	CF2	9	2
INTTNTL3	CF4	8	2
INTTNTNM	CF6	64	2
INTTNT1	CD8	0	2
INTTNT1C	CDC	0	2
INTTNT1E	CE0	0	2
INTTNT2	CE4	0	2
INTTNT2C	CE8	0	2
INTTNT2E	CEC	0	2
INTTNT3	CF8	0	2
INTTNT3C	CFC	0	2
INTTNT3E	D00	0	2
INTTRDDB	BA8	0	2
INTUXECB	A4		2
INTUXLAD	B8		2
INTWARN	B94	20	2
INTYYYDB	B2C	0	2
INTYYYEA	B24		2
INTYYYEL	B22		2
INTYYYSZ	B28		2
INTYYYYY	B20		2
INTZZZDB	B60	0	2
INTZZZEA	B58		2
INTZZZEL	B56		2
INTZZZSZ	B5C		2
INTZZZZZ	B54		2
INT001BE	9AD	9C5	2
INT001CE	9E8	9FC	2
INT3001B	988	3D	2
INT3001C	9C6	36	2
MSGCD9I	35C	40C2	2
MSGR17I	365	40C2	2
SCNRECAB	B9F	1	2



## Chapter 6. Job Control Table – JCT

The job control table (JCT) contains job information, including job name, status, priority, and point of origin. A JCT entry is built at the global node for each file-to-file transaction submitted, and at the submitting node for each network job entry transaction submitted. The transaction driver BDTGRXD creates the entry after the transaction is submitted, using information in the BSID and the MJD.

Each JCT entry is followed by a single scheduler element (SE), which contains “from” and “to” information.

<b>Function:</b>	The JCT is used by all functions that need information about the job as it is processed.
<b>Macro ID:</b>	BDTDJCT
<b>DSECT name:</b>	JCTSTART
<b>Created by:</b>	BDTGRXD, when the job is scheduled
<b>Size of fixed area:</b>	Hex B8 bytes without scheduler element, hex 100 with scheduler element
<b>Accessed by:</b>	The JCT access method, in BDTGRJX, which is pointed to by TVTXJCT
<b>Location:</b>	BDTGRXD originally builds the JCT in cell pool JCTB and copies it on the BDT work queue.

OFFSETS		TYPE	LENGTH	NAME	DESCRIPTION
JOB CONTROL TABLE ENTRY MAPPING MACRO					
JCT HEADER DEFINITION					
0	(0)	CHARACTER	4	JCTID	JCT ID
4	(4)	CHARACTER	4	JCTVERS#	JCT VERSION ID
8	(8)	FIXED	2	JCTTOTL	LENGTH OF ENTIRE JCT W/ALL SE'S
10	(A)	FIXED	2	JCTFIXL	LENGTH OF FIXED PORTION
12	(C)	FIXED	2	JCTVARL	LENGTH OF EACH SE
JOB INFORMATION					
14	(E)	FIXED	2	JCTJOB	JOB NUMBER (BINARY)
16	(10)	CHARACTER	8	JCTJBNAM	JOB NAME
24	(18)	FIXED	4	JCTQDATE	DATE JOB ENTERED SYSTEM
28	(1C)	FIXED	2	JCTTQUID	
TQI UNIQUE IDENTIFIER MAPPING MACRO					
28	(1C)	FIXED	4	JCTUTI	
28	(1C)	BITSTRING	1	JCTRECS	NUMBER OF RECORDS REQUIRED
		1... ..		JCTREXMT	"BIT0" RETRANSMISSION FLAG
		1... ..		JCTPNDFG	"BIT0" TQI PENDING FLAG
29	(1D)	CHARACTER	3	JCTCPUID	CPU ID CHARACTERS
32	(20)	FIXED	4	JCTRNWD	ALIGNMENT
32	(20)	FIXED	2	JCTRUD1	RESERVED FOR DEVELOPMENT
34	(22)	FIXED	2	JCTRNUM	RELATIVE RECORD NUMBER
36	(24)	CHARACTER	8	JCTDTTM	DATE TIME STAMP
44	(2C)	CHARACTER	8	JCTXMTTM	TIME OF SUBMISSION
52	(34)	FIXED	4	JCTEND	END OF UTI
		...1 1...		JCTSIZE	LENGTH OF UTI
		...1 11..		JCTENTRY	UTI EQUATE
52	(34)	CHARACTER	4	JCTXHDR	CONTROL BLOCK ACRONYM
56	(38)	CHARACTER	4	JCTXREL	VERSION ID
60	(3C)	ADDRESS	2	JCTXLEN	XOID LENGTH
62	(3E)	BITSTRING	8	JCTXBSI	XACTION ORIGIN BDT SYS ID
70	(46)	BITSTRING	8	JCTXBSN	XACTION ORIGIN BDT SYS NAME

78	TRANSACTION ORIGIN TYPE (4E) BITSTRING 1	JCTXTYP	XACTION ORIGIN TYPE
	.... ...1	JCTTSO	"1" TSO USER
	.... ..1.	JCTJES	"2" JES CONSOLE
	.... ...11	JCTBTCH	"3" BATCH JOB
	.... .1..	JCTMCS	"4" MCS CONSOLE
	.... .1.1	JCTLOG	"5" JOB MESSAGE LOG
	.... .11.	JCTFCT	"6" BDT FCT
	.... .111	JCTJMC	"7" JES MESSAGE CLASS
	.... 1...	JCTRDEV	"8" BEGIN DEVELOPMENT
	1... ....	JCTUSER	DEFINED XOIDXTYP "128" BEGIN USER DEFINED XOIDXTYP
79	FLAG 1 DEFINITION (4F) BITSTRING 1	JCTXFL1	XOID FLAG 1
	1... ....	JCTXMCL	"BIT0" SUPPRESSION OF MESSAGE CLASS
	.1.. ....	JCTX1R1	"BIT1" RESERVED
	..1. ....	JCTX1R2	"BIT2" RESERVED
	...1 ....	JCTX1R3	"BIT3" RESERVED
	.... 1...	JCTX1R4	"BIT4" RESERVED
	.... .1..	JCTX1R5	"BIT5" RESERVED
	.... ..1.	JCTX1R6	"BIT6" RESERVED
	.... ...1	JCTX1R7	"BIT7" RESERVED
80	MISCELLANEOUS INFORMATION (50) CHARACTER 8	JCTXDDN	TRANSACTION ORIGIN DDNAME
80	(50) CHARACTER 8	JCTUSID	TSO USERID
80	(50) CHARACTER 8	JCTCND	JES CONSOLE DDNAME
80	(50) CHARACTER 8	JCTJCLS	JES MESSAGE CLASS
80	(50) CHARACTER 8	JCTBJNM	BATCH JOB NAME
80	(50) ADDRESS 1	JCTMCSI	MCS CONSOLE ID
80	(50) BITSTRING 2	JCTBJNO	BDT JOB NUMBER
80	(50) BITSTRING 8	JCTDDRS	DDNAME
88	RESERVED FIELDS (58) BITSTRING 4	JCTXRD2	RESERVED
92	(5C) BITSTRING 4	JCTXRD3	RESERVED
96	(60) BITSTRING 4	JCTXRS1	RESERVED
100	(64) BITSTRING 4	JCTXRS2	RESERVED
104	(68) BITSTRING 4	JCTXRU1	RESERVED
108	(6C) BITSTRING 4	JCTXRU2	RESERVED
	.1.1 ...1	JCTMCSA	MCS CONSOLE UX28 AUTH
	.111 ....	JCTXEND	END OF XOID
	..11 .1..	JCTXOID	XOID EQUATE
	..11 111.	JCTXALL	BSI EQUATE
112	(70) BITSTRING 1	JCTNOSES	NUMBER OF SCHEDULER ELEMENTS
113	(71) BITSTRING 1	JCTPRTY	JOB PRIORITY
114	DEFINITION OF JCTFL1 (72) BITSTRING 1	JCTFL1	FLAG BYTE
	1... ....	JCTOPHLD	"BIT0" OPERATOR HOLD
	.1.. ....	JCTCALL	"BIT1" JOB IS CALLED DAP
	..1. ....	JCTNCHNG	"BIT2" JCT NOT CHANGED
	...1 ....	JCTNTHLD	"BIT3" NET HOLD
	.... 1...	JCTPURG	"BIT4" PURGE COMPLETE
	.... .1..	JCTRESCH	"BIT5" RESCHEDULE
	.... ..1.	JCTCANCL	"BIT6" JSS TO CANCEL
	.... ...1	JCTDUMP	"BIT7" JSS TO CANCEL W/DUMP
115	DEFINITION OF JCTFL2 (73) BITSTRING 1	JCTFL2	FLAG BYTE
	1... ....	JCTTAAD	"BIT0" JCT ADD
	.1.. ....	JCTSTCHG	"BIT1" THIS JCT HAS STATUS CHANGE
	..1. ....	JCTDSENQ	"BIT2" JOB HELD DUE TO DS ENQUEUE
	...1 ....	JCTFREEZ	"BIT3" JCT FROZEN
	.... 1...	JCTDEL	"BIT4" JCT DEL

		.... .1..		JCTOPCAN	"BIT5" OPERATOR CANCEL
		.... ..1.		JCTFL2R2	"BIT6" RESERVED
		.... ...1		JCTNDSNQ	"BIT7" NO BDT DSN ENQUEUE
116	DEFINITION OF JCTFL3 (74)	BITSTRING 1		JCTFL3	FLAG BYTE
		1... ....		JCTNETRL	"BIT0" NET RELEASE PROC'ING COMP
		.1.. ....		JCTNETFL	"BIT1" NET FLUSHED
		..1. ....		JCTNJE	"BIT2" NJE TRANSACTION
		...1 ....		JCTNJOB	"BIT3" NJE JOB TRANSACTION
		.... 1...		JCTNSSOT	"BIT4" NJE SYSOUT TRANSACTION
		.... .1..		JCTFL3R4	"BIT5" RESERVED
		.... ..1.		JCTFL3R5	"BIT6" RESERVED
		.... ...1		JCTFL3R6	"BIT7" RESERVED
117	(75)	BITSTRING 1		JCTRSS1	RESERVED
120	(78)	FIXED 4		JCTWCT	WRITE ITERATION COUNT
124	(7C)	FIXED 4		JCTTOD	TOD JCT ADDED TO THIS PRY
128	(80)	CHARACTER 8		JCTNETID	NET ID
136	(88)	FIXED 2		JCTNETHC	NET HOLD COUNT
138	(8A)	FIXED 2		JCTMJDLN	LENGTH OF THE MJD (FIXED+VARIABLE)
140	(8C)	BITSTRING 1		JCTSIDDB	CMA/MJD DDB (MAX 2 EXTENTS)
		1... 11..		JCTCMDDB	"JCTSIDDB" CONSOLE MESSAGE AREA DDB
		1... 11..		JCTMJDDB	"JCTSIDDB" MASTER JOB DEFINITION DDB
152	(98)	ADDRESS 4		JCTJML	ADDRESS OF JOB MSG LOG CONTROL BLOCK
156	(9C)	BITSTRING 1		JCTJMLMD	JOB MESSAGE LOG MASTER DDB
28	JES3 INFORMATION (1C)	CHARACTER 24		JCTJSINF	JES3 JOB NUMBER, GROUP ID AND NJE TIME STAMP
28	(1C)	CHARACTER 8		JCTJESNR	JES3 JOB ID
36	(24)	CHARACTER 8		JCTGRPID	JES3 GROUP ID
44	(2C)	CHARACTER 8		JCTDATI	JES3 NJE TIME STAMP
164	(A4)	CHARACTER 8		JCTRSV1	RESERVED
172	(AC)	CHARACTER 8		JCTRSV2	RESERVED
180	(B4)	FIXED 4		JCTRSV3	RESERVED
184	(B8)	FIXED 4		JCTFEND	END OF FIXED AREA
184	(B8)	BITSTRING 1		JCTFSIZE	SIZE OF FIXED AREA = L'JCTFSIZE
16	ACCOUNTING INFORMATION (10)	FIXED 4		JCTLOCPU	LOCAL CPU TIME
20	(14)	FIXED 4		JCTLOCPF	LOCAL CPU FACTOR
24	(18)	BITSTRING 4		JCTLOCID	LOCAL CPU ID
0	FORMAT OF EACH JCT SCHEDULER ELEMENT DEFINITION OF SEFLAGS (0)	BITSTRING 1		SEFLAGS	FLAG BYTE 1
		1... ....		SECOMP	"BIT0" SE COMPLETE
		1... ....		SEGBLCMP	"BIT0" SE GLOBL FUNCTION COMPLETE
		.1.. ....		SEACTIVE	"BIT1" SE ACTIVE
		.1.. ....		SEGBLACT	"BIT1" SE GLOBL FUNCTION ACTIVE
		..1. ....		SEGBLTO	"BIT2" SE GLOBL SCHEDULE 'TO' SIDE
		...1 ....		SEGBLFR	"BIT3" SE GLOBL SCHED 'FROM' ALSO
		.... 1...		SELCLACT	"BIT4" SE LOCAL FUNCTION ACTIVE
		.... .1..		SELCLCMP	"BIT5" SE LOCAL FUNCTION COMPLETE
		.... ..1.		SELCLTO	"BIT6" SE LOCAL SCHEDULE 'TO' SIDE
		.... ...1		SELCLRQ	"BIT7" SE LOCAL SCHED REQUEST SENT

DEFINITION OF SEFLAG2					
1	(1)	BITSTRING	1	SEFLAG2	FLAG BYTE 2
		1... ..		SESECAN	"BIT0" DAP NOTIFIED TO CANCEL SESSION
		.1.. ....		SEFL2R1	"BIT1" RESERVED
		..1. ....		SEFL2R2	"BIT2" RESERVED
		...1 ....		SEFL2R3	"BIT3" RESERVED
		.... 1...		SEFL2R4	"BIT4" RESERVED
		.... .1..		SEFL2R5	"BIT5" RESERVED
		.... ..1.		SEFL2R6	"BIT6" RESERVED
		.... ...1		SEFL2R7	"BIT7" RESERVED
DEFINITION OF SEFLAG3					
2	(2)	BITSTRING	1	SEFLAG3	RESERVED
3	(3)	BITSTRING	1	SESEQNO	SE SEQUENCE NUMBER
4	(4)	CHARACTER	8	SEDAP	DAP NAME (CALLED DAP)
4	(4)	CHARACTER	8	SEFRDAP	FROM DAP NAME
12	(C)	CHARACTER	8	SETODAP	TO DAP NAME
20	(14)	CHARACTER	8	SEFRLOC	FROM LOCATION NAME
28	(1C)	CHARACTER	8	SETOLOC	TO LOCATION NAME
36	(24)	FIXED	2	SEFRCPD	MJD DISP OF CKPT AREA SOURCE
38	(26)	FIXED	2	SEFRCPD	LEN OF CKPT AREA SOURCE
40	(28)	FIXED	2	SETOCPD	MJD DISP OF CKPT AREA DESTINATION
42	(2A)	FIXED	2	SETOCPL	LEN OF CKPT AREA DEST
44	(2C)	FIXED	2	SELUNO	ALLOCATED TRANSFER LU NO
46	(2E)	CHARACTER	5	SEFRCOMP	COMPLETION CODE SOURCE
51	(33)	CHARACTER	5	SETOCOMP	COMPLETION CODE DEST
RESERVED					
56	(38)	ADDRESS	4	SELCTAD	LCT ADDRESS
60	(3C)	ADDRESS	4	SERSS1	RESERVED
64	(40)	ADDRESS	4	SERSS2	RESERVED
68	(44)	ADDRESS	4	SERSU1	RESERVED
72	(48)	FIXED	4	SEEND	END OF SE
72	(48)	BITSTRING	1	SESIZE	SIZE OF SE = L'SESIZE
CROSS REFERENCE					
NAME	HEX OFFSET	HEX VALUE	LEVEL		
JCTBJNM	50		2		
JCTBJNO	50		2		
JCTBTCH	4E	3	2		
JCTCALL	72	40	2		
JCTCANCL	72	2	2		
JCTCMDDDB	8C	8C	2		
JCTCNDD	50		2		
JCTCPUID	1D	4040	2		
JCTDATI	2C		2		
JCTDDRS	50	0	2		
JCTDEL	73	8	2		
JCTDSENG	73	20	2		
JCTDTTM	24	4040	2		
JCTDUMP	72	1	2		
JCTEND	34		2		
JCTENTRY	34	1C	2		
JCTFCT	4E	6	2		
JCTFEND	B8		2		
JCTFIXL	A		2		
JCTFL1	72		2		
JCTFL2	73		2		
JCTFL2R2	73	2	2		
JCTFL3	74		2		
JCTFL3R4	74	4	2		
JCTFL3R5	74	2	2		
JCTFL3R6	74	1	2		
JCTFREEZ	73	10	2		
JCTFSIZE	B8		2		
JCTGRPID	24		2		
JCTID	0		2		
JCTJBNAM	10		2		
JCTJCLS	50		2		
JCTJES	4E	2	2		
JCTJESNR	1C		2		
JCTJMC	4E	7	2		
JCTJML	98		2		

JCTJMLMD	9C	0	2
JCTJOB	E		2
CTJSINF	1C		2
JCTLOCID	18	0	2
JCTLOCPF	14	0	2
JCTLOCPU	10	0	2
JCTLOG	4E	5	2
JCTMCS	4E	4	2
JCTMCSA	6C	51	2
JCTMCSI	50		2
JCTMJDDDB	8C	8C	2
JCTMJDLN	8A	0	2
JCTNCHNG	72	20	2
JCTNDSNQ	73	1	2
JCTNETFL	74	40	2
JCTNETHC	88	0	2
JCTNETID	80	4040	2
JCTNETRL	74	80	2
JCTNJE	74	20	2
JCTNJOBT	74	10	2
JCTNOSES	70		2
JCTNSSOT	74	8	2
JCTNTHLD	72	10	2
JCTOPCAN	73	4	2
JCTOPHLD	72	80	2
JCTPNDFG	1C	80	2
JCTPRTY	71		2
JCTPURG	72	8	2
JCTQDATE	18		2
JCTRDEV	4E	8	2
JCTRECS	1C	0	2
JCTRESCH	72	4	2
JCTREXMT	1C	80	2
JCTRNUM	22	0	2
JCTRNWD	20		2
JCTRSS1	75		2
JCTRSV1	A4		2
JCTRSV2	AC		2
JCTRSV3	B4		2
JCTRUD1	20	0	2
JCTSIDDB	8C		2
JCTSIZE	34	18	2
JCTSTCHG	73	40	2
JCTTAAD	73	80	2
JCTTOD	7C	0	2
JCTTOTL	8		2
JCTTQUID	1C		2
JCTTSO	4E	1	2
JCTUSER	4E	80	2
JCTUSID	50		2
JCTUTI	1C		2
JCTVARL	C		2
JCTVERS#	4		2
JCTWCT	78	0	2
JCTXALL	6C	3E	2
JCTXBSI	3E	0	2
JCTXBSN	46	0	2
JCTXDDN	50		2
JCTXEND	6C	70	2
JCTXFL1	4F	0	2
JCTXHDR	34	E7D6	2
JCTXLEN	3C	3C	2
JCTXMCL	4F	80	2
JCTXMTTM	2C	4040	2
JCTXOID	6C	34	2
JCTXRD2	58	0	2
JCTXRD3	5C	0	2
JCTXREL	38	F1F0	2
JCTXRS1	60	0	2
JCTXRS2	64	0	2
JCTXRU1	68	0	2
JCTXRU2	6C	0	2
JCTXTYP	4E	0	2
JCTX1R1	4F	40	2
JCTX1R2	4F	20	2
JCTX1R3	4F	10	2
JCTX1R4	4F	8	2
JCTX1R5	4F	4	2
JCTX1R6	4F	2	2
JCTX1R7	4F	1	2
SEACTIVE	0	40	2
SECOMP	0	80	2

SEDAP	4		2
SEEND	48		2
SEFLAGS	0		2
SEFLAG2	1		2
SEFLAG3	2		2
SEFL2R1	1	40	2
SEFL2R2	1	20	2
SEFL2R3	1	10	2
SEFL2R4	1	8	2
SEFL2R5	1	4	2
SEFL2R6	1	2	2
SEFL2R7	1	1	2
SEFRCOMP	2E		2
SEFRCPD	24		2
SEFRCPD	26		2
SEFRDAP	4		2
SEFRLOC	14		2
SEGBLACT	0	40	2
SEGBLCMP	0	80	2
SEGBLFR	0	10	2
SEGBLTO	0	20	2
SELCLACT	0	8	2
SELCLCMP	0	4	2
SELCLRQ	0	1	2
SELCLTO	0	2	2
SELCTAD	38		2
SELUNO	2C		2
SERSS1	3C		2
SERSS2	40		2
SERSU1	44		2
SESECAN	1	80	2
SESEQNO	3		2
SESIZE	48		2
SETOCOMP	33		2
SETOCPD	28		2
SETOCPL	2A		2
SETODAP	C		2
SETOLOC	1C		2

## Chapter 7. Job Queue Element — JQE

A job queue element (JQE) is an in-storage representation of each transaction represented by a JCT on the work queue. It allows direct access to the desired JCT on the work queue. There is one JQE entry allocated for each job.

<b>Function:</b>	The JQE provides access to the associated JCT on the work queue.
<b>Macro ID:</b>	BDTDJQE
<b>DSECT name:</b>	JQESTART
<b>Created by:</b>	BDTGRXD, when the job is scheduled
<b>Size:</b>	Hex 68 bytes
<b>Accessed by:</b>	The JQE access method in BDTGRJX, which is pointed to by TVTXJQE
<b>Location:</b>	In the JQX in the BDT address space

OFFSETS	TYPE	LENGTH	NAME	DESCRIPTION
MAPS THE BDT JOB QUEUE ELEMENT (JQE)				
0	(0) CHARACTER	4	JQEID	CONTROL BLOCK ACRONYM
4	(4) CHARACTER	4	JQEREL	RELEASE NUMBER
8	(8) BITSTRING	12	JQEDDB	DDBRQ FOR JCT I/O REQUESTS
20	(14) CHARACTER	8	JQENETID	NET ID
28	(1C) FIXED	2	JQEJNO	JOB NUMBER
30	(1E) FIXED	2	JQEPREV	JOBNO PREVIOUS JOB THIS PRY
32	(20) FIXED	2	JQENEXT	JOBNO NEXT JOB THIS PRY
34	(22) BITSTRING	1	JQEPRTY	JOB PRIORITY
35	(23) BITSTRING	1	JQEUCT	USE COUNT FOR READ ONLY USERS
36	(24) ADDRESS	1	JQERW	JQE JCT WRITE LOCK
MJD UPDATE LOCK FOOT PRINT				
37	(25) BITSTRING	1	JQEMJDID	MJD UPDATE LOCK FOOT PRINT
38	(26) BITSTRING	1	JQERWR1	RESERVED
MJD UPDATE SYNC LOCK				
39	(27) BITSTRING	1	JQEMJDLK	MJD UPDATE SYNC LOCK
	1... ..1		JQEMJD81	"X'81'" LOCK HELD BY CKPT
	1... ..1.		JQEMJD82	"X'82'" LOCK HELD BY GRJS
	1... ..11		JQEMJD83	"X'83'" LOCK HELD BY GRJR
40	(28) ADDRESS	4	JQERWFCT	JQE JCT WRITE FCT ADDRESS
JML LOCK				
44	(2C) ADDRESS	1	JQEJMLL	JML LOCK
45	(2D) ADDRESS	3	JQEJMRS	RESERVED
48	(30) ADDRESS	4	JQEJMLLA	JML LOCK WRITE FCT ADDRESS
52	(34) ADDRESS	4	JQEJML	JOB MESSAGE LOG CONTROL BLOCK
56	(38) FIXED	4	JQEQDATE	DATE JOB ENTERED THE SYSTEM
60	(3C) CHARACTER	8	JQEFRT0	FROM OR TO LOC
68	(44) CHARACTER	8	JQJGID	JES3 GROUP ID
76	(4C) CHARACTER	8	JQEJOBNO	JOB NAME
84	(54) CHARACTER	8	JQEJJNO	JES3 JOB ID
92	(5C) CHARACTER	8	JQEDATI	JES3 NJE TIME STAMP
DEFINITION OF JQE FLAG 1				
100	(64) BITSTRING	1	JQEFL1	SAME AS JCTFL1
	1... ..		JQEOPHLD	"BIT0" OPERATOR HOLD
	1.. ..		JQECALL	"BIT1" JOB IS CALLED DAP
	..1. ....		JQENCHNG	"BIT2" JCT NOT CHANGED
	...1 ....		JQENTHLD	"BIT3" NET HOLD
	.... 1...		JQEPURG	"BIT4" PURGE COMPLETE
	.... .1..		JQERESCH	"BIT5" RESCHEDULE

	....	..1.		JQECANCL	"BIT6" JSS TO CANCEL
	....	...1		JQEDUMP	"BIT7" JSS TO CANCEL W/DUMP
101	DEFINITION OF JQE FLAG 2 (65) BITSTRING 1				JQEFL2 SAME AS JCTFL2
	1...	....		JQETAAD	"BIT0" JCT ADD
	.1..	....		JQESTCHG	"BIT1" THIS JCT HAS STATUS CHANGE
	..1.	....		JQEDSEQ	"BIT2" JOB HELD DUE TO DS ENQUEUE
	...1	....		JQEFREZ	"BIT3" JCT FROZEN
	....	1...		JQEJDEL	"BIT4" JCT DEL
	....	.1..		JQEFL2R1	"BIT5" RESERVED
	....	..1.		JQEFL2R2	"BIT6" RESERVED
	....	...1		JQENDSNQ	"BIT7" NO BDT DSN ENQUEUE
102	DEFINITION OF JQE FLAG 3 (66) BITSTRING 1				JQEFL3 JQE FLAG 3
	1...	....		JQENETRL	"BIT0" NET RELEASE PROC'ING COMP
	.1..	....		JQENETFL	"BIT1" NET FLUSHED
	..1.	....		JQENJE	"BIT2" NJE TRANSACTION
	...1	....		JQENJOBT	"BIT3" NJE JOB TRANSACTION
	....	1...		JQENSSOT	"BIT4" NJE SYSOUT TRANSACTION
	....	.1..		JQEFL3R5	"BIT5" RESERVED
	....	..1.		JQEFL3R6	"BIT6" RESERVED
	....	...1		JQEFL3R7	"BIT7" RESERVED
103	(67)	BITSTRING	1	JQESTAT2	SEFLAGS FOR CURNT/NXT S.E.
104	DEFINITION OF CONTROL FLAG 1 (68) BITSTRING 1				JQEFLG1 CONTROL FLAG 1
	1...	....		JQEALLOC	"BIT0" THIS JQE CURRENTLY ALLOCATED
	.1..	....		JQENORD	"BIT1" RO ACCESS PROHIBITED
	..1.	....		JQEDEL	"BIT2" ALLOW TYPE=DEL ONLY
	...1	....		JQEFREEZ	"BIT3" SAME AS JCTFREEZ
	....	1...		JQERESDT	"BIT4" JCT IS RESIDENT
	....	.1..		JQEDSENQ	"BIT5" JOB IS HELD DUE TO DS ENQ
	....	..1.		JQECAT	"BIT6" CATASTROPHIC ERR JQE OR JCT
	....	...1		JQEMSG	"BIT7" CAT ERR MSG ISSUED
105	DEFINITION OF CONTROL FLAG 5 (69) BITSTRING 1				JQEFL5 CONTROL FLAG 5
	1...	....		JQETQPNQ	"BIT0" TQI PENDING FLAG ON IF JQE IS FOR JOB WHICH HAS NOT YET RECEIVED A COMMIT
	.1..	....		JQEFL5R1	"BIT1" RESERVED
	..1.	....		JQEFL5R2	"BIT2" RESERVED
	...1	....		JQEFL5R3	"BIT3" RESERVED
	....	1...		JQEFL5R4	"BIT4" RESERVED
	....	.1..		JQEFL5R5	"BIT5" RESERVED
	....	..1.		JQEFL5R6	"BIT6" RESERVED
	....	...1		JQEFL5R7	"BIT7" RESERVED
108	(6C)	FIXED	4	JQERSD01	RESERVED
112	(70)	FIXED	4	JQERSD02	RESERVED
116	(74)	FIXED	4	JQERSD03	RESERVED
120	(78)	FIXED	4	JQERSD04	RESERVED
	.111	11..		JQEEEND	END OF JQE
	.111	11..		JQESIZE	JQESIZE = JQE SIZE



## Chapter 8. JQE/JCT Access Control Table – JQX

The JQE/JCT access control table (JQX) contains control information. It is used by the JQE and JCT access routines.

<b>Function:</b>	The JQX is used by the JQE and JCT access routines.
<b>Macro ID:</b>	BDTDJQX
<b>DSECT name:</b>	JQXSTART
<b>Created by:</b>	BDTGRJX
<b>Size of fixed area:</b>	Hex 2C4 bytes
<b>Pointed to by:</b>	TVTJQX
<b>Location:</b>	In the BDT address space

OFFSETS	TYPE	LENGTH	NAME	DESCRIPTION
MAPS CONTROL TABLES USED BY BDT JQE/JCT ACCESS ROUTINES JQX (JQE/JCT ACCESS CONTROL TABLE)				
0	(0)	CHARACTER 4	JQXID	CONTROL BLOCK ACRONYM
4	(4)	CHARACTER 4	JQXVERS#	CONTROL BLOCK VERSION ID
8	(8)	ADDRESS 2	JQXLNGTH	CONTROL BLOCK LENGTH
10	(A)	FIXED 2	JQXRSVD1	RESERVED
12	(C)	ADDRESS 4	JQX0AD	BDTINJC ADDR JQE0
16	(10)	ADDRESS 4	JQX1AD	BDTINJC ADDR JQE1
20	(14)	ADDRESS 4	JQX2AD	BDTINJC ADDR JQE2
24	(18)	ADDRESS 4	JQX4AD	BDTINJC ADDR JQE4
28	(1C)	ADDRESS 4	JQXJEND	BDTINJC END OF JQE4 TABLE
32	(20)	FIXED 4	JQXHINM	HI JOBNAME ADDR IN JQE3
36	(24)	FIXED 4	JQXHIJQ	HI JQE ADDR IN JQE4
40	(28)	FIXED 4	JQXREAD	TOTAL JCT RREADS
44	(2C)	FIXED 4	JQXWRITE	TOTAL JCT RWRITES
48	(30)	FIXED 4	JQXTRKA	BDTINJC MRCH FOR JCT ADD (WARM/HOT)
52	(34)	FIXED 4	JQXWCT	WRITE ITERATION COUNT
56	(38)	FIXED 4	JQXMRCH	BDTINIO FIRST JCT REC MRCH
60	(3C)	FIXED 2	JQXRTRK	BDTINIO REC/TRK ON JCT DEVICE
62	(3E)	FIXED 2	JQXHCYL	BDTINIO HEADS/CYL ON JCT DEVICE
64	(40)	FIXED 2	JQXCNT	BDTINJC TOTAL ACTV BYTES IN JQE1 TBL
66	(42)	FIXED 2	JQXCURNT	CURRENT JQE ALLOCATION
68	(44)	FIXED 2	JQXHW	HI H20 JQE ALLOCATION
70	(46)	FIXED 2	JQXJMAX	BDTINIO TOTAL JCT RECORDS IN EXTENT
72	(48)	FIXED 2	JQXRCUR	CURRENT RESIDENT JCT COUNT
74	(4A)	FIXED 2	JQXMXSZ	BDTINIO JCT + SE'S + SRF PREFIX SIZE
76	(4C)	BITSTRING 1	JQXRSVD2	RESERVED
DEFINITION OF JQE/JCT CONTROL FLAG 1				
77	(4D)	BITSTRING 1	JQXFLG1	JQE/JCT CONTROL FLAG 1
	1...	....	JQXINIT	"BIT0" JQE/JCT INIT COMPLETE
	.1..	....	JQXPRNJE	"BIT1" REMOVE NJE TRANSACTION FROM JOB QUEUE
	..1.	....	JQXFL1R2	"BIT2" RESERVED
	...1	....	JQXFL1R3	"BIT3" RESERVED
	....	1...	JQXFL1R4	"BIT4" RESERVED
	....	.1..	JQXFL1R5	"BIT5" RESERVED
	....	..1.	JQXFL1R6	"BIT6" RESERVED
	....	...1	JQXFL1R7	"BIT7" RESERVED
DEFINITION OF JQE/JCT CONTROL FLAG 2				
78	(4E)	BITSTRING 1	JQXFLG2	JQE/JCT CONTROL FLAG 2

		1... ..		JQXFL2R0	"BIT0" RESERVED
		.1. ....		JQXFL2R1	"BIT1" RESERVED
		..1. ....		JQXFL2R2	"BIT2" RESERVED
		...1 ....		JQXFL2R3	"BIT3" RESERVED
		.... 1...		JQXFL2R4	"BIT4" RESERVED
		.... .1..		JQXFL2R5	"BIT5" RESERVED
		.... ..1.		JQXFL2R6	"BIT6" RESERVED
		.... ...1		JQXFL2R7	"BIT7" RESERVED
79	DEFINITION OF JQE/JCT CONTROL FLAG 3 (4F) BITSTRING 1 JQXFLG3 JQE/JCT CONTROL FLAG 3				
		1... ..		JQXFL3R0	"BIT0" RESERVED
		.1. ....		JQXFL3R1	"BIT1" RESERVED
		..1. ....		JQXFL3R2	"BIT2" RESERVED
		...1 ....		JQXFL3R3	"BIT3" RESERVED
		.... 1...		JQXFL3R4	"BIT4" RESERVED
		.... .1..		JQXFL3R5	"BIT5" RESERVED
		.... ..1.		JQXFL3R6	"BIT6" RESERVED
		.... ...1		JQXFL3R7	"BIT7" RESERVED
80	(50)	FIXED	4	JQXRESV3	RESERVED
88	(58)	FIXED	4	JQXRESV4	RESERVED
PRIORITY LEVEL ACCESS CONTROL FIELDS THE FIRST SIXTEEN SLOTS IN EACH FIELD ARE FOR FTF JOBS (PRIORITY 0-15) AND THE NEXT SIXTEEN SLOTS IN EACH FIELD ARE FOR NJE JOBS(PRIORITY(0-15)).					
100	(64)	FIXED	2	JQXPHEAD	FIRST JOB PRTY
164	(A4)	FIXED	2	JQXPTAIL	LAST JOB PRTY
228	(E4)	FIXED	2	JQXPCHN	NEXT JOB (PRTY SCAN)
292	(124)	BITSTRING	5	JQXPENQ	ENQ BYTE/FCT ADDR PRTY
452	(1C4)	FIXED	4	JQXPENQ2	ENQ CALLER RETURN ADDR
JQX PRIORITY STATUS TO ADDRESS FLAG BYTES FOR A SPECIFIC PRIORITY ASSUME R1=PRIORITY, R2=ADDRESS OF JQXPSTAT MH R1,=H'L'JQXPSTAT' PRTY ENTRY SIZE AR R2,R1 ADDR PRTY STATUS WORD USING JQXPSTAT,R2 BASE FOR PRTY STATUS WORD ACCESS JQXPFL0-3 AS REQUIRED DROP R2 RESET					
580	(244)	FIXED	4	JQXPSTAT	PRTY STATUS (1 FLWD/PRTY)
580	DEFINITION OF PRIORITY STATUS FLAG 0 (244) BITSTRING 1 JQXPFL0 PRIORITY STATUS				
		1... ..		JQXPHOLD	"BIT0" PRTY IS HELD PRTY
		..1. ....		JQXPREST	"BIT2" JOBS REQ RESTART PROCESSING
		...1 ....		JQXPRELH	"BIT3" PRIORITY RELEASED FROM HOLD
		.... 1...		JQXFL0R1	"BIT4" RESERVED
		.... .1..		JQXFL0R2	"BIT5" RESERVED
		.... ..1.		JQXFL0R3	"BIT6" RESERVED
		.... ...1		JQXFL0R4	"BIT7" RESERVED
581	(245)	BITSTRING	1	JQXPFL1	RESERVED
582	(246)	BITSTRING	1	JQXPFL2	COMPOSITE JCTFL2
583	(247)	BITSTRING	1	JQXPFL3	RESERVED
580	(244)	FIXED	4	JQXPTYCW	INIT PRTY CONTROL WORDS
580	(244)			JQXEND	END OF JQX

## Chapter 9. Logical Unit Control Table – LCT and LCTLU

A logical unit control table (LCT) describes either a SNA session or a VLU associated with a node. An LCT describing a session provides the interface with an LCB (an LCB contains the status of a session).

The logical control table for logical units (LCTLU) is an extension of the LCTs that describe the VLUs associated with a node. It describes inbound and outbound buffers associated with data transfer.

<b>Function:</b>	The LCT is used by BDTSNA to control sessions and to interleave data transfers and communication about those transfers on a single session with a node.
<b>Macro ID:</b>	BDTDLCT
<b>DSECT name:</b>	LCTSTART
<b>Created by:</b>	BDTINR2, at BDT initialization (LCTLUs are created by BDTSCINT at SNA initialization.)
<b>Size:</b>	Hex 84 bytes, hex F4 bytes including LCTLUs.
<b>Pointed to by:</b>	GLADDR, LCBLCT, LCTLUSAD, LCTCHAIN, LCTNODCH, LCTTYPCH, LCTLUVARS, TVTIFC, TVTXFER, TVTSNLTP, TVTLCTUN, RLTLNLPTR, RLTLCTAD
<b>Location:</b>	In the BDT address space

OFFSETS	TYPE	LENGTH	NAME	DESCRIPTION
BDT LOGICAL UNIT CONTROL BLOCK MAPPING MACRO FORMAT OF EACH LOGICAL UNITS TABLE ENTRY				
0	(0)	CHARACTER 4	LCTHDR	CONTROL BLOCK ACRONYM
4	(4)	CHARACTER 4	LCTREL	VERSION RELEASE ID
8	(8)	ADDRESS 2	LCTFLEN	FIXED LENGTH
10	(A)	FIXED 2	LCTRSVD1	RESERVED
12	(C)	ADDRESS 4	LCTRLT	ADDR RLT ENTRY
16	(10)	ADDRESS 4	LCTCHAIN	ADDR NEXT LCT
20	(14)	ADDRESS 4	LCTTYPCH	ADDR NEXT LCT OF SAME TYPE
24	(18)	ADDRESS 4	LCTNODCH	ADDR NEXT LCT OF SAME NODE
28	(1C)	ADDRESS 4	LCTLVARS	LU VARIABLE SEGMENT
32	(20)	ADDRESS 4	LCTLGETA	LGET AREA ADDR
36	(24)	ADDRESS 2	LCTLGETL	LGET DATA LENGTH
38	(26)	ADDRESS 2	LCTLGETD	LGET DISPLACEMENT
40	(28)	ADDRESS 4	LCTMSKEF	POST MASK, ECF ADR (COM VLU)
40	(28)	BITSTRING 3	LCTRSD02	RESERVED
43	(2B)	BITSTRING 1	LCTMSK	POST ECF MASK (COMM VLU)
44	(2C)	ADDRESS 4	LCTMSKAD	POST ECF ADDRESS (COMM VLU)
48	(30)	ADDRESS 2	LCTNOLU	LU NUMBER ON NODE
50	(32)	ADDRESS 2	LCTJOBNO	JOB NUMBER THAT HAS LU ALLOCATE
52	(34)	ADDRESS 4	LCTFCT	CALLER'S FCT ADDRESS
56	(38)	CHARACTER 8	LCTTYPE	LOGICAL LU TYPE
56	(38)	CHARACTER 3	LCTTGEN	GENERAL LU TYPE
59	(3B)	CHARACTER 5	LCTTSPEC	SPECIFIC LU TYPE
64	(40)	CHARACTER 11	LCTDD	LOGICAL LU DDNAME
64	(40)	CHARACTER 8	LCTNODE	LOGICAL LU NODE NAME
72	(48)	CHARACTER 3	LCTVLUNO	LOGICAL LU NUMBER
72	(48)	CHARACTER 1	LCTVLUCC	FIRST CHARACTER OF FTF VLU ID
73	(49)	CHARACTER 2	LCTVLUN2	VLU NUMBER
75	(4B)	BITSTRING 1	LCTLPUTF	LPUT FLAGS
76	(4C)	ADDRESS 4	LCTLPUTA	LPUT AREA ADDRESS (COM VLU)
80	(50)	FIXED 2	LCTLPUTL	LPUT DATA LENGTH (COM VLU)
82	(52)	FIXED 2	LCTLPUTD	LPUT DISPLACEMENT (COM VLU)
84	(54)	FIXED 2	LCTNJSEQ	SEQUENCE NUMBER FOR NJE NODES
86	(56)	FIXED 2	LCTNJSR1	RESERVED
88	(58)	FIXED 4	LCTIFCBF	IFC INPUT BUFFER ADDRESS
96	(60)	8	LCTOUTQ	IFC OUTPUT QUEUE
96	(60)	ADDRESS 4	LCTOUTQU	PTR TO FIRST IFC ON QUEUE
100	(64)	ADDRESS 4	LCTOUTCT	NUMBER OF IFC'S ON QUEUE
104	(68)	FIXED 4	LCTFLAGS	LCTUNITS FLAG BYTES

DEFINITION OF LCTFLAGX (BUFFER STATUS) (MUST BE MODIFIED WITH COMPARE AND SWAP)				
104	(68)	BITSTRING	1	LCTFLAGX ASYNCHRONOUSLY CHANGING FLAG
		1... ..	LCTEODAP	"BIT0" ACK PENDING FOR EOD (COM LU)
		.1.. ..	LCTFLXR1	"BIT1" RESERVED
		..1. ....	LCTFLXR2	"BIT2" RESERVED
		...1 ....	LCTFLXR3	"BIT3" RESERVED
		...1 ....	LCTLPTAC	"BIT4" COM LPUT TO BE DEQUEUED
		.... .1..	LCTFLXR4	"BIT5" RESERVED
		.... ..1.	LCTBFRCV	"BIT6" COM INPUT BUF RECVD
		.... ...1	LCTBFSNT	"BIT7" COM OUTPUT BUF SENT
DEFINITION OF LCTFLAG1 (VLU STATUS)				
105	(69)	BITSTRING	1	LCTFLAG1 LCTUNITS FLAG 1
		1... ..	LCTOFFLN	"BIT0" LU VARIED OFFLINE
		.1.. ..	LCTBDTOF	"BIT1" REMOTE LU NOT AVAILABLE
		..1. ....	LCTBDTAL	"BIT2" BDT LU IS ALLOCATED
		...1 ....	LCTBDTAB	"BIT3" BDT LINE IS ABORTING
		.... 1...	LCTBDTOO	"BIT4" LU OPEN FOR OUTPUT
		.... .1..	LCTBDTOI	"BIT5" LU OPEN FOR INPUT
		.... ..1.	LCTEOD	"BIT6" LU REACHED EOD
		.... ...1	LCTFLUSH	"BIT7" FLUSH INPUT UNTIL SOD
DEFINITION OF LCTFLAG2 (VLU TYPE)				
106	(6A)	BITSTRING	1	LCTFLAG2 LCTUNITS FLAG 2
		1... ..	LCTBDTLN	"BIT0" BDT LINE LU
		.1.. ..	LCTBDTTR	"BIT1" BDT TRANSFER LU
		..1. ....	LCTBDTCM	"BIT2" BDT COM LU (SYSTEM FUNCTION)
		...1 ....	LCTNJE	"BIT3" NODE TYPE IS NJE
		.... 1...	LCTBDTSC	"BIT4" SECONDARY LU (LOCAL)
		.... .1..	LCTFL2R1	"BIT5" RESERVED
		.... ..1.	LCTBDTFR	"BIT6" LU FENCED 'FROM'
		.... ...1	LCTBDTTO	"BIT7" LU FENCED 'TO'
DEFINITION OF LCTFLAG3 (VLU CONTROL FLAG)				
107	(6B)	BITSTRING	1	LCTFLAG3 VLU CONTROL FLAG
		1... ..	LCTVTERM	"BIT0" VLU TERMINATION IN PROGRESS
		.1.. ..	LCTFL3R1	"BIT1" RESERVED
		..1. ....	LCTNJEST	"BIT2" SNA TERM. EXTENSION SUPPORTED
		...1 ....	LCTSODSN	"BIT3" START OF DATA SENT
		.... 1...	LCTOPNOU	"BIT4" OPENED FOR OUTPUT (LCTBDTOO)
		.... .1..	LCTOPNIN	"BIT5" OPENED FOR INPUT (LCTBDTOI)
		.... ..1.	LCTBFLMT	"BIT6" VLU HAS ITS LIMIT OF TWO BUFFERS
		.... ...1	LCTLRDPD	"BIT7" VLU HAS AN LREAD REQUEST PENDING
DEFINITION OF LCTCSOPT (COMPRESSION OPTION FLAG)				
108	(6C)	BITSTRING	1	LCTCSOPT COMPRESSION OPTION FLAG
		1... ..	LCTCNDUP	"BIT0" NJE DUPLICATE IN COMPRESSION
		.1.. ..	LCTCRDUP	"BIT1" REPEATED DUP. COMPRESSION
		..1. ....	LCTCOPR1	"BIT2" RESERVED
		...1 ....	LCTCOPR2	"BIT3" RESERVED
		.... 1...	LCTCOPR3	"BIT4" RESERVED
		.... .1..	LCTCOPR4	"BIT5" RESERVED
		.... ..1.	LCTCOPR5	"BIT6" RESERVED
		.... ...1	LCTCOPR6	"BIT7" RESERVED
DEFINITION OF LCTCSDAP (SAME AS LCTCSOPT)				
109	(6D)	BITSTRING	1	LCTCSDAP DAP COMPRESSION FLAG

		1... ..		LCTCSDUP	"BIT0" NJE DUPLICATE IN COMPRESSION
		.1.. ..		LCTCSRDP	"BIT1" REPEATED DUP. COMPRESSION
		..1. ....		LCTCSDR1	"BIT2" RESERVED
		...1 ....		LCTCSDR2	"BIT3" RESERVED
		.... 1...		LCTCSDR3	"BIT4" RESERVED
		.... .1..		LCTCSDR4	"BIT5" RESERVED
		.... ..1.		LCTCSDR5	"BIT6" RESERVED
		.... ...1		LCTCSDR6	"BIT7" RESERVED
110	(6E)	BITSTRING	1	LCTSDSEQ	START OF DATA SEQ NUMBER
111	(6F)	BITSTRING	1	LCTRSVU2	RESERVED
112	(70)	ADDRESS	2	LCTCSLEN	COMPRESSED DATA LENGTH
114	DEFINITION OF THE (72)	LCTFLAG4 BITSTRING	1	LCTFLAG4	LCTFLAG4
		1... ..		LCTTQLSD	"BIT0" LINE IS IN SLOWDOWN FOR TQI
		.1.. ..		LCTTQSDP	"BIT1" TQI POST REQUIRED WHEN IFC LOW
		..1. ....		LCTFL4S1	"BIT2" RESERVED
		...1 ....		LCTFL4S2	"BIT3" RESERVED
		.... 1...		LCTFL4S3	"BIT4" RESERVED
		.... .1..		LCTFL4S4	"BIT5" RESERVED
		.... ..1.		LCTFL4S5	"BIT6" RESERVED
		.... ...1		LCTOPOFF	"BIT7" OPERATOR VARY ACROSS SESSIONS
		11.. ..		LCTTQSL0	"LCTTQLSD+LCTTQSDP" LINE IN SLOWDOWN AND TQI NEEDS POSTING
115	(73)	BITSTRING	1	LCTTQRS1	RESERVED
116	(74)	BITSTRING	1	LCTBSTRM	NJE BINARY STREAM ID
117	(75)	CHARACTER	3	LCTESTRM	NJE EBCDIC STREAM NAME
120	(78)	ADDRESS	4	LCTTQRS3	RESERVED
124	(7C)	ADDRESS	4	LCTTQRS4	RESERVED
128	(80)	ADDRESS	8	LCTTQRS5	RESERVED
136	(88)	FIXED	4	LCTFEND	END OF FIXED AREA
136	(88)	BITSTRING	1	LCTFSIZE	LCTUNITS FIXED SIZE
	FORMAT OF THE NODE	VLU	VARIABLE	SEGMENT	
0	(0)	CHARACTER	4	LCTLUHDR	GENERATE HEADER
4	(4)	CHARACTER	4	LCTLUREL	GENERATE LENGTH
8	(8)	ADDRESS	2	LCTLULEN	GENERATE LENGTH
10	(A)	FIXED	2	LCTLURS1	RESERVED
12	(C)	ADDRESS	4	LCTLUSAD	LCTUNITS ADDR
16	(10)	ADDRESS	4	LCTLUDCL	PTR COMPRESSION PARM LIST
20	(14)	ADDRESS	4	LCTLULIN	LINE LCTLN SEGMENT ADDR
24	(18)	ADDRESS	4	LCTLULUE	PTR NXT LU (CHAINS ENDS)
28	(1C)	ADDRESS	4	LCTLULUL	PTR NXT LU (CHAIN CIRCULAR)
32	(20)	ADDRESS	2	LCTLUBFN	BUFNO
34	(22)	ADDRESS	2	LCTLUREC	GIVEN RECORD SIZE
36	(24)	ADDRESS	2	LCTLUMAX	MAX RECORD SIZE
38	(26)	ADDRESS	2	LCTLUSIZ	NODE BUFFER SIZE
40	(28)	BITSTRING	1	LCTLUBIT	LU ID NUMBER
41	(29)	BITSTRING	1	LCTLUXFG	USER REQUEST FLAGS
42	(2A)	BITSTRING	1	LCTLUISQ	INPUT BUF SEQ COUNTER
43	(2B)	BITSTRING	1	LCTLUOSQ	OUTPUT BUF SEQ COUNTER
44	(2C)	ADDRESS	4	LCTLUIBQ	INPUT BUFFER QUEUE
48	(30)	ADDRESS	4	LCTLUIQD	INPUT QUEUE DEPTH
52	(34)	ADDRESS	4	LCTLUACK	NUMBER OF PENDING ACKS FOR INPUT BUFFERS PROCESSED
56	(38)	ADDRESS	4	LCTLUIBE	INPUT BUFFER BEING EMPTIED
60	(3C)	ADDRESS	4	LCTLUOBQ	OUTPUT BUFFER QUEUE
64	(40)	ADDRESS	4	LCTLUOQD	OUTPUT QUEUE DEPTH
68	(44)	ADDRESS	4	LCTLUSNT	NUMBER OF PENDING ACKS FOR OUTPUT BUFFERS SENT
72	(48)	ADDRESS	4	LCTLUOBF	OUTPUT BUFFER BEING FILLED
76	(4C)	ADDRESS	4	LCTLUOBS	OUTPUT BUFFER SENT
80	DEFINITION OF LU FLAG 2 (50)	LCTLUFL2 BITSTRING	1	LCTLUFL2	LU FLAG 2
		1... ..		LCTLU2AE	"BIT0" ACKNOWLEDGE END OF STREAM
		.1.. ..		LCTLU2BA	"BIT1" BUFFER AVAILABLE TO

..1. ....	LCTLU2SC	SEND DATA
...1 ....	LCTLU2RC	"BIT2" SEND A SENDER CANCEL
		"BIT3" RECEIVER CANCEL
		RECEIVED
.... 1...	LCTLU2R5	"BIT4" RESERVED
.... .1..	LCTLU2R6	"BIT5" RESERVED
.... ..1.	LCTLU2R7	"BIT6" RESERVED
.... ...1	LCTLU2SU	"BIT7" SEQNO UPDATED

81	DEFINITION OF LU FLAG 3 (51) BITSTRING 1	LCTLUFL3	LU FLAG 3
	1... ....	LCTLU3CR	"BIT0" JOB CANCEL FOR left 0 RESCHEDULE
	.1.. ....	LCTLU3CH	"BIT1" JOB CANCEL FOR HOLD
	..1. ....	LCTLU3R3	"BIT2" RESERVED
	...1 ....	LCTLU3R4	"BIT3" RESERVED
	.... 1...	LCTLU3R5	"BIT4" RESERVED
	.... .1..	LCTLU3R6	"BIT5" RESERVED
	.... ..1.	LCTLU3R7	"BIT6" RESERVED
	.... ...1	LCTLU3R8	"BIT7" RESERVED

82	RESERVED AREA (52) BITSTRING 2	LCTRSVU3	RESERVED
84	(54) FIXED 4	LCTRSVU4	RESERVED
88	(58) FIXED 4	LCTRSVD3	RESERVED
92	(5C) FIXED 4	LCTRSVD4	RESERVED
96	(60) FIXED 4	LCTRSVD5	RESERVED
100	(64) FIXED 4	LCTRSVD6	RESERVED

104	LU DDN INFORMATION (68) CHARACTER 8	LCTLUDDN	LU DDN
104	(68) CHARACTER 1	LCTLUDDC	LU DDN SEQUENCE CONTROL CHAR.
105	(69) CHARACTER 4	LCTLUDE	LU DDN SEQUENCE NUMBER
109	(6D) CHARACTER 1	LCTLUDDV	LU DDN VLU NUMBER CONTROL CHAR.
110	(6E) CHARACTER 2	LCTLUNIT	LU DDN VLU NUMBER
112	(70) FIXED 4	LCTLUEND	END OF ENTRY
112	(70) BITSTRING 1	LCTLUSZE	LEN OF EXTENSION

NAME	CROSS REFERENCE HEX OFFSET	HEX VALUE	LEVEL
LCTBDTAB	69	10	2
LCTBDTAL	69	20	2
LCTBDTCM	6A	20	2
LCTBDTFR	6A	2	2
LCTBDTLN	6A	80	2
LCTBDTOF	69	40	2
LCTBDTOI	69	4	2
LCTBDTOO	69	8	2
LCTBDTSC	6A	8	2
LCTBDTTO	6A	1	2
LCTBDTTR	6A	40	2
LCTBFLMT	6B	2	2
LCTBFRCV	68	2	2
LCTBFSNT	68	1	2
LCTBSTRM	74		2
LCTCHAIN	10		2
LCTCNDUP	6C	80	2
LCTCOPR1	6C	20	2
LCTCOPR2	6C	10	2
LCTCOPR3	6C	8	2
LCTCOPR4	6C	4	2
LCTCOPR5	6C	2	2
LCTCOPR6	6C	1	2
LCTCRDUP	6C	40	2
LCTCSDAP	6D		2
LCTCSDR1	6D	20	2
LCTCSDR2	6D	10	2
LCTCSDR3	6D	8	2
LCTCSDR4	6D	4	2
LCTCSDR5	6D	2	2
LCTCSDR6	6D	1	2
LCTCSDUP	6D	80	2
LCTCSLEN	70		2
LCTCSOPT	6C		2

LCTCSRDP	6D	40	2
LCTDD	40		2
LCTE0D	69	2	2
LCTE0DAP	68	80	2
LCTESTRM	75		2
LCTFCT	34		2
LCTFEND	88		2
LCTFLAGS	68		2
LCTFLAGX	68		2
LCTFLAG1	69		2
LCTFLAG2	6A		2
LCTFLAG3	6B		2
LCTFLAG4	72		2
LCTFLEN	8	84	2
LCTFLUSH	69	1	2
LCTFLXR1	68	40	2
LCTFLXR2	68	20	2
LCTFLXR3	68	10	2
LCTFLXR4	68	4	2
LCTFL2R1	6A	4	2
LCTFL3R1	6B	40	2
LCTFL4S1	72	20	2
LCTFL4S2	72	10	2
LCTFL4S3	72	8	2
LCTFL4S4	72	4	2
LCTFL4S5	72	2	2
LCTFSIZE	88		2
LCTHDR	0	D3C3	2
LCTIFCBF	58	0	2
LCTJOBNO	32		2
LCTLGETA	20		2
LCTLGETD	26		2
LCTLGETL	24		2
LCTLPTAC	68	8	2
LCTLPUTA	4C		2
LCTLPUTD	52		2
LCTLPUTF	4B	0	2
LCTLPUTL	50		2
LCTLRDPD	6B	1	2
LCTLUACK	34		2
LCTLUBFN	20		2
LCTLUBIT	28	0	2
LCTLUDCL	10		2
LCTLUDDC	68		2
LCTLUDDN	68		2
LCTLUDDV	6D		2
LCTLUOSE	69		2
LCTLUEND	70		2
LCTLUFL2	50		2
LCTLUFL3	51		2
LCTLUHDR	0	D3C3	2
LCTLUIBE	38		2
LCTLUIBQ	2C		2
LCTLUIQD	30		2
LCTLUISQ	2A	0	2
LCTLULEN	8	70	2
LCTLULIN	14		2
LCTLULUE	18		2
LCTLULUL	1C		2
LCTLUMAX	24		2
LCTLUNIT	6E		2
LCTLU0BF	48		2
LCTLU0BQ	3C		2
LCTLU0BS	4C		2
LCTLU0QD	40		2
LCTLU0SQ	2B	0	2
LCTLUREC	22		2
LCTLUREL	4	F2F0	2
LCTLURS1	A		2
LCTLUSAD	C		2
LCTLUSIZ	26		2
LCTLUSNT	44		2
LCTLUSZE	70		2
LCTLUXFG	29	0	2
LCTLU2AE	50	80	2
LCTLU2BA	50	40	2
LCTLU2RC	50	10	2
LCTLU2R5	50	8	2
LCTLU2R6	50	4	2
LCTLU2R7	50	2	2
LCTLU2SC	50	20	2
LCTLU2SU	50	1	2

LCTLU3CH	51	40	2
LCTLU3CR	51	80	2
LCTLU3R3	51	20	2
LCTLU3R4	51	10	2
LCTLU3R5	51	8	2
LCTLU3R6	51	4	2
LCTLU3R7	51	2	2
LCTLU3R8	51	1	2
LCTLVARS	1C		2
LCTMSK	2B	0	2
LCTMSKAD	2C		2
LCTMSKEF	28		2
LCTNJE	6A	10	2
LCTNJEST	6B	20	2
LCTNJSEQ	54		2
LCTNJSR1	56		2
LCTNODCH	18		2
LCTNODE	40		2
LCTNOLU	30		2
LCTOFFLN	69	80	2
LCTOPNIN	6B	4	2
LCTOPNOU	6B	8	2
LCTOPOFF	72	1	2
LCTOUTCT	64		2
LCTOUTQ	60		2
LCTOUTQU	60		2
LCTREL	4	F2F0	2
LCTRLT	C		2
LCTRSD02	28		2
LCTRSVD1	A	0	2
LCTRSVD3	58	0	2
LCTRSVD4	5C	0	2
LCTRSVD5	60	0	2
LCTRSVD6	64	0	2
LCTRSVU2	6F	0	2
LCTRSVU3	52		2
LCTRSVU4	54	0	2
LCTSDSEQ	6E	0	2
LCTSODSN	6B	10	2
LCTTGEN	38		2
LCTTQLSD	72	80	2
LCTTQRS1	73	0	2
LCTTQRS3	78		2
LCTTQRS4	7C		2
LCTTQRS5	80		2
LCTTQSDP	72	40	2
LCTTQSL0	72	C0	2
LCTTSPEC	3B		2
LCTTYPCH	14		2
LCTTYPE	38		2
LCTVLUCC	48		2
LCTVLUN0	48		2
LCTVLUN2	49		2
LCTVTERM	6B	80	2



## Chapter 10. Master Job Definition – MJD

The master job definition (MJD) contains job-related and data set information from the transaction, parameters from the generic MJD, and information gathered as BDT processes the job. There is one MJD for each job. The major portion of the MJD is the dynamic allocation text units used to allocate the “from” and “to” data sets involved in the data transfer.

The MJD is associated with a BSID from the time a transaction is first received until the MJD is placed on the work queue.

<b>Function:</b>	The MJD is used in scheduling jobs.
<b>Macro ID:</b>	BDTDMJD
<b>DSECT name:</b>	MJDSTART
<b>Created by:</b>	BDTLP, called from either the BDT, user, or JESaddress space.
<b>Size of fixed area:</b>	Hex 160 bytes
<b>Pointed to by:</b>	RSQAJDBR, when active in the address space; JCTMJDDDB, for the MJD on the work queue
<b>Location:</b>	The MJD originally resides in the address space of the caller. If TQI is active, the MJD is also written to the TQI checkpoint data set. BDT reads it and writes it to the BDT work queue, where it stays while the job is active. The accounting driver processes it on the work queue after the job is purged.

OFFSETS		TYPE	LENGTH	NAME	DESCRIPTION
BDT MASTER JOB DEFINITION CONTROL BLOCK FIXED PART OF THE MJD					
0	(0)	FIXED	4	MJDID	CONTROL BLOCK IDENTIFIER
4	(4)	CHARACTER	4	MJDVER#	BDT VERSION NUMBER
8	(8)	FIXED	2	MJDFXDLN	LENGTH OF FIXED PART OF THE MJD
10	(A)	FIXED	2	MJDTOTLN	TOTAL LENGTH OF THE MJD
12	(C)	FIXED	2	MJDFRCPD	SOURCE CKPT AREA DISPLACEMENT
14	(E)	FIXED	2	MJDFRCPL	SOURCE CKPT AREA LENGTH
		.... 11..		MJDFRCP	"MJDFRCPD,*-MJDFRCPD,C'H'"
16	(10)	FIXED	2	MJDTOCPD	DESTINATION CKPT AREA DISPLACEMENT
18	(12)	FIXED	2	MJDTOCL	DESTINATION CKPT AREA LENGTH
		...1 ....		MJDTOCP	"MJDTOCPD,*-MJDTOCPD,C'H'"
		.... 11..		MJDCP	"MJDFRCPD,*-MJDFRCPD,C'H'"
		..1. .1..		MJDKDEF	"36" DEFAULT DAP CHECKPOINT LEN.
20	(14)	CHARACTER	8	MJDJOBNM	JOB NAME
JOB PRIORITY AND LOCATION INFORMATION					
28	(1C)	ADDRESS	1	MJDPRTY	JOB PRIORITY
29	(1D)	CHARACTER	8	MJDLOC	LOCATION
29	(1D)	CHARACTER	8	MJDFRLOC	SOURCE LOCATION
37	(25)	CHARACTER	8	MJDTOLOC	DESTINATION LOCATION
DAP INFORMATION					
45	(2D)	CHARACTER	8	MJDDAP	DAP NAME
45	(2D)	CHARACTER	8	MJDFRDAP	SOURCE DAP NAME
53	(35)	CHARACTER	8	MJDTODAP	DESTINATION DAP NAME
61	(3D)	CHARACTER	4	MJDXHDR	CONTROL BLOCK ACRONYM
65	(41)	CHARACTER	4	MJDXREL	VERSION ID
69	(45)	ADDRESS	2	MJDXLEN	XOID LENGTH
71	(47)	BITSTRING	8	MJDXBSI	XACTION ORIGIN BDT SYS ID
79	(4F)	BITSTRING	8	MJDXBSN	XACTION ORIGIN BDT SYS NAME

87	TRANSACTION ORIGIN (57)	BITSTRING	1	MJDXTYP	XACTION ORIGIN TYPE
		.... .1		MJDTSO	"1" TSO USER
		.... .1.		MJDJES	"2" JES CONSOLE
		.... .11		MJDBTCH	"3" BATCH JOB
		.... .1..		MJDMCS	"4" MCS CONSOLE
		.... .1.1		MJDLOG	"5" JOB MESSAGE LOG
		.... .11.		MJDFCT	"6" BDT FCT
		.... .111		MJDJMC	"7" JES MESSAGE CLASS
		.... 1...		MJDRDEV	"8" BEGIN DEVELOPMENT
					DEFINED XOIDXTYP
		1... ....		MJDUSER	"128" BEGIN USER DEFINED XOIDXTYP
88	FLAG 1 (58)	BITSTRING	1	MJDXFL1	XOID FLAG 1
		1... ....		MJDXMCL	"BIT0" SUPPRESSION OF MESSAGE CLASS
		.1.. ....		MJDX1R1	"BIT1" RESERVED
		..1. ....		MJDX1R2	"BIT2" RESERVED
		...1 ....		MJDX1R3	"BIT3" RESERVED
		.... 1...		MJDX1R4	"BIT4" RESERVED
		.... .1..		MJDX1R5	"BIT5" RESERVED
		.... ..1.		MJDX1R6	"BIT6" RESERVED
		.... ...1		MJDX1R7	"BIT7" RESERVED
89	MISCELLANEOUS INFORMATION (59)	CHARACTER	8	MJDXDDN	TRANSACTION ORIGIN DDNAME
89	(59)	CHARACTER	8	MJDUSID	TSO USERID
89	(59)	CHARACTER	8	MJDCNDD	JES CONSOLE DDNAME
89	(59)	CHARACTER	8	MJDJCLS	JES MESSAGE CLASS
89	(59)	CHARACTER	8	MJDBJNM	BATCH JOB NAME
89	(59)	ADDRESS	1	MJDMCSI	MCS CONSOLE ID
89	(59)	BITSTRING	2	MJDBJNO	BDT JOB NUMBER
89	(59)	BITSTRING	8	MJDDDRS	DDNAME
97	RESERVED FIELDS (61)	BITSTRING	4	MJDXRD2	RESERVED
101	(65)	BITSTRING	4	MJDXRD3	RESERVED
105	(69)	BITSTRING	4	MJDXRS1	RESERVED
109	(6D)	BITSTRING	4	MJDXRS2	RESERVED
113	(71)	BITSTRING	4	MJDXRU1	RESERVED
117	(75)	BITSTRING	4	MJDXRU2	RESERVED
		.1.1 1.1.		MJDMCSA	MCS CONSOLE UX28 AUTH
		.111 1..1		MJDXEND	END OF XOID
		..11 11.1		MJDXOID	XOID EQUATE
		.1.. .111		MJDXALL	BSI EQUATE
121	TRANSACTION CODE (79)	CHARACTER	8	MJDXCODE	TRANSACTION CODE
129	(81)	BITSTRING	1	MJDFLAG1	FLAGS
		..1. ....		MJDHOLD	"X'20'" QUEUE JOB IN OPERATOR HOLD STATUS
130	(82)	FIXED	2	MJDFRNTU	NUMBER OF SOURCE TEXT UNITS
132	(84)	FIXED	2	MJDTONTU	NUMBER OF DESTINATION TEXT UNITS
134	(86)	FIXED	2	MJDNETHC	NET HOLD COUNT
136	INFORMATION PERTAINING TO THE JOB (88)	FIXED	4	MJDTIME	JOB TIME LIMIT .01 SEC
140	(8C)	BITSTRING	4	MJDJST	JOB ENTER TIME .01 SEC
144	(90)		4	MJDJSD	JOB ENTER DATE 00YYDDDF
148	INFORMATION PERTAINING TO EXECUTION (94)	BITSTRING	4	MJDXST	EXECUTION START TIME
152	(98)		4	MJDXSD	EXECUTION START DATE
		1..1 .1..		MJDXSTD	"MJDXST,*-MJDXST,C'X' "

156	(9C)	BITSTRING	4	MJDXPT	EXECUTION STOP TIME
160	(A0)		4	MJDXPD	EXECUTION STOP DATE
NUMBER OF BYTES TRANSFERRED AND PRIORITY					
164	(A4)	FIXED	4	MJDBTYPES	BYTES TRANSFERRED
168	(A8)	BITSTRING	1	MJDXPTY	EXECUTION PRIORITY
'FROM' AND 'TO' VOLSEQ					
169	(A9)	BITSTRING	1	MJDFRVSQ	'FROM' VOLSEQ
170	(AA)	BITSTRING	1	MJDOVSQ	'TO' VOLSEQ
USER EXIT 27 STATUS FLAG					
171	(AB)	BITSTRING	1	MJDOFRM	UX27 STATUS FLAG
		1... ..		MJDO	"BIT0" UX27 ENTERED FOR TO SIDE
		.1.. ..		MJDFROM	"BIT1" UX27 ENTERED FOR FROM SIDE
		..1. ....		MJDOFR1	"BIT2" RESERVED
		...1 ....		MJDOFR2	"BIT3" RESERVED
		.... 1...		MJDOFR3	"BIT4" RESERVED
		.... .1..		MJDOFR4	"BIT5" RESERVED
		.... ..1.		MJDOFR5	"BIT6" RESERVED
		.... ...1		MJDOFR6	"BIT7" RESERVED
172	(AC)	BITSTRING	11	MJDRESV1	RESERVED
FROM CPU INFORMATION					
184	(B8)	FIXED	4	MJDFRCPU	FROM CPU TIME .01 SEC
188	(BC)	FIXED	4	MJDFRCPF	FROM CPU FACTOR
192	(C0)	BITSTRING	4	MJDFRCID	FROM CPU ID
		1.11 1...		MJDCPULN	"MJDFRCPU,*-MJDFRCPU,C'X'"
TO CPU INFORMATION					
196	(C4)	FIXED	4	MJDTOCPU	TO CPU TIME .01 SEC
200	(C8)	FIXED	4	MJDTOCPF	TO CPU FACTOR
204	(CC)	BITSTRING	4	MJDTOCID	TO CPU ID
		1..1 11..		MJDEXECD	"MJDXPT,*-MJDXPT,C'X'"
NET ID AND JES JOB NUMBER					
208	(D0)	CHARACTER	8	MJDNETID	NET ID
216	(D8)	FIXED	2	MJDJESJN	JES JOB NUMBER (TRANSACTION ORIGIN)
USER FLAG FIELDS					
218	(DA)	BITSTRING	1	MJDUFLG1	USER FLAG1
219	(DB)	BITSTRING	1	MJDUFLG2	USER FLAG2
ADDITIONAL JOB IDENTIFICATION INFORMATION FOR NJE					
220	(DC)	CHARACTER	16	MJDJSINF	JES3 GROUP ID AND GROUP ID
220	(DC)	CHARACTER	8	MJDJESNR	JES3 JOB NUMBER
228	(E4)	CHARACTER	8	MJDGRPID	JES3 GROUP ID
NJE FLAG FIELD DEFINITION INFORMATION FOR NJE					
236	(EC)	BITSTRING	1	MJDNFLG1	NJE FLAG
		1... ..		MJDNJOB	"BIT0" NJE JOB REQUEST
		.1.. ....		MJDNSOUT	"BIT1" NJE SYSOUT REQUEST
		..1. ....		MJDNF1R1	"BIT2" RESERVED
		...1 ....		MJDNF1R2	"BIT3" RESERVED
		.... 1...		MJDNF1R3	"BIT4" RESERVED
		.... .1..		MJDNF1R4	"BIT5" RESERVED
		.... ..1.		MJDNF1R5	"BIT6" RESERVED
		.... ...1		MJDNF1R6	"BIT7" RESERVED
NJE ACCOUNTING INFORMATION					
237	(ED)	CHARACTER	2	MJD59NJT	JOB TYPE
237	(ED)	CHARACTER		MJD59JB	"C'JB'" DATA IS A JOB STREAM
237	(ED)	CHARACTER		MJD590P	"C'OP'" DATA IS COMPLETED SYSOUT

239	(EF)	BITSTRING	2	MJD59NUM	ORIGINAL JOB NUMBER
241	(F1)	CHARACTER	8	MJD59NAN	NETWORK ACCOUNT NUMBER
249	(F9)	CHARACTER	8	MJD59NAM	ORIGINAL JOB NAME
257	(101)	CHARACTER	8	MJD59NUI	NOTIFY USER ID
265	(109)	BITSTRING	8	MJD59NTD	JOB ENTRY DATE/ORIGIN TIME STAMP
273	(111)	CHARACTER	8	MJD59XQN	EXECUTION NODE NAME
281	(119)	CHARACTER	8	MJD59XQU	EXECUTION USER ID
289	(121)	CHARACTER	20	MJD59NPN	PROGRAMMER'S NAME
309	(135)	CHARACTER	8	MJD59NPR	PROGRAMMER'S ROOM NUMBER
317	(13D)	CHARACTER	8	MJD59NPD	PROGRAMMER'S DEPT NUMBER
325	(145)	CHARACTER	8	MJD59NPB	PROGRAMMER'S BUILDING NUMBER
333	(14D)	CHARACTER	8	MJD59NR1	RESERVED
341	(155)	CHARACTER	8	MJD59NR2	RESERVED
352	(160)	FIXED	4		
	....	....		MJDFIXD	"MJDSTART,*-MJDSTART,C'X'"
VARIABLE PART OF THE MJD					
352	(160)	FIXED	4	MJDTEXTU	TEXT UNITS
BDT TEXT UNIT KEY VALUES NON-GENERIC KEY VALUES (MAY BE SPECIFIED ON SOURCE AND DESTINATION - SHOULD BE UNIQUE FROM DYNAMIC ALLOCATION KEYWORD VALUES)					
	....	...1		BTUMNNG	"1" MINIMUM NON GENERIC KEY VALUE
KEYS 200-220 ARE FOR USE BY THE USER ONLY.					
	1111	1..		BTUPRFX	"248" TSO USER DSN PREFIX
	1111	1..1		BTUSECP	"249" RACF PASSWORD PARAMETER
	1111	1.1.		BTUSECG	"250" RACF GROUP PARAMETER
	1111	1.11		BTUSECU	"251" RACF USER PARAMETER
	1111	11..		BTULOC	"252" LOCATION
	1111	11.1		BTUDAP	"253" DAP
	1111	111.		BTUUSER	"254" USER PARAMETER
	1111	1111		BTUBDTNQ	"255" BDT DATA SET ENQUEUE TYPE
352	(160)	FIXED	4	BTUMXNG	"256" MAXIMUM NON GENERIC KEY VALUE
GENERIC KEY VALUES (MAY BE SPECIFIED ONLY ONCE PER TRANSACTION)					
352	(160)	FIXED		BTUMNG	"257" MINIMUM GENERIC KEY VALUE
352	(160)	FIXED		BTUJOB	"257" JOB NAME
352	(160)	FIXED		BTUACCT	"258" ACCOUNTING PARAMETERS
352	(160)	FIXED		BTUPGMR	"259" PROGRAMMER NAME
352	(160)	FIXED		BTUNETID	"260" NET ID
352	(160)	FIXED		BTUNETHC	"261" NET HOLD COUNT
352	(160)	FIXED		BTUNETRL	"262" NET RELEASE
352	(160)	FIXED		BTUPRTY	"263" JOB PRIORITY
352	(160)	FIXED		BTUTIME	"264" JOB TIME LIMIT
352	(160)	FIXED		BTUGMJD	"265" USER SPECIFIED GMJD LIBRARY
352	(160)	FIXED		BTUMSGCL	"266" MESSAGE CLASS
352	(160)	FIXED		BTUHOLD	"267" JOB HOLD
352	(160)	FIXED		BTUFAIL	"268" FAILURE OPTION
352	(160)	FIXED		BTUDUMP	"269" DUMP OPTION
352	(160)	FIXED		BTUNETCN	"270" NORMAL NET CONDITIONAL RELEASE
352	(160)	FIXED		BTUNETCA	"271" ABNORMAL NET CONDITIONAL RELEASE
352	(160)	FIXED		BTUCSOPT	"272" COMPRESSION OPTION
352	(160)	FIXED		BTUSYSTEM	"273" BDT SUBSYSTEM ID
352	(160)	FIXED		BTUDEFU	"274" RACF DEFAULT USER
352	(160)	FIXED		BTUDEFG	"275" RACF DEFAULT
352	(160)	FIXED		BTUDEFPP	"276" RACF DEFAULT PASSWORD
KEYS 491-511 ARE FOR USE BY THE USER ONLY.					
	....	....		BTURACP0	"0" RACF PASSWORD 'OPEN' CODE
	....	...1		BTURACP1	"1" RACF PASSWORD 'ENCRYPT' CODE
	....	..1.		BTURACP2	"2" RACF PASSWORD 'IN CLEAR' CODE

352	(160)	FIXED	BTUMXG	"512" MAXIMUM GENERIC KEY VALUE
-----	-------	-------	--------	------------------------------------

SPECIAL KEY VALUES				
352	(160)	BITSTRING	BTUEOTU	"X'FFFF'" END OF TEXT UNITS

D.A AND BDT TEXT UNIT PARAMETER VALUE EQUATES				
	....	1...	BTUNQSHR	"X'08'" BDTENQ(SHR)
	....	...1	BTUNQOLD	"X'01'" BDTENQ(OLD)
	....	...1	BTUNQEXC	"BTUNQOLD" BDTENQ(EXC)
	1...	....	BTUCSNJE	"X'80'" CSOPT(NJEDUP NJE)
	.1..	....	BTUCSREP	"X'40'" CSOPT(REPDUP)
	.1..	....	BTUCSDUP	"BTUCSREP" CSOPT(DUP)
	....	..11	BTUDEN0	"X'03'" DEN(0) (7 TRACK, 200 BPI)
	.1..	..11	BTUDEN1	"X'43'" DEN(1) (7 TRACK, 556 BPI)
	1...	..11	BTUDEN2	"X'83'" DEN(2) (7/9 TRACK, 800 BPI)
	11..	..11	BTUDEN3	"X'C3'" DEN(3) (9 TRACK, 1600 BPI)
	11.1	..11	BTUDEN4	"X'D3'" DEN(4) (9 TRACK, 6250 BPI)
	....	...1	BTUUNCAT	"X'01'" DISP(UNCATLG)
	....	..1.	BTUCATAL	"X'02'" DISP(CATLG)
	....	..1.	BTUCATLG	"X'02'" DISP(CATLG)
	....	..1.	BTUDELET	"X'04'" DISP(DELETE)
	....	1...	BTUKEEP	"X'08'" DISP(KEEP)
352	(160)	BITSTRING	BTUPO	"X'0200'" DSORG(PO)
352	(160)	BITSTRING	BTUPS	"X'4000'" DSORG(PS)
	....	...1	BTUNL	"X'01'" LABEL(NL)
	....	..1.	BTUSL	"X'02'" LABEL(SL)
	....	..1.	BTUNSL	"X'04'" LABEL(NSL)
	....	1.1.	BTUSUL	"X'0A'" LABEL(SUL)
	....	...1	BTUBLP	"X'10'" LABEL(BLP)
	..1.	...1	BTULTM	"X'21'" LABEL(LTM)
	.1..	....	BTUAL	"X'40'" LABEL(AL)
	.1..	1...	BTUAUL	"X'48'" LABEL(AUL)
352	(160)	BITSTRING	BTULRECX	"X'8000'" LRECL(X)
	1...	....	BTUNETCD	"X'80'" NETCOND(DECREMENT)
	.1..	....	BTUNETCF	"X'40'" NETCOND(FLUSH)
	.1..	....	BTUNETCR	"X'20'" NETCOND(RETAIN)
	....	..1.	BTURECMR	"X'02'" RECFM(M)
	....	..1.	BTURECR	"X'02'" RECFM(R)
	....	..1.	BTURECA	"X'04'" RECFM(A)
	....	..1.	BTURECG	"X'04'" RECFM(G)
	....	1...	BTURECS	"X'08'" RECFM(S)
	...1	....	BTURECB	"X'10'" RECFM(B)
	.1..	....	BTURECD	"X'20'" RECFM(D)
	..1.	....	BTURECT	"X'20'" RECFM(T)
	.1..	....	BTURECV	"X'40'" RECFM(V)
	1...	....	BTURECF	"X'80'" RECFM(F)
	11..	....	BTURECU	"X'C0'" RECFM(U)
	....	..1.	BTUALX	"X'02'" ALX
	....	..1.	BTUMXIG	"X'04'" MXIG
	....	1...	BTUCONTG	"X'08'" CONTIG
	....	...1	BTUOLD	"X'01'" OLD
	....	..1.	BTUMOD	"X'02'" MOD
	....	..1.	BTUNEW	"X'04'" NEW
	....	1...	BTUSHR	"X'08'" SHR
	...1	..11	BTUTRTC	"X'13'" TRTCH(C)
	.1..	..11	BTUTRTE	"X'23'" TRTCH(E)
	..1.	1.11	BTUTRTET	"X'2B'" TRTCH(ET)
	..11	1.11	BTUTRTT	"X'3B'" TRTCH(T)

CROSS REFERENCE			
NAME	HEX OFFSET	HEX VALUE	LEVEL
BTUACCT	160	102	2
BTUAL	160	40	2
BTUALX	160	2	2
BTUAUL	160	48	2
BTUBDTNQ	160	FF	2
BTUBLP	160	10	2
BTUCATAL	160	2	2
BTUCATLG	160	2	2
BTUCONTG	160	8	2
BTUCSDUP	160	40	2

BTUCSNJE	160	80	2
BTUCSOPT	160	110	2
BTUCSREP	160	40	2
BTUDAP	160	FD	2
BTUDEFB	160	113	2
BTUDEFP	160	114	2
BTUDEFU	160	112	2
BTUDELET	160	4	2
BTUDEN0	160	3	2
BTUDEN1	160	43	2
BTUDEN2	160	83	2
BTUDEN3	160	C3	2
BTUDEN4	160	D3	2
BTUDUMP	160	10D	2
BTUE0TU	160	FFFF	2
BTUFAIL	160	10C	2
BTUGMJD	160	109	2
BTUHOLD	160	10B	2
BTUJOB	160	101	2
BTUKEEP	160	8	2
BTULOC	160	FC	2
BTULRECX	160	8000	2
BTULTM	160	21	2
BTUMNG	160	101	2
BTUMNNG	160	1	2
BTUMOD	160	2	2
BTUMSGCL	160	10A	2
BTUMXG	160	200	2
BTUMXIG	160	4	2
BTUMXNG	160	100	2
BTUNETCA	160	10F	2
BTUNETCD	160	80	2
BTUNETCF	160	40	2
BTUNETCN	160	10E	2
BTUNETCR	160	20	2
BTUNETHC	160	105	2
BTUNETID	160	104	2
BTUNETRL	160	106	2
BTUNEW	160	4	2
BTUNL	160	1	2
BTUNQEXC	160	1	2
BTUNQOLD	160	1	2
BTUNQSHR	160	8	2
BTUNSL	160	4	2
BTUOLD	160	1	2
BTUPGMR	160	103	2
BTUPO	160	200	2
BTUPRFX	160	F8	2
BTUPRTY	160	107	2
BTUPS	160	4000	2
BTURACP0	160	0	2
BTURACP1	160	1	2
BTURACP2	160	2	2
BTURECA	160	4	2
BTURECB	160	10	2
BTURECD	160	20	2
BTURECF	160	80	2
BTURECG	160	4	2
BTURECM	160	2	2
BTURECR	160	2	2
BTURECS	160	8	2
BTURECT	160	20	2
BTURECU	160	C0	2
BTURECV	160	40	2
BTUSECG	160	FA	2
BTUSECP	160	F9	2
BTUSECU	160	FB	2
BTUSHR	160	8	2
BTUSL	160	2	2
BTUSUL	160	A	2
BTUSYSTM	160	111	2
BTUTIME	160	108	2
BTUTRTC	160	13	2
BTUTRTE	160	23	2
BTUTRTET	160	2B	2
BTUTRTT	160	3B	2
BTUUNCAT	160	1	2
BTUSER	160	FE	2
MJDBJNM	59		2
MJDBJNO	59		2
MJDBTCH	57	3	2
MJDBYTES	A4		2

MJDCKDEF	12	24	2
MJDCNDD	59		2
MJDCP	12	C	2
MJDCPULN	C0	B8	2
MJDDAP	2D		2
MJDDDRS	59	0	2
MJDEXECD	CC	9C	2
MJDFCT	57	6	2
MJDFIXD	160	0	2
MJDFLAG1	81		2
MJDFRCID	C0		2
MJDFRCP	E	C	2
MJDFRCPD	C		2
MJDFRCPF	BC		2
MJDFRCPL	E		2
MJDFRCPU	B8		2
MJDFRDAP	2D		2
MJDFRLOC	1D		2
MJDFRNTU	82		2
MJDFROM	AB	40	2
MJDFRVSQ	A9	0	2
MJDFXDLN	8		2
MJDGRPID	E4		2
MJDHOLD	81	20	2
MJDID	0	D4D1	2
MJDJCLS	59		2
MJDJES	57	2	2
MJDJESJN	D8		2
MJDJESNR	DC		2
MJDJMC	57	7	2
MJDJOBNM	14		2
MJDJSD	90		2
MJDJSINF	DC		2
MJDJST	8C		2
MJDL0C	1D		2
MJDLOG	57	5	2
MJDMCS	57	4	2
MJDMCSA	75	5A	2
MJDMCSI	59		2
MJDNETHC	86		2
MJDNETID	D0		2
MJDNFLG1	EC	0	2
MJDNF1R1	EC	20	2
MJDNF1R2	EC	10	2
MJDNF1R3	EC	8	2
MJDNF1R4	EC	4	2
MJDNF1R5	EC	2	2
MJDNF1R6	EC	1	2
MJDNJ0B	EC	80	2
MJDNSOUT	EC	40	2
MJDPRTY	1C		2
MJDRDEV	57	8	2
MJDRESV1	AC		2
MJDTEXTU	160		2
MJDTIME	88		2
MJDT0	AB	80	2
MJDT0CID	CC		2
MJDT0CP	12	10	2
MJDT0CPD	10		2
MJDT0CPF	C8		2
MJDT0CPL	12		2
MJDT0CPU	C4		2
MJDTODAP	35		2
MJDT0FRM	AB	0	2
MJDT0FR1	AB	20	2
MJDT0FR2	AB	10	2
MJDT0FR3	AB	8	2
MJDT0FR4	AB	4	2
MJDT0FR5	AB	2	2
MJDT0FR6	AB	1	2
MJDT0LOC	25		2
MJDTONTU	84		2
MJDTOTLN	A		2
MJDT0VSQ	AA	0	2
MJDTSO	57	1	2
MJDUFLG1	DA		2
MJDUFLG2	DB		2
MJDUSER	57	80	2
MJDUSID	59		2
MJDVER#	4	F2F0	2
MJDXALL	75	47	2
MJDXBSI	47	0	2

MJDXBSN	4F	0	2
MJDXCODE	79		2
MJDXDDN	59		2
MJDXEND	75	79	2
MJDXFL1	58	0	2
MJDXHDR	3D	E7D6	2
MJDXLEN	45	3C	2
MJDXMCL	58	80	2
MJDXOID	75	3D	2
MJDXPD	A0		2
MJDXPRTY	A8		2
MJDXPT	9C		2
MJDXRD2	61	0	2
MJDXRD3	65	0	2
MJDXREL	41	F1F0	2
MJDXRS1	69	0	2
MJDXRS2	6D	0	2
MJDXRU1	71	0	2
MJDXRU2	75	0	2
MJDXSD	98		2
MJDXST	94		2
MJDXSTD	98	94	2
MJDXTYP	57	0	2
MJDX1R1	58	40	2
MJDX1R2	58	20	2
MJDX1R3	58	10	2
MJDX1R4	58	8	2
MJDX1R5	58	4	2
MJDX1R6	58	2	2
MJDX1R7	58	1	2
MJD59JB	ED	D1C2	2
MJD59NAM	F9		2
MJD59NAN	F1		2
MJD59NJT	ED		2
MJD59NPB	145		2
MJD59NPD	13D		2
MJD59NPN	121		2
MJD59NPR	135		2
MJD59NR1	14D		2
MJD59NR2	155		2
MJD59NTD	109		2
MJD59NUI	101		2
MJD59NUM	EF		2
MJD59OP	ED	D6D7	2
MJD59XQN	111		2
MJD59XQU	119		2



## Chapter 11. Resident Logical Units Table – RLT

The resident logical units table (RLT) contains information about all the remote nodes with which your node can communicate, as well as information about your own node. There is one entry for each SNA session and for each BDT node defined by the BDTNODE initialization statement. Each entry for a session is associated with an entry for a node.

<b>Function:</b>	The RLT is used during session establishment to determine whether a node is defined in your network, and to access the session-related control blocks.
<b>Macro ID:</b>	BDTDRLT
<b>DSECT name:</b>	BDTSTART
<b>Created by:</b>	BDTINR2, at BDT initialization
<b>Size:</b>	Hex 54 bytes
<b>Pointed to by:</b>	LCBRLT, LCTRLT, and TVTRLTTB (beginning of session entries), TVTRSTPU (beginning of node entries) RLTNLPTR in the node RLT points to the corresponding session RLT entry; RLTNLPTR in the session RLT points to the corresponding node RLT entry.
<b>Location:</b>	The BDT address space

OFFSETS	TYPE	LENGTH	NAME	DESCRIPTION
RESIDENT LOGICAL UNITS TABLE MAPPING MACRO CHANGE ACTIVITY \$L1 = 2103400,HBD2103,840606,KDP1 REL 2.0 RESIDENT BDT LINE/NODE LOGICAL UNITS TABLE ENTRY				
0	(0)	CHARACTER 4	RLTHDR	CONTROL BLOCK ACRONYM
4	(4)	CHARACTER 4	RLTVER	VERSION RELEASE ID
8	(8)	ADDRESS 2	RLTLEN	LENGTH OF RLT SECTION
10	(A)	FIXED 2	RLTRSVD4	RESERVED
12	(C)	CHARACTER 8	RLTNAME	LINE/NODE DDNAME
	....	1...	RLTPUNLN	"8" LENGTH OF BDT NODE NAME
20	(14)	CHARACTER 8	RLTPSWDR	RECEIVE PASSWORD IF A NODE ENTRY
	...1	.1..	RLTNODE	"RLTPSWDR" NODE NAME IF A LINE ENTRY
28	(1C)	CHARACTER 8	RLTPSWDS	SEND PASSWORD IF A NODE ENTRY
36	(24)	CHARACTER 8	RLTLMODE	LOGMODE NAME
44	(2C)	ADDRESS 4	RLTLCTAD	LU LCTUNITS ADDRESS
48	(30)	ADDRESS 4	RLTNLPTR	MATCHING NODE/LINE RLT ADDR
52	(34)	ADDRESS 1	RLTNLU	TOTAL NUMBER OF LUS
53	(35)	ADDRESS 1	RLTCOMLU	NUMBER OF 'COM' LUS
54	(36)	FIXED 2	RLTACTLU	ACTIVE VLU COUNT
56	(38)	FIXED 4	RLTSF	BDT SELECTABLE FEATURES
60	(3C)	FIXED 2	RLTBLK	BUFSIZE
	1111	1111	RLTENDC	"X'FF'" END OF LIST CHARACTER.
RLTFLAG1 ENTRY FLAG DEFINITIONS				
62	(3E)	BITSTRING 1	RLTFLAG1	ENTRY FLAG BITS
	1...	....	RLTNJE	"BIT0" NODE TYPE IS NJE
	.1..	....	RLTQPEND	"BIT1" QUIESCE IS PENDING FOR THIS NODE
	..1.	....	RLTACT	"BIT2" LINE/NODE CURRENTLY ACTIVE
	...1	....	RLTLINE	"BIT3" SNA LINE ENTRY
	....	1...	RLTLOCAL	"BIT4" TYPE=LOCAL (RELATIONSHIP)
	....	.1..	RLTFL1R3	"BIT5" RESERVED

		.... ..1.		RLTSIGN	"BIT6" AUTO LOGON (AUTO START)
		.... ...1		RLTFL1R4	"BIT7" RESERVED
RLTFLAG2 ENTRY FLAG DEFINITIONS					
63	(3F)	BITSTRING	1	RLTFLAG2	ENTRY FLAG BITS
		1... ....		RLTFL2R1	"BIT0" RESERVED
		.1.. ....		RLTFL2R2	"BIT1" RESERVED
		..1. ....		RLTFL2R3	"BIT2" RESERVED
		...1 ....		RLTFL2R4	"BIT3" RESERVED
		.... 1...		RLTFL2R5	"BIT4" RESERVED
		.... .1..		RLTFL2R6	"BIT5" RESERVED
		.... ..1.		RLTFL2R7	"BIT6" RESERVED
		.... ...1		RLTOWNSY	"BIT7" NODE OWNER IS SYSTEM
64	(40)	FIXED	2	RLTCKPT	8K CKPT INTERVAL
66	(42)	FIXED	2	RLTBUFNO	VLU PACING WINDOW
RLTCSOPT COMPRESSION FLAG DEFINITIONS					
68	(44)	BITSTRING	1	RLTCSOPT	COMPRESSION OPTION FLAG
		1... ....		RLTCNDUP	"BIT0" NJE DUPLICATE COMPRESSION
		.1.. ....		RLTCRDUP	"BIT1" REPEATED DUP. COMPRESSION
		..1. ....		RLTCSOR1	"BIT2" RESERVED
		...1 ....		RLTCSOR2	"BIT3" RESERVED
		.... 1...		RLTCSOR3	"BIT4" RESERVED
		.... .1..		RLTCSOR4	"BIT5" RESERVED
		.... ..1.		RLTCSOR5	"BIT6" RESERVED
		.... ...1		RLTCSOR6	"BIT7" RESERVED
RLTASRFG FLAG DEFINITIONS					
69	(45)	BITSTRING	1	RLTASRFG	ASR ENABLED
		1... ....		RLTASRON	"BIT0" ASR ENABLED FLAG
		.1.. ....		RLTASRR1	"BIT1" RESERVED
		..1. ....		RLTASRR2	"BIT2" RESERVED
		...1 ....		RLTASRR3	"BIT3" RESERVED
		.... 1...		RLTASRR4	"BIT4" RESERVED
		.... .1..		RLTASRR5	"BIT5" RESERVED
		.... ..1.		RLTASRR6	"BIT6" RESERVED
		.... ...1		RLTASRR7	"BIT7" RESERVED
70	(46)	FIXED	2	RLTLIMIT	RESTART LIMIT
72	(48)	ADDRESS	1	RLTLUFR	NUMBER OF LU'S FENCED 'FROM'
73	(49)	ADDRESS	1	RLTLUTO	NUMBER OF LU'S FENCED 'TO'
74	(4A)	BITSTRING	1	RLTFRCNT	FROM LU COUNT
75	(4B)	BITSTRING	1	RLTTOCNT	TO LU COUNT
USER FLAG DEFINITIONS					
76	(4C)	BITSTRING	1	RLTFLAGU	USER FLAGS
		1... ....		RLTFLAR1	"BIT0" RESERVED
		.1.. ....		RLTFLAR2	"BIT1" RESERVED
		..1. ....		RLTFLAR3	"BIT2" RESERVED
		...1 ....		RLTFLAR4	"BIT3" RESERVED
		.... 1...		RLTFLAR5	"BIT4" RESERVED
		.... .1..		RLTFLAR6	"BIT5" RESERVED
		.... ..1.		RLTFLAR7	"BIT6" RESERVED
		.... ...1		RLTFLAR8	"BIT7" RESERVED
77	(4D)	BITSTRING	1	RLTRSVU7	RESERVED
80	(50)	FIXED	4	RLTRSDV5	RESERVED
84	(54)	FIXED	4	RLTEND	RESIDENT BDT ENTRY END
84	(54)	CHARACTER	1	RLTSIZE	RESIDENT BDT ENTRY SIZE

## Chapter 12. Sequential Transfer Data Area – SEQ

The SEQ is the data CSECT used by the SEQ dynamic application program (DAP) in the file-to-file copying of sequential data sets.

<b>Function:</b>	The SEQ is used as a work area in the file-to-file copying of sequential data sets.
<b>Macro ID:</b>	BDTDSEQ
<b>DSECT name:</b>	BDTSEQD
<b>Created by:</b>	BDTSEQD
<b>Size:</b>	Hex 84E bytes
<b>Location:</b>	Subpool 251

DATA CSECT FOR BDTSEQ					
	LOCAL DATA SET CONTROL BLOCK HEADER				
0	(0) CHARACTER 4	SEQHDR	CONTROL BLOCK ACRONYM SEQ		
4	(4) CHARACTER 4	SEQREL	VERSION RELEASE ID		
8	(8) ADDRESS 2	SEQLEN	LENGTH OF SEQ CONTROL BLOCK		
LENGTH FIELDS					
10	(A) ADDRESS 2	SEQLENCK	LENGTH OF CHECKPOINT RECORD		
12	(C) ADDRESS 2	SEQDBLEN	LENGTH OF DCB		
14	(E) ADDRESS 2	SEQRSVD1	RESERVED		
I/O BUFFER DEFINITION					
16	(10) ADDRESS 4	SEQBUFAD	I/O BUFFER ADDRESS		
20	(14) ADDRESS 4	SEQBUFSZ	I/O BUFFER SIZE		
24	(18) ADDRESS 4	SEQEOBAD	END OF BLOCK ADDRESS		
28	(1C) ADDRESS 4	SEQNLRAD	ADDR OF NEXT LOGICAL RECORD		
32	(20) ADDRESS 4	SEQLRWRT	LOGICAL RECORDS WRITTEN		
36	(24) BITSTRING 1	SEQRSVU1	RESERVED		
LOCAL DATA SET RECORDING FLAG DEFINITION					
39	(27) BITSTRING 1	SEQRECFM	LOCAL DATA SET RECORDING FORMAT		
	1... ..	SEQFECR1	"BIT0" RESERVED		
	.1... ..	SEQFECR2	"BIT1" RESERVED		
	..1. ....	SEQFMBLK	"BIT2" BLOCKED RECORDS		
	...1 ....	SEQFMVL	"BIT3" VARIABLE LENGTH RECORDS		
	.... 1...	SEQFMUR	"BIT4" UNDEFINED RECORDS		
	.... .1..	SEQFECR3	"BIT5" RESERVED		
	.... ..1.	SEQFECR4	"BIT6" RESERVED		
	.... ...1	SEQFECR5	"BIT7" RESERVED		
40	(28) ADDRESS 4	SEQRSVD2	RESERVED		
CHECKPOINT DATA					
44	(2C) FIXED 4	SEQCKPTD	CHECKPOINT DATA AREA		
44	(2C) ADDRESS 2	SEQCKLEN	LENGTH OF CHECKPOINT RECORD		
46	(2E) ADDRESS 2	SEQCKNLR	NEXT LOGICAL RECORD DISPLACEMENT		
48	(30) ADDRESS 4	SEQCKNOT	BSAM NOTE INFORMATION		
52	(34) ADDRESS 4	SEQCKCLR	CURRENT LOGICAL RECD NUMBER		
CHECKPOINT FLAG DEFINITION					
56	(38) BITSTRING 1	SEQCKFLG	CHECKPOINT FLAGS		
	1... ..	SEQQFCKPT	"BIT0" CHECKPOINT OPTION SELECTED		
	.1... ..	SEQFCKIB	"BIT1" CURRENT BLOCK IS INCOMPLETE		
	..1. ....	SEQFCKSO	"BIT2" DEST IS SYSOUT DATA		

		...1 ....		SEQFCKPD	SET
		.... 1...		SEQFCKDD	"BIT3" DESTINATION IS MEMBER OF PDS
		.... .1..		SEQFCFR1	"BIT4" DESTINATION IS A DUMMY DS
		.... ..1.		SEQFCFR2	"BIT5" RESERVED
		.... ...1		SEQFCFR3	"BIT6" RESERVED
57	(39)	BITSTRING	1	SEQCKRU2	RESERVED
60	(3C)	ADDRESS	4	SEQCKRD3	RESERVED
		..1. 11..		SEQCKREC	CHECKPOINT RECORD
64	(40)	FIXED	4	SEQCKTEM	FULLWORD ALIGNMENT
NEXT VALUE REPRESENTS ACTUAL CHECKPOINT AREA ALLOCATED IN MJD					
		..1. .1..		SEQCKMAX	"36" MJD DEFAULT LENGTH
					MJDCKDEF
64	SUPERSCAN PARAMETER LIST				
	(40) FIXED	4		SEQSUPC	
64	DEFINITION OF SUPCFLG1 FIELD				
	(40) BITSTRING	1		SEQFLG1	FLAGS
	1... ....			SEQNUMR	"BIT0" PARAMETER MAY CONTAIN NUMERICS
	.1.. ....			SEQALPH	"BIT1" PARAMETER MAY CONTAIN ALPHABETICS
	..1. ....			SEQNATL	"BIT2" PARAMETER MAY CONTAIN NATIONAL CHARS
	...1 ....			SEQHEX	"BIT3" PARAMETER MAY CONTAIN HEX CHARACTERS
	.... 1...			SEQDSN	"BIT4" PARAMETER IS TO BE INTERPRETED AS DS
	.... .1..			SEQKEYW	"BIT5" KEYWORD PARAMETER IS PERMISSIBLE
	.... ..1.			SEQSUBL	"BIT6" SUBLIST PARAMETER IS PERMISSIBLE
	.... ...1			SEQRSCN	"BIT7" THIS IS A RE SCAN OF PREVIOUS PARM
DATA RESTRICTIONS EXIST					
	1111 1...			SEQRSTR	"SEQNUMR+SEQALPH+SEQNATL+SEQHEX+SEQDSN"
65	DEFINITION OF SUPCFLG2 FIELD				
	(41) BITSTRING	1		SEQFLG2	FLAGS
	1... ....			SEQBIN	"BIT0" TARGET AREA TYPE ATTRIBUTE IS BINARY
	.1.. ....			SEQPACK	"BIT1" TARGET AREA TYPE ATTRIBUTE IS 'PACKED DECIMAL'
	..1. ....			SEQSTDA	"BIT2" SUPRSCAN IS BEING INVOKED AS A STAND ALONE FUNCTION
	...1 ....			SEQQUOT	"BIT3" QUOTED STRING IS PERMISSIBLE
	.... 1...			SEQKERR	"BIT4" KEYWORD FOUND IN ERROR
	.... .1..			SEQF2R1	"BIT5" RESERVED
	.... ..1.			SEQF2R2	"BIT6" RESERVED
	.... ...1			SEQF2R3	"BIT7" RESERVED
66	LENGTH DEFINITIONS				
	(42) ADDRESS	1		SEQMINL	MINIMUM PARAMETER LENGTH
67	(43) ADDRESS	1		SEQMAXL	MAXIMUM PARAMETER LENGTH
68	(44) ADDRESS	1		SEQTRGL	LENGTH OF TARGET AREA
69	RESERVED				
	(45) ADDRESS	3		SEQRSV1	RESERVED

72	TARGET AREA ADDRESS (48)	ADDRESS	4	SEQTRGA	ADDRESS OF TARGET AREA
76	PARAMETER VALUES (4C)	ADDRESS	4	SEQMINV	MINIMUM PARAMETER VALUE
80	(50)	ADDRESS	4	SEQMAXV	MINIMUM PARAMETER VALUE
84	LENGTH OF THE KEYWORD AND PARAMETER (54)	ADDRESS	1	SEQKEYL	LENGTH OF KEYWORD
85	(55)	ADDRESS	1	SEQPRML	LENGTH OF PARAMETER
86	RESERVED (56)	ADDRESS	2	SEQRSV2	RESERVED
88	ADDRESSES OF THE KEYWORD AND PARAMETER (58)	ADDRESS	4	SEQKEYA	ADDRESS OF KEYWORD
92	(5C)	ADDRESS	4	SEQPRMA	ADDRESS OF PARAMETER
96	ADDITIONAL INFORMATION (60)	ADDRESS	2	SEQDSNL	NUMBER OF DSN INDEX LEVELS
98	(62)	ADDRESS	2	SEQDSNG	RELATIVE GENERATION NUMBER
100	INPUT CONSOLE MESSAGE AREA MAP BDT CONSOLE BUFFER AREAS CONSOLE MESSAGE AREA (64)	FIXED	4	CONSMESS	CONSOLE MESSAGE AREA
100	SUPERSCAN FLAG (64)	BITSTRING	1	CONSFLGS	FLAG (USED BY SUPRSCAN)
101	AUTHORITY LEVEL (65)	BITSTRING	1	CONSAUTH	AUTHORITY LEVEL
102	(66)	CHARACTER	4	CONSXHDR	CONTROL BLOCK ACRONYM
106	(6A)	CHARACTER	4	CONSXREL	VERSION ID
110	(6E)	ADDRESS	2	CONSXLEN	XOID LENGTH
112	(70)	BITSTRING	8	CONSXBSI	XACTION ORIGIN BDT SYS ID
120	(78)	BITSTRING	8	CONSXBSN	XACTION ORIGIN BDT SYS NAME
128	TRANSACTION ORIGIN TYPE (80)	BITSTRING	1	CONSXTYP	XACTION ORIGIN TYPE
		.... ..1		CONSTSO	"1" TSO USER
		.... ..1.		CONSJES	"2" JES CONSOLE
		.... ..11		CONSBTCH	"3" BATCH JOB
		.... ..1.		CONSMCS	"4" MCS CONSOLE
		.... ..1.1		CONSLQG	"5" JOB MESSAGE LOG
		.... ..11.		CONSFCT	"6" BDT FCT
		.... ..111		CONSJMC	"7" JES MESSAGE CLASS
		.... 1...		CONSRDEV	"8" BEGIN DEVELOPMENT
		1... ....		CONSUMER	DEFINED XOIDXTYP
					"128" BEGIN USER DEFINED XOIDXTYP
129	FLAG 1 DEFINITION (81)	BITSTRING	1	CONSXFL1	XOID FLAG 1
		1... ....		CONSXMCL	"BIT0" SUPPRESSION OF MESSAGE CLASS
		..1.. ....		CONSX1R1	"BIT1" RESERVED
		..1. ....		CONSX1R2	"BIT2" RESERVED
		...1 ....		CONSX1R3	"BIT3" RESERVED
		.... 1...		CONSX1R4	"BIT4" RESERVED
		.... ..1.		CONSX1R5	"BIT5" RESERVED
		.... ..1.		CONSX1R6	"BIT6" RESERVED
		.... ..1		CONSX1R7	"BIT7" RESERVED
130	MISCELLANEOUS INFORMATION (82)	CHARACTER	8	CONSXDDN	TRANSACTION ORIGIN DDNAME
130	(82)	CHARACTER	8	CONSUSID	TSO USERID
130	(82)	CHARACTER	8	CONSCNDD	JES CONSOLE DDNAME

130	(82)	CHARACTER	8	CONSJCLS	JES MESSAGE CLASS
130	(82)	CHARACTER	8	CONSBJNM	BATCH JOB NAME
130	(82)	ADDRESS	1	CONSMCSI	MCS CONSOLE ID
130	(82)	BITSTRING	2	CONSBJNO	BDT JOB NUMBER
130	(82)	BITSTRING	2	CONSDDRS	DDNAME
RESERVED FIELDS					
138	(8A)	BITSTRING	4	CONSXRD2	RESERVED
142	(8E)	BITSTRING	4	CONSXRD3	RESERVED
146	(92)	BITSTRING	4	CONSXRS1	RESERVED
150	(96)	BITSTRING	4	CONSXRS2	RESERVED
154	(9A)	BITSTRING	4	CONSXRU1	RESERVED
158	(9E)	BITSTRING	4	CONSXRU2	RESERVED
	1...	..11		CONSMCSA	"CONSMCSI+1,1,C'C'" MCS
	1.1.	..1.		CONSXEND	CONSOLE UX28 AUTH
	.11.	.11.		CONSXOID	END OF XOID
	.111	....		CONSXALL	XOID EQUATE
					BSI EQUATE
MISCELLANEOUS					
162	(A2)	BITSTRING	1	CONSIFLG	FLAGS
	1...	....		CNIFLR1	"BIT0" RESERVED
	.1..	....		CNIFLR2	"BIT1" RESERVED
	..1.	....		CNIFLR3	"BIT2" RESERVED
	...1	....		CNMULT	"BIT3" OPERAND SUBLIST
	....	1...		CNBLEOD	"BIT4" BLANK IS EOD
	....	.1..		CNIFLR4	"BIT5" RESERVED
	....	..1.		CNIFLR5	"BIT6" RESERVED
	....	...1		CNCOMMA	"BIT7" DELIMITER WAS COMMA
CONSOLE MESSAGE AREA INFORMATION					
163	(A3)	ADDRESS	1	CONCHRCT	CONSOLE MESSAGE AREA LENGTH
164	(A4)	ADDRESS	1	CONACTN	INPUT VERB ACTION CODE
165	(A5)	ADDRESS	1	CONSCAN	CURRENT SCAN DISPLACEMENT
RESERVED					
166	(A6)	ADDRESS	4	CONSRSD1	RESERVED
170	(AA)	ADDRESS	1	CONSRSD2	RESERVED
171	(AB)	ADDRESS	1	CONSRSS1	RESERVED
172	(AC)	ADDRESS	4	CONSRSS2	RESERVED
MESSAGE TEXT					
	.11.	.1..		CONSPRFX	CONS PREFIX LENGTH
176	(B0)	CHARACTER	1	CONMESSG	TEXT OF MESSAGE
	.11.	.1..		CONSAREA	CONS TOTAL LENGTH
MISCELLANEOUS DATA					
356	(164)	ADDRESS	4	SEQGSDAD	ADDRESS OF THE GSD
OPERATING REGISTERS					
360	(168)	FIXED	4	SEQREGS	OPERATING REGISTERS
360	(168)	ADDRESS	4	SEQR9	SECONDARY BASE REGISTER
364	(16C)	ADDRESS	4	SEQR10	PRIMARY BASE REGISTER
368	(170)	ADDRESS	4	SEQR11	ADDRESS OF DATA CSECT
372	(174)	ADDRESS	4	SEQR12	ADDRESS OF TVT
376	(178)	ADDRESS	4	SEQR13	ADDR OF REGISTER SAVE AREA
INTERNAL SAVE AREA AND WORK AREA					
380	(17C)	ADDRESS	4	SEQSVAR1	INTERNAL REGISTER SAVE AREA
396	(18C)	ADDRESS	4	SEQSVAR2	INTERNAL REGISTER SAVE AREA
404	(194)	BITSTRING	20	SEQSWORK	INTERNAL WORK AREA
REMOTE DATA SET I/O BUFFER INFORMATION					
424	(1A8)	ADDRESS	4	SEQRDSBA	REMOTE DATA SET I/O BUFFER ADDRESS
428	(1AC)	ADDRESS	4	SEQRDSBS	REMOTE DATA SET I/O BUFFER SIZE
432	(1B0)	ADDRESS	4	SEQDCBXL	DCB EXIT LIST
432	(1B0)	ADDRESS	1	SEQJBLTM	CODE = JFCB, LIST TERMINATOR

433	(1B1)	ADDRESS	3	SEQJFCBA	JFCB BUFFER ADDRESS
436	(1B4)	ADDRESS	2	SEQRTNCD	RETURN CODE
438	(1B6)	BITSTRING	1	SEQPADVL	PADDING VAL TO BE USED WHEN LRECL EXPANSION IS REQUIRED

439	PROCESSING FLAG 1 DEFINITION (1B7) BITSTRING 1				PROCESSING FLAGS
	1...	....		SEQF1LSR	"BIT0" SOURCE DATA SET IS LOCAL
	.1..	....		SEQF1LDS	"BIT1" DEST DATA SET IS LOCAL
	..1.	....		SEQF1CIP	"BIT2" CHECKPOINT IS PROCESS
	...1	....		SEQF1DXS	"BIT3" DATA TRANSFER STARTED
	....	1...		SEQF1DXC	"BIT4" DATA TRANSFER COMPLETE
	....	.1..		SEQF1CWM	"BIT5" CKPOINT WARNING MSG ISSUED
	....	..1.		SEQF1PRM	"BIT6" RECEIVER PROCESSING USER PARM ON FROM SIDE
	....	...1		SEQF1NCL	"BIT7" PREVENT CLOSE OF DATASET
	1...	....		SEQF1SND	"SEQF1LSR" WE ARE THE SENDER
	.1..	....		SEQF1RCV	"SEQF1LDS" WE ARE THE RECEIVER

440	PROCESSING FLAG 2 DEFINITION (1B8) BITSTRING 1				PROCESSING FLAGS
	1...	....		SEQF2PAD	"BIT0" PADDING VALUE SPECIFIED
	.1..	....		SEQMSGA	"BIT1" DISPLAY ALL MESSAGES
	..1.	....		SEQMSGS	"BIT2" DISPLAY STATUS MESSAGES ONLY
	...1	....		SEQF2RS1	"BIT3" RESERVED
	....	1...		SEQF2RS2	"BIT4" RESERVED
	....	.1..		SEQF2RS3	"BIT5" RESERVED
	....	..1.		SEQF2RS4	"BIT6" RESERVED
	....	...1		SEQF2RS5	"BIT7" RESERVED

441	(1B9)	CHARACTER	80	SEQJ2DEL	JES2 'DELETE' CONTROL CARD
-----	-------	-----------	----	----------	----------------------------

MESSAGES ISSUED BY BDTSEQ					
521	(209)	ADDRESS	1	SEQ00001	
522	(20A)	CHARACTER	12	SEQ01TXT	
534	(216)	CHARACTER	44	SEQ01DSN	
578	(242)	CHARACTER	7		
585	(249)	CHARACTER	2	SEQ01FX	
585	(249)			SEQ01VX	"SEQ01FX,2,C'C' "
585	(249)			SEQ01U	"SEQ01FX,2,C'C' "
585	(249)			SEQ01B	"SEQ01FX+1,1,C'C' "
587	(24B)	CHARACTER	7		
594	(252)	CHARACTER	5	SEQ01LRL	
599	(257)	CHARACTER	9		
608	(260)	CHARACTER	5	SEQ01BSZ	
608	(260)			SEQ01END	
613	(265)	ADDRESS	1	SEQ00002	
614	(266)	CHARACTER	30	SEQ02TXT	
614	(266)			SEQ02END	
644	(284)	ADDRESS	1	SEQ00003	
645	(285)	ADDRESS	38	SEQ03TXT	
645	(285)			SEQ03END	
683	(2AB)	ADDRESS	1	SEQ00004	
684	(2AC)	CHARACTER	8	SEQ04TXT	
692	(2B4)	CHARACTER	10	SEQ04RCD	0Y00613
702	(2BE)	CHARACTER	17		
719	(2CF)	CHARACTER	11	SEQ04XMT	

719	(2CF)	CHARACTER	11	SEQ04WRT
719	(2CF)			SEQ04END
730	(2DA)	CHARACTER	11	SEQXMTTD
741	(2E5)	CHARACTER	11	SEQWRTTN
752	(2F0)	ADDRESS	1	SEQ0005
753	(2F1)	CHARACTER	41	SEQ05TXT
753	(2F1)			SEQ05END
794	(31A)	ADDRESS	1	SEQ0006
795	(31B)	CHARACTER	26	SEQ06FXD
821	(335)	CHARACTER	1	SEQ06VAR
821	(335)			SEQ06END
1001	(3E9)	CHARACTER	6	SEQNOPRM
1007	(3EF)	ADDRESS	1	SEQ0007
1008	(3F0)	CHARACTER	53	SEQ07TXT
1053	(41D)	CHARACTER	8	SEQ07TEX
1061	(425)	CHARACTER	6	SEQ07RCD
1061	(425)			SEQ07END
1067	(42B)	ADDRESS	1	SEQ0008
1068	(42C)	CHARACTER	22	SEQ08TXT
1090	(442)	CHARACTER	10	SEQ08INC
1090	(442)	CHARACTER	10	SEQ08CMP
1090	(442)	CHARACTER	10	SEQ08ABT
1090	(442)			SEQ08END
1100	(44C)	CHARACTER	10	SEQINCOM
1110	(456)	CHARACTER	10	SEQCOMPL
1120	(460)	CHARACTER	10	SEQABORT
1130	(46A)	ADDRESS	1	SEQ0009
1131	(46B)	CHARACTER	45	SEQ09TXT
1176	(498)	CHARACTER	26	SEQ09TEX
1176	(498)			SEQ09END
1202	(4B2)	ADDRESS	1	SEQ0011
1203	(4B3)	CHARACTER	1	SEQ11TXT
1248	(4E0)	CHARACTER	41	SEQ11TEX
1248	(4E0)			SEQ11END
1289	(509)	ADDRESS	1	SEQ0012
1290	(50A)	CHARACTER	44	SEQ12TXT
1290	(50A)			SEQ12END
1334	(536)	ADDRESS	1	SEQ0013
1335	(537)	CHARACTER	47	SEQ13TXT
1382	(566)	CHARACTER	2	SEQ13FL
1384	(568)	CHARACTER	5	
1389	(56D)	CHARACTER	2	SEQ13CC
1391	(56F)	CHARACTER	8	
1399	(577)	CHARACTER	4	SEQ13SN
1403	(57B)	CHARACTER	7	
1410	(582)	CHARACTER	4	SEQ13ST
1410	(582)			SEQ13END
1414	(586)	ADDRESS	1	SEQ0014
1415	(587)	CHARACTER	29	SEQ14TXT
1444	(5A4)	CHARACTER	8	SEQ14TY
1444	(5A4)	CHARACTER	8	
1444	(5A4)	CHARACTER	8	
1444	(5A4)	CHARACTER	8	
1444	(5A4)	CHARACTER	8	SEQ14END
1452	(5AC)	ADDRESS	1	SEQ0015
1453	(5AD)	CHARACTER	35	SEQ15TXT
1453	(5AD)			SEQ15END
1488	(5D0)	ADDRESS	1	SEQ0016
1489	(5D1)	CHARACTER	48	SEQ16TXT
1537	(601)	CHARACTER	5	
1542	(606)	CHARACTER	2	SEQ16ER



1544	(608)	CHARACTER	6		
1550	(60E)	CHARACTER	2	SEQ16RS	
1550	(60E)			SEQ16END	
1552	(610)	ADDRESS	1	SEQ0017	
1553	(611)	CHARACTER	40	SEQ17TXT	
1553	(611)			SEQ17END	
1593	(639)	ADDRESS	1	SEQ0018	
1594	(63A)	CHARACTER	8	SEQ18TXT	
1602	(642)	CHARACTER	7	SEQ18TYP	
1609	(649)	CHARACTER	27		
1636	(664)	CHARACTER	13		
1649	(671)	CHARACTER	2	SEQ1815	
1649	(671)			SEQ18END	
1651	(673)	CHARACTER	7	SEQ18JFR	
1658	(67A)	CHARACTER	7	SEQ180BT	
1665	(681)	CHARACTER	7	SEQ18DEV	
1672	(688)	CHARACTER	7	SEQ18DCK	
1679	(68F)	ADDRESS	1	SEQ0019	
1680	(690)	CHARACTER	52	SEQ19TXT	
1680	(690)			SEQ19END	
1732	(6C4)	ADDRESS	1	SEQ0020	
1733	(6C5)	CHARACTER	48	SEQ20TXT	
1733	(6C5)			SEQ20END	
1784	(6F8)	ADDRESS	4	SEQRSVU4	RESERVED
1788	(6FC)	ADDRESS	4	SEQRSVD5	RESERVED

LOCAL DATA SET DCB					
DCB DDNAME=SEQLDDCB,DSORG=PS,MACRF=(RC,WC),EXLST=SEQDCBXL					
DATA CONTROL BLOCK					
1792	(700)	FIXED	4	SEQLCDCB	ORIGIN ON WORD BOUNDARY DIRECT ACCESS DEVICE INTERFACE
1792	(700)	BITSTRING	16		FDAD,DVTBL
1808	(710)	ADDRESS	4		KEYLE,DEVT,TRBAL COMMON ACCESS METHOD INTERFACE
1812	(714)	ADDRESS	1		BUFNO
1813	(715)	ADDRESS	3		BUFCB
1816	(718)	ADDRESS	2		BUFL
1818	(71A)	BITSTRING	2		DSORG
1820	(71C)	ADDRESS	4		IOBAD FOUNDATION EXTENSION
1824	(720)	BITSTRING	1		BFTEK,BFLN,HIARCHY
1825	(721)	ADDRESS	3		EODAD
1828	(724)	BITSTRING	1		RECFM
1829	(725)	ADDRESS	3		EXLST FOUNDATION BLOCK
1832	(728)	CHARACTER	8		DDNAME
1840	(730)	BITSTRING	1		OFLGS
1841	(731)	BITSTRING	1		IFLG
1842	(732)	BITSTRING	2		MACR BSAM BPAM QSAM INTERFACE
1844	(734)	BITSTRING	1		RER1
1845	(735)	ADDRESS	3		CHECK, GERR, PERR
1848	(738)	ADDRESS	4		SYNAD
1852	(73C)	FIXED	2		CIND1, CIND2
1854	(73E)	ADDRESS	2		BLKSIZE
1856	(740)	FIXED	4		WCPO, WCPL, OFFSR, OFFSW
1860	(744)	ADDRESS	4		IOBA
1864	(748)	ADDRESS	1		NCP
1865	(749)	ADDRESS	3		EOBR, EOBA, BSAM BPAM INTERFACE
1868	(74C)	ADDRESS	4		EOBW
1872	(750)	FIXED	2		DIRECT
1874	(752)	ADDRESS	2		LRECL
1876	(754)	ADDRESS	4		CNTRL, NOTE, POINT
1876	(754)	ADDRESS	4	SEQLDDCB	LOCAL DATA SET DCB

LIST-FORM MACROS					
ESTAE 0,MF=L ESTAE LIST					
MACDATE 80247					
1880	(758)	FIXED	4		
1880	(758)	ADDRESS	1	SEQUESTAE	FLAGS FOR TCB,PURGE,ASYNCH
1881	(759)	ADDRESS	3		STAE EXIT ROUTINE ADDR.

1884	(75C)	ADDRESS	4		PARM. LIST ADDR. NOT SPECIFIED
1888	(760)	ADDRESS	4		TCB NOT SPECIFIED
1892	(764)	ADDRESS	1		FLAGS
1893	(765)	ADDRESS	3		RESERVED
1896	(768)	ADDRESS	4		TOKEN VALUE AREA
	RDJFCB 0,MF=L READ JFCB LIST				
1900	(76C)	FIXED	4	SEQRDJFC	ALIGN LIST TO FULLWORD
1900	(76C)	ADDRESS	1		OPTION BYTE
1901	(76D)	ADDRESS	3		DCB ADDRESS
	OPEN 0,MF=L OPEN LIST				
1904	(770)	FIXED	4	SEQOPENL	ALIGN LIST TO FULLWORD
1904	(770)	ADDRESS	1		OPTION BYTE
1905	(771)	ADDRESS	3		DCB ADDRESS
	READ READDECB,SF,MF=L BSAM READ LIST				
1908	(774)	FIXED	4	SEQREADL	
1908	(774)	FIXED	4	READDECB	EVENT CONTROL BLOCK
1912	(778)	BITSTRING	1		TYPE FIELD
1913	(779)	BITSTRING	1		TYPE FIELD
1914	(77A)	ADDRESS	2		LENGTH
1916	(77C)	ADDRESS	4		DCB ADDRESS
1920	(780)	ADDRESS	4		AREA ADDRESS
1924	(784)	ADDRESS	4		RECORD POINTER WORD
	WRITE WRITDECB,SF,MF=L BSAM WRITE LIST				
1928	(788)	FIXED	4	SEQWRITL	
1928	(788)	FIXED	4	WRITDECB	EVENT CONTROL BLOCK
1932	(78C)	BITSTRING	1		TYPE FIELD
1933	(78D)	BITSTRING	1		TYPE FIELD
1934	(78E)	ADDRESS	2		LENGTH
1936	(790)	ADDRESS	4		DCB ADDRESS
1940	(794)	ADDRESS	4		AREA ADDRESS
1944	(798)	ADDRESS	4		RECORD POINTER WORD
	CLOSE 0,MF=L CLOSE LIST				
1948	(79C)	FIXED	4	SEQCLOSL	ALIGN LIST TO FULLWORD
1948	(79C)	ADDRESS	1		OPTION BYTE
1949	(79D)	ADDRESS	3		DCB ADDRESS
1952	JFCB BUFFER AREA				
(7A0)	FIXED	4	SEQJFCBF	JFCB BUFFER AREA	
	DEVTYPE RESPONSE AREA				
2128	(850)	FIXED	4	SEQDEVTA	DEVTYPE RESPONSE AREA
2128	(850)	CHARACTER	1	SEQDMODL	DEVICE MODEL CODE
2129	(851)	CHARACTER	1	SEQDOPTS	OPTIONAL FEATURES
2130	(852)	CHARACTER	1	SEQDVCLS	DEVICE CLASS
2131	(853)	CHARACTER	1	SEQUNTYT	UNIT TYPE
2132	(854)	FIXED	4	SEQDEVTB	MAXIMUM DEVICE/SYSTEM BLKSIZE
2132	(854)			SEQDEVTO	"SEQDMODL,4,C'F'" DEVICE TYPE
					WORD ZERO
	DSCB WORK AREA				
2136	(858)	BITSTRING	44	SEQF1DSN	DS NAME FOR OBTAIN
2180	(884)	BITSTRING	6	SEQF1VOL	VOL SER FOR OBTAIN
2186	(88A)	BITSTRING	140	SEQF1WRK	WORK AREA FOR OBTAIN
2328	(918)	FIXED	4		
2328	(918)	BITSTRING	16	SEQOBLST	OBTAIN PARM LIST
2328	(918)	ADDRESS	1	SEQOPCDE	OBTAIN OP CODE X'C1'
2329	(919)	ADDRESS	3		FLAG BYTES
2332	(91C)	ADDRESS	4	SEQF1DSP	DS NAME PTR FOR OBT
2336	(920)	ADDRESS	4	SEQF1VP	VOL PTR FOR OBTAIN
2340	(924)	ADDRESS	4	SEQWRKPT	OBTAIN WRK AREA PTR
2344	(928)	BITSTRING	1	SEQEMPFL	DATA SET EMPTY FLAG
	1... ..			SEQEMPTY	"BIT0" EMPTY DATA SET
2344	(928)			SEQEND	END OF CONTROL BLOCK
CROSS REFERENCE					
HEX      HEX					
NAME	OFFSET	VALUE	LEVEL		

CNBLE0D	A2	8	2
CNCOMMA	A2	1	2
CNIFLR1	A2	80	2
CNIFLR2	A2	40	2
CNIFLR3	A2	20	2
CNIFLR4	A2	4	2
CNIFLR5	A2	2	2
CNMULT	A2	10	2
CONACTN	A4		2
CONCHRCT	A3		2
CONMESSG	B0		2
CONSAREA	B0	64	2
CONSAUTH	65		2
CONSBJNM	82		2
CONSBJNO	82		2
CONSBTCH	80	3	2
CONSCAN	A5		2
CONSCNDD	82		2
CONSDDRS	82	0	2
CONSFCT	80	6	2
CONSFLGS	64		2
CONSIFLG	A2		2
CONSJCLS	82		2
CONSJES	80	2	2
CONSJMC	80	7	2
CONSLOG	80	5	2
CONSMCS	80	4	2
CONSMCSA	9E	83	2
CONSMCSI	82		2
CONSMESS	64		2
CONSPRFX	AC	64	2
CONSRDEV	80	8	2
CONSRSD1	A6		2
CONSRSD2	AA		2
CONSRSS1	AB		2
CONSRSS2	AC		2
CONSTS0	80	1	2
CONSUSER	80	80	2
CONSUSID	82		2
CONSXALL	9E	70	2
CONSXBSI	70	0	2
CONSXBSN	78	0	2
CONSXDDN	82		2
CONSXEND	9E	A2	2
CONSXFL1	81	0	2
CONSXHDR	66	E7D6	2
CONSXLEN	6E	3C	2
CONSXMCL	81	80	2
CONSXOID	9E	66	2
CONSXRD2	8A	0	2
CONSXRD3	8E	0	2
CONSXREL	6A	F1F0	2
CONSXRS1	92	0	2
CONSXRS2	96	0	2
CONSXRU1	9A	0	2
CONSXRU2	9E	0	2
CONSX TYP	80	0	2
CONSX1R1	81	40	2
CONSX1R2	81	20	2
CONSX1R3	81	10	2
CONSX1R4	81	8	2
CONSX1R5	81	4	2
CONSX1R6	81	2	2
CONSX1R7	81	1	2
READDECB	73C	0	2
SEQABORT	45C	C1C2	2
SEQALPH	40	40	2
SEQBIN	41	80	2
SEQBUFAD	10		2
SEQBUFSZ	14		2
SEQCKCLR	34		2
SEQCKFLG	38	0	2
SEQCKLEN	2C		2
SEQCKMAX	40	24	2
SEQCKNLR	2E		2
SEQCKNOT	30		2
SEQCKPTD	2C		2
SEQCKRD3	3C		2
SEQCKREC	3C	2C	2
SEQCKRU2	39	0	2
SEQCKTEM	40		2
SEQCLOSL	764		2

SEQCOMPL	452	C3D6	2
SEQDBLEN	C	58	2
SEQDCBXL	1B0		2
SEQDEVTA	818		2
SEQDEVTB	81C		2
SEQDEVT0	81C	818	2
SEQDMODL	818		2
SEQDOPTS	819		2
SEQDSN	40	8	2
SEQDSNG	62		2
SEQDSNL	60		2
SEQDVCLS	81A		2
SEQEMPFL	93C		2
SEQEMPTY	93C	80	2
SEQEND	93C	93D	2
SEQEOBAD	18		2
SEQESTAE	720		2
SEQFCFR1	38	4	2
SEQFCFR2	38	2	2
SEQFCFR3	38	1	2
SEQFCKDD	38	8	2
SEQFCKIB	38	40	2
SEQFCKPD	38	10	2
SEQFCKPT	38	80	2
SEQFCKSO	38	20	2
SEQFECD1	27	80	2
SEQFECD2	27	40	2
SEQFECD3	27	4	2
SEQFECD4	27	2	2
SEQFECD5	27	1	2
SEQFLGS1	1B7	0	2
SEQFLGS2	1B8	0	2
SEQFLG1	40	0	2
SEQFLG2	41	0	2
SEQFMBLK	27	20	2
SEQFMUR	27	8	2
SEQFMVL	27	10	2
SEQF1CIP	1B7	20	2
SEQF1CWM	1B7	4	2
SEQF1DSN	86E	0	2
SEQF1DSP	930		2
SEQF1DXC	1B7	8	2
SEQF1DXS	1B7	10	2
SEQF1LDS	1B7	40	2
SEQF1LSR	1B7	80	2
SEQF1RCV	1B7	40	2
SEQF1RS1	1B7	2	2
SEQF1RS2	1B7	1	2
SEQF1SND	1B7	80	2
SEQF1VOL	89A	0	2
SEQF1VP	934		2
SEQF1WRK	8A0	0	2
SEQF2PAD	1B8	80	2
SEQF2RS1	1B8	10	2
SEQF2RS2	1B8	8	2
SEQF2RS3	1B8	4	2
SEQF2RS4	1B8	2	2
SEQF2RS5	1B8	1	2
SEQF2R1	41	4	2
SEQF2R2	41	2	2
SEQF2R3	41	1	2
SEQGSDAD	164		2
SEQHDR	0	E2C5	2
SEQHEX	40	10	2
SEQINCOM	448	C9D5	2
SEQJBLTM	1B0		2
SEQJFCBA	1B1		1
SEQJFCBF	768	4040	2
SEQJ2DEL	1B9	615C	2
SEQKERR	41	8	2
SEQKEYA	58		2
SEQKEYL	54		2
SEQKEYW	40	4	2
SEQLCDCB	6C8		2
SEQLDDCB	71C	6C8	2
SEQLEN	8	93D	2
SEQLENCK	A	14	2
SEQLRWRT	20		2
SEQMAXL	43		2
SEQMAXV	50		2
SEQMINL	42		2
SEQMINV	4C		2

SEQMSGGA	1B8	40	2
SEQMSGGS	1B8	20	2
SEQNATL	40	20	2
SEQNLRAD	1C		2
SEQNOPRM	3E5	60D5	2
SEQNUMR	40	80	2
SEQOBLST	92C	0	2
SEQOPCDE	92C		2
SEQOPENL	738		2
SEQPACK	41	40	2
SEQPADVL	1B6	0	2
SEQPRMA	5C		2
SEQPRML	55		2
SEQQUOT	41	10	2
SEQRDJFC	734		2
SEQRDSBA	1A8		2
SEQRDSBS	1AC		2
SEQREADL	73C		2
SEQRECFM	27	0	2
SEQREGS	168		2
SEQREL	4	F1F0	2
SEQRSCN	40	1	2
SEQRSTR	40	F8	2
SEQRSVD1	E		2
SEQRSVD2	28		2
SEQRSVD5	6C4		2
SEQRSVU1	24	0	2
SEQRSVU4	6C0		2
SEQRSV1	45		2
SEQRSV2	56		2
SEQRTNCD	1B4		2
SEQR10	16C		2
SEQR11	170		2
SEQR12	174		2
SEQR13	178		2
SEQR9	168		2
SEQSAV01	820		2
SEQSTDA	41	20	2
SEQSUBL	40	2	2
SEQSUPC	40		2
SEQSVAR1	17C		2
SEQSVAR2	18C		2
SEQSWORK	194	0	2
SEQTRGA	48		2
SEQTRGL	44		2
SEQUNTYP	81B		2
SEQVOLSR	868	4040	2
SEQWRITL	750		2
SEQWRKPT	938		2
SEQWRTTN	2E1	E6D9	2
SEQXMTTD	2D6	E3D9	2
SEQ0001	209		2
SEQ0002	265		2
SEQ0003	284		2
SEQ0004	2AB		2
SEQ0005	2EC		2
SEQ0006	316		2
SEQ0007	3EB		2
SEQ0008	427		2
SEQ0009	466		2
SEQ0011	4AE		2
SEQ0012	505		2
SEQ0013	532		2
SEQ0014	582		2
SEQ0015	5A8		2
SEQ0016	5CC		2
SEQ0017	60C		2
SEQ0018	635		2
SEQ0019	68B		2
SEQ01B	249	24A	2
SEQ01BSZ	260	4040	2
SEQ01DSN	216	4040	2
SEQ01END	260	265	2
SEQ01FX	249	C6E7	2
SEQ01LRL	252	4040	2
SEQ01TXT	20A	C2C4	2
SEQ01U	249	249	2
SEQ01VX	249	249	2
SEQ02END	266	284	2
SEQ02TXT	266	C2C4	2
SEQ03END	285	2AB	2
SEQ03TXT	285	C2C4	2

SEQ04END	2CB	2D6	2
SEQ04RCD	2B4	4040	2
SEQ04TXT	2AC	C2C4	2
SEQ04WRT	2CB	E6D9	2
SEQ04XMT	2CB		2
SEQ05END	2ED	316	2
SEQ05TXT	2ED	C2C4	2
SEQ06END	331	3E5	2
SEQ06FXD	317	C2C4	2
SEQ06VAR	331	4040	2
SEQ07END	421	427	2
SEQ07RCD	421	4040	2
SEQ07TEX	419	40D9	2
SEQ07TXT	3EC	C2C4	2
SEQ08ABT	43E	C1C2	2
SEQ08CMP	43E		2
SEQ08END	43E	448	2
SEQ08INC	43E		2
SEQ08TXT	428	C2C4	2
SEQ09END	494	4AE	2
SEQ09TEX	494	40E2	2
SEQ09TXT	467	C2C4	2
SEQ11END	4DC	505	2
SEQ11TEX	4DC	40C9	2
SEQ11TXT	4AF	C2C4	2
SEQ12END	506	532	2
SEQ12TXT	506	C2C4	2
SEQ13CC	569	4040	2
SEQ13END	57E	582	2
SEQ13FL	562	4040	2
SEQ13SN	573	4040	2
SEQ13ST	57E	4040	2
SEQ13TXT	533	C2C4	2
SEQ14END	5A0	5A8	2
SEQ14TXT	583	C2C4	2
SEQ14TY	5A0		2
SEQ15END	5A9	5CC	2
SEQ15TXT	5A9	C2C4	2
SEQ16END	60A	60C	2
SEQ16ER	602	4040	2
SEQ16RS	60A	4040	2
SEQ16TXT	5CD	C2C4	2
SEQ17END	60D	635	2
SEQ17TXT	60D	C2C4	2
SEQ18DCK	684	C4C5	2
SEQ18DEV	67D	C4C5	2
SEQ18END	66D	66F	2
SEQ18JFR	66F	D9C4	2
SEQ18OBT	676	D6C2	2
SEQ18TXT	636	C2C4	2
SEQ18TYP	63E	4040	2
SEQ1815	66D		2
SEQ19END	68C	6C0	2
SEQ19TXT	68C	C2C4	2
WRITDECB	750	0	2

## Scheduler Interface Control Area CSECT – SICA

The scheduler interface control area (SICA) is a temporary work area. It is used with the move mode scheduler work area (SWA) manager to obtain a copy of a scheduler control block.

<b>Function:</b>	The SICA is used to manipulate MVS scheduler control blocks.
<b>Macro ID:</b>	BDTDSICA
<b>DSECT name:</b>	SICA
<b>Created by:</b>	BDTCKPT
<b>Size:</b>	Hex 100 bytes
<b>Pointed to by:</b>	BDTGRCPD

**Location:** Subpool 230

#### MAPS THE SCHEDULER INTERFACE CONTROL AREA

0	(0)	ADDRESS	4	SICALINK	POINTER TO NEXT SICA
4	(4)	CHARACTER	4	SICAID	CONTROL BLOCK IDENTIFIER
8	(8)	CHARACTER	4	SICAREL	VERSION/RELEASE IDENTIFIER
12	(C)	ADDRESS	2	SICALEN	LENGTH OF SICA
14	(E)	BITSTRING	1	SICAFLGS	FLAG BYTE
		1... ..		SICANFCP	"BIT0" SICA NOT FROM CELLPOOL
		.1.. ....		SICAFLG1	"BIT1" RESERVED
		.1. ....		SICAFLG2	"BIT2" RESERVED
		...1 ....		SICAFLG3	"BIT3" RESERVED
		.... 1...		SICAFLG4	"BIT4" RESERVED
		.... .1..		SICAFLG5	"BIT5" RESERVED
		.... ..1.		SICAFLG6	"BIT6" RESERVED
		.... ...1		SICAFLG7	"BIT7" RESERVED
15	(F)	FIXED	1	SICACBID	SWA CONTROL BLOCK ID
15	(F)	FIXED		SICASIZE	"256"
		111. .11.		SICAPOL	"230"
		.... ....		SICAHDR	POINTER TO NEXT SICA
16	(10)	CHARACTER	1	SICADATA	

#### SWA CONTROL BLOCK TARGET AREA

16	(10)	CHARACTER	176	SICATGT	SWA CONTROL BLOCK TARGET AREA
----	------	-----------	-----	---------	-------------------------------

#### SWA CONTROL BLOCK ACCESS PARAMETERS

		SICAMEPA DS CL(L 'SWAMMEPA ) MOVE MODE EXTERNAL PARAMETER AREA			
192	(C0)	CHARACTER	36	SICAQMPA	QUEUE MANAGER PARAMETER AREA
228	(E4)	CHARACTER	8	SICAMEPA	MOVE MODE EXTERNAL PARAMETER AREA
236	(EC)	CHARACTER	20		

## SNA Buffer Pool Control Block – SNBP

The SNA buffer pool control block (SNBP) is built as the result of a SNABUF initialization statement. For each buffer pool, storage is obtained at BDT initialization for an SNBP, extent entries, and buffers for the primary extent. Secondary extents are acquired dynamically. The SNBP contains information describing that buffer pool, including a pointer to each extent, the buffer size, the number of buffers in each extent, the maximum number of secondary extents, and the number of available buffers.

<b>Function:</b>	Provides information describing a buffer pool
<b>Macro ID:</b>	BDTDSNB
<b>DSECT name:</b>	SNBP
<b>Created by:</b>	INR2 via BDTXGTMN
<b>Size:</b>	Hex 60 bytes
<b>Accessed by:</b>	INR1, INR2, IQCP, SCBUF, SCMGR, SCOCT
<b>Location:</b>	BDT address space

#### SNA BUFFER POOL

MAPS THE SNA BUFFER POOL AND SNA INITIALIZATION  
CONTROL BLOCKS  
SNA BUFFER POOL CONTROL BLOCK

0	(0)	CHARACTER	4	SNBPID	CONTROL BLOCK ID
4	(4)	ADDRESS	4	SNBPNEXT	NEXT BUF POOL CONTROL BLOCK
8	(8)	ADDRESS	4	SNBPSize	BUFFER SIZE
12	(C)	ADDRESS	4	SNBPPXSZ	PRIMARY EXTENT SIZE

16	(10)	ADDRESS	4	SNPBSXSZ	SECONDARY EXTENT SIZE
20	(14)	ADDRESS	4	SNBPSXNO	NUMBER OF SECONDARY EXTENTS
24	(18)	ADDRESS	2	SNBPATF	ANTI THRASHING FACTOR (%)
26	(1A)	BITSTRING	1	SNBPFLG1	FLAGS
		1... ..		SNBPADL	"BIT0" AUTO DELETE SECONDARY EXTNS
27	(1B)	BITSTRING	1	SNBPRSD1	RESERVED FOR DEVELOPMENT
		BUFFER POOL STATISTICS			
28	(1C)	ADDRESS	4	SNBPTOTL	CURRENT SIZE OF BUFFER POOL
32	(20)	ADDRESS	4	SNBPINUS	CURRENT NUM OF BUF IN USE
36	(24)	ADDRESS	4	SNBPSEXT	CUR NUM OF SECONDARY EXTENTS
40	(28)	ADDRESS	4	SNBPDPLT	NUM OF TIMES BUF PL DEPLETED
44	(2C)	ADDRESS	4	SNBPMXSZ	MAXIMUM SIZE OF BUFFER POOL
48	(30)	ADDRESS	4	SNBPMXUS	MAX NUMBER OF BUFFER IN USE
52	(34)	ADDRESS	4	SNBPMXSE	MAX NUM OF SECONDARY EXTENTS
56	(38)	BITSTRING	1	SNBPSubI	SUBPOOL FOR SNA BUFFER POOLS
57	(39)	BITSTRING	1	SNBPRSD2	RESERVED FOR DEVELOPMENT
60	(3C)	ADDRESS	4	SNBPRSD3	RESERVED FOR DEVELOPMENT
		.... ..		SNBPFXD	LENGTH = L'SNBPFIXD
		EXTENT ENTRY			
64	(40)	ADDRESS	4	SNBPXPTR	POINTER TO THE EXTENT
68	(44)	ADDRESS	4	SNBPCNT	NUM OF AVAILABLE BUF IN THE EXTENT
72	(48)	FIXED	4	SNBPXNXT	ALIGN TO START OF NEXT ENT
		.1... ..		SNBPXENT	LENGTH = L'SNBXPENT
		SNA BUFFER POOL EXTENT			
0	(0)	ADDRESS	4	SNBPXSIZ	AMOUNT OF STORAGE OBTAINED FOR THIS EXTENT
4	(4)	ADDRESS	4		RESERVED
8	(8)	ADDRESS	4	SNBPXAVL	FIRST AVAILABLE BUFFER
12	(C)	ADDRESS	4	SNBPXQUC	QUEUE UPDATE COUNT
		.... 1...		SNBPXHDR	FIRST AVAILABLE BUFFER
16	(10)	ADDRESS	4	SNBPXFST	FIRST BUFFER IN THIS EXTENT
20	(14)	ADDRESS	4	SNBPXLST	LAST BUFFER IN THIS EXTENT
24	(18)	FIXED	4	SNBPXBUF	FIRST BUFFER IN THIS EXTENT
		.... ..		SNBPXPFX	LENGTH = L'SNBXPFX



## Chapter 13. Transfer Vector Table — TVT

The transfer vector table (TVT) is the primary control block of BDT. It includes:

- Pointers to the beginning of control block chains
- Addresses of general BDT routines
- Constants
- Initialization parameters from the OPTIONS statement.

<b>Function:</b>	The TVT is a central source of information for all BDT routines.
<b>Macro ID:</b>	BDTDTV
<b>DSECT name:</b>	BDTGRVT
<b>Loaded by:</b>	BDTINTK, during BDT initialization
<b>Size:</b>	Hex 7DD bytes
<b>Pointed to by:</b>	Register 12, JMLREG12, GSDTV, FCTTVPTR
<b>Location:</b>	BDTGRVT CSECT in BDTNUC

TVT HEADER FILES					
0	(0)	CHARACTER	4	TVTID	TVTABLE ID
4	(4)	CHARACTER	4	TVTVERS	TVTABLE VERSION ID
8	(8)	ADDRESS	2	TVTLNGTH	TVTABLE LENGTH
12	(C)	ADDRESS	4	TVTINDAT	BDTINIT DATE BDT STARTED 00YYDDDF
16	(10)	ADDRESS	4	TVTINTIM	BDTINIT TIME BDT STARTED HHMMSSSTH
20	(14)	CHARACTER	4	TVTRELN	BDT RELEASE NUMBER
ROUTINE ENTRY POINTS					
24	(18)	ADDRESS	4	TVTEPS	START OF ENTRY POINTS
24	(18)	ADDRESS	4	TVTASAVE	"V(ASAVEYES)"BDTGRSV ASAVE PROCESSING
28	(1C)	ADDRESS	4	TVTASVRT	"V(ASARETRN)"BDTGRSV ASAVE PROCESSING RETURN
RESOURCE MANAGEMENT					
32	(20)	ADDRESS	4	TVTADEQ	"V(RESMGMT)" BDTGRRQ RESOURCE MANAGEMENT
	..1.	....		TVTAENQ	"TVTADEQ" RESOURCE MANAGEMENT
	..1.	....		TVTATEST	"TVTADEQ" RESOURCE MANAGEMENT
GETMAIN/FREEMAIN ADDRESS					
36	(24)	ADDRESS	4	TVTAPTMN	"V(PUTMAINX)" BDTGRGM FREEMAIN
40	(28)	ADDRESS	4	TVTAGTMN	"V(GETMAINX)" BDTGRGM GETMAIN
44	(2C)	ADDRESS	4	TVTALLO	"V(BDTGRDA)" BDTGRDA ADDR OF DYNAM ALLOCAT RTN
QUICK CELL					
48	(30)	ADDRESS	4	TVTXBPL	"V(BDTXBPL)" BDTGRQC QUICK CELL SVCS BUILD POOL
52	(34)	ADDRESS	4	TVTXCPD	"V(BDTXCPD)" BDTGRQC QUICK CELL SVCS CPD ACCESS
56	(38)	ADDRESS	4	TVTXGCL	"V(BDTXGCL)" BDTGRQC QUICK CELL SVCS GET CELL
60	(3C)	ADDRESS	4	TVTXRCL	"V(BDTXRCL)" BDTGRQC QUICK CELL SVCS RETRN CELL
64	(40)	ADDRESS	4	TVTXDPL	"V(BDTXDPL)" BDTGRQC QUICK CELL SVCS DEL POOL

68	AWAIT (44)	BITSTRING	1	TVTAWAIT	AWAIT CONDITION CODE
69	(45)	ADDRESS	3	TVTAWTA	"VL3(AWAITX)"BDTGRCT MFM AWAIT PROCESSING
72	(48)	BITSTRING	1	TVTAWTL	AWAIT LIST CONDITION CODE
73	(49)	ADDRESS	3	TVTAWTLA	"VL3(AWAITX)"BDTGRCT MFM AWAIT PROCESSING
76	(4C)	BITSTRING	1	TVTAWTOF	AWAITOFF CONDITION CODE
77	(4D)	ADDRESS	3	TVTAWTOA	"VL3(AWAITX)"BDTGRCT MFM AWAIT PROCESSING
80	(50)	BITSTRING	1	TVTAWTOL	AWAITOFF LIST CONDITION CODE
81	(51)	ADDRESS	3	TVTWTOLA	"VL3(AWAITX)"BDTGRCT MFM AWAIT PROCESSING
84	(54)	BITSTRING	1	TVTAWTE	AWAIT EXIT CONDITON CODE
85	(55)	ADDRESS	3	TVTAWTEA	"VL3(AWAITX)"BDTGRCT MFM AWAIT PROCESSING

88	ESTAE (58)	ADDRESS	4	TVTABMNO	"V(BDTABMN)"BDTABMN BDT ESTAE ROUTINE
92	(5C)	ADDRESS	4	TVTABNDO	"V(BDTABNO)"BDTABNO ABEND
96	(60)	ADDRESS	4	TVTABSRV	"V(ABSERV2)"BDTABMN ESTAE RECOVERY ABEND SVC
100	(64)	ADDRESS	4	TVTFLDAP	"V(FAILDAPX)"BDTABMN FAIL A DAP
104	(68)	ADDRESS	4	TVTGSDAX	"V(ABSERV1)"BDTABMN ESTAE EXIT ABEND SVC RTN

108	COMMON (6C)	SUBTASK BITSTRING	1	TVTCSECF	COMMON SUBTASK REQUEST ECF
		1... ..		TVTCSPST	"BIT0" COMMON SUBTASK REQUEST POST
		.1.. ..		TVTCRSR1	"BIT1" RESERVED
		..1. ....		TVTCRSR2	"BIT2" RESERVED
		...1 ....		TVTCRSR3	"BIT3" RESERVED
		.... 1...		TVTCRSR4	"BIT4" RESERVED
		.... .1..		TVTCRSR5	"BIT5" RESERVED
		.... ..1.		TVTCRSR6	"BIT6" RESERVED
		.... ...1		TVTCRSR7	"BIT7" COMMON SUBTASK TERMINATION
108	(6C)	ADDRESS	4	TVTCRQR	"V(BDTCRQR)" BDTGRCS COMN SUBTASK REQST QUEUE RTN
112	(70)	ADDRESS	4	TVTCRCP	COMN SUBTSK RQST CELL POOL

116	FCT ROUTINE (74)	ADDRESS	4	TVTADFCT	"V(ADDFACTX)" BDTGRFC ADD FCT ROUTINE
120	(78)	ADDRESS	4	TVTDLFCT	"V(DELFACTX)" BDTGRFC DELETE FCT ROUTINE
124	(7C)	ADDRESS	4	TVTENFCT	"V(ENQFACTX)" BDTGRFC ENQ/DEQ FCT ROUTINE
128	(80)	ADDRESS	4	TVTGTFACT	"V(GETFACTX)" BDTGRFC GET FCT ROUTINE
132	(84)	ADDRESS	4	TVTPTFACT	"V(PUTFACTX)" BDTGRFC PUT FCT ROUTINE

136	INTERFUNCTION COMMUNICATION MANAGER (88)	BITSTRING	1	TVTIFECF	INTER FUNC COMMGR ECF
		1... ..		TVTIFPST	"BIT0" INTER FUNC COMMGR POST
136	(88)	ADDRESS	4	TVTIFSND	"V(BDTIFCS)" BDTIFCM INTER FUNC COM SEND RTN

140	JOB NUMBER (8C)	ADDRESS	4	TVTFDJNR	"V(JOBNTXT)"BDTGRJN FIND JOB NUMBER
144	(90)	ADDRESS	4	TVTJOBNR	"V(JOBNUMBER)"BDTGRJN JOB NUMBER
148	(94)	ADDRESS	4	TVTJNUMR	"V(RETURNJN)"BDTGRJN RETURN A JOB NUMBER

152	DAP (98)	ADDRESS	4	TVTJSSRT	"V(JSSRTN)" BDTGRJR DAP RETURN POINT TO BDTGRJR
156	(9C)	ADDRESS	4	TVTJSSNJ	"V(NJERTN)" BDTGRJR DAP RETURN POINT TO BDTGRJR
160	(A0)	ADDRESS	4	TVTXCKPT	"V(BDTXCKPT)" BDTCKPT DAP CHECKPOINT ROUTINE
164	GETLU/PUTLU (A4)	ADDRESS	4	TVTGETLU	"V(GETLUI)" BDTGRGU GETLU
168	(A8)	ADDRESS	4	TVTPUTLU	"V(PUTLUI)" BDTGRGU PUTLU
172	LU (AC)	ADDRESS	4	TVTLOPN0	"V(BDTLOPN)" BDTLAMB LU OPEN
176	(B0)	ADDRESS	4	TVTLCLS0	"V(BDTLCLS)" BDTLAMB LU CLOSE
180	(B4)	ADDRESS	4	TVTLPUT0	"V(BDTLPUT)" BDTLAMB LU GET
184	(B8)	ADDRESS	4	TVTLGET0	"V(BDTLGET)" BDTLAMB LU PUT
188	(BC)	ADDRESS	4	TVTLRD0	"V(BDTLRD)" BDTLAMB LREAD ROUTINE EP
192	(C0)	ADDRESS	4	TVTLWRT0	"V(BDTLWRT)" BDTLAMB LWRITE ROUTINE EP
196	TRACE (C4)	ADDRESS	4	TVTXTRC	"V(BDTGRTX)" BDTGRTX TRACE ROUTINE ENTRY POINT
200	(C8)	ADDRESS	4	TVTVATR	"V(ATRSTART)" BDTGRTX TRACE ROUTINE CONTROL AREA
204	(CC)	ADDRESS	4	TVTLGREC	"V(BDLOGREC)" BDTABMN LOGREC SUPPRESSION ROUTINE
208	(D0)	ADDRESS	4	TVTRSD01	RESERVED
212	(D4)	ADDRESS	4	TVTRSD02	RESERVED
216	RBAM (D8)	ADDRESS	4	TVTRFMT0	"V(RFORMAT)" BDTRBAM RBAM FORMAT QUEUE
220	(DC)	ADDRESS	4	TVTRALC0	"V(RALLOC)" BDTRBAM ALLOC BLOCKS (RBNS)
224	(E0)	ADDRESS	4	TVTRCLS0	"V(RCLOSE)" BDTRBAM CLOSE RBAM FILE
228	(E4)	ADDRESS	4	TVTROPN0	"V(ROPEN)" BDTRBAM OPEN RBAM FILE
232	(E8)	ADDRESS	4	TVTRPRG0	"V(RPURGE)" BDTRBAM RETURN BLOCKS (RBNS)
236	(EC)	ADDRESS	4	TVTRRED0	"V(RREAD)" BDTRBAM READ DATA
240	(F0)	ADDRESS	4	TVTRWRT0	"V(RWRITE)" BDTRBAM WRITE DATA
244	SNA MANAGEMENT (F4)	ADDRESS	4	TVTSNOPN	SET BY BDTSCMGR SNA BDTXL0PN EXTENSION
248	(F8)	ADDRESS	4	TVTSNCLS	SET BY BDTSCMGR SNA BDTXLCLS EXTENSION
252	(FC)	ADDRESS	4	TVTSNGET	SET BY BDTSCMGR SNA BDTXLGET EXTENSION
256	(100)	ADDRESS	4	TVTSNPUT	SET BY BDTSCMGR SNA BDTXLPUT EXTENSION
260	(104)	ADDRESS	4	TVTSCDTA	SET BY BDTSCMGR
264	(108)	ADDRESS	4	TVTSNRD	SET BY BDTSCMGR BDTXLRD EXTENSION
268	(10C)	ADDRESS	4	TVTSNWRT	SET BY BDTSCMGR BDTXLWRT EXTENSION
272	ADDITIONAL ADDRESSES (110)	ADDRESS	4	TVTDQMSG	"V(DEQMSGX)" BDTQMOM BDTXDQMS SERVICE ROUTINE
276	(114)	ADDRESS	4	TVTRQTBA	"V(RQTAADDX)" BDTGRRQ RQ TABLE ADD
280	(118)	ADDRESS	4	TVTRQTB0	"V(RQTADELX)" BDTGRRQ RQ TABLE DEL
284	(11C)	ADDRESS	4	TVTRQTB0	"V(RQTAPUTX)" BDTGRRQ RQ TABLE PUT
288	(120)	ADDRESS	4	TVTXJCT	"V(BDTXJCT)" BDTGRJX JCT ACCESS ROUTINE
292	(124)	ADDRESS	4	TVTXJQE	"V(BDTXJQE)" BDTGRJX JQE ACCESS ROUTINE

296	(128)	ADDRESS	4	TVTXCOMP	"V(BDTXCOMP)"BDTCMQM SCNBLENK COMPRESSION ROUTINE
300	(12C)	ADDRESS	4	TVTXDCMP	"V(BDTXDCMP)"BDTGRDC DATA COMPRESS/DECOMPRESS
304	(130)	BITSTRING	1	TVTBDKEY	BDT STORAGE PROTECT KEY
304	(130)	ADDRESS	4	TVTCKPNT	"V(BDTCHECK)"BDTGRCP CHECKPOINT
308	(134)	ADDRESS	4	TVTABNGT	"V(ABNCORE)" BDTABN0 VIRT ADDR VALID'N RTN
312	(138)	ADDRESS	4	TVTCSF	"V(GRGSNTRY)"BDTGRGS CALL SUBTASK FUNCTION RTN
316	(13C)	ADDRESS	4	TVTDJNR	"V(BDTDJNR)" BDTDJNR DJC NET RELEASE PROCESSING
320	(140)	ADDRESS	4	TVTRSD51	RESERVED
324	(144)	ADDRESS	4	TVTMDLK	"V(BDTMODUP)"BDTABMN MODULE NAME LOOK UP ROUTINE
328	(148)	ADDRESS	4	TVTMESAG	"V(MESSAGEX)"BDTCMQM CONSOLE MESSAGE
332	(14C)	ADDRESS	4	TVTNMSG	"V(MESSAGEH)"BDTCMQM MESSAGE HANDLER SUPPORT
336	(150)	ADDRESS	4	TVTMFMEP	"V(CNTORG)" BDTGRCT EP FOR MULTI FUNC MONITOR
340	(154)	ADDRESS	4	TVTSUPC	"V(BDTSUPC)" BDTSUPC SUPRSCAN ROUTINE ENTRY PNT
344	(158)	ADDRESS	4	TVTTUAM	"V(BDTTUAMX)"BDTGRDA MJD TEXT UNIT ACS METHOD
348	(15C)	ADDRESS	4	TVTRSD05	RESERVED
352	(160)	ADDRESS	4	TVTXOIDF	"V(BDTXOIDX)"BDTGRXD XOID FORMATTING ROUTINE
356	(164)	ADDRESS	4	TVTXTIME	"V(BDTXTIME)"BDTGRTS TIMING SERVICES
360	(168)	ADDRESS	4	TVTRSD06	RESERVED
364	(16C)	ADDRESS	4	TVTXACC	"V(BDTXACC)" BDTACDV BDT ACCOUNTING STIMER RRTN
368	(170)	ADDRESS	4	TVTXLOG	"V(BDTGRLG)" BDTGRLG BDT LOG MANAGER
ACCESS METHOD CONTROL BLOCK ADDRESSES (ORDER MUST BE MAINTAINED)					
372	(174)	ADDRESS	4	TVTSLACB	ACCESS METHOD CB POINTER
376	(178)	ADDRESS	4	TVTSLEXL	ACCESS METHOD CB POINTER
380	(17C)	ADDRESS	4	TVTSLRPL	ACCESS METHOD CB POINTER
380	(17C)			TVTSDVBL	TVTSLACB (ACCESS METHOD CB POINTER)
384	(180)	ADDRESS	4	TVTRSD10	RESERVED
388	(184)	ADDRESS	4	TVTEXL	"V(BDTXEXL)" BDTGRPT USER EXIT RTN ADDRESS LIST
RESERVED FIELDS					
392	(188)	ADDRESS	4	TVTRSD11	RESERVED
396	(18C)	ADDRESS	4	TVTRSD12	RESERVED
400	(190)	ADDRESS	4	TVTRSD13	RESERVED
404	(194)	ADDRESS	4	TVTRSD14	RESERVED
408	(198)	ADDRESS	4	TVTRSD15	RESERVED
412	(19C)	ADDRESS	4	TVTRSD05	RESERVED
416	(1A0)	ADDRESS	4	TVTRSD06	RESERVED
420	(1A4)	ADDRESS	4	TVTRSD07	RESERVED
424	(1A8)	ADDRESS	4	TVTRSD08	RESERVED
428	(1AC)	ADDRESS	4	TVTRSD09	RESERVED
432	(1B0)	ADDRESS	4	TVTRSD10	RESERVED
436	(1B4)	ADDRESS	4	TVTRSD11	RESERVED
440	(1B8)	ADDRESS	4	TVTRSD12	RESERVED
444	(1BC)	ADDRESS	4	TVTRSD13	RESERVED
448	(1C0)	ADDRESS	4	TVTRSD14	RESERVED
452	(1C4)	ADDRESS	4	TVTRSD15	RESERVED
456	(1C8)	ADDRESS	4	TVTEPE	END OF ENTRY POINTS
SYSTEM TABLE POINTERS					
456	(1C8)	ADDRESS	4	TVTABDCB	"V(ABNDCB)" BDTABN0 ABEND DCB
BDT INITIALIZATION FLAG					
460	(1CC)	BITSTRING	1	TVTINITF	BDTINCN BDT INITIALIZATION FLAGS
	1... ..			TVTINCMF	"BIT0" INITIALIZATION COMPLETE FLAG

		.1.. ....		TVTINIR1	"BIT1" RESERVED
		..1. ....		TVTINIR2	"BIT2" RESERVED
		...1 ....		TVTINIR3	"BIT3" RESERVED
		.... 1...		TVTINIR4	"BIT4" RESERVED
		.... .1..		TVTINIR5	"BIT5" RESERVED
		.... ..1.		TVTINIR6	"BIT6" RESERVED
		.... ...1		TVTINIR7	"BIT7" RESERVED
464	(1D0)	ADDRESS	4	TVTINDTA	SET BY BDTINTK POINTER TO INIT DATA CSECT
468	(1D4)	ADDRESS	4	TVTMSTCB	BDTINIT BDT MASTER TCB
CELL POOL ADDRESSES					
472	(1D8)	ADDRESS	4	TVTFCTCP	ADDR OF FCT CELL POOL CPB
476	(1DC)	ADDRESS	4	TVTICMCP	ADDR OF ICMB CELL POOL CPB
480	(1E0)	ADDRESS	4	TVTIFCCP	ADDR OF IFC CELL POOL CPB
484	(1E4)	ADDRESS	4	TVTIFNCP	ADDR OF NJE IFC CELL POOL CPB
488	(1E8)	ADDRESS	4	TVTJCBCP	ADDR JCT BUFR CELL POOL CPB
492	(1EC)	ADDRESS	4	TVTJMLCP	ADDR OF JML CELL POOL CPB
496	(1F0)	ADDRESS	4	TVTNUMAP	"V(NUCMAP)" BDTGRVT MAP OF BDTNUC CSECTS
500	(1F4)	ADDRESS	4	TVTOCMCP	ADDR OF OCMB CELL POOL CPB
504	(1F8)	ADDRESS	4	TVTSCPD	"V(CPDTABLE)"BDTGRCPD BDT SYSTEM CELL POOL DIRECT
508	(1FC)	ADDRESS	4	TVTSVCPB	ADDR SAV AREA CELL POOL CPB
512	(200)	ADDRESS	4	TVTTQECF	ADDR OF TQE CELL POOL CPB
516	(204)	ADDRESS	4	TVTTQICP	ADDR OF TQI CELL POOL CPB
LCT ADDRESSES					
520	(208)	ADDRESS	4	TVTIIFC	SET BY BDTINR2 START OF IFC LCTS
524	(20C)	ADDRESS	4	TVTLCTUN	SET BY BDTINGN LOGICAL UNITS TABLE
528	(210)	ADDRESS	4	TVTRSTPU	SET BY BDTINR2 1ST PU ENTRY IN RESTABL
532	(214)	ADDRESS	4	TVTRLTTB	SET BY BDTINR2 RESIDENT RLT TABLE
536	(218)	ADDRESS	4	TVTSNBP	SET BY BDTINR2 SNA BUFFER POOL
540	(21C)	ADDRESS	4	TVTSNLTP	SET BY BDTSNA SNA LINE LCTUNITS CHAIN
544	(220)	ADDRESS	4	TVTXFER	SET BY BDTINR2 START OF TRANSFER LCTS
548	(224)	ADDRESS	4	TVTMSGDV	ADDR OF FIRST MSGD DATA AREA
RESERVED FIELDS					
552	(228)	ADDRESS	4	TVTRSD17	RESERVED
556	(22C)	ADDRESS	4	TVTRSD18	RESERVED
560	(230)	ADDRESS	4	TVTRSD16	RESERVED
564	(234)	ADDRESS	4	TVTRSD17	RESERVED
568	(238)	ADDRESS	4	TVTRSD18	RESERVED
TRANSACTION DRIVER QUEUE					
576	(240)		8	TVTXDQUE	TRANSACTION DRIVER QUEUE
576	(240)	ADDRESS	4	TVTADFQE	ADDRESS OF FIRST QUEUE ENTRY
580	(244)	ADDRESS	4	TVTXDQCT	NUMBER OF ELEMENTS QUEUED
584	(248)	ADDRESS	2	TVTXDQHI	HIGH WATER MARK
586	(24A)	ADDRESS	2	TVTXDQLO	LOW WATER MARK
592	(250)		8	TVTXMQUE	CROSS MEMORY QUEUE
592	(250)	ADDRESS	4	TVTXMQ	CMDV CROSS MEMORY QUEUE
596	(254)	ADDRESS	4	TVTXMQCT	NUMBER OF ELEMENTS ON QUEUE
600	(25A)	ADDRESS	2	TVTXMQHI	HIGH WATER MARK
602	(25A)	ADDRESS	2	TVTXMQLO	LOW WATER MARK
TRANSACTION DRIVER ECF					
604	(25C)	BITSTRING	1	TVTXDECF	TRANSACTION DRIVER ECF
		1... ....		TVTXDXQD	"BIT0" TRANSACTION QUEUED
		..1. ....		TVTXDIFC	"BIT1" INTER FUNCTION COMM POST
		...1 ....		TVTXDQR1	"BIT2" RESERVED
		.... 1...		TVTXDQR2	"BIT3" RESERVED
		.... .1..		TVTXDQR3	"BIT4" RESERVED
		.... ..1.		TVTXDQR4	"BIT5" RESERVED
		.... ...1		TVTXDQR5	"BIT6" RESERVED
				TVTXDQR6	"BIT7" RESERVED

608	(260)	ADDRESS	4	TVTRSV01	RESERVED
612	(264)	ADDRESS	4	TVTRSV02	RESERVED
616	(268)	ADDRESS	4	TVTRSV03	RESERVED
620	(26C)	ADDRESS	4	TVTRSV04	RESERVED

DAP COUNTERS (COMPARE AND SWAP MUST BE USED TO ALTER)					
624	(270)	FIXED	4	TVTRSDAP	RESIDENT DAP COUNTER
628	(274)	FIXED	4	TVTNRDAP	DYNAMIC DAP COUNTER
632	(278)	FIXED	4	TVTCLDAP	CALLED DAP COUNTER

BDT TERMINATION FLAG 1 DEFINITION (COMPARE AND SWAP MUST BE USED TO ALTER)					
636	(27C)	BITSTRING	1	TVTPFLG1	BDT TERMINATION FLAG 1
		1... ..		TVTDYNS0	"BIT0" DYNAMIC DAP COUNT = 0
		.1.. ..		TVTCALL0	"BIT1" CALLED DAP COUNT =
		..1. ....		TVTPRES4	"BIT2" RESIDENT DAP COUNT = 4
		...1 ....		TVTPRES0	"BIT3" RESIDENT DAP COUNT = 0
		.... 1...		TVTPABMN	"BIT4" FCT ABEND LIMIT REACHED
		.... .1..		TVTFTFEC	"BIT5" FTF EFP COMPLETE
		.... ..1.		TVTNJEEC	"BIT6" NJE EFP COMPLETE
		.... ...1		TVTPTERM	"BIT7" BDT SHUTDOWN IN PROGRESS

BDT TERMINATION FLAG 2 DEFINITION (COMPARE AND SWAP MUST BE USED TO ALTER)					
637	(27D)	BITSTRING	1	TVTPFLG2	BDT TERMINATION FLAG 2
		1... ..		TVTPCMDV	"BIT0" BDTCMDV TERMINATION
		.1.. ..		TVTPGRJS	"BIT1" BDTGRJS ROUTINE ERROR
		..1. ....		TVTPERR	"BIT2" BDTCMDV ROUTINE ERROR
		...1 ....		TVTPGRGS	"BIT3" CRITICAL FCT ENDING
		.... 1...		TVTPF2R1	"BIT4" RESERVED
		.... .1..		TVTPF2R2	"BIT5" RESERVED
		.... ..1.		TVTPF2R3	"BIT6" RESERVED
		.... ...1		TVTPF2R4	"BIT7" RESERVED

RESERVED FIELDS					
638	(27E)	BITSTRING	2	TVTRSV05	RESERVED
640	(280)	ADDRESS	4	TVTRSV06	RESERVED
644	(284)	ADDRESS	4	TVTRSV07	RESERVED
648	(288)	ADDRESS	4	TVTRSV08	RESERVED
652	(28C)	ADDRESS	4	TVTRSV19	RESERVED
656	(290)	ADDRESS	4	TVTRSV20	RESERVED
660	(294)	ADDRESS	4	TVTRSV21	RESERVED

664	(298)	ADDRESS	4	TVTITECB	ECB FOR BDTINIT TO WAIT ON
-----	-------	---------	---	----------	----------------------------

BDT MASTER ECB					
668	(29C)	ADDRESS	4	TVTMECBL	BDT MASTER ECB LIST
668	(29C)	BITSTRING	1	TVTMTECB	BDT MASTER ECB FLAG
		.111 1111		TVTMTOFF	"X'7F'" RESET MASTER ECB
		1... ..		TVTMTON	"X'80'" SET MASTER ECB FLAG
669	(29D)	ADDRESS	3	TVTAMECB	ADDRESS OF MASTER ECB

MCS CONSOLE COMMAND ECB					
672	(2A0)	ADDRESS	4	TVTMCECB	MCS CONSOLE COMMAND ECB
		.111 1111		TVTMCOFF	"X'7F'" RESET MASTER CONSOLE ECB
		1... ..		TVTMCON	"X'80'" SET MASTER CONSOLE ECB

676	BDT MASTER ECB (2A4)	ADDRESS	4	TVTMSECB	BDTINIC BDT MASTER ECB
		.111 1111 1... ....		TVTMSOFF TVTMSON	"X'7F'" RESET MASTER ECB "X'80'" SET MASTER ECB
680	(2A8)	ADDRESS	4	TVTNUECB	SET BY BDTINTK ECB THAT BDTINTK WAITS ON
MISCELLANEOUS INFORMATION					
684	(2AC)	ADDRESS	4	TVTAMQUE	BDT ACTION MESSAGE QUEUE
688	(2B0)	ADDRESS	4	TVTBTAB	BDTRBAM RBAM BIT TABLE
692	(2B4)	ADDRESS	4	TVTCKPAR	"V(CKPTDATA)"BDTGRCP CHECKPOINT AREA
696	(2B8)	ADDRESS	4	TVTCMTCB	BDTCMDV'S TCB
700	(2BC)	ADDRESS	4	TVTCSRQU	COMMON SUBTASK REQUEST QUEUE
704	(2C0)	ADDRESS	4	TVTEFTOP	RQ ENDING FUNCTION TOP
708	(2C4)	ADDRESS	4	TVTNETOP	NJE ENDING FUNCTION QUEUE
712	(2C8)	ADDRESS	4	TVTFCTTP	"V(FCTTOP)" BDTGRPT FIRST FCT ENTRY
716	(2CC)	ADDRESS	4	TVTMSGQU	SET BY BDTCMMSG OCMB QUEUE FOR BDTMSDV
720	(2D0)	ADDRESS	4	TVTITKPM	SET BY BDTINIT BDTINTK PARMS LIST ADDR
724	(2D4)	ADDRESS	4	TVTJNM	ADDRESS OF JOB NUMBER TABLE
728	(2D8)	ADDRESS	4	TVTJQX	"V(JQXSTART)"BDTGRJX ADDR JQX
732	(2DC)	ADDRESS	4	TVTJSSFCT	"V(JSSFCT)" BDTGRPT BDTGRJS FCT
736	(2E0)	ADDRESS	4	TVTLBCB	SET BY BDTINTK BDTLIB DCB POINTER
740	(2E4)	ADDRESS	4	TVTRSD19	RESERVED
NUCLEUS STARTING AND ENDING ADDRESS					
744	(2E8)	ADDRESS	4	TVTSTGLS	BDTGRVT START OF NUCLEUS
748	(2EC)	BITSTRING	1	TVTNUCND	END OF NUCLEUS FLAG
749	(2ED)	ADDRESS	3	TVTNUCNA	END OF NUCLEUS ADDRESS
752	(2F0)	ADDRESS	4	TVTOCMQU	OUTPUT CONSOLE MESSAGE QUEUE
756	(2F4)	ADDRESS	4	TVTRSTBL	"V(RESTABLX)"BDTGRRQ RESOURCE MGMT TABLE
760	(2F8)	ADDRESS	4	TVTTRTAB	"V(TRANSTAB)"BDTGRVT SYSTEM TRANSLATE TABLE
764	(2FC)	ADDRESS	4	TVTSCAN	"V(SCNSTART)"BDTGRSCN SCAN/VALIDATE/TRANSLATE TBL
768	(300)	ADDRESS	4	TVTSPDCB	BDTRBAM SPOOL DCB
772	(304)	ADDRESS	4	TVTSSCVT	POINTER TO BDT SSCVT
776	(308)	ADDRESS	4	TVTWFCFCT	"V(WAIT FCTFCT)" BDTGRPT WAIT ADDR
RESERVED FIELDS					
780	(30C)	ADDRESS	4	TVTRSD20	RESERVED
784	(310)	ADDRESS	4	TVTRSD21	RESERVED
788	(314)	ADDRESS	4	TVTRSD22	RESERVED
792	(318)	ADDRESS	4	TVTRSD23	RESERVED
796	(31C)	ADDRESS	4	TVTRSD24	RESERVED
800	(320)	ADDRESS	4	TVTRSD23	RESERVED
804	(324)	ADDRESS	4	TVTRSD24	RESERVED
808	(328)	ADDRESS	4	TVTRSD25	RESERVED
812	(32C)	ADDRESS	4	TVTRSD26	RESERVED
816	(330)	ADDRESS	4	TVTRSD27	RESERVED
820	(334)	ADDRESS	4	TVTRSD28	RESERVED
824	(338)	ADDRESS	4	TVTRSD29	RESERVED
MASTER DDBFX					
828	(33C)	BITSTRING	12	TVTDDBRQ	MASTER DDBFX
840	(348)	BITSTRING	1	TVTDDBFX	MASTER DDBFX
STANDARDS/DEFAULTS AND DATA - FULLWORD					
848	(350)	FIXED	4	TVTRSD33	RESERVED
852	(354)	FIXED	4	TVTSZBUF	SET BY BDTINIO SIZE OF BUFFER FULLWORD
852	(354)	FIXED	2	TVTSZBUX	INITIALIZE 1ST HALFWORD
854	(356)	FIXED	2	TVTBUF5Z	SET BY BDTINIO SIZE OF BUFFER HALFWORD
856	(358)	ADDRESS	4	TVTRSD34	RESERVED
860	(35C)	FIXED	4	TVTCPUID	CPU ID

860	(35C)	BITSTRING	1	TVTCPUVC	CPU VERSION CODE
861	(35D)	BITSTRING	1	TVTCPUVX	INITIALIZE REST OF FWD
		1111 1111		TVTVMSYS	"X'FF'" VM TEST SYSTEM
864	(360)	FIXED	4	TVTIFCGM	CURRENT STORAGE BEING USED FOR IFC GETMAINED BUFFERS
868	(364)	FIXED	4	TVTIFCCT	CURRENT CNT OF GETMAINED IFC BUFFERS
872	(368)	FIXED	4	TVTIFCGH	HI WATER MARK FOR IFC GETMAINED BUFFER STORAGE
876	(36C)	FIXED	4	TVTIFCCH	HI WATER MARK FOR NUMBER OF IFC GETMAINED BUFFERS
RESERVED FIELDS					
880	(370)	ADDRESS	4	TVTRSU05	RESERVED
884	(374)	ADDRESS	4	TVTRSU06	RESERVED
888	(378)	ADDRESS	4	TVTRSU07	RESERVED
892	(37C)	ADDRESS	4	TVTRSU08	RESERVED
896	(380)	FIXED	4	TVTRSD56	RESERVED
900	(384)	FIXED	4	TVTRSD57	RESERVED
904	(388)	FIXED	4	TVTRSD58	RESERVED
908	(38C)	FIXED	4	TVTRSD59	RESERVED
912	(390)	FIXED	4	TVTRSD60	RESERVED
DDB'S AND DATA - HALFWORD					
916	(394)	FIXED	2	TVTJSCMX	CURRENT SCHEDULED XFERS
918	(396)	FIXED	2	TVTLNOHI	TQI HIGH WATER MARK FOR LCTOUT QUEUE
920	(398)	FIXED	2	TVTLNOLO	TQI LOW WATER MARK FOR LCTOUT QUEUE
RESERVED FIELDS					
922	(39A)	FIXED	2	TVTRSD36	RESERVED
924	(39C)	FIXED	2	TVTRSD37	RESERVED
926	(39E)	FIXED	2	TVTRSD38	RESERVED
928	(3A0)	FIXED	2	TVTRSD39	RESERVED
930	(3A2)	FIXED	2	TVTRSD40	RESERVED
932	(3A4)	FIXED	2	TVTRSD41	RESERVED
934	(3A6)	FIXED	2	TVTRSD40	RESERVED
936	(3A8)	FIXED	2	TVTRSD41	RESERVED
938	(3AA)	FIXED	2	TVTRSD42	RESERVED
940	(3AC)	FIXED	2	TVTRSD43	RESERVED
942	(3AE)	FIXED	2	TVTRSD44	RESERVED
944	(3B0)	FIXED	2	TVTRSD45	RESERVED
FLAGS AND ECFS ACCOUNTING ECF					
946	(3B2)	BITSTRING	1	TVTACECF	BDTACMN ACCOUNTING ECF
		1... ..		TVTACPST	"BIT0" ACCOUNTING POST
		.1.. ..		TVTOMPST	"BIT1" OPERATOR MSG POST
		..1. ....		TVTATPST	"BIT2" TIMER POST
		...1 ....		TVTACEC1	"BIT3" RESERVED
		.... 1...		TVTACEC2	"BIT4" RESERVED
		.... .1..		TVTACEC3	"BIT5" RESERVED
		.... ..1.		TVTACEC4	"BIT6" RESERVED
		.... ...1		TVTACEC5	"BIT7" RESERVED
947	(3B3)	BITSTRING	1	TVTRSD44	RESERVED
JOB SEQUENCE SCHEDULER INDICATOR FLAG BYTE 1					
948	(3B4)	BITSTRING	1	TVTJSFL1	JSS FLAG BYTE
		1... ..		TVTJSGPS	"BIT0" GENERAL POST OF JSS
		1... ..		TVTJSJCA	"BIT0" JCT TABLE ADD HAS OCCURRED
		1... ..		TVTJSDUC	"BIT0" DAP USE COUNT CHG REQUIRED
		1... ..		TVTJSTSC	"BIT0" JCT TAB STAT CHNG OCCURRED
		.1.. ....		TVTJSPRG	"BIT1" PURGE THE QUEUE REQUEST
		..1. ....		TVTJSNPS	"BIT2" NJE POST OF JSS
		...1 ....		TVTJSEFN	"BIT3" NJE ENDING FUNCTION
		.... 1...		TVTJSTRM	"BIT4" JSS TERMINATION ROUTINE POST



	....	.1..	TVTJSLPS	"BIT5" LCT VLU SCAN POST
	....	..1.	TVTJSEFA	"BIT6" ENDING FUNC ADDED TO EFCHN
	....	...1	TVTJSRPS	"BIT7" IFCM RCVE POST
949	JOB SEQUENCE SCHEDULER INDICATOR FLAG (3B5)	1	TVTJSFL2	JSS FLAG BYTE
	1...	....	TVTJSFR1	"BIT0" RESERVED
	.1..	....	TVTJSACT	"BIT1" S JSS COMMAND ENTERED
	..1.	....	TVTJSCKP	"BIT2" JCT RELEASE PUTBUF=NO
	...1	....	TVTJSFR2	"BIT3" RESERVED
	....	1...	TVTJSFR3	"BIT4" RESERVED
	....	.1..	TVTJSFR4	"BIT5" RESERVED
	....	..1.	TVTJSFR5	"BIT6" RESERVED
	....	...1	TVTJSFR6	"BIT7" RESERVED
950	BDT START FLAG INDICATORS (3B6)	1	TVTRSTFL	BDT START FLAG
	1...	....	TVTCOLDS	"BIT0" THIS CPU IS COLD STARTING
	.1..	....	TVTWARMS	"BIT1" THIS CPU IS WARM STARTING
	..1.	....	TVTHOTST	"BIT2" THIS CPU IS HOT STARTING
	...1	....	TVTANALZ	"BIT3" QUEUE ANALYSIS REQUIRED
	....	1...	TVTPRMST	"BIT4" START SPECIFIED VIA PARM=
	....	.1..	TVTRSTR1	"BIT5" RESERVED
	....	..1.	TVTRSTR2	"BIT6" RESERVED
	....	...1	TVTRSTR3	"BIT7" RESERVED
951	BDT CONNECTION STATE MACHINE (3B7)	1	TVTSTATE	BDT CONNECTION STATE MACHINE
	1...	....	TVTINITS	"BIT0" INITIALIZE STATE
	.1..	....	TVTDISCS	"BIT1" DISCONNECT STATE
	..1.	....	TVTCONTS	"BIT2" CONNECT STATE
	...1	....	TVTSPNDS	"BIT3" SUSPEND STATE
	....	1...	TVTCONR1	"BIT4" RESERVED
	....	.1..	TVTCONR2	"BIT5" RESERVED
	....	..1.	TVTCONR3	"BIT6" RESERVED
	....	...1	TVTCONR4	"BIT7" RESERVED
	1...	....	TVTSETI	"X'80'" SET INITIALIZE STATE
	.1..	....	TVTSETD	"X'40'" SET DISCONNECT STATE
	..1.	....	TVTSETC	"X'20'" SET CONNECT STATE
	...1	....	TVTSETS	"X'10'" SET SUSPEND STATE
952	BDT CONNECTION STATE MACHINE FLAG (3B8)	1	TVTSTFLG	BDT CONNECT STATE MACHINE FLAG
	1...	....	TVTSTSPN	"BIT0" SYSTEM SUSPEND
	.1..	....	TVTSTRSM	"BIT1" SYSTEM RESUME
	..1.	....	TVTSTOPN	"BIT2" OPERATOR SUSPEND
	...1	....	TVTSTORS	"BIT3" OPERATOR RESUME
	....	1...	TVTSTFR3	"BIT4" RESERVED
	....	.1..	TVTSTFR4	"BIT5" RESERVED
	....	..1.	TVTSTVON	"BIT6" VARY ONLINE REQUEST
	....	...1	TVTSTCLD	"BIT7" NJE COLD START
953	SNA MANAGER ECF (3B9)	1	TVTSNECF	SNA MANAGER ECF
	1...	....	TVTSNACT	"BIT0" SNA MANAGER IS ACTIVE
	.1..	....	TVTSNCPS	"BIT1" OPERATOR COMMAND POST
	..1.	....	TVTSNWRK	"BIT2" WORK TO DO POST
	...1	....	TVTSNIDL	"BIT3" IDLE SESSION CHECK POST

	.... 1...		TVTSNASR	"BIT4" AUTO SESSION RESTART POST
	.... .1..		TVTSNWAT	"BIT5" WAIT STATE EXT POST
	.... ..1.		TVTSNAST	"BIT6" MESSAGE PENDING POST
	.... ...1		TVTSNAST	"BIT7" SCHEDULE ASR TIMER
954	TQI ECF (3BA) BITSTRING 1		TVTTQECF	TQI ECF
	1... ....		TVTSUMTF	"BIT0" PROCESS CHECKPOINT FILE
	.1.. ....		TVTIFCMF	"BIT1" PROCESS IFCM MESSAGE
	..1. ....		TVTCMDVF	"BIT2" PROCESS OPERATOR COMMAND
	...1 ....		TVTACKNF	"BIT3" PROCESS ACK FROM BDTGRXD
	.... 1...		TVTCMSDE	"BIT4" COMMAND SLOWDOWN ENDED
	.... .1..		TVTXNSDE	"BIT5" TRANSACTION SLOWDOWN ENDED
	.... ..1.		TVTLNSDE	"BIT5" SLOWDOWN FOR A LINE ENDED
	.... ...1		TVTTQER4	"BIT7" RESERVED
	1111 111.		TVTTQPST	"X'FE'" MASK WAITING ON ALL CONDITION
955	TQI INOPERATIVE FLAG (3BB) BITSTRING 1		TVTTQIOF	TQI INOPERATIVE FLAG
	1111 1111		TVTTQINO	"X'FF'" TQI INOPERATIVE
956	TQI CONTROL FLAG (3BC) BITSTRING 1		TVTTQIFG	TQI CONTROL FLAG
	1... ....		TVTTQCS	"BIT0" TQI COMMAND SLOWDOWN
	.1.. ....		TVTTQXS	"BIT1" TQI TRANSACTION SLOWDOWN
	..1. ....		TVTTQRS1	"BIT2" RESERVED
	...1 ....		TVTTQRS2	"BIT3" RESERVED
	.... 1...		TVTTQRS3	"BIT4" RESERVED
	.... .1..		TVTTQRS4	"BIT5" RESERVED
	.... ..1.		TVTTQRS5	"BIT6" RESERVED
	.... ...1		TVTTQRS6	"BIT7" RESERVED
957	SLOWDOWN FLAGS - GROUP 1 (3BD) BITSTRING 1		TVTCPD1	SLOWDOWN FLAGS GROUP 1
	1... ....		TVTFCTSD	"BIT0" FCT CELLPOOL SLOWDOWN FLAG
	.1.. ....		TVTJCTSD	"BIT1" JCT CELLPOOL SLOWDOWN FLAG
	..1. ....		TVTTQISD	"BIT2" TQI CELLPOOL SLOWDOWN FLAG
	...1 ....		TVTCP1R1	"BIT3" RESERVED
	.... 1...		TVTCP1R2	"BIT4" RESERVED
	.... .1..		TVTCP1R3	"BIT5" RESERVED
	.... ..1.		TVTCP1R4	"BIT6" RESERVED
	.... ...1		TVTCP1R5	"BIT7" RESERVED
958	SLOWDOWN FLAGS - GROUP 2 (3BE) BITSTRING 1		TVTCPD2	SLOWDOWN FLAGS GROUP 2
	1... ....		TVTICMBS	"BIT0" ICMB CELLPOOL SLOWDOWN FLAG
	.1.. ....		TVTIFCSD	"BIT1" IFC CELLPOOL SLOWDOWN FLAG
	..1. ....		TVTOCMBS	"BIT2" OCMB CELLPOOL SLOWDOWN FLAG
	...1 ....		TVTJMLSD	"BIT3" JML CELLPOOL SLOWDOWN FLAG
	.... 1...		TVTSAVSD	"BIT4" SAVE CELLPOOL SLOWDOWN FLAG
	.... .1..		TVTTQESD	"BIT5" TQE CELLPOOL SLOWDOWN FLAG
	1111 1111		TVTFALON	"X'FF'" MASK TO TEST IF ANY FLGS ON

959	COMMUNICATIONS DRIVER ECF (3BF) BITSTRING 1	TVTCDECF	COMMUNICATIONS DRIVER ECF
	1... ..	TVTCDIFC	"BIT0" INTER FUNCTION COMM POST
	.1.. ..	TVTCDOCM	"BIT1" OUTPUT CONSOLE MESSAGE POST
	..1. ....	TVTCDEC1	"BIT2" RESERVED
	...1 ....	TVTCDMCS	"BIT3" MCS CONSOLE COMMAND POST
	.... 1...	TVTCDJES	"BIT4" BDT/JES3 INTERFACE STATUS POST
	.... .1..	TVTCDMOT	"BIT5" TASK TIME POST
	.... ..1.	TVTCDSSI	"BIT6" SUBSYSTEM INTERFACE POST
	.... ...1	TVTCDEXT	"BIT7" ECF EXTENSION IS ACTIVE
960	COMMUNICATIONS DRIVER ECF EXTENSION (3C0) BITSTRING 1	TVTCDECX	COMM DRIVER ECF EXTENSION
	1... ..	TVTCDNJE	"BIT0" NJE POST
	.1.. ..	TVTCDTRM	"BIT1" CMDV TERMINATION ROUTINE POST
	..1. ....	TVTCDRS1	"BIT2" RESERVED
	...1 ....	TVTCDRS2	"BIT3" RESERVED
	.... 1...	TVTCDRS3	"BIT4" RESERVED
	.... .1..	TVTCDRS4	"BIT5" RESERVED
	.... ..1.	TVTCDRS5	"BIT6" RESERVED
	.... ...1	TVTCDRS6	"BIT7" RESERVED
961	MESSAGE DATASET DRIVER ECF (3C1) BITSTRING 1	TVTMSGCF	MESSAGE DATASET DRIVE ECF
	1... ..	TVTMSGOC	"BIT0" BDTCMMSG OCMB POST
	.1.. ..	TVTMSGTP	"BIT1" TASK TIME POST
	..1. ....	TVTMSGCM	"BIT2" CMDV COMMAND POST
	...1 ....	TVTMSGR1	"BIT3" RESERVED
	.... 1...	TVTMSGR2	"BIT4" RESERVED
	.... .1..	TVTMSGG3	"BIT5" RESERVED
	.... ..1.	TVTMSGG4	"BIT6" RESERVED
	.... ...1	TVTMSGG5	"BIT7" RESERVED
	.... ...1	TVTMSGTM	"TVTPTERM" TERMINATION POST
962	RESERVED FIELDS (3C2) BITSTRING 1	TVTRSD47	RESERVED
963	(3C3) BITSTRING 1	TVTRSD53	RESERVED
964	(3C4) BITSTRING 1	TVTRSD54	RESERVED
965	(3C5) BITSTRING 1	TVTRSD48	RESERVED
966	(3C6) BITSTRING 1	TVTRSD49	RESERVED
967	(3C7) BITSTRING 1	TVTRSD50	RESERVED
968	(3C8) BITSTRING 1	TVTRSD51	RESERVED
969	(3C9) BITSTRING 1	TVTRSD52	RESERVED
970	(3CA) BITSTRING 1	TVTRSD53	RESERVED
971	(3CB) BITSTRING 1	TVTRSD54	RESERVED
972	(3CC) BITSTRING 1	TVTRSD55	RESERVED
976	UNIVERSAL CONSTANTS AND MISCELLANEOUS DATA (3D0) FIXED 4	TVTADMSK	CONSTANT FOR ADDRESS MASK
980	(3D4) BITSTRING 1	TVTBDTPL	USED BY BDTXGMPM FOR DEFAULT SUBPOOL
981	(3D5) CHARACTER 8	TVTBLANK	CONSTANT BLANKS
992	(3E0) FIXED 4	TVTCPUF	CPU FACTOR
996	(3E4) CHARACTER 43	TVTDFACT	DEFAULT ACCTG
1039	(40F) CHARACTER 16	TVTHXCHR	HEXADECIMAL CHARACTERS
1055	(41F) BITSTRING 1	TVTRSD26	RESERVED
1056	(420) BITSTRING 4	TVTRMFF	CONSTANT 'FF'S
1060	(424) BITSTRING 4	TVTRM7F	CONSTANT '7F'S
1064	SESSION INFORMATION (428) ADDRESS 4	TVTSNSET	TOTAL SNA SESSIONS FOR FTF
1068	(42C) ADDRESS 4	TVTSNSTN	TOTAL SNA SESSIONS FOR NJE
1072	(430) ADDRESS 4	TVTSNSEL	SESSION LIMIT
1080	(438) ADDRESS 8	TVTZERO	CONSTANT ZEROS
1088	(440) BITSTRING 1	TVTRSD55	RESERVED
1092	(444) ADDRESS 4	TVTJMLWA	JOB MESSAGE LOG WORK AREA

1108	(454)	CHARACTER	5	TVTCID	COMPONENT ID
1113	(459)	CHARACTER	4	TVTCIDB	COMPONENT ID BASE
1117	(45D)	BITSTRING	1	TVTRSS56	RESERVED
1118	(45E)	BITSTRING	1	TVTRSS57	RESERVED
1119	(45F)	BITSTRING	1	TVTRSS58	RESERVED
1120	(460)	ADDRESS	4	TVTRSS59	RESERVED

NJE STREAM EBCDIC STREAM ID TABLE					
1124	(464)	FIXED	2	TVTEBCST	
1124	(464)	CHARACTER	3	TVTEBCOM	COMM VLU
1127	(467)	CHARACTER	3	TVTEBCS1	1ST QUARTET
1139	(473)	CHARACTER	3	TVTEBCS2	2ND QUARTET
1151	(47F)	CHARACTER	3	TVTEBCS3	3RD QUARTET
1163	(48B)	CHARACTER	3	TVTEBCS4	4TH QUARTET
1175	(497)	CHARACTER	3	TVTEBCS5	5TH QUARTET
1187	(4A3)	CHARACTER	3	TVTEBCS6	6TH QUARTET
1199	(4AF)	CHARACTER	3	TVTEBCS7	7TH QUARTET
1212	(4BC)	FIXED	2	TVTIDEND	END OF TABLE

NJE STREAM ID TABLE					
1212	(4BC)	FIXED	2	TVTSTRID	
1212	(4BC)	BITSTRING	1	TVTSTCOM	COMM VLU
1213	(4BD)	BITSTRING	1	TVTSTID1	STREAM 1
1217	(4C1)	BITSTRING	1	TVTSTID2	STREAM 2
1221	(4C5)	BITSTRING	1	TVTSTID3	STREAM 3
1225	(4C9)	BITSTRING	1	TVTSTID4	STREAM 4
1229	(4CD)	BITSTRING	1	TVTSTID5	STREAM 5
1233	(4D1)	BITSTRING	1	TVTSTID6	STREAM 6
1237	(4D5)	BITSTRING	1	TVTSTID7	STREAM 7
1242	(4DA)	FIXED	2	TVTSTEND	END OF TABLE

RECURSIVE ABEND PARAMETERS					
1244	(4DC)	ADDRESS	4	TVTABTIM	BDTINCD RECURSIVE ABEND TIME DELAY
1248	(4E0)	BITSTRING	1	TVTABMAX	SET BY BDTINCD RECURSIVE ABEND MAX. ABENDS
1249	(4E1)	BITSTRING	1	TVTRSS60	RESERVED
1250	(4E2)	BITSTRING	1	TVTRSS61	RESERVED
1251	(4E3)	BITSTRING	1	TVTRSS62	RESERVED

BDT SHARED SUBPOOL ENTRIES					
1252	(4E4)	ADDRESS	1	TVTSSP	BDT SHR SUBPL LIST # ENT
1252	(4E4)			TVTSSPB	BEGIN SHR SUBPL ENTRIES
1252	(4E4)			TVTSRSP	DEFAULT SHARED
1253	(4E5)	ADDRESS	1	TVTSSP00	SHARED SUBPOOL 0 SHR SUBPOOL
1254	(4E6)	ADDRESS	1	TVTSSP01	SHARED SUBPOOL 1 SNA CNT BLK
1255	(4E7)	ADDRESS	1	TVTSSP02	SHARED SUBPOOL 2 SNA BUF 1
1256	(4E8)	ADDRESS	1	TVTSSP03	SHARED SUBPOOL 3 SNA BUF 2
1257	(4E9)	ADDRESS	1	TVTSSP04	SHARED SUBPOOL 4 SNA BUF 3
1258	(4EA)	ADDRESS	1	TVTSSP05	SHARED SUBPOOL 5 SNA BUF 4
1259	(4EB)	ADDRESS	1	TVTSSP06	SHARED SUBPOOL 6 MSG DS
1260	(4EC)	ADDRESS	1	TVTSSP07	SHARED SUBPOOL 7
1261	(4ED)	ADDRESS	1	TVTSSP08	SHARED SUBPOOL 8
1262	(4EE)	ADDRESS	1	TVTSSP09	SHARED SUBPOOL 9
1263	(4EF)	ADDRESS	1	TVTSSP0A	SHARED SUBPOOL 10 SAVE CP
1264	(4F0)	ADDRESS	1	TVTSSP0B	SHARED SUBPOOL 11 OCMB CP
1265	(4F1)	ADDRESS	1	TVTSSP0C	SHARED SUBPOOL 12 ICMB CP
1266	(4F2)	ADDRESS	1	TVTSSP0D	SHARED SUBPOOL 13 CSRB CP
1267	(4F3)	ADDRESS	1	TVTSSP0E	SHARED SUBPOOL 14 JCTB CP
1268	(4F4)	ADDRESS	1	TVTSSP0F	SHARED SUBPOOL 15 FCT CP
1269	(4F5)	ADDRESS	1	TVTSSP10	SHARED SUBPOOL 16 DCQE CP
1270	(4F6)	ADDRESS	1	TVTSSP11	SHARED SUBPOOL 17 TQE CP
1271	(4F7)	ADDRESS	1	TVTSSP12	SHARED SUBPOOL 18 JML CP
1272	(4F8)	ADDRESS	1	TVTSSP13	SHARED SUBPOOL 19 IFC CP
1273	(4F9)	ADDRESS	1	TVTSSP14	SHARED SUBPOOL 20 TQCP CP
1274	(4FA)	ADDRESS	1	TVTSSP15	SHARED SUBPOOL 21 NJE IFC CP
1275	(4FB)	ADDRESS	1	TVTSSP27	SHARED SUBPOOL 39 USED FOR IFC GETMAINED BUFFERS
1276	(4FC)	ADDRESS	1	TVTSSP28	SHARED SUBPOOL 40 USED FOR IFC LCT INPUT BUFFERS

BDT RESERVED SHARED SUBPOOL ENTRIES					
1277	(4FD)	ADDRESS	1	TVTSSP17	SHARED SUBPOOL 23
1278	(4FE)	ADDRESS	1	TVTSSP18	SHARED SUBPOOL 24
1279	(4FF)	ADDRESS	1	TVTSSP19	SHARED SUBPOOL 25

1280	(500)	ADDRESS	1	TVTSSP1A	SHARED SUBPOOL 26
1281	(501)	ADDRESS	1	TVTSSP1B	SHARED SUBPOOL 27
1282	(502)	ADDRESS	1	TVTSSP1C	SHARED SUBPOOL 28
1283	(503)	ADDRESS	1	TVTSSP1D	SHARED SUBPOOL 29
1283	(503)			TVTSSPE	END SHR SUBPOOL ENTRIES
1284	(504)	BITSTRING	1	TVTSSRSV	RESERVED
1360	(550)		8		END OF TABLE

#### BDTXWAIT CONDITION CODE EQUATES

1111	1111	TVTAWEX	"X'FF'" AWAIT EXIT CONDITION CODE
1...	...1	TVTAWL	"X'81'" AWAIT LIST ON CONDITION CODE
.1.1	...1	TVTAWLO	"X'51'" AWAIT LIST OFF CONDITION CODE
1...	....	TVTAW	"X'80'" AWAIT ON CONDITION CODE
.1.1	....	TVTAWO	"X'50'" AWAIT OFF CONDITION CODE

#### LAMB BDTXRTRN EQUATES

....	....	TVTLOPER	"0" ERROR RETURN FROM BDTXLOPN
....	.1..	TVTLOPNB	"4" NJE NO OUTPUT BUFFER BDTXLOPN
....	1...	TVTLOPNM	"8" NORMAL RETURN FROM BDTXLOPN
....	....	TVTLCLER	"0" ERROR RETURN FROM BDTXLCLS
....	.1..	TVTLCLNM	"4" NORMAL RETURN FROM BDTXLCLS
....	....	TVTLGTER	"0" ERROR RETURN FROM BDTXLGET
....	.1..	TVTLGTEF	"4" EOF RETURN FROM BDTXLGET
....	1...	TVTLGTED	"8" EOF RETURN FROM BDTXLGET
....	11..	TVTLGTCK	"12" CKPT RETURN FROM BDTXLGET
...1	....	TVTLGTBE	"16" EOB RETURN FROM BDTXLGET
...1	.1..	TVTLGTNM	"20" NORMAL RETURN FROM BDTXLGET
....	....	TVTLPTER	"0" ERROR RETURN FROM BDTXLPUT
....	.1..	TVTLPTBE	"4" EOB RETURN FROM BDTXLPUT
....	1...	TVTLPTCK	"8" CKPT RETURN FROM BDTXLPUT
....	11..	TVTLPTMN	"12" NORMAL RETURN FROM BDTXLPUT
....	....	TVTLRDER	"0" ERROR RETURN FROM BDTXLRD
....	.1..	TVTLRDNI	"4" NO INPUT RETURN FROM BDTXLRD
....	1...	TVTLRDNM	"8" NORMAL RETURN FROM BDTXLRD
....	....	TVTLWRER	"0" ERROR RETURN FROM BDTXLWRT
....	.1..	TVTLWRNB	"4" NO BUFFER OBTAINED RETURN
....	1...	TVTLWRNM	"8" NORMAL RETURN FROM BDTXWRT
....	....	TVTSNDER	"0" ERROR RETURN FROM BDTSNSND
....	.1..	TVTSNDNM	"4" NORMAL RETURN FROM BDTSNSND
....	....	TVTINTFA	"0" INIT SEND RPL FAILED BDTSNSND
....	.1..	TVTSNDFA	"4" VTAM SEND FAILED IN BDTSNSND
....	1...	TVTNOBUF	"8" NO BUFFER FOUND IN BDTSNSND

#### RESOURCE NAMES

NOTE RESOURCE NAMES INDEXED BY PRIORITY,  
MUST BE SPECIFIED SEQUENTIALLY TO ENSURE CORRECT

OPERATION OF THE BDTXENQ, ADEQ, ATEST ROUTINES.				
....	....	RQ	"0"	
....	...1	RSV2	"1"	
....	..1.	JNCBCTL	"2"	
....	..11	SYSUNIT	"3"	
....	.1..	CHKPNT	"4"	
....	.1.1	WTD	"5"	
....	..11.	RSV1	"6"	
....	..111	AMQ1	"7"	
....	1...	RSCARNAM	"8"	NUMBER OF RESOURCES

RESOURCE MANAGEMENT FUNCTION VALUES				
....	....	RSCNOWAT	"0"	NO WAIT
....	..1..	RSCWAIT	"4"	BUSY=WAIT
....	1...	RSCNOFCT	"8"	NO FCT
....	11..	RSCFCT	"12"	FCT
...1	....	RSCTTEST	"16"	TYPE=TEST
...1	.1..	RSCTFCT	"20"	TYPE=FCT

START OF AREAS OF TVT SAVED FOR INITIALIZATION CHECKPOINTS				
1360	(550)	FIXED	4	TVTINSAV TVT SAVED FROM HERE
1360	(550)	BITSTRING	20	TVTCIDYN DYNALLOC CARD
1380	(564)	BITSTRING	20	TVTCIDYX 5 EXTENT ENTRIES
1400	(578)	BITSTRING	20	TVTCIDAT INITIALIZATION CHECKPOINT DATA
1420	(58C)	BITSTRING	40	TVTCIDAX 10 EXTENT ENTRIES
1460	(5B4)	BITSTRING	20	TVTCICK1 CHECKPOINT RECORD 1
1480	(5C8)	BITSTRING	20	TVTCICKX 5 EXTENT ENTRIES
1500	(5DC)	BITSTRING	20	TVTCICK2 CHECKPOINT RECORD 2
1520	(5F0)	BITSTRING	20	TVTCICKY 5 EXTENT ENTRIES
1540	(604)	BITSTRING	4	TVTCIJCT JCT DDB FIXED AREA
1544	(608)	BITSTRING	40	TVTCIJCX 10 EXTENT ENTRIES
1584	(630)	BITSTRING	20	TVTDDBR1 RESERVED
1604	(644)	BITSTRING	20	TVTDDBR2 RESERVED
1624	(658)	BITSTRING	20	TVTDDBR3 RESERVED
1644	(66C)	BITSTRING	1	TVTDDBR4 RESERVED
1644	(66C)		TVTSAVLN	LENGTH OF DDB SAVE AREA
1664	(680)	FIXED	4	TVTACNTL ACCTNG TIM'G INTERV .01 SEC
1668	(684)	ADDRESS	1	TVTJBPTY DEFAULT JOB PRIORITY
1669	(685)	ADDRESS	3	TVTJBRSV RESERVED
1672	(688)	ADDRESS	4	TVTJBNTL DEFAULT JOB EXECUTION TIME
1676	(68C)	CHARACTER	8	TVTAPLID APPLICATION ID FOR OPEN ACB
1684	(694)	CHARACTER	8	TVTAPLNJ APPLICATION ID FOR NJE ACB
1692	(69C)	FIXED	4	TVTASRTM ASR TIME DELAY
1696	(6A0)	ADDRESS	4	TVTJBPRD JOB RETENTION PERIOD (DAYS)
1700	(6A4)	CHARACTER	8	TVTPASWD PASSWORD FOR OPEN ACB
1708	(6AC)	CHARACTER	8	TVTNJPAS NJE PASSWORD
1716	(6B4)	CHARACTER	2	TVTRSD25 RESERVED
1718	(6B6)	FIXED	2	TVTRSJCT RESIDENT JCT MAX COUNT
1720	(6B8)	CHARACTER	8	TVTSYSID BDT SYSTEM ID FOR FTF
1728	(6C0)	CHARACTER	8	TVTNJEID BDT SYSTEM ID FOR NJE
1736	(6C8)	ADDRESS	4	TVTTQITD TQI TIME DELAY 30 SECONDS

FAILSOFT FLAG 1 DEFINITION				
1740	(6CC)	BITSTRING	1	TVTFSG1 FAILSOFT FLAGS
	.1..	....	TVTGPBDT	"BIT1" BDT TERMINATION REQUIRED
	..1.	....	TVTGFSAC	"BIT2" BDT FAIL SOFT IS ACTIVE
	...1	....	TVTFSUFD	"BIT3" SET BY BDTABN0 UNFORMATTED DUMP TAKEN OK
	....	1...	TVTGDMPO	"BIT4" OPTIONS,DUMP=BDT
	....	..1..	TVTGDMPS	"BIT5" OPTIONS,DUMP=PRDMP
	....	...1.	TVTFSNDP	"BIT6" OPTIONS,WANTDUMP=NO
	....	...1	TVTFSASK	"BIT7" OPTIONS,WANTDUMP=ASK

FAILSOFT FLAG 2 & FEATURES DEFINITIONS				
1741	(6CD)	BITSTRING	1	TVTFSG2 FAILSOFT FLAGS
	1...	....	TVTWSIOE	"BIT0" I/O ERROR DURING WARM START
	..1..	....	TVTFEFR1	"BIT1" RESERVED
	...1.	....	TVTFEFR2	"BIT2" RESERVED
	....	1...	TVTFEFR3	"BIT3" RESERVED
	....	1...	TVTFEFR4	"BIT4" RESERVED

	....	.1..		TVTFSFR5	"BIT5" RESERVED
	....	..1.		TVTFTFFI	"BIT6" FTF FEATURE INSTALLED
	....	...1		TVTNJEFI	"BIT7" NJE FEATURE INSTALLED
BDT OPTIONS FLAG BYTE DEFINITION					
1742	(6CE)	BITSTRING	1	TVTOPTNS	BDT OPTIONS
	1...	....		TVTJESAV	"BIT0" JES3 INTERFACE AVAILABLE
	.1..	....		TVTSMIAV	"BIT1" SYSMMSG INTERCEPT AVAILABLE
	..1.	....		TVTJMLAV	"BIT2" JOB MESSAGE LOG AVAILABLE
	...1	....		TVTAUTRS	"BIT3" AUTO RESTART AVAILABLE
	....	1...		TVTSHUTA	"BIT4" SHUTTLE AVAILABLE
	....	..1.		TVTBDTRF	"BIT5" BDT RACF SUPPORT FLAG 0Y01465
	....	...1.		TVTOPTR3	"BIT6" RESERVED
	....	...1		TVTOPTR4	"BIT7" RESERVED
TQI AUTO DISABLE FLAG					
1743	(6CF)	BITSTRING	1	TVTQIDFG	AUTO DISABLE FLAG FOR TQI
	1111	1111		TVTQINOD	"X'FF'" NO AUTO DISABLE VALUE
1744	(6D0)	FIXED	4	TVTSLDRT	SYSLOG DESTINATION ROUTING TBL
SYSLOG FLAG DEFINITION					
1744	(6D0)	BITSTRING	1	TVTSYSLG	SYSLOG FLAGS
	1...	....		TVTSLGPR	"BIT0" SYSLOG=PRINT
	.1..	....		TVTSLGJS	"BIT1" SYSLOG=JES3
	..1.	....		TVTSLGW0	"BIT2" SYSLOG=WTO
	...1	....		TVTSLGP	"BIT3" LOG HAS BEEN STOPPED
	....	1...		TVTSYSR2	"BIT4" RESERVED
	....	..1.		TVTSYSR3	"BIT5" RESERVED
	....	...1.		TVTSYSR4	"BIT6" RESERVED
	....	...1		TVTSYSR5	"BIT7" RESERVED
1745	(6D1)	ADDRESS	3		BDTDCMDA SYSLOG DESTINATION ROUTE TABLE
JES IDENTIFIER					
1748	(6D4)	CHARACTER	1	TVTJES	JES IDENTIFIER
	1111	..1.		TVTJES2	"X'F2'" JES2 IDENTIFIER
	1111	..11		TVTJES3	"X'F3'" JES3 IDENTIFIER
CONSTANTS					
1749	(6D5)	CHARACTER	1	TVTSLOGC	DEFAULT BDT SYSLOG CLASS
1750	(6D6)	FIXED	2	TVTJSXMX	MAXIMUM SCHEDULED XFERS
1752	(6D8)	FIXED	4	TVTSLOGL	DEFAULT BDT SYSLOG LINE LMT
1756	(6DC)	FIXED	4	TVTSLOGP	DEFAULT BDT SYSLOG PAGE LEN
1760	(6E0)	CHARACTER	8	TVTSYSN	SYSNAME FOR PROC BDT ON
RESERVED FIELDS					
1768	(6E8)	ADDRESS	4	TVTRSD29	RESERVED
1772	(6EC)	ADDRESS	4	TVTRSD30	RESERVED
1776	(6F0)	ADDRESS	4	TVTRSD31	RESERVED
1780	(6F4)	ADDRESS	4	TVTRSD32	RESERVED
1784	(6F8)	ADDRESS	4	TVTRSD30	RESERVED
1788	(6FC)	ADDRESS	4	TVTRSD31	RESERVED
1792	(700)	ADDRESS	4	TVTRSD32	RESERVED
1796	(704)	ADDRESS	4	TVTRSD33	RESERVED
1800	(708)	ADDRESS	4	TVTRSD34	RESERVED
1804	(70C)	ADDRESS	4	TVTRSD35	RESERVED
1808	(710)	ADDRESS	4	TVTRSU01	RESERVED
1812	(714)	ADDRESS	4	TVTRSU02	RESERVED
1816	(718)	ADDRESS	4	TVTRSU03	RESERVED
1820	(71C)	ADDRESS	4	TVTRSU04	RESERVED

END OF AREAS OF TVT SAVED FOR INITIALIZATION CHECKPOINTS					
1824	(720)	FIXED	4	TVTENDSV	TVT SAVED UP TO HERE
EXECUTABLE CODE CONTAINED IN TVT					
BDTDXOID TVTS					
1824	(720)	CHARACTER	4	TVTSXHDR	CONTROL BLOCK ACRONYM
1828	(724)	CHARACTER	4	TVTSXREL	VERSION ID
1832	(728)	ADDRESS	2	TVTSXLN	XOID LENGTH
1834	(72A)	BITSTRING	8	TVTSXBISI	XACTION ORIGIN BDT SYS ID
1842	(732)	BITSTRING	8	TVTSXBSN	XACTION ORIGIN BDT SYS NAME
TRANSACTION ORIGIN TYPE					
1850	(73A)	BITSTRING	1	TVTSXTYP	XACTION ORIGIN TYPE
		....	...1	TVTSTSO	"1" TSO USER
		....	..1.	TVTSJES	"2" JES CONSOLE
		....	..11	TVTSBTCH	"3" BATCH JOB
		....	.1..	TVTSMCS	"4" MCS CONSOLE
		....	.1.1	TVTSLG	"5" JOB MESSAGE LOG
		....	.11.	TVTSFCT	"6" BDT FCT
		....	.111	TVTSJMC	"7" JES MESSAGE CLASS
		....	1...	TVTSRDEV	"8" BEGIN DEVELOPMENT
		1...	....	TVTSUSER	DEFINED XOIDXTYP
					"128" BEGIN USER DEFINED XOIDXTYP
FLAG 1 DEFINITION					
1851	(73B)	BITSTRING	1	TVTSXFL1	XOID FLAG 1
		1...	....	TVTSXMCL	"BIT0" SUPPRESSION OF MESSAGE CLASS
		.1..	....	TVTSX1R1	"BIT1" RESERVED
		..1.	....	TVTSX1R2	"BIT2" RESERVED
		...1	....	TVTSX1R3	"BIT3" RESERVED
		....	1...	TVTSX1R4	"BIT4" RESERVED
		....	.1..	TVTSX1R5	"BIT5" RESERVED
		....	..1.	TVTSX1R6	"BIT6" RESERVED
		....	...1	TVTSX1R7	"BIT7" RESERVED
MISCELLANEOUS INFORMATION					
1852	(73C)	CHARACTER	8	TVTSXDDN	TRANSACTION ORIGIN DDNAME
1852	(73C)	CHARACTER	8	TVTSUSID	TSO USERID
1852	(73C)	CHARACTER	8	TVTSCNDD	JES CONSOLE DDNAME
1852	(73C)	CHARACTER	8	TVTSJCLS	JES MESSAGE CLASS
1852	(73C)	CHARACTER	8	TVTSBJNM	BATCH JOB NAME
1852	(73C)	ADDRESS	1	TVTSMCSI	MCS CONSOLE ID
1852	(73C)	BITSTRING	2	TVTSBJNO	BDT JOB NUMBER
1852	(73C)	BITSTRING	8	TVTSDDRS	DDNAME
RESERVED FIELDS					
1860	(744)	BITSTRING	4	TVTSXRD2	RESERVED
1864	(748)	BITSTRING	4	TVTSXRD3	RESERVED
1868	(74C)	BITSTRING	4	TVTSXRS1	RESERVED
1872	(750)	BITSTRING	4	TVTSXRS2	RESERVED
1876	(754)	BITSTRING	4	TVTSXRU1	RESERVED
1880	(758)	BITSTRING	4	TVTSXRU2	RESERVED
1880	(758)			TVTSMCSA	"TVTSMCSI+1,1,C'C'"MCS CONSOLE UX28 AUTH
1880	(758)			TVTSXEND	END OF XOID
1880	(758)			TVTSXOID	XOID EQUATE
1880	(758)			TVTSXALL	BSI EQUATE
BDTXFDAP CODE=805,DUMP=YES					
1884	(75C)	FIXED	2	TVTDM805	
1906	(772)	FIXED	2	FAIL0013	
1906	(772)	FIXED	2	NGSD0013	
1906	(772)	FIXED	2		
ABEND (1),DUMP ABEND W/SPECIFIED FAILURE CODE					
1910	(776)	FIXED	2		
1922	(782)	CHARACTER	4	CGSD0013	



BDTXFDAP CODE=(R1),DUMP=YES					
1934	(78E)	FIXED	2		
1956	(7A4)	FIXED	2	FAIL0018	
1956	(7A4)	FIXED	2	NGSD0018	
ABEND (1),DUMP ABEND W/SPECIFIED FAILURE CODE					
1956	(7A4)	FIXED	2		
1968	(7B0)	CHARACTER	4	CGSD0018	
BDTXFDAP CODE=651,DUMP=YES					
1972	(7B4)	FIXED	2	TVTDM651	
1994	(7CA)	FIXED	2	FAIL0023	
1994	(7CA)	FIXED	2	NGSD0023	
1994	(7CA)	FIXED	2		
ABEND (1),DUMP ABEND W/SPECIFIED FAILURE CODE					
1998	(7CE)	FIXED	2		
2010	(7DA)	CHARACTER	4	CGSD0023	
2016	(7E0)		8	TVTEND	END OF TABLE
END OF BDTDTVT (TVTABLE)					
BDTDDDB					
DATA DESCRIPTION BLOCK					
DATA DESCRIPTION BLOCK (DDB) REQUEST AREA					
0	(0)	ADDRESS	4	DDBRQADR	AREA ADDR
4	(4)	ADDRESS	4	DDBRQDSP	DISPL INTO DATA
8	(8)	ADDRESS	4	DDBRQLEN	LEN OF DATA
12	(C)	BITSTRING	1	DDBRQEND	END OF ENTRY
12	(C)	BITSTRING	1	DDBRQSIZE	SIZE OF ENTRY
DATA DESCRIPTION BLOCK (DDB) FIXED AREA					
12	(C)	FIXED	4	DDBFX	START OF DDB FIXED AREA
12	(C)	BITSTRING	1	DDBFXENO	NO OF EXTENTS
13	(D)	BITSTRING	3	DDBFXLEN	LEN OF DATA
16	(10)	BITSTRING	1	DDBFXEND	END OF ENTRY
16	(10)	BITSTRING	1	DDBFXSIZE	SIZE OF ENTRY
DATA DESCRIPTION BLOCK (DDB) EXTENT ENTRY					
16	(10)	FIXED	4	DDBEX	START OF DDB EXTENT ENTRY
16	(10)	BITSTRING	1	DDBEXNOR	NO OF RCDS IN EXTENT
17	(11)	BITSTRING	3	DDBEXRBA	STARTING REL BLOCK ADDR (BDAM)
20	(14)	BITSTRING	1	DDBEXEND	END OF ENTRY
20	(14)	BITSTRING	1	DDBEXSIZE	SIZE OF ENTRY
	....	1...		DDBFIXSZ	"L'DDBFXSIZE+L'DDBEXSIZE" SIZE OF SINGLE EXTENT
	...1	.1..		DDBSZ	DDBSZ
					"L'DDBRQSIZE+L'DD BFXSIZE+DDBEXSIZE" SIZE OF FULL DDB
CROSS REFERENCE					
NAME	HEX OFFSET	HEX VALUE	LEVEL		
AMQ	550	7	2		
CGSD0023	7DA	C7E2	2		
CHKPNT	550	4	2		
DDBEX	10		2		
DDBEXEND	14		2		
DDBEXNOR	10		2		
DDBEXRBA	11		2		
DDBEXSIZE	14		2		
DDBFIXSZ	14	8	2		
DDBFX	C		2		
DDBFXEND	10		2		
DDBFXENO	C		2		
DDBFXLEN	D		2		
DDBFXSIZE	10		2		
DDBRQADR	0		2		
DDBRQDSP	4		2		
DDBRQEND	C		2		
DDBRQLEN	8		2		

DDBRQSZ	C		2
DDBSZ	14	14	2
JNCBCTL	550	2	2
RQ	550	0	2
RSCARNAM	550	8	2
RSCFCT	550	C	2
RSCNOFCT	550	8	2
RSCNOWAT	550	0	2
RSCTFCT	550	14	2
RSCTTEST	550	10	2
RSCWAIT	550	4	2
RSV1	550	6	2
RSV2	550	1	2
SYSUNIT	550	3	2
TVTABDCB	1C8		2
TVTABLE	0	0	2
TVTABMAX	4E0	3	2
TVTABMN0	58		2
TVTABND0	5C		2
TVTABNGT	134		2
TVTABSRV	60		2
TVTABTIM	4DC		2
TVTACECF	3B2	0	2
TVTACEC1	3B2	10	2
TVTACEC2	3B2	8	2
TVTACEC3	3B2	4	2
TVTACEC4	3B2	2	2
TVTACEC5	3B2	1	2
TVTACKNF	3BA	10	2
TVTACNTL	680	0	2
TVTACPST	3B2	80	2
TVTADEQ	20		2
TVTADFCT	74		2
TVTADFQE	240		2
TVTADMSK	3D0	FF	2
TVTAENQ	20	20	2
TVTAGTMN	28		2
TVTALLOC	2C		2
TVTAMECB	29D		2
VTAMQUE	2AC		2
VTANALZ	3B6	10	2
VTAPLID	68C	4040	2
VTAPLNJ	694	4040	2
VTAPTMM	24		2
VTASAVE	18		2
VTASRTM	69C	0	2
VTASVRT	1C		2
TVTATEST	20	20	2
TVTATPST	3B2	20	2
VTAUTRS	6CE	10	2
VTAW	550	80	2
VTAWAIT	44	80	2
VTAWEX	550	FF	2
VTAWL	550	81	2
VTAWLO	550	51	2
VTAWO	550	50	2
VTAWTA	45		2
VTAWTE	54	FF	2
VTAWTEA	55		2
VTAWTL	48	81	2
VTAWTLA	49		2
VTAWTOA	4D		2
VTAWTOF	4C	50	2
VTAWTOL	50	51	2
VTBDKEY	130		2
VTBDTPL	3D4	0	2
VTBLANK	3D5	4040	2
VTBTAB	2B0		2
VTBUFSZ	356	0	2
TVTCALL0	27C	40	2
TVTCDECf	3BF	0	2
TVTCDECX	3C0	0	2
TVTCDEC1	3BF	20	2
TVTCDEXT	3BF	1	2
TVTCDIFC	3BF	80	2
TVTCDJES	3BF	8	2
TVTCDMCS	3BF	10	2
TVTCDMOT	3BF	4	2
TVTCDNJE	3C0	80	2
TVTCDOCM	3BF	40	2
TVTCDRS1	3C0	20	2
TVTCDRS2	3C0	10	2

TVTCDRS3	3C0	8	2
TVTCDRS4	3C0	4	2
TVTCDRS5	3C0	2	2
TVTCDRS6	3C0	1	2
TVTCDSI	3BF	2	2
TVTCOTRM	3C0	40	2
TVTCICKX	5C8	0	2
TVTCICKY	5F0	0	2
TVTCICK1	5B4	0	2
TVTCICK2	5DC	0	2
TVTCID	454	F3F0	2
TVTCIDAT	578	0	2
TVTCIDAX	58C	0	2
TVTCIDB	459	F5F6	2
TVTCIDYN	550	0	2
TVTCIDYX	564	0	2
TVTCIJCT	604	0	2
TVTCIJCX	608	0	2
TVTCCKPAR	2B4		2
TVTCCKPNT	130		2
TVTCCLDAP	278	0	2
TVTCMDVF	3BA	20	2
TVTCMSDE	3BA	8	2
TVTCMTCB	2B8		2
TVTCOLDS	3B6	80	2
TVTCONR1	3B7	8	2
TVTCONR2	3B7	4	2
TVTCONR3	3B7	2	2
TVTCONR4	3B7	1	2
TVTCONTS	3B7	20	2
TVTCPSD1	3BD	0	2
TVTCPSD2	3BE	0	2
TVTCPUF	3E0	0	2
TVTCPUID	35C		2
TVTCPUVC	35C	0	2
TVTCPUVX	35D	0	2
TVTCP1R1	3BD	10	2
TVTCP1R2	3BD	8	2
TVTCP1R3	3BD	4	2
TVTCP1R4	3BD	2	2
TVTCP1R5	3BD	1	2
TVTCSECF	6C		2
TVTCSEF	138		2
TVTCSPST	6C	80	2
TVTCSRCP	70		2
TVTCSRQR	6C		2
TVTCSRQU	2BC		2
TVTCRS1	6C	40	2
TVTCRS2	6C	20	2
TVTCRS3	6C	10	2
TVTCRS4	6C	8	2
TVTCRS5	6C	4	2
TVTCRS6	6C	2	2
TVTCSTRM	6C	1	2
TVTDDBFX	348	0	2
TVTDDBRQ	33C	0	2
TVTDDBR1	630	0	2
TVTDDBR2	644	0	2
TVTDDBR3	658	0	2
TVTDDBR4	66C	0	2
TVTDFACT	3E4	94D	2
TVTDISCS	3B7	40	2
TVTDJNR	13C		2
TVTDLFCT	78		2
TVTDM805	75C		2
TVTDQMSG	110		2
TVTDYNS0	27C	80	2
TVTEBCOM	464	C3D6	2
TVTEBCST	464		2
TVTEBCS1	467	D6D1	2
TVTEBCS2	473	D6D1	2
TVTEBCS3	47F	D6D1	2
TVTEBCS4	48B	D6D1	2
TVTEBCS5	497	D6D1	2
TVTEBCS6	4A3	D6D1	2
TVTEBCS7	4AF	D6D1	2
TVTEFTOP	2C0		2
TVTEND	550		2
TVTENDSV	720		2
TVTENFCT	7C		2
TVTEPE	1C8		2
TVTEPS	18		2

TVTEXTL	184		2
TVTFALON	3BE	FF	2
TVTFCTCP	1D8		2
TVTFCTSD	3BD	80	2
TVTFCTTP	2C8		2
TVTFDJNR	8C		2
TVTFLDAP	64		2
TVTFSASK	6CC	1	2
TVTFSFG1	6CC	0	2
TVTFSFG2	6CD	0	2
TVTFSFR1	6CD	40	2
TVTFSFR2	6CD	20	2
TVTFSFR3	6CD	10	2
TVTFSFR4	6CD	8	2
TVTFSFR5	6CD	4	2
TVTFSNDP	6CC	2	2
TVTFSUFD	6CC	10	2
TVTFTFEC	27C	4	2
TVTFTFFI	6CD	2	2
TVTGDMPO	6CC	8	2
TVTGDMPS	6CC	4	2
TVTGETLU	A4		2
TVTGFSAC	6CC	20	2
TVTGPPBDT	6CC	40	2
TVTGSDAX	68		2
TVTGTFTCT	80		2
TVTHOTST	3B6	20	2
TVTHXCHR	40F	F0F1	2
TVTICMBS	3BE	80	2
TVTICMCP	1DC		2
TVTID	0	E3E5	2
TVTIDEND	4BC		2
TVTIFC	208		2
TVTIFCCH	36C	0	2
TVTIFCCP	1E0		2
TVTIFCCT	364	0	2
TVTIFCGH	368	0	2
TVTIFCGM	360	0	2
TVTIFCMF	3BA	40	2
TVTIFCSD	3BE	40	2
TVTIFECF	88		2
TVTIFNCP	1E4		2
TVTIFPST	88	80	2
TVTIFSND	88		2
TVTINCMF	1CC	80	2
TVTINDAT	C		2
TVTINDTA	1D0		2
TVTINIR1	1CC	40	2
TVTINIR2	1CC	20	2
TVTINIR3	1CC	10	2
TVTINIR4	1CC	8	2
TVTINIR5	1CC	4	2
TVTINIR6	1CC	2	2
TVTINIR7	1CC	1	2
TVTINITF	1CC	0	2
TVTINITS	3B7	80	2
TVTINSAV	550		2
TVTINTFA	550	0	2
TVTINTIM	10		2
TVTITECB	298		2
TVTITKPM	2D0		2
TVTJBNTL	688		2
TVTJBPTY	684		2
TVTJBPRD	6A0		2
TVTJBRSV	685		2
TVTJCBCP	1E8		2
TVTJCTSD	3BD	40	2
TVTJES	6D4	F0	2
TVTJESAV	6CE	80	2
TVTJES2	6D4	F2	2
TVTJES3	6D4	F3	2
TVTJMLAV	6CE	20	2
TVTJMLCP	1EC		2
TVTJMLSD	3BE	10	2
TVTJMLWA	444		2
TVTJNM	2D4		2
TVTJNUMR	94		2
TVTJOBNR	90		2
TVTJQX	2D8		2
TVTJSACT	3B5	40	2
TVTJSCKP	3B5	20	2
TVTJSCMX	394	0	2

TVTJSDUC	3B4	80	2
TVTJSEFA	3B4	2	2
TVTJSEFN	3B4	10	2
TVTJSFL1	3B4	0	2
TVTJSFL2	3B5	0	2
TVTJSFR1	3B5	80	2
TVTJSFR2	3B5	10	2
TVTJSFR3	3B5	8	2
TVTJSFR4	3B5	4	2
TVTJSFR5	3B5	2	2
TVTJSFR6	3B5	1	2
TVTJSGPS	3B4	80	2
TVTJSJCA	3B4	80	2
TVTJSLPS	3B4	4	2
TVTJSNPS	3B4	20	2
TVTJSPRG	3B4	40	2
TVTJSRPS	3B4	1	2
TVTJSSFC	2DC		2
TVTJSSNJ	9C		2
TVTJSSRT	98		2
TVTJSTRM	3B4	8	2
TVTJSTSC	3B4	80	2
TVTJSXMX	6D6	40	2
TVTLBDCB	2E0		2
TVTLCCLER	550	0	2
TVTLCCLNM	550	4	2
TVTLCCLS0	B0		2
TVTLCTUN	20C		2
TVTLGET0	B8		2
TVTLGREC	CC		2
TVTLGTCK	550	C	2
TVTLGTED	550	10	2
TVTLGTED	550	8	2
TVTLGTEF	550	4	2
TVTLGTER	550	0	2
TVTLGTNM	550	14	2
TVTLNGTH	8	550	2
TVTLNOHI	396	28	2
TVTLNOLO	398	14	2
TVTLNSDE	3BA	2	2
TVTLOPER	550	0	2
TVTLOPN0	AC		2
TVTLOPNB	550	4	2
TVTLOPNM	550	8	2
TVTLPTCK	550	8	2
TVTLPTED	550	4	2
TVTLPTER	550	0	2
TVTLPTNM	550	C	2
TVTLPUT0	B4		2
TVTLRDER	550	0	2
TVTLRDNI	550	4	2
TVTLRDNM	550	8	2
TVTLRD0	BC		2
TVTLWRER	550	0	2
TVTLWRNB	550	4	2
TVTLWRNM	550	8	2
TVTLWRT0	C0		2
VTMCECB	2A0		2
VTMCOFF	2A0	7F	2
VTMCON	2A0	80	2
VTMECB	29C		2
VTMESAG	148		2
VTMFMEP	150		2
VTMODLK	144		2
VTMSECB	2A4		2
VTMSGCF	3C1	0	2
VTMSGCM	3C1	20	2
VTMSGDV	224		2
VTMSGOC	3C1	80	2
VTMSGQU	2CC		2
VTMSGR1	3C1	10	2
VTMSGR2	3C1	8	2
VTMSGR3	3C1	4	2
VTMSGR4	3C1	2	2
VTMSGR5	3C1	1	2
VTMSGTM	3C1	1	2
VTMSGTP	3C1	40	2
VTMSOFF	2A4	7F	2
VTMSON	2A4	80	2
VTMSTCB	1D4		2
VTMTTECB	29C	80	2
VTMTOFF	29C	7F	2

TVTMTON	29C	80	2
TVTNETOP	2C4		2
TVTNJEEC	27C	2	2
TVTNJEFI	6CD	1	2
TVTNJEID	6C0	4040	2
TVTNJPAS	6AC	4040	2
TVTNMSG	14C		2
TVTN0BUF	550	8	2
TVTNRDAP	274	0	2
TVTNUCNA	2ED		2
TVTNUCND	2EC	80	2
TVTNUECB	2A8		2
TVTNUMAP	1F0		2
TVTOCMBS	3BE	20	2
TVTOCMCP	1F4		2
TVTOCMQU	2F0		2
TVTOMPST	3B2	40	2
TVTOPTNS	6CE	0	2
TVTOPTR2	6CE	4	2
TVTOPTR3	6CE	2	2
TVTOPTR4	6CE	1	2
TVTPABMN	27C	8	2
TVTPASWD	6A4	4040	2
TVTPCMDV	27D	80	2
TVTPERR	27D	20	2
TVTPFLG1	27C	0	2
TVTPFLG2	27D	0	2
TVTPF2R1	27D	8	2
TVTPF2R2	27D	4	2
TVTPF2R3	27D	2	2
TVTPF2R4	27D	1	2
TVTPGRGS	27D	10	2
TVTPGRJS	27D	40	2
TVTPRES0	27C	10	2
TVTPRES4	27C	20	2
TVTPRMST	3B6	8	2
TVTPTERM	27C	1	2
TVTPTFCT	84		2
TVTPUTLU	A8		2
TVTQIDFG	6CF	0	2
TVTQINOD	6CF	FF	2
TVTRALC0	DC		2
TVTRCLS0	E0		2
TVTRELNR	14	F1F0	2
TVTRFMT0	D8		2
TVTRLTTB	214		2
TVTRMFF	420	FFFF	2
TVTRM7F	424	7F7F	2
TVTR0PN0	E4		2
TVTRPRG0	E8		2
TVTRQTB A	114		2
TVTRQTB D	118		2
TVTRQTB P	11C		2
TVTRRED0	EC		2
TVTRSDAP	270	0	2
TVTRSD01	D0		2
TVTRSD02	D4		2
TVTRSD05	15C		2
TVTRSD06	168		2
TVTRSD10	180		2
TVTRSD11	188		2
TVTRSD12	18C		2
TVTRSD13	190		2
TVTRSD14	194		2
TVTRSD15	198		2
TVTRSD17	228		2
TVTRSD18	22C		2
TVTRSD19	2E4		2
TVTRSD20	30C		2
TVTRSD21	310		2
TVTRSD22	314		2
TVTRSD23	318		2
TVTRSD24	31C		2
TVTRSD25	6B4	4040	2
TVTRSD26	41F	0	2
TVTRSD29	6E8		2
TVTRSD30	6EC		2
TVTRSD31	6F0		2
TVTRSD32	6F4		2
TVTRSD33	350	0	2
TVTRSD34	358		2
TVTRSD36	39A	0	2

TVTRSD37	39C	0	2
TVTRSD38	39E	0	2
TVTRSD39	3A0	0	2
TVTRSD40	3A2	0	2
TVTRSD41	3A4	0	2
TVTRSD44	3B3	0	2
TVTRSD47	3C2	0	2
TVTRSD51	140		2
TVTRSD53	3C3	0	2
TVTRSD54	3C4	0	2
TVTRSD55	440	0	2
TVTRSD56	380	0	2
TVTRSD57	384	0	2
TVTRSD58	388	0	2
TVTRSD59	38C	0	2
TVTRSD60	390	0	2
TVTRSJCT	6B6	0	2
TVTRSS05	19C		2
TVTRSS06	1A0		2
TVTRSS07	1A4		2
TVTRSS08	1A8		2
TVTRSS09	1AC		2
TVTRSS10	1B0		2
TVTRSS11	1B4		2
TVTRSS12	1B8		2
TVTRSS13	1BC		2
TVTRSS14	1C0		2
TVTRSS15	1C4		2
TVTRSS16	230		2
TVTRSS17	234		2
TVTRSS18	238		2
TVTRSS19	28C		2
TVTRSS20	290		2
TVTRSS21	294		2
TVTRSS23	320		2
TVTRSS24	324		2
TVTRSS25	328		2
TVTRSS26	32C		2
TVTRSS27	330		2
TVTRSS28	334		2
TVTRSS29	338		2
TVTRSS30	6F8		2
TVTRSS31	6FC		2
TVTRSS32	700		2
TVTRSS33	704		2
TVTRSS34	708		2
TVTRSS35	70C		2
TVTRSS40	3A6	0	2
TVTRSS41	3A8	0	2
TVTRSS42	3AA	0	2
TVTRSS43	3AC	0	2
TVTRSS44	3AE	0	2
TVTRSS45	3B0	0	2
TVTRSS48	3C5	0	2
TVTRSS49	3C6	0	2
TVTRSS50	3C7	0	2
TVTRSS51	3C8	0	2
TVTRSS52	3C9	0	2
TVTRSS53	3CA	0	2
TVTRSS54	3CB	0	2
TVTRSS55	3CC	0	2
TVTRSS56	45D	0	2
TVTRSS57	45E	0	2
TVTRSS58	45F	0	2
TVTRSS59	460		2
TVTRSS60	4E1	0	2
TVTRSS61	4E2	0	2
TVTRSS62	4E3	0	2
TVTRSTBL	2F4		2
TVTRSTFL	3B6	0	2
TVTRSTPU	210		2
TVTRSTR1	3B6	4	2
TVTRSTR2	3B6	2	2
TVTRSTR3	3B6	1	2
TVTRSU01	710		2
TVTRSU02	714		2
TVTRSU03	718		2
TVTRSU04	71C		2
TVTRSU05	370		2
TVTRSU06	374		2
TVTRSU07	378		2
TVTRSU08	37C		2

TVTRSV01	260		2
TVTRSV02	264		2
TVTRSV03	268		2
TVTRSV04	26C		2
TVTRSV05	27E	0	2
TVTRSV06	280		2
TVTRSV07	284		2
TVTRSV08	288		2
TVTRWRT0	F0		2
TVTSAVSD	3BE	8	2
TVTSBJNM	73C		2
TVTSBJNO	73C		2
TVTSBTCH	73A	3	2
TVTSCAN	2FC		2
TVTSCDTA	104		2
TVTSCNDD	73C		2
TVTSCPD	1F8		2
TVTSDDRS	73C	0	2
TVTSDVBL	174	174	2
TVTSETC	3B7	20	2
TVTSETD	3B7	40	2
TVTSETI	3B7	80	2
TVTSETS	3B7	10	2
TVTSFCT	73A	6	2
TVTSHRSP	4E5	4E5	2
TVTSHUTA	6CE	8	2
TVTSJCLS	73C		2
TVTSJES	73A	2	2
TVTSJMC	73A	7	2
TVTSLACB	174		2
TVTSLDRT	6D0		2
TVTSLEXL	178		2
TVTSLGJS	6D0	40	2
TVTSLGP	6D0	10	2
TVTSLGPR	6D0	80	2
TVTSLGWO	6D0	20	2
TVTSLOG	73A	5	2
TVTSLOGC	6D5	C1	2
TVTSLOGL	6D8	1	2
TVTSLOGP	6DC	0	2
TVTSLRPL	17C		2
TVTSMCS	73A	4	2
TVTSMCSA	73D	73D	2
TVTSMCSI	73C		2
TVTSMIAV	6CE	40	2
TVTSNACT	3B9	80	2
TVTSNASR	3B9	8	2
TVTSNAST	3B9	1	2
TVTSNBP	218		2
TVTSNCLS	F8		2
TVTSNCPS	3B9	40	2
TVTSNDER	550	0	2
TVTSNDFA	550	4	2
TVTSNDNM	550	4	2
TVTSNECF	3B9	0	2
TVTSNGET	FC		2
TVTSNIDL	3B9	10	2
TVTSNIMP	3B9	2	2
TVTSNLTP	21C		2
TVTSNOPN	F4		2
TVTSNPUT	100		2
TVTSNRD	108		2
TVTSNSEL	430		2
TVTSNSET	428		2
TVTSNSTN	42C		2
TVTSNWAT	3B9	4	2
TVTSNWRK	3B9	20	2
TVTSNWRT	10C		2
TVTSPDCB	300		2
TVTSPNDS	3B7	10	2
TVTSRDEV	73A	8	2
TVTSSCVT	304		2
TVTSSP	4E4		2
TVTSSPB	4E5	4E5	2
TVTSSPE	504	504	2
TVTSSP0A	4EF		2
TVTSSP0B	4F0		2
TVTSSP0C	4F1		2
TVTSSP0D	4F2		2
TVTSSP0E	4F3		2
TVTSSP0F	4F4		2
TVTSSP00	4E5		2



TVTSSP01	4E6	2
TVTSSP02	4E7	2
TVTSSP03	4E8	2
TVTSSP04	4E9	2
TVTSSP05	4EA	2
TVTSSP06	4EB	2
TVTSSP07	4EC	2
TVTSSP08	4ED	2
TVTSSP09	4EE	2
TVTSSP1A	500	2
TVTSSP1B	501	2
TVTSSP1C	502	2
TVTSSP1D	503	2
TVTSSP10	4F5	2
TVTSSP11	4F6	2
TVTSSP12	4F7	2
TVTSSP13	4F8	2
TVTSSP14	4F9	2
TVTSSP15	4FA	2
TVTSSP17	4FD	2
TVTSSP18	4FE	2
TVTSSP19	4FF	2
TVTSSP27	4FB	2
TVTSSP28	4FC	2
TVTSRSV	504	0
TVTSTATE	3B7	0
TVTSTCLD	3B8	1
TVTSTCOM	4BC	0
TVTSTEND	4DA	2
TVTSTFLG	3B8	0
TVTSTFR3	3B8	8
TVTSTFR4	3B8	4
TVTSTGLS	2E8	2
TVTSTID1	4BD	9899
TVTSTID2	4C1	A8A9
TVTSTID3	4C5	B8B9
TVTSTID4	4C9	C8C9
TVTSTID5	4CD	D8D9
TVTSTID6	4D1	E8E9
TVTSTID7	4D5	F8F9
TVTSTOPN	3B8	20
TVTSTORS	3B8	10
TVTSTRID	4BC	2
TVTSRSM	3B8	40
TVTSTS0	73A	1
TVTSTSPN	3B8	80
TVTSTVON	3B8	2
TVTSUMTF	3BA	80
TVTSUPC	154	2
TVTSUSER	73A	80
TVTSUSID	73C	2
TVTSVCPB	1FC	2
TVTSXALL	72A	72A
TVTSXBSI	72A	0
TVTSXBSN	732	0
TVTSXDDN	73C	2
TVTSXEND	75C	75C
TVTSXFL1	73B	0
TVTSXHDR	720	E7D6
TVTSXLEN	728	3C
TVTSXMCL	73B	80
TVTSX0ID	720	720
TVTSXRD2	744	0
TVTSXRD3	748	0
TVTSXREL	724	F1F0
TVTSXRS1	74C	0
TVTSXRS2	750	0
TVTSXRU1	754	0
TVTSXRU2	758	0
TVTSXTYP	73A	0
TVTSX1R1	73B	40
TVTSX1R2	73B	20
TVTSX1R3	73B	10
TVTSX1R4	73B	8
TVTSX1R5	73B	4
TVTSX1R6	73B	2
TVTSX1R7	73B	1
TVTSYSID	6B8	4040
TVTSYSLG	6D0	0
TVTSYSN	6E0	4040
TVTSYSR2	6D0	8
TVTSYSR3	6D0	4

TVTSYSR4	6D0	2	2
TVTSYSR5	6D0	1	2
TVTSZBUF	354		2
TVTSZBUX	354	0	2
TVTTQCSO	3BC	80	2
TVTTQECF	3BA	0	2
TVTTQECF	200		2
TVTTQER4	3BA	1	2
TVTTQES0	3BE	4	2
TVTTQICP	204		2
TVTTQIFG	3BC	0	2
TVTTQINO	3BB	FF	2
TVTTQIOF	3BB	0	2
TVTTQISD	3BD	20	2
TVTTQITD	6C8		2
TVTTQPST	3BA	FE	2
TVTTQRS1	3BC	20	2
TVTTQRS2	3BC	10	2
TVTTQRS3	3BC	8	2
TVTTQRS4	3BC	4	2
TVTTQRS5	3BC	2	2
TVTTQRS6	3BC	1	2
TVTTQXSD	3BC	40	2
TVTTRTAB	2F8		2
TVTTUAM	158		2
TVTVATR	C8		2
TVTVERS	4	F2F0	2
TVTVMSYS	35D	FF	2
TVTWARMS	3B6	40	2
TVTWFCF	308		2
TVTWSIOE	6CD	80	2
TVTWTOLA	51		2
VTXACC	16C		2
VTXBPPL	30		2
VTXCKPT	A0		2
VTXCOMP	128		2
VTXCPD	34		2
VTXDCMP	12C		2
VTXDECFF	25C	0	2
VTXDIFC	25C	40	2
VTXDPL	40		2
VTXDQCT	244		2
VTXDQHI	248		2
VTXDQLO	24A		2
VTXDQR1	25C	20	2
VTXDQR2	25C	10	2
VTXDQR3	25C	8	2
VTXDQR4	25C	4	2
VTXDQR5	25C	2	2
VTXDQR6	25C	1	2
VTXDQUE	240		2
VTXDXQD	25C	80	2
VTXFER	220		2
VTXGCL	38		2
VTXJCT	120		2
VTXJQE	124		2
VTXLOG	170		2
VTXMQ	250		2
VTXMQCT	254		2
VTXMQHI	258		2
VTXMQLO	25A		2
VTXMQUE	250		2
VTXNSDE	3BA	4	2
VTXQIDF	160		2
VTXRCL3	C		2
VTXTIME	164		2
VTXTRC	C4		2
VTZERO	438	0	2
WTD	550	5	2

## Chapter 14. Trace Work Area – TWA

The TWA is an input control block for the BDTGRTX trace facility module. At the time of entry to BDTGRTX, register 11 points to the TWA data area.

There is one TWA for each resident BDT function and for each scheduled job.

<b>Function:</b>	The contents of the TWA are used to create a trace entry in the BDT trace table.
<b>Macro ID:</b>	BDTDTWA
<b>DSECT name:</b>	TWASTART
<b>Created by:</b>	BDTGRFC
<b>Size:</b>	Hex CC bytes
<b>Pointed to by:</b>	GSDTWA
<b>Location:</b>	The FCT subpool

OFFSETS	TYPE	LENGTH	NAME	DESCRIPTION
	TRACE WORK AREA			
0	(0) CHARACTER	4	TWACBID	CONTROL BLOCK ID
4	(4) CHARACTER	4	TWAREL	VERSION RELEASE ID
8	(8) ADDRESS	2	TWALEN	CONTROL BLOCK SIZE
10	(A) BITSTRING	1	TWAWORK	GENERIC FOR TWA WORK AREA
10	(A) CHARACTER	4	TWANAME	CHARS 4 7 OF MODULE NAME
14	(E) BITSTRING	1	TWARES	RESERVED FOR DEV
15	(F) CHARACTER	1	TWAID	ID FOR THIS TRACE ENTRY
16	(10) ADDRESS	2	TWAOFF	OFFSET IN MOD FOR BDTXTRC
20	(14) FIXED	4	TWATW	GENERIC FOR ALL TWATW WORDS
20	(14) ADDRESS	4	TWATW1	TRC ENT BDTXTRC ENTRY WORD 1
24	(18) ADDRESS	4	TWATW2	TRC ENT BDTXTRC ENTRY WORD 2
28	(1C) ADDRESS	4	TWATW3	TRC ENT BDTXTRC ENTRY WORD 3
32	(20) ADDRESS	4	TWATW4	TRC ENT BDTXTRC ENTRY WORD 4
36	(24) ADDRESS	4	TWATW5	TRC ENT BDTXTRC ENTRY WORD 5
40	(28) ADDRESS	4	TWATW6	TRC ENT BDTXTRC ENTRY WORD 6
44	(2C) BITSTRING	1	TWATWEND	GENERIC FOR ALL TWATW WORDS
44	(2C) BITSTRING	1	TWAREGS	TRC ENT REG SAVE AREA
44	(2C) ADDRESS	4	TWAR00	TRC ENT REG 00
48	(30) ADDRESS	4	TWAR01	TRC ENT REG 01
52	(34) ADDRESS	4	TWAR02	TRC ENT REG 02
56	(38) ADDRESS	4	TWAR03	TRC ENT REG 03
60	(3C) ADDRESS	4	TWAR04	TRC ENT REG 04
64	(40) ADDRESS	4	TWAR05	TRC ENT REG 05
68	(44) ADDRESS	4	TWAR06	TRC ENT REG 06
72	(48) ADDRESS	4	TWAR07	TRC ENT REG 07
76	(4C) ADDRESS	4	TWAR08	TRC ENT REG 08
80	(50) ADDRESS	4	TWAR09	TRC ENT REG 09
84	(54) ADDRESS	4	TWAR10	TRC ENT REG 10
88	(58) ADDRESS	4	TWAR11	TRC ENT REG 11
92	(5C) ADDRESS	4	TWAR12	TRC ENT REG 12
96	(60) ADDRESS	4	TWAR13	TRC ENT REG 13
100	(64) ADDRESS	4	TWAR14	TRC ENT REG 14
104	(68) ADDRESS	4	TWAR15	TRC ENT REG 15
108	(6C) ADDRESS	4	TWASAVE	BDTXTRC REG SAVE AREA
176	(B0) ADDRESS	8	TWASTCL	TRC ENT TIME FIELD
184	(B8) ADDRESS	4	TWARETC	RC FROM LAST GRTX CALL
188	(BC) ADDRESS	4	TWARES1	RES FOR DESIGN
192	(C0) ADDRESS	4	TWARES2	RES FOR DESIGN
196	(C4) ADDRESS	4	TWARES3	RES FOR SERVICE
200	(C8) ADDRESS	4	TWARES4	RES FOR SERVICE
204	(CC) BITSTRING	1	TWAEND	END of TWA
	11.. 11..		TWASIZE	LENGTH OF TWA
	11.. ..1.		TWAWORKL	LENGTH OF TWA WORK AREA
	...1 1...		TWATWL	LTH FOR GENERIC TWATW WORDS



## Chapter 15. Transaction Origin Data Area – XOID

The XOID defines the origin of the transaction.

<b>Function:</b>	The XOID defines the origin of the transaction.
<b>Macro ID:</b>	BDTGXOID
<b>DSECT name:</b>	XHDR
<b>Size:</b>	Hex 3C bytes
<b>Location:</b>	Subpool 251

OFFSETS		TYPE	LENGTH	NAME	DESCRIPTION
0	(0)	CHARACTER	4	XHDR	CONTROL BLOCK ACRONYM
4	(4)	CHARACTER	4	XREL	VERSION ID
8	(8)	ADDRESS	2	XLEN	XOID LENGTH
10	(A)	BITSTRING	8	XBSI	XACTION ORIGIN BDT SYS ID
18	(12)	BITSTRING	8	XBSN	XACTION ORIGIN BDT SYS NAME
26	TRANSACTION ORIGIN TYPE (1A)	BITSTRING	1	XTYP	XACTION ORIGIN TYPE
		....	...1	TSO	"1" TSO USER
		....	..1.	JES	"2" JES CONSOLE
		....	..11	BTCH	"3" BATCH JOB
		....	.1..	MCS	"4" MCS CONSOLE
		....	.1.1	LOG	"5" JOB MESSAGE LOG
		....	.11.	FCT	"6" BDT FCT
		....	.111	JMC	"7" JES MESSAGE CLASS
		....	1...	RDEV	"8" BEGIN DEVELOPMENT
		1...	....	USER	DEFINED XOIDXTYP
					"128" BEGIN USER DEFINED XOIDXTYP
27	FLAG 1 DEFINITION (1B)	BITSTRING	1	XFL1	XOID FLAG 1
		1...	....	XMCL	"BIT0" SUPPRESSION OF MESSAGE CLASS
		.1..	....	X1R1	"BIT1" RESERVED
		..1.	....	X1R2	"BIT2" RESERVED
		...1	....	X1R3	"BIT3" RESERVED
		....	1...	X1R4	"BIT4" RESERVED
		....	.1..	X1R5	"BIT5" RESERVED
		....	..1.	X1R6	"BIT6" RESERVED
		....	...1	X1R7	"BIT7" RESERVED
MISCELLANEOUS INFORMATION					
28	(1C)	CHARACTER	8	XDDN	TRANSACTION ORIGIN DDNAME
28	(1C)	CHARACTER	8	USID	TSO USERID
28	(1C)	CHARACTER	8	CNDD	JES CONSOLE DDNAME
28	(1C)	CHARACTER	8	JCLS	JES MESSAGE CLASS
28	(1C)	CHARACTER	8	BJNM	BATCH JOB NAME
28	(1C)	ADDRESS	1	MCSI	MCS CONSOLE ID
28	(1C)	BITSTRING	2	BJNO	BDT JOB NUMBER
28	(1C)	BITSTRING	8	DDRS	DDNAME
RESERVED FIELDS					
36	(24)	BITSTRING	4	XRD2	RESERVED
40	(28)	BITSTRING	4	XRD3	RESERVED
44	(2C)	BITSTRING	4	XRS1	RESERVED
48	(30)	BITSTRING	4	XRS2	RESERVED
52	(34)	BITSTRING	4	XRU1	RESERVED
56	(38)	BITSTRING	4	XRU2	RESERVED
		...1	11.1	MCSA	MCS CONSOLE UX28 AUTH
		..11	11..	XEND	END OF XOID

.... ....  
.... 1.1.

X0ID  
XALL

X0ID EQUATE  
BSI EQUATE

---

## Appendix A. Accessibility

Accessible publications for this product are offered through [IBM Documentation \(www.ibm.com/docs/en/zos\)](http://www.ibm.com/docs/en/zos).

If you experience difficulty with the accessibility of any z/OS information, send a detailed message to the [Contact the z/OS team web page \(www.ibm.com/systems/campaignmail/z/zos/contact\\_z\)](http://www.ibm.com/systems/campaignmail/z/zos/contact_z) or use the following mailing address.

IBM Corporation  
Attention: MHVRCFS Reader Comments  
Department H6MA, Building 707  
2455 South Road  
Poughkeepsie, NY 12601-5400  
United States

---

### Accessibility features

Accessibility features help users who have physical disabilities such as restricted mobility or limited vision use software products successfully. The accessibility features in z/OS can help users do the following tasks:

- Run assistive technology such as screen readers and screen magnifier software.
- Operate specific or equivalent features by using the keyboard.
- Customize display attributes such as color, contrast, and font size.

---

### Consult assistive technologies

Assistive technology products such as screen readers function with the user interfaces found in z/OS. Consult the product information for the specific assistive technology product that is used to access z/OS interfaces.

---

### Keyboard navigation of the user interface

You can access z/OS user interfaces with TSO/E or ISPF. The following information describes how to use TSO/E and ISPF, including the use of keyboard shortcuts and function keys (PF keys). Each guide includes the default settings for the PF keys.

- *z/OS TSO/E Primer*
- *z/OS TSO/E User's Guide*
- *z/OS ISPF User's Guide Vol I*

---

### Dotted decimal syntax diagrams

Syntax diagrams are provided in dotted decimal format for users who access IBM Documentation with a screen reader. In dotted decimal format, each syntax element is written on a separate line. If two or more syntax elements are always present together (or always absent together), they can appear on the same line because they are considered a single compound syntax element.

Each line starts with a dotted decimal number; for example, 3 or 3.1 or 3.1.1. To hear these numbers correctly, make sure that the screen reader is set to read out punctuation. All the syntax elements that have the same dotted decimal number (for example, all the syntax elements that have the number 3.1)

are mutually exclusive alternatives. If you hear the lines 3.1 USERID and 3.1 SYSTEMID, your syntax can include either USERID or SYSTEMID, but not both.

The dotted decimal numbering level denotes the level of nesting. For example, if a syntax element with dotted decimal number 3 is followed by a series of syntax elements with dotted decimal number 3.1, all the syntax elements numbered 3.1 are subordinate to the syntax element numbered 3.

Certain words and symbols are used next to the dotted decimal numbers to add information about the syntax elements. Occasionally, these words and symbols might occur at the beginning of the element itself. For ease of identification, if the word or symbol is a part of the syntax element, it is preceded by the backslash (\) character. The \* symbol is placed next to a dotted decimal number to indicate that the syntax element repeats. For example, syntax element \*FILE with dotted decimal number 3 is given the format 3 \\* FILE. Format 3\* FILE indicates that syntax element FILE repeats. Format 3\* \\* FILE indicates that syntax element \* FILE repeats.

Characters such as commas, which are used to separate a string of syntax elements, are shown in the syntax just before the items they separate. These characters can appear on the same line as each item, or on a separate line with the same dotted decimal number as the relevant items. The line can also show another symbol to provide information about the syntax elements. For example, the lines 5.1\*, 5.1 LASTRUN, and 5.1 DELETE mean that if you use more than one of the LASTRUN and DELETE syntax elements, the elements must be separated by a comma. If no separator is given, assume that you use a blank to separate each syntax element.

If a syntax element is preceded by the % symbol, it indicates a reference that is defined elsewhere. The string that follows the % symbol is the name of a syntax fragment rather than a literal. For example, the line 2.1 %OP1 means that you must refer to separate syntax fragment OP1.

The following symbols are used next to the dotted decimal numbers.

#### **? indicates an optional syntax element**

The question mark (?) symbol indicates an optional syntax element. A dotted decimal number followed by the question mark symbol (?) indicates that all the syntax elements with a corresponding dotted decimal number, and any subordinate syntax elements, are optional. If there is only one syntax element with a dotted decimal number, the ? symbol is displayed on the same line as the syntax element, (for example 5? NOTIFY). If there is more than one syntax element with a dotted decimal number, the ? symbol is displayed on a line by itself, followed by the syntax elements that are optional. For example, if you hear the lines 5 ?, 5 NOTIFY, and 5 UPDATE, you know that the syntax elements NOTIFY and UPDATE are optional. That is, you can choose one or none of them. The ? symbol is equivalent to a bypass line in a railroad diagram.

#### **! indicates a default syntax element**

The exclamation mark (!) symbol indicates a default syntax element. A dotted decimal number followed by the ! symbol and a syntax element indicate that the syntax element is the default option for all syntax elements that share the same dotted decimal number. Only one of the syntax elements that share the dotted decimal number can specify the ! symbol. For example, if you hear the lines 2? FILE, 2.1! (KEEP), and 2.1 (DELETE), you know that (KEEP) is the default option for the FILE keyword. In the example, if you include the FILE keyword, but do not specify an option, the default option KEEP is applied. A default option also applies to the next higher dotted decimal number. In this example, if the FILE keyword is omitted, the default FILE (KEEP) is used. However, if you hear the lines 2? FILE, 2.1, 2.1.1! (KEEP), and 2.1.1 (DELETE), the default option KEEP applies only to the next higher dotted decimal number, 2.1 (which does not have an associated keyword), and does not apply to 2? FILE. Nothing is used if the keyword FILE is omitted.

#### **\* indicates an optional syntax element that is repeatable**

The asterisk or glyph (\*) symbol indicates a syntax element that can be repeated zero or more times. A dotted decimal number followed by the \* symbol indicates that this syntax element can be used zero or more times; that is, it is optional and can be repeated. For example, if you hear the line 5.1\* data area, you know that you can include one data area, more than one data area, or no data area. If you hear the lines 3\* , 3 HOST, 3 STATE, you know that you can include HOST, STATE, both together, or nothing.

#### **Notes:**



1. If a dotted decimal number has an asterisk (\*) next to it and there is only one item with that dotted decimal number, you can repeat that same item more than once.
2. If a dotted decimal number has an asterisk next to it and several items have that dotted decimal number, you can use more than one item from the list, but you cannot use the items more than once each. In the previous example, you can write HOST STATE, but you cannot write HOST HOST.
3. The \* symbol is equivalent to a loopback line in a railroad syntax diagram.

**+ indicates a syntax element that must be included**

The plus (+) symbol indicates a syntax element that must be included at least once. A dotted decimal number followed by the + symbol indicates that the syntax element must be included one or more times. That is, it must be included at least once and can be repeated. For example, if you hear the line 6.1+ data area, you must include at least one data area. If you hear the lines 2+, 2 HOST, and 2 STATE, you know that you must include HOST, STATE, or both. Similar to the \* symbol, the + symbol can repeat a particular item if it is the only item with that dotted decimal number. The + symbol, like the \* symbol, is equivalent to a loopback line in a railroad syntax diagram.



## Notices

---

This information was developed for products and services that are offered in the USA or elsewhere.

IBM may not offer the products, services, or features discussed in this document in other countries. Consult your local IBM representative for information on the products and services currently available in your area. Any reference to an IBM product, program, or service is not intended to state or imply that only that IBM product, program, or service may be used. Any functionally equivalent product, program, or service that does not infringe any IBM intellectual property right may be used instead. However, it is the user's responsibility to evaluate and verify the operation of any non-IBM product, program, or service.

IBM may have patents or pending patent applications covering subject matter described in this document. The furnishing of this document does not grant you any license to these patents. You can send license inquiries, in writing, to:

*IBM Director of Licensing  
IBM Corporation  
North Castle Drive, MD-NC119  
Armonk, NY 10504-1785  
United States of America*

For license inquiries regarding double-byte character set (DBCS) information, contact the IBM Intellectual Property Department in your country or send inquiries, in writing, to:

*Intellectual Property Licensing  
Legal and Intellectual Property Law  
IBM Japan Ltd.  
19-21, Nihonbashi-Hakozakicho, Chuo-ku  
Tokyo 103-8510, Japan*

**The following paragraph does not apply to the United Kingdom or any other country where such provisions are inconsistent with local law:** INTERNATIONAL BUSINESS MACHINES CORPORATION PROVIDES THIS PUBLICATION "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF NON-INFRINGEMENT, MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. Some states do not allow disclaimer of express or implied warranties in certain transactions, therefore, this statement may not apply to you.

This information could include technical inaccuracies or typographical errors. Changes are periodically made to the information herein; these changes will be incorporated in new editions of the publication. IBM may make improvements and/or changes in the product(s) and/or the program(s) described in this publication at any time without notice.

This information could include missing, incorrect, or broken hyperlinks. Hyperlinks are maintained in only the HTML plug-in output for IBM Documentation. Use of hyperlinks in other output formats of this information is at your own risk.

Any references in this information to non-IBM websites are provided for convenience only and do not in any manner serve as an endorsement of those websites. The materials at those websites are not part of the materials for this IBM product and use of those websites is at your own risk.

IBM may use or distribute any of the information you supply in any way it believes appropriate without incurring any obligation to you.

Licensees of this program who wish to have information about it for the purpose of enabling: (i) the exchange of information between independently created programs and other programs (including this one) and (ii) the mutual use of the information which has been exchanged, should contact:

*IBM Corporation  
Site Counsel  
2455 South Road*

Poughkeepsie, NY 12601-5400  
USA

Such information may be available, subject to appropriate terms and conditions, including in some cases, payment of a fee.

The licensed program described in this document and all licensed material available for it are provided by IBM under terms of the IBM Customer Agreement, IBM International Program License Agreement or any equivalent agreement between us.

Any performance data contained herein was determined in a controlled environment. Therefore, the results obtained in other operating environments may vary significantly. Some measurements may have been made on development-level systems and there is no guarantee that these measurements will be the same on generally available systems. Furthermore, some measurements may have been estimated through extrapolation. Actual results may vary. Users of this document should verify the applicable data for their specific environment.

Information concerning non-IBM products was obtained from the suppliers of those products, their published announcements or other publicly available sources. IBM has not tested those products and cannot confirm the accuracy of performance, compatibility or any other claims related to non-IBM products. Questions on the capabilities of non-IBM products should be addressed to the suppliers of those products.

All statements regarding IBM's future direction or intent are subject to change or withdrawal without notice, and represent goals and objectives only.

This information contains examples of data and reports used in daily business operations. To illustrate them as completely as possible, the examples include the names of individuals, companies, brands, and products. All of these names are fictitious and any similarity to the names and addresses used by an actual business enterprise is entirely coincidental.

#### COPYRIGHT LICENSE:

This information contains sample application programs in source language, which illustrate programming techniques on various operating platforms. You may copy, modify, and distribute these sample programs in any form without payment to IBM, for the purposes of developing, using, marketing or distributing application programs conforming to the application programming interface for the operating platform for which the sample programs are written. These examples have not been thoroughly tested under all conditions. IBM, therefore, cannot guarantee or imply reliability, serviceability, or function of these programs. The sample programs are provided "AS IS", without warranty of any kind. IBM shall not be liable for any damages arising out of your use of the sample programs.

## Terms and conditions for product documentation

---

Permissions for the use of these publications are granted subject to the following terms and conditions.

### **Applicability**

These terms and conditions are in addition to any terms of use for the IBM website.

### **Personal use**

You may reproduce these publications for your personal, noncommercial use provided that all proprietary notices are preserved. You may not distribute, display or make derivative work of these publications, or any portion thereof, without the express consent of IBM.

### **Commercial use**

You may reproduce, distribute and display these publications solely within your enterprise provided that all proprietary notices are preserved. You may not make derivative works of these publications, or

reproduce, distribute or display these publications or any portion thereof outside your enterprise, without the express consent of IBM.

## Rights

Except as expressly granted in this permission, no other permissions, licenses or rights are granted, either express or implied, to the publications or any information, data, software or other intellectual property contained therein.

IBM reserves the right to withdraw the permissions granted herein whenever, in its discretion, the use of the publications is detrimental to its interest or, as determined by IBM, the above instructions are not being properly followed.

You may not download, export or re-export this information except in full compliance with all applicable laws and regulations, including all United States export laws and regulations.

IBM MAKES NO GUARANTEE ABOUT THE CONTENT OF THESE PUBLICATIONS. THE PUBLICATIONS ARE PROVIDED "AS-IS" AND WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING BUT NOT LIMITED TO IMPLIED WARRANTIES OF MERCHANTABILITY, NON-INFRINGEMENT, AND FITNESS FOR A PARTICULAR PURPOSE.

## IBM Online Privacy Statement

---

IBM Software products, including software as a service solutions, ("Software Offerings") may use cookies or other technologies to collect product usage information, to help improve the end user experience, to tailor interactions with the end user, or for other purposes. In many cases no personally identifiable information is collected by the Software Offerings. Some of our Software Offerings can help enable you to collect personally identifiable information. If this Software Offering uses cookies to collect personally identifiable information, specific information about this offering's use of cookies is set forth below.

Depending upon the configurations deployed, this Software Offering may use session cookies that collect each user's name, email address, phone number, or other personally identifiable information for purposes of enhanced user usability and single sign-on configuration. These cookies can be disabled, but disabling them will also eliminate the functionality they enable.

If the configurations deployed for this Software Offering provide you as customer the ability to collect personally identifiable information from end users via cookies and other technologies, you should seek your own legal advice about any laws applicable to such data collection, including any requirements for notice and consent.

For more information about the use of various technologies, including cookies, for these purposes, see IBM's Privacy Policy at [ibm.com/privacy](http://ibm.com/privacy) and IBM's Online Privacy Statement at [ibm.com/privacy/details](http://ibm.com/privacy/details) in the section entitled "Cookies, Web Beacons and Other Technologies," and the "IBM Software Products and Software-as-a-Service Privacy Statement" at [ibm.com/software/info/product-privacy](http://ibm.com/software/info/product-privacy).

## Policy for unsupported hardware

---

Various z/OS elements, such as DFSMSdfp, JES2, JES3, and MVS™, contain code that supports specific hardware servers or devices. In some cases, this device-related element support remains in the product even after the hardware devices pass their announced End of Service date. z/OS may continue to service element code; however, it will not provide service related to unsupported hardware devices. Software problems related to these devices will not be accepted for service, and current service activity will cease if a problem is determined to be associated with out-of-support devices. In such cases, fixes will not be issued.

## Minimum supported hardware

---

The minimum supported hardware for z/OS releases identified in z/OS announcements can subsequently change when service for particular servers or devices is withdrawn. Likewise, the levels of other software products supported on a particular release of z/OS are subject to the service support lifecycle of those

products. Therefore, z/OS and its product publications (for example, panels, samples, messages, and product documentation) can include references to hardware and software that is no longer supported.

- For information about software support lifecycle, see: [IBM Lifecycle Support for z/OS \(www.ibm.com/software/support/systemsz/lifecycle\)](http://www.ibm.com/software/support/systemsz/lifecycle)
- For information about currently-supported IBM hardware, contact your IBM representative.

## Programming Interface Information

---

This book is intended to help the customer to do diagnosis of BDT. This book documents information that is Diagnosis, Modification or Tuning Information provided by BDT.

**Attention:** Do not use this Diagnosis, Modification or Tuning Information as a programming interface.

## Trademarks

---

IBM, the IBM logo, and [ibm.com](http://ibm.com) are trademarks or registered trademarks of International Business Machines Corp., registered in many jurisdictions worldwide. Other product and service names might be trademarks of IBM or other companies. A current list of IBM trademarks is available on the Web at [Copyright and Trademark information \(www.ibm.com/legal/copytrade.shtml\)](http://www.ibm.com/legal/copytrade.shtml).

# GLOSSARY

---

This glossary defines important terms and abbreviations used in this book. If you do not find the term you are looking for, refer to the index or to the *IBM Dictionary of Computing* New York: McGraw-Hill, 1994.

## **ACF/VTAM**

Advanced Communication Function for the Virtual Telecommunications Access Method.

## **Advanced Communication Function for the Virtual Telecommunications Access Method (ACF/VTAM)**

A licensed program that provides single-domain network capability, and optionally, multiple-domain capability.

## **ASR**

Automatic session restart.

## **automatic session restart (ASR)**

A function defined at initialization that causes an interrupted session to attempt to restart automatically.

## **checkpoint data set**

See TQI checkpoint data set.

## **DAP**

Dynamic application program.

## **dependent transaction control (DTC)**

A method of controlling the scheduling of file-to-file transactions by organizing the transactions into a network in which some transactions wait for the completion of other transactions before being scheduled.

## **DTC**

Dependent transaction control.

## **dynamic application program (DAP)**

A part of BDT that performs a particular function; especially the transfer of data.

## **fencing**

In BDT, a method by which an installation can restrict the direction in which a set of VLUs can transmit file-to-file data.

## **generic master job definition (GMJD) library**

In BDT, a data set that contains predefined transaction definitions.

## **GMJD library**

generic master job definition library.

## **global node**

In BDT, the node that schedules and manages all file-to-file transactions involving itself and a local node and responds to commands issued against those transactions.

## **local node**

In BDT, the node that receives file-to-file transactions and commands submitted by users and sends them to the global node for processing.

## **network**

In BDT, two or more BDT nodes that are joined by SNA sessions.

## **network job entry (NJE)**

The transmission of jobs, in-stream data sets, operator commands and messages, system output data sets, and job accounting information from one computer complex to another across a telecommunication link.

## **NJE**

Network job entry.

**node**

In BDT, the point in a BDT address space that is linked to another BDT address space for either file-to-file communication or SNA NJE communication.

**poly-BDT complex**

A JES complex that has more than one BDT address space.

**Remote Spooling Communication Subsystem (RSCS)**

A licensed program that transfers spool files between VM/SP users, remote stations, and remote and local batch systems via telecommunication facilities.

**RSCS**

Remote Spooling Communication Subsystem.

**scheduler element (SE)**

Information that follows each JCT entry, including such things as sending and receiving DAP names, sending and receiving locations, and the number of VLUs allocated for the transfer.

**SE**

Scheduler element.

**session**

In SNA, a logical connection between two network addressable units. The connection can be activated, deactivated, or tailored to provide different protocols.

**SMF**

System Management Facilities.

**SNA**

Systems Network Architecture.

**SNA manager**

The BDT internode communication processor. It is initiated by a BDT operator command and subsequently invoked by the DAPs to send and receive data.

**System Management Facilities (SMF)**

An optional control program feature that provides the means for gathering and recording information that can be used to evaluate system usage.

**Systems Network Architecture (SNA)**

The description of the logical structure, formats, protocols, and operational sequences for transmitting information units through and controlling the configuration and operation of networks.

**TQI**

Transaction queuing integrity.

**TQI checkpoint data set**

In BDT, a data set on which the transaction queuing integrity (TQI) facility records user-submitted commands and file-to-file transactions before sending them to the BDT address space. Should a command or transaction fail to reach the BDT address space, BDT automatically recovers it from the TQI checkpoint data set and attempts the transfer again.

**transaction**

In BDT, (1) a request to copy a data set, transmit a SNA NJE job, or transmit SNA NJE output (SYSOUT), and (2) the work that BDT does to process the request. Requests to copy data sets are submitted to BDT by users. Requests to transmit SNA NJE jobs and output are submitted to BDT by JES3.

**transaction queuing integrity (TQI)**

In BDT, a program that records commands and file-to-file transactions on a data set at the submitting node, thus allowing the transfers to be resubmitted automatically should they not reach the BDT work queue. TQI also allows users to receive messages.

**virtual logical unit (VLU)**

In BDT, data and program logic that represents one user of a SNA session. The virtual logical unit enables more than one user to concurrently use a session.

**VLU**

Virtual logical unit.



**work queue**

In BDT, a queue whose elements represent work that BDT must do on behalf of a transaction.



---

# Index

## A

- abend code [2](#), [38](#)
- abending program, name of [38](#)
- ACB [55](#)
- access control block (ACB) [55](#)
- accessibility
  - contact IBM [153](#)
  - features [153](#)
- accounting driver [47](#), [50](#), [99](#)
- ACF/VTAM
  - RECEIVE RPL entries in formatted dump [31](#)
  - RPL fields in formatted dump [31](#)
  - SEND RPL entries in formatted dump [31](#)
- active jobs, information about [28](#)
- assembly module at abend [38](#)
- assistive technologies [153](#)

## B

- BDT address space, activity in [37](#)
- BDT DUMP command [1](#)
- BDT formatted dump
  - changing option for [1](#)
  - contents of [1](#)
  - contents of BDTNUC in [36](#)
  - CPB fields in [33](#)
  - CPD fields in [33](#)
  - FCT fields in [25](#)
  - heading of [2](#)
  - how to request a copy [1](#)
  - JQE fields in [28](#)
  - LCB fields in [31](#)
  - LCT fields in [30](#)
  - LCTLU fields in [31](#)
  - map of BDTNUC in [3](#)
  - RLT fields in [29](#)
  - RPL fields in [31](#)
  - SNA control blocks in [33](#)
  - title page of [2](#)
- BDT nucleus (BDTNUC)
  - BDTGRVT CSECT in [123](#)
  - contents of [45](#), [48](#)
  - contents of, in formatted dump [36](#)
  - map of, in formatted dump [3](#)
  - resident functions in [3](#)
- BDT trace table
  - description of [40](#)
  - example of [40](#)
  - how to
    - locate [42](#)
    - use [40](#)
- BDTDATR data area
  - description of [42](#)
  - format of [42](#)
- BDTGRCPD CSECT
  - CPD mapped by [55](#)

- BDTGRCPD CSECT (*continued*)
  - location of [55](#)
- BDTGRCT module
  - use of GSD [63](#)
- BDTGRFC module
  - GSD entries created by [63](#)
- BDTGRJS module
  - GSD entries created by [63](#)
- BDTGRJX module [54](#), [83](#), [89](#)
- BDTGRPT CSECT
  - GSD entries in [63](#)
- BDTGRSV module
  - and trace table entries [40](#)
- BDTGRTX module [40](#)
- BDTGRVT CSECT
  - and the TVT [4](#), [123](#)
- BDTGRXD module
  - JCT entries created by [83](#)
  - JQE entries created by [89](#)
- BDTINR2 initialization module
  - LCTs created by [93](#)
  - RLT entries created by [107](#)
- BDTINTK initialization module
  - TVT loaded by [123](#)
- BDTLP
  - MJD entries created by [99](#)
- BDTNODE initialization statement [29](#)
- BDTSNA
  - use of LCTs [93](#)
- BDTXTRC macro
  - and BDTGRSV [40](#)
  - and entries in the trace table [40](#)
- BSID (BDT subsystem interface data area)
  - and BDTGRXD [83](#)
  - and MJD [99](#)
  - description of [56](#)
- BSIW [56](#)

## C

- checkpoint interval [30](#)
- CLSDST RPL
  - entries in formatted dump [31](#)
- common service area (CSA) [38](#)
- completion code [2](#), [38](#)
- configuration control block for TQI [38](#)
- console message area
  - in SEQ [109](#)
- constants, addresses of [4](#)
- contact
  - z/OS [153](#)
- control blocks
  - descriptions of [55](#)
  - locations of
    - after initialization [45](#)
    - after job is purged [47](#), [50](#)
    - after job is scheduled [46](#), [49](#)

- control blocks (*continued*)
  - pointers to, in TVT [4](#)
  - relationships among [51](#)
- CPB (cell pool control block)
  - addresses in TVT [10](#)
  - description of [55](#)
  - fields in the formatted dump [33](#)
  - location of [45](#)
  - names of entries [51](#)
- CPD (cell pool directory)
  - address of, in TVT [12](#)
  - description of [55](#)
  - fields in the formatted dump [33](#)
  - location of [45](#)
  - relationship to CPBs [51](#)

## D

- DAP (dynamic application program) [25](#)
- DAP dictionary [55](#)
- data areas
  - descriptions of [55](#)
  - in BDT nucleus [3](#)
  - locations of
    - after initialization [45](#)
    - after job is purged [47](#), [50](#)
    - after job is scheduled [46](#), [49](#)
  - relationships among [51](#)
- data compression list (DCL) [55](#)
- data description block (DDB) [56](#)
- data support work area (DSWA) [56](#)
- DCL [55](#)
- DDB [56](#)
- DSWA [56](#)
- DUMP command [1](#)
- dynamic allocation text units
  - formatted in the MJD [99](#)
  - location of [99](#)

## E

- exit list [56](#)
- EXLST [56](#)

## F

- F,DUMP command [1](#)
- failing instruction, address of [2](#)
- failing module, name of [2](#)
- FCT (function control table)
  - cell pool
    - FCT entries built in [46](#), [48](#), [49](#)
    - GETUNIT list entries built in [46](#), [48](#), [49](#)
    - GSD entries built in [46](#), [48](#), [49](#), [63](#)
    - RESQUEUE entries built in [46](#), [48](#)
    - TWA entries built in [46](#), [49](#)
  - description of [56](#)
  - entry active at time of abend [2](#)
  - fields in the formatted dump [25](#)
  - location of resident entries [45](#)
  - register save area in formatted dump [26](#)
  - relationship to dispatching control blocks [54](#)
- feedback [xi](#)

- formatted dump
  - contents of [1](#)
  - contents of BDTNUC in [36](#)
  - CPB fields in [33](#)
  - CPD fields in [33](#)
  - FCT fields in [25](#)
  - heading of [2](#)
  - how to request a copy [1](#)
  - JQE fields in [28](#)
  - LCB fields in [31](#)
  - LCT fields in [30](#)
  - LCTLU fields in [31](#)
  - map of BDTNUC in [3](#)
  - RLT fields in [29](#)
  - RPL fields in [31](#)
  - SNA control blocks in [33](#)
  - title page of [2](#)

## G

- GETUNIT list
  - address of, in FCT [27](#)
  - description of [56](#)
  - fields in the formatted dump [27](#)
  - for IFC [27](#), [45](#)
  - for JSS [27](#), [45](#)
  - location of [45](#)
  - location of nonresident entries [46](#), [49](#)
  - relationship to dispatching control blocks [54](#)
- glossary [161](#)
- GSD (generalized subtask directory)
  - address of, in FCT [27](#)
  - description of [63](#)
  - location of nonresident entries [63](#)
  - location of resident entries [45](#), [63](#)
  - relationship to dispatching control blocks [54](#)

## I

- IFC (interfunction communication manager)
  - CPBs [10](#)
  - GETUNIT list entry for [27](#)
- initialization parameters [4](#)
- INT (initialization data CSECT)
  - location of [69](#)

## J

- JCT (job control table)
  - access method of [54](#), [83](#)
  - access routine [9](#)
  - description of [83](#)
  - format of scheduler element [83](#)
  - location in BDT address space [83](#)
  - location on work queue [46](#)
  - relationship to JQE [89](#)
  - relationship to scheduling control blocks [54](#)
- JCTB cell pool
  - JCT built in [83](#)
- JML (job message log)
  - description of [56](#)
  - location of [46](#)
  - relationship to scheduling control blocks [54](#)

- job dispatching control blocks [54](#)
- job scheduling control blocks [54](#)
- jobs, information about [28](#)
- JQE (job queue element)
  - access method of [54](#), [89](#)
  - and JQX [46](#), [48](#)
  - description of [89](#)
  - fields in the formatted dump [28](#)
  - location of [45](#)
- JQX (job queue access table)
  - description of [91](#)
  - JQE entries created in [89](#)
  - location of [45](#)
  - relationship to scheduling control blocks [54](#)

## K

- keyboard
  - navigation [153](#)
  - PF keys [153](#)
  - shortcut keys [153](#)

## L

- LCB (logical unit control block)
  - description of [56](#)
  - fields in the formatted dump [31](#)
  - location of [45](#)
  - relationship to LCT [93](#)
  - relationship to session-related control blocks [53](#)
- LCT (logical unit control table)
  - address in TVT [10](#)
  - address, in RLT [30](#)
  - fields in the formatted dump [30](#)
- LCTLU (LCT for logical units)
  - description of [93](#)
  - fields in the formatted dump [32](#)
  - location of [45](#), [46](#), [48](#)
  - relationship to LCT [93](#)
  - relationship to session-related control blocks [53](#)
- load module at abend [38](#)
- local system queue area (LSQA) [38](#)

## M

- MJD (master job definition)
  - description of [99](#)
  - location of [46](#), [99](#)
  - relationship to scheduling control blocks [54](#)
  - used by BDTGRXD [83](#)
- MODIFY,DUMP command [1](#)
- modules
  - addresses of [3](#)
  - names of [3](#)
- MVS SNAP dump, in formatted dump [1](#)
- MVS SVC dump
  - contents of [38](#)
  - description of [37](#)
  - how to
    - access [37](#)
    - format and print [37](#)
    - request a copy [37](#)
    - transmit to another node [38](#)

- MVS SVC dump (*continued*)
  - purpose of [37](#)
  - title page of [38](#)
  - trace table in [40](#)

## N

- navigation
  - keyboard [153](#)
- nodes, information about [29](#), [30](#)
- nonresident functions
  - definition of [25](#)
  - in formatted dump [28](#)
  - locations of during processing [46](#), [49](#)

## O

- OPNDST RPL
  - entries in formatted dump [31](#)
- OPNSEC RPL
  - entries in formatted dump [31](#)

## P

- prefixed storage areas (PSAs) [38](#)
- private user area [38](#)
- program call table
  - for BDT address space [38](#)
  - for TQI address space [38](#)

## R

- RECEIVE RPL
  - entries in formatted dump [31](#)
- recovery routine, module containing [38](#)
- resident functions
  - definition of [3](#)
  - FCT fields in the formatted dump [25](#)
  - in formatted dump [25](#)
- RESQUEUE
  - address of, in FCT [27](#)
  - description of [56](#)
  - location of [46](#), [49](#)
  - relationship to dispatching control blocks [54](#)
- RLT (resident logical units table)
  - fields in the formatted dump [29](#)
  - for BDT nodes [53](#)
  - for SNA sessions [53](#)
  - relationship to session-related control blocks [53](#)
- routines, addresses of [4](#)
- RPL (request parameter list)
  - fields in formatted dump [31](#)
  - request types [31](#)
  - return code fields in formatted dump [32](#)

## S

- scheduler element (SE)
  - and JCT [83](#)
  - contents of [83](#)
- SDWA (system defined work area)
  - in the SVC dump [38](#)
- SEND RPL

- SEND RPL (*continued*)
  - entries in formatted dump [31](#)
- sending to IBM
  - reader comments [xi](#)
- SEQ (sequential transfer data area)
  - location of [109](#)
- service routines [3](#)
- session-related control blocks, diagram of [53](#)
- sessions, information about [29](#), [30](#)
- shortcut keys [153](#)
- SICA (Scheduler interface control area) [120](#)
- SMF [56](#)
- SNA manager
  - control blocks in formatted dump [33](#)
  - definition of [162](#)
  - LCTLUs created by [93](#)
- SNAP dump in formatted dump [1](#)
- SNBP (SNA buffer pool control block) [121](#)
- SSIB [56](#)
- SSOB [56](#)
- storage management control blocks, diagram of [51](#)
- subsystem interface identification block (SSIB) [56](#)
- subsystem interface options block (SSOB) [56](#)
- subsystem interface work area (BSIW) [56](#)
- subsystem vector table (SSVT) [38](#)
- summary of changes
  - z/OS BDT Diagnosis Reference [xiii](#)
- SVC dump
  - contents of [38](#)
  - description of [37](#)
  - how to
    - access [37](#)
    - format and print [37](#)
    - request a copy [37](#)
    - transmit to another node [38](#)
  - purpose of [37](#)
  - title page of [38](#)
  - trace table in [40](#)
- SYS1.DUMP data set [37](#)
- system management facilities (SMF) [56](#)
- system queue area (SQA) [38](#)

## T

- TCB (task control block)
  - address, in FCT [26](#)
  - location of [45](#), [46](#)
  - pointer to [63](#)
  - relationship to dispatching control blocks [54](#)
- trace table
  - description of [40](#)
  - example of [40](#)
  - how to
    - locate [42](#)
    - use [40](#)
- trademarks [160](#)
- TVT (transfer vector table)
  - description of [123](#)
  - fields in the formatted dump [4](#)
  - location of [4](#), [45](#), [123](#)
  - pointers to CPBs [51](#)
  - pointers to job-scheduling and dispatching control blocks [54](#)

- TVT (transfer vector table) (*continued*)
  - pointers to session-related control blocks [53](#)
- TWA (trace work area)
  - description of [149](#)
  - location of [149](#)

## U

- user interface
  - ISPF [153](#)
  - TSO/E [153](#)

## V

- VLU (virtual logical unit)
  - definition of [162](#)
  - description of [30](#)
  - information about
    - in LCTLU [32](#)
    - in RLT [29](#)
  - represented by LCTLU [93](#)

## W

- WANTDUMP parameter [1](#)
- work queue
  - after job is purged [47](#), [50](#)
  - definition of [163](#)
  - during job processing [46](#), [48](#)
  - JCT entries located on [83](#)
  - MJD entries located on [99](#)

## X

- XOID (transaction origin data area)
  - description of [151](#)
  - location of [151](#)

## Z

- z/OS BDT Diagnosis Reference
  - summary of changes [xiii](#)





Product Number: 5650-ZOS

SC14-7586-50

