

z/OS
2.5

MVS Planning: Workload Management



Note

Before using this information and the product it supports, read the information in [“Notices” on page 231](#).

This edition applies to Version 2 Release 5 of z/OS® (5650-ZOS) and to all subsequent releases and modifications until otherwise indicated in new editions.

Last updated: 2023-08-25

© **Copyright International Business Machines Corporation 1994, 2023.**

US Government Users Restricted Rights – Use, duplication or disclosure restricted by GSA ADP Schedule Contract with IBM Corp.

Contents

Figures.....	ix
Tables.....	xiii
About this information.....	xv
How to send your comments to IBM.....	xvii
If you have a technical problem.....	xvii
Summary of changes.....	xix
Summary of changes for z/OS MVS Planning: Workload Management for Version 2 Release 5 (V2R5).....	xix
Summary of changes V2R4.....	xx
Summary of changes for z/OS Version 2 Release 3 (V2R3).....	xxi
Chapter 1. Why MVS workload management?.....	1
Problems addressed by workload management.....	1
MVS workload management solution for today and tomorrow.....	1
Chapter 2. What is MVS workload management?.....	3
Performance administration.....	4
Performance management.....	5
Workload balancing.....	5
Workload management concepts.....	5
What is a service definition?.....	6
Why use service policies?.....	6
Organizing work into workloads and service classes.....	6
Why use resource groups or tenant resource groups?.....	9
Assigning work to a service class.....	10
Why use application environments?.....	11
Why use scheduling environments?.....	12
Summary of service definition and service policy concepts.....	13
Chapter 3. Workload management participants.....	15
Workload management work environments.....	15
Subsystem support for goal types and multiple periods.....	16
Subsystem-specific performance hints.....	17
Workload balancing.....	17
Workload management in a CPSM environment.....	18
Workload management in a DB2 Distributed Data Facility environment.....	18
Batch workload management.....	18
Multisystem enclave support.....	20
Intelligent Resource Director.....	20
HiperDispatch mode.....	20
Overview.....	20
The concept of HiperDispatch mode.....	20
Setting HiperDispatch mode in SYS1.PARMLIB.....	21
I/O storage management.....	22
Handling service class periods with a response time goal.....	22

Handling service class periods with a velocity goal.....	23
Handling other I/O requests.....	23
Controlling the information passed to the I/O manager.....	23
Non-z/OS partition CPU management.....	23
Workload management and Workload License Charges.....	24
Defining the capacity of a partition.....	25
Defining group capacity.....	26
Workload management with other products.....	28
Chapter 4. Setting up a service definition.....	29
Specifying a service definition.....	29
Storing service definitions.....	29
Defining the parts of a service definition.....	30
Chapter 5. Defining service policies.....	31
Using policy overrides.....	32
Chapter 6. Defining workloads.....	35
Defining a departmental workload.....	35
Chapter 7. Defining resource groups.....	37
Calculating an LPAR share — Example 1.....	40
Specifying the capacity as a number of CPs — Example 2.....	42
Chapter 8. Defining tenant resource groups.....	45
Chapter 9. Defining service classes and performance goals.....	47
Calculating the amount of service consumed.....	49
Velocity formula.....	50
Defining performance goals.....	51
Determining system response time goals.....	51
Examples of service classes with response time goals.....	52
Defining velocity goals.....	53
Adjusting velocity goals based on samples included in velocity calculation.....	54
Using velocity goals for started tasks.....	54
Using discretionary goals.....	54
Using performance periods.....	55
Defining goals appropriate for performance periods.....	56
Using importance levels in performance periods.....	56
Chapter 10. Defining classification rules.....	57
Defining classification rules for each subsystem.....	59
Defining work qualifiers.....	62
Defining special reporting options for workload reporting.....	75
Defining recovery process boost for middleware recycle.....	77
Defining the order of classification rules.....	78
Defining a subsystem service class default.....	78
Organizing work for classification.....	82
Using masking notation.....	83
Using wildcard notation.....	83
Using the start position.....	84
Using groups.....	86
Using the system-supplied service classes.....	88
Chapter 11. Defining tenant report classes.....	91

Chapter 12. Defining report classes.....	93
Chapter 13. Defining service definition options.....	95
Specifying I/O priority management.....	95
Considerations for I/O priority management.....	95
Enabling I/O priority groups.....	95
Considerations for I/O priority groups.....	96
Specifying dynamic alias management.....	96
Workload management considerations for dynamic alias management.....	96
HCD considerations for dynamic alias management.....	96
Deactivate discretionary goal management.....	98
Chapter 14. Defining special protection options for critical work.....	99
Long-term storage protection.....	99
Storage critical for address spaces.....	99
Storage critical for CICS and IMS transactions.....	100
Long-term CPU protection.....	100
Long-term I/O protection.....	100
Honor priority.....	101
Modifications of transaction response time management.....	102
Sample scenarios.....	103
Scenario 1.....	103
Scenario 2.....	104
Scenario 3.....	106
Scenario 4.....	107
Scenario 5.....	108
Scenario 6.....	109
Reporting.....	110
Option summary.....	111
Chapter 15. Defining application environments.....	113
Getting started with application environments.....	113
Specifying application environments to workload management.....	114
Selecting server limits for application environments.....	116
How WLM manages servers for an application environment	117
Using application environments.....	118
Managing application environments.....	119
Using operator commands for application environments.....	119
Making changes to the application environment servers.....	120
Changing the definition of an application environment.....	120
Handling error conditions in application environments.....	121
Authorizing application environment servers.....	121
Example for restricting access to application environment servers.....	121
Chapter 16. Defining scheduling environments.....	123
Getting started with scheduling environments.....	123
Specifying scheduling environments to workload management.....	123
Managing resource states.....	125
Associating scheduling environments with incoming work.....	128
Displaying information about scheduling environments and resource states.....	128
MVS operator commands.....	128
JES2/JES3 operator commands.....	130
SDSF commands.....	130
Chapter 17. Workload management migration.....	131

Creating a service definition for the first time.....	131
Migrating to a new z/OS release with an existing service definition.....	133
Migration activities.....	134
Restricting access to the WLM service definition.....	134
Start the application and enter/edit the service definition.....	135
Calculate the size of the WLM couple data set.....	138
Allocate a WLM couple data set.....	138
Make a WLM couple data set available to the sysplex for the first time.....	140
Make a newly formatted couple data set available to the sysplex.....	141
Migration considerations for velocity.....	142
Migration considerations for discretionary goal management.....	143
Migration considerations for dynamic alias management.....	143
Migration considerations for multisystem enclaves.....	143
Migration considerations for protection of critical work.....	143
Migration considerations for managing non-enclave work in enclave servers.....	144
Migration considerations for an increased notepad size.....	144
WLM managed batch initiator balancing.....	144
Consider resource group maximum in WLM batch initiator management.....	145
Migration considerations for service definition coefficients.....	145

Chapter 18. Defining a coupling facility structure for multisystem enclave support.....	147
Defining the coupling facility.....	147
Shutting down the coupling facility.....	148
Coupling facility failures.....	149

Chapter 19. The Intelligent Resource Director.....	151
LPAR CPU management.....	153
Dynamic channel path management.....	153
Channel subsystem priority queuing.....	154
Example: How the Intelligent Resource Director works.....	154
Making the Intelligent Resource Director work	156
Defining the SYSZWLMwnnnnnttt coupling facility structure.....	156
Enabling LPAR CPU management.....	157
Enabling non-z/OS CPU management.....	157
Enabling dynamic channel path management.....	158
Enabling channel subsystem priority queuing.....	159
For more information.....	159

Chapter 20. Using IBM z Integrated Information Processor (zIIP).....	161
Planning for zIIPs.....	161
Acquiring zIIPs.....	161
Defining zIIPs.....	162
Reviewing parameter settings.....	162

Chapter 21. System Recovery Boost.....	165
---	------------

Chapter 22. Using the WLM ISPF application.....	167
Before you begin.....	167
Panel areas and how to use them.....	167
Using the menu bar.....	168
Using the status line.....	169
Using the scrollable area.....	169
Using the Action field.....	170
Using the command line.....	170
Using the function keys.....	170

Starting the WLM application.....	171
Now you're started.....	171
Using the Definition Menu.....	172
Using the menu bar on the Definition Menu.....	174
Working with service policies.....	176
Working with workloads.....	177
Working with resource groups.....	178
Working with service classes.....	178
Defining goals.....	179
Using action codes on service class panels.....	180
Defining service policy overrides.....	181
Working with tenant resource groups.....	182
Working with classification rules.....	183
Using action codes on the Modify Rules panel.....	187
Using selection lists for classification rules.....	190
Creating a subsystem type for rules.....	190
Deleting a subsystem type for rules.....	190
Working with classification groups.....	190
Working with report classes.....	191
Working with tenant report classes.....	191
Working with service definition options.....	192
Working with application environments.....	193
Working with scheduling environments.....	193
Creating a new scheduling environment.....	193
Modifying a scheduling environment.....	195
Copying a scheduling environment.....	196
Browsing a scheduling environment.....	196
Printing a scheduling environment.....	197
Deleting a scheduling environment.....	197
Creating a new resource.....	197
Showing all cross-references for a resource definition.....	201
Deleting a resource.....	201
Coordinating updates to a service definition.....	202
Using the WLM couple data set.....	202
Using MVS data sets.....	204
Restricting access to your service definition.....	205
Activating a service policy.....	205
Printing in the application.....	205
Browsing definitions.....	205
Using XREF function to view service definition relationships.....	206
WLM application messages.....	206

Chapter 23. Using the z/OS Management Facility (z/OSMF) to administer WLM.... 213

Overview of the z/OSMF workload management task.....	213
Key functions of the Workload Management task in z/OSMF.....	213

Appendix A. Customizing the WLM ISPF application..... 217

Specifying the exits.....	217
Coding the WLM exits.....	218
IWMARIN1.....	218
Customizing the WLM application libraries — IWMAREX1.....	218
Customizing the WLM application data sets — IWMAREX2.....	219
Adding WLM as an ISPF menu option.....	222
Moving pop-up windows.....	223
Customizing the keylists.....	223

Appendix B. CPU capacity table..... 225

Using SMF task time.....	225
Appendix C. Return codes for the IWMINSTL sample job.....	227
Appendix D. Accessibility.....	229
Notices.....	231
Terms and conditions for product documentation.....	232
IBM Online Privacy Statement.....	233
Policy for unsupported hardware.....	233
Minimum supported hardware.....	233
Trademarks.....	234
Workload management terms.....	235
Index.....	241

Figures

1. MVS Workload Management Overview.....	4
2. Workload organized by subsystem.....	8
3. Workload organized by department.....	8
4. Resource groups.....	9
5. Work classification.....	10
6. Application environment example.....	11
7. Scheduling environment example.....	12
8. Service definition, including two service policies.....	14
9. Sysplex view of the management environment.....	16
10. Workload management in a CICS environment.....	18
11. Workload management enforcing a defined capacity limit.....	24
12. Example of workload consumption for partitions MVS1, MVS2, and MVS3.....	27
13. Example: Resource group overview.....	42
14. Working With A Resource Type 2 - Sample Calculation.....	42
15. Formula for calculating service consumption.....	49
16. Using classification rules to assign work to service classes.....	59
17. Specifying the Storage Critical Option.....	99
18. Specifying the CPU Critical option.....	100
19. Specifying the I/O Priority Group option.....	101
20. Specifying the Honor Priority option.....	101
21. Specifying the Manage Region Using Goals Of option.....	102
22. Scenario 1: Address Spaces.....	103
23. Scenarios 2, 3, 4, 5: CICS/IMS regions.....	105

24. Scenario 6: CICS Regions Adhering to a Work Manager/Consumer Model.....	109
25. Sample Systems and Scheduling Environments.....	127
26. One LPAR cluster on one CPC.....	151
27. Four LPAR clusters on two CPCs.....	152
28. Intelligent Resource Director example – Day shift.....	155
29. Intelligent Resource Director Example – Night Shift.....	156
30. Menu Bar on the Definition Menu.....	168
31. Definition Menu File Choices.....	168
32. Service Class Selection List.....	169
33. Service Class Selection List panel.....	169
34. Action field on the Subsystem Type Selection List panel.....	170
35. Function key area.....	171
36. Choose Service Definition pop-Up.....	171
37. Definition Menu panel.....	172
38. Create a Service Policy panel.....	176
39. Service Policy Selection List panel.....	177
40. Create a Workload panel.....	177
41. Workload Selection List panel.....	178
42. Create a Resource Group panel.....	178
43. Create a Service Class panel.....	179
44. Choose a Goal Type pop-up.....	179
45. Average Response Time Goal pop-up.....	180
46. Create a Service Class panel.....	180
47. Action Codes for Goal.....	180
48. Service Policy Selection List panel.....	181

49. Override Service Class Selection List panel.....	182
50. Override Attributes for a Service Class panel.....	182
51. Create a Tenant Resource Group panel.....	183
52. Subsystem Type Selection List for Rules panel.....	184
53. Modify Rules for the Subsystem Type panel.....	184
54. Modify Rules for the Subsystem Type panel, scrolled right to description fields.....	185
55. Modify Rules for the Subsystem Type panel, scrolled right to Storage Critical, Reporting Attribute, and Manage Regions Using Goals Of fields.....	186
56. Modify Rules for the Subsystem Type panel, scrolled right to Boost field.....	186
57. Action codes for classification rules.....	187
58. Create a Group panel.....	190
59. Modify Rules for STC Subsystem.....	191
60. Create a Report Class confirmation panel.....	191
61. Create a Tenant Report Class.....	191
62. Service Definition Options panel.....	192
63. Create an Application Environments panel.....	193
64. Decide What to Create panel.....	193
65. Scheduling Environment Selection List panel.....	194
66. Create a Scheduling Environment panel.....	194
67. Resource Definition List panel.....	194
68. Create a Scheduling Environment panel.....	195
69. Scheduling Environment Selection List panel.....	195
70. Modify a Scheduling Environment panel.....	196
71. Copy a Scheduling Environment panel.....	196
72. Browse a Scheduling Environment panel.....	197
73. Delete a Scheduling Environment panel.....	197

74. Scheduling Environment Selection List panel.....	198
75. Resource Definition List panel.....	198
76. Define Resource oanel.....	198
77. Resource Definition List panel.....	198
78. Modify a Scheduling Environment panel.....	199
79. Resource Definition List panel.....	199
80. Resource Definition List panel.....	200
81. Modify a Scheduling Environment Panel.....	200
82. Resource Definition List panel.....	201
83. Resource Cross-Reference Of Scheduling Environments panel.....	201
84. Resource Definition List panel.....	202
85. Overwrite Service Definition panel.....	202
86. Allocate couple data set using CDS values panel.....	203
87. Allocate couple data set panel using service definition values.....	204
88. Policy Selection List panel to activate a service policy.....	205
89. Browse function from the Service Class Selection List.....	206
90. Service Class Subsystem Xref panel.....	206
91. z/OS Management Facility - Overview Panel.....	215
92. Example of adding WLM as an option on the ISPF menu.....	223
93. Keylist Utility panel.....	224

Tables

1. Levels of processing.....	23
2. Example of definitions for MVS1, MVS2, and MVS3 partitions.....	26
3. Example: LPAR configuration.....	40
4. Example: ELPMAX in sysplex WLMPLEX.....	41
5. IBM-defined subsystem types.....	60
6. Enclave transactions, address space-oriented transactions, and CICS/IMS transactions.....	62
7. Work qualifiers supported by each IBM-defined subsystem type.....	63
8. Effects of WLM PAV settings on base and alias devices.....	97
9. Summary of options for storage protection, CPU protection, and exemption from transaction response time management.....	111
10. IBM-supplied Subsystems Using Application Environments.....	113
11. Application environment server characteristics.....	117
12. WLM libraries.....	135
13. Functionality levels for service definition.....	136
14. The current WLM couple data set format level.....	137
15. Values to use in storage estimation formulas.....	147
16. Menu bar options on the Definition Menu.....	174
17. Return codes from IWMARIN0.....	217
18. WLM Libraries.....	218
19. Keylist names and usage descriptions.....	224
20. Return codes from IWMINSTL.....	227

About this information

This information describes workload management in a z/OS environment.

Note: The z/OS workload management component is sometimes also called "Workload Manager."

Who should use this information

This information is intended for the system programmers, system analysts, and systems engineers who are responsible for implementing z/OS workload management.

WLM information updates on the web

For the latest information, go to [IBM z/OS Workload Manager \(github.com/IBM/IBM-Z-zOS/tree/main/zOS-WLM\)](https://github.com/IBM/IBM-Z-zOS/tree/main/zOS-WLM).

Where to find more information

You can find more information about system capacity planning best practices, techniques, and tooling at IBM Techdocs (www.ibm.com/support/techdocs/atsmastr.nsf/Web/TechDocs).

Where necessary, this document references information in other documents, using shortened versions of the document title. For complete titles and order numbers of the documents for all products that are part of z/OS, see [z/OS Information Roadmap](#).

How to send your comments to IBM

We invite you to submit comments about the z/OS product documentation. Your valuable feedback helps to ensure accurate and high-quality information.

Important: If your comment regards a technical question or problem, see instead [“If you have a technical problem”](#) on page xvii.

Submit your feedback by using the appropriate method for your type of comment or question:

Feedback on z/OS function

If your comment or question is about z/OS itself, submit a request through the [IBM RFE Community](#) (www.ibm.com/developerworks/rfe/).

Feedback on IBM® Documentation function

If your comment or question is about the IBM Documentation functionality, for example search capabilities or how to arrange the browser view, send a detailed email to IBM Documentation Support at ibmdocs@us.ibm.com.

Feedback on the z/OS product documentation and content

If your comment is about the information that is provided in the z/OS product documentation library, send a detailed email to mhvrcfs@us.ibm.com. We welcome any feedback that you have, including comments on the clarity, accuracy, or completeness of the information.

To help us better process your submission, include the following information:

- Your name, company/university/institution name, and email address
- The following deliverable title and order number: z/OS MVS Planning: Workload Management, SC34-2662-50
- The section title of the specific information to which your comment relates
- The text of your comment.

When you send comments to IBM, you grant IBM a nonexclusive authority to use or distribute the comments in any way appropriate without incurring any obligation to you.

IBM or any other organizations use the personal information that you supply to contact you only about the issues that you submit.

If you have a technical problem

If you have a technical problem or question, do not use the feedback methods that are provided for sending documentation comments. Instead, take one or more of the following actions:

- Go to the [IBM Support Portal](#) (support.ibm.com).
- Contact your IBM service representative.
- Call IBM technical support.

Summary of changes

This information includes terminology, maintenance, and editorial changes. Technical changes or additions to the text and illustrations for the current edition are indicated by a vertical line to the left of the change.

Note: IBM z/OS policy for the integration of service information into the z/OS product documentation library is documented on the z/OS Internet Library under [IBM z/OS Product Documentation Update Policy \(www-01.ibm.com/servers/resourceLink/svc00100.nsf/pages/ibm-zos-doc-update-policy?OpenDocument\)](http://www-01.ibm.com/servers/resourceLink/svc00100.nsf/pages/ibm-zos-doc-update-policy?OpenDocument).

Summary of changes for z/OS MVS Planning: Workload Management for Version 2 Release 5 (V2R5)

The following content is new, changed, or no longer included in V2R5.

New

The following content is new.

May 2022 refresh

- The topic, [“Defining recovery process boost for middleware recycle”](#) on page 77, has been added. (APARs OA60660/OA60841, which also apply to z/OS V2R4)
- The topic, [“Migration considerations for service definition coefficients”](#) on page 145, has been added.

Changed

The following content is changed.

August 2023 refresh

- The notes are updated in [“Batch workload management”](#) on page 18.

June 2023 refresh

- Additional guidance about the default service class for the STC subsystem type is provided in [“Defining a subsystem service class default”](#) on page 78.

March 2023 refresh

- Updates are made in [“System-provided service classes”](#) on page 80 and [“Using the system-supplied service classes”](#) on page 88. (APAR OA64269, which also applies to z/OS 2.4)

February 2023 refresh

- Information about using the WLM ISPF application is updated in [“Before you begin”](#) on page 167. (APAR OA64145, which also applies to z/OS 2.4)

September 2022 refresh

- [“Absolute MSU capping”](#) on page 25 is updated for clarity.

May 2022 refresh

- The following topics are updated in support of recovery process boost for middleware recycle. (APARs OA60660/OA60841, which also apply to z/OS V2R4)
 - [“Migrating to a new z/OS release with an existing service definition”](#) on page 133

- [“Service definition functionality levels, CDS format levels, and WLM application levels”](#) on page 136
- [Chapter 21, “System Recovery Boost,”](#) on page 165
- [“Working with classification rules”](#) on page 183
- [Appendix C, “Return codes for the IWMINSTL sample job,”](#) on page 227
- Information about zAAPs has been removed, and the terms *standard CP* and *regular CP* have been converged to *general purpose CP* throughout the text. In addition, information about zIIPs has been reviewed and, where necessary, updated for currency.

February 2022 refresh

- [“Storage critical for address spaces”](#) on page 99 is updated to indicate that storage protection can also be assigned for address spaces with the SYSSTC or SYSTEM service class.

Prior to February 2022 refresh

- The phrase *service coefficients and options* has been changed to *service definition options* throughout this publication.
- The Service Coefficients/Service Definition Options panel has been changed to the Service Definition Options panel.
- The topic, [“Calculating the amount of service consumed”](#) on page 49 was updated and relocated from Chapter 13, [“Defining service definition options,”](#) on page 95 to Chapter 9, [“Defining service classes and performance goals,”](#) on page 47.
- Chapter 13, “Defining service coefficients and options,” has been retitled to [Chapter 13, “Defining service definition options,”](#) on page 95.
- Information about WLM batch initiator management has been updated in [“Batch workload management”](#) on page 18.

Deleted

The following content was deleted.

May 2022 refresh

- The chapter, “Using System z Application Assist Processors (zAAP),” has been removed.
- Service coefficients are no longer used, and most information about them has been removed from this publication except for the topic about migration.

Summary of changes for z/OS Version 2 Release 4 (V2R4)

The following changes are made for z/OS Version 2 Release 4 (V2R4).

New

The following information is new in this publication:

Prior to September 2020 refresh

- A new chapter about System Recovery Boost is added. For more information, see [Chapter 21, “System Recovery Boost,”](#) on page 165.

Changed

The following information is changed in this publication:

January 2021 refresh

- For APAR OA59066, the topic, “Changing your coefficient values”, is updated.

September 2020 refresh

- For APAR OA59366, information about System Recovery Boost is updated. See [Chapter 21, “System Recovery Boost,”](#) on page 165.

Prior to September 2020 refresh

- Resource group type descriptions are updated. See [Chapter 7, “Defining resource groups,”](#) on page 37.

Deleted

The following information is deleted in this publication:

January 2021 refresh

- For APAR OA59066, the topic, "Using the storage (MSO) coefficient for calculations," has been removed from [Chapter 13, “Defining service definition options,”](#) on page 95.

Summary of changes for z/OS Version 2 Release 3 (V2R3)

The following changes are made for z/OS Version 2 Release 3 (V2R3). All technical changes for z/OS V2R3 are indicated by a vertical line to the left of the change.

New

- New chapters discussing tenant resource groups and tenant report classes added:
 - [Chapter 8, “Defining tenant resource groups,”](#) on page 45
 - [Chapter 11, “Defining tenant report classes,”](#) on page 91
- New subtopics discussing tenant resource groups and tenant report classes added:
 - [“Deactivate discretionary goal management”](#) on page 98
 - [“Working with tenant resource groups”](#) on page 182
- Resource group type 4 was added to [Chapter 7, “Defining resource groups,”](#) on page 37.
- [“Why use resource groups or tenant resource groups?”](#) on page 9 now includes tenant resource groups.
- Absolute MSU capping is added. See [“Workload management and Workload License Charges”](#) on page 24.

Changed

- Container Pricing for IBM Z was renamed Tailored Fit Pricing for IBM Z.
- For APAR OA52611, [Chapter 7, “Defining resource groups,”](#) on page 37, Setting a memory limit, is updated.
- The following now include information about tenant resource groups and tenant report classes:
 - [“What is a service definition?”](#) on page 6
 - [“Assigning work to a service class”](#) on page 10
 - [“Specifying a service definition”](#) on page 29
 - [Chapter 5, “Defining service policies,”](#) on page 31
 - [“Using policy overrides”](#) on page 32
 - [Chapter 7, “Defining resource groups,”](#) on page 37
 - [Chapter 8, “Defining tenant resource groups,”](#) on page 45
 - [Chapter 10, “Defining classification rules,”](#) on page 57
 - [“Defining special reporting options for workload reporting”](#) on page 75

- [Chapter 11, “Defining tenant report classes,” on page 91](#)
- [Chapter 13, “Defining service definition options,” on page 95](#)
- [“Migrating to a new z/OS release with an existing service definition” on page 133](#)
- [“Service definition functionality levels, CDS format levels, and WLM application levels” on page 136](#)
- [“Working with resource groups” on page 178](#)
- [“Defining service policy overrides” on page 181](#)
- [“Working with tenant resource groups” on page 182](#)
- [“Using selection lists for classification rules” on page 190](#)
- [“Working with service definition options” on page 192](#)
- [“IWMAM040” on page 206](#)
- [“Why use resource groups or tenant resource groups?” on page 9](#) now includes tenant resource groups.
- For service class periods with an average response time goal or a response time goal with percentile, the lowest goal that can be specified is changed from 15 milliseconds to 1 millisecond. New functionality levels are added. See [“Service definition functionality levels, CDS format levels, and WLM application levels” on page 136](#).
- [“Migrating to a new z/OS release with an existing service definition” on page 133](#).
- [“Client IP address” on page 66](#).
- For APAR OA5342, updates are made in:
 - [Chapter 17, “Workload management migration,” on page 131](#)
 - [“Allocate a WLM couple data set” on page 138](#)
 - [“Increasing the size of the WLM couple data set” on page 140](#)
 - [Chapter 22, “Using the WLM ISPF application,” on page 167](#)
 - [“IWMAM065” on page 209](#)
 - [“Utilities” on page 175](#)
 - [“Allocating a WLM couple data set” on page 203](#)

Deleted

- Information relating to GPMP has been removed.

Chapter 1. Why MVS workload management?

Before the introduction of MVS™ workload management, MVS required you to translate your data processing goals from high-level objectives about what work needs to be done into the extremely technical terms that the system can understand. This translation requires high skill-level staff, and can be protracted, error-prone, and eventually in conflict with the original business goals. Multi-system, sysplex, parallel processing, and data sharing environments add to the complexity.

MVS workload management provides a solution for managing workload distribution, workload balancing, and distributing resources to competing workloads. MVS workload management is the combined cooperation of various subsystems (CICS®, IMS/ESA®, JES, APPC, TSO/E, z/OS UNIX System Services, DDF, DB2®, SOM, LSFM, and Internet Connection Server) with the MVS workload management (WLM) component.

This information identifies the problems that led to workload management, and describes the high-level objectives for the long term.

Problems addressed by workload management

The problems that needed to be solved by workload management include:

- **System externals:**

Performance and tuning externals are scattered between MVS and various subsystems, as well as throughout monitoring and reporting products. This is true for the OPT parameters, and, prior to z/OS V1R3, for the MVS installation performance specifications (IPS) and the installation control specifications (ICS). MVS and the subsystems each have their own terminology for similar concepts, each have their own controls, and the controls are not coordinated.

- **Expectations:**

Many of the MVS externals are geared towards implementation. You tell MVS how to process work, not your expectations of how well it should run work. There is no single way to make sure that important work is getting the necessary system resources.

- **Integration and feedback:**

The multiple monitoring and reporting products show many different views of how well MVS is doing, or how well individual subsystems are managing work. Since there is no single way to specify performance goals for your installation, it is also difficult to get feedback from monitors and reporters on how well your installation actually achieved what you expected it to. There is little sense of which reports and fields relate to the externals you specified.

- **Managing towards expectations:**

Some installations configure their systems to handle a peak load. This could result in inefficient use of expensive resources. Today's externals do not allow you to reflect your performance expectations for work. Today, a system programmer must completely understand the implications of changing a parameter before he or she can configure an installation to achieve performance objectives. Since there is no direct path between specification and expectation, it is difficult to predict the effects of changing any one control or parameter.

Given this mix of problems, workload management has some high level objectives to provide a solution.

MVS workload management solution for today and tomorrow

Workload management requires a shift of focus from tuning at a system resources level to defining performance expectations. This requires a basic shift in philosophy towards goal-oriented systems management. The complete workload management solution offers a shift in philosophy in the following areas:

- ***Fewer, simpler, and consistent system externals:***

Workload management provides a way to define MVS externals and tune MVS without having to specify low-level parameters. The focus is on setting performance goals for work, and letting workload management handle processing to meet the goals.

- ***Externals reflect customer expectations:***

Workload management provides new MVS performance management externals in a *service policy* that reflects goals for work, expressed in terms commonly used in service level agreements (SLA). Because the terms are similar to those commonly used in an SLA, you can communicate with end-users, with business partners, and with MVS using the same terminology.

- ***Expectations-to-feedback correlation:***

With one common terminology, workload management provides feedback to support performance reporting, analysis, and modelling tools. The feedback describes performance achievements in the same terms as those used to express goals for work.

- ***“System Managed” toward expectations:***

Workload management provides automatic work and resource management support that dynamically adapts as needed. It manages the trade-offs between meeting your service goals for work and making efficient use of system resources.

- ***Sysplex externals and management scope:***

Workload management eliminates the need to micro-manage each individual MVS image, providing a way for you to increase the number of systems in your installation without greatly increasing the necessary skill level.

Chapter 2. What is MVS workload management?

Installations today process different types of work with different response times. Every installation wants to make the best use of its resources and maintain the highest possible throughput and achieve the best possible system responsiveness.

WLM manages the system resources that are available and can only meet performance objectives if the necessary resources are available. Therefore, installations must perform regular capacity planning as outlined by the information available at [IBM Techdocs \(www.ibm.com/support/techdocs/atsmastr.nsf/Web/TechDocs\)](http://www.ibm.com/support/techdocs/atsmastr.nsf/Web/TechDocs).

With workload management, you define performance goals and assign a business importance to each goal. You define the goals for work in business terms, and the system decides how much resource, such as CPU and storage, should be given to the work to meet its goal.

An installation should know what it expects to accomplish in the form of performance goals, as well as how important it is to the business that each performance goal be achieved. With workload management, you define performance goals for work, and the system matches resources to the work to meet those goals, constantly monitoring and adapting processing to meet the goals. Reporting reflects how well the system is doing compared to its goals.

[Figure 1 on page 4](#) shows a high level overview of the workload management philosophy. The following section explains the performance administration and performance management processes.




Figure 1. MVS Workload Management Overview

Performance administration

Performance administration is the process of defining and adjusting performance goals. Workload management introduces the role of the service level administrator. The service level administrator is responsible for defining the installation's performance goals based on business needs and current performance. This explicit definition of workloads and performance goals is called a *service definition*. Some installations might already have this kind of information in a service level agreement (SLA). The service definition applies to all types of work, CICS, IMS, TSO/E, z/OS UNIX System Services, JES, APPC/MVS, LSFM, DDF, DB2, SOM, Internet Connection Server (also referred to as IWEB) and others. You can specify goals for all MVS managed work, whether it is online transactions or batch jobs. The goals defined in the service definition apply to all work in the sysplex.

Because the service definition terminology is similar to the terminology found in an SLA, the service level administrator can communicate with the installation user community, with upper level management, and with MVS using the same terminology. When the service level requirements change, the service level administrator can adjust the corresponding workload management terms, without having to convert them into low-level MVS parameters.

Workload management provides an online panel-based application for setting up and adjusting the service definition. You specify the service definition through this ISPF administrative application.

Workload management provides the capability to collect performance and delay data in context of the service definition. The performance and delay data are available to reporting and monitoring products, so that they can use the same terminology.

Performance management

Performance management is the process workload management uses to decide how to match resources to work according to performance goals. Workload management algorithms use the service definition information and internal monitoring feedback to check how well they are doing in meeting the goals. The algorithms periodically adjust the allocation of resource as the workload level changes.

For each system, workload management handles the system resources. Workload management coordinates and shares performance information across the sysplex. How well it manages one system is based on how well the other systems are also doing in meeting the goals. If there is contention for resources, workload management makes the appropriate trade-offs based on the importance of the work and how well the goals are being met.

Workload management can dynamically start and stop server address spaces to process work from application environments. Workload management starts and stops server address spaces in a single system or across the sysplex to meet the work's goals.

You can turn over management of batch initiators to workload management, allowing workload management to dynamically manage the number of batch initiators for one or more job classes to meet the performance goals of the work.

In addition to internal feedback monitoring, workload management keeps track of what is happening in the sysplex in the form of real time performance data collection, and delay monitoring. All this information is available for performance monitors and reporters for integration into detailed reports.

Workload balancing

To make the most of workload management, work needs to be properly distributed so that MVS can manage the resources. It is essential that the subsystems distributing work are configured properly for workload distribution in a sysplex. You do this with the controls provided by each subsystem. For example, in a JES2 and JES3 environment, you spread initiator address spaces across each system.

Initial cooperation between MVS and the transaction managers (CICS, IMS, DB2) allows you to define performance goals for all types of MVS-managed work. Workload management dynamically matches resources (access to the processor and storage) to work to meet the goals.

CICS, however, goes further with the CICSplex Systems Manager (CICSplex® SM) to dynamically route CICS transactions to meet the performance goals. CPSM monitors the performance of CICS resources and systems and presents the resources as though they were part of a single system. This type of cooperation greatly improves CICS transaction workload balancing.

Other subsystems also have automatic and dynamic work balancing in a sysplex. For example, DB2 can spread distributed data facility (DDF) work across a sysplex automatically. DB2 can also distribute work in a sysplex through its sysplex query parallelism function. CICS, TSO, and APPC cooperate with VTAM® and workload management in a sysplex to balance the placement of sessions. SOMobjects can automatically spread its servers across a sysplex to meet performance goals and to balance the work.

For more detail on workload management in different subsystem environments, see [Chapter 3, “Workload management participants,”](#) on page 15.

Workload management concepts

The *service definition* contains all the information about the installation needed for workload management processing. There is one service definition for the entire sysplex. The service level administrator specifies

the service definition through the WLM administrative application. The service level administrator sets up *policies* within the service definition to specify the goals for work. A service level administrator must understand how to organize work, and be able to assign it performance objectives.

What is a service definition?

A *service definition* consists of:

- One or more *service policies*, which are named sets of overrides to the goals in the service definition. When a policy is activated, the overrides are merged with the service definition. You can have different policies to specify goals for different times. Service policies are activated by an operator command or through the ISPF administrative application utility.
- *Service classes*, which are subdivided into periods, group work with similar performance goals, business importance, and resource requirements for management and reporting purposes. You assign performance goals to the periods within a service class.
- *Workloads*, which aggregate a set of service classes for reporting purposes.
- *Report classes*, which group work for reporting purposes. They are commonly used to provide more granular reporting for subsets of work within a single service class.
- *Resource groups*, which define processor capacity boundaries within a system or across a sysplex. You can assign a minimum and maximum amount of CPU service units on general purpose processors, per second, to work by assigning a service class to a resource group.
- *Tenant resource groups* and *tenant report classes*, which are comparable to resource groups and report classes. They allow for the metering and optional capping of workloads, along with the ability to map those workloads directly to Tailored Fit Pricing for IBM Z solutions.
- *Classification rules*, which determine how to assign incoming work to a service class and report class or tenant report class.
- *Application environments*, which are groups of application functions that execute in server address spaces and can be requested by a client. Workload management manages the work according to the defined goal, and automatically starts and stops server address spaces as needed.
- *Scheduling environments*, which are lists of resource names along with their required states. If a z/OS image satisfies all of the requirements in a scheduling environment, then units of work associated with that scheduling environment can be assigned to that z/OS image.

The following section explains each of the concepts.

Why use service policies?

A *service policy* is a named set of overrides to the performance goals and processing capacity boundaries in the service definition. A policy applies to all of the work running in a sysplex. Because processing requirements change at different times, service level requirements may change at different times. If you have performance goals that apply to different times or a business need to limit access to processor capacity at certain times, you can define multiple policies.

In order to start workload management processing, you must define at least one service policy. You can activate only one policy at a time.

Organizing work into workloads and service classes

To workload management, work is a demand for service, such as a batch job, an APPC, CICS, DB2, or IMS transaction, a TSO/E logon, a TSO/E command, or a SOM request. All work running in the installation is divided into workloads. Your installation may already have a concept of workload. A *workload* is a group of work that is meaningful for an installation to monitor. For example, all the work created by a development group could be a workload, or all the work started by an application, or in a subsystem.

Within a workload, you group work with similar performance characteristics into *service classes*. You create a service class for a group of work that has similar:

- Performance goals

- Resource requirements
- Business importance to the installation

Performance goals

You assign a *performance goal* to each service class period, such as a response time goal, and you indicate an importance. *Importance* is how important it is to your business that the performance goal be achieved.

There are three kinds of goals:

- *Response-time goals* indicate how quickly you want your work to be processed. Since response time goals are not appropriate for all kinds of work, such as long running batch jobs, there are execution velocity goals.
- *Execution velocity goals* define how fast work should run when ready, without being delayed for processor, storage, I/O access, and queue delay. Execution velocity goals are intended for work for which response time goals are not appropriate, such as started tasks, or long running batch work.
- *Discretionary goals* are for low priority work for which you do not have any particular performance goal. Workload management then processes the work using resources not required to meet the goals of other service classes.

Resource requirements

Because some work may have variable resource requirements, you can define multiple periods for a service class. *Periods* are a way of defining different goals for work depending on the amount of resources the work consumes. Typically, periods are used to give shorter transactions more aggressive goals and to give longer running work of the same type less aggressive goals. If you have multiple periods, each period except the last has a duration. *Duration* is the amount of resources (including all processor types), in service units, that the work consumes before it is switched to the goals of the next period.

You can also group work into a service class based on resource requirements. If you have a group of batch work that can consume vast amounts of resources, and you want to limit it, you can define a service class and assign it to a resource group with a maximum amount of capacity. If the work exceeds that capacity, workload management slows the execution rate. Also, if a certain group of work needs a minimum amount of processor capacity, you can set up a service class and assign it to a resource group.

Business importance

When there is not sufficient capacity for all work in the system to meet its goals, business importance is used to determine which work should give up resources and which work should receive more. You assign an *importance* to a service class period, which indicates how important it is that the goal be met relative to other goals. Importance plays a role only when a service class period is not meeting its goal. There are five levels of importance: lowest (5), low, medium, high, and highest (1).

Figure 2 on page 8 shows an example of the relationship between workloads and service classes. Work in the figure is represented by different size triangles. The IMS workload in the figure, represents all of the IMS work. There are three single-period service classes set up, each with a different importance, and a different response time goal.




Figure 2. Workload organized by subsystem

Figure 3 on page 8 shows an example of a workload that is organized by division. In the figure, work is represented by different shapes: circles, squares, and triangles. The OFFICE workload represents all of the work in the office division. There are three service classes set up, each for a different kind of work in the OFFICE workload. The IMSTEST class represents the IMS test work, CICS represents all of the CICS work, and JES represents all of the batch work in the OFFICE workload. Each of the service classes has one period with a different response time goal assigned to it.




Figure 3. Workload organized by department

Why use resource groups or tenant resource groups?

Why use resource groups?

Resource groups are a way of limiting or guaranteeing general purpose and specialty processor resource capacity. A resource group is a named amount of CPU capacity on general purpose processors that you can assign to one or more service classes. For most systems, you can let workload management decide how to manage the resources in the sysplex and not use resource groups. You set performance goals for work and let workload management adjust to meet the goals.

In some cases, however, you might want to use a resource group, for example, to limit the service that a certain service class can consume. Note that it is recommended that each resource group is assigned to only one service class. Using a resource group is appropriate, for example:

- If you have an SLA that charges for a fixed amount of CPU capacity and you want to ensure that no more is used.
- If you want to ensure that some work with discretionary goals receives some minimum amount of capacity.

Generally, it is recommended to evaluate whether using a resource group fulfills your requirements best, or whether you let workload management take care of managing the resources.

For a resource group, you specify either a minimum or a maximum amount of general purpose processor capacity in unweighted CPU service units per second, or both.

Figure 4 on page 9 shows some examples of resource groups.




Figure 4. Resource groups

In Figure 4 on page 9, the BATHOG service class is assigned to the LIMIT resource group. BATHOG might include work that consumes processing capacity in huge amounts, so you assign it to a resource group, and limit it to a maximum of 800 CPU service units per second. Also, the goal assigned to BATHOG is discretionary.

The TSOMED service class, on the other hand, is associated with the PROTECT resource group because, according to an SLA, it is contracted to be guaranteed a minimum amount of processing capacity. So the PROTECT resource group is assigned a minimum of 1000 CPU service units per second. Then, when there is sufficient TSOMED work in the system, and TSOMED is underachieving its goal, TSOMED is guaranteed

at least 1000 CPU service units per second. Note that if TSOMED is surpassing its goal, then the minimum capacity setting has no effect. Workload management then processes work from both service classes, making sure that TSOMED gets its minimum amount of capacity, and making sure BATHOG does not consume more than its assigned maximum. Keep in mind the service class goal: if BATHOG is assigned a stringent goal, the goal may never be achievable within the LIMIT resource group capacity. You should determine whether the resource group capacity fulfills your purpose, or the goal. Using both controls could introduce some conflict, and the resource group controls will prevail.

Why use tenant resource groups?

Tenant resource groups are similar to resource groups but accept and process an IBM provided Solution ID which maps workloads as required by some pricing models.

Assigning work to a service class

Classification rules are the rules workload management uses to associate a performance goal and a resource group with work by associating incoming work with a service class. Optionally, classification rules can also associate incoming work with a report class or tenant report class.

The classification rules for a subsystem are specified in terms of transaction qualifiers such as job name or transaction class. These qualifiers identify groups of transactions that should have the same performance goals and importance. The attributes of incoming work are compared to these qualifiers and, if there is a match, the rule is used to assign a service class to the work. A subsystem can also have a default class for work that does not match any of the rules.

Figure 5 on page 10 shows how work classification rules associate a service class, and optionally a report class (or tenant report class) with incoming work.




Figure 5. Work classification

Optionally, classification rules can assign incoming work to a report class or tenant report class. You get reporting information in terms of workloads, service classes, report classes, or tenant report classes and tenant resource groups. Use report classes for obtaining data on a subset of work within a service class, or for rolling up data across workloads. If you need to map additional work to Tailored Fit Pricing for IBM Z, use tenant report classes instead of report classes.

Why use application environments?

An *application environment* is a way to group similar server programs together and have workload management dynamically create and delete server address spaces as needed to handle the work. Each application environment typically represents a named group of server functions that require access to the same application libraries. Depending on the subsystem's implementation of application environments, the scope of server address space management is either confined to a single system or is sysplex-wide. There is also an option to manually start and stop the server address spaces for an application environment if there is a special or temporary requirement to control the number of servers independently of workload management.

If you are using a subsystem that takes advantage of application environments, you need to refer to the subsystem documentation for guidance on how to use them for that subsystem. For a list of the IBM-supplied subsystems currently using application environments, see [Chapter 15, “Defining application environments,”](#) on page 113.

Figure 6 on page 11 shows an example of how two application environments, AE1 and AE2, can be used to handle work requests from a subsystem. In this example, three types of work requests, X, Y, and Z are handled. X and Y might be two different kinds of payroll inquiries, and Z might be a loan inquiry.




Figure 6. Application environment example

The names X, Y, and Z are used by clients when making the work requests. The work manager subsystem contains a table or file that associates the work request names with an application environment name; in this example, X and Y are associated with application environment AE1, and Z with AE2. The application environment names AE1 and AE2 are specified to workload management in the service definition stored in the WLM couple data set, and are included in the active policy when a policy is activated.

Each application environment must be assigned a system procedure library (PROCLIB) member name that contains the JCL required to start server address spaces for the application environment. In the example, PROCS1 and PROCS2 are associated with application environments AE1 and AE2, respectively.

When the work manager subsystem receives a type Y work request from a client, the subsystem requests that workload management associate the request with AE1. Workload management determines if a server address space is available to handle the request, or if an address space needs to be created. If a server

address space exists, workload management makes the request available for the server. If a server address space does not exist or if more are required, workload management starts a server address space using the startup JCL procedure named PROCS1 which is defined for AE1 in the active policy.

Workload management dynamically creates new server address spaces if they are needed to handle more incoming work and, for certain subsystems such as DB2, decreases the number of server address spaces if less capacity is needed. Refer to [Chapter 15, “Defining application environments,”](#) on [page 113](#) for a description of how to define application environments to workload management.

Why use scheduling environments?

Scheduling environments help ensure that units of work are sent to systems that have the appropriate resources to handle them. A scheduling environment is a list of resource names along with their required states. Resources can represent actual physical entities, such as a data base or a peripheral device, or they can represent intangible qualities such as a certain period of time (like second shift or weekend).

These resources are listed in the scheduling environment according to whether they must be set on or off. A unit of work can be assigned to a specific system only when all of the required states are satisfied. This function is commonly referred to as *resource affinity scheduling*.

[Figure 7 on page 12](#) shows a simple scheduling environment example. The arriving work units, X, Y, and Z, could be batch jobs submitted through JES2 or JES3. Each of the jobs had a scheduling environment associated with it at the time it was submitted (in this case the X and Y jobs are each associated with the A scheduling environment, and the Z job is associated with the B scheduling environment).




Figure 7. Scheduling environment example

JES checks the scheduling environment associated with each arriving batch job and then assigns the work to a system that matches that scheduling environment. In the example, both the X and Y jobs require that both Resource P and Resource Q be set to ON, so those jobs can be initiated only on System 1 in the sysplex. The Z job requires that Resource P be set to ON and that Resource Q be set to OFF. So that job can be initiated only on System 2.

In a sysplex containing only one system, scheduling environments have some degree of usefulness, as JES will hold batch jobs until the required states become satisfied. In a multisystem sysplex, the full power of scheduling environments becomes apparent, as work is assigned only to those systems that have the correct resource states (the resource affinity) to handle that work.

Presently, JES2 and JES3 are the only participants that use scheduling environments, although the concepts could certainly apply to other types of work in the future.

See [Chapter 16, “Defining scheduling environments,” on page 123](#) for a description of how to define scheduling environments to workload management.

Summary of service definition and service policy concepts

When you set up your service definition, you identify the workloads, the resource groups, the service classes, the service class periods, and goals based on your performance objectives. Then you define classification rules and one or more service policies. This information makes up the base service definition.

A two-step process is required before the sysplex starts using a new service definition. First, you install the service definition onto the WLM couple data set. Second, you activate one of the service policies from the definition.

With a service policy, you can override specific goals or resource groups in your base service definition. In a typical scenario, you might define a base service definition that is appropriate for your normal business hours. Because you need to have at least one service policy defined, you might create an empty service policy called NORMAL. While the NORMAL service policy is in effect, there would be no overrides to the goals or resource groups in the base service definition. If you have a special business need to change your goals for offshift processing, you might then also create a service policy called OFFSHIFT. If you were to activate this policy at the end of the business day (either by invoking the VARY WLM, POLICY=*polycyname* command or by using the “Activating a Service Policy” panel in the ISPF application), then the goal overrides in the OFFSHIFT service policy would be in effect until you switched back to NORMAL the next morning.

[Chapter 5, “Defining service policies,” on page 31](#) tells you more about how to define a policy, and also shows a few examples.

Note that you can override *only* goals, number and duration of periods, resource group assignments and values. All of the workloads, service class names, classification rules, scheduling environments, and application environments defined in the service definition remain the same for any policy. If you need to change any of these, you will need to change the base service definition, reinstall the service definition, and then activate a policy from that changed service definition.

Note, also, that you need to define all of your policies at the outset, while you are defining the rest of the service definition. Once the service definition is installed, then you can switch from one defined policy to another. If you need to create a new policy or change the overrides in an existing policy, you will need to reinstall the service definition with the new or changed policy definition before you can activate the new policy.

[Figure 8 on page 14](#) shows a service definition with two service policies.




Figure 8. Service definition, including two service policies

Chapter 3. Workload management participants

You use the WLM ISPF administrative application to define your service definition. The administrative application requires the following products:

- TSO/E Version 2.5 plus SPEs, or later
- ISPF 4.3, or later

This information describes the work and reporting environments that support workload management.

Workload management work environments

Cooperation between MVS and the subsystem work managers enable the sysplex-wide specification and reporting of goals defined for work in the service policy. You can define goals for the following kinds of work:

- IMS, if you have IMS/ESA Release 5 or higher
- CICS, if you have CICS/ESA 4.1 or higher
- z/OS UNIX System Services
- JES2
- JES3
- APPC
- TSO/E
- SOMobjects
- WebSphere® Application Server objects (CB)
- LSFM
- DDF, if you have DB2 V4.1, or higher
- DB2, if you have DB2 V 5, or higher
- IWEB, if you have Internet Connection Server V 2.2, or higher, Domino® Go Webserver, or IBM http Server Powered by Domino (IHS powered by Domino)
- IBM MQ Workflow
- SYSH, if you need to manage non z/OS partitions
- NETV

Arriving work is associated with a service class, and therefore a goal and possibly a resource group. You get feedback from RMF as to how well the system is doing in meeting the goals. RMF provides sysplex-wide workload management reporting, providing sysplex-wide as well as single system feedback on the goals through the Post Processor and Monitor III realtime reports. The reports show kinds of delays seen by subsystem work managers such as CICS and IMS. SDSF displays workload management related information.

The Workload Management Environment




Figure 9. Sysplex view of the management environment

Workload management understands which address spaces (INITs, AORs, MPPs, BMPs, TORs, FORs) are involved in processing work within a service class, and matches the resources to meet the goal. Information as to how well each system is doing in processing towards a service class goal is recorded in SMF records on each system. For more information about workload management information in RMF reports, see [z/OS Resource Measurement Facility Report Analysis](#).

Subsystem support for goal types and multiple periods

The types of goals a subsystem supports depends on the workload management services it uses. For the following subsystems that have address space-oriented transactions or use enclaves, you can specify any goal type and multiple periods:

- Subsystems that have address space-oriented transactions:
 - APPC
 - JES2
 - JES3
 - z/OS UNIX System Services
 - TSO/E
- Subsystems that use enclaves:
 - WebSphere Application Server
 - DB2
 - DDF
 - IWEB
 - IBM MQ Workflow
 - LSFM
 - NETV
 - SOMobjects

Note: Enclaves are transactions that can span multiple dispatchable units in one or more address spaces, and in the case of multisystem enclaves, one or more address spaces on multiple systems in a parallel sysplex. See [z/OS MVS Programming: Workload Management Services](#) for more information about enclaves.

The CICS and IMS subsystems do not use enclaves, but use a different set of WLM services to support their transactions to WLM. Therefore, they support only response time goals, either percentile or average, and single period service classes.

Subsystem-specific performance hints

Based on installation experiences, here are some subsystem-specific performance hints:

- Watch out for increased CPU usage by the WLM address space due to a high CICS **MAXTASK** setting.

For CICS 4.1 and higher releases, WLM collects delay samples for each performance block. Because the number of performance blocks created is based on the **MAXTASK** value (a value of 100 means 100 performance blocks created per region), a **MAXTASK** value that is too high can cause a large sampling overhead when a CICS workload is switched to goal mode. If **MAXTASK** has been set to an arbitrarily high value, it should be reduced to a true “high water mark” value.

- Watch out for work defaulting to SYSOTHER.

Work in subsystems that use enclaves (see “Subsystem support for goal types and multiple periods” on page 16 for a list of these subsystems) can suffer performance degradation if left unclassified in the service definition. If you do not add classification rules for this work in your service definition, it will be assigned to the SYSOTHER service class, which has a discretionary goal. Using the WLM application, you need to add classification rules to assign the work to service classes with appropriate response time or velocity goals.

As a general rule, it's a good idea to keep an eye on the SYSOTHER service class through RMF or another monitor. Any service accumulating in the SYSOTHER service class is a signal that you have unclassified work in your system.

For the latest information on these topics and others, see [IBM Workload Manager for z/OS Frequently Asked Questions \(www.ibm.com/downloads/cas/4ROABVG5\)](http://www.ibm.com/downloads/cas/4ROABVG5).

Workload balancing

Workload management allocates resources to meet goals of the work that arrives. System programmers must use the existing methods of routing and scheduling work for subsystems except for those listed. For subsystems not exploiting workload balancing or routing services, if you want to balance your work across all MVS images in a sysplex, the system programmer must set the routing controls to either balance the arrival of work, or to ensure that all MVS images are equal candidates for processing work.

Examples of subsystems that can automatically balance work in a sysplex include:

- CPSM provides goal-oriented routing based on the goal defined for CICS work in the workload management service policy.
- DB2 V 4.1 provides automatic and dynamic work balancing in a sysplex for distributed data facility (DDF) work.
- DB2 V 5 provides additional automatic work balancing through its sysplex query parallelism function.
- SOMobjects uses application environments to help balance object class binding requests in a sysplex.
- CICS V 4.1, DB2 V 4.1, TSO/E V 2.5, and APPC cooperate with VTAM 4.4 and workload management in a sysplex to manage session placement. New sessions for these subsystems are directed to the appropriate systems in the sysplex to balance work and meet performance goals.
- JES2 and JES3 provides automatic and dynamic placement of initiators for WLM-managed job classes. z/OS 1.4 together with JES2 1.4, and z/OS 1.5 together with JES3 1.5 provide Initiator Balancing, so that already available WLM managed initiators can be reduced on fully loaded systems and increased on low loaded systems to improve overall batch work performance and throughput over the sysplex.
- WebSphere Application Server cooperates with WLM in a sysplex to balance work among application control regions and to meet performance goals.

Workload management in a CICS environment

Figure 10 on page 18 shows workload management in a CICS with CPSM environment.

WLM recognizes that the terminal owning region (TOR) and the application owning region (AOR) on one or more systems are involved in processing CICS transactions. Using RMF Monitor I, you can get reporting information on the CICS response times, and on any execution delays experienced by a service class period for a single system or for the sysplex.




Figure 10. Workload management in a CICS environment

In a CPSM environment, WLM provides the CICS service class goal to CPSM. If the goal is an average response time goal and you specified the dynamic goal-oriented algorithm for CPSM, then CPSM uses the transaction's goal to help decide where to route the transaction for processing to meet the goal. If the goal is a percentile response time goal, CPSM reverts to its “shortest queue” algorithm since it only has average response time data available to it. Percentile goals are still preferred for any workload that can have a few unusually long transactions distorting the average response time. Following is a summary of the two CPSM algorithms:

Shortest Queue

Send the CICS transaction to the AOR that has the shortest queue of pending work, but prefer AORs on a local MVS image, and be sure to avoid “unhealthy” AORs.

Goal

Send the transaction to an AOR that has been successfully meeting the goal, but prefer AORs on a local image and be sure to avoid “unhealthy” AORs. If the goal is a percentile goal, use the shortest queue.

For more information, see *CICSplex SM Managing Workloads*.

Workload management in a DB2 Distributed Data Facility environment

The definition of a response time for the enclaves used to manage DB2 Distributed Data Facility (DDF) transactions depends upon several parameters, including DB2 installation parameters and the attributes used when binding the package or plan. For more information, see *DB2 Administration Guide*.

Batch workload management

Workload management can dynamically manage the number of batch initiator address spaces in a JES2 or JES3 environment. You can selectively turn over control of the batch initiator management to WLM for one or more job classes. WLM will start new initiators, as needed, to meet the performance goals of this work.

By specifying or defaulting `MODE=JES` on the JES2 `JOBCLASS` statement or the JES3 `GROUP` statement, you indicate that the initiators for the job class should be JES-managed, as in the past. By specifying `MODE=JES`, you keep the job class in JES-managed mode. (JES will manage the batch initiators for that job class, in the same way it has in prior releases.) By specifying `MODE=WLM`, you put that class into WLM-managed mode.

You can switch as many job classes to WLM-managed mode as you wish. You can easily switch any job class back to JES-managed mode by using the JES2 **\$TJOBCLASS** command or the JES3 **MODIFY** command.

WLM manages the number of batch initiator address spaces based on available or displaceable standard processor capacity. Starting with z/OS 2.5, WLM also takes specialty processors into consideration. That is, batch jobs that primarily consume standard processor capacity cause initiators to be started preferentially on systems with available standard processor capacity. Batch jobs that primarily execute on specialty processors cause initiators to be started preferentially on systems with available specialty processor capacity.

Tip: Use separate service classes for batch jobs that primarily execute on general purpose CPs and batch jobs that primarily execute on zIIPs such that all jobs running in the same service class either execute on general purpose CPs or on zIIPs. This allows WLM to manage initiators more efficiently.

Notes:

1. If you have velocity performance goals set for the work running on WLM-managed batch initiators, be aware that the initiation delays will be figured into the velocity formula. This will affect your velocity values and probably require some adjustment to your goals. See [Chapter 9, “Defining service classes and performance goals,”](#) on page 47 for information on defining velocity goals.
2. All jobs with the same service class should be managed by the same type of initiation. For example, if jobs in job classes A and B are classified to the HOTBATCH service class, and JOBCLASS(A) is MODE=WLM, while JOBCLASS(B) is MODE=JES, workload management will have a very difficult time managing the goals of the HOTBATCH service class without managing class B jobs.
3. You can use the JES2 JOBCLASS parameter to specify a default scheduling environment, thereby saving the effort of changing JCL JOB statements or writing a specific JES2 exit to assign the scheduling environment.
4. If a WLM initiator is experiencing system abend 822 and you can determine the ASID of the initiator, you can stop the initiator by issuing the **P INIT,A=asid** command. The initiator does not need to be idle at the time that you enter the command. If the initiator is busy processing a job, it will stop after the job finishes. WLM automatically replaces the initiator with a new one.
5. If a WLM initiator is experiencing system abend 822 and you cannot determine the ASID of the initiator, or if you want to recycle all initiators as part of a regular cleanup process, or initiators are generally not started for a certain atypical period of time, you can enter the **\$P XEQ** and **\$S XEQ** commands. The **\$P XEQ** command causes all WLM initiators on that system to be "flagged" to terminate. The **\$S XEQ** command enables WLM to start new initiators (without needing to wait for the old initiators to end). Beware that the **\$P XEQ** command purges WLM's history which tells it how many initiators are needed for each service class.

See the following JES2 and JES3 documentation for more information about WLM-managed JES2 job classes:

- [z/OS JES2 Initialization and Tuning Guide](#)
- [z/OS JES2 Initialization and Tuning Reference](#)
- [z/OS JES3 Initialization and Tuning Guide](#)
- [z/OS JES3 Initialization and Tuning Reference](#)
- [z/OS JES3 Commands](#)

The following other functions exist to help you manage batch work in a JES environment:

- A new work qualifier, **PRI**, which allows you to use the job priority when defining work classification rules. See [Chapter 10, “Defining classification rules,”](#) on page 57.
- Scheduling environments, which allow you to define resource requirements for incoming work, ensuring that the work will be scheduled on a system within the sysplex only if the resource settings on that system satisfy those requirements. See [Chapter 16, “Defining scheduling environments,”](#) on page 123.

Multisystem enclave support

With multisystem enclave support, enclaves can run in multiple address spaces spanning multiple systems within a parallel sysplex. As in a single system enclave, the work will be reported on and managed as a single unit.

z/OS UNIX System Services Parallel Environment uses multisystem enclaves to run parallel jobs. With all tasks of the job running in the same enclave, WLM can manage all of the work to a single performance goal.

See Chapter 18, “[Defining a coupling facility structure for multisystem enclave support](#),” on page 147 for more information on setting up the SYSZWLM_WORKUNIT coupling facility structure, a prerequisite to multisystem enclave support.

See the “[Creating and Using Enclaves](#)” topic in *z/OS MVS Programming: Workload Management Services* for more information on multisystem enclaves.

See *z/OS UNIX System Services Parallel Environment Operation and Use* for more information on UNIX System Services Parallel Environment.

Intelligent Resource Director

The Intelligent Resource Director (IRD) extends the concept of goal-oriented resource management by allowing you to group logical partitions that are resident on the same physical server, and in the same sysplex, into an “LPAR cluster.” This gives WLM the ability to manage resources, both processor and DASD I/O, not just in one single image but across the entire cluster of logical partitions.

See Chapter 19, “[The Intelligent Resource Director](#),” on page 151 for more information.

HiperDispatch mode

This information briefly describes the HiperDispatch mode.

Overview

In addition to the performance improvements available with the IBM System z10 processors, z/OS workload management and dispatching are enhanced to take advantage of the System z10 hardware design. A mode of dispatching called HiperDispatch provides additional processing efficiencies.

The HiperDispatch mode aligns work to a smaller subset of processors to maximize the benefits of the processor cache structures, and thereby, reduce the amount of CPU time required to execute work. Access to processors has changed with this mode, and as a result, LPAR weights prioritization of workloads via WLM policy definitions becomes more important.

The concept of HiperDispatch mode

Without HiperDispatch, for all levels of z/OS, a TCB or SRB may be dispatched on any logical processor of the type required (general purpose CP or zIIP). A unit of work starts on one logical processor and subsequently may be dispatched on any other logical processor. The logical processors for one LPAR image will receive an equal share for equal access to the physical processors under PR/SM LPAR control. For example, if the weight of a logical partition with four logical processors results in a share of two physical processors, or 200%, the LPAR hypervisor will manage each of the four logical processors with a 50% share of a physical processor. All logical processors will be used if there is work available, and they typically have similar processing utilizations.

With HiperDispatch mode, work can be managed across fewer logical processors. A concept of maintaining a working set of processors required to handle the workload is introduced. In the previous example of a logical partition with a 200% processor share and four logical processors, two logical processors are sufficient to obtain the two physical processors worth of capacity specified by the weight;

the other two logical processors allow the partition to access capacity available from other partitions with insufficient workload to consume their share. z/OS limits the number of active logical processors to the number needed based on partition weight settings, workload demand and available capacity. z/OS also takes into account the processor topology when dispatching work, and it works with enhanced PR/SM microcode to build a strong affinity between logical processors and physical processors in the processor configuration.

Processor categories

The logical processors for a partition in HiperDispatch mode fall into one of the following categories:

- Some of the logical processors for a partition may receive a 100% processor share, meaning this logical processor receives an LPAR target for 100% share of a physical processor. This is viewed as having a high processor share. Typically, if a partition is large enough, most of the logical partition's share will be allocated among logical processors with a 100% share. PR/SM LPAR establishes a strong affinity between the logical processor and a physical processor, and these processors provide optimal efficiencies in HiperDispatch mode.
- Other logical processors may have a medium amount of physical processor share. The logical processors would have a processor share greater than 0% and up to 100%. These medium logical processors have the remainder of the partition's shares after the allocation of the logical processors with the high share. LPAR reserves at least a 50% physical processor share for the medium processor assignments, assuming the logical partition is entitled to at least that amount of service.
- Some logical processors may have a low amount, or 0%, of physical processor share. These "discretionary" logical processors are not needed to allow the partition to consume the physical processor resource associated with its weight. These logical processors may be parked. In a parked state, discretionary processors do not dispatch work; they are in a long term wait state. These logical processors are parked when they are not needed to handle the partition's workload (not enough load) or are not useful because physical capacity does not exist for PR/SM to dispatch (no time available from other logical partitions).

When a partition wants to consume more CPU than is guaranteed by its share and other partitions are not consuming their full guaranteed share, a parked processor can be unparked to start dispatching additional work into the available CPU cycles not being used by other partitions. An unparked discretionary processor may assist work running on the same processor type.

When examining an RMF CPU activity report in HiperDispatch mode, one may now see very different processing utilizations across different logical processors of a logical partition. For further information, refer to [*z/OS Resource Measurement Facility Report Analysis*](#).

Setting HiperDispatch mode in SYS1.PARMLIB

The HiperDispatch state of the system is determined by the number of logical processors defined on an LPAR and the HIPERDISPATCH=YES|NO keyword in the IEAOPTxx member of SYS1.PARMLIB.

All partitions with more than 64 logical processors defined at IPL are forced to run with HIPERDISPATCH=YES. LPARs with more than 64 logical processors defined are also unable to switch into HIPERDISPATCH=NO after IPL.

For all partitions with less than 64 logical processors, HiperDispatch is enabled or disabled by the HIPERDISPATCH=YES|NO keyword in parmlib member IEAOPTxx. This parameter can be changed dynamically with the use of the **SET OPT** command. This enables the operating system to choose the desired mode of operation.

When a new hardware generation is installed, for any z/OS image(s) that are running with HiperDispatch disabled, the system programmer should reevaluate whether those z/OS image(s) should be migrated to running with HiperDispatch enabled in the new environment.

On z10 on any z/OS release, HiperDispatch disabled is the default. However, customers are encouraged to run with HiperDispatch enabled on z10 to take advantage of the processing benefits.

Beginning with z/OS V1R13 on IBM zEnterprise® 196 (z196), HiperDispatch enabled is the default. With z/OS V1R13 running on a z196, z/OS partitions with share greater than 1.5 physical processors will typically experience improved processor efficiency with HiperDispatch enabled. z/OS partitions with share less than 1.5 physical processors typically do not receive a detectable performance improvement with HiperDispatch enabled, but IBM recommends running those LPARs with HiperDispatch enabled when the performance improvement is greater than or equal to HiperDispatch disabled.

There are no new hardware controls or settings to enable use of HiperDispatch within a logical partition; however, the existing “control global performance data” security setting must be enabled on HMC for proper operation of HiperDispatch in a logical partition. HiperDispatch cannot effectively utilize vertical low processors when other partitions are active on the system and “global performance data” is not enabled.

For further information about the **HIPERDISPATCH** parameter, refer to *z/OS MVS Initialization and Tuning Reference*.

I/O storage management

Workload management can pass service class importance and goal information to the storage I/O priority manager in the IBM System Storage® DS8000® series. The information enables the storage I/O priority manager to provide favored processing for I/O requests of important z/OS workloads that are not achieving their goals.

The storage I/O priority manager may throttle I/O requests to facilitate favored access to storage server resources for other I/O requests. The storage I/O priority manager analyzes the properties of the service class period associated with an I/O request and determines whether the I/O request should be favored, or throttled.

Handling service class periods with a response time goal

For service class periods with a response time goal, the goal achievement and specified importance are analyzed. Service class periods that exceed their goal may be throttled if there are service class periods that do not achieve their goal. Service class periods that miss their goal might only be throttled if there are service class periods with a higher importance that do not achieve their goal. In detail, service class periods are processed as follows:

- Service class periods with a response time goal and importance 1 that do not achieve their goal are favored. They are not throttled when they exceed their goal.
- Service class periods with a response time goal and importance 2 that do not achieve their goal are favored. They are not throttled when they exceed their goal, except when more important work is missing its goals.
- Service class periods with a response time goal and importance 3 that do not achieve their goal are favored. They might be moderately throttled when they exceed their goal or more important work is missing its goals.
- Service class periods with a response time goal and importance 4 that do not achieve their goal are moderately favored. They might be throttled when they exceed their goal or more important work is missing its goals.
- Service class periods with a response time goal and importance 5 may be throttled when they exceed their goal or more important work is missing its goals. They are not favored when they miss their goal.

The level of favored processing or throttling that the I/O requests of a service class period with a certain importance receive, depends on the goal achievement, that is, the performance index (PI), of the service class period. A service class period does not receive favored processing if its performance index is between 0.9 and 1.4. The more the PI of a service class period exceeds 1.4, the more it is favored: moderate, strong, or very strong. The more the PI of a service class period falls below 0.9, the more it may be throttled: moderate, strong, or very strong.

Table 1 on page 23 shows the possible levels of favored processing, or throttling in relationship to the importance and goal achievement of a service class period with response time goal:

Table 1. Levels of processing

Importance	Service class period misses goal (PI is higher than or equals 1.4)	Service class period exceeds goal (PI is lower than or equals 0.9)
1	Favored processing — moderate, strong, or very strong	Not throttled
2	Favored processing — moderate, strong, or very strong	Not throttled, except when there are service class periods with higher importance that miss their goal
3	Favored processing — moderate or strong	Throttled — moderate
4	Favored processing — moderate	Throttled — moderate or strong
5	No favored processing	Throttled — moderate, strong, or very strong

Handling service class periods with a velocity goal

For service class periods with a velocity goal, the specified velocity goal and importance are taken into account.

Service class periods with a high importance (1 or 2) and a high velocity goal are most likely being favored. Service class periods with a low importance and a low velocity goal might be throttled.

Because the goal achievement of service class periods with a velocity goal is not taken into account, I/O requests of these service class periods might be throttled even when they miss their goal and might be favored even when they exceed their goal.

Handling other I/O requests

I/O requests associated with the system-provided service classes SYSTEM, SYSSTC, or SYSSTC1 - SYSSTC5 are not managed by the I/O priority manager.

I/O requests associated with service class periods that have a discretionary goal may be throttled, but will never be favored.

Controlling the information passed to the I/O manager

The STORAGESEVERMGT=YES|NO parameter in the IEAOPTxx member of SYS1.PARMLIB controls whether service class importance and goal information is passed to the storage I/O priority manager.

STORAGESEVERMGT=YES specifies that SRM should provide service class importance and goal information to the storage I/O priority manager. The default is STORAGESEVERMGT=NO. Before specifying STORAGESEVERMGT=YES, verify that your IBM System Storage DS8000 model incorporates the I/O priority manager feature. Furthermore, verify if the service option I/O Priority Management in the WLM service definition is set to YES.

Throttle delays introduced by the storage I/O priority manager are reflected in control unit queue delays. Therefore, if STORAGESEVERMGT=YES is specified, control unit queue delays are not considered when the execution velocity is calculated for service class periods with a velocity goal.

If you have significant control unit queue delays in your installation, you might have to adjust the velocity goal of service class periods when you specify STORAGESEVERMGT=YES.

For further information about the STORAGESEVERMGT parameter, refer to [z/OS MVS Initialization and Tuning Reference](#).

Non-z/OS partition CPU management

If you have logical partitions running Linux® or other non-z/OS systems, you can manage CPU resources across these logical partitions in accordance with workload goals. Non-z/OS partition CPU management does not support the management of partitions running z/OS systems.

Non-z/OS partition CPU management allows WLM to shift weight from either z/OS or non-z/OS partitions to another z/OS or non z/OS partition in the same LPAR cluster.

A new SYSH subsystem type is introduced for Linux CPU management. SY and PX are the qualifiers which are valid for SYSH. No resource groups can be associated with service classes for SYSH. Also CPU protection cannot be assigned. SYSH supports velocity goals with single periods, but no discretionary goals.

In order to activate non-z/OS CPU Management, see [“Enabling non-z/OS CPU management”](#) on page 157.

Workload management and Workload License Charges

As part of the z/OS support of Workload License Charges, you can set a defined capacity limit, also called a *soft cap*, for the work that is running in a logical partition. This defined capacity limit is measured in millions of service units (MSUs) per hour. It allows for short-term spikes in the CPU usage, while managing to an overall, long-term *four-hour rolling average* usage. It applies to all work that is running on general purpose processors in the partition, regardless of the number of individual workloads the partition might contain.

See *PR/SM Planning Guide* for more information about how to set a defined capacity limit.

You can also request absolute MSU capping, with the AbsMSUcapping parameter in the IEAOPTxx member of parmlib. For more information, refer to [“Absolute MSU capping”](#) on page 25.

WLM caps a partition's CPU usage only when the four-hour average reaches the defined capacity limit. Before that point, you might see CPU usage spikes over the limit. You might see the four-hour average go over the limit after capping, until the passage of time gradually brings the average back down to the limit.

WLM allows the CPU usage to remain at the defined capacity limit. Therefore, the four-hour average can continue to go up. In this example, this occurs because the low usage numbers of the four-hour default time interval at IPL are falling off the back end of the four-hour horizon, and being replaced by the new usage numbers, starting at IPL (09:00). This is a consequence of managing to the four-hour average.

This partition has a 50-MSU defined capacity limit, as shown by the gray dashed line. The solid black line is the actual MSU consumption of the partition, and the dashed black line is the four-hour rolling average usage. At IPL (09:00), the partition's CPU usage starts with more than 100 MSUs. However, the four-hour average is below the defined capacity limit at that point, because WLM is using the default four-hour interval time containing no partition CPU usage. No action is taken. Just before 11:00, the four-hour average reaches the defined capacity limit. Now WLM caps the partition's CPU usage at 50 MSUs.




Figure 11. Workload management enforcing a defined capacity limit

Consider the example shown in [Figure 11](#) on page 24:

At IPL, WLM defaults to a four-hour time interval that contains no partition CPU usage. This means the four-hour rolling average starts with zero.

WLM enforces the defined capacity limit by tracking the partition's CPU usage and continually averaging it over the past 4 hours. Spikes higher than the defined capacity limit are possible, as long as they are offset by low points that keep the four-hour average at or below the limit. When this four-hour average goes over

the defined capacity limit, then WLM caps the partition. At that point, it can use no more than the defined capacity limit until the average drops below the limit.

Absolute MSU capping

With absolute MSU capping, WLM always applies a cap to the partition to limit its consumption to the effective limit, independent of the four-hour rolling average consumption. Therefore, absolute MSU capping is an effective means to permanently limit the consumption of an LPAR to a specific MSU figure, including when the four-hour rolling average does not exceed the defined limit.

Similarly, when absolute MSU capping is used with an LPAR capacity group, the limit on behalf of the group entitlement is always enforced, regardless of the four-hour rolling average consumption for the group. With or without absolute capping, an LPAR can benefit from the unused group capacity, unless the LPAR is also capped through other LPAR limits. Since WLM forecasts CPU consumption of group members based on the previous interval, it could take a couple of minutes until the limit is enforced when workload of group members changes significantly.

Absolute MSU capping affects how WLM enforces the LPAR-defined capacity limit or group capacity limit that is specified at the Support Element (SE) or HMC. WLM absolute MSU capping is unrelated to PR/SM LPAR and LPAR group absolute capping.

You request absolute MSU capping on a system basis by specifying `AbsMSUcapping=YES` in the `IEAOPTxx` member of `parmlib`.

All members of a capacity group that use `AbsMSUcapping=YES` permanently enforce the limit on behalf of the capacity group. The members of a capacity group that use `AbsMSUcapping=NO` (the default) are capped while the four-hour rolling average consumption for the group is greater than or equal to the group limit.

A capacity group with all members using `AbsMSUcapping=YES` ensures that the MSU limit of the group is not exceeded, while allowing for redistribution of the capacity within the group.

Defining the capacity of a partition

WLM instructs the PR/SM hypervisor to cap the partition, as described in the previous example, in 1 of 3 possible ways that depend on the ratio of the defined capacity limit and the weight of the partition. The weight that is defined for a partition determines the capacity share of the partition within the shared processor capacity. The following cap mechanisms are used when the four-hour rolling average exceeds the defined capacity limit:

- **Option 1:** If the capacity share exactly equals the defined capacity limit, WLM instructs PR/SM to fully cap the partition at its weight.
- **Option 2:** If the capacity share is less than the defined capacity limit it is not possible to permanently cap the partition at its weight because the partition would not be able to use the capacity it is entitled to. WLM defines a cap pattern which caps the partition at its weight for some amount of time over an interval and then removes the cap during the remaining time of the interval. On average this appears as if the partition was constantly capped at its defined capacity limit. The cap pattern depends on the ratio of the capacity share to the defined capacity limit. If the capacity share based on the weight is rather small compared to the defined capacity limit the partition will be capped very drastically during short periods of time. Therefore, for configurations requiring the capacity share to be smaller than the defined capacity limit, it is recommended to keep both definitions as close as possible.
- **Option 3:** If the capacity based on the weight is greater than the defined capacity limit, WLM instructs PR/SM hypervisor to define a phantom weight, because it is not possible for WLM to cap the partition at its capacity based on the weight. A phantom weight pretends a utilization of the CPC for a particular partition which makes it possible to cap the partition to be managed at the defined capacity limit.

Options 1 and 3 are the recommended ways of specifying defined capacity limits and weights because they provide a capping behavior that is smooth.

zEC12 (GA2) and later systems support the use of negative phantom weights in Option 3. For systems running on eligible hardware with the required software support (z/OS V2R1), option 2 is obsolete and

option 3 is used. Therefore the smoother type of capping is always used regardless of the ration of the capacity share to the defined capacity limit.

Soft capping can influence the HiperDispatch configuration of a partition. While a partition is being capped according to a positive phantom weight (option 3), the priority of the partition is effectively reduced and the number of logical processors with high or medium share might be reduced.

Defining group capacity

Group capacity limit is an extension of the defined capacity limit. It allows an installation to define a “soft cap” for multiple logical partitions of the same CPC (all running z/OS V1R8 or later). The group limit is a defined capacity (soft cap) for all partitions defined in the group. The capacity group is defined on the Hardware Management Console (HMC). Each capacity group has a name and a defined capacity which becomes effective to all partitions in the group.

See *PR/SM Planning Guide* for more information about how to define a capacity group.

WLM uses the weight definitions of the partitions and their actual demand to decide how much capacity may be consumed by each partition in the group. In the following example a capacity group is defined which consists of three partitions MVS1, MVS2 and MVS3. The group limit is defined to 50 MSU and the weights of the partitions are shown in [Table 2 on page 26](#):

Table 2. Example of definitions for MVS1, MVS2, and MVS3 partitions

Partition	Weight	Share (MSU)
MVS1	100	16,7
MVS2	50	8,3
MVS3	150	25


zEC12 (GA2) and later systems support the use of the initial weight for sharing the group limit. If all partitions of the capacity group are running on this hardware and if all of them also have the required software support installed (z/OS V2R1, z/OS V1R12/13 with OA41125), the initial weight will be used instead of the current weight to calculate the share of the partitions.

The total weight of all partitions in the group is 300. Based on the weight definitions, each partition gets an entitled share of the group capacity of 50 MSU. The entitled share is important to decide how much MSU can be used by each partition if the 4-hour rolling average of the group exceeds the group capacity limit. The share is also shown in [Table 2 on page 26](#).

[Figure 12 on page 27](#) shows an example how the partitions use their entitled capacity. At 07:00 p.m. all three partitions are started. In the beginning, only partition MVS1 and MVS2 use approximately 60 MSU. No work is running on partition MVS3. Therefore its measured consumption is very small. WLM starts to cap the partitions when the 4-hour rolling average for the combined usage exceeds the 50 MSU limit. This happens around 09:00 p.m. At that point, MVS1 is reduced to about 30 MSU and MVS2 to about 20 MSU. MVS3 still does not demand much CPU. Therefore the available MSU of the group can be consumed by MVS1 and MVS2.

Around 11:00 p.m. work is started on MVS3. A small spike can be observed when WLM recognizes that the third partition starts to demand its share of the group. After that spike MVS3 gets up to 25 MSU of the group because its weight is half of the group weight. MVS1 is reduced to 16.7 MSU and MVS2 to 8.3 MSU. Based on variation in the workload the actual consumption of the partitions can vary but the group limit of 50 MSU is always met on average.

The work on MVS3 stops around 04:00 p.m. At that point, a small negative spike can be observed and afterwards the capacity is consumed again only by the partitions MVS1 and MVS2.



© 2005 IBM Corporation

1

ON DEMAND BUSINESS™ = Make it happen now

Figure 12. Example of workload consumption for partitions MVS1, MVS2, and MVS3

Group capacity can be combined with all other existing management capabilities of z/OS workload management:

- Group capacity can be combined with an individually defined capacity for a partition. The partition will always honor the individually defined capacity.
- It is possible to define multiple capacity groups on a CPC. A partition can only belong to one capacity group at a given point in time.

Note that WLM only manages partitions which comply with the following rules within a group:

- The partitions must not be defined with dedicated processors.
- The partitions must run with shared CPs and wait completion must be No.
- The operating system must be z/OS V1R8, or higher.
- A hardware cap (that is, **Initial Capping** checked on the Change Logical Partitions Controls panel) which limits the partition to its weight is not allowed for a partition being managed in a capacity group.

All partitions which do not conform to these rules are not considered part of the group. WLM will dynamically remove such partitions from the group and manage the remaining partitions towards the group limit.

Group capacity functions together with IRD weight management.

Group capacity does not work when z/OS is running as a z/VM® guest system.

Workload management with other products

For subsystem work managers, if you do not have the product or product release supporting workload management, you can define goals only for the subsystem regions. Since subsystem regions are treated as batch jobs or started tasks, a velocity goal is most appropriate. All started tasks are managed on the system where they are started.

For example, if you have a CICS release that is not at least at the CICS/ESA 4.1 level, you could define velocity goals for the TORS and AORS. You could not manage CICS transactions to response time goals.

For reporting or monitoring products, you should check whether they support workload management. Vendor information should explain whether or not they report on the workload management activity.

Chapter 4. Setting up a service definition

This information describes how to set up a service definition based on your performance objectives. A service definition contains all of the information necessary for workload management processing. Based on this information, you should be able to set up a preliminary service definition using the worksheets provided. Then, you can enter your service definition into the ISPF administrative application with ease.

The service definition is the way to express your installation's business goals to your sysplex. In order to do this, you must understand your installation's business environment from the following areas:

- What are your installation's revenue-earning workloads?
- Is there a business priority to the workloads?
- Do you understand what kind of service users expect and the timeframe they expect it in?
- Do you understand the service you can deliver?

Even if your installation does not currently have an SLA, or other written performance objectives, users most often have service expectations.

- How can you use monitoring and performance products to gather information?

Specifying a service definition

You define a minimum of one policy in a service definition. A service definition contains workloads, service classes, and classification rules. Optionally, it contains resource groups, report classes, application environments and scheduling environments as well as tenant resource groups and tenant report classes. A service definition also includes one or more policies. A policy is a set of overrides to the goals and resource group limits in the service definition. In a service definition, you also specify whether you want workload management to manage I/O priorities based on your service class goals. A service definition has an identifying name and description.

There is one notepad available for the service definition. You can update the notepad whenever you are creating or modifying any of the other parts of a service definition, such as the policy, workload, service class, resource group, and classification rules. All of the information in a service definition is available to reporting products, except for the notepad information and the classification rules. The notepad information is provided for a history log, and change management.

Name

Service definition name

Description

Description of the service definition

Name

(Required) An eight-character identifier of the service definition.

Description

(Optional) An area of 32 characters to describe the service definition. For example, you could include the time period this service definition is intended to cover.

Storing service definitions

You can work in the ISPF administrative application with one service definition at a time. In order to make the service definition accessible to all systems in the sysplex, you store the service definition on a WLM couple data set. Only one service definition can be installed on the WLM couple data set at a time.

If you want to work on more than one service definition at a time, you can keep each in a distinct MVS partitioned data set (PDS), or in an MVS sequential data set (PS). As an MVS service definition data set, the service definition is subject to all the same functions as an MVS data set. You can restrict access to the service definition data set, send it, and copy it, as you can any MVS data set.

The service definition must be installed on a WLM couple data set, and a service policy activated. Only service policies in the service definition installed on the WLM couple data set can be activated. A WLM couple data set can have automatic backup. For more information about allocating and using a WLM couple data set, see [Chapter 17, “Workload management migration,” on page 131](#).

Defining the parts of a service definition

This information explains how to set up a service definition by defining each of its parts: policies, workloads, resource groups, application environments, service classes, classification rules, and report classes. When you set up your service definition, you should define its parts in the following order:

1. Service policy

See [Chapter 5, “Defining service policies,” on page 31](#).

2. Workloads

See [Chapter 6, “Defining workloads,” on page 35](#).

3. Resource groups and tenant resource groups

See [Chapter 7, “Defining resource groups,” on page 37](#) and [Chapter 8, “Defining tenant resource groups,” on page 45](#).

4. Service classes

See [Chapter 9, “Defining service classes and performance goals,” on page 47](#).

5. Service policy overrides

See [“Using policy overrides” on page 32](#).

6. Classification rules

See [Chapter 10, “Defining classification rules,” on page 57](#).

7. Report classes and tenant report classes

See [Chapter 12, “Defining report classes,” on page 93](#) and [Chapter 11, “Defining tenant report classes,” on page 91](#).

8. Service definition options

See [Chapter 13, “Defining service definition options,” on page 95](#).

9. Application environments

See [Chapter 15, “Defining application environments,” on page 113](#).

10. Scheduling environments

See [Chapter 16, “Defining scheduling environments,” on page 123](#).

Chapter 5. Defining service policies

A *service policy* is a named collection of service class, resource group and tenant resource group specification overrides. When a policy is put into effect, the overrides are merged with the service class, resource group and tenant resource group specifications in the service definition. A policy override is a way to change a goal or (tenant) resource group capacity without having to redefine all of your service classes and (tenant) resource groups.

See [“Summary of service definition and service policy concepts” on page 13](#) for an overview of the relationship between a service definition and a service policy, and [Figure 8 on page 14](#) for a visual overview of how service policy overrides work. Note that in an ideal scenario, you would only have to define your service definition once. As part of that service definition, you would predefine multiple policies to meet varying performance goals or business needs. Once the service definition is installed, you would then activate one policy at a time, and then, when appropriate, switch to another. Note that you *must* define at least one service policy, and you can define up to 99.

When you are creating your service definition, you may choose to define one empty “default” policy with no overrides at all. Next, create your workloads and service classes. Then determine how and when your service classes may have different goals at different times, or when your resource groups or tenant resource groups may have different capacities at different times. Define additional policies with the appropriate overrides for these time periods.

Defining service policies
Name Service policy name
Description Description of the service policy
Policy override Changing a service class goal, resource group or tenant resource group

Name

(Required) Eight characters identifying the service policy. Every service policy name must be unique in a service definition. The service policy is activated by name in one of the following ways:

- An operator command from the operator console.
- A utility function from the workload management ISPF application.

You can display the name of the active service policy with an operator command, or by viewing a performance monitor, such as RMF.

Description

(Optional) An area of 32 characters describing the service policy. The descriptive text is available to performance monitors for reporting.

Policy override

(Optional) A way to change a performance goal, a service class-resource group assignment, or a resource group or tenant resource group capacity for a service policy. For more information about defining policy overrides, see [“Using policy overrides” on page 32](#).

Examples of service policies

- Daytime policy:

```
Name           = DAYTIME
Description = Policy from 9:00 am to 5:00 pm
```

- Policy for national holidays:

```
Name          = HOLIDAY
Description = Policy for Arbor day
```

- Weekend policy:

```
Name          = WEEKEND
Description = Policy for Sat and Sun
```

Using policy overrides

Once you have defined your service classes, you can determine whether any of your service class goals, resource group capacities or tenant resource group capacities change at different times. If they do, you can define a policy override. With an override, you can change one or more of the following for a service policy:

- A goal for a service class period
- Number and duration of periods
- A service class - resource group assignment
- Other properties of the service class like CPU protection
- Resource group attributes
- Tenant resource group attributes

Example 1: Policy overrides

In this example, the service class BATPIG is in the BATCH workload. It is associated with the resource group LIMIT. Suppose the LIMIT resource group is assigned some maximum capacity. BATPIG is assigned a discretionary goal. Since it is a discretionary goal, it does not have an assigned importance. In the Weekend policy, however, both the goal and the resource group association is overridden. The resource group association is overridden, so that in the Weekend policy, BATPIG is not assigned to a resource group. It is instead assigned a response time goal of 1 hour, with an importance of 5.

```
----- Base -----
Policy: Standard          Policy: Weekend
                          (overrides)
Service Class..... BATPIG
Description..... All batch CPU hogs
Workload..... BATCH
Resource Group. LIMIT
-----
Period   Goal.... discretionary   1 hour AVG
 1       Import.. n/a             5
```

Example 2: Policy overrides

In this example, the CICS HIGH service class is in the CICS workload. In the Standard policy, it is assigned a response time goal of 1 second average, with an importance of 1. It is not assigned a resource group, because there is no business need to limit or guarantee capacity. For the weekend policy, however, it has an overridden goal. Because of a contract with CICS users, the agreed response time for weekends is 2 seconds average, with an importance of 2.

```
----- Base -----
Policy: Standard          Policy: Weekend
                          (overrides)
Service Class..... CICS HIGH
Description..... All short CICS transactions
Workload..... CICS
Resource Group. -----
-----
Period   Goal.... 1 sec avg       2 sec avg
 1       Import.. 1              2
```

Example 3: Policy overrides

In this example, the resource group DEPT58 is associated with 3 service classes: 58CICS, 58TSO, and 58BATCH. Since the department is willing to pay for more capacity on the weekends, the minimum is overridden for the weekend policy. It is 1500 CPU service units per second. So in the weekend policy, the service classes 58CICS, 58TSO, and 58 BATCH have a minimum of 1500 CPU service units guaranteed.

```
----- Base -----
Policy: Standard                                Policy: Weekend
                                              (overrides)

Resource Group..... DEPT58
Description..... Contracted capacity for dept. 58

Minimum      1000                                1500
Maximum      -----

Service Class 58CICS__
               58TSO__
               58BATCH_
```


Chapter 6. Defining workloads

A *workload* is a named collection of work to be reported as a unit. You can arrange workloads by subsystem (CICS, IMS), by major application (production, batch, office) or by line of business (ATM, inventory, department). Logically, a workload is a collection of service classes.

Defining workloads
Name Workload name
Description Description of workload

Name
(Required) Eight characters identifying the workload. Every workload name must be unique for all defined workloads in a service definition.

Description
(Optional) An area of 32 characters describing the workload. The descriptive text is available to performance monitors for reporting.

Defining a departmental workload

In order to set up a departmental workload that crosses subsystem boundaries, you must keep in mind how you can assign the work to service classes. You should review [Chapter 10, “Defining classification rules,” on page 57](#) and find out the best way you can assign your work to service classes. The following list provides some examples of what would be required for some of the subsystems:

TSO
You must set up TSO user IDs or account numbers according to department structure, so that the user IDs correspond to a specific department.

JES
You must have unique batch classes or account numbers by department.

CICS
You must have unique CICS regions for each department.

IMS
You must have a separate IMS/VS resource lock manager (IRLM), IMS control region, and IMS message processing region (MPR) for each workload.

For more information, see [Chapter 10, “Defining classification rules,” on page 57](#).

Examples of workloads

- By subsystem:

Name
IMS

Description
All work in classes IMS1 IMSA IMSS TIMS IMSV

- By department/location:

Name
DEVELOP

Description
All work in classes STSO IMSB and LINKA

Chapter 7. Defining resource groups

A *resource group* is an amount of processor capacity and/or memory. It is optional. Unless you have some special need to limit or protect processor capacity or memory for a group of work, you should skip defining resource groups and let workload management manage all of the processor and memory resource to meet performance goals. You use a resource group to:

- Limit the amount of processor capacity available to one or more service classes.
- Set a minimum for processor capacity for one or more service classes if the work is not achieving its goals.
- Define a minimum and maximum amount of processor capacity sysplex-wide, or on a system level.
- Specify whether capacity values of the resource groups apply to general purpose processors only or to general purpose and specialty processors.
- Limit the amount of memory capacity that is available to one or more service classes on a system level.

You can specify a minimum and maximum amount of processor capacity and a maximum amount of memory to a resource group. You can assign only one resource group to a service class. You can assign multiple service classes to the same resource group. You can define up to 32 resource groups per service definition.

Keep in mind your service class goals when you assign a service class to a resource group. Given the combination of the goals, the importance level, and the resource capacity, some goals might not be achievable when capacity is restricted.

Setting a maximum processing capacity

If work in a resource group is consuming more processor resources than the specified maximum processor capacity, the system caps the associated work accordingly to slow down the rate of processor resource consumption. The system might use several mechanisms to slow down the rate of processor resource consumption, including swapping the address spaces, changing their dispatching priority, and capping the amount of processor service that can be consumed. Reporting information reflects that the service class might not be achieving its goals because of the resource group capping.

Setting a minimum processing capacity

By setting a minimum processing capacity, you create an overriding mechanism to circumvent the normal rules of importance. If the work in a resource group is not meeting its goals, then workload management attempts to provide the defined minimum amount of CPU resource to that work.

Setting a memory limit

By specifying a memory limit, you explicitly restrict the use of real memory of work that runs in address spaces that are associated with the resource group through classification. For a resource group with a memory limit, the system creates a memory pool. A memory pool does not reserve real memory for use by the pool, but rather tracks the aggregate usage in order to limit the total usage by address spaces connected to the pool.

An address space that is associated with the resource group through classification connects to the memory pool when the address space, or a new job, starts. In that case, all its frames are counted toward the pool limit. When a memory pool approaches its limit, the system takes actions such as initiating self-stealing to page out memory pool pages and thus free up memory pool frames. This protects the real memory allocation of other work that is running on the system.

An address space can be switched to another memory pool or back to system storage either by activating another service policy, or resetting it to another service class.

IBM recommends that you use memory pools only when it is required to limit the use of memory by workloads and for applications which provide guidance on how to operate them in a memory pool.

When you install and activate a service definition that deletes an existing resource group with a memory limit, the system defers deletion of the associated memory pool until all address spaces associated with the memory pool disconnect and end.

When a memory pool approaches its limit, address spaces starting up and connecting to the pool are deferred until enough frames are available through self-stealing from the pool.

Defining resource groups	
Name	Resource Group name
Description	Description of resource group
Resource Group Type	Description of resource group type
Capacity Maximum	Can be calculated in various ways, depending on which resource group is used, and is explained in the following.
Capacity Minimum	Can be calculated in various ways, depending on which resource group is used, and is explained in the following.
Include Specialty Processor Consumption	Specifies whether minimum and maximum capacity applies to the sum of general purpose processors and specialty processor consumption.
Memory Limit	Maximum amount of real memory the address spaces that are associated with the resource group through classification may use on the local system. The value has a system scope.

Name

Eight characters that identify the name of the resource group. Each resource group must be unique within a service definition.

Description

Up to 32 characters that describe the resource group.

Resource Group Type

Resource groups allow to define a guaranteed maximum and minimum CPU consumption for work on the sysplex and on each individual member of the sysplex. This allows to:

- Prioritize work on a system-level basis.
- Control the minimum and maximum resource consumption.

The following types of resource groups are valid:

Resource Group Type 1

The capacity is specified in unweighted CPU service units per second, the value must be between 0 and 99999999.

Minimum and maximum capacity applies sysplex-wide, that is, WLM ensures that the limits are met within the sysplex.

The table in [Appendix B, “CPU capacity table,”](#) on [page 225](#) shows the service units per second by CPU model.

Resource Group Type 2

The capacity is specified as a percentage of the LPAR share in the general purpose processor pool, the value must be between 0 and 99999. To accommodate specialty processor capacity, values greater than 100 may be specified.

Minimum and maximum capacity has a system scope, that is, WLM ensures that the limits are met on each system within the sysplex. Refer to [“Calculating an LPAR share — Example 1” on page 40](#) for a scenario showing how to calculate an LPAR share when using resource group type 2.

Resource Group Type 3

The capacity is specified as a number of general purpose processors (CPs), a number of 100 represents the capacity of 1 CP. The number should be between 0 and 999999. To accommodate specialty processors that run at a different speed, a number greater than 100 must be specified to represent the capacity of one specialty processor. Refer to [“Specifying the capacity as a number of CPs — Example 2” on page 42](#) for a scenario showing how to calculate a number of CPs when using resource group type 3.

Minimum and maximum capacity has a system scope, that is WLM ensures that the limits are met on each system within the sysplex.

Resource Group Type 4

The capacity is specified in accounted workload MSU that is based on captured time. Minimum and maximum capacity is processor consumption that is expressed in million service units per hour and applies sysplex-wide, that is, WLM ensures that the limits are met within the sysplex. Minimum and maximum must be a value between 0 and 999999.

Resource group type 4 is intended to simplify the specification of a limit expressed in MSU. This limit only applies to captured TCB and SRB times. System management time, also known as uncaptured time, is not included. Furthermore, this limit is managed on a short interval. Thus, it is no four-hour rolling average MSU consumption.

The Appendix B, “CPU capacity table,” on page 225 shows the service units per second by CPU model. Also, refer to *Large Systems Performance Reference for IBM Z* to determine the MSU rating of your sysplex.

Capacity

Identifies the amount of available capacity you want workload management to allocate to the resource group. Capacity includes cycles in both TCB and SRB mode. The table in Appendix B, “CPU capacity table,” on page 225 shows the service units per second by CPU model. Resource group minimum can equal resource group maximum.

Maximum

CPU service that this resource group might use. *Maximum* specified for this resource group applies to all service classes in that resource group combined. *Maximum* is enforced. There is no default maximum value. If specified, *Maximum* must be greater than 0.

Minimum

CPU service that should be available for this resource group when work in the group is missing its goals. The default is 0. If a resource group is not meeting its minimum capacity and work in that resource group is missing its goal, workload management attempts to give CPU resource to that work, even if the action causes more important work (outside the resource group) to miss its goal. If there is discretionary work in a resource group that is not meeting its minimum capacity, WLM attempts to give the discretionary work more CPU resource if that action does not cause other work to miss its goal.

The minimum capacity setting has no effect when work in a resource group is meeting its goals.

Memory Limit

Maximum amount of memory that address spaces that are associated with the resource group through classification might consume on the local system. The attribute is specified as absolute value in GB. The attribute value has system scope.

Include Specialty Processor Consumption

The attribute specifies whether capacity minimum and maximum apply not only to general purpose processors but also to specialty processors. The default is **no**, which ignores CPU consumption of specialty processors when managing the guaranteed minimum and maximum capacity. If **yes** is specified, the total CPU consumption on general purpose and specialty processors is applied.

Note:

1. You cannot assign a resource group to service classes representing transaction-oriented work, such as CICS or IMS transactions. The ISPF application notifies you with an error message if you attempt to do so. If you want to assign a minimum or a maximum processor capacity and a maximum amount of memory to CICS or IMS work, you can do so by assigning a resource group to their regions. For example, suppose that you have three service classes representing your CICS works: CICSTRN, CICSAORS, and CICSTORS. CICSTRN represents all of your online CICS transactions, and has one period with a short response time goal. CICSAORS and CICSTORS represent all of your CICS AOR and TOR regions, respectively, that process the online transactions. To assign a maximum processor capacity and a maximum amount of memory to your CICSTRN work, define a resource group, and assign it to the regions. So you assign the resource group to the CICSAORS and CICSTORS service classes.
2. Similarly, resource groups with a memory limit cannot be applied to enclave service classes. However, because enclave service classes can be used anywhere, unlike CICS or IMS transaction service classes, the ISPF application does not notify you with an error message if you attempt to do so. As for CICS or IMS, a resource group with a memory limit must be assigned to the service class of the address spaces that join the enclaves.
3. A memory limit overrules the storage critical attribute assigned in classification rules and also any protective storage target managed through SRM.
4. Resource group processor capacity capping is implemented by marking the work units that belong to resource group non-dispatchable for some time slices and dispatchable for the remaining time slices (awake slices). Depending on the configuration, it might not be possible to enforce very low resource group limits. The granularity to which a resource group limit can be managed depends on how much service the work can consume in a system or across the Sysplex, respectively, during one awake time slice. Beginning with z/OS V2.1 the granularity of awake slices is 1/256 of the time.
5. When resource groups are managed based on the general purpose processor service (the attribute, Include Specialty Processor Consumption, specifies no) the dispatchability attribute is also honored by zIIPs.
6. Resource group capping will not be enforced while system recovery boost is active in a partition.

Calculating an LPAR share — Example 1

The following example illustrates how the capping works for a resource group type 2 and how to calculate this. For this resource group the minimum and maximum capacity is defined as a percentage of the share for the logical partition:

LPAR share

The LPAR share is defined as the percentage of the weight definition for the logical partition to the sum of all weights for all active partitions on the CEC.

In this example a resource group type 2 ELPMAX is defined to cap CPU-intensive work on the systems in the sysplex environment. The aim is to limit the consumption of the work to 60% of the LPAR share. The sysplex consists of 2 systems: WLM1 and WLM2 which share the CEC with other VM and MVS systems:

Table 3. Example: LPAR configuration				
Partition	Current weight	Share	Logical processors	Sysplex
WLM1	78	7,8%	2	WLMPLEX

Table 3. Example: LPAR configuration (continued)				
Partition	Current weight	Share	Logical processors	Sysplex
WLM2	132	13.2%	2	WLMPLEX
VMA	590	59.0%	6	n/a
MVSA	200	20.0%	4	n/a

The CEC is a zSeries 990, Model 306. For the value service units per second (SU/s) of 18626.3, refer to Appendix B, “CPU capacity table,” on page 225. With 6 processors the total SU/s is 111758. This value is called CEC-capacity. Based on the CEC-capacity value, it is possible to calculate the LPAR share capacity, which is the CEC-capacity multiplied with the LPAR share of each system in the sysplex. For system WLM1 the LPAR share is 7.8%. The LPAR share capacity for WLM1 results to 8717 SU/s. For ELPMAX a maximum limit of 60% is defined. On WLM1 this results to 5230 SU/s.

Table 4. Example: ELPMAX in sysplex WLMPLEX					
CEC-Capacity for zSeries 990, Model 306 => 18626.3 SU/s * 6 = 111758 SU/s					
Partition	LPAR share	Share capacity (SU/s)	RG limit: 60%	Logical processors (LCPs)	SU/s based on LCPs
WLM1	7.8%	8717	5230 SU/s	2	37252.6
WLM2	13.2%	14752	8851 SU/s	2	37252.6

Note that ELPMAX is still defined sysplex-wide but the capacity definition depends on the logical and physical configuration of the systems. On WLM1 work in ELPMAX is entitled to consume 5230 SU/s and on WLM2 to 8851 SU/s. Furthermore, the following two factors are also important for the entitled capacity:

- The SU/s based on the logical processor configuration of the LPAR. If this SU/s for the logical processor configuration is smaller than the share of the logical partition, we will calculate the entitlement for ELPMAX based on the logical processor configuration. In our example there are 2 logical processors defined per partition. This results to 37252.6 SU/s and this value is bigger than the SU/s based on the LPAR share.
- If there is a defined capacity and the partition is capped to that defined capacity, the entitlement for ELPMAX is based on that defined capacity. In the current example it is assumed that there is no defined capacity.

Figure 13 on page 42 shows how work is capped in resource group ELPMAX on system WLM1. For this reason we associate a service class with ELPMAX and submit work which consumes a lot of CPU service:




Figure 13. Example: Resource group overview

It can be observed that the system needs a short period to apply the correct number of capping slices for the work units associated with the resource group. After this ramp up period, the resource group is capped slightly below the entitled capacity. The reason for that is, that the work is being capped by slices which depend on the capacity of the partition. Therefore, the capacity used can never match the entitlement exactly.

The following shows the complete calculations for applying and interpreting the results of a resource group type 2:

$$RG_{[SUs]} = \begin{cases} \text{Softcap}_{[SUs]} \bullet RG_{\text{Limit}[\%]} & \text{if softcap} < \text{ShareCapacity or LCPCapacity} \\ \text{LCPCapacity}_{[SUs]} \bullet RG_{\text{Limit}[\%]} & \text{if LCPCapacity} < \text{ShareCapacity or softcap} \\ \text{ShareCapacity}_{[SUs]} \bullet RG_{\text{Limit}[\%]} & \text{if ShareCapacity} < \text{LCPCapacity or softcap} \end{cases}$$

$$\text{ShareCapacity}_{[SUs]} = \text{CECCapacity}_{[SUs]} \bullet \text{LPARShare}$$

CECCapacity_[SUs] = Capacity based on shared physical processors for the CEC

$$\text{LPARShare} = \frac{\text{Weight}(\text{Current Partition})}{\sum_{\text{all active partitions } i} \text{Weight}(i)}$$

$$\text{LCPCapacity}_{[SUs]} = \text{Capacity based on shared processors available on the LPAR}$$

Figure 14. Working With A Resource Type 2 - Sample Calculation

RG[SUs] is the result entitlement for the resource group which depends on the LPAR share, LCP capacity and whether there is a defined capacity which is active.

Specifying the capacity as a number of CPs — Example 2

For resource group type 3, the capacity is defined as a number of general purpose processors (CPs). The following example illustrates how the capping works for a resource group type 3 and how to calculate this. This means, finding out to how many service units per second (SU/s) the defined capacity corresponds.

The CEC is a zSeries 990, Model 316. The WLM service definition specifies a resource group RGT3 (= type 3) with a maximum/minimum value of 250. For resource group type 3 a number of 100 represents the capacity of 1 CP. The LPAR has 6 processors assigned on the hardware console and none of them have been varied offline from the MVS console. To calculate the capping value, do the following:

1. For the correct SU/s value for the resource group, refer to [Appendix B, “CPU capacity table,”](#) on page 225. In the table for z990s, find the row that represents the model with the number of online processors that your LPAR has. In the current example, this is Model 306, because your LPAR has 6 online processors.

Note: The higher number in this row compared to the value for Model 316 accounts for the lower MP factor that your LPAR has because it has only 6 processors.

2. So, the value you pick is 18 626.3.
3. Multiply 18 626.3 by 250/100.
4. The result is: on that system, the maximum capacity for RGT3 is 46 565 SU/s.

The calculation is done individually for each LPAR. If the LPARs in the sysplex have a different number of processors assigned to them - one can still calculate the correct capping value. This means, the same resource group may represent different SU/s on different LPARs.

An advantage of using resource group type 3 is that it dynamically adjusts to the processor capacity when the work is run on another hardware.

Chapter 8. Defining tenant resource groups

Tenant resource groups allow the metering and optional capping of workloads, along with the ability to map those workloads directly to Tailored Fit Pricing for IBM Z solutions. A tenant resource group is comparable to a resource group but accepts and processes an IBM provided 64-character Solution ID. While a resource group is associated with service classes, a tenant resource group is associated with tenant report classes. You must define a tenant resource group before you can define tenant report classes.

When you specify a maximum capacity or memory limit for the tenant resource group, WLM limits the amount of processor capacity or memory available to work, which is classified to the tenant report classes associated with the tenant resource group.

You can define up to 32 tenant resource groups per service definition.

Defining tenant resource groups	
Name	Tenant Resource Group Name
Description	Description of the tenant resource group.
Tenant ID	Tenant identifier.
Tenant Name	Descriptive name for the Tenant ID.
Solution ID	IBM provided 64-character solution ID.
Tenant Resource Group Type	Description of the tenant resource group type. This is the same as the resource group type.
Capacity Maximum	Specifies the maximum amount of processor capacity that work associated with the tenant resource group may use.
Include Specialty Processor Consumption	Specifies whether capacity maximum applies to the sum of general purpose processor consumption and specialty processor consumption.
Memory Limit	Maximum amount of real memory that address spaces associated with the tenant resource group through classification may use on the local system. The value has a system scope.

Name
Eight characters that identify the name of the tenant resource group. Each tenant resource group must be unique within a service definition and may not have the same name as a resource group.

Description
Up to 32 characters that describe the tenant resource group.

Tenant ID
Up to eight characters that identify a tenant.

Tenant Name
Up to 32 characters that provide a descriptive name for the Tenant ID.

Solution ID
The 64 character Solution ID as provided by IBM.

Tenant Resource Group Type

Optionally, a tenant resource group allows for the control of the maximum processor consumption. Refer to [Chapter 7, “Defining resource groups,” on page 37](#) for a detailed description of the different types available.

Maximum Capacity

CPU service that this tenant resource group may use. *Maximum* applies to all tenant report classes associated with the tenant resource group. *Maximum* is enforced. There is no default maximum value. Tenant resource group capping will not be enforced while system recovery boost is active in a partition.

Include Specialty Processor Consumption

The attribute specifies whether capacity maximum applies not only to general purpose processors but also to specialty processors. The default is **no**, which ignores CPU consumption of specialty processors when managing the maximum capacity. If **yes** is specified, the total CPU consumption on general purpose and specialty processors is limited by the Maximum Capacity.

Memory Limit

Maximum amount of real memory that address spaces that are associated with the tenant resource group through classification may use on the local system. The attribute is specified in GB. The attribute value has system scope. Please refer to [Chapter 7, “Defining resource groups,” on page 37](#) for a detailed description for setting a memory limit.

Tenant report classes representing transaction-oriented work, such as CICS or IMS transactions, can only be assigned to tenant resource groups without a maximum capacity defined. If you assign a tenant resource group with a maximum capacity, the WLM ISPF application displays an appropriate warning message. Although the tenant resource group is accepted, the capacity limit is ignored for the CICS and IMS transactions.

Chapter 9. Defining service classes and performance goals

A *service class* is a named group of work within a workload with the following similar performance characteristics:

- Performance goals
- Resource requirements
- Business importance to the installation

Workload management manages a service class period as a single entity when allocating resources to meet performance goals. A service class can be associated with only one workload. You can define up to 100 service classes.

You can assign the following kinds of *performance goals* to service classes: average response time, response time with percentile, velocity, and discretionary. You assign an importance level to the performance goal. Importance indicates how vital it is to the installation that the performance goal be met relative to other goals.

Because some work has variable resource requirements, workload management provides *performance periods* where you specify a series of varying goals and importances. You can define up to eight performance periods for each service class. You can also assign a service class to a resource group if its CPU service must be either protected or limited.

This information explains the parts of a service class, how to define performance goals, and how to use performance periods.

Defining service classes and performance goals	
Name	Service class name
Description	Service class description
Workload	The name of the workload associated with this service class.
Resource Group	The name of the resource group associated with the work in this service class.
Performance Period	One goal per period.
Duration	Number of service units for this performance period. This value is calculated including all processor types.
Average Response Time	Average response time for transactions completing within the period in terms of hours, minutes, and seconds. Decimal points are accepted. Response time varies from 1 millisecond to 24 hours.
Response Time and Percentile	A percentile of work to be completed in the specified amount of time. Percentile boundaries vary from 1 to 99. Amount of time is in hours, minutes, or seconds. Decimal points are accepted. Response time ranges from 1 millisecond millisecond to 24 hours.
Velocity	Measure of how fast work should run when ready, without being delayed for WLM-managed resources. Velocity ranges from 1 to 99.

Defining service classes and performance goals

Discretionary

Workload management defined goal. Work is run as system resources are available.

Importance

How important it is to the installation that the goal be achieved.

CPU Protection

Whether long-term CPU protection should be assigned to this service class.

I/O Priority Group

Whether long-term I/O protection should be assigned to this service class.

Honor Priority

Whether this service class is exempted from the system-wide IFAHONORPRIORITY or IIPHONORPRIORITY processing as specified in parmlib member IEAOPTxx

Name (required)

Eight characters describing the service class. Service class names must be unique within a service definition.

Description (optional)

An area of 32 characters describing the service class. The descriptive text is available to performance monitors for reporting.

Workload (required)

The name of the workload associated with the service class. You can associate only one workload per service class in a service definition. The workload must have been previously defined.

Resource Group (optional)

The resource group name associated with this service class. You can assign only one resource group per service class in a service policy. You can override the resource group assigned to a service class in each service policy. For more information about resource groups, see [Chapter 7, “Defining resource groups,”](#) on page 37.

Performance Period

A performance goal, importance, and *duration* for a service class. You set up multiple performance periods for work that has changing performance requirements as work consumes more and more resources. You can specify up to eight performance periods.

Duration

Specifies the length of the period in service units. For a definition of service units, see [“Calculating the amount of service consumed”](#) on page 49. If the work included in this service class period does not complete when the number of service units have been used, the work moves into the next performance period. You do not specify a duration on the last defined period.

Response Time

The expected amount of time required to complete the work submitted under the service class, in milliseconds, seconds, minutes and hours. Specify either an average response time, or response time with a percentile. Percentile is the percentage of work in that period that should complete within the response time. Percentile must be a whole number. You must specify a system response time goal, not “end-to-end”. That is, workload management does not control all aspects of system performance, so response time scope is confined to the time workload management has control of the work. This time includes the time the work is using or waiting for CPU, storage, or I/O service.

Note: Workload management does not delay work, or limit it, to achieve the response time goal when extra processing capacity exists.

Velocity

A measure of how fast work should run when ready, without being delayed for WLM-managed resources. Velocity is a percentage from 1 to 99. See [“Velocity formula”](#) on page 50 for a description of the calculations needed to determine velocity.

Discretionary

Workload management defined goal. Associate this goal with work for which you do not have a specific performance goal. Work with a discretionary goal is run when excess resources are available.

Importance

The relative importance of the service class goal. Importance is a reflection of how important it is that the service class goal be achieved. Workload management uses importance only when work is not meeting its goal. Importance indicates the order in which work should receive resources when work is not achieving its goal. Importance is required for all goal types except discretionary. Importance applies on a performance period level and you can change importance from period to period. Importance is in five levels: 1 to 5, 1 being the highest importance.

CPU Protection

By specifying YES in the “CPU Critical” field when defining a service class, you ensure that work of lower importance will always have a lower dispatch priority. See [Chapter 14, “Defining special protection options for critical work,” on page 99](#) for more information.

I/O Priority Group

By specifying HIGH in the “I/O Priority Group” field when defining a service class, you ensure that work in this service class will always have a higher I/O priority than work in service classes assigned to I/O priority group NORMAL. See [Chapter 14, “Defining special protection options for critical work,” on page 99](#) for more information.

Honor Priority

By specifying NO in the Honor Priority field, you explicitly prevent the overflow of specialty-engine (IBM z Integrated Information Processor, or zIIP) intensive work to general purpose processors. See [Chapter 14, “Defining special protection options for critical work,” on page 99](#).

The values are:

DEFAULT

Current value of the IIPHONORPRIORITY parameter in the IEAOPTxx member of parmlib is used when there is insufficient capacity on zIIPs for the workload demand in the service class. This is the default.

NO

Independent of the current value of the IIPHONORPRIORITY parameter in the IEAOPTxx member of parmlib, work in this service class is not allowed to overflow to standard processors when there is insufficient capacity on zIIPs for the workload demand in the service class. The only exception is if it is necessary to resolve contention for resources with general purpose processor work.

The Honor Priority option is insignificant for discretionary service classes since work that is classified to these service classes never gets help from general purpose processors.

Calculating the amount of service consumed

The amount of system resources that an address space or enclave consumes is measured in *service units*. Service units are calculated based on the CPU and SRB service that an address space or enclave consumes.

Service units are the basis for period switching within a service class that has multiple periods. The *duration* of a service class period is specified in terms of service units. When an address space or enclave running in the service class period has consumed the amount of service specified by the duration, workload management moves it to the next period. The work is managed to the goal and importance of the new period.

The amount of service consumed by an address space is computed by the following formula:

$$\text{service} = \text{CPU service units} + \text{SRB service units}$$

Figure 15. Formula for calculating service consumption

where:

CPU service units

Task (TCB) execution time, multiplied by an SRM constant which is CPU model dependent. Included in the execution time is the time used by the address space while executing in cross-memory mode (that is, during either secondary addressing mode or a cross-memory call). This execution time is not counted for the address space that is the target of the cross-memory reference.

SRB service units

Service request block (SRB) execution time for both local and global SRBs, multiplied by an SRM constant which is CPU model dependent. Included in the execution time is the time used by the address space while executing in cross-memory mode (that is, during either secondary addressing mode or a cross-memory call). This execution time is not counted for the address space that is the target of the cross-memory reference.

Given the size and processing capacity of processors, it is no longer meaningful to weigh CPU and SRB service differently. Resources such as I/O or MSO (main storage occupancy) are no longer scarce, so it is not necessary to allow them to influence period switching. Thus, starting with z/OS V2R5, service definition coefficients and I/O and storage service units are no longer considered when computing the amount of service consumed. For more information, see [“Migration considerations for service definition coefficients”](#) on page 145.

Velocity formula

The formula for *velocity* is:

$$velocity = using\ samples \div (using\ samples + delay\ samples) \times 100$$

where:

using samples

include:

- The number of samples of work using the processor
- The number of samples of work using non-paging DASD I/O resources (in a state of device connect).¹

The I/O samples are derived from actual time measurements.

delay samples

include:

- The number of samples of work delayed for the processor
- The number of samples of work delayed for storage
- The number of samples of work delayed for non-paging DASD I/O.¹

Work delayed for storage includes:

- Paging
- Swapping
- Multiprogramming level (MPL)
- Server address space creation delays
- Initiation delays for batch jobs in WLM-managed job classes.

MPL is the SRM-controlled function that adjusts the number of address spaces allowed to be in central storage and ready to be dispatched.

I/O delays include:

- IOS queue
- Subchannel pending

¹ If I/O priority management is off, these samples are *not* included.

- Control unit queue delays

The samples for subchannel pending and control unit queue delay are derived from actual time measurements.

Defining performance goals

This section explains how to define performance goals in your service definition. If you have an SLA today, you should consider a few things:

- Does it contain end-to-end response time?

If it does, then you need to keep in mind that workload management processes towards system response times, and make the adjustment when you define the performance goal. Section [“Determining system response time goals” on page 51](#) explains how you can determine the system response times of work.

- For what type of workloads do you need a different goal?

You may have some throughput type goals, which you need to convert into either response time goals, or velocity goals.

Determining system response time goals

Goal mode introduces several changes in the definition of a work request's response time. The changes more accurately reflect end-user expectations of response time.

The number of batch transactions equals number of jobs. Defining a response time goal may not be appropriate for some types of batch work, such as jobs with very long execution times. Work that is appropriate for a response time goal should have at least three transaction completions per 20 minutes of elapsed time. If there are too few completions, use a velocity or discretionary goal.

TYPRUN=HOLD and TYPRUN=JCLHOLD times are *not* included in batch response times.

Examples of service classes with response time goals

- A service class representing TSO/E work with multiple periods.

Service Class

TSO

Period

1

Response Time

85% 0.5 second

Importance

1

Duration

400 Service Units

Period

2

Response Time

80% 1 second

Importance

3

Duration

1000 Service Units

Period

3

Response Time

60% 15 second

Importance

4

Note that the percentile in period 1 and 2 refer to the transactions ending in each period, not the total TSO/E transactions.

- A service class representing CICS transactions.

Service Class

CICSHOT

Period

1

Response Time

0.5 second AVG

Importance

1

- A service class representing IMS transactions.

Service Class

IMSCAT1

Response Time

95% .3 Second

Importance

1

- A service class representing IMS transactions.

Service Class

OIMSCAT3

Response Time

5 sec AVG

Importance

3

Examples of service classes with response time goals

- A service class representing TSO/E work with multiple periods.

Service Class

TSO

Period

1

Response Time

85% 0.5 second

Importance

1

Duration

400 Service Units

Period

2

Response Time

80% 1 second

Importance

3

Duration

1000 Service Units

Period

3

Response Time

60% 15 second

Importance

4

Note that the percentile in period 1 and 2 refer to the transactions ending in each period, not the total TSO/E transactions.

- A service class representing CICS transactions.

Service Class

CICSHOT

Period

1

Response Time

0.5 second AVG

Importance

1

- A service class representing IMS transactions.

Service Class

IMSCAT1

Response Time

95% .3 Second

Importance

1

- A service class representing IMS transactions.

Service Class

OIMSCAT3

Response Time

5 sec AVG

Importance

3

Defining velocity goals

This section describes where to find information to set a velocity goal, and what kind of work is appropriate for velocity goals. Velocity goals define the acceptable amount of delay for work when work is ready to run. Velocity goals are intended for subsystems which use address spaces or enclaves to represent individual work requests. Velocity goals are not supported for work in the IMS and CICS subsystem work environments because velocity data is accounted to the region, not to the individual transaction. Velocity is a goal to consider for long-running jobs.

For a service class with multiple periods, you cannot switch from a velocity goal in one period to a response time goal in a later period. See [“Subsystem support for goal types and multiple periods” on page 16](#) for a list of subsystems for which you can specify multiple periods.

Velocity goals are more sensitive to configuration changes than response time goals and should be monitored and adjusted when required after configuration changes. These configuration changes include:

- Change to the physical configuration, such as a new processor type.
- Changes to the capacity that is available to a system.

- Changes to the logical configuration, such as significant changes to the number of online processors, or implementation of HiperDispatch, or implementation of multi-threading

Adjusting velocity goals based on samples included in velocity calculation

You can adjust your velocity goals based on whether or not the following samples are to be included in the velocity calculation:

- I/O samples (included in the velocity calculation if I/O priority management is turned on)
- Initiation delay samples (included in the velocity calculation if you have WLM-managed batch initiators).

In the RMF Monitor I workload activity report, there are two fields, **I/O PRTY** and **INIT MGMT**, which indicate the following:

I/O PRTY

If you have I/O priority management turned off, then the **I/O PRTY** value shows you what your velocity would be if you were to turn I/O priority management on.

INIT MGMT

If you are not currently using WLM-managed batch initiators, then the **INIT MGMT** value shows you what your velocity would be if you turned over control of all batch initiators in this service class to WLM.

Note: For both the **I/O PRTY** and **INIT MGMT** fields, it is assumed that the *other* setting is unchanged. For example, the **INIT MGMT** field assumes that your current I/O priority management setting remains the same.

These fields may help you to adjust a current velocity goal in anticipation of including these samples.

Using velocity goals for started tasks

Velocity goals are the most appropriate goal for started tasks and long running work. Instead of figuring out a specific velocity goal for your started tasks, you should divide your started tasks into a high, a medium, and a low importance service class, and define a velocity that suffices for each category.

You can also take advantage of the system supplied service classes for started tasks: SYSTEM and SYSSTC. Workload management recognizes special system address spaces (like GRS, SMF, CATALOG, MASTER, RASP, XCFCAS, SMXC, CONSOLE, IOSAS, WLM), puts them into the SYSTEM service class, and treats them accordingly. Address spaces in the SYSSTC service class are kept at a very high dispatching priority.

Note: You can also assign address spaces to the SYSTEM and SYSSTC service classes as part of your work classification rules. See [“System-provided service classes”](#) on page 80.

For information about how to define service classes and associated classification rules for started tasks, see [“Using the system-supplied service classes”](#) on page 88.

Velocity is also appropriate for the “server” started tasks, that is, the address spaces that do work on behalf of a transaction manager or resource manager, such as CICS AOR, or an IMS control region. Since the server address spaces are processing work that also has an assigned performance goal, the velocity goal that you assign to servers applies only during address space startup. Then workload management manages resources to meet the goals defined for the work the servers are processing, and not towards the goals defined for the servers.

If you have a version of a work manager such as CICS and IMS that does not support workload management, you cannot define a goal to the work manager's transactions, but you can define a velocity goal for its server address spaces.

Using discretionary goals

With discretionary goals, workload management decides how best to run this work. Since workload management's prime responsibility is matching resources to work, discretionary goals are used best

for the work for which you do not have a specific performance goal. For a service class with multiple performance periods, you can specify discretionary only as the goal in the last performance period.

Discretionary work is run using any system resources not required to meet the goals of other work. If certain types of other work are overachieving their goals, that work may be “capped” so that the resources may be diverted to run discretionary work. See [“Migration considerations for discretionary goal management”](#) on page 143 for more information on the types of work that are eligible for resource donation, and how you may want to adjust those goals.

Examples of service classes with discretionary goals

- Discretionary goal as last period goal

Service Class

DEVBATCH

Period

1

Response Time

80% 1 minute

Importance

2

Duration

2000 Service Units

Period

2

Response Time

80% 5 minutes

Importance

3

Duration

10000 Service Units

Period

3

Discretionary

- Discretionary goal for leftover work

Service Class

ASDBATCH

Discretionary

Using performance periods

Performance periods are available for work that has variable resource requirements and for which your goals change as the work uses more resources. You specify a goal, an importance, and a duration for a performance period. Duration is the amount of service that period should consume before going on the next goal. Duration is specified in service units. For a definition of service units, see [“Calculating the amount of service consumed”](#) on page 49.

You can define multiple performance periods for work in subsystems which use address spaces or enclaves to represent individual work requests. For a list of subsystems for which you can specify multiple periods, see [“Subsystem support for goal types and multiple periods”](#) on page 16.

Multiple periods are not supported for work in the IMS and CICS subsystem work environments because service units are accumulated to the address space, not the individual transactions. So, the system cannot

track a duration for those transactions. Multiple periods are also not supported for work in the SYSH subsystem.

Defining goals appropriate for performance periods

As you go from one performance period to the next, you can change the type of goal. Goals should become less stringent going from one period to the next. A prime example would be changing to a velocity or discretionary type goal in the last period.

Using importance levels in performance periods

Importance levels should stay the same or decrease as the transactions move from one performance period to the next. Remember that importance applies only if a goal is not being met during the duration of the period.

Examples of multiple performance period goals

- Decreasing stringency of goal and decreasing importance from one period to the next

```
Service Class = BATCHX
Period 1
  Velocity      = 50
  Importance    = 3
  Duration      = 2500 SU
Period 2
  Velocity      = 15
  Importance    = 5
```

Chapter 10. Defining classification rules

Classification rules are the rules you define to categorize work into service classes or tenant report classes, and optionally report classes, based on *work qualifiers*. A work qualifier is what identifies a work request to the system. The first qualifier is the subsystem type that receives the work request.

There is one set of classification rules in the service definition for a sysplex. They are the same regardless of what service policy is in effect; a policy cannot override classification rules. You should define classification rules after you have defined service classes, and ensure that every service class has a corresponding rule.

The full list of work qualifiers and their abbreviations is:

AI

Accounting information

CAI

Client accounting information

CI

Correlation information

CIP

Client IP address

CN

Collection name

CT

Connection type

CTN

Client transaction name

CUI

Client userid

CWN

Client workstation name

ESC

zEnterprise service class name from a Unified Resource Manager performance policy

LU

Logical Unit name

NET

Netid

PC

Process name

PF

Perform

PK

Package name

PN

Plan name

PR

Procedure name

PRI

Priority

PX

Sysplex name This is the same as cluster name for the SYSH subsystem.

SE

Scheduling environment name

SI

Subsystem instance

SPM

Subsystem parameter

SSC

Subsystem collection name

SY

System name

TC

Transaction class/job class

TN

Transaction name/job name

UI

Userid

Note:

1. Not all work qualifiers are valid for every subsystem type; they are subsystem dependent. For details about which qualifiers are valid for which subsystems, see [Table 7 on page 63](#).
2. For many of the qualifiers, you can specify *classification groups* by adding a G to the type abbreviation. For example, a transaction name group would be **TNG**. See [“Using groups” on page 86](#) for more information.

A singular classification rule consists of a work qualifier and an associated service class, report class or tenant report classes. You can also have multiple classification rules.

Example of a classification rule

```
Subsystem Type . : IMS          Fold qualifier names?   Y  (Y or N)
Description . . . IMS medium interactive
-----Qualifier-----
Action   Type      Name      Start      DEFAULTS:  IMSMED      Service      Report
----- 1 -----
-----  -----
```

Note: The **Fold qualifier names** option, set to the default Y, means that the qualifier names will be folded to uppercase as soon as you type them and press Enter. If you set this option to N, the qualifier names will remain in the same case as they are typed. Leave this option set to Y unless you know that you need mixed-case qualifier names in your classification rules.

This example shows that all work coming into any IMS subsystem is associated with service class IMSMED. Service class IMSMED is the default service class for the IMS subsystem type. You can also assign a default report class or a default tenant report class to a subsystem type.

Since you might not want all work coming into a subsystem assigned to the same service class, or the same report class or tenant report class, you can specify multiple classification rules.

[Figure 16 on page 59](#) shows two classification rules. In the example, the incoming work request has work qualifiers of subsystem type, job name, job class, accounting information, and user ID.




Figure 16. Using classification rules to assign work to service classes

In the example, the service administrator set up classification rules to assign all work coming into JES into service class BATCHA, unless the work has a user ID of BOND, in which case, it should be assigned to service class BATCHB. For JES classification, you do not need to specify JES2 or JES3.

Example of multiple classification rules

If you want all CICS work to go into service class CICSB except the following:

- You want work originating from LU name LONDON to run in service class CICSD
- You want work originating from LU name PARIS to run in service class CICSA, unless:
- The work is from the PAYROLL application, in which case you want it to go into service class CICSC.

You could specify the following classification rules:

```
Subsystem Type . . . . . CICS

-----Qualifier-----
Type      Name
1  LU      LONDON
1  LU      PARIS
2    TN      PAYROLL

-----Class-----
Service    Report
DEFAULT:  CICSB
          CICSD
          CICSA
          CICSC
```

This example has two classification rules with level 1 qualifiers: LU name LONDON and LU name PARIS. Under PARIS, there is a level 2 qualifier with transaction name PAYROLL. The PAYROLL qualifier applies only to transactions associated with the level 1 qualifier of PARIS.

In this example, if a work request comes in from an LU name other than LONDON or PARIS, it is assigned to the CICSB service class. If another work request comes in from Paris and is from the payroll application, it is assigned to the CICSC service class. If a work request is from the payroll application but came in from a system in London, then it is assigned to the CICSD service class.

The order of the nesting and the order of the level 1 qualifiers determine the hierarchy of the classification rules. The application supports eight characters for each rule. For more information about defining the hierarchy of the classification rules, see [“Defining the order of classification rules”](#) on page 78.

Defining classification rules for each subsystem

Work qualifiers depend on the subsystem that first receives the work request. When you are defining the rules, start with the service classes you have defined, and look at the type of work they represent. Determine which subsystem type or types process the work in each service class. Then understand which work qualifiers your installation could use for setting up the rules. It may be that your installation follows certain naming conventions for the qualifiers for accounting purposes. These naming conventions could help you to filter work into service classes. Also, understand which work qualifiers are available for each subsystem type. You can then decide which qualifiers you can use for each service class.

The following table shows the IBM-supplied subsystem types that workload management supports, the kind of work they run, whether they use address space-oriented transactions or enclaves (see special note for CICS and IMS), and where to go for more information. (Unless otherwise noted, look for “Workload Manager” in each book.) A comparison of the various transaction types is shown in [Table 6](#) on [page 62](#).

Note: Enclaves are transactions that can span multiple dispatchable units in one or more address spaces. See *z/OS MVS Programming: Workload Management Services* for more information on enclaves.

Table 5. IBM-defined subsystem types			
Subsystem type	Work description	Enclave, address space, or LPAR	For more information, see...
ASCH	The work requests include all APPC transaction programs scheduled by the IBM-supplied APPC/MVS transaction scheduler.	Address Space	<ul style="list-style-type: none"> • z/OS MVS Planning: APPC/MVS Management
CB	The work requests include all WebSphere Application Server client object method requests.	Enclave	<ul style="list-style-type: none"> • The online information included with the WebSphere Application Server system management user interface
CICS	The work requests include all transactions processed by CICS Version 4, and higher.	See note.	<ul style="list-style-type: none"> • CICS Performance Guide • CICS Dynamic Transaction Routing in a CICSplex
DB2	The work requests include only the queries that DB2 has created by splitting a single, larger query and distributed to remote systems in a sysplex. The local piece of a split query, and any other DB2 work, is classified according to the subsystem type of the originator of the request (for example, DDF, TSO, or JES).	Enclave	<ul style="list-style-type: none"> • DB2 Data Sharing: Planning and Administration
DDF	The work requests include all DB2 distributed data facility (DB2 Version 4 and higher) work requests.	Enclave	<ul style="list-style-type: none"> • DB2 Data Sharing: Planning and Administration
EWLM	Work requests include DB2 distributed data facility (DDF) requests that originate from an ensemble, through virtual servers that are classified within a Unified Resource Manager performance policy.	Enclave	
IMS	The work requests include all messages processed by IMS Version 5 and higher.	See note.	<ul style="list-style-type: none"> • IMS Administration Guide: System
IWEB	The work requests include all requests from the world-wide-web being serviced by the Internet Connection Server (ICS), Domino Go Webserver, or IBM HTTP Server Powered by Domino (IHS powered by Domino). These requests also include those handled by the Secure Sockets Layer (SSL). This also includes transactions handled by the Fast Response Cache Accelerator.	Enclave	
JES	The work requests include all jobs that JES2 or JES3 initiates.	Address Space	<ul style="list-style-type: none"> • z/OS JES2 Initialization and Tuning Guide • z/OS JES3 Initialization and Tuning Guide
LDAP	The work requests include all work processed by the z/OS LDAP server	Enclave	<ul style="list-style-type: none"> • z/OS IBM Tivoli Directory Server Administration and Use for z/OS
LSFM	The work requests include all work from LAN Server for MVS.	Enclave	
MQ	The work requests include IBM MQ Workflow work such as new client server requests, activity executions, activity responses, and subprocess requests.	Enclave	

Table 5. IBM-defined subsystem types (continued)

Subsystem type	Work description	Enclave, address space, or LPAR	For more information, see...
NETV	The work requests include NetView® network management subtasks and system automation (SA) subtasks created by Tivoli® NetView for z/OS.	Enclave	<ul style="list-style-type: none"> • <i>The Tivoli NetView for z/OS Tuning Guide</i> • <i>Tivoli NetView for z/OS Installation</i> • <i>Tivoli NetView for z/OS Administration Reference</i> • APAR OW54858
OMVS	The work requests include work processed in z/OS UNIX System Services forked children address spaces. (Work that comes from an enclave is managed to the goals of the originating subsystem.)	Address Space	<ul style="list-style-type: none"> • <i>z/OS UNIX System Services Planning</i>
SOM	The work requests include all SOM client object class binding requests.	Enclave	<ul style="list-style-type: none"> • <i>z/OS SOMobjects Configuration and Administration Guide</i>
STC	The work requests include all work initiated by the START and MOUNT commands. STC also includes system component address spaces such as the TRACE and PC/AUTH address spaces.	Address Space	<ul style="list-style-type: none"> • “Using the system-supplied service classes” on page 88
TCP	The work requests include work processed by the z/OS Communications Server.	Enclave	<ul style="list-style-type: none"> • <i>z/OS Communications Server: IP Configuration Guide</i>
TSO	The work requests include all commands issued from foreground TSO sessions.	Address Space	<ul style="list-style-type: none"> • <i>z/OS MVS Initialization and Tuning Guide</i> (Look for the discussion of TSO/E transactions in the “System Resources Manager” information.)
SYSH	Identifies non z/OS partitions (e.g. LINUX partition) in the LPAR cluster which needs to be managed by WLM according to business goals set for the partition.	LPAR	<ul style="list-style-type: none"> • “Non-z/OS partition CPU management” on page 23 and Chapter 19, “The Intelligent Resource Director,” on page 151

Important note about CICS and IMS transactions

CICS and IMS do not use enclaves, but use a different set of WLM services to provide transaction management.

CICS and IMS transactions can be assigned only response time goals (either percentile or average) within single period service classes. If you do not define any goals at all for CICS or IMS work, then the work will be managed to the velocity goals of the address spaces. Once you have defined a transaction goal for CICS or IMS work, then *all* subsequent work will be managed to those transaction goals, *not* to the velocity goals of the address spaces.

For example, you may initially be managing all CICS work to the velocity goals of the CICS address space. If you define a response time goal for a CICS transaction, you will be required to declare a default goal as part of that definition. Now all CICS transactions will be managed to those response time goals, even if they must accept the default.

Important note about NETV subsystem

Make sure to add the subsystem type NETV to your service definition (option 6 in ISPF application).

Tivoli NetView optionally allows you to let WLM manage NetView subtask performance in relation to other tasks and applications running on the system or sysplex. If enabled, NetView creates enclaves during subtask initialization and calls WLM to classify a subtask to the appropriate service class.

When a user decides to separate the management of NetView's network and system automation (SA) subtasks, NetView creates z/OS enclaves to manage those two sets of subtasks so that users can assign different performance goals to the enclaves. "Network" subtasks include all those not connected with system automation.

These two types of NetView enclaves should be classified to service classes with velocity goals. The goals should have approximately the same velocity value, but the goal assigned to NetView system automation enclaves should be more important than the goal assigned to any NetView network enclaves. There is no need to define a separate service class for NetView, if existing service classes in your service definition satisfy these conditions. For example, if SA z/OS or other system automation is used, a goal of Velocity = 50 and an Importance of 1 could be assigned. For non-system automation NetView subtasks, a goal of Velocity = 30 and an Importance of 2 could be assigned to give preference to the system automation NetView subtasks.

If the NetView WLM support is enabled, the absence of classification rules for subsystem type NETV will result in the NetView enclaves being classified to service class SYSOTHER.

Note that the WLM ISPF application does *not* validate the classification attributes used in the classification rules for subsystem type NETV.

If you have a subsystem *not* included in either of these tables, check its documentation for the kind of work requests supported by workload management and the applicable work qualifiers.

Table 6 on page 62 summarizes the key differences among the service classes for enclave transactions, address space-oriented transactions, and IMS/CICS transactions.

Table 6. Enclave transactions, address space-oriented transactions, and CICS/IMS transactions

Transaction type	Allowable goal types	Allowable number of periods	RMF (or other monitor) reporting
Address space-oriented	<ul style="list-style-type: none"> Response Time Execution Velocity Discretionary 	Multiple	<ul style="list-style-type: none"> IOC, CPU, MSO, and SRB service consumption reported Execution delays reported Special reporting data provided. See note 1.
Enclave	<ul style="list-style-type: none"> Response Time Execution Velocity Discretionary 	Multiple	<ul style="list-style-type: none"> CPU service consumption reported Execution delays reported “Served by” reported for enclaves using TCBS Special reporting data provided. See note 1.
CICS/IMS	<ul style="list-style-type: none"> Response Time 	1	<ul style="list-style-type: none"> No service consumption reported (reported under regions) No execution delays reported (reported under regions) “Service Classes Being Served” reported (for service classes assigned to the server address spaces) “Response Time Breakdown in Percentage” reported Special reporting data provided. See note 1.

Note 1: See [“Defining special reporting options for workload reporting” on page 75](#) for more information on special reporting.

The ISPF application provides these subsystem types as a selection list on the classification rules panel. You can add any additional subsystem type if it supports workload management on the same panel.

Defining work qualifiers

The name field for work qualifiers is 8 characters long. You can use nesting for the work qualifiers that run longer than 8 characters, which are the following:

- Accounting information
- Client accounting information
- Client IP address
- Client transaction name

- Client user ID
- Client workstation name
- Collection name
- Correlation information
- Package name
- Procedure name
- Process name
- Scheduling environment
- Subsystem parameter
- zEnterprise service class name

See [“Organizing work for classification” on page 82](#) for how to nest by using the start position.

You can use masking and wildcard notation to group qualifiers that share a common substring. For work qualifiers that run longer than 8 characters, you can use a start position to indicate how far to index into the character string. When no start parameter is specified, WLM matches the name field for work qualifiers that run longer than 8 characters according to the number of characters specified. See [“Organizing work for classification” on page 82](#) for details on how WLM matches the name field for work qualifiers.

Table 7 on page 63 shows which work qualifiers are supported by each IBM-defined subsystem.

	A S C H	C B	C I C S	D B 2	D D F	E W L M	I M S	I W E B	J E S	L D A P	L S F M	M Q	N E T V	O M V S	S O M	S T C	T C P	T S O	S Y S H
Accounting information	●			●	●				●					●		●		●	
Client accounting information				●	●														
Client IP address				●	●														
Client Transaction Name				●	●		●												
Client user ID				●	●														
Client workstation name				●	●														
Collection name		●		●	●										●				
Connection type			●	●	●		●												
Correlation information				●	●														
LU name			●	●	●		●						●						

Table 7. Work qualifiers supported by each IBM-defined subsystem type (continued)

	A S C H	C B	C I C S	D B 2	D D F	E W L M	I M S	I W E B	J E S	L D A P	L S F M	M Q	N E T V	O M V S	S O M	S T C	T C P	T S O	S Y S H
Netid				•	•		•												
Package name				•	•														
Perform				•					•							•		•	
Plan name				•	•														
Priority				•					•			•	•						
Procedure Name				•	•														
Process name				•	•							•							
Scheduling environment name				•					•										
Subsystem collection name				•	•				•										
Subsystem instance		•	•	•	•		•	•	•	•	•	•	•				•		
Subsystem parameter				•	•			•				•			•	•			
Sysplex name	•	•	•	•	•		•	•	•	•	•	•		•	•	•		•	•
System name	•													•		•		•	•
Transaction Class / job class	•	•	•	•			•	•	•			•	•						
Transaction name / job name	•	•	•	•			•	•	•	•	•	•	•	•		•	•		
User ID	•	•	•	•	•		•	•	•			•	•	•	•	•		•	
zEnterprise service class						•													

Note: For subsystem type STC, you can use Subsystem Parameter as a work qualifier. However, you cannot use Subsystem Parameter Groups as a work qualifier.

For information about which qualifiers are used by other subsystems that are supporting workload management, see their supporting documentation.

Accounting information

ASCH

The information passed on the JOB statement.

DB2

Accounting information is associated with the originator of the query; for example, the accounting information from TSO, JES, or DDF.

DDF

Accounting information is the value of the DB2 accounting string associated with the DDF server thread.

JES

The information passed on the JOB statement, not the EXEC statement.

Note: WLM/SRM ignores this if the JES2 init deck has a JOBDEF statement with parm ACCTFLD=OPTIONAL specified.

OMVS

Accounting data is normally inherited from the parent process of a z/OS UNIX System Services address space. In addition, when a daemon creates a process for another user, accounting data is taken from the WORKATTR of the RACF® user profile. A user can also assign accounting data by setting the _BPX_ACCT_DATA environment variable or by passing accounting data on the interface to the _spawn service. For more information about z/OS UNIX System Services accounting information, see [z/OS UNIX System Services Planning](#).

STC

The information passed on the JOB statement.

TSO

The accounting information specified by the TSO/E user when logging on to the system.

Because JCL supports 143 characters in accounting information, and the application allows only eight characters per rule, the application allows “nesting” for accounting information. See [“Organizing work for classification”](#) on page 82 for more information.

Example of nesting accounting information

In this example, you can “nest” accounting information (AI) in the classification rules.

```
Subsystem Type . . . . . JES      (Required)
Description  . . . . . All batch rules

-----Qualifier-----
Type      Name      Start
1  AI      43876AAA  1
2  AI      DEPT58*  9

-----Class-----
Service    Report
DEFAULTS:  BATH00EY
           BATHBEST
```

This example shows the classification rules for the JES subsystem. You can classify with more than the allowed 8 characters by nesting accounting information. In the example, all work with accounting information ‘43876AAADEPT58’ starting in position 1 for 14 characters is associated with service class BATHBEST.

Client accounting information

Db2

The client accounting information associated with the originator of the query. Provided by the client information specified for the connection; may be different from the accounting information of TSO, JES, or DDF.

DDF

The client accounting information associated with the DDF server thread. Provided by the client information specified for the connection; may be different from the Db2 accounting string associated with the DDF server thread.

Client IP address**Db2**

The source client IP address associated with the originator of the query. Provided by the client information specified for the connection. SOURCELU, CLIENTIPADDR and NETID are mutually exclusive.

DDF

The source client IP address associated with the DDF server thread. Provided by the client information specified for the connection. For details, see [Classifying Db2 DDF threads in WLM \(www.ibm.com/docs/en/db2-for-zos/11?topic=manager-classifying-db2-ddf-threads-in-wlm\)](http://www.ibm.com/docs/en/db2-for-zos/11?topic=manager-classifying-db2-ddf-threads-in-wlm). SOURCELU, CLIENTIPADDR and NETID are mutually exclusive.

Client transaction name**DB2**

The client transaction name for the work request. Provided by the client information that is specified for the connection; might be different from the transaction or job name that is associated with the originator of the query.

DDF

The client transaction name for the work request. Provided by the client information that is specified for the connection.

IMS

The name of the Transaction Pipe (TPIPE).

Client user ID**DB2**

The client userid associated with the originator of the query. Provided by the client information specified for the connection; may be different from the user ID from TSO, JES or DDF.

DDF

The client userid associated with the DDF server thread. Provided by the client information specified for the connection; may be different from the DDF server thread's primary AUTHID.

Client workstation name**DB2**

The client workstation name or host name associated with the originator of the query. Provided by the client information specified for the connection.

DDF

The client workstation name or host name associated with the DDF server thread. Provided by the client information specified for the connection.

Collection name**CB**

The logical server group name defined using the WebSphere Application Server system management utility. This represents a set of WebSphere Application Server objects that are grouped together and run in a logical server. For more information, see the online information included with the WebSphere Application Server system management user interface.

DB2

The collection name associated with the originator of the query; for example, the collection name from DDF.

DDF

The DB2 collection name of the first SQL package accessed by the distributed relational database architecture (DRDA) requestor in the work request.

SOM

The logical server name defined using the SOM REGIMPL utility (defined to REGIMPL as the application alias). This represents a set of SOM objects that are grouped together and run in a logical server. For more information, see *z/OS SOMobjects Configuration and Administration Guide*.

Connection type**CICS**

The name of the TCP/IP service that received the request for this transaction.

DB2

Connection type that is associated with the originator of the query; for example, the connection type from DDF.

DDF

The DB2 connection type of the DDF server thread. The thread contains the value 'DIST' indicating it is a server.

IMS

The port number of the TCP/IP service that received the request for this transaction.

Correlation information**DB2**

Correlation ID associated with the originator of the query; for example, the correlation ID from DDF.

DDF

The DB2 correlation ID of the DDF server thread.

LU name and netid

LU name and netid are used mostly for qualifying CICS, DB2, DDF, and IMS work. If you want to filter on the fully qualified name, you can use the LU name value of up to 8 characters, and then define a sub-rule of netid for up to 8 characters.

CICS

Only the LU name is available for CICS. It is the 8-byte NETNAME of the principal facility of the transaction instance. For details of the value of this parameter for non-VTAM terminals, and for transaction-routed transactions see *CICS/ESA Performance Guide*.

DB2

The LU name and netid associated with the originator of the query; for example, the LU name and netid from DDF. For more information about the format of the LU name, see *DB2 SQL Reference*.

DDF

The VTAM LU name and netid of the system that issued the structured query language (SQL) request. For more information about the format of the LU name, see *DB2 SQL Reference*.

IMS

If a transaction comes in from an LU 6.2 device, you can specify both the LU name and the netid. Otherwise, you can specify only the 8 byte LU name.

NETV

The LU name and the netid associated with the NetView subtask.

Package name**DB2**

Package name of the originator of the query; for example, the package name from DDF.

DDF

The name of the first DB2 package accessed by the DRDA requestor in the work request.

Perform

DB2

The performance group number for the thread associated with the query.

JES

The performance group number specified using the PERFORM keyword on the JCL JOB statement.

STC

One of the following:

- The performance group number specified using the PERFORM keyword on the START command.
- The performance group number specified using the PERFORM keyword on the JCL JOB statement.

TSO

The performance group number specified on the logon panel.

Plan name

DB2

Plan name associated with the originator of the query; for example, the plan name from DDF.

DDF

The DB2 plan name associated with the DB2 server thread. For DB2 private protocol requestors and DB2 Version 3 or higher DRDA requestors, this is the DB2 plan name of the requesting application. For non-DB2 requestors and other DRDA requestors, this is not applicable.

Priority

DB2

Priority associated with the originator of the query; for example, the priority from a batch job.

JES

A value between 0 and 15, the priority associated with the batch job submitted through JES2 or JES3.

Note: For JES work, 15 is the highest priority and 0 is the lowest. (Contrast with MQ work, where 0 is the highest priority and 9 is the lowest.)

MQ

A value between 0 and 9, the priority associated with the Websphere MQ Workflow message.

Note: For MQ work, 0 is the highest priority and 9 is the lowest. (Contrast with JES work, where 15 is the highest priority and 0 is the lowest.)

NETV

Indicates a number between 1 and 9 that defines the dispatching priority of this task in relation to other subtasks running in this NetView program. For more information, see *Tivoli NetView Administration Reference*.

When you use priority as a work qualifier, you can use operators such as greater-than ('>') and less-than ('<') to group a range of priorities into one service or report class.

Priority Example

To put priority 8 and higher work into service class BATCH020, and put all other work into service class BATCH005, you would code the following:

```
Subsystem Type . . . . . JES      (Required)
Description . . . . . Job Priority

-----Qualifier-----
Type      Name      Start
1 PRI      >=8

-----Class-----
Service   Report
DEFAULTS: BATCH005
          BATCH020
```

Procedure name

DB2

Procedure name associated with the originator of the query; for example, the DB2 stored procedure name from DDF.

DDF

If the first SQL statement issued by the DDF client is a CALL statement, this field contains the unqualified name of the DB2 stored procedure. In all other cases, this field contains blanks.

Process name

DB2

A client application name

DDF

A client application name

MQ

The MQWIH_ServiceName from the message's work information header.

Scheduling environment name

JES

The scheduling environment name assigned to the job.

DB2

Scheduling environment name associated with the originator of the query.

DDF

The user ID for the client. This can be different from the authorization ID used to connect to DB2. This information is for identification only, and is not used for any authorization.

Subsystem collection name

JES

The XCF group name.

DB2

Subsystem collection name associated with the originator of the query.

DDF

The subsystem collection name is the name assigned by the subsystem to related groups of its work. For example, DB2 data sharing group name.

Subsystem instance

You can use subsystem instance to isolate multiple instances of a subsystem. For example, use subsystem instance if you have a CICS production system as well as a CICS test system.

CB

The WebSphere Application Server specific short name.

CICS

The VTAM applid for the subsystem instance. For more information, see *CICS/ESA Dynamic Transaction Routing in a CICSplex*.

DB2

The subsystem type associated with the originator of the query; for example:

- TSO for requests from TSO/E
- JES for requests from batch jobs
- DDF for requests from DDF

DDF

The DB2 server's MVS subsystem name. For more information about the name, see *DB2 Administration Guide*.

IMS

The IMS subsystem name, as defined on the IMSID positional parameter in the IMS DFSMPR procedure. It is a 1- to 4-character value that uniquely identifies the control region. The generation default is IMSA. For more information, see *IMS/ESA System Definition Reference*

IWEB

The subsystem name from the application environment definition. (Note that this is identical to bits 0-7 of the Subsystem Parameter qualifier for IWEB).

JES

The JES2 or JES3 subsystem name from the IEFSSNxx parmlib member.

LDAP

The z/OS LDAP server's job name. Needed to distinguish between different LDAP servers.

LSFM

The procname of address space in which LAN Server for MVS is running.

MQ

The IBM MQ Workflow subsystem name.

NETV

The NetView WLM subsystem name as coded in CNMSTYLE. This is usually the NetView domain name. For more information, see *Tivoli NetView Administration Reference*.

TCP

The TCP/IP jobname. For further information, refer to *z/OS Communication Server IP Configuration Guide*.

Subsystem parameter

If you have a vendor or home-grown subsystem type that has a qualifier other than the IBM supported ones, it could use the subsystem parameter. You should check your subsystem documentation to determine whether your subsystem supports the subsystem parameter, and in what parameter format.

Because the subsystem parameter is up to 256 characters long, you can nest to use more than the limit of eight characters. See [“Organizing work for classification” on page 82](#) for further information on how to nest using the start position.

DB2

The subsystem parameter, if any, associated with the originator of the query.

DDF

The subsystem parameter. This qualifier has a maximum length of 255 bytes. The first 16 bytes contain the client's user ID. The next 18 bytes contain the client's workstation name. The remaining 221 bytes are reserved.

Note the following:

- If the length of the client's user ID is less than 16 bytes, use blanks after the user ID to pad the length.
- If the length of the client's workstation is less than 18 bytes, use blanks after the workstation name to pad the length.

IWEB

A 47-byte string formatted as follows:

1-8

Subsystem name

9

Blank

10-24

Source IP address

25

Blank

26-40

Target IP address

41

Blank

42-47

Target port

For more information, see *Internet Connection Server User's Guide*.

MQ

The 32-byte *application_environment_name* from the APPLICID attribute of the process definition associated with the WLM-managed queue.

SOM

A 246-byte string consisting of two 123-byte fields:

- Field 1 — class name
- Field 2 — method name

For more information, see *z/OS SOMobjects Configuration and Administration Guide*.

STC

Indicates the system-provided service class name that will be assigned if a started task created with the high dispatching priority, privileged, or system task attribute is not assigned to a service class.

Values:

- SYSTEM — Started task was created with high dispatching priority attribute.
- SYSSTC — Started task is privileged or is a system task.
- (blank) — Started task was not created with the high dispatching attribute, is not privileged, and is not a system task.

Note: Subsystem Parameter Groups can be used as a work qualifier for subsystem types DB2, DDF, IWEB, MQ, SOM but **not** for subsystem type STC. See [“Using groups” on page 86](#) for further information.

Sysplex name

For all subsystem types, use the sysplex name qualifier if you have a common service definition in multiple sysplexes, and need to assign different service classes or report classes based on the specific sysplex in which the work is running.

System name

The system name qualifier is supported for address spaces whose execution system is known at classification time. Note that JES is not eligible for this qualifier, as the system on which classification occurs may not be the system on which the job is run. Subsystem-defined transactions (CICS/IMS) and enclave-based transactions are not bound to an execution system at classification time, and are therefore not eligible either.

ASCH

The name of the execution system.

OMVS

The name of the execution system.

STC

The name of the execution system.

TSO

The name of the execution system.

SYSH

The name of the execution system.

Transaction class / job class**ASCH**

The job class that is used for work selection.

CB

Name resulting from mapping the URI to a name. For more information, see *WebSphere Application Server for z/OS: Installation and Customization*.

CICS

The name of the transaction class to which this transaction, or transid, belongs.

DB2

The job or transaction class that is associated with the originator of the query; for example, the job class from JES.

IMS

The CLASS keyword on the PGMTYPE=parameter in the APPLCNT macro. For more information, see *IMS/ESA System Definition Reference*.

IWEB

The arbitrary class name that is specified in the APPLENV directive in the Webserver's administrative file. Using the filtering function in the webserver, you can assign transactions to transaction classes based on the requested URL. The transaction classes can then be assigned unique service classes that use this Transaction Class qualifier. This is probably the most useful qualifier for IWEB work, because of its flexibility.

For the function Fast Response Cache Accelerator for high performance handling of cached static web pages, you must classify work as described in the following paragraph. Otherwise, it is assigned the default service class for IWEB work.

The transactions that are handled by the Cache Accelerator are all joined to a single, long-lived enclave. This enclave should be assigned a unique transaction class (as specified on the Webserver FRCWLMParms directive). This transaction class should then be assigned to a service class with a single period and a velocity goal in the service policy under the IWEB subsystem type. Neither response time goals nor multiple periods are appropriate for this work, as WLM is not aware of the individual Cache Accelerator requests. (Because each individual transaction is so trivial, it would cost more resource to manage them than to simply process them.) In RMF reports, you see zero ended transactions for the Cache Accelerator service class (assuming you have no other work that is running in this service class), but you see some amount of accumulated service for this single enclave.

JES

The job class that is used for work selection.

MQ

A value of either ONLINE, meaning that the server is immediately available, or BACKLOG, meaning that the message was queued pending availability of a server.

NETV

The NetView subtask type. Valid types are AOST, DST, HCT, MNT, NNT, OPT, OST, and PPT. For more information, see *Tivoli NetView Customization: Using Assembler*.

Transaction name / job name**ASCH**

The jobname in the JCL JOB statement in the APPC/MVS transaction program (TP) profile.

CB

The method name, for example, GET, POST, or DELETE. For more information, see *WebSphere Application Server for z/OS: Installation and Customization*.

CICS

A parameter on many CICS commands. It is often referred to as the CICS transaction identifier, or *tranid*. For more information, see *CICS/ESA Resource Definition Guide*.

DB2

The transaction or job name associated with the originator of the query; for example, the job name from JES.

IMS

The CODE= parameter on the IMS TRANSACT macro. For more information, see *IMS/ESA System Definition Reference*.

IWEB

The method name, for example, GET, HEAD, POST, DELETE, or PUT.

JES

The jobname of the JES managed job. For example, you may run a CICS region as a batch job in your installation. You would define it in classification rules as a transaction name in the JES subsystem type.

LDAP

The z/OS LDAP server's enclave transaction name:

- Any transaction name that is also defined in the configuration file of the directory server.
- GENERAL for all LDAP work that is not assigned a user-defined exception class.

For further information, refer to *z/OS IBM Tivoli Directory Server Administration and Use for z/OS*.

LSFM

One of the following:

- LSFMMMTX - multi-media transactions
- LSFMFITX - file transactions
- LSFMAMTX - administration transactions
- LSFMCMTX - communication transactions

MQ

The MQWIH_ServiceStep value from the message's work information header.

NETV

The NetView subtask module name. For more information, see the NetView TASK statement description in the *Tivoli NetView Administration Reference*.

OMVS

The jobname for the z/OS UNIX System Services address space. By default, fork and spawn set jobname values to the user ID with a number (1-9) appended. However, daemons or users with appropriate privileges can set the _BPX_JOBNAME environment variable to change the jobname for forked or spawned children. In this way, servers and daemons in z/OS UNIX System Services address spaces can easily be assigned performance attributes different than other z/OS UNIX System Services address spaces.

STC

One of the following:

- The name as specified on the JOBNAME= parameter of the START command
- The name specified on the MOUNT command
- The system address space name
- The name on the JOB statement.

For example, you may run your IMS regions as started tasks in your installation. You would define these as transaction names in your STC subsystem type in classification rules. However, if IMS V5.1 is present, the STC rule for IMS is ignored and the rules for the IMS subsystem type are used when IMS becomes a server.

TCP

The z/OS Communications Server transaction name associated with data traffic being processed by z/OS Communications Server on an independent enclave that has been active for a relatively long period of time. Currently the only transaction name supported by z/OS Communications Server is TCPENC01 for IPSec traffic. For further information, refer to *z/OS Communication Server IP Configuration Guide*.

User ID**ASCH**

The user ID of the user requesting the APPC/MVS service.

CB

The user ID of the user requesting the WebSphere Application Server service.

CICS

The user ID specified at LOGON time, which is the RACF (or other access control facility) defined resource. For more information about CICS user IDs, see *CICS/ESA CICS-RACF Security Guide*.

DB2

The user ID associated with the originator of the query; for example, the user ID from TSO, JES, or DDF.

DDF

The DDF server thread's primary AUTHID, after inbound name translation.

IMS

The user ID specified at LOGON time, which is the RACF (or other access control facility) defined resource.

IWEB

The user ID of the web server address space (not the original requestor's user ID). Note that because this user ID will generally be the same for all transactions, using this qualifier for IWEB work will have limited usefulness.

JES

The user ID specified on the JOB statement on the RACF USER keyword.

MQ

The first 8 bytes of the 12-byte message header field MQMD_USERIDENTIFIER.

NETV

The NetView subtask ID. For NetView OST and NNT subtasks this is the NetView operator ID. For more information, see *Tivoli NetView User's Guide*. For AOST (automation subtasks) this is the NetView operator ID on the AUTOTASK command that started the AOST. For more information, see *Tivoli NetView Command Reference*. For NetView DST and OPT subtasks this is the taskname on the NetView TASK statement. For more information, see the *Tivoli NetView Administration Reference*. The MNT subtask ID is MNT. The PPT subtask ID is the NetView domain ID concatenated with the characters "PPT". The HCT subtask ID is the same as its LU name which is specified on the HARDCOPY statement. For more information, see *Tivoli NetView Administration Reference*.

OMVS

The RACF user ID associated with the address space. This user ID is either inherited from the parent process or assigned by a daemon process (for example, the rlogin or telnet daemon). For more information about z/OS UNIX System Services user IDs, see [z/OS UNIX System Services Planning](#).

SOM

The user ID of the user requesting the SOM service.

STC

The user ID assigned to the started task by RACF (or other access control facility).

TSO

The user ID specified at LOGON time, which is the RACF (or other access control facility) defined user profile.

zEnterprise service class name (ESC) from a Unified Resource Manager performance policy

EWLM

The subsystem type associated with work requests that originate from virtual servers in an ensemble workload. This subsystem type and work qualifier enable administrators to assign zEnterprise service classes to WLM service classes and report classes.

Defining special reporting options for workload reporting

To simplify mobile workload reporting, you can specify which work is mobile work that is eligible for mobile workload pricing. You do this with classification rules. When you create the rules, scroll right twice (PF11) on the panel and supply values for the Reporting Attribute option, as shown in the following example.

Modify Rules for the Subsystem Type						Row 1 to 3 of 3
Command ==> _____						Scroll ==> CSR
Subsystem Type . : CICS						Fold qualifier names? Y (Y or N)
Description . . . CICS rules						
Action codes: A=After C=Copy M=Move I=Insert rule						
B=Before D=Delete row R=Repeat IS=Insert Sub-rule						<=== More
Action	Type	Qualifier Name	Start	Storage Critical	Reporting Attribute	Manage Region Using Goals Of
----	1 TC	BANKING	---	NO	MOBILE	N/A
----	1 TC	HR	---	NO	NONE	N/A
----	1 TN	ACCT	---	NO	NONE	N/A

The Reporting Attribute option is supported for all IBM-supplied subsystem types. You can specify these values:

- NONE, for all your work. This is the default.
- MOBILE, for mobile work.
- CATEGORYA, for a first general purpose subset of work. This is provided for future use.
- CATEGORYB, for a second general purpose subset of work. This is provided for future use.

As soon as you specify a non-default value, you can no longer associate the classification rule with a tenant report class. You cannot associate the classification rule directly, using its parent classification rule, or using the default report class specification.

WLM then tracks processor consumption separately for each value of the reporting attribute, and reports consumption at the service and report class level in the IWMWRCAA answer area that is provided by the WLM Workload Activity Collection Service, IWMRCOLL. See the topic about [Using the workload reporting services in z/OS MVS Programming: Workload Management Services](#) for details. At the system level, WLM reports consumption in the SRM Resource Control Table IRARCT.

The Reporting Attribute is independent from the assigned service and report class. It can be used to report on subsets of work that is running in a service or report class, and on subsets of work that is running on the whole system. This eliminates the need for introducing new dedicated service and report classes for mobile workload reporting, and leaves your existing reporting processes unaffected.

Classification with the Reporting Attribute option can be based on any work qualifier that is supported for the subsystem types. As for other classification rules, classification groups can be used to keep the classification rules simple to read, and efficient to check.

Example: mobile classification

Suppose that you have a classification rule for your banking transactions, and part of the transactions flows in from mobile devices. To differentiate those transactions from “normal” transactions, insert a subrule as shown in this example:

Modify Rules for the Subsystem Type				Row 1 to 3 of 3		
Command ==> _____				Scroll ==> CSR		
Subsystem Type . : CICS		Fold qualifier names? Y (Y or N)				
Description . . . CICS rules						
Action codes:		A=After	C=Copy	M=Move	I=Insert rule	
		B=Before	D=Delete	row R=Repeat	IS=Insert Sub-rule	
More ==>						
-----Qualifier-----		-----Class-----				
Action	Type	Name	Start	DEFAULTS:	Service Report	
is__	1 TC	BANKING	---		CICSDFT	
----	1 TC	HR	---		CICSFAST	CICS_RC1
----	1 TN	ACCT	---		CICSSLOW	CICS_RC2
----					CICSSLOW	CICS_RC3

If all mobile banking transactions flowed in through TCP/IP service TCP001, your subrule would look like the following:

Modify Rules for the Subsystem Type					Row 1 to 4 of 4	
Command ==> _____					Scroll ==> CSR	
Subsystem Type . : CICS		Fold qualifier names? Y (Y or N)				
Description . . . CICS rules						
Action codes:		A=After	C=Copy	M=Move	I=Insert rule	
		B=Before	D=Delete	R=Repeat	IS=Insert Sub-rule	
		More ==>				
-----Qualifier-----		-----Class-----				
Action	Type	Name	Start	DEFAULTS:	Service	Report
----	1 TC	BANKING	---		CICSDFT	
----	2 CT	TCP001	---		CICSFAST	CICS_RC1
----	1 TC	HR	---		CICSSLOW	CICS_RC2
----	1 TN	ACCT	---		CICSSLOW	CICS_RC3

Do not add a service or report class. This means that the service and report class of the parent rule is used, and your existing reporting processes are not affected. Then, you can scroll right twice (PF11) to complete the Reporting Attribute option, as shown in this example:

Modify Rules for the Subsystem Type						Row 1 to 4 of 4	
Command ==> _____						Scroll ==> CSR	
Subsystem Type . : CICS						Fold qualifier names? Y (Y or N)	
Description . . . CICS rules							
Action codes:		A=After	C=Copy	M=Move	I=Insert rule		
		B=Before	D=Delete	R=Repeat	IS=Insert Sub-rule		
						<== More	
Action	Type	Name	Start	Storage Critical	Reporting Attribute	Manage Region Using Goals Of	
----	1 TC	BANKING	---	NO	NONE	N/A	
----	2 CT	TCP001	---	NO	MOBILE	N/A	
----	1 TC	HR	---	NO	NONE	N/A	
----	1 TN	ACCT	---	NO	NONE	N/A	

WLM then tracks the total and mobile processor consumption for the service and report class of the banking transactions, and also at the system level.

If you have mobile banking transactions that flow in through several TCP/IP services, you can create a classification group for them, as shown in this example:

Create a Group						Row 1 to 10 of 10	
Command ==> _____							

Enter or change the following information:

Qualifier type : Connection Type
Group name : TCPMOBIL (required)
Description : TCP Service Names for mobile TX
Fold qualifier names? Y (Y or N)

Qualifier Name	Start	Description
TCP001	---	-----
TCP004	---	-----
TCP008	---	-----
TCP009	---	-----
TCP143	---	-----
TCP762	---	-----
-----	---	-----

Use the group that you created in your subrule, as shown in the following example:

```

                                Modify Rules for the Subsystem Type          Row 1 to 4 of 4
Command ==> _____ Scroll ==> CSR

Subsystem Type . : CICS          Fold qualifier names?  Y (Y or N)
Description . . C=Copy          M=Move      I=Insert rule
                  B=Before      D=Delete row R=Repeat  IS=Insert Sub-rule
                  . CICS rules

Action codes:  A=After
               -----Qualifier-----
Action  Type   Name      Start      Service      Report
-----  ---   ---      ---      ---
      1 TC     BANKING   ---      CICSDFD      CICS_RC1
      2 CTG    TCPMOBIL  ---      CICSFAST
      1 TC     HR        ---      CICSLOW
      1 TN     ACCT      ---      CICSLOW      CICS_RC3

```

Defining recovery process boost for middleware recycle

To accelerate middleware start or restart processing, you can specify which regions initiate a recovery process boost when being recycled. You do this with classification rules. When you create the rules for subsystem type STC, scroll right three times (PF11) and supply values for the **Boost** option, as shown in the following example.

```

Subsystem-Type  Xref  Notes  Options  Help
-----
Command ==> _____ Modify Rules for the Subsystem Type          Row 1 to 5 of
SCROLL ==> CSR

Subsystem Type . : STC          Fold qualifier names?  Y (Y or N)
Description . . . IBM-defined subsystem type

Action codes:  A=After      C=Copy      M=Move      I=Insert rule
               B=Before      D=Delete row R=Repeat  IS=Insert Sub-rule
               <=== More

Action  Type   Name      Start      Boost
-----  ---   ---      ---      ---
      1 TN     TV1*      ---      YES
      1 TN     TV2*      ---      NO
      1 TN     TOR       ---      YES
      1 TN     AOR1      ---      NO
      1 TN     AOR2      ---      NO

```

For STC work only, you can specify the following values:

NO

The region does not initiate a recovery process boost when started or restarted. This is the default.

YES

The region initiates a recovery process boost when started or restarted.

For all other subsystem types except STC, the **Boost** field is not applicable and contains N/A.

If an address space that matches a classification rule in the active policy with Boost=YES is started or restarted, a recovery process boost is initiated that provides short-term acceleration for the process. This boost follows the same rules as recovery process boosts provided by z/OS for sysplex recovery processes. For details, see [Chapter 21, “System Recovery Boost,”](#) on page 165.

Defining the order of classification rules

When the subsystem receives a work request, the system searches the classification rules for a matching qualifier and its service class or report class. Because a piece of work can have more than one work qualifier associated with it, it may match more than one classification rule. Therefore, the order in which you specify the classification rules determines which service classes are assigned. You can use a different order and hierarchy for each subsystem type.

Example of defining an order of rules

Suppose you are defining your JES classification rules. For all work requests coming into the JES2 subsystem instance, you want to assign work with user ID MNGRBIG and jobname PERFVAL to service class BATSLOW. All other work with user ID beginning with MNGR should be assigned to service class BATHOT. So in this case, the hierarchy for the JES subsystem is:

1. Subsystem type, because it is always the first
2. Subsystem instance
3. User ID
4. Job name

Defining a subsystem service class default

A service class default is the service class that is assigned if no other classification rule matches for that subsystem type. If you want to assign any work in a subsystem type to a service class, then you must assign a default service class for that subsystem — except for STC. You are not required to assign a default service class for STC, even if you assign started tasks to different service classes. In that case, all started tasks for which no classification rule matches will be assigned to the SYSSTC service class. If this is not as you intend, specify a less important default service class for the STC subsystem type.

Optionally, you can assign a default report class for the subsystem type. If you want to assign work running in a subsystem to report classes, then you do not have to assign a default service class for that subsystem.

Using inheritance in classification rules

Keep in mind that if you leave out the service class or report class on a classification rule, the work inherits the service class or report class from the higher level rule.

You can use this to your advantage by using the qualifier that applies to the most service classes in the subsystem as your first level qualifier. You can then list the exceptions in the subsequent levels.

Example of using inheritance

For example, for CICS, the available qualifiers include subsystem instance, user ID, transaction name, and LU name.

```
Subsystem Type . . . . . : CICS
Description . . . . . : CICS subsystem

-----Class-----
Service  Report
DEFAULTS: CICSB   ATMA
           CICSA   CASHA
           CASHA   DEPOSITA
           DEPOSITA BIGDEP
           BIGDEP
```

1	UI	ATMC	CICSC	ATMC
2	TN	CASH	-----	CASHC
2	TN	DEPOSIT	-----	DEPOSITC
3	LU	WALLST	-----	BIGDEP

In this example, the installation set up their user IDs for their CICS work according to the ATM setup that they have. Since all of their interactive work is related to the ATMs, they chose user ID as their first level qualifier. Then, they wanted to separate out their cash transactions from their deposit transactions for reporting purposes, so they set up a report class for each.

The transactions do not have a service class explicitly assigned to them, so they inherit the service class from the rule one level before.

In addition, for the deposit transactions, they wanted to separate out those deposits coming from ATMs on Wall St location, because that area had been having some service troubles. So they defined a report class at a level 3 under the DEPOSIT transactions for each ATM user ID.

You cannot nest all qualifier types within themselves. For example, if you choose user ID as a first level, you cannot use user ID as a second level, or sub-rule qualifier. Nesting is allowed only for qualifiers longer than 8 characters and their associated groups. These are:

- Accounting information
- Client accounting information
- Client IP address
- Client transaction name
- Client userid
- Client workstation name
- Collection name
- Correlation information
- Package name
- Procedure name
- Process name
- Scheduling environment
- Subsystem parameter
- zEnterprise service class name

See [“Organizing work for classification” on page 82](#) for how to nest using the start position.

Keep in mind that the system sequentially checks for a match against each level one rule. When it finds a match, it continues just in that family through the level two rules for the first match. Similarly, if a match is found at any given level, then its sub-rules are searched for further qualifier matches. The last matching rule is the one that determines the service class and report class to be assigned.

Example 1: Using the order of rules

Suppose you have defined the following classification rules for your IMS work:

			-----Class-----	
			Service	Report
1	Tran Name	5128	DEFAULTS: IMSB	-----
2	LU Name	BERMU	IMSA	-----
			IMSC	-----

Suppose the following kind of work requests enter the system:

	Transaction 1	Transaction 2	Transaction 3
Tran Name	5128	6666	5128
LU Name	BERMU	BERMU	CANCUN

- Transaction 1 is assigned service class IMSC, because the transaction 5128 is from the BERMU LU name.
- Transaction 2 is assigned service class IMSB, the subsystem default, because it is not transaction 5128, and therefore the system never checks any sub-rules.
- Transaction 3 is assigned service class IMSA, because it is associated with LU name CANCUN.
- If you specified the classification rules as:

1	LU Name	BERMU	IMSC	-----
2	Tran Name	5128	IMSA	___ -----

Then all work from LU BERMU is assigned in service class IMSC, except work with Tran name 5128.

Example 2: Using the order of rules

Suppose you have defined the following rules for your IMS work:

-----Qualifier----			-----Class-----	
Type	Name		Service	Report
			DEFAULTS:	
1	SI	IMST	PRDIMSR	-----
2	TC	15	TRNIMSR	-----
1	TC	15	TRNIMSNR	-----
1	SI	IMSM	PRDIMSNR	-----
2	TC	15	MDLIMSR	-----
			MDLIMSNR	-----

- If a work request in transaction class (TC) 15 enters the system from subsystem instance (SI) IMST, it is assigned service class TRNIMSNR.
- If a work request in transaction class (TC) 15 enters the system from subsystem instance (SI) IMSM, it is assigned service class PRDIMSNR and not MDLIMSNR as you might expect.

This is because the level 1 classification rule

1	TC	15	PRDIMSNR	-----
---	----	----	----------	-------

comes first and the more explicit classification rule comes second:

1	SI	IMSM	MDLIMSR	-----
2	TC	15	MDLIMSNR	-----

The system stopped on the first level one match that it encountered. You can re-order the rules so that this does not occur. Put the most explicit rule first and the more general rule second as shown here:

-----Qualifier----			-----Class-----	
Type	Name		Service	Report
			DEFAULTS:	
1	SI	IMST	PRDIMSR	-----
2	TC	15	TRNIMSR	-----
1	SI	IMSM	TRNIMSNR	-----
2	TC	15	MDLIMSR	-----
1	TC	15	MDLIMSNR	-----
			PRDIMSNR	-----

System-provided service classes

If some work comes into a system for which there is no associated service class defined in the classification rules, workload management assigns it to a default service class. There are several such default service classes:

SYSTEM

For all system address spaces designated 'high dispatching priority' (X'FF') address spaces. The high dispatching priority address spaces include MASTER, TRACE, GRS, DUMPSRV, SMF, CATALOG, RASP, XCFAS, SMXC, CONSOLE, IOSAS, JESXCF, and others. For a list of the high dispatching priority address spaces in your installation, see the RMF Monitor II report and look for the x'FF' dispatching priority.

You do not need to set up service classes for these system address spaces. Workload management recognizes these as special system address spaces and treats them accordingly.

If for some reason you do want to control these address spaces, you can do the following:

- Define a service class for them
- Set up a classification rule in the STC subsystem type which assigns the address space to a service class other than the default STC service class.

Note: To make sure that the system runs smoothly, certain address spaces cannot be freely assigned to all service classes. The following address spaces are always classified into service class SYSTEM, independently of the user defined classification rules:

- *MASTER*
- CATALOG
- CONSOLE
- GRS
- IEFSCHAS
- IOSAS
- IXGLOGR
- RASP
- SMF
- SMSPDSE
- SMSPDSE1
- XCFAS
- WLM

When you assign a service class other than SYSTEM to a started task eligible for the SYSTEM service class, it loses the high dispatching priority attribute and runs at the dispatching priority of the assigned service class period. The high dispatching priority attribute can be restored by one of the following methods:

- You can use the RESET command to change the started task's service class to SYSTEM.
- You can change the classification rules to explicitly classify the started task to SYSTEM and activate a policy.

You can also assign work to the SYSTEM service class as part of your work classification rules. You can *only* do this, however, for classification rules in the STC subsystem type and only for address spaces that are designated as "high dispatching priority" address spaces. Furthermore, some caution is necessary, as the SYSTEM service class runs at the highest dispatching priority, above all other work. Not all work is appropriate for such a high dispatching priority because, if the work is CPU-intensive, it could use a large amount of processor cycles, which could cause CPU delays for other important work in the system.

For more information about using SYSTEM in classification rules for started tasks, see [“Using the system-supplied service classes”](#) on page 88.

SYSSTC

For all started tasks not otherwise associated with a service class. Workload management treats work in SYSSTC just below special system address spaces in terms of dispatching.

You can also assign work to the SYSSTC service class as part of your work classification rules. You can do this for classification rules in the following subsystem types:

- ASCH
- JES
- OMVS (z/OS UNIX System Services)

- STC
- TSO

Some address spaces normally created when running MVS are neither high dispatching priority, privileged, nor a system task, such as NETVIEW. These address spaces must be explicitly assigned to a service class such as SYSSTC.

However, not all work is appropriate for SYSSTC because, if the work is CPU-intensive, it could use a large amount of processor cycles, which could cause CPU delays for other important work in the system. The criteria for the type of work appropriate for SYSSTC are:

- Work that absolutely needs a higher dispatch priority than other work
- Work that is not going to use a lot of CPU but requires fast CPU access
- Work that is trusted, such as production-level code and not development

For more information about using SYSSTC in classification rules for started tasks, see [“Using the system-supplied service classes”](#) on page 88.

SYSSTC1 - SYSSTC5

The service classes SYSSTC1, SYSSTC2, SYSSTC3, SYSSTC4, and SYSSTC5 are provided for future z/OS support. Service class SYSSTC and the SYSSTCx service classes are congruent as far as management of work is concerned. Work assigned to any of these service classes is managed identically to work assigned to any other. Currently, there is no technical reason to choose SYSSTCx as an alternative to SYSSTC. Many displays, for example, SDSF displays, provide the service class assigned to an address space. It is possible that one might assign SYSSTCx to convey some meaning that would be similar to a report class.

SYSOTHER

For all other work not associated with a service class. This is intended as a ‘catcher’ for all work whose subsystem type has no classification. It is assigned a discretionary goal.

Organizing work for classification

There are some ways you can organize your qualifiers for easier classification. You can use masking or wildcard notation as a way of grouping work to the same service class or report class. Or, you could set up a qualifier group for any qualifier except Priority and zEnterprise service class name.

If you have more than five rules at a given level for the same classification qualifier within a subsystem type, there may be performance implications. Qualifier groups are quicker to check than a single rule, so it may make sense to use them for performance sensitive subsystems like CICS and IMS.

You can use the start position for qualifiers longer than 8 characters. Those qualifiers are:

- Accounting information
- Client accounting information
- Client IP address
- Client transaction name
- Client userid
- Client workstation name
- Collection name
- Correlation information
- Package name
- Procedure name
- Process name
- Scheduling environment
- Subsystem parameter
- zEnterprise service class name

The following sections explain each kind of notation.

Using masking notation

You can use masking notation to replace a single character within a qualifier. This allows any character to match the position in the rule. Use a % in the position where the character would be. You can use multiple masks successively for multiple character replacement. If you specify a mask at the end of a character string, it could match on a null value OR a single character.

Examples of masking notation

For example, suppose you have a naming convention for all users in your IS services department that all user IDs start with DEPT58, followed by a letter A-F (depending on which division), ended by an I. Suppose also, you would like to bill your IS services department separately. You could use masking notation in setting up the classification rules as shown below.

-----Qualifier-----			-----Class-----	
Type	Name	Start	Service	Report
1 UI	DEPT58%I	---	DEFAULTS: BATREG	DEPT58

In the example, all work in this subsystem is associated with service class BATREG, and all work from the IS services department is associated with the report class DEPT58.

Using wildcard notation

You can also use *wildcard* notation for multiple character replacement in a character string. The wildcard character is an asterisk (*). You can use the wildcard character as the last position of a character string, or by itself. If a character string contains an asterisk in a position other than the last, it is treated as a character; for example, if you specify a character string of CI*S, the third character in a matching character string *must* have an asterisk as the third character. An asterisk by itself indicates a match for all characters.

Examples of wildcard notation

For example, suppose your installation has a naming convention for your CICS AORS and TORS. You can use the following wildcard notation in your CICS classification rules. Note that the subsystem instance of CI*S is not wildcard notation, a matching subsystem instance must be CI*S.

-----Qualifier-----			-----Class-----	
Type	Name	Start	Service	Report
1 TN	TOR*	---	DEFAULTS: CICSSTC2	-----
1 TN	AOR*	---	CICSSTC1_	
1 SI	CI*S	---	CICSSTC3_	
			CICSTEST_	

Important Note

Be careful when putting specific definitions below wildcards, which might cause an unwanted early match. In the example, the rule for TOR11 is useless, because a TOR11 transaction will match the TOR* rule before it.

-----Qualifier-----			-----Class-----	
Type	Name	Start	Service	Report
1 TN	TOR*	---	DEFAULTS: CICSSTC2	-----
1 TN	TOR11	---	CICSSTC1_	
			CICSSTC4_	

Using the start position

For work qualifiers longer than 8 characters, you can use a start position to indicate how far to index into the character string for a match. For example, you can assign all TSO/E users in a department to the same service class, assuming you follow a naming convention for accounting information for the department. Work qualifiers that run longer than 8 characters are:

- Accounting information
- Client accounting information
- Client IP address
- Client transaction name
- Client userid
- Client workstation name
- Collection name
- Correlation information
- Package name
- Procedure name
- Process name
- Scheduling environment
- Subsystem parameter
- zEnterprise service class name

The ISPF administrative application provides the **Start** field where you can specify the starting position for work qualifiers longer than 8 characters. The name field for a work qualifier is 8 characters long. If you are matching on a string that is fewer than 8 characters using a start position, you must use wildcard notation (asterisk) at the end of the string. Otherwise, the qualifier is padded with blanks to be 8 characters, and the blanks are used when making a match.

Example 1: Using the start position

Assume that you want to associate all JES2 work from department DIRS with the service class JESFAST. You assigned the default for JES2 work as service class JESMED. If all JES2 accounting information from department DIRS has the characters 'DIRS' starting in the eighth position, you enter a rule with qualifier DIRS* to match on just the 4 characters. If you want to filter out those jobs with the 8 characters 'DIRS ' starting in the eighth position, you need another rule with qualifier DIRS to assign those jobs to JESMED. The example shows the rules:

Subsystem Type : JES			
Description All JES2 service classes			
-----Qualifier-----			-----Class-----
Type	Name	Start	Service Report
			DEFAULT: JESMED
1	AI	DIRS	8 JESMED
1	AI	DIRS*	8 JESFAST

In this case, all jobs that have accounting information with the 8 characters 'DIRS ' starting in the eighth position are assigned to JESMED. All other jobs that have the 4 characters 'DIRS' starting in the eighth position are assigned to JESFAST. All other work that is coming into JES is assigned to service class JESMED.

When no start parameter is specified, WLM matches the name field for work qualifiers that run longer than 8 characters according to the number of characters specified. This is different from work qualifiers that are 8 characters long. For those qualifiers, the qualifier name is always padded with blanks to be 8 characters. Work qualifiers that are 8 characters long are the following:

- Connection type

- LU name
- Net ID
- Perform
- Plan name
- Priority
- Sysplex name
- Subsystem instance
- Subsystem collection name
- System name
- Transaction class
- Transaction name
- Userid

Example 2: Blank padding for long and short work qualifiers

Assume that you want to associate all JES2 work from accounts with numbers that start with 0201, and all work from user IDs starting with DEPT58 with the service class JESFAST. The example shows the rules:

```
Subsystem Type . . . . . : JES
Description . . . . . : All JES2 service classes

-----Qualifier-----
Type      Name      Start
1  AI      0201
1  UI      DEPT58*

-----Class-----
Service    Report
DEFAULT:   JESMED
           JESFAST
           JESFAST
```

Without a start position, WLM matches work qualifiers longer than 8 characters according to the number of characters specified. In the example, when matching the accounting information for 0201, WLM matches it as a 4 character string. Therefore, a job with accounting information '020175,D123' would match.

For work qualifiers that are 8 characters long, you must use wildcard notation at the end of the string. Otherwise, the qualifier is padded with blanks to be 8 characters, and the blanks are used when making a match. In the example, user ID DEPT58* matches 'DEPT58XY', 'DEPT58Z', and so on. If you specified user ID DEPT58 without the asterisk at the end, it would match only 'DEPT58 '.

The same applies to qualifiers longer than 8 characters when a start position is specified. The following table summarizes this behavior:

-----Qualifier-----			-----Behaviour-----
Type	Name	Start	
8 characters long	DEPT58	not supported	Matches on 'DEPT58__' only, nothing else. Must use wildcard notation at the end of the string to match any 'DEPT58xx'.
longer than 8 characters	0201	none	Matches on '020175', '0201XY', '0201Z', etc. Same as if wildcard notation at the end of the string had been specified
longer than 8 characters	DIRS	8	Matches on 'DIRS____' starting at the eighth position only, nothing else. Must use wildcard notation at the end of the string to match any 'DIRSXYZZ' starting at the eighth position.

Work qualifiers that run longer than 8 characters can be nested. In combination with the start position, this allows matching more than 8 characters.

Example 3: Nesting using the start position

Assume that you want to associate all JES2 work from account number 020175 with service class JESSLOW, except if it originates in department D58I*, in which case JESFAST should be used. The example shows the rules:

```
Subsystem Type . . . . . : JES
Description . . . . . All JES2 service classes
-----Qualifier-----Class-----
Type      Name      Start      Service      Report
              DEFAULT: JESMED
1 AI      020175      8          JESSLOW
2 AI      D58I*      8          JESFAST
```

A job with accounting information '020175,D58I1234' is then assigned service class JESFAST. A job that contains the job statement '020175,D64I9876' is assigned service class JESSLOW, because the department is different from D58I*. A job with accounting information '020177,D58I5678' is assigned the default service class JESMED, because the account number does not match, and therefore the system never checks any subrules.

Using groups

Groups are available for grouping together work qualifiers to make classification simpler. You can create groups to collect together work when you don't have a standard naming convention that allows masking or wildcarding. A *group* is a collection of the same work qualifiers. For example, you may want to create a group of started tasks because you want to assign them all to the same service class.

Groups are allowed for all work qualifiers except for Priority and zEnterprise Service Class.

Group types are specified by adding G to the type abbreviation. For example, a transaction group name is indicated as TNG.

Group types are usually valid for the same subsystem types as the underlying work qualifiers they group. For details on which qualifiers are valid for which subsystems, see Table 8. The only exception to this rule is the Subsystem Parameter Group which is **not** valid for subsystem type STC although the underlying Subsystem Parameter work qualifier is.

Qualifier groups of more than 5 members are quicker to check than single instances in the classification rules. So if you have, for example, a long list of CICS or IMS transaction names that you want to group in a service class or report class, consider setting up a group.

Example 1: Groups

If you want to assign a large number of CICS transactions to the same service class, you can create a transaction name group (TNG). You name the group, for example *CICSCONV*, and list all the transaction names you want included in the group.

```
Qualifier type . . . . . : Transaction Name
Group name . . . . . CICSCONV (required)
Description . . . . . CICS Conversational Group
Fold qualifier names? . . . . Y (Y or N)

Qualifier Name  Start  Description
CDBC           ---    -----
CDBI           ---    -----
CDBM           ---    -----
CEBR           ---    -----
CECI           ---    -----
CECS           ---    -----
CEDA           ---    -----
CEDB           ---    -----
```

```

Qualifier type . . . . . : Transaction Name
Group name . . . . . : CICSLONG (required)
Description . . . . . : CICS Long-Running Transaction
Fold qualifier names? . . . . Y (Y or N)

```

Qualifier Name	Start	Description
CDB0	---	-----
CSGX	---	-----
CSNC	---	-----
CSNE	---	-----
CSSX	---	-----

Then you use those group names in the classification rules, as shown in this panel:

```

Subsystem Type . . . . . : CICS
Description . . . . . : CICS transactions

-----Qualifier-----
Type      Name      Start
1  TNG      CICS CONV ---
1  TNG      CICS LONG ---

-----Class-----
Service   Report
DEFAULTS: CICS MED
           CICS CONV
           CICS LONG

```

For work qualifiers running longer than 8 characters, you can use a start position for each group member to indicate how far to index into the character string for a match. Note that the start position needs not be the same for all group members. Furthermore, groups of such long work qualifiers can be nested.

Example 2: Groups of long work qualifiers

Assume you want to associate all JES2 work from a certain group of accounts with service class JESSLOW, except if it originates in a certain group of departments, in which case JESFAST should be used. The example shows the rules:

```

Qualifier type . . . . . : Accounting Information
Group name . . . . . : ACCOUNTS (required)
Description . . . . . : Accounts for JESSLOW
Fold qualifier names? . . . . Y (Y or N)

Qualifier Name  Start  Description
020175         ---   -----
030275         ---   -----
040375         ---   -----
060575         ---   -----
070675         ---   -----
080775         ---   -----
090875         ---   -----
Qualifier type . . . . . : Accounting Information
Group name . . . . . : FASTDEPT (required)
Description . . . . . : Department for JESFAST
Fold qualifier names? . . . . Y (Y or N)

Qualifier Name  Start  Description
PURCHASE       8      -----
SALES          8      -----
SHIPPING       8      -----
ITDEP*        11      -----
HRDEP*        11      -----

```

Then you use those group names in the classification rules, as shown in this panel:

```

Subsystem Type . : JES Fold qualifier names? Y (Y or N)
Description . . . CICS transactions

-----Qualifier-----
Type      Name      Start
1  AIG      ACCOUNTS ---
2  AIG      FASTDEPT ---

-----Class-----
Service   Report
DEFAULTS: JES MED
           JESSLOW
           JESFAST

```

A job with accounting information '040375,SHIPPING' is then assigned service class JESFAST. Similarly, a job with accounting information '070675,D71ITDEP' is assigned service class JESFAST. A job that contains the job statement '050475,CONTROL ' is assigned service class JESSLOW, because the

department is not contained in the FASTDEPT group. A job with accounting information '020177,SALES ' is assigned the default service class JESMED, because the account number does not match group ACCOUNTS, and therefore the system never checks any sub-rules.

Using the system-supplied service classes

You can also take advantage of the system-supplied service classes to simplify the process of defining service classes and classification rules for started tasks.

Use the system-provided service classes SYSTEM and SYSSTC for your STC work. WLM recognizes certain system address spaces when they are created (like GRS, SMF, CATALOG, MASTER, RASP, XCFAS, SMXC, CONSOLE, IOSAS, WLM), puts them into the SYSTEM service class, and treats them accordingly. If a started task is not assigned to a service class, WLM manages the started task in the SYSSTC service class. Started tasks in SYSSTC are assigned a high dispatching priority. This is appropriate for started tasks such as JES and VTAM. Not all started tasks are appropriate for SYSSTC, as a CPU-intensive started task could use a large amount of processor cycles, which could cause CPU delays for other important work in the system. However, if your processor is lightly loaded, or in a 6-way, 8-way, or 10-way MP, SYSSTC might be appropriate, because that one task may not affect the ability of the remaining processors to manage the important work with goals.

The criteria for the type of work appropriate for SYSSTC are:

- Work that absolutely needs a higher dispatch priority than other work
- Work that is not going to use a lot of CPU but requires fast CPU access
- Work that is trusted, such as production-level code and not development

Note: *MASTER*, INIT and WLM always run in the SYSTEM service class and cannot be reassigned via the service definition.

The following example implements started task classification with these assumptions:

- Any started tasks not explicitly classified are given low priority.
- Started tasks are defined in three transaction name groups: HI_STC, MED_STC, and LOW_STC.
- System defaults are used for MVS-owned address spaces.
- Separate reporting is used for Master, DUMPSRV, and GRS.

```

Subsystem Type . . . . . : STC
Description . . . . . : All started tasks
-----Qualifier-----
Type      Name      Start      Service      Report
-----
1 TN      %MASTER%  ___      DISC         MASTER__
1 TN      GRS         ___      SYSTEM__    GRS__
1 TN      DUMPSRV_    ___      SYSTEM__    DUMPSRV_
1 TNG     DB2         ___      VEL60__     DB2S___

.....
1 SPM     SYSTEM__    ___      SYSTEM__    _____
1 SPM     SYSSTC__   ___      SYSSTC__   _____
1 TNG     HI_STC     ___      SYSSTC__   _____
1 TNG     MED_STC    ___      VEL35I3    _____
1 TNG     LOW_STC    ___      VEL15I5    _____
.....

```

The first rule assigns *MASTER* to report class MASTER. (Note that “SYSTEM” is shown in the service class column. In this case, it is not a true assignment as *MASTER* must *always* run in the SYSTEM service class anyway.) *MASTER* could also be classified using the SPM SYSTEM rule, but since separate reporting is desired for *MASTER*, it is classified separately. GRS and DUMPSRV are handled similarly.

The SPM rules assign started tasks created with the high dispatching priority attribute to SYSTEM, and other privileged or system tasks to SYSSTC. This allows you to let MVS manage started tasks that it recognizes as special.

Notes:

1. Note that explicitly defining the SPM rules, as in the example at hand, is optional. If they were removed from the example, then the high dispatching priority work would still be assigned to SYSTEM, and the other privileged or system tasks would still be assigned to SYSSTC, as those are the defaults. The reason for explicitly defining them here with the SPM rules is to protect yourself from inadvertently assigning them elsewhere in the rules that follow the SPM rules.
2. Note, also, that the placement of these SPM rules is crucial. If they had been declared first, then the three TN rules intended to assign *MASTER*, DUMPSRV, and GRS to report classes would have never been reached.

System tasks are those given the privileged and/or system task attribute in the IBM-supplied program properties table or in the SCHEDxx parmlib member. See the SCHEDxx chapter in [z/OS MVS Initialization and Tuning Reference](#) for a list of system tasks. An example for such a system task is DB's subsystem parameter module, the program DSNYASCP that is defined in the IBM-supplied PPT (IEFSDPPT) with the system task attribute. Without the fourth classification rule, the SPM rules would enforce all DB2 subsystem address spaces that execute this program (MSTR, DBM1, DIST, SPAS) to be classified into SYSSTC.

A transaction name group is defined to match all DB2 subsystem regions with 4-character subsystem names not already classified. Such a group for DB2 V4 could be defined as follows:

```
Qualifier type . . . . . : Transaction Name
Group name . . . . . : DB2      (required)
Description . . . . . : All non-IRLM DB2 regions
Fold qualifier names? . . . . Y (Y or N)

Qualifier Name  Start  Description
%%%%%%%%DBM1    ---    DB2 database services AS_____
%%%%%%%%MSTR     ---    DB2 master AS_____
%%%%%%%%DIST     ---    DB2 distributed data facility AS_____
%%%%%%%%SPAS     ---    DB2 stored procedure AS_____
```

Note: The **Fold qualifier names** option, set to the default Y, means that the qualifier names will be folded to uppercase as soon as you type them and press Enter. If you set this option to N, the qualifier names will remain in the case they are typed in. Leave this option set to Y unless you know that you need mixed case qualifier names in your classification rules.

Started tasks in the HI_STC transaction name group are run in service class SYSSTC, MED_STC in VEL35I3, and LOW_STC in VEL15I5. The goals on the service classes use importance to guarantee that started tasks of low value will be sacrificed if necessary to keep medium-value started tasks meeting goals. Note that this does not guarantee any relationship between the dispatching priorities that will be observed for service classes VEL35I3 and VEL15I5.

Started tasks which do not match any of the classification rules are assigned the default service class DISC. If the default service class were left blank, these started tasks would be assigned to SYSSTC. It is good practice to provide a default service class which is less important than SYSSTC so that unclassified work does not cause any performance issues.

Chapter 11. Defining tenant report classes

Optionally, classification rules can assign incoming work to a tenant report class. Tenant report classes are similar to report classes and reported likewise. However, it is required that a tenant report class be assigned to a tenant resource group. A tenant resource group allows for additional metering capabilities or association to a solution.

You can define up to 2047 tenant report classes per service definition whereby the sum of report classes and tenant report classes may not exceed 2047.

Defining tenant report classes	
Name	Tenant report class name
Description	Description of the tenant report class
Tenant Resource Group	Name of the tenant resource group associated with the tenant report class

Name

Eight character identifier of the tenant report class. Each tenant report class must be unique within a service definition and may not have the same name as a report class.

Description

Up to 32 characters that describe the tenant report class.

Tenant Resource Group

Eight character identifier of the tenant resource group that is associated with the tenant report class.

When using tenant report classes in classification rules, note the following:

- A tenant report class cannot be specified on a classification rule with a Reporting Attribute of MOBILE, CATEGORYA, or CATEGORYB. Workload management can report on processor consumption either based on tenant resource groups or based on special reporting options, but not both at the same time.
- A classification rule cannot categorize work into a tenant report class and a service class which is associated with a resource group. Work cannot be subject to capping by means of resource groups and tenant resource groups at the same time.
- As with report classes, tenant report classes are homogeneous or heterogeneous. WLM workload reporting services provide less meaningful data for heterogeneous than for homogeneous tenant report classes. Thus, it is recommended to define separate tenant report classes for each service class and assign them all to the same tenant resource group. If your tenant report class might become heterogeneous, the WLM ISPF applications displays an appropriate warning message.
- The SYSTEM and SYSSTC service classes cannot be associated with a resource group. But, through classification with tenant report classes such work could become part of a tenant resource group that has a processor or memory limit defined:
 - The processor consumption of SYSTEM and SYSSTC work is counted towards the limit of the respective Tenant Resource Group. But, because it represents very important work which is latency sensitive, it will not be capped. Therefore, it is possible that other work may need to be capped more or that the Tenant Resource Group exceeds the defined limit.
 - Address spaces classified into the SYSTEM or SYSSTC service classes will not be associated to a memory pool. Thus, the memory pool of the Tenant Resource Group can fully be used by other work associated with it.

- A memory limit overrules the storage critical attribute assigned in classification rules and any protective storage target managed through SRM. IBM recommends that you do not classify memory sensitive work into a memory pool.

Chapter 12. Defining report classes

Optionally, classification rules can assign incoming work to a report class. Workload management provides data for reporting on all of the service definition terms on a service class period and workload basis. Report classes can be used to report on a subset of transactions running in a single service class but also to combine transactions running in different service classes within one report class. In the first case, a report class is called homogeneous, in the second case it is called heterogeneous. Heterogeneous report classes can cause incorrect performance data, since the data collected is based on different goals, importance, or duration. WLM allows a caller of the workload reporting service IWMRCOLL to detect whether a report class is homogeneous or heterogeneous for a given report interval. See [z/OS MVS Programming: Workload Management Services](#) for more information on how a reporting product can receive an indication whether a report class is homogeneous or heterogeneous.

The data available for report classes include:

- Number of transactions completed
- Average response times
- Resource usage data
- State samples
- Response time distribution buckets
- Work manager delay data

Each item in the list is related to a report class period. The reporting products are advised to report response time distributions only for homogenous report class periods, where only 1 service class contributed data to the report class.

For CICS and IMS workloads, resource usage data and state samples are reported with the service classes for the regions, not the service classes assigned to the transactions.

Note that a report class can have as many periods as the largest service class within the same service definition has periods. Not all of them may be used, though. Report classes inherit periods automatically based on the transaction's service class period that is contributing to the report class. A reporting product can determine whether a report class is homogeneous within a given reporting interval and is advised to report the data as one period if the report class is heterogeneous. Based on its capabilities and options, a reporting product can report the data of a homogeneous report class as one period or as multiple periods.

For subsystem STC initiator INITs should never be in a report class.

You can assign up to a maximum of 2047 report classes, with no more than one report class per work request or transaction.

Defining report classes	
Name	Report class name
Description	Description of the report class

Name (required)

Eight character identifier of the report class.

Description (optional)

An area of 32 characters to describe the report class.

Example 1: Defining report classes

Suppose you have defined the following rules for your CICS work:

```

Subsystem Type . . . . . : CICS
Description . . . . . : CICS subsystem
                        -----Class-----
                        Service    Report
1  UI          ATMA          DEFAULTS: CICSB    ATMA
2  TN          CASH          CICSA    CASHA
2  TN          DEPOSIT       -----    DEPOSITA
3  LU          WALLST       -----    BIGDEP
1  UI          ATMC          CICSB    ATMC
2  TN          CASH          CICSB    CASHC
2  TN          DEPOSIT       -----    DEPOSITC
3  LU          WALLST       -----    BIGDEP

```

In this example, the cash transactions are separated from their deposit transactions for reporting purposes. Report class ATMA therefore, does not include all transactions with userid ATMA, because it does not include the cash or deposit transactions.

Chapter 13. Defining service definition options

First, you should understand how *service* is calculated in WLM, as described in [“Calculating the amount of service consumed”](#) on page 49.

Next, the following information describes the options that you must specify for workload management. They are:

- Whether workload management is to dynamically set I/O priorities based on performance goals. See [“Specifying I/O priority management”](#) on page 95.
- Whether workload management is to consider I/O priority groups when dynamically setting I/O priorities. See [“Enabling I/O priority groups”](#) on page 95.
- Whether workload management is to dynamically reassign parallel access volume alias addresses based on performance goals. See [“Specifying dynamic alias management”](#) on page 96.
- Whether workload management is to deactivate discretionary goal management. See [“Deactivate discretionary goal management”](#) on page 98.

All of these options can be set using the Service Definition Options panel in the WLM ISPF application, as shown in [“Working with service definition options”](#) on page 192.

Specifying I/O priority management

I/O priority queueing is used to control non-paging DASD I/O requests that are queued because the device is busy. You can optionally have the system manage I/O priorities in the sysplex based on service class goals.

The default for I/O priority management is **no**, which sets I/O priorities equal to dispatching priorities. If you specify **yes**, workload management sets I/O priorities in the sysplex based on goals.

WLM dynamically adjusts the I/O priority based on how well each service class is meeting its goals and whether the device can contribute to meeting the goal. The system does not micro-manage the I/O priorities, and changes a service class period's I/O priority infrequently.

When I/O priority management is on, I/O samples are used in the velocity formula. See [“Velocity formula”](#) on page 50 for more information.

Considerations for I/O priority management

If you specify I/O priority management, workload management dynamically sets I/O priorities based on goals and I/O activity, and includes the I/O information when calculating execution velocity. So you might see some changes in your velocity values. The recommended setting for I/O priority management is YES.

The new DASD I/O using and DASD I/O delay samples are reported even when I/O priority management is turned off. This allows you to calculate the new velocity values to plan for velocity changes.

Enabling I/O priority groups

I/O priority groups can be used to protect work which is extremely I/O-sensitive. When you assign a service class to I/O priority group HIGH, you ensure that work managed by this service class always has a higher I/O priority than work managed by service classes assigned to I/O priority group NORMAL which is the default for service classes.

The default for Enabling I/O Priority Groups is **no**, which will ignore I/O priority groups. If you specify **yes**, you enable workload management to consider I/O priority groups and setting higher I/O priorities for work in I/O priority group HIGH than for work in NORMAL.

Considerations for I/O priority groups

I/O priorities are also recognized at the I/O controller level. To ensure that all connected systems utilize the same ranges of I/O priorities consistently it is recommended that you enable I/O priority groups in the service definitions of all active systems and sysplexes sharing I/O controllers as soon as you exploit I/O priority groups in one sysplex. In other words, you may have to enable I/O priority groups even if no service class is assigned to I/O priority group HIGH in the service definition.

Enabling I/O priority groups requires to specify **yes** for I/O priority management.

Specifying dynamic alias management

This section discusses the WLM and HCD considerations for dynamic alias management.

Workload management considerations for dynamic alias management

As part of the Enterprise Storage Subsystem's implementation of parallel access volumes, the concept of base addresses versus alias addresses is introduced. While the base address is the actual unit address of a given volume, there can be many alias addresses assigned to a base address, and any or all of those alias addresses can be reassigned to a different base address. With dynamic alias management, WLM can automatically perform those alias address reassignments to help work meet its goals and to minimize IOS queueing.

Note that to be able to move aliases to other bases, the aliases first have to have been initially assigned to bases via the ESS specialist, and the bases have to have come online at some point.

When you specify yes for this value on the Service Definitions Options panel, you enable dynamic alias management globally throughout the sysplex. WLM will keep track of the devices used by different workloads and broadcast this information to other systems in the sysplex. If WLM determines that a workload is not meeting its goal due to IOS queue time, then WLM attempts to find alias devices that can be moved to help that workload achieve its goal. Even if all work is meeting its goals, WLM will attempt to move aliases to the busiest devices to minimize overall queueing.

In addition to automatically managing aliases, WLM ensures during system initialization that a minimum number of aliases is assigned to parallel access volumes with page data sets. The minimum number of aliases for a volume is:

```
2 * number_of_page_datasets - 1
```

This allows each page data set to have two I/Os active at a time, and ensures that paging intensive activities such as system dumping are not delayed by IOS queueing. This automatic enforcement of the minimum aliases only happens if dynamic parallel access volumes management is active for the device.

IMPORTANT: If you enable dynamic alias management, you must also enable I/O priority management. So you need to specify yes for both of these options on the panel. If I/O priority management is set to no, you will get only the efficiency part of dynamic alias management and not the goal-oriented management. This means that WLM will make alias moves that minimize overall IOS queueing, but these moves will not take service class goals into consideration.

HCD considerations for dynamic alias management

While you can globally enable or disable dynamic alias management on the WLM ISPF panel, you can also individually enable or disable dynamic alias management on a given device via HCD. You can do this by specifying WLMPAV=YES or NO in that device's HCD definition.

Note, however, that there is no consistency checking for dynamic alias management between different systems in a sysplex. If at least one system in the sysplex specifies WLMPAV=YES for a device, then dynamic alias tuning will be enabled on that device for *all* systems in the sysplex, even if other systems have specified WLMPAV=NO. It is recommended *not* to use dynamic alias management for a device unless all systems sharing that device have dynamic alias management enabled. Otherwise,

WLM will be attempting to manage alias assignments without taking into account the activity from the non-participating systems.

Note, also, that you can specify WLMPAV=YES or NO on both base and alias devices. The WLMPAV settings on an alias device, however, is only meaningful when the alias device is bound to a base device that is offline, as follows:

- If the base device is *offline*, then only alias devices with WLMPAV set to YES will be reassigned to other base devices.

The WLMPAV setting on the base device itself is irrelevant when the base device is offline, for either “giving” or “receiving” aliases. (Even if WLMPAV was set to YES on the base device, it cannot have new aliases assigned to it, as it is offline.)

- For any base device that is offline to one or more systems in the sysplex and online to others, the WLMPAV keyword in HCD needs to be set to NO for the base device and its aliases. You need to statically assign the desired number of aliases for the base device via the ESS Specialist. If you try to use dynamic alias management for such a device, WLM will make unpredictable alias moves.
- If the base device is *online*, then the WLMPAV settings on the aliases are ignored, as follows:
 - If WLMPAV is set to YES on the base device, then the aliases can be reassigned regardless of their WLMPAV settings.
 - If WLMPAV is set to NO on the base device, then no aliases can be reassigned, regardless of their WLMPAV settings.

For a WLMPAV=YES base device, the aliases initially assigned to it should be allowed to default to YES. The only situation where you might want to change an alias to WLMPAV=NO is if the alias is initially assigned to a WLMPAV=NO base device. Because the base is set to NO, the aliases initially assigned to it will not be moved to other bases by WLM. Then, because the aliases are set to NO, if the base is ever varied offline, the aliases remain assigned to that base and cannot be reassigned by WLM to other bases. Certain combinations of WLMPAV settings are not recommended, as described in table [Table 8 on page 97](#):

Table 8. Effects of WLMPAV settings on base and alias devices		
Base device WLMPAV setting	Alias device WLMPAV setting	Effects / recommendations
YES	YES	<ul style="list-style-type: none"> • If base is online: Base is WLM-managed. Aliases can be freely moved to and from the base device by WLM. • If base is offline: Aliases become unbound and are available to WLM to assign to other WLM-managed bases.
YES	NO	Not recommended. If base is WLM-managed, then it is not predictable which aliases will remain bound to that base when the base goes offline. If the base device is set to YES, then you should set the aliases to YES as well. (See previous option.)
NO	YES	Not recommended. If the base is not WLM-managed, then you risk losing all of its aliases when the device goes offline. (See next option.)
NO	NO	<ul style="list-style-type: none"> • If base is online: Base is not WLM-managed. The initial aliases assigned to this base remain there. • If base is offline: Aliases remain bound to the offline base device and are not available to WLM for reassignment. When the base comes back online, it retains its initial alias assignments.

In order for dynamic alias management to be most effective, you should try to spread out your aliases in the initial definition. If one base device has several alias devices while other base devices have none, it will take more time for WLM to reassign the aliases appropriately. Ideally, you should have at least two aliases assigned to each base at the outset.

For more information about HCD definitions, see [z/OS HCD Planning](#).

Deactivate discretionary goal management

Certain types of work, when overachieving their goals, can potentially have their general purpose processor resources “capped” in order to give discretionary work a better chance to run. Specifically, work that is *not* part of a resource group and has one of the following two types of goals can be eligible for this resource donation:

- A velocity goal of 30 or less
- A response time goal of over one minute

The default for Deactivate Discretionary Goal Management is **no**, which enables this kind of resource donation. If you specify **yes**, you deactivate this kind of resource donation and workload management can not cap processor resources in order to help discretionary work. Discretionary goal management is not active while system recovery boost is in effect.

Chapter 14. Defining special protection options for critical work

Several options are available to help performance administrators protect critical work. Although applicable to several other subsystem types, CICS and IMS work will particularly benefit from the enhancements described in this section:

- Long-term storage protection
- Long-term CPU protection
- Long-term I/O protection
- Modifications of transaction response time management

These three options are described, and then illustrated by an example in [“Sample scenarios” on page 103](#).

Important: The use of these options limits WLM's ability to manage the system. This may affect system performance and/or reduce the system's overall throughput.

Long-term storage protection

When you assign long-term storage protection to critical work, WLM restricts storage donations to other work. This option can be useful for work that needs to retain storage during long periods of inactivity because it cannot afford paging delays when it becomes active again. With long-term storage protection assigned, this work loses storage only to other work of equal or greater importance that needs the storage to meet performance goals.

You assign long-term storage protection with the “Storage Critical” option, found by scrolling right on the Modify Rules for the Subsystem Type panel:

```
====> Modify Rules for the Subsystem Type Row 1 to 2 of Command
===== SCROLL =====> PAG

Subsystem Type . : CICS Fold qualifier names? Y (Y or N)
Description . . : CICS Transactions

Action codes: A=After C=Copy M=Move I=Insert rule
               B=Before D=Delete row R=Repeat IS=Insert Sub-rule
               <=== More

Action  Type  Qualifier  Name  Start  Storage  Reporting  Manage Region
-----  -  -  -  -  -  -  -  -  -
-----  1  TN  COMBL*  ---  NO  NONE  N/A
-----  2  UI  COMBLD  ---  NO  NONE  N/A
-----  2  UI  COMFTP  ---  YES  NONE  N/A
```

Figure 17. Specifying the **Storage Critical** Option

Storage critical for address spaces

You can assign storage protection to all types of address spaces using classification rules for subsystem types ASCH, JES, OMVS, STC, and TSO. By specifying YES in the **Storage Critical** field for a classification rule, you assign storage protection to all address spaces that match that classification rule. An address space must be in a service class that meets the following requirements, however, before it can be storage-protected:

- The service class must have a single period.
- The service class must have either a velocity goal, or a response time goal of over 20 seconds.

- The service class must not be connected to a resource group that has a memory limit defined.

Notes:

1. These requirements only apply to the address spaces classified under subsystem types ASCH, JES, OMVS, STC, and TSO.
2. While an address space which has the storage critical attribute joins an enclave, it loses the storage critical attribute.
3. You can also specify **Storage Critical** for an address space with the SYSSTC or SYSTEM service class.

Storage critical for CICS and IMS transactions

For CICS and IMS work, you can assign long-term storage protection by specifying YES in the **Storage Critical** field in the rules for specific transactions. Once you specify YES for one transaction in a CICS/IMS service class, *all CICS/IMS transactions in that service class* will be storage-protected. If a CICS or IMS region is managed as a server by WLM (managed to the response time goals of the transactions it serves) and *any* of the transaction service classes it serves is assigned storage protection, then the CICS/IMS region itself is automatically storage-protected by WLM.

As an alternative to assigning storage protection based on specific transaction service classes, you can instead choose to assign storage protection to the region in which the transactions run. You do this by adding or modifying the STC or JES classification rule that assigns the service class to the region.

Long-term CPU protection

When you assign long-term CPU protection to critical work, you ensure that less important work will generally have a lower dispatch priority. (There are some rare exceptions, such as when other work is promoted because it is holding an enqueue for which there is contention.) This protection can be valuable for work which is extremely CPU-sensitive, such as certain CICS and IMS transactions.

Use the **CPU Critical** option on the Create or Modify a Service Class panel to assign long-term CPU protection to a specific service class:

Create a Service Class Row 1 to 2 of 2

Service Class Name	APPC9	(Required)
Description		
Workload Name	APPC	(name or ?)
Base Resource Group		(name or ?)
Cpu Critical	YES	(YES or NO)
I/O Priority Group	NORMAL	(NORMAL or HIGH)
Honor Priority	DEFAULT	(DEFAULT or NO)

Specify BASE GOAL information. Action Codes: I=Insert new period, E=Edit period, D=Delete period.

Figure 18. Specifying the **CPU Critical** option

You can assign CPU protection to service classes handling address space-oriented work, enclave work, or CICS/IMS transactions, but the service class must have only one period, and it cannot have a discretionary goal. If a CICS or IMS region is managed as a server by WLM (managed to the response time goals of the transactions it serves) and any of the transaction service classes it serves is assigned CPU protection, then the CICS/IMS region itself is automatically CPU-protected by WLM

Long-term I/O protection

When you assign a service class to I/O priority group HIGH, you ensure that work managed by this service class always has a higher I/O priority than work managed by service classes assigned to I/O priority group NORMAL. This protection can be valuable for work which is extremely I/O-sensitive.

Use the **I/O Priority Group** field on the Create or Modify a Service Class panel and specify HIGH to assign long-term I/O protection to a specific service class.

Create a Service Class		Row 1 to 1 of 1
Service Class Name	CICSHI	(Required)
Description		
Workload Name	CICSWKLD	(name or ?)
Base Resource Group		(name or ?)
Cpu Critical	NO	(YES or NO)
I/O Priority Group	HIGH	(NORMAL or HIGH)
Honor Priority	DEFAULT	(DEFAULT or NO)

Specify BASE GOAL information. Action Codes: I=Insert new period, E=Edit period, D=Delete period.

Figure 19. Specifying the **I/O Priority Group** option

I/O priority group HIGH is ignored by workload management unless I/O priority groups are enabled (see [“Enabling I/O priority groups” on page 95](#)).

Honor priority

With parameters IFAHONORPRIORITY and IIPHONORPRIORITY in parmlib member IEAOPTxx, you control at the system level whether specialty engines get help from general purpose processors when there is insufficient capacity for the workload demand. The recommended default setting for the parameters is YES. While this makes sense for important workloads that offload work to specialty engines, like CICS or DB2, there might be individual workloads for which you want to prevent the overflow from specialty engines to general purpose processors, so that the overflow cannot negatively impact the work running on general purpose processors.

In the **Honor Priority** field on the Create or Modify a Service Class panel, specify NO to prevent overflow from specialty engines to general purpose processors for work in this service class.

Create a Service Class		Row 1 to 1 of 1
Service Class Name	OFFONLY	(Required)
Description		
Workload Name	CB	(name or ?)
Base Resource Group		(name or ?)
Cpu Critical	NO	(YES or NO)
I/O Priority Group	NORMAL	(NORMAL or HIGH)
Honor Priority	NO	(DEFAULT or NO)

Specify BASE GOAL information. Action Codes: I=Insert new period, E=Edit period, D=Delete period.

Figure 20. Specifying the **Honor Priority** option

With this setting, specialty engine work that is running in the service class does not get help from general purpose processors. You might still see work in that service class accumulate small amounts of time on a general purpose processor as a by-product of routine activity to manage certain resource contention.

For transaction servers and enclave servers, consider the following:

- For CICS and IMS work, you can specify Honor Priority=NO for the service classes of the individual transactions running in a CICS or IMS region. While in a region that is not managed as a transaction server all work is always associated to a single service class, CICS and IMS regions can execute transactions that are classified into different transaction service classes. The region is then managed by WLM to the mix of service classes that it serves. In that case, only if you specify Honor Priority=NO for all transaction service classes that are running in the same region, work in that region is prevented from overflowing to general purpose processors. If any of the transaction service classes is assigned Honor Priority=DEFAULT, work in that region might overflow to general purpose processors.
- For enclave servers like WebSphere Application Server, which execute work within enclaves, the meaning of the Honor Priority option is the following:

- Work that is running within an enclave is handled according to the definition of the enclave’s service class.
- For work that is not running as part of an enclave, that is, work that is running in a TCB/SRB that has not joined an enclave, the meaning of the Honor Priority option depends on the setting of parameter MANAGENONENCLAVEWORK in parmlib member IEAOPTxx:
 - With MANAGENONENCLAVEWORK=NO, which is the default, work running outside of an enclave in the server address space is conceptually unmanaged. If you specify Honor Priority=NO for all service classes of the enclaves that are running in the same address space, non-enclave work is prevented from overflowing to general purpose processors.
 - With MANAGENONENCLAVEWORK=YES, non-enclave work in that address space is managed towards the goal of the service class of the address space. If the service class of the address space is defined with Honor Priority=NO, the non-enclave work in the address space is prevented from overflowing to general purpose processors.

Server address spaces can switch dynamically into and out of the “server” status, depending on what work they must do. If you want them to always keep the same value for the Honor Priority option, be sure that you also specify the option for the region service classes.

Modifications of transaction response time management

Use the **Manage Region Using Goals Of** field in the Modify Rules for the Subsystem Type panel to declare that a specific CICS/IMS region is not managed to the response times of the CICS/IMS transactions that it processes. Other regions are not affected by what is in this column, and that this option can be used only in STC and JES classification rules:

```

====>      Modify Rules for the Subsystem Type      Row 1 to 2 of Command
====>      ----- SCROLL =====> PAG

Subsystem Type . : STC      Fold qualifier names?   Y (Y or N)
Description . . . IBM-defined subsystem type
Action codes:  A=After      C=Copy      M=Move      I=Insert rule
                B=Before      D=Delete row  R=Repeat  IS=Insert Sub-rule
                                     <==== More
Action  Type  Qualifier  Name  Start  Storage  Reporting  Manage Region
-----  --  -
1  SY  SYST1  ---  NO  NONE  TRANSACTION
2  TN  CICS*  ---  NO  NONE  REGION
2  TN  TOR  ---  YES  NONE  TRANSACTION
2  TN  AOR*  ---  NO  NONE  BOTH
2  TN  ---  ---  NO  NONE  TRANSACTION
  
```

Figure 21. Specifying the **Manage Region Using Goals Of** option

If you specify TRANSACTION in this field (the default), the region is managed as a CICS/IMS transaction server by WLM. If you specify REGION in this field, the region is managed to the performance goal of the service class that is assigned to that region (address space). In other words, it is *not* managed as a CICS/IMS transaction server by WLM.

If you specify BOTH in this field, the region is also managed to the performance goal of the service class that is assigned to that region, but it nevertheless tracks all transaction completions so that WLM can still manage the CICS service classes with response time goals. Option BOTH should be used only for CICS TORs. All AORs should remain at the default TRANSACTION.

If you specify TRANSACTION or BOTH, RMF reports performance information as follows:

- Response time data is reported in the WLMGL SCPER report for the service class in which those transactions are running
- Response time data is also reported in the WLMGL RCLASS report for the report class in which those transactions are running

- The service classes that are served by the region are reported in the WLMGL SCLASS report for the service class in which the region is running.

If you specify REGION, only the information in the SCPER report changes. Transaction response times reported by these regions is not reported in any service class. This response time data is still reported in the RCLASS report for the transaction report class, and the service classes that are served by the region are still reported in the SCLASS report for the service class in which the region is running. In both of these cases, this information is useful if you are migrating the CICS/IMS region to transaction response time management, and need both a transaction response time benchmark and a list of the service classes the region is serving.

Sample scenarios

The following scenarios illustrate different configurations and how they would benefit from these options.

Many of the panels shown in this section are actually composites of the information that is displayed after scrolling right from the Modify Classification Rules panels.

Scenario 1

In this scenario, you want to assign storage protection and/or CPU protection to address spaces.




Figure 22. Scenario 1: Address Spaces

Suppose that you have the following classification rules:

```
Subsystem Type . . : JES          Fold qualifier names?   Y  (Y or N)
Description . . . IBM-defined subsystem type
```

Action	Type	Qualifier	Name	Start	Service	Class	Report	Storage Critical
----	1	TN	HAMLET1	---	PRODBAT	-----	-----	NO
----	1	TN	HAMLET*	---	PRODBAT	-----	-----	NO

To assign storage protection to the address space HAMLET1, change the **Storage Critical** value to field to YES in the classification rule for HAMLET1:

```
Subsystem Type . . : JES          Fold qualifier names?   Y  (Y or N)
Description . . . IBM-defined subsystem type
```

Action	Type	Qualifier	Name	Start	Service	Class	Report	Storage Critical
----	1	TN	HAMLET1	---	PRODBAT	-----	-----	YES
----	1	TN	HAMLET*	---	PRODBAT	-----	-----	NO

To assign storage protection to the address spaces HAMLET2 and HAMLET3 (but not HAMLET1), change the **Storage Critical** value to field to YES in the wildcard rule for HAMLET*:

```
Subsystem Type . . : JES          Fold qualifier names?   Y  (Y or N)
Description . . . IBM-defined subsystem type
```

Action	Type	Qualifier	Name	Start	Service	Class	Report	Storage Critical
----	1	TN	HAMLET1	---	PRODBAT	-----	-----	NO
----	1	TN	HAMLET*	---	PRODBAT	-----	-----	YES

In this instance, HAMLET1 is not protected, as it matches the HAMLET1 rule first. To protect all of the address spaces, you would specify YES in both rules.

The default values (with no CPU protection assigned) in the service class definitions would be:

```
Service Class Name . . . . . PRODBAT  (Required)
Description . . . . . Production Batch-----
Workload Name . . . . . JES          (name or ?)
Base Resource Group . . . . .          (name or ?)
Cpu Critical . . . . . NO            (YES or NO)
```

To assign CPU protection to all of these address spaces, change the value in the **Cpu Critical** field in the service class definition for PRODBAT:

```
Service Class Name . . . . . PRODBAT  (Required)
Description . . . . . Production Batch-----
Workload Name . . . . . JES          (name or ?)
Base Resource Group . . . . .          (name or ?)
Cpu Critical . . . . . YES          (YES or NO)
```

Scenario 2

The next few example scenarios will use the CICS/IMS regions shown in [Figure 23 on page 105](#).




Figure 23. Scenarios 2, 3, 4, 5: CICS/IMS regions

Suppose you have the following CICS classification rules:

Subsystem Type . . : CICS		Fold qualifier names? Y (Y or N)				
Description . . . : IBM-defined subsystem type						
		-----Qualifier-----		-----Class-----		Storage
Action	Type	Name	Start	Service	Report	Critical
----- 1	TN	AA1	----	TRXAA	AA1RPT	NO
----- 1	TN	AA2	----	TRXAA	AA2RPT	NO
----- 1	TN	BB	----	TRXBB	-----	NO
----- 1	TN	CC	----	TRXCC	-----	NO

Suppose you have the following STC classification rules to classify the CICS regions:

Subsystem Type . . : STC		Fold qualifier names? Y (Y or N)						
Description . . . IBM-defined		subsystem type						
-----Qualifier-----		-----Class-----		Storage	Manage Region			
Action	Type	Name	Start	Service	Report	Critical	Using Goals Of:	
----	1	TN	CICSREGP	---	PRODRGNS	-----	NO	TRANSACTION
----	1	TN	CICSREGT	---	TESTRGNS	-----	NO	TRANSACTION

Suppose the transaction service classes are defined as follows. (Only TRXAA is shown here. The definitions for TRXBB and TRXCC would also have NO specified in the **Cpu Critical** field.)

```
Service Class Name . . . . . TRXAA (Required)
Description . . . . . Transactions AA1, AA2
Workload Name . . . . . JES (name or ?)
Base Resource Group . . . . . (name or ?)
Cpu Critical . . . . . NO (YES or NO)
```

Suppose the regions' service classes are defined as follows (PRODRGNS shown here, TESTRGNS would look the same):

```
Service Class Name . . . . . PRODRGNS (Required)
Description . . . . . Production Regions
Workload Name . . . . . STC (name or ?)
Base Resource Group . . . . . (name or ?)
Cpu Critical . . . . . NO (YES or NO)
```

In this scenario, assume that the regions are running normal, non-conversational transactions. Response time goals are appropriate, and there is enough activity so that WLM can manage the regions as servers virtually all of the time. Transaction AA1 is very important to the business, and you wish to give it both storage and CPU protection.

In this case, protection on a transaction service class level is sufficient. This approach allows you to focus on protecting specific transactions rather than the regions that process them. The protection will be inherited by any regions in which the transactions run, as long as WLM is allowed to manage the region to the transactions' goals. ([“Scenario 5”](#) on page 108 shows what happens when WLM is *not* allowed to manage the region to the transactions' goals.)

Assign storage protection to transaction AA1 using the CICS classification rule:

```
Subsystem Type . . : CICS          Fold qualifier names?   Y (Y or N)
Description . . . : IBM-defined subsystem type

Action  -----Qualifier-----  -----Class-----  Storage
Type      Name      Start  Service      Report      Critical
----  1  TN      AA1      ---  TRXAA      AA1RPT      YES
----  1  TN      AA2      ---  TRXAA      AA2RPT      NO
----  1  TN      BB       ---  TRXBB      -----      NO
----  1  TN      CC       ---  TRXCC      -----      NO
```

Transaction service class TRXAA runs only in the CICSREGP region, and not in CICSREGT; therefore, CICSREGP will inherit the storage protection, and CICSREGT will *not* inherit the storage protection.

Assign CPU protection to the transaction service class TRXAA in the service class definition:

```
Service Class Name . . . . . TRXAA      (Required)
Description . . . . . CICS Transactions-----
Workload Name . . . . . CICS      (name or ?)
Base Resource Group . . . . . ----- (name or ?)
Cpu Critical . . . . . YES      (YES or NO)
```

Any region serving any TRXAA transactions, even one serving AA2 only, inherits CPU protection. As was true for storage protection, CICSREGT will *not* inherit CPU protection because it does not serve transaction service class TRXAA.

Reporting products which display data about the regions themselves will not show that storage and CPU protection was specified, but will show that they were protected while serving the transactions. (See [“Reporting”](#) on page 110.) Service class reports will show the storage and CPU protection assigned to the TRXAA transaction service class.

Scenario 3

In this scenario, again using the CICS regions shown in [Figure 23](#) on page 105, assume that the regions are running non-conversational transactions, but with periods of low activity during which WLM may stop managing them as servers. During this time, it is more likely that the regions' pages will be stolen by competing workloads. In this scenario, assume that transaction BB needs storage and CPU protection.

Protection on a transaction service class level is once again useful, ensuring that the transactions will be protected wherever they run. The regions themselves should also be protected, as WLM may not manage them as servers during the low activity periods.

Assign storage protection to transaction BB using the CICS classification rules:

```
Subsystem Type . . : CICS          Fold qualifier names?   Y (Y or N)
Description . . . : IBM-defined subsystem type

Action  -----Qualifier-----  -----Class-----  Storage
Type      Name      Start  Service      Report      Critical
----  1  TN      AA1      ---  TRXAA      AA1RPT      NO
----  1  TN      AA2      ---  TRXAA      AA2RPT      NO
----  1  TN      BB       ---  TRXBB      -----      YES
----  1  TN      CC       ---  TRXCC      -----      NO
```


Also, assign storage protection to the regions themselves using the STC classification rules:

```
Subsystem Type . . : STC          Fold qualifier names?   Y  (Y or N)
Description . . . IBM-defined subsystem type

Action      -----Qualifier-----      -----Class-----      Storage  Manage Region
          Type      Name      Start      Service      Report      Critical Using Goals Of:
---- 1  TN      CICSREGP    ---      PRODRGNS    -----      YES      TRANSACTION
---- 1  TN      CICSREGT    ---      TESTRGNS    -----      YES      TRANSACTION
```

Assign CPU protection to the transaction service classes TRXBB (the **Cpu Critical** field in the TRXAA and TRXCC service class definitions would remain set to NO):

```
Service Class Name . . . . . TRXBB      (Required)
Description . . . . . CICS Transactions
Workload Name . . . . . CICS      (name or ?)
Base Resource Group . . . . . ----- (name or ?)
Cpu Critical . . . . . YES      (YES or NO)
```

And also to the regions themselves (PRODRGNS shown here, TESTRGNS would also specify YES in the **Cpu Critical** field):

```
Service Class Name . . . . . PRODRGNS (Required)
Description . . . . . CICS Regions
Workload Name . . . . . STC      (name or ?)
Base Resource Group . . . . . ----- (name or ?)
Cpu Critical . . . . . YES      (YES or NO)
```

Note that since both CICSREGP and CICSREGT run transaction BB, *both* regions must be protected.

Reporting products which display data about the regions will show that both CPU and storage protection was specified. (See “Reporting” on page 110.) While the regions are serving transactions, protection will occur if either the regions themselves or any of their served transaction service classes are protected.

Scenario 4

In this scenario, again using the CICS regions shown in Figure 23 on page 105, assume that the regions are running conversational transactions, and response time goals are not appropriate. By exempting the regions from management to the transaction response time goals, the regions will instead be managed according to the goal of the service class assigned to those regions. (If either storage or CPU protection is needed, that goal must be a velocity goal, since discretionary goals are not eligible for storage or CPU protection.) In this scenario, assume that only the production region CICSREGP needs protection.

Assign storage protection to the CICSREGP region. Also, in the same panel, exempt both regions from management to the transaction response time goals:

```
Subsystem Type . . : STC          Fold qualifier names?   Y  (Y or N)
Description . . . IBM-defined subsystem type

Action      -----Qualifier-----      -----Class-----      Storage  Manage Region
          Type      Name      Start      Service      Report      Critical Using Goals Of:
---- 1  TN      CICSREGP    ---      PRODRGNS    -----      YES      REGION
---- 1  TN      CICSREGT    ---      TESTRGNS    -----      NO      REGION
```

Assign CPU protection to the PRODRGNS service class (the **Cpu Critical** field in the TESTRGNS service class definitions would remain set to NO):

```
Service Class Name . . . . . PRODRGNS (Required)
Description . . . . . CICS Regions
Workload Name . . . . . STC      (name or ?)
Base Resource Group . . . . . ----- (name or ?)
Cpu Critical . . . . . YES      (YES or NO)
```

Reporting products which display data about the regions will show that CPU or storage protection was specified based on the regions' storage protection value and the CPU protection value of the regions' service classes. (See “Reporting” on page 110.)

Scenario 5

This scenario is similar to [“Scenario 2” on page 104](#), but here you'll see what happens when WLM is not allowed to manage one of the regions to the transactions' goals, and how this will prevent protection of a transaction. In this case, assume that it is transaction BB that you wish to give both storage and CPU protection, and assume that at the same time you have exempted region CICSREGT from management to the transaction response time goals.

You've assigned the storage protection to transaction BB using the CICS classification rule:

Subsystem Type		: CICS		Fold qualifier names?		Y (Y or N)	
Description		. . . IBM-defined		subsystem type			
Action	Type	Qualifier	Name	Start	Service	Report	Storage
-----	1	TN	AA1	---	TRXAA	AA1RPT	NO
-----	1	TN	AA2	---	TRXAA	AA2RPT	NO
-----	1	TN	BB	---	TRXBB	-----	YES
-----	1	TN	CC	---	TRXCC		NO

You have also assigned CPU protection to the transaction service class TRXBB in the service class definition:

```

Service Class Name . . . . . TRXBB      (Required)
Description . . . . . CICS Transactions_____
Workload Name . . . . . CICS          (name or ?)
Base Resource Group . . . . . _____ (name or ?)
Cpu Critical . . . . . YES           (YES or NO)

```

In the classification rule for CICSREGT, you have exempted the region from management to the transaction response time goals:

Subsystem Type . : STC						Fold qualifier names? Y (Y or N)
Description . . . IBM-defined subsystem type						
Action	Type	Name	Start	Service	Report	Storage Manage Region Critical Using Goals Of:
-----Qualifier-----				-----Class-----		
----	1 TN	CICSREGP	---	PRODRGNS	-----	YES TRANSACTION
----	1 TN	CICSREGT	---	TESTRGNS	-----	YES REGION

As illustrated in [Figure 23 on page 105](#), transaction BB runs in both regions, CICSREGP and CICSREGT. *Since WLM will not manage region CICSREGT to transaction response times, it will not inherit storage or CPU protection from the TRXBB transaction service class.* Transaction BB will therefore *not* run with storage or CPU protection in region CICSREGT.

Scenario 6

Transactions




Figure 24. Scenario 6: CICS Regions Adhering to a Work Manager/Consumer Model

Suppose you have the following STC classification rules to classify the CICS regions:

Subsystem Type . . : STC		Fold qualifier names? Y (Y or N)	
Description . . . IBM-defined subsystem type			
Action	-----Qualifier-----	-----Class-----	Storage
----	Type Name Start	Service Report	Critical
----	1 TN TOR ---	VEL80I1	NO
----	1 TN AOR* ---	VEL60I2	NO
			Manage Region
			Using Goals Of:
			TRANSACTION
			TRANSACTION

In this scenario, assume that the CICS regions adhere to a Work Manager/Consumer model. This means that the TOR acts as a work receiver of requests from the work originator and as a sender of results back to the work originator. The TOR just distributes the work to consumer processes in the AORs which start application programs to perform the function behind the work requests.

The TOR typically only requires short access to resources, but it also needs very fast access in order to avoid being a bottleneck. The AORs typically run more resource intensive programs which do not require the same fast access to the resources.

In this setup, when contention increases on the system, WLM has no way to give faster access to TORs than to AORs, if no other workload like batch work with lower service goals exists that can be demoted. At higher utilization levels, typically above 85%, a noticeable queue delay within the TORs can be recognized. This reduces the end-to-end response times of the CICS transactions and the throughput of the CICS work.

One could avoid this problem by exempting the CICS regions from being managed towards response time goals:

```
Subsystem Type . : STC          Fold qualifier names?   Y  (Y or N)
Description   . . . IBM-defined subsystem type
```

Action	Type	Name	Start	Service	Report	Storage	Manage Region
1	TN	TOR	---	VEL80I1	---	NO	Using Goals Of: REGION
1	TN	AOR*	---	VEL60I2	---	NO	REGION

The negative effect of this solution is that CICS transaction statistics are no longer available for managing the CICS work and only through classes for reporting purposes. This workaround in fact reduces WLM's capabilities to a reporting only function for CICS.

The best solution to solve this issue is to use option BOTH for the TOR:

```
Subsystem Type . : STC          Fold qualifier names?   Y  (Y or N)
Description . . . IBM-defined subsystem type
```

-----Qualifier-----				-----Class-----		Storage	Manage Region
Action	Type	Name	Start	Service	Report	Critical	Using Goals Of:
----	1	TN		VEL80I1	-----	NO	BOTH
----	1	TN		VEL60I2	-----	NO	TRANSACTION

This option allows WLM to manage a region by the goals of the regions but also ensures that the region tracks all transaction completions correctly so that WLM can still manage the CICS service classes with response time goals. The new option should only be used for CICS TORs. All AORs should remain at the default (TRANSACTION). In addition, the service class for the CICS TORs should be defined with a higher importance than the service classes for the CICS transactions.

The result is that the CICS TORs now can access the resources they need as fast as possible. Because TORs consume typically only between 5 to 10% of the total CICS resource consumption the goals of the CICS service classes still manage the important parts of the CICS workloads and ensure that work is managed towards response times.

Reporting

Because storage protection can be implicitly applied to an entire transaction service class, and because WLM may or may not be honoring a customer's storage or CPU protection assignment at any given time (for example, due to a RESET), there are seven different “states” that can be reported:

- Storage protection has been explicitly assigned on a classification rule
- Storage protection has been implicitly assigned to a CICS/IMS transaction service class (because it was assigned to at least one transaction in that service class)
- Storage protection is currently being honored
- CPU protection has been explicitly assigned in a service class definition
- CPU protection is currently being honored
- Exemption from transaction response time management has been explicitly assigned on a classification rule.
- Management of a region using the goal of both region and transaction service classes has been explicitly assigned on a classification rule.

These states are reported in SMF type 30 and type 79.1 records. States that apply to an entire service class are also reported in SMF 72.3 records.

Option summary

The following table summarizes the effects of the storage protection, CPU protection, and exemption from transaction response time management options:

<i>Table 9. Summary of options for storage protection, CPU protection, and exemption from transaction response time management</i>	
When you...	WLM...
Assign CPU protection to a service class used to manage address spaces and/or enclaves.	Protects any address space or enclave managed according to the goals of that service class. Address spaces being managed as servers are managed according to the goals of the served transactions.
Assign storage protection to an ASCH, JES, OMVS, STC, or TSO address space.	Protects any address space which matches the classification rule, regardless of its server status. Address spaces currently running in multiperiod service classes or in service classes with a short response time goal (20 seconds or less) are excluded from protection.
Assign CPU or storage protection to a CICS or IMS transaction.	Protects any regions recognized as serving that CICS/IMS transaction, unless you prevent WLM from managing the regions as servers. Note that once storage protection is assigned to any transaction in a service class, then <i>all</i> transactions in the same service class become storage protected.
Manage a CICS or IMS region using the goals of the region.	Is prevented from managing the region according to the response time goals of the transactions it is running. It does not recognize the region as a server. The region is managed using the goal of the service class assigned to the region. Transaction response time data is not reported in the service classes to which the transactions are classified, but is still reported in their report classes, if assigned.
Manage a CICS or IMS region using the goals of both region and transaction.	Manages the region using the goal of the service class assigned to the region. This also ensures that the region tracks all transaction completions correctly so that it can still manage the CICS service classes with response time goals. The option should only be used for CICS TORs. All AORs should remain at the default (TRANSACTION). In addition, the service class for the CICS TORs should be defined with a higher importance than the the service class for the CICS transactions.
Issue the RESET QUIESCE command.	Will no longer enforce CPU protection. All other options remain unchanged.
Issue the RESET SRVCLASS or RESET RESUME command.	Will assign CPU protection if the target service class has the CPU protection attribute. All other options remain unchanged.

Chapter 15. Defining application environments

An application environment is a group of application functions requested by a client that execute in server address spaces. Workload management can dynamically manage the number of server address spaces to meet the performance goals of the work making the requests. Alternatively, the server address spaces can be started and stopped manually or by automation.

Each application environment should represent a named group of server functions that require access to the same application libraries. Grouping server functions helps simplify library security, application program change control, performance management, and system operation.

For example, an application environment could be one or more DB2 stored procedures. DB2 could have an associated application environment named PAYROLL that handles specific types of stored procedure requests.

Getting started with application environments

The following conditions are required before an application environment can be used:

- The work manager subsystem must have implemented the workload management services that make use of application environments. Examples of IBM-supplied work managers that use application environments are:
 - DB2 (subsystem type DB2)
 - SOMobjects (subsystem type SOM)
 - WebSphere Application Server (subsystem CB)
 - Internet Connection Server, Domino Go Webserver, or IBM HTTP Server Powered by Domino (IHS powered by Domino)
 - IBM MQ Workflow (subsystem type MQ)

Refer to subsystem documentation to determine if the subsystems used in your installation make use of application environments.

- One or more application environments must be defined in the workload management service definition. The subsystem reference information should provide guidance for logically grouping applications into application environments.
- The subsystem's work requests must be associated with the appropriate application environment. This step is unique for each subsystem and should be described in the subsystem reference information.

If you request through the service definition that server address spaces be automatically managed, workload management starts and stops server spaces as needed. For example, when a DB2 stored procedure request comes into the system, workload management determines whether there is a server address space to process the work, and if there is, makes the work available to the server. If there is no server address space available, workload management creates one.

Table 10 on page 113 shows the IBM-supplied subsystems that use application environments, the types of requests made by each subsystem, and where the subsystem stores the information that maps the work to application environments.

Table 10. IBM-supplied Subsystems Using Application Environments		
Application Environment Subsystem Type	Request Type	Application Environment Mapping
CB	WebSphere Application Server object method requests	Server group name

Table 10. IBM-supplied Subsystems Using Application Environments (continued)

Application Environment Subsystem Type	Request Type	Application Environment Mapping
DB2	Stored procedure requests	DB2 SYSIBM.SYSROUTINES catalog table
IWEB	Hyper Text Transfer Protocol (HTTP) requests	Web configuration file
MQ	IBM MQ Workflow requests	MQ process definition for the WLM-managed queue (APPLICID) field
SOM	SOM client object class binding requests	Implementation repository

Specifying application environments to workload management

Note: For applications exploiting the service for defining application environments (IWM4AEDF), you may not need to define the application environment manually. For further information, refer to the appropriate product documentation.

To define an application environment, specify:

- The subsystem type under which the applications are running.
- The JCL procedure to start server address spaces if you wish workload management to automatically manage the number of servers.
- If a JCL procedure is specified, any required start parameters.
- Whether requests can execute in multiple server address spaces and on multiple systems.

Application Environment

Application environment name.

Description (optional)

Description of the application environment.

Subsystem Type

The subsystem type associated with the application environment, such as SOM, DB2, or IWEB.

Procedure Name (optional)

The name of the JCL procedure for starting the address space. The procedure name may be omitted.

Start Parameters (optional)

Parameters required by the JCL procedure to start the address space.

Starting of address spaces

Specify whether workload management can start multiple or single server address spaces for a subsystem instance.

Application Environment

(Required) One to 32 character name of the application environment. You must use this name when specifying to the subsystem how to map work to the application environments. You also use this name in operator commands when performing actions on the application environment. The name cannot begin with the letters SYS.

For guidance in mapping subsystem work to application environments, see the subsystem reference information.

If you check the authorization of application environment server address spaces through a SAF product, such as RACF, or if you plan to do so, choose an application environment name that does not exceed 27 characters. There is a restriction with respect to the maximum length of a server profile name passed to the SAF product (see also [“Authorizing application environment servers”](#) on page 121).

Description

(Optional) Up to 32 characters describing the application environment.

Subsystem Type

(Required) Subsystem type is the one to four character name of the subsystem using application environments. This subsystem type is provided to workload management when the subsystem initializes. The types currently in use are listed in [Table 10 on page 113](#). For a subsystem not listed, refer to the subsystem's documentation for the required information.

Note: If you are using DB2 stored procedures, note that the subsystem type DB2 specified here for an application environment is used only for identifying the DB2 subsystem when it begins to use the application environment. There is no connection between this value and classification. For more information on classification, see [Chapter 10, “Defining classification rules,” on page 57](#).

Procedure Name

(Optional) Procedure name is the one to eight character name of the JCL procedure that workload management uses to start a server for the application environment work requests. Refer to the appropriate subsystem documentation for sample JCL procedures to use.

To ensure that an application environment uses the same JCL procedure across the sysplex, either (1) identical procedure proclibs must be maintained across the sysplex or (2) all the procedures must be stored in a single, shared proclib.

If you specify a procedure name, “automatic” control is in effect, and workload management manages the number of servers. If you do not specify a procedure name, manual control is in effect, and servers must be started manually or by automation. In either case, workload management processes work requests from the application environment according to the goals defined for the work once a server address space is available.

Start Parameters

(Optional) Start parameters are the parameters required for the JCL procedure defined in **Procedure Name**. These parameters define how workload management should start the server address spaces. Specify parameters here that you would use for starting a server address space with an MVS START command.

Note that any parameters you specify here override the parameters specified in the JCL procedure for that server.

If you specify the symbol &IWMSSNM, workload management substitutes the subsystem instance name provided to workload management when the subsystem connected to it. Refer to the subsystem reference information to determine the instance name and the appropriate parameters to specify.

Starting of server address spaces for a subsystem instance

(Required) You can limit the number of servers for a subsystem instance. Reasons for limiting the number of servers might be a need to serialize or limit application environment server activity while testing, or a restriction in the subsystem itself. There are three options:

- Managed by WLM
- Limited to a single server address space per system
- Limited to a single server address space per sysplex

The options that are valid for a subsystem depend on its scope as described in the next section. For guidance on deciding which options to use, and to find out which options are valid for subsystems not explicitly covered in the next section, see the subsystem reference information.

Example of an application environment

To enable workload management to dynamically start server address spaces to process work from a DB2 payroll application environment, do the following:

- Define the application environment

Application Environment

PAYROLL

Description

DB2 Payroll APPLENV

Subsystem Type

DB2

Procedure Name

PAYPROC

Start Parameters

DB2SSN=&IWMSSNM

Server Start

Managed by WLM

When payroll work arrives into the system, workload management manages system resources to meet the goals defined for the work, and dynamically starts and stops server address spaces to process the work.

Selecting server limits for application environments

The previous section describes an option how servers of an application environment can be started. You can allow WLM to manage the number of servers or you can limit them. This option is applied independently for each instance of a subsystem. For IBM-supplied subsystems, you can usually use the default value supplied by the WLM ISPF application. This section defines subsystem instance as it is used by application environments and tells how to select the server start option for IBM-supplied subsystems.

A *subsystem instance* for an application environment is defined as a unique combination of:

- Subsystem type, as specified in the service definition for an application environment, and
- Subsystem name, as defined by the work manager subsystem when it connects to workload management.

A subsystem instance using application environments has one of two different scopes, single-system or sysplex, depending on workload management services used by its subsystem type.

If the scope is single-system, all the server address spaces for the subsystem instance are created on the system where the instance connected to workload management.

If the scope is sysplex, the server spaces can be spread across the sysplex, with workload management starting at most one server on each system. The installation may choose to start additional servers on a system through the START command or automation, and these servers are equally eligible to accept application environment work as the one started automatically.

Note that this scope applies only to application environment server management. A subsystem with single-system scope for application environments, can still perform sysplex-wide functions for other purposes.

You can specify how the number of servers for a subsystem instance will be started when defining the application environment in the service definition. Reasons for limiting the number of servers might be a need to serialize or limit application environment server activity while testing, or a restriction in the subsystem itself. There are three options how to start servers:

- Managed by WLM
- Limited to a single server address space per system
- Limited to a single server address space per sysplex

Options 1 and 2 apply when the subsystem type supports single-system scope. Options 1 and 3 apply when the subsystem type supports sysplex scope. “Managed by WLM” for single-system scope means any number of servers may be created for the subsystem instance on the system where it connected to workload management. “Managed by WLM” for sysplex scope means servers may be created for the subsystem instance on any number of systems in the sysplex.

The IBM-supplied subsystems using application environments, their scopes, and valid server limit options are as follows:

Table 11. Application environment server characteristics

Subsystem type	Scope	Valid server limit options
CB	system	<p>1.) Managed by WLM</p> <p>Use this to address the WLM managed servers. This is the default for the WebSphere Application Server.</p> <p>2.) Limited to a single server address space per system</p> <p>Use this if you are testing and want to temporarily limit the number of servers. The WebSphere Application Server itself does not have a requirement for limiting servers.</p>
DB2	system	<p>1.) Managed by WLM</p> <p>Use this to address the WLM managed servers. This is the default for DB2.</p> <p>2.) Limited to a single server address space per system</p> <p>Use this if the DB2 stored procedure cannot execute concurrently in multiple address spaces. This option should be used if a stored procedure is to be run in “debug” mode and writes to a trace.</p>
IWEB	system	<p>1.) Managed by WLM</p> <p>Use this to address the WLM managed servers. This is the default for Internet Connection Server, Domino Go Webserver, or IBM HTTP Server Powered by Domino (IHS powered by Domino).</p> <p>2.) Limited to a single server address space per system</p> <p>Use this if you are testing and want to temporarily limit the number of servers. The Internet Connection Server, Domino Go Webserver, or IBM HTTP Server Powered by Domino (IHS powered by Domino) does not have a requirement for limiting servers.</p>
MQ	system	<p>1.) Managed by WLM</p> <p>Use this to address the WLM managed servers. This is the default for IBM MQ Workflow.</p> <p>2.) Limited to a single server address space per system</p> <p>Use this if you are testing and want to temporarily limit the number of servers. IBM MQ Workflow itself does not have a requirement for limiting servers.</p>
SOM	sysplex	<p>3.) Limited to a single server address space per sysplex</p> <p>SOMObjects requires this limit on the number of servers for an application environment. This option is enforced by the WLM application.</p>

For guidance on deciding which option to use, or to find out what options are valid for other subsystems that use application environments, refer to the subsystem reference information.

How WLM manages servers for an application environment

You allow WLM to manage the number of servers and server address spaces for an application environment if you choose the option “Managed by WLM” for starting servers of a subsystem instance. In this case, WLM has the ability to consider the delays of work requests sent to the application environments in its algorithms to supervise the goal achievement of your service classes and to adjust

the resources needed by them. Servers and server address spaces are considered resources which can be made available to the work using an application environment. This is illustrated in the following example:

1. If a DB2 stored procedure request comes into the system, DB2 classifies the work request to WLM and WLM assigns a service class to it. DB2 then queues the work request to the application environment under which the stored procedure should be executed.
2. WLM queues the work requests for each application environment by service class. This allows WLM to understand how the queuing affects the goal achievement of the service class.
 - When the first request is queued to an application environment, workload management detects that there are no active servers for the request, and automatically starts one.
3. From then on, WLM collects statistics about the queue delays for each application environment and each service class used for the work requests. These queue delays then become part of the WLM algorithms which assess the goal achievement of the service classes and adjust the resources as needed.
 - If, for example, the service class for the DB2 stored procedure requests do not meet their goals, WLM determines which resources are needed to help the work in the service class.
 - If queue delay shows up as the dominating factor, WLM assesses how many additional servers are needed to help the work to meet their goals or at least to see a significant improvement.
 - Once the number of servers has been assessed, WLM makes sure that the system resources are available to start the necessary server address spaces for the required number of servers. During this step, WLM makes sure that more important work is not affected and that the system does not run into a shortage situation because of the new server address spaces. Among the resources considered are:
 - Processor
 - Real storage
 - Auxiliary storage constraints
 - Common storage (SQA) constraints
4. When all tests have completed successfully, WLM starts the required number of server address spaces.

In cases where the system has low utilization, WLM is also able to start one additional server address space for the application environment if this may immediately help the work and it is granted that sufficient resources remain available for other work in the system.

Server address spaces are stopped when the utilization of the servers drops and many servers become idle. WLM then returns the resources used by the server address spaces and thus allows other work to utilize the system.

Using “Managed by WLM” is the optimal way to manage the number of server address spaces. It provides the best performance for the work executed under the application environment and only uses the resources which are optimal based on the goal for the work and the overall utilization of the system.

Using application environments

Application environments can be manually controlled by the installation or automatically controlled by workload management. Note, however, that Dynamic Application Environments can only be automatically controlled by workload management. All of the applications in an application environment are supported by a single JCL startup procedure. Defining the name of this startup JCL procedure to workload management indicates that workload management should control the server address spaces. This is called automatic control. If you omit the name of the JCL procedure in the application environment definition, then manual control is in effect.

Under manual control, the installation must create and delete, as needed, the server address spaces for each application environment. Note that the VARY WLM,APPLENV command can be used to terminate manually started server address spaces (through the quiesce or refresh options), but it will not restart

them. For more information on the **VARY WLM,APPLENV** command, see [“Using operator commands for application environments”](#) on page 119.

Under automatic control, workload management creates server address spaces as started tasks using the JCL procedure specified in the application environment definitions. The startup parameters may be contained in either the JCL procedure defined for each application environment or in the application environment definition. When the server address spaces are no longer needed, workload management deletes them.

Under automatic control, the quantity of server address spaces is totally controlled by workload management. If an operator or automation starts or cancels the server address spaces under automatic control, workload management will:

- Use servers not started by workload management as if they were started by workload management
- Terminate servers not started by workload management if they are not needed
- Replace a server address space that was unexpectedly cancelled

Note: You should use the **VARY WLM,APPLENV** or **VARY WLM,DYNAPPL** command to manage application environment servers rather than the CANCEL command. If there are more than five server cancellations in 10 minutes, workload management stops creating new servers for the application environment. For more information on stop conditions, see [“Handling error conditions in application environments”](#) on page 121.

Managing application environments

Once an application environment is defined, and there are server address spaces in use by the subsystem, you can use operator commands to manage the application environment. There are options on the **VARY WLM,APPLENV** or **VARY WLM,DYNAPPL** command that allow you to quiesce, resume, or refresh application environments. These functions allow you, for example, to make changes to the JCL procedure, start parameters, or application libraries, and ensure that new work requests run with the modified information. The resume function also allows you to recover from error conditions that have caused workload management to stop an application environment.

An action taken for an application environment is saved in the WLM couple data set and is not discarded across an IPL. For example, if a quiesce action is in effect and the system is IPLed, the quiesce action remains in effect. You can query the current state of an application environment using the **DISPLAY WLM,APPLENV** or **DISPLAY WLM,DYNAPPLENV** command. The scope of both the **VARY** and **DISPLAY** commands for application environments is sysplex-wide, that is, they affect the application environment on all systems in the sysplex, regardless of the scope of the subsystem using the application environment. The sysplex scope of the command ensures that an application environment remains consistent across the sysplex, especially where there are shared resources.

This section first introduces the commands that can be used to perform actions on an application environment. Then it describes activities that make use of the commands and describes other conditions that affect the state of an application environment.

Using operator commands for application environments

An application environment initially enters the AVAILABLE state when the service policy that contains its definition is activated. AVAILABLE means the application environment is available for use, and servers are allowed to be started for it. There are three options on the VARY command that you can use to change the state of an application environment after it has been made available:

- **VARY WLM,APPLENV=xxxx,QUIESCE** or
VARY WLM,DYNAPPL=xxxx,QUIESCE

The quiesce option causes workload management to request the termination of server address spaces for the application environment upon completion of any active requests. Additional work requests are not handled by the servers, although work requests can continue to be queued, waiting for a server. If you do not want work queued, use subsystem functions to stop the queueing.

You can issue a quiesce action for an application environment that is in the AVAILABLE state. When a quiesce action is issued for an application environment, it first enters the QUIESCING state until all servers have been requested to terminate. It then enters the QUIESCED state.

- VARY WLM,APPLENV=*xxxx*, RESUME or
VARY WLM,DYNAPPL=*xxxx*, RESUME

The resume option restarts an application environment that was previously quiesced and is in the QUIESCED state. It indicates to workload management that server address spaces can once again be started for this application environment. The new servers process any queued requests and all new requests.

When a resume action is issued for an application environment, it first enters the RESUMING state until all systems in the sysplex have accepted the action. It then enters the AVAILABLE state.

- VARY WLM,APPLENV=*xxxx*, REFRESH or
VARY WLM,DYNAPPL=*xxxx*, REFRESH

The refresh option requests the termination of existing server address spaces and starts new ones in their place. Existing servers finish their current work requests and end. The new servers process any queued requests and all new requests.

You can issue a refresh action for an application environment that is in the AVAILABLE state. When a refresh action is issued for an application environment, it first enters the REFRESHING state until all servers have been requested to terminate. It then enters the AVAILABLE state.

Making changes to the application environment servers

The command options described are intended to allow changes to application environments without having to shut down the application itself. Use the quiesce function when you want to do one of the following:

- Perform maintenance on application program libraries statically allocated to server address spaces.
- Update the JCL procedure for an application environment.

When you are ready to put the changes into effect, quiesce the application environment, make the changes to the libraries or service definition as needed, then use the resume function to start new servers with the changed information.

You can also use the quiesce function to suspend execution after repeated application failures or errors. After the errors are corrected, you can resume the application environment.

You may have an application environment where the servers keep application program executable modules in a private cache. If you update the application program, you need to ensure that all copies of the changed modules are replaced wherever they are cached. Use the refresh function to do this.

Changing the definition of an application environment

Workload management initiates a refresh when one of the following changes are made to the application environment definition and activated:

- The JCL procedure name is changed.
- The application environment is switched to automatic control, that is, the JCL procedure name was previously left blank, but now one is provided.
- The server start parameters are changed.
- The limit on server address spaces is changed, for example, from “Managed by WLM” to “Limited to a single address space per system”.

If an application environment is deleted from the service definition, it enters the DELETING state. After workload management requests the termination of all associated servers, the application environment is no longer displayed at all by the **DISPLAY WLM,APPLENV** or **DISPLAY WLM,DYNAPPLENV** command.

Handling error conditions in application environments

Workload management stops the creation of new server address spaces when one of the following conditions exist:

- JCL errors in the procedure associated with the application environment.
- Coding errors in the server code which cause five unexpected terminations of server address spaces within ten minutes.
- Failure of the server address space to connect to workload management due to an invalid invocation environment or invalid parameters.

The application environment first enters the STOPPING state, then the STOPPED state after all systems in the sysplex have accepted the action. In STOPPED state, no new servers are created. Any existing server address spaces continue to process work, and workload management is able to accept new work. If there are no existing servers, then workload management rejects any new work requests.

In STOPPED state, you can make changes to libraries, change the procedure, or make any other changes needed to repair the condition that caused workload management to stop the application environment. When the problem is resolved, use the resume function to allow workload management to start new servers. The application environment enters the RESUMING state, then the AVAILABLE state after all systems in the sysplex have accepted the action.

Note: If you want to ensure all servers are restarted after a STOPPED state, especially after the JCL procedure or libraries have been modified, you should issue a quiesce function prior to the resume. This ensures there are no servers remaining active that are using back-level information.

Authorizing application environment servers

Because the server address spaces started on behalf of an application environment can run in problem program state, workload management enables you to check the validity of a server through an SAF product such as RACF. When the server is being created, workload management makes an SAF call using a new SERVER class to check whether the server is valid for the application environment. If you do not have the SERVER class defined to your SAF product, workload management allows the server address space to be started.

You can use the SERVER and STARTED classes with a SAF product to restrict access to application environment servers. For example, if you are using DB2, SOM or IWEB servers with application environments, you first associate a userid with the MVS procedure name being used to start the server. This is done using the STARTED resource class or by changing ICHRIN03 (started procedures table). Then you use the SERVER resource class to authorize this userid, and possibly others, to become a server for DB2 stored procedures, SOM method requests, or Internet Connection Server web requests.

Example for restricting access to application environment servers

In this example, the installation has the following situation:

- MVS JCL procedures for DB2 stored procedure servers: PAY1, PAY2, PER1, PER2

These are the JCL procedures that workload management uses to start the DB2 servers that handle stored procedure calls.

- DB2 subsystem names: DB2A and DB2B

These are the subsystem names used when the DB2 subsystem connects to workload management.

1. Activate STARTED and SERVER classes (if not already done):

```
SETR CLASSACT(STARTED)  RACLIST(STARTED)  GENERIC(STARTED)
SETR CLASSACT(SERVER)   RACLIST(SERVER)    GENERIC(SERVER)
```

2. Establish an arbitrary user ID to use in a subsequent **RDEFINE** command to tie an MVS procedure name to a server.

```
ADDUSER DB2SERV NOPASSWORD
```

The **NOPASSWORD** keyword here is important, it makes DB2SERV a protected user.

3. Associate the user ID with the started task name.

```
RDEFINE STARTED PAY*.* STDATA(USER(DB2SERV) GROUP(SYS1))
RDEFINE STARTED PER*.* STDATA(USER(DB2SERV) GROUP(SYS1))
```

4. Define server profiles in the form:

```
subsys_type.subsys_name.applenv[.subsys_node]
```

where,

subsys_type

is the subsystem type, as specified in the service definition

subsys_name

is the instance name of the subsystem associated with this server. Refer to subsystem reference information for how to determine the subsystem name. The subsystem uses this name when establishing itself as the work manager for application environment server requests.

subsys_node

is the node name of the server when Work_Manager=Yes is specified. This is an optional parameter.

applenv

is the application environment name, as specified in the service definition

```
RDEFINE SERVER DB2.DB2A.* UACC(NONE)
RDEFINE SERVER DB2.DB2B.* UACC(NONE)
```

Note: The maximum length of a server profile name passed to a SAF product is restricted to 41 characters. WLM cannot start server address spaces for application environments that do not follow this restriction. If you ensure that the applenv is at maximum 27 characters long, it is guaranteed that the maximum server profile name length does not exceed 41 characters.

5. Permit the userid to the servers. This completes the association between the MVS procedure names and the servers:

```
PERMIT DB2.DB2A.* CLASS(SERVER) ID(DB2SERV) ACCESS(READ)
PERMIT DB2.DB2B.* CLASS(SERVER) ID(DB2SERV) ACCESS(READ)
```

6. Refresh the classes to refresh the RACF data base and make these changes go into effect:

```
SETR RACLIST(STARTED) REFRESH
SETR RACLIST(SERVER) REFRESH
```

Chapter 16. Defining scheduling environments

A scheduling environment is a list of resource names along with their required states. It allows you to manage the scheduling of work in an asymmetric sysplex where the systems differ in installed applications, or installed hardware facilities. If an MVS image satisfies all of the requirements in the scheduling environment associated with a given unit of work, then that unit of work can be assigned to that MVS image. If any of the resource requirements are *not* satisfied, then that unit of work *cannot* be assigned to that MVS image.

Scheduling environments and resource names reside in the service definition and apply across the entire sysplex. They are sysplex-oriented. Resource states have a different setting in each system in the sysplex and are, therefore, system-oriented.

Each element in a scheduling environment consists of the name of a resource and a required state of either ON or OFF, as follows:

- If the required state is ON, then the resource state must be set to ON on an MVS image for the requirement to be satisfied.
- If the required state is OFF, then the resource state must be set to OFF on an MVS image for the requirement to be satisfied.

In theory, each resource name represents the potential availability of a resource on an MVS system. That resource can be an actual physical entity such as a data base or a peripheral device, or it can be an intangible quality such as a certain time of day or a certain day of the week. The resource names are abstract, and have no inherent meaning.

For instance, you could define a resource name to be XXXX with a required state of ON. If on system SYS1 the corresponding XXXX resource state is set to ON, then the requirement is satisfied. WLM does not care what “XXXX” means, or whether the ON setting really does signify the existence of some real resource. (You could use XXXX as nothing more than an arbitrary toggle switch, setting it ON for whatever reason you wish.) As long as the settings match, the requirement is satisfied.

This information shows how to define the scheduling environments, the resource names, and their required states. It also shows how to set the resource states on each individual MVS system, and how to associate a scheduling environment name with incoming work.

Getting started with scheduling environments

The following steps are required to use scheduling environments:

- You must define one or more scheduling environments, and all of the resource names and required states that are listed in those scheduling environments, in the workload management service definition. See [“Specifying scheduling environments to workload management” on page 123](#).
- For every system in the sysplex on which you want the resource settings to satisfy either ON or OFF requirements, you must set the individual resource states to either ON or OFF, as appropriate. There is also a third setting, RESET, that satisfies neither an ON nor OFF requirement. See [“Managing resource states” on page 125](#) for more information on the RESET state.
- For each unit of work with resource state requirements that is submitted for execution, you must specify the name of the scheduling environment that should be used to determine which systems can execute that work. See [“Associating scheduling environments with incoming work” on page 128](#).

Specifying scheduling environments to workload management

To define a scheduling environment, you need to specify the following information:

Scheduling Environment Name

(Required) One to 16 character name of the scheduling environment.

- You can have up to 999 unique scheduling environments defined in a service definition.
- Alphanumerics and the special characters @, \$, # and _ are allowed.
- Underscores (_) must be imbedded (for example, PLEX_D01 is valid, but PLEX_ is not).
- Names beginning with SYS_ are reserved for system use.

Description

(Optional) Up to 32 characters describing the scheduling environment.

Once you have defined a scheduling environment, you can start selecting its resource names and required states, as follows:

Resource Name

(Required) One to 16 character name of the resource. There can be more than one resource name listed in a scheduling environment.

- You can have up to 999 unique resource names defined in a service definition.
- Alphanumerics and the special characters @, \$, # and _ are allowed.
- Underscores (_) must be imbedded (for example, PLEX_D01 is valid, but PLEX_ is not).
- Names beginning with SYS_ are reserved for system use.

Resource Description

(Optional) Up to 32 characters describing each resource.

When you select a resource name to become part of the scheduling environment, you also need to specify a required state:

Required State

(Required) For each resource name in a scheduling environment, you must specify a required state of either ON or OFF:

- ON specifies that the resource name must be set to ON on a given system for the work associated with this scheduling environment to be assigned to that system.
- OFF specifies that the resource name must be set to OFF on a given system for the work associated with this scheduling environment to be assigned to that system.

Scheduling environment example

To define a scheduling environment called DB2LATE that contains the following requirements:

- The “DB2A” resource must be set to ON. (In this example, we'll say that DB2A has been defined to represent the existence of the DB2 subsystem.)
- The “PRIMETIME” resource must be set to OFF. (In this example, we'll say that PRIMETIME has been defined to be ON during the normal weekday business hours, and OFF for all other times.)

You would define the following scheduling environment:

Scheduling Environment

DB2LATE

Description

Offshift DB2 Processing

Resource Name	Required State	Resource Description
DB2A	ON	DB2 Subsystem
PRIMETIME	OFF	Peak Business Hours

Null scheduling environments

If you no longer need to restrict where work executes in a sysplex, you can remove all the resource state requirements from a scheduling environment. A null or empty scheduling environment always allows

work to be scheduled; that is, any system in the sysplex is satisfactory for work associated with a null scheduling environment. This is a migration aid when you initially have resources that exist on only some of the systems in a sysplex, but later make the resources available to every system. It saves the effort of having to remove the scheduling environment specification from all the incoming work.

Refer to [“Working with scheduling environments” on page 193](#) to see how to use the WLM ISPF application to create and modify scheduling environments.

Managing resource states

For every resource name that is referenced by a scheduling environment, a corresponding resource state must be set on each system in the sysplex. The resource state can be:

- **ON**, which will satisfy a resource state requirement of ON.
- **OFF**, which will satisfy a resource state requirement of OFF.
- **RESET**, which will not satisfy any resource state requirement. Resources are put into the RESET state when:
 - A system is IPLed
 - A policy is activated that defines a resource name that did not exist in the previously active policy

These resource states can be manipulated in three ways:

- The operator command:

```
F WLM,RESOURCE=resource_name,setting
```

where *setting* can be ON, OFF, or RESET.

For example, to set DB2A to ON on system SYS1, here is the command you would enter *on system SYS1*, along with the response you would receive:

```
F WLM,RESOURCE=DB2A,ON
IWM039I  RESOURCE DB2A IS NOW IN THE ON STATE
```

- The equivalent WLM application programming interface IWMSESET. See [z/OS MVS Programming: Workload Management Services](#) for more information on using this interface.
- Using SDSF, you can change resource state settings directly on the panel displaying the current states.

Note: Do not attempt to issue the **F WLM, RESOURCE** command from the COMMNDxx parmlib member, as this member is processed too early during system initialization. If you want resource states to be set on every system IPL, this needs to be done through an automation product such as IBM Z® System Automation as soon as that automation product comes up during system initialization.

It is expected that, in most cases, the mechanics of managing resources states will be handled by installation-provided automation, as opposed to having a human operator issue a modify command every time a resource state is changed. Two examples of how automation could manage resource settings:

- By listening for messages from a subsystem that indicate that subsystem has completed its initialization and is ready to accept work. The automation script could issue the appropriate `F WLM,RESOURCE=subsystem,ON` command on that system. When messages are issued indicating that the subsystem is about to terminate, the script could issue the appropriate `F WLM,RESOURCE=subsystem,OFF` command on that system.
- For time-related resource settings, a simple script can turn settings ON and OFF at certain times of the day (like at the beginning and end of peak business hours).

See [z/OS MVS Programming: Workload Management Services](#) for more information on automation of resource states, WLM services, and coordination with other job scheduling programs.

When you modify the resource state settings on a given system, you do so *on that system only*. If you modify the DB2A resource state on system SYS1, it has no effect on the DB2A setting on SYS2. If you

wish to modify the settings on both systems, you would have to explicitly direct the commands to each individual system.

When *all* of the resource state settings on a particular system match the resource names and required states defined in a particular scheduling environment, only then is that system eligible to receive work associated with the scheduling environment.

Example of resource states

Using the DB2LATE scheduling environment defined in the first example, here's how the resource states might be set, and how that would affect the eligibility of work scheduled with DB2LATE to run on each system in the sysplex.

1. The resource names DB2A and PRIMETIME have just been defined (and not set on the individual systems yet) or the systems have just IPLed:

Resource state	SYS1 settings	SYS2 settings
DB2A	RESET	RESET
PRIMETIME	RESET	RESET

2. Because of the existence of DB2 on SYS1 only, the DB2A resource state is modified to ON on that system and OFF on SYS2. Also, automation has been set up to modify the PRIMETIME setting according to the time of day. At the moment, it is 10:00 a.m. on a Monday morning, so PRIMETIME is set to ON on both systems:

Resource state	SYS1 settings	SYS2 settings
DB2A	ON	OFF
PRIMETIME	ON	ON

At the moment, the DB2LATE scheduling environment is not satisfied by the resource state settings of either system. Therefore, any work submitted that is associated with the DB2LATE scheduling environment cannot yet be executed on either system.

3. At 5:00 p.m., automation modifies PRIMETIME to OFF on both systems:

Resource state	SYS1 settings	SYS2 settings
DB2A	ON	OFF
PRIMETIME	OFF	OFF

SYS1 now finally has all of the correct resource state settings to satisfy the DB2LATE scheduling environment. The work submitted associated with the DB2LATE scheduling environment can now be executed on SYS1.

In the previous example, work associated with the DB2LATE scheduling environment was assigned to SYS1, because that system satisfied all of the DB2LATE requirements. In the case of a single-system sysplex, this ability to choose the “right” system is no longer applicable. But scheduling environments may still be useful. Consider if, in the previous example, there was only a SYS1 in the sysplex. Only when the DB2A resource setting was set to ON (signalling that DB2 was up and running) and the PRIMETIME resource setting was set to OFF (signalling that the peak business hours were over) would DB2LATE work be processed on SYS1. The DB2LATE scheduling environment would act as a “ready” flag, holding the work until all of the requirements were met.

[Figure 25 on page 127](#) summarizes the relationship between scheduling environments and the resource state settings on several sample systems.





Figure 25. Sample Systems and Scheduling Environments

Note that in [Figure 25 on page 127](#):

- Work associated with the DB2PRIME scheduling environment can be scheduled only on SYS1, because only that system satisfies both of the requirements.

- Similarly, work associated with the DB2LATE scheduling environment can be scheduled only on SYS2, because only that system satisfies both of the requirements.
- Work associated with the ANYPRIME scheduling environment can be scheduled on either SYS1 or SYS4, because both of those systems satisfy the sole requirement (PRIMETIME must be ON). This scheduling environment does not care about the DB2A setting. Therefore the RESET state for DB2A on SYS4 is irrelevant.
- Work associated with the WHEREVER scheduling environment can be scheduled on any system in the sysplex, because it is empty (it has *no* requirements at all).

Associating scheduling environments with incoming work

Having defined scheduling environments to WLM, and having set the resource states on the individual systems, all you need now is a way to associate the scheduling environment name with actual work.

The **SCHENV** parameter on the JES2 or JES3 JCL JOB statement associates the job with the scheduling environment as shown in the following JCL example:

```
//SHAMIL JOB (C003,6363),'Steve Hamilton',
//          MSGLEVEL=(1,1),
//          REGION=4096K,
//          CLASS=A,
//          SCHENV=DB2LATE,
//          MSGCLASS=0
//
...

```

This specification associates this batch job with the DB2LATE scheduling environment. It can be coded by the end user, or automatically supplied by installation-provided exits.

If the scheduling environment name specified is not defined in the active WLM policy, the job will fail with a JCL error during conversion, accompanied by an appropriate error message.

Existing JES2 or JES3 exits can be used to change the scheduling environment name associated with batch jobs. This can be done during JCL conversion. These exits can also be used to dynamically generate scheduling environment associations as work is submitted. This could be useful in migrating from another scheduling mechanism to scheduling environments. See [z/OS JES2 Installation Exits](#) or [z/OS JES3 Customization](#) for more information.

Displaying information about scheduling environments and resource states

Once you have defined scheduling environments, you can issue several different operator commands, both from MVS and from JES2 or JES3 to display information about the scheduling environments and about the resource states.

MVS operator commands

To display sysplex-level information about a scheduling environment, you can issue the following command from an MVS console:

```
D WLM,SCHENV=scheduling_environment
```

For example, to display information about the DB2LATE scheduling environment, here is the command you would issue and the response you would receive:

```
D WLM,SCHENV=DB2LATE

IWM036I 12.21.05 WLM DISPLAY 181
SCHEDULING ENVIRONMENT: DB2LATE
DESCRIPTION:           Offshift DB2 Processing
AVAILABLE ON SYSTEMS:  SYS1 SYS3
```

The **AVAILABLE ON SYSTEMS** field shows that at the time this command was issued, only systems SYS1 and SYS3 satisfied the requirements of the DB2LATE scheduling environment.

To display information about *all* scheduling environments in a sysplex, issue the command with an asterisk (*) in the *scheduling_environment* field, as in this example:

```
D WLM,SCHENV=*  
  
IWM036I 12.21.05 WLM DISPLAY 181  
SCHEDULING ENVIRONMENT: DB2LATE  
DESCRIPTION: Offshift DB2 Processing  
AVAILABLE ON SYSTEMS: SYS1 SYS3  
  
SCHEDULING ENVIRONMENT: IMSPRIME  
DESCRIPTION: Primetime IMS Processing  
NOT AVAILABLE ON ANY SYSTEM
```

In this example, NOT AVAILABLE ON ANY SYSTEM is shown for the IMSPRIME scheduling environment, meaning that *no* systems in the sysplex currently satisfy the IMSPRIME requirements.

To display system-level information about a scheduling environment, use the `SYSTEM=system_name` parameter. You will see all of the resource names included in that scheduling environment, along with their required and current states. Requirements that are *not* satisfied are marked with an asterisk. So assuming that the DB2LATE scheduling environment is satisfied on SYS1 but not on SYS2, here is what the commands and responses might look like if you wanted the information for both systems:

```
D WLM,SCHENV=DB2LATE,SYSTEM=SYS1  
  
IWM037I 12.21.05 WLM DISPLAY 181  
SCHEDULING ENVIRONMENT: DB2LATE  
DESCRIPTION: Offshift DB2 Processing  
SYSTEM: SYS1  
STATUS: AVAILABLE  
  
RESOURCE NAME    REQUIRED    CURRENT  
STATE            STATE  
DB2A             ON         ON  
PRIMETIME        OFF        OFF  
  
D WLM,SCHENV=DB2LATE,SYSTEM=SYS2  
  
IWM037I 12.21.05 WLM DISPLAY 181  
SCHEDULING ENVIRONMENT: DB2LATE  
DESCRIPTION: Offshift DB2 Processing  
SYSTEM: SYS2  
STATUS: NOT AVAILABLE  
  
RESOURCE NAME    REQUIRED    CURRENT  
STATE            STATE  
*DB2A            ON         OFF  
PRIMETIME        OFF        OFF
```

To display information about a specific resource state on a specific system, use the command:

```
D WLM,RESOURCE=resource_name,SYSTEM=system
```

To display information about the DB2A resource state on system SYS1, for example, here is the command and response:

```
D WLM,RESOURCE=DB2A,SYSTEM=SYS1  
  
IWM038I 12.21.05 WLM DISPLAY 181  
RESOURCE: DB2A  
DESCRIPTION: DB2 Subsystem  
SYSTEM STATE  
SYS1 ON
```

To display information about *all* resource settings, use the asterisk in the *resource_name* field. Also, to display information on *all* systems in the sysplex, use the `SYSTEMS` keyword in place of the `SYSTEM=system_name` parameter. So to display information about all the resource states on all systems in the sysplex, here is a typical command and response:

D WLM,RESOURCE=*,SYSTEMS

```
IWM038I 12.21.05 WLM DISPLAY 181
RESOURCE: DB2A
DESCRIPTION: DB2 Subsystem
SYSTEM STATE SYSTEM STATE SYSTEM STATE
SYS1 ON SYS2 OFF SYS3 RESET

RESOURCE: PRIMETIME
DESCRIPTION: Peak Business Hours
SYSTEM STATE SYSTEM STATE SYSTEM STATE
SYS1 OFF SYS2 OFF SYS3 OFF
```

JES2/JES3 operator commands

The JES2 display command **\$D JOBQ** can be used to list those queued jobs associated with a scheduling environment, as in this example:

\$djobq,schenv=DB2LATE

```
JOB00007 $HASP608 JOB(SHAMIL)
$HASP608 JOB(SHAMIL) STATUS=(AWAITING EXECUTION),CLASS=S,
$HASP608 PRIORITY=1,SYSAFF=(ANY),HOLD=(NONE),
$HASP608 CMDAUTH=(LOCAL),OFFS=(),SECLABEL=,
$HASP608 USERID=DEALLOC,SPool=(VOLUMES=(SPool1),
$HASP608 TGS=2,PERCENT=0.3809),ARM_ELEMENT=NO,
$HASP608 SRVCLASS=HOTBATCH,SCHENV=DB2LATE
```

For JES3, use the ***INQUIRY,Q** command, as in this example:

*I,Q,SCHENV=IMSPROD

```
IAT8674 JOB JOB123 (JOB32787) P=02 CL=Z MAIN(ALLOCATE)
IAT8674 JOB JOBABC (JOB32790) P=02 CL=Z MAIN(ALLOCATE)
IAT8674 JOB JOBDEF (JOB32791) P=02 CL=Z MAIN(ALLOCATE)
IAT8674 JOB JOBGHI (JOB32800) P=02 CL=Z MAIN(ALLOCATE)
IAT8674 JOB JOBJKL (JOB32987) P=02 CL=Z MAIN(ALLOCATE)
IAT8674 JOB JOBMNO (JOB33101) P=02 CL=Z MAIN(ALLOCATE)
```

See [z/OS JES3 Commands](#) for more information on using JES3 operator commands.

SDSF commands

SDSF can display scheduling environment information, resource information, and allows modification of resource states.

Chapter 17. Workload management migration

This information covers two different workload management migration scenarios, depending on whether you already have an existing service definition, or need to create one for the first time:

- **Creating a service definition for the first time**

In this scenario, you do not presently have a service definition, but would like to start exploiting workload management functions.

For the required steps, see [“Creating a service definition for the first time” on page 131](#).

- **Migrating to a new z/OS release with an existing service definition**

In this scenario, you already have a service definition created on a previous release of z/OS and need to accommodate any changes introduced by a higher release.

For the required steps, see [“Migrating to a new z/OS release with an existing service definition” on page 133](#).

This information contains a checklist for each of the two scenarios. The major migration activities are described in detail following the checklist sections, as follows:

- [“Restricting access to the WLM service definition” on page 134](#)
- [“Start the application and enter/edit the service definition” on page 135](#)
- [“Calculate the size of the WLM couple data set” on page 138](#)
- [“Allocate a WLM couple data set” on page 138](#)
- [“Make a WLM couple data set available to the sysplex for the first time” on page 140](#)
- [“Make a newly formatted couple data set available to the sysplex” on page 141](#)
- [“Migration considerations for velocity” on page 142](#)
- [“Migration considerations for discretionary goal management” on page 143](#)
- [“Migration considerations for dynamic alias management” on page 143](#)
- [“Migration considerations for multisystem enclaves” on page 143](#)
- [“Migration considerations for protection of critical work” on page 143](#)
- [“Migration considerations for managing non-enclave work in enclave servers” on page 144](#)
- [“Migration considerations for an increased notepad size” on page 144](#)
- [“WLM managed batch initiator balancing” on page 144](#)
- [“Consider resource group maximum in WLM batch initiator management” on page 145](#)
- [“Migration considerations for service definition coefficients” on page 145](#)

Creating a service definition for the first time

Use the following checklist to create a service definition for the first time, allocate the WLM couple data set, and then activate a service policy.

1. **Set up performance objectives.** If your installation already has performance objectives, [Chapter 4, “Setting up a service definition,” on page 29](#) is still helpful in setting up a service policy with realistic performance goals.
2. **Set up a service definition** from the performance objectives.

Refer to [Chapter 4, “Setting up a service definition,” on page 29](#) through [Chapter 16, “Defining scheduling environments,” on page 123](#) for further information.
3. **Restrict access to the ISPF administrative application.**

Refer to [“Restricting access to the WLM service definition” on page 134](#) for further information.

4. **Start the application** and enter the service definition.

Refer to [“Start the application and enter/edit the service definition” on page 135](#) for further information.

5. **Upgrade the sysplex couple data set**

Make sure that you have installed the z/OS release and allocated your sysplex couple data set with the IXCL1DSU utility.

For information about how to format the sysplex couple data set, refer to [z/OS MVS Setting Up a Sysplex](#).

6. **Allocate a WLM couple data set.**

For more information, refer to [“Allocate a WLM couple data set” on page 138](#).

7. **Make the WLM couple data set available** for use in the sysplex for the first time by either:

- Issuing the **SETXCF** command
- Updating the COUPLExx parmlib member and re-IPLing

For more information, see [“Make a WLM couple data set available to the sysplex for the first time” on page 140](#).

8. **Install a service definition** on the WLM couple data set.

Before you can activate a service policy, you need to install the service definition on the WLM couple data set. To do this, use either the WLM ISPF application, or the Install Definition Utility (new with z/OS R3).

To use the ISPF application, go into it specifying the name of the data set containing your service definition. From the Definition Menu, go to **UTILITIES** on the action bar, then select the pull-down option **Install Service Definition**.

To use the Install Definition Utility, configure the sample JCL (member IWMINSTL, shipped in SYS1.SAMPLIB) as directed in the prolog. Once the JCL has been prepared, it can be started from the command console or submitted as a batch job. A sample service definition has been provided (member IWMSSDEF, also shipped in SYS1.SAMPLIB) that is available for those customers without any other definition.

9. **Adjust SMF recording**

In particular, review the recording of SMF type 99 records. They trace the actions SRM takes while in goal mode, and are written frequently. SMF type 99 records are for detailed audit information only. IBM recommends that you record SMF 99 subtype 14 records, and, if WLM group capping is used, subtype 11 records. There is usually no need to retain other subtypes for an extended period.

If you do chargeback based on SMF record type 30 or record type 72 records, you may need to update your accounting package.

For more information about SMF record changes for goal mode, see [z/OS MVS System Management Facilities \(SMF\)](#).

10. **Activate a service policy**

Once you have installed a service definition, you can activate a service policy. You can activate a policy either from the administrative application, with the VARY operator command, or the WLM Install Definition Utility.

To activate a service policy from the application, choose the Utilities option from the action bar on the definition menu.

To activate a service policy with the VARY command, specify

```
VARY WLM,POLICY=xxxx
```

where xxxx is the name of a policy defined in the installed service definition.

To activate a service policy with the Install Definition Utility, start or submit the sample JCL (member IWMINSTL in SYS1.SAMPLIB).

Once you issue the command, there is an active policy for the sysplex. Systems will start managing system resources to meet the goals defined in the service policy.

For more information about the **VARY** command, see [z/OS MVS System Commands](#).

Migrating to a new z/OS release with an existing service definition

Use the following checklist to migrate to the current z/OS release with an existing service definition. You may or may not need to reallocate the WLM couple data set, depending on which release you are migrating from.

1. **Evaluate your service definition.** At some point, either before or after you migrate to the new release, you may need to make one or more adjustments to your service definition.

If you increase your service definition from a lower level to LEVEL011 or above, your service definition is subject to a more rigorous verification. Errors might be flagged if you attempt to either save or install your service definition. The application allows you to save the service definition, but prevents you from installing it until the errors are corrected.

For more information, see the discussion of LEVEL011 in [“Service definition functionality levels, CDS format levels, and WLM application levels”](#) on page 136.

2. **Ensure compatibility of downlevel releases..**

If you are running mixed MVS releases on a sysplex, you need to install the compatibility PTFs on all downlevel systems to enable different levels of workload management to coexist until you can upgrade the entire sysplex to the new release. Refer to [z/OS Upgrade Workflow](#) for further details.

3. **Select the correct z/OS release for policy updates.**

The WLM service definition is stored in ISPF tables, or in XML format. When a new release or a new function APAR adds certain specifications to the service definition, structural changes to the ISPF tables are required. In that case, the WLM application automatically updates the ISPF table structure when you save the service definition in ISPF table format, even if you do not exploit the new functionality. If this occurs, the saved service definition cannot be read by older levels of the WLM application, or the IWMINSTL sample job.

Therefore, it is recommended that you always use XML format when saving service definitions. If using ISPF table format, it is recommended that you start updating a WLM policy with a higher level of administrative application (that is, a higher z/OS release) only when you are sure that you do not have to update that policy data set with a lower level of administrative application in the future. The following releases and new function APARs changed the ISPF table structure:

- OS/390® V1R3, V1R4, V1R6, and V1R10
- z/OS V1R1, V1R8, V1R10, V1R11, and V2R1
- APAR OA47042 for z/OS V2R1 and later
- APAR OA50845 for z/OS V2R1 and later
- APAR OA52312 for z/OS V2R2 and later
- APAR OA60841 for z/OS V2R4 and later

4. **Start the WLM application.**

For more information, see [“Start the application and enter/edit the service definition”](#) on page 135. Please note the discussion of service definition functionality levels in [“Service definition functionality levels, CDS format levels, and WLM application levels”](#) on page 136. Once you choose to use a new functionality level, from that point on you must always use a level of the WLM application that is compatible with that functionality level. It is recommended that you do not use the new functions (which automatically updates the functionality level) until all those systems are upgraded to the new release.

Migration activities

The following sections provide more detail for certain migration activities referenced out of the migration checklists. To determine if you need to perform an activity, refer to the preceding checklists.

Restricting access to the WLM service definition

Before you create a WLM service definition, you should determine who needs access to it, and the kind of functions each person needs to perform. The installation's capacity planners, systems programmers that analyze workloads and the system's performance, system operators, service administrator, and help desk support may all need access to the service definition information.

There are two levels of access you need to consider:

- Access to an MVS data set
- Access to the WLM couple data set

Restricting access to an MVS data set

Any user with access to the administrative application can create their own “practice” service definitions in their own MVS data set. The MVS data set containing the actual service definition that will be installed into the WLM couple data set should be protected. Use a data set profile, just as you would for any other data set. Give READ access only to those people who should be able to view the service definition in the MVS data set, and UPDATE access to those people who should be able to create or modify the service definition in the MVS data set.

Restricting access to the WLM couple data set

Once you have determined who needs access to the WLM couple data set itself, define the kind of access authority required, as follows:

READ

With READ access, a user can extract a service definition from the WLM couple data set.

UPDATE

With UPDATE access, a user can:

- Do all the functions available for READ access.
- Install a service definition to a WLM couple data set.
- Activate a service policy.

To control access to the WLM couple data set, use **RDEFINE** to add a profile to the RACF database. Then use **PERMIT** to permit or deny access to the RACF profile. Do not forget to issue the **SETROPTS REFRESH** command after the **PERMIT** command to refresh the RACF data base and activate the changes you have made.

Example of RDEFINE for the WLM couple data set

```
RDEFINE FACILITY MVSADMIN.WLM.POLICY UACC(NONE)
```

Example of PERMIT for the WLM couple data set

```
PERMIT MVSADMIN.WLM.POLICY CLASS(FACILITY)
                                     ID(user)
                                     ACCESS(READ)

PERMIT MVSADMIN.WLM.POLICY CLASS(FACILITY)
                                     ID(user)
                                     ACCESS(UPDATE)
```

where:

user

Indicates the user or user group that needs access to the WLM couple data set.

ACCESS

Indicates the type of access, either READ or UPDATE.

Start the application and enter/edit the service definition

Start the new release's WLM administrative application, and enter your service definition.

If you want to keep the previous release's WLM application, each version of the application must have unique library names. So, when you install the new release, make sure you keep the previous release application on the system under a unique name. You can rename your libraries by using an exit as described in [Appendix A, “Customizing the WLM ISPF application,” on page 217](#).

When you enter the service definition, you can keep the service definition in an MVS partitioned data set until you are ready to install the service definition into the WLM couple data set. If you are migrating to use a new version of the WLM application, always save the partitioned data set created by the previous version of the application for backup purposes.

Before starting the WLM application

To start the WLM application, you use the TSO/E REXX exec IWMARIN0. The exec concatenates (via LIBDEF and ALTLIB), the following libraries necessary to run the application:

Table 12. WLM libraries

Library	Content
SYS1.SBLSCLI0	Application REXX code
SYS1.SBLSKEL0	Application skeletons
SYS1.SBLSPNL0	Application panels
SYS1.SBLSTBL0	Application keylists and commands
SYS1.SBLSMSG0	Application messages

The exec also allocates some MVS partitioned data sets for the service definition using TSO ALLOCATE, and then invokes the WLM panels. If you have different data set conventions for your IPCS/WLM libraries, or if you use storage managed data sets, you should use the WLM application exits IWMAREX1 and IWMAREX2. For more information about how to code the exits, see [Appendix A, “Customizing the WLM ISPF application,” on page 217](#).

Start the WLM application

To start the application, specify:

```
ex 'SYS1.SBLSCLI0(IWMARIN0)'
```

For more information about IWMARIN0, and for examples on how to start the application specifying the WLM exits, see [Appendix A, “Customizing the WLM ISPF application,” on page 217](#).

Enter/edit the service definition

Type in the service definition (or else edit the existing service definition), and then save it as a partitioned data set (PDS), or a sequential data set (PS). For help on using the application, see [Chapter 22, “Using the WLM ISPF application,” on page 167](#).

Note that if you change the service definition to use certain functions of the new release, you may not be able to use the service definition on the previous release.

Service definition functionality levels, CDS format levels, and WLM application levels

A service definition has a *functionality level* for each release as shown in [Table 13 on page 136](#):

Table 13. Functionality levels for service definition

Release	Functionality level
OS/390 R4/R5	LEVEL004
OS/390 R6	LEVEL006 or LEVEL007 (LEVEL007 available only with APAR OW33509 installed)
OS/390 R7	LEVEL007 or LEVEL008 (LEVEL008 available only with APAR OW39854 installed)
OS/390 R8	LEVEL007 or LEVEL008 (LEVEL008 available only with APAR OW39854 installed)
OS/390 R9	LEVEL008
OS/390 V1R10 and z/OS V1R1	LEVEL011
z/OS V1R2, V1R3, V1R4, and V1R5	LEVEL013
z/OS V1R6 and V1R7	LEVEL013, LEVEL017 (LEVEL017 available only with APAR OA12784 installed)
z/OS V1R8 and V1R9	LEVEL019
z/OS V1R10	LEVEL021
z/OS V1R11	LEVEL023
z/OS V1R12 and z/OSV1R13	LEVEL025
z/OS V2R1	LEVEL029, LEVEL030 (LEVEL030 available only with APAR OA47042 installed), LEVEL031 (LEVEL031 available only with APAR OA50845 installed)
z/OS V2R2	LEVEL029, LEVEL030 (LEVEL030 available only with APAR OA47042 installed), LEVEL031 (LEVEL031 available only with APAR OA50845 installed), LEVEL032 (LEVEL032 available only with APAR OA52312 installed)
z/OS V2R3	LEVEL032 (LEVEL032 available only with APAR OA52312 installed), LEVEL035
z/OS V2R4	LEVEL035, LEVEL038 (LEVEL038 available only with APAR OA60841 installed)
z/OS V2R5	LEVEL035, LEVEL038 (LEVEL038 available only with APAR OA60841 installed)

Note: LEVEL005, LEVEL009, LEVEL010, LEVEL012, LEVEL014-016, LEVEL018, LEVEL020, LEVEL022, LEVEL024, LEVEL026, LEVEL027, and LEVEL028, LEVEL033, LEVEL034, LEVEL036, and LEVEL037 are reserved.

If you do not use any of the new functions for a new release, then the functionality level does not change, even if you are using the service definition on a new release. When you install the service definition, the system checks whether you have used any of the new functions, and sets the functionality level. For example, if you created your service definition on z/OS V1R8, then its functionality level is LEVEL017. If you installed this service definition from a z/OS V1R7 system but did not use any of the new functions, then its functionality level remains LEVEL013.

You should use the new functions when you are comfortable running the new release on your sysplex. Once you use the new functions and increase the functionality level, then you may not be able to use the service definition on a lower level system. For example, you cannot extract a LEVEL017 service definition from a z/OS V1R5 system. You also cannot activate a policy in a LEVEL017 service definition from a z/OS V1R5 system.

The following function, available on z/OS V1R11, increases the service definition level to LEVEL023:

- The number of report classes in the service definition exceeds 999

The following function, available on z/OS V1R12, increases the service definition level to LEVEL025:

- The service definition contains guest platform management provider (GPMP) configuration settings

The following function, available on z/OS V2R1, increases the service definition level to LEVEL029:

- The service definition contains service class(es) assigned to the I/O priority group or I/O priority groups are enabled
- The number of application environments in the service definition exceeds 999
- The service definition contains new qualifier types Client Accounting Information, Client IP Address, Client Transaction Name, Client User ID, or Client Workstation Name in classification rules for subsystem types DB2 or DDF
- The service definition contains groups of the new group types Accounting Information, Correlation Information, Client Accounting Information, Client IP Address, Collection Name, Client Transaction Name, Client Userid, Client Workstation Name, Process Name, Procedure Name, Sysplex Name, Scheduling Environment, Subsystem Parameter, or Subsystem Collection
- The service definition uses a start position for qualifier type Package Name, either in classification rules or group members
- The service definition uses a start position exploiting the new length of 128 bytes for qualifier type Procedure Name, either in classification rules or group members
- The notepad contains more than 500 lines of information.

Note that if you plan to add more than 500 lines of notepad information, you need to re-allocate the WLM couple data set before installing this definition. See [“Migration considerations for an increased notepad size”](#) on page 144 for further information.

The following function, available on z/OS V2R1 with APAR OA47042 installed, increases the service definition level to LEVEL030:

- A non-default value is specified for the Reporting Attribute for classification rules.

The following function, available on z/OS V2R1 with APAR OA50845 installed, increases the service definition level to LEVEL031:

- NO is specified for the Honor Priority attribute for any service class on the service class definition panel, or service class override panel.
- A memory limit is specified for any resource group on the resource group definition panel or resource group override panel.

The following function, available on z/OS V2R2 with APAR OA52312 installed, and z/OS V2R3 with APAR OA52312 installed, increases the service definition level to LEVEL032:

- A service definition has tenant resource groups defined
- A resource group is defined with capacity type 2 (as percentage of the LPAR share) and minimum or maximum capacity is greater than 99
- A resource group is defined with capacity type 4 (accounted workload MSU)
- A resource group is defined with option *Include specialty processor consumption*
- The service definition is defined with option *Deactivate discretionary goal management*

The following function, available on z/OS V2R3, increases the service definition level to LEVEL035:

- A service class has a period with a percentile or average response time goal defined and the goal value is below 0.015 seconds.

The following function, available with z/OS V2R4 with APAR OA60841 installed, increases the service definition level to LEVEL038:

- YES is specified for the **Boost** attribute in any classification rule.

Table 14. The current WLM couple data set format level

Current CDS format level	Description
3	Format updated in OS/390 Release 4, with addition of scheduling environments. This is the format level for OS/390 Release 4 or higher.

Calculate the size of the WLM couple data set

When you reallocate a WLM couple data set, it must be at least as large as the current one or you will not be able to make it available to the sysplex. It is recommended that you increase the size of your couple data set to allow you to exploit new functions, even if you do not plan to exploit new functions immediately.

Use the WLM ISPF Application Utilities option (see [“Utilities” on page 175](#)) with the “Allocate couple data set using CDS values” option to determine your couple data set size. If you already have a record of the values, you can skip this step; just ensure you allocate the WLM couple data set with the same or larger values as the current one.

Allocate a WLM couple data set

You need to define a WLM couple data set for storing the service definition information. If you are running a sysplex with mixed release levels, you should format the WLM couple data set from the highest level system. This allows you to use the current level of the WLM application.

To allocate the WLM couple data set you can either use the facility provided in the WLM application, or you can run an XCF utility. For each case, you need to estimate how many workload management objects you are storing on the WLM couple data set. You must provide an approximate number of the following:

- Policies in your service definition
- Workloads in your service definition
- Service classes in your service definition
- Application environments in your service definition
- Scheduling environments in your service definition

The values you define are converted to space requirements for the WLM couple data set being allocated. The total space is *not* strictly partitioned according to these values. For most of these values, you can consider the total space to be one large pool.

If you specify 50 service classes, for instance, you are simply requesting that the space required to accommodate 50 service classes be added to the couple data set. You have NOT limited yourself to 50 service classes in the service definition. Although note that if you DO define more than 50 service classes, you will use up space that was allocated for something else.

Not all workload management objects are contained in the above list. Therefore, you might need to specify larger numbers than you actually have in order to set aside enough space for those objects. For example, if you have many classification rules, you should specify a larger value for the number of service classes to accommodate all the rules. The ISPF application helps you in doing so by calculating recommended values for the above list which ensure that the service definition you are currently working with fits into the newly allocated WLM couple data set. From the Definition Menu in the ISPF application, choose **Utilities**. In the Utilities pull-down, **4. Allocate couple data set**. The values you see in that panel are the recommended values for allocating your WLM couple data set.

You should define an alternate WLM couple data set (similar to the sysplex alternate couple data set) for recovery purposes. You can define an alternate WLM couple data set using the same method (either the ISPF application or the XCF utility), but specifying a different data set.

To allocate a WLM couple data set using the ISPF application, choose **Utilities** from the Definition Menu.

To allocate a WLM couple data set using the XCF utility, you can follow some JCL provided in the IWMFTCDS member of SYS1.SAMPLIB.

Sample JCL to allocate a WLM couple data set

To allocate a WLM couple data set, use the sample JCL and fill in the following information:

```
//FMTCDSD  JOB MSGLEVEL=(1,1)
//STEP1    EXEC PGM=IXCL1DSU
//STEPLIB  DD  DSN=SYS1.MIGLIB,DISP=SHR
```



```
//SYSPRINT DD   SYSOUT=A
//SYSIN DD      *
  DEFINEDS  SYSPLEX(PLEX1)
            DSN(SYS1.WLMCDS01) VOLSER(TEMPAK)
            MAXSYSTEM(32)
            CATALOG
  DATA TYPE(WLM)
        ITEM NAME(POLICY) NUMBER(10)
        ITEM NAME(WORKLOAD) NUMBER(35)
        ITEM NAME(SRVCLASS) NUMBER(30)
        ITEM NAME(SVDEFEXT) NUMBER(5)
        ITEM NAME(SVDCREXT) NUMBER(5)
        ITEM NAME(APPLENV) NUMBER(50)
        ITEM NAME(SVAEAEXT) NUMBER(5)
        ITEM NAME(SCHENV) NUMBER(50)
        ITEM NAME(SVSEAEXT) NUMBER(5)
```

Where:

SYSPLEX(*sysplex*)

The name of your sysplex as it appears in your COUPLExx parmlib member.

DSN

The name you are calling your WLM couple data set

VOLSER

A volume that you have access to. If you are using DFSMS, you do not need to specify a VOLSER.

TYPE

The type of function for which this data set is allocated. For a service definition, the type is WLM.

ITEM NAME(POLICY) NUMBER(*nn*)

Specifies that an increment of space large enough to accommodate the specified number of policies be allocated in the WLM couple data set (Default=5, Minimum=1, Maximum=99).

ITEM NAME(WORKLOAD) NUMBER(*nnn*)

Specifies that an increment of space large enough to accommodate the specified number of workloads be allocated in the WLM couple data set (Default=32, Minimum=1, Maximum=999).

ITEM NAME(SRVCLASS) NUMBER(*nnn*)

Specifies that an increment of space large enough to accommodate the specified number of service classes be allocated in the WLM couple data set (Default=128, Minimum=1, Maximum=999).

Note: WLM allows no more than 100 service classes to be defined in a service definition. The default, however, is 128. This will set aside as much space as you will ever need for service classes, as well as a little extra for other WLM objects.

ITEM NAME(SVDEFEXT) NUMBER(*nnnn*)

Specifies that an exact amount of space (in K bytes) for extension areas to the WLM Service Definition (IWMSVDEF) be allocated in the WLM couple data set (Default=0, Minimum=0, Maximum=8092).

ITEM NAME(SVDCREXT) NUMBER(*nnnn*)

Specifies that an exact amount of space (in K bytes) for extension areas to the WLM Service Definition Classification Rules (IWMSVDCR) be allocated in the WLM couple data set (Default=0, Minimum=0, Maximum=8092).

ITEM NAME(APPLENV) NUMBER(*nnnn*)

Specifies that an increment of space large enough to accommodate the specified number of application environments be allocated in the WLM couple data set (Default=100, Minimum=1, Maximum=3000).

ITEM NAME(SVAEAEXT) NUMBER(*nnnn*)

Specifies that an exact amount of space (in K bytes) for extension areas to the WLM Service Definition Application Environment Area (IWMSVAEA) be allocated in the WLM couple data set (Default=0, Minimum=0, Maximum=8092).

ITEM NAME(SCHENV) NUMBER(*nnn*)

Specifies that an increment of space large enough to accommodate the specified number of scheduling environments be allocated in the WLM couple data set (Default=100, Minimum=1, Maximum=999).

ITEM NAME(SVSEAEXT) NUMBER(nnnn)

Specifies that an exact amount of space (in K bytes) for extension areas to the WLM Service Definition Scheduling Environment Area (IWMSVSEA) be allocated in the WLM couple data set (Default=0, Minimum=0, Maximum=8092).

If you encounter a problem during processing, make sure you take a dump by adding the following to your JCL and re-submit.

```
//SYSABEND DD SYSOUT=*
```

Note: The intended users of SVDEFEXT, SVDCREXT, SVAEAEXT, and SVSEAEXT are system management product vendors who wish to include some of their own unique information about customer workload definitions along with the WLM definitions. The WLM interfaces allow these extensions to accompany the service class definitions, report class definitions, or even classification rules. The amount of extra information is specific to each product that exploits these interfaces. That product's documentation should tell the customer how to set SVDEFEXT, SVDCREXT, SVAEAEXT, and SVSEAEXT to ensure that there is sufficient space available in the WLM couple data set to hold the extra information. For more information, see the “Adding Program-Specific Extensions to a Service Definition” topic in the “Using the Administrative Application Services” Chapter in *z/OS MVS Programming: Workload Management Services*.

Increasing the size of the WLM couple data set

You must use a series of **SETXCF** commands to add a new, larger couple data set as the primary WLM couple data set. During this processing you may encounter a message from XCF (IXC250I) indicating your new couple data set is too small. The message indicates which subrecords had insufficient space. If this occurs you must reallocate the new couple data set with a larger size.

From the Definition Menu in the ISPF application, choose **Utilities**. In the Utilities pull-down, **4. Allocate couple data set**. The values you see in that panel are calculated by WLM and ensure that the service definition you are currently working with fits into the newly allocated WLM couple data set. Record these values. Then choose **5. Allocate couple data set using CDS values**. Record the values that you see in that panel. Now compare the two sets of values and choose the *highest* from each category. To allow for future growth, increase each by 10%. For example, if the two panels showed the following values:

Allocate couple data set	Allocate couple data set using CDS values
Service policies . . . 5	Service policies . . . 10
Workloads 40	Workloads 35
Service classes . . . 35	Service classes . . . 30
Application environments 100	Application environments 50
Scheduling environments 80	Scheduling environments 50

Then, you should use the highest values in each category plus 10% to allow for future growth, in this case 11, 44, 39, 110, and 88, to allocate your new couple data set.

Make a WLM couple data set available to the sysplex for the first time

This section applies when creating a service definition for the first time. If you already have a service definition and want to make a re-allocated WLM couple data set available, see [“Make a newly formatted couple data set available to the sysplex” on page 141](#).

To make your WLM couple data set available to the sysplex, you must either:

- Update your COUPLExx parmlib member to include the data set name and volume of your WLM couple data set, and re-IPL. Use this option if you have not yet IPLed in a sysplex.
- Issue the **SETXCF** command, if you have already IPLed in a sysplex. You must still update your COUPLExx member for subsequent IPLs.

Using the SETXCF command

To make the WLM couple data set available to the sysplex, you can use the **SETXCF** command. Remember that you still need to update your COUPLExx member as shown in “[Updating the COUPLExx member](#)” on [page 141](#) so that any subsequent IPLs will automatically pick up the WLM couple data sets.

For more information about using the **SETXCF** command, see [z/OS MVS System Commands](#).

Examples of the SETXCF command

- To make a primary WLM couple data set called SYS1.WLMCDS01 residing on volume TEMP01 available to the sysplex, enter the following command:

```
SETXCF COUPLE,TYPE=WLM,PCOUPLE=(SYS1.WLMCDS01,TEMP01)
```

- To make an alternate WLM couple data set called SYS1.WLMCDS02 residing on volume TEMP02 available to the sysplex, enter the following command:

```
SETXCF COUPLE,TYPE=WLM,ACOUPLE=(SYS1.WLMCDS02,TEMP02)
```

Updating the COUPLExx member

To make the WLM couple data set available for use in the sysplex, you need to update the DATA keyword in the COUPLExx parmlib member, and IPL so that the member is in use. For more information about updating the COUPLExx member, see [z/OS MVS Setting Up a Sysplex](#).

Example of updating the COUPLExx member

```
DATA      TYPE(WLM)
          PCOUPLE(SYS1.WLMCDS01,TEMP01)
          ACOUPLE(SYS1.WLMCDS02,TEMP02)
```

Where:

TYPE

The function type, WLM.

PCOUPLE(dataset.name,volume)

The WLM couple data set name, and the volume it resides on.

ACOUPLE(dataset.name,volume)

The alternate WLM couple data set name, and the volume it resides on. If you do not have an alternate WLM couple data set, then delete this keyword.

Specify the modified COUPLExx member on your next IPL.

Make a newly formatted couple data set available to the sysplex

This section applies when you already have WLM couple data sets, have just allocated new WLM couple data sets, and want to make them available to the sysplex. You do this, for example, if you want to increase the size of the existing WLM couple data sets.

You must use a series of **SETXCF** command to switch from the currently active primary and alternate couple data sets to the new couple data sets. All systems in the sysplex then operate with the newly allocated data set.

If you are making newly formatted WLM couple data sets available to the sysplex, you can continue to use an older WLM application to modify, install and activate your service definition (as long as new functions are not exploited), or you can switch to using the z/OS Release 2 WLM application.

For more information on compatibility of release levels, WLM application levels, couple data set formats, and functionality levels, see [“Service definition functionality levels, CDS format levels, and WLM application levels”](#) on page 136.

Example of making re-allocated couple data sets available

1. Allocate two new couple data sets as described in [“Allocate a WLM couple data set”](#) on page 138 For this example, it is assumed you want a primary and an alternate couple data set, and that the names of the new data sets are SYS1.WLMP residing on volume SYS001, and SYS1.WLMA residing on volume SYS002.
2. Make SYS1.WLMP the alternate using the command:

```
SETXCF COUPLE,TYPE=WLM,ACOUPLE=(SYS1.WLMP,SYS001)
```

As part of this processing, **SETXCF** copies the contents of the current primary WLM couple data set to SYS1.WLMP which now is the new alternate.

3. Switch SYS1.WLMP to primary using the command:

```
SETXCF COUPLE,TYPE=WLM,PSWITCH
```

4. Now make SYS1.WLMA the new alternate using the command:

```
SETXCF COUPLE,TYPE=WLM,ACOUPLE=(SYS1.WLMA,SYS002)
```

As in Step 1, this causes the contents of the new primary WLM couple data set SYS1.WLMP to be copied to the new alternate SYS1.WLMA.

Migration considerations for velocity

Initiation delays cause the velocity value to decrease. Recalculate and adjust your velocity goals accordingly. See [“Velocity formula”](#) on page 50 for information on calculating velocity.

Before migrating to WLM batch management, you can estimate the new velocity goal for a service class as follows:

Note: All jobs with the same service class should be migrated together to WLM-managed job classes.

- Run the jobs under normal circumstances
- Examine the initiation delay data:
 - In the IWMWRCAA data area, if you are using the workload reporting services:

RCAETOTDQ

Total delay samples, including initiation delay

RCAETOTU

Total using samples

- In the SMF type 72, subtype 3 record, if you are using RMF:

R723CTDQ

Total delay samples, including initiation delay

R723CTOU

Total using samples

Include the initiation delay in the velocity formula for an estimate of the new, lower velocity. Plugging this delay data into the velocity formula gives you:

$$velocity = RCAETOTU \div (RCAETOTU + RCAETOTDQ) \times 100$$

or

$$velocity = R723CTOU \div (R723CTOU + R723CTDQ) \times 100$$

RMF will do this calculation for you — look for the **INIT MGMT** field in the RMF Monitor I workload activity report (on the line that begins “VELOCITY MIGRATION:”). See [“Adjusting velocity goals based on samples included in velocity calculation”](#) on page 54 for more information.

If you had originally given a velocity goal to a service class period *only* because TYPRUN=HOLD time was included in response time goals, you can now give that service class period a response time goal because the TYPRUN=HOLD time is no longer included in the response time. In this case, you no longer need to recalibrate the velocity goal since it has been replaced with the response time goal.

Migration considerations for discretionary goal management

Certain types of work, *when overachieving their goals*, potentially will have their resources “capped” in order to give discretionary work a better chance to run. Specifically, work that is *not* part of a resource group and has one of the following two types of goals will be eligible for this resource donation:

- A velocity goal of 30 or less
- A response time goal of over one minute

Work that is eligible for resource donation may be affected in OS/390 Release 6 and higher if this work has been significantly overachieving its goals. If you have eligible work that must overachieve its goals to provide the required level of service, adjust the goals to more accurately reflect the work's true requirements.

Migration considerations for dynamic alias management

With dynamic alias management, WLM can automatically perform alias address reassignments to help work meet its goals and to minimize IOS queueing.

It is recommended *not* to use dynamic alias management for a device unless all systems sharing that device have dynamic alias management enabled. Otherwise, WLM will be attempting to manage alias assignments without taking into account the activity from the non-participating systems.

See [“Specifying dynamic alias management”](#) on page 96 for more information.

Migration considerations for multisystem enclaves

Before using multisystem enclaves, an installation needs to define a specific coupling facility structure named SYSZWLM_WORKUNIT in the CFRM policy. See Chapter 18, [“Defining a coupling facility structure for multisystem enclave support,”](#) on page 147 for more information.

Programs that use data from the SMF 30 record may need to be updated in conjunction with multisystem enclave support. The enclave owner's SMF 30 record has new fields containing the CPU time accumulated by all of its split transactions, for *all* systems on which they executed.

For more detailed information on multisystem enclaves, see the “Creating and Using Enclaves” in [z/OS MVS Programming: Workload Management Services](#).

Migration considerations for protection of critical work

You should be aware of several options available to help system administrators protect critical work, and how these options may affect other work.

These options include:

- Long-term storage protection
- Long-term CPU protection
- Exemption from management as a transaction server

See Chapter 14, [“Defining special protection options for critical work,”](#) on page 99 for more information on these options.

Migration considerations for managing non-enclave work in enclave servers

Starting with z/OS Release V1R12, the non-enclave work of enclave servers is managed towards the first service class period of the address space performance goal. Based on this expanded performance management it is recommended to verify the performance goals for the service class of the address spaces which process enclave work.

For a detailed description about how performance is managed in address spaces with enclaves, see [z/OS MVS Programming: Workload Management Services](#).

Migration considerations for an increased notepad size

Starting with z/OS V2R1 the maximum notepad size in the WLM service definition has increased from 500 to 1000 lines. If you plan to use more than 500 lines of notepad information for your WLM service definition, you need to re-allocate the WLM couple data set.

Before you install a service definition with more than 500 lines of notepad information on z/OS V2R1, perform the following steps:

1. Allocate a new WLM couple data set using the IXCL1DSU utility, as described in [“Allocate a WLM couple data set”](#) on page 138. Use the current NUMBER specification for each section (POLICY, WORKLOAD, SRVCLASS, etc.).

Note that by using z/OS V2R1 to allocate your WLM couple data set, the allocated space will be sufficient for the increased notepad size. Ensure that the values provided for number of policies, workloads, and service classes are the current values because these values will be used by WLM to calculate the space required. Specifying higher values to allow for growth is acceptable.

2. Switch to the new WLM couple data set or sets, as described in [“Make a newly formatted couple data set available to the sysplex”](#) on page 141.
3. Update the COUPLExx parmlib member to specify the new WLM couple data set or couple data sets.

If WLM determines during policy installation that the WLM couple data set is too small to hold the notepad information, the WLM administrative application issues message IWMAM047:

```
WLM couple data set is too small to hold the service definition.
```

It is also possible that message IWMAM044 is issued:

```
Install failed, service definition is not valid.  
Validation reason code: 2903,  
Validation offset: 0.
```

where validation reason code 2903 means “Number of notepad entries (SVNPANPN) exceeds the maximum number allowed (500)”.

If the IWMDINST service is used for policy installation and the WLM couple data set is too small to hold the notepad information, it returns RC 8 with Reason Code xxxx083D and VALCHECK_RSN xxxx2903.

To resolve this issue, allocate and activate a new, larger WLM couple data set.

For further information refer to [“WLM application messages”](#) on page 206 and to [Appendix B. Application Validation Reason Codes](#) in [z/OS MVS Programming: Workload Management Services](#).

WLM managed batch initiator balancing

Starting with z/OS Release V1R4 and JES2 V1R4, and z/OS V1R5 with JES V1R5 WLM is enhanced to improve the balancing of WLM managed batch initiators between systems of a sysplex. While in earlier releases a balancing of initiators between high and low loaded systems was only done when new initiators were started, this is now done when initiators are already available. On highly utilized systems, the number of initiators is reduced while new ones are started on low utilized systems. This enhancement can improve sysplex performance with better use of the processing capability of each system. WLM attempts to distribute the initiators across all members in the sysplex to reduce batch work on highly used systems while taking care that jobs with affinities to specific systems are not hurt by WLM decisions. Initiators are

stopped on systems that are utilized over 95% when another system in the sysplex offers the required capacity for such an initiator. WLM also increases the number of initiators more aggressively when a system is low utilized and jobs are waiting for execution.

Batch Initiator Balancing improves the performance and throughput of batch workload over the sysplex. Its intention is not to reach an equally balanced distribution of batch jobs over the LPARs of a sysplex. That is why initiator balancing only comes into effect, when at least one of the systems of the sysplex has a CPU utilization of more than 95%, while other systems have more idle capacity. When the most loaded system has still enough idle capacity to run batch jobs without CPU constraints, it would not improve the total batch throughput if initiators were moved away from that system to other systems, even if the other systems had more idle CPU capacity.

Consider resource group maximum in WLM batch initiator management

Starting with z/OS V1R12 WLM considers the resource group maximum and whether the projected increase in service demand will not exceed the resource group maximum. When the service is already capped due to the resource group maximum, then no additional initiators are started.

Note: This resource maximum check is not done on a LPAR for a service class if WLM has not started an initiator for that particular service class on that LPAR, or if WLM has only started initiators in that service class on other LPARs in the sysplex. In this case, WLM can start an initiator for that service class on that LPAR even if resource group capping is already active for that service class. Otherwise, WLM cannot determine how much capacity is being used on average by a batch job for that service class.

Migration considerations for service definition coefficients

Starting with z/OS V2R5, service definition coefficients can no longer be specified in the WLM ISPF application and are no longer considered when computing the amount of service consumed. If you had specified coefficient values other than the IBM-recommended values ($CPU = 1$, $SRB = 1$, $IOC = 0$, and $MSO = 0$) and did not change them before migrating to z/OS V2R5 or later, review the durations for any multi-period service classes and adjust them accordingly.

Before z/OS V2R5, period duration was calculated by the following formula:

$$DUR = (CPU \times CPU \text{ service units}) + (SRB \times SRB \text{ service units}) + (IOC \times I/O \text{ service units}) + (MSO \times storage \text{ service units})$$

where *CPU*, *SRB*, *IOC*, and *MSO* were the defined WLM service coefficients.

Starting with z/OS V2R5, the following formula applies:

$$NEW \text{ DUR} = CPU \text{ service units} + SRB \text{ service units}$$

To convert *DUR* into *NEW DUR*, use the following formula:

$$NEW \text{ DUR} = DUR \div Total \text{ service units} \times ((CPU \text{ service units} \div CPU) + (SRB \text{ service units} \div SRB))$$

where *CPU* and *SRB* are the old service coefficients, and *Total service units* is the sum of *CPU*, *SRB*, *IOC*, and *MSO* service units. These values should be collected for a peak period interval from, for instance, the RMF Postprocessor Workload Activity (WLMGL) report.

Example:

Given the following values:

- Old *DUR* is 90000.
- Old default service coefficients used are $CPU = 10$, $SRB = 10$.
- Values from RMF WLMGL peak period interval:

```
TOTAL_SU = 6218K
CPU_SU   = 5877K
SRB_SU   = 95667
```

NEW DUR is calculated as follows:

$$NEW\ DUR = 90000 \div 6218K \times ((5877K \div 10) + (95667 \div 10)) = 8645$$

When changing the durations in the WLM service definition, accounting procedures might also need to be adjusted.

Chapter 18. Defining a coupling facility structure for multisystem enclave support

Some work managers split large transactions across multiple systems in a parallel sysplex, improving the transaction's overall response time. These work managers can use multisystem enclaves to provide consistent management and reporting for these types of transactions.

Among the benefits of using multisystem enclaves:

- All parts of a split transaction are managed to the same service class. If the service class has multiple periods, the CPU usage of the entire transaction is used to switch periods.
- The enclave owner's SMF 30 record includes CPU time accumulated by all of its split transactions, for *all* systems on which they executed.

Before using multisystem enclaves, an installation needs to define a specific coupling facility structure named SYSZWLM_WORKUNIT in the CFRM policy. Once the CFRM policy with this structure definition is activated, WLM will automatically connect to the structure, enabling the use of multisystem enclaves.

This information shows how to define the SYSZWLM_WORKUNIT structure, a prerequisite to the use of multisystem enclaves. For more information on defining coupling facilities, see [z/OS MVS Setting Up a Sysplex](#).

Programs that use data from the SMF 30 record may need to be updated in conjunction with multisystem enclave support. The enclave owner's SMF 30 record has new fields containing the CPU time accumulated by all of its split transactions, for *all* systems on which they executed.

For more detailed information on multisystem enclaves, see the “Creating and Using Enclaves” in [z/OS MVS Programming: Workload Management Services](#).

Defining the coupling facility

It may be difficult to size the SYSZWLM_WORKUNIT structure at first, as there is no sure way to know exactly how many parallel units-of-work may exist at any given time. The best option is take a best guess at the initial and maximum sizes and then alter the structure size based on performance and/or change in demand.

If the structure's maximum size is defined too low, work managers will experience failures when they try to export enclaves. It is the work manager's responsibility to respond to such a failure. The work requests may instead be run locally (increasing the response time), or the work requests may fail.

The best way to estimate the storage size needed is to use the CFSIZER tool, which you can find at [Coupling Facility sizer \(www.ibm.com/support/docview.wss?uid=isg3T1027062\)](http://www.ibm.com/support/docview.wss?uid=isg3T1027062).

Alternately, there are formulas in *PR/SM Planning Guide* to help estimate the storage size needed. As shown in [Table 15 on page 147](#), the TDEC value is the estimated number of concurrently executing parallel units-of-work. Use the TDEC estimate along with the other values explicitly given in the table, as follows:

Table 15. Values to use in storage estimation formulas		
Value	Description	Specify:
TDEC	Total directory entry count — the maximum number of concurrently executing parallel units of work	Best estimate
TDAEC	Total data area element count	TDEC X 2
MSC	Maximum number of storage classes	1
MCC	Maximum number of castout classes	1
MDAS	Maximum number of data area elements associated with a directory entry	32

Table 15. Values to use in storage estimation formulas (continued)

Value	Description	Specify:
DAEX	Data area element characteristic	3
AAI	Adjunct assignment indicator	0
R_de/R_data	Directory to data ratio	1/2

Once you have estimated the initial and maximum sizes for the SYSZWLM_WORKUNIT structure, define the structure as described in [z/OS MVS Setting Up a Sysplex](#). Keep the following points in mind:

- WLM requests a coupling facility with “default” connectivity.
- Non-volatility is not required.
- The coupling facility control code must be at CFLEVEL 9 or higher.

The following sample JCL shows the definition of a SYSZWLM_WORKUNIT structure:

```
//POLICYX JOB ...
//STEP1 EXEC PGM=IXCMIAPU
//SYSPRINT DD SYSOUT=A
//SYSIN DD *

DATA TYPE(CFRM) REPORT(YES)

DEFINE POLICY NAME(POLICY1) REPLACE(YES)

CF NAME(FACIL01)
TYPE(123456)
MFG(IBM)
PLANT(02)
SEQUENCE(123456789012)
PARTITION(1)
CPCID(00)
SIDE(0)
DUMPSPACE(2000)

CF NAME(FACIL02)
TYPE(123456)
MFG(IBM)
PLANT(02)
SEQUENCE(123456789012)
PARTITION(2)
CPCID(00)
SIDE(1)
DUMPSPACE(2000)

STRUCTURE NAME(SYSZWLM_WORKUNIT)
SIZE(4000)
INITSIZE(3328)
PREFLIST(FACIL02,FACIL01)
```

Shutting down the coupling facility

If it becomes necessary to shut down a coupling facility containing the SYSZWLM_WORKUNIT structure (either to apply maintenance or to reconfigure), there are two options:

- If another coupling facility has enough storage available, use the XES system-managed rebuild function to rebuild the SYSZWLM_WORKUNIT structure into another coupling facility. See [z/OS MVS System Commands](#) for more information.
- If there is no other coupling facility into which the SYSZWLM_WORKUNIT structure can be rebuilt, the structure will be deleted when its coupling facility is shut down and therefore multisystem enclave support will be disabled (as described in “Coupling facility failures” on page 149).

An installation should take the appropriate steps to quiesce any active work which may be using multisystem enclaves before shutting down the coupling facility containing the SYSZWLM_WORKUNIT structure.

Coupling facility failures

If the coupling facility containing the SYSZWLM_WORKUNIT structure fails, or if the structure itself fails, then all existing multisystem enclaves will be lost. It is the work manager's responsibility to respond to such a failure. The work manager may fail the work requests, or it may process them without using multisystem enclaves.

If another coupling facility is available, WLM will automatically create a new (empty) SYSZWLM_WORKUNIT structure in it. New multisystem enclaves can now be created for new work requests.

If the original coupling facility is still intact, but the *link* fails, then the use of multisystem enclaves is temporarily disabled. Again, it is the work manager's responsibility to respond to this situation, either failing the work requests, or processing them without using multisystem enclaves. When the link is restored, then the use of multisystem enclaves can continue.

Chapter 19. The Intelligent Resource Director

The Intelligent Resource Director (IRD) extends the concept of goal-oriented resource management by allowing you to group system images that are resident on the same physical server running in LPAR mode, and in the same Parallel Sysplex®, into an “LPAR cluster.” This gives workload management the ability to manage processor and channel subsystem resources, not just in one single image but across the entire cluster of system images. [Figure 26 on page 151](#) shows one LPAR cluster in one central processor complex (CPC):




Figure 26. One LPAR cluster on one CPC

A CPC can have multiple LPAR clusters supporting different Parallel Sysplexes, and a Parallel Sysplex can, in turn, comprise multiple LPAR clusters in different CPCs. This is illustrated in [Figure 27 on page 152](#), in which two sysplexes across two CPCs are grouped into four LPAR clusters:




Figure 27. Four LPAR clusters on two CPCs

WLM manages a Parallel Sysplex by directing work to the available resources. With the Intelligent Resource Director, WLM can additionally move resources within an LPAR cluster to the work. Processor resources are automatically moved to the partitions with the greatest need, based on the business goals of the workloads they are running. Channels are automatically moved to the I/O control units with the greatest need, based on the business goals of the workloads using them.

The LINUX partition is not part of the Parallel Sysplex, but WLM manages it as if it were part of it.

The three functions that make up the Intelligent Resource Director are as follows:

- LPAR CPU Management
- Dynamic Channel Path Management
- Channel Subsystem Priority Queuing.

Note: Dynamic channel path management and channel subsystem priority queueing also are functional in single-system environments, such as a z/OS system operating as a monoplex. If a z/OS system is operating as a monoplex, each z/OS system must be assigned a different sysplex name.

LPAR CPU management

LPAR CPU management allows dynamic adjustment of processor resources across logical partitions in the same LPAR cluster. WLM achieves this with two different mechanisms:

- **LPAR weight management**

When you divide your central processing complex into separate logical partitions, each partition is assigned its own *LPAR weight*, which corresponds to the percentage of overall processing power that is guaranteed to the work in that partition. Previously, if the workload shifted to the extent that more processing power was needed in a particular partition, the weights had to be changed manually. With LPAR weight management, you give each logical partition an initial LPAR weight, along with an optional minimum and maximum weight if desired. WLM will then dynamically balance these weights to best meet the goals of the work in the partitions, with no human intervention. Note that the total weight of the cluster as a whole will remain constant, so LPARs outside the cluster are unaffected.

LPAR weight management takes effect when two or more LPARs in the cluster are running CPU-constrained, and the CPC's shared physical CPs are fully utilized. When just one LPAR is using all or most of the CPC because other LPARs are idle, then LPAR weight management will have no effect on resource distribution.

If there are non z/OS partitions in the LPAR cluster, the Intelligent Resource Director manages the weight of these partitions by exchanging weight between the non z/OS and the z/OS partitions of the cluster. LPAR weight of any non z/OS partition will not be reset to its initial weight when the z/OS partition is reset or deactivated. Non z/OS partitions weight can be reset through the service element panel in this situation.

Note: LPAR weight management can be done for general purpose processors only. LPAR weight management is not supported for zIIPs.

- **VARY CPU management**

VARY CPU Management works for z/OS partitions only. It works hand-in-hand with LPAR weight management. As the LPAR weights change, the number of online logical CPUs is also changed to maintain the best match between logical CPU speed and physical CPU speed. Optimizing the number of logical CPUs benefits workloads that have large amounts of work done under single tasks, and minimizes LPAR overhead for all workloads.

LPAR CPU Management requires System z servers in z/Architecture® mode. z/OS images require a CFLEVEL 9 coupling facility structure. Linux for System z requires kernel 2.4 or higher. General purpose CPUs are supported, but Integrated Facility for Linux (IFL) CPUs are not supported. Vary CPU Management is automatically disabled when HiperDispatch is in effect.

Dynamic channel path management

Prior to dynamic channel path management, all channel paths to I/O control units had to be statically defined. In the event of a significant shift in workload, the channel path definitions would have to be reevaluated, manually updated via HCD, and activated or PORed into the configuration. Dynamic channel path management lets workload management dynamically move channel paths through the ESCON Director from one I/O control unit to another, in response to changes in the workload requirements. By defining a number of channel paths as *managed*, they become eligible for this dynamic assignment. By moving more bandwidth to the important work that needs it, your DASD I/O resources are used more

efficiently. This may decrease the number of channel paths you need in the first place, and could improve availability — in the event of a hardware failure, another channel could be dynamically moved over to handle the work requests.

Dynamic channel path management operates in two modes: balance mode and goal mode. In balance mode, dynamic channel path management will attempt to equalize performance across all of the managed control units. In goal mode, which is available only when WLM is operating in goal mode on *all* systems in an LPAR cluster, WLM will still attempt to equalize performance, as in balance mode. In addition, when work is failing to meet its performance goals due to I/O delays, WLM will take additional steps to manage the channel bandwidth accordingly, so that important work meets its goals.

Dynamic channel path management requires z/OS and an IBM Z server. If a system image running dynamic channel path management in LPAR mode is defined as being part of a multisystem sysplex, it also requires a CFLEVEL 9 or higher coupling facility structure, even if it is the only image currently running on the CPC.

Channel subsystem priority queuing

Channel subsystem priority queuing is an extension of the existing concept of I/O priority queuing. Previously, I/O requests were handled by the channel subsystem on a first-in, first-out basis. This could at times cause high priority work to be delayed behind low priority work. With Channel subsystem priority queuing, if important work is missing its goals due to I/O contention on channels shared with other work, it will be given a higher channel subsystem I/O priority than the less important work. This function goes hand in hand with the dynamic channel path management described — as additional channel paths are moved to control units to help an important workload meet goals, channel subsystem priority queuing ensures that the important workload receives the additional bandwidth before less important workloads that happen to be using the same channel.

WLM sets the priorities using the following basic scheme:

- System related work is given the highest priority
- High importance work missing goals is given a higher priority than other work
- Work meeting goals is managed so that light I/O users will have a higher priority than heavy I/O users
- Discretionary work is given the lowest priority in the system.

Channel subsystem priority queuing requires z/OS and a System z® server in z/Architecture mode. It does not require a coupling facility structure.

Example: How the Intelligent Resource Director works

To illustrate how the Intelligent Resource Director works in a mixed workload environment, consider this example:

- You have three workloads running on one server:
 - **Online Transactions**, your most important workload. This runs only during the day shift.
 - **Data Mining**, which has a medium importance. This is always running, and will consume as much resource as you give it.
 - **Batch**, which is your lowest importance work. Like data mining, it is always running, and will consume as much resource as you give it.
- In this example, the server is divided into two logical partitions (and both partitions are in the same sysplex):
 - **Partition 1** runs both the online transactions and the batch work, as they happen to share the same database.
 - **Partition 2** runs the data mining work.

Figure 28 on page 155 shows a day shift configuration. As the online transaction workload is the most important, Partition 1 is given a high enough weight to ensure that the online transaction work does

not miss its goals due to CPU delay. Within the partition, the existing workload management function is making sure that the online transaction work is meeting its goals before giving any CPU resource to the batch work.

Day Shift




Figure 28. Intelligent Resource Director example – Day shift

The DASD used by the online transaction work is given enough channel bandwidth to ensure that channel path delays do not cause the work to miss its goals. The channel subsystem I/O priority ensures that online transaction I/O requests are handled first. Even though the batch work is running in Partition 1 (with the increased partition weight and channel bandwidth), the data mining I/O requests will still take precedence over the batch I/O requests if the data mining work is not meeting its goals.

Figure 29 on page 156 shows the night shift, when there are no more online transactions. If the partition weights had remained the same, then the batch work would be consuming most of the CPU resource, and using most of the I/O bandwidth, even though the more important data mining work may still be missing its goals. LPAR CPU management automatically adjusts to this change in workload, adjusting the partition weights accordingly. Now the data mining work will receive the CPU resource it needs to meet its goals. Similarly, dynamic channel path management will move most of the I/O bandwidth back to the data mining work.

Night Shift




Figure 29. Intelligent Resource Director Example – Night Shift

Making the Intelligent Resource Director work

There are several tasks you need to perform to make the Intelligent Resource Director work in your installation:

- Define the `SYSZWMwnnnntttt` coupling facility structure.
- Enable LPAR CPU management.
- Enable dynamic channel path management.
- Enable channel subsystem priority queuing.

Defining the `SYSZWMwnnnntttt` coupling facility structure

Before using LPAR CPU management or dynamic channel path management in a multisystem sysplex, you need to define a specific coupling facility structure named `SYSZWMwnnnntttt` in the CFRM policy for each LPAR cluster. In each `SYSZWMwnnnntttt` structure, the 9-character `wnnnntttt` field represents a portion of the CPU ID for the CPC. To obtain this 9-character field, issue the `D M=CPU` command or `D M=CORE` command, as follows:

```
SYS1 d m=cpu
SYS1 IEE174I 13.51.42 DISPLAY M 884
...
CPC SI = 2964.7C1.IBM.02.00000000000819E7
```

The CPC type `tttt` is returned in the first 4 digits of the CPC SI. The CPC sequence number is returned in the last characters of the CPC SI.

If you plan to operate two or more CECs with identical last four-digit CPC sequence numbers and CPC type in the sysplex, define the structure as `SYSZWMnnnnntttt`, where `nnnnn` is the last 5 digits of the CPC sequence number and `tttt` is the machine type. In the previous example, the coupling facility structure would be named `SYSZWM819E72964`. Before IPLing the system, `WLMIRDSTRUC=5DIGITS` must be added to the `IEAOPTxx` member that will become active.

Otherwise you can define the structure as `SYSZWLM_nnnntttt`, where *nnnn* is the last 4 digits of the CPC sequence number and *tttt* is the machine type. In the previous example, the coupling facility structure would be named `SYSZWLM_19E72964`. In `IEAOPTxx`, you can add or default to `WLMIRDSTRUC=4DIGITS`.

Enabling LPAR CPU management

Once you have defined the `SYSZWLMwnnnntttt` coupling facility structure, the remaining actions you need to take to enable LPAR CPU Management all occurs on the hardware management console (HMC).

- In the Primary Support Element Workplace, make sure that **Not dedicated central processors** is selected in the activation profile of each logical partition. This ensures that the logical partition uses shared CPs instead of dedicated CPs. On the same panel, specify the initial and reserved number of logical CPs you want to have available to each logical partition. Production partitions which potentially need access to the full power of the CPC should be defined with the maximum number of logical CPs (equal to the number of shared physical CPs). Other partitions can be defined with a fewer number of logical CPs if they need less power, or if you want to specifically restrict them to less power. At a minimum, the number of logical CPs should be sufficient to achieve the partition's maximum weight.

For some logical partitions, you may not need to make any of those changes, as the settings are already correct. If you do need to make any of those changes, note that you need to deactivate and then reactivate the logical partition for the changes to take effect. For the remaining actions, you do *not* need to do this after making changes.

- For each logical partition that participates in LPAR weight management, do the following:
 - Make sure that **Initial Capping** is turned off. WLM cannot manage the weight of a logical partition that is capped.
 - Enter the initial processing weight. This becomes the logical partition's weight when it is first IPLed.
 - It is recommended to set a minimum and a maximum weight (zero means unlimited). These set the lower and upper limits for the weights that WLM assigns to the logical partition.
 - Check the **WLM Managed** box. This is the final step in activating LPAR weight management.

Once you have made those changes for z/OS images, you do not have to do anything else to activate VARY CPU management. You can disable VARY CPU management, if you want, by adding the keyword `VARYCPU=NO` to the `IEAOPTxx` parmlib member and then issuing the `SET OPT=xx` command to activate the change. The scope of this command is by single system. If there are multiple systems in the LPAR cluster, then the other systems continues to use VARY CPU management. You can set `VARYCPU=YES` to return the system to VARY CPU management. Note that if any CPs were taken offline by an operator, those CPs needs to be configured back online before they can again be managed by VARY CPU management. IRD weight changes are suspended for images with system recovery boost being active.

Enabling non-z/OS CPU management

In addition to the actions that you have already taken to enable LPAR CPU management, you need to do the following to enable non-z/OS CPU management:

- Before activating the Linux partition, specify the CP management cluster name under the **Options** tab of the activation profile. This causes LPAR to group the Linux partition with the appropriate sysplex.
- For the Linux partition, the system name must be set in order to activate LPAR CPU management. WLM needs the Linux system name in order to handle the Linux partition. This also applies if you use only the PX qualifier. The sysplex name that is specified in the service element panel must be the same as the z/OS sysplex name. The system name must be unique in relation to the other system names in the same sysplex. Set the system name by using the `system_name` attribute in the `/sys/firmware/cpi` directory in `sysfs`, for example:

```
# echo sysname > /sys/firmware/cpi/system_name
```

where *sysname* is a string that consists of up to 8 characters of the following set: A-Z, 0-9, \$, @, #, and blank.

Use the `set` attribute to make the setting known to LPAR CPU management, as follows:

```
# echo 1 > /sys/firmware/cpi/set
```

Depending on your Linux distribution, you might be able to configure the `system_name` in the `/etc/sysconfig/cpi` configuration file. VSE/ESA and z/VM® set the system name during IPL.

- Goals for non-z/OS partitions are specified in the WLM service definition. You can define velocity goals, but no discretionary goals. Multiple periods are not supported.

Enabling dynamic channel path management

A coupling facility structure is required if you wish to use dynamic channel path management in any logical partition containing a system that is a member of a multisystem complex (even if the system image is the only member of that sysplex on this CPC). You do not need a coupling facility structure if all the logical partitions are running in XCFLOCAL or MONOPLEX mode.

The IBM Redbook, *z/OS Intelligent Resource Director* (SG24-5952), provides extensive guidance on choosing the appropriate channels and control units for dynamic channel path management. Once you have selected them, there are two specific HCD definitions that will need to be changed:

• Channel definitions

When defining (or modifying) a channel, you must specify YES in the **Managed** field. You must also specify a dynamic switch (in this case, the ESCON Director) to which the channel is attached. You should also specify the entry switch ID and entry port so that HCD can do consistency checking.

If you are running in LPAR mode, you must also define the name of the sysplex to which a logical partition must belong in order to have this channel in its configuration. Specify this name in the **I/O Cluster** field. You must also define this channel as shared. Note that, unlike traditional shared channels which potentially can be shared by all logical partitions on a CPC, managed channels can only be shared by logical partitions in the same LPAR cluster.

Note: Ensure that each LPAR cluster name (the sysplex name that is associated with the LPAR cluster) is uniquely named across the entire CPC. As managed channels have an affinity to a specific LPAR cluster, non-unique names would create problems with the scope of control.

• Control unit definitions

Whereas non-managed channel paths (otherwise called *static* channel paths) are defined in the traditional way, via the CHPID number, a managed path is defined by specifying a double asterisk (**). The number of double asterisks you specify will limit the number of managed channel paths per LPAR cluster. The total number of non-managed and managed channel paths, per CPC, cannot exceed 8.

Important: You must define at least one non-managed channel path (which must be defined as shared) per control unit.

The control unit must be attached to a switch (again, in this case an ESCON Director) which in turn must be attached to managed channels.

After changing the HCD definitions, the remaining actions to enable dynamic channel path management occur in the Primary Support Element Workplace, as follows:

- Ensure that the CPC's reset profile is enabled for dynamic I/O.
- For an LPAR cluster environment, ensure that all partitions in the cluster are authorized to control the I/O configuration.
- Ensure that the automatic input/output (I/O) interface reset option is enabled in the CPC's reset profile. This will allow dynamic channel path management to continue functioning in the event that one participating system image fails.

If you wish to disable dynamic channel path management, issue the **SETIOS DCM=OFF** command. The **SETIOS DCM=ON** command will turn it back on. Issue the **SETIOS DCM=REFRESH** command to refresh the control unit model table (for instance, to include a new IOST`nnn` load module provided by the control unit's manufacturer).

Note: After issuing the **SETIOS DCM=OFF** command, your I/O configuration might now be unable to handle your workload needs, as it will now be in whatever state dynamic channel path management left it before being disabled. You might need to activate a new I/O configuration that will meet your workload needs across the entire LPAR cluster.

Enabling channel subsystem priority queuing

To enable channel subsystem priority queuing, you'll need to do the following:

- In the WLM ISPF application, make sure that **I/O Priority Management** is set to YES on the Service Definition Options panel.
- If your CPC is partitioned, click the **Change LPAR I/O Priority Queuing** icon in the Primary Support Element Workplace. You will see a list of all of the logical partitions. Define the range of I/O priorities that will be used by each image, specifying the minimum and maximum I/O priority numbers. It is recommended that you use a range of eight values (for example 8 to 15), as this will correspond to the number of values in the range that WLM uses. While it is not enforced, it is assumed that you'll set the same range of I/O priorities for all images in the same LPAR cluster. You can, however, prioritize multiple LPAR clusters on the same CPC by setting different ranges for each LPAR cluster.

If you have a partition running a system other than z/OS (for instance z/VM, z/TPF, z/VSE®) specify an appropriate default priority by setting the minimum and maximum to the same number. For example, if you have a z/VM partition running work that is equal in importance to the discretionary work in a z/OS partition, you could set the z/VM partition's range to 8–8, and the z/OS partition's range to 8–15. If you have critical OLTP applications running in a partition, on the other hand, you could set the range for that partition to 15–15, and the z/OS partition's range to 7–14. In this way, the OLTP work would always have a higher priority than the z/OS work.

- In the Primary Support Element Workplace, click the **Enable I/O Priority Queuing** icon. You will see a simple panel that reads “Global input/output (I/O) priority queuing.” Click on the **Enable** box. Channel subsystem priority queuing is now enabled for the entire CPC.

For more information

- For more detailed information about the Intelligent Resource Director, see the IBM Redbook, *z/OS Intelligent Resource Director*.
- For more information about defining coupling facilities, see *z/OS MVS Setting Up a Sysplex*.
- For more information about PR/SM, see *PR/SM Planning Guide*.
- For more information about the Primary Support Element Workplace, see *Support Element Operations Guide*.
- For more information about HCD, see *z/OS HCD User's Guide*.
- For more information about RMF, see *z/OS Resource Measurement Facility User's Guide*.
- For more information about the IEAOPTxx parmlib member, see *z/OS MVS Initialization and Tuning Reference*.
- For more information about any of the system commands mentioned here, see *z/OS MVS System Commands*.

Chapter 20. Using IBM z Integrated Information Processor (zIIP)

An IBM z Integrated Information Processor (zIIP) is a dedicated processor designed to operate asynchronously with the general processors in an IBM Z system to help improve utilization of computing capacity and control costs. A zIIP is designed for select data (database), cloud, and transaction (Java™) processing workloads.

zIIPs allow users to leverage additional processing power for new applications without affecting their total million service units (MSU) rating or machine model designation. Benefits of having zIIPs: When running standard CPs on a server, there are a wide variety of speeds or MSU ratings available. The zIIPs, however, always run at full speed.

When workload is dispatched onto a zIIP, the processing cycles that are used do not contribute to the MSU count and therefore do not impact software usage charges. This makes adding new applications to the IBM Z platform extremely cost-effective especially compared to competing platforms such as distributed systems or public cloud.

While zIIP exploitation for individual workloads may vary, hardware configuration updates to allocate zIIPs are minimal. Additionally, zIIP usage is transparent to the applications; no changes are needed within the application to run zIIP-eligible work.

For more information, see [IBM z Integrated Information Processor \(zIIP\) \(www.ibm.com/products/z-integrated-information-processor\)](http://www.ibm.com/products/z-integrated-information-processor).

Planning for zIIPs

The IEAOPTxx member of parmlib provides the **PROJECTCPU** statement. Specifying the **PROJECTCPU** parameter allows you to project zIIP consumption when a zIIP processor is not yet defined to the configuration. RMF and SMF will show the potential calculated zIIP time, so that an accurate zIIP projection can be made. The **PROJECTCPU** parameter can be used while running the target workload, once all software is installed that enables hardware sizing data to be produced.

You can use the **DISPLAY M=CPU** command to show if a zIIP processor is defined in the configuration. (In the **D M=CPU** command output, zIIPs are represented by the letter "I"). A zIIP processor is considered to be defined in the offline or reserved state, as well as in the online state.

See *z/OS MVS Initialization and Tuning Reference* for more information on the IEAOPTxx member of parmlib.

The SMF type 30 (IFASMFR3) and type 72 (ERBSMF72) records include zIIP consumption fields. See *z/OS MVS System Management Facilities (SMF)* for more information.

The TIMEUSED macro allows zIIP execution time to be requested in addition to the general purpose CP consumption.

Acquiring zIIPs

You can order zIIPs up to double the number of permanently purchased general purpose processors (CPs) on a given machine model. Contact an IBM representative for purchasing zIIPs for your IBM Z server. zIIPs can only be purchased as an additional processor unit (PU) for your server. That is, you cannot convert a general purpose CP that you already have to a zIIP.

It is possible to concurrently install temporary capacity by ordering On/Off Capacity on Demand Active zIIPs. The number of On/Off Capacity on Demand zIIPs that you may rent is limited by the number of permanently purchased zIIPs on a given server. On/Off Capacity on Demand zIIPs may not exceed the number of permanently purchased zIIPs on a server.

Defining zIIPs

zIIPs are configured via the normal PR/SM logical partition image profile. For more information about how to define the zIIPs to your logical partitions, see *IBM Z Processor Resource/System Manager Planning Guide*.

You can define a logical partition to use one or more zIIPs with either of the following combinations:

- One or more dedicated general purpose CPs and one or more dedicated zIIPs
- One or more shared general purpose CPs and one or more shared zIIPs

There are the following requirements regarding zIIPs and general purpose CPs:

- You must have at least one general purpose CP defined for a partition. The z/OS system needs at least one general purpose CP online at all times.
- You can have as many zIIPs defined as you want for a partition as long as the number does not exceed twice the number of general purpose CPs for your server.
- With the implementation of multi-threading, a zIIP can operate with two concurrently dispatchable units of zIIP work, compared to one dispatchable unit of work on a general purpose CP (albeit less than 2:1 in capacity).
- You can set the number of zIIPs for an LPAR, and each processor pool (for example, CPs and zIIPs) can be assigned a unique weight when the processors are being shared.
- There is hard capping for zIIPs, but there is no support of defined capacity (which is the WLM support for 4-hour rolling average). The existing single set of PR/SM logical partition processor weights (INITIAL, MIN, MAX) are applied independently to the shared general purpose CPs; capping only applies to shared general purpose CPs configured to the logical partition. If you use WLM weight management for the LPAR with SCRT, then z/OS WLM manages shared general purpose CPs as today, but not the zIIPs.
- zIIPs do not participate in Intelligent Resource Director. zIIPs do not participate in dynamic share management or in the number of logical zIIPs online.

Note that zIIPs are brought online and offline like general purpose CPs.

Combining zIIP-enabled sysplex members with non-zIIP enabled sysplex members is supported.

Reviewing parameter settings

Use the following information to review z/OS and Java parameter settings.

Review z/OS parameter settings

zIIP-eligible work may also execute on general purpose CPs in order to achieve workload goals.

The IEAOPTxx member of parmlib contains the **IIPHONORPRIORITY** statement which controls the workflow to zIIPs. If you specify IIPHONORPRIORITY=YES this indicates that general purpose CPs may execute zIIP-eligible and non-zIIP-eligible work in priority order, if zIIP processors are unable to execute all zIIP-eligible work. This is the default.

Specifying IIPHONORPRIORITY=NO means that general purpose processors will not process zIIP processor eligible work *unless it is necessary* to resolve contention for resources with non-zIIP processor eligible work.

If you specify NO for Honor Priority when defining a service class, work in this service class does not receive help from general purpose CPs when there is insufficient zAAP or zIIP capacity for the workload in the system, regardless of the setting for IIPHONORPRIORITY in parmlib member IEAOPTxx. General purpose CPs may still help when it is necessary to resolve contention for resources with general purpose CP work.

See [z/OS MVS Initialization and Tuning Reference](#) for more information about the IEAOPTxx member of parmlib.

Review Java parameter settings

The **-Xifa** option enables Java applications on zIIPs if they are available. The default value for the **-Xifa** option is on. See IBM SDK, Java Technology Edition (www.ibm.com/docs/en/sdk-java-technology/7?topic=options-xifa-option) for more information.

Chapter 21. System Recovery Boost

Starting with IBM z15, System Recovery Boost can deliver higher processor capacity for a limited time after an IPL, while shutting down a system, or during specific, short-term sysplex recovery events. The increased capacity can be provided in one or more of the following ways:

- In an LPAR on a sub-capacity machine, by utilizing the full speed for the general purpose processors of the boosted partition (speed boost)
- Dispatching some work on z Integrated Information Processors (zIIP), even if the work is not eligible for zIIP (zIIP boost)
- Configure online zIIPs that are in the standby state for the duration of the boost period (zIIP boost)

While the boost is in effect, any defined capacity and group capacity limits remain in effect. However, WLM can manage the system slightly differently than at regular non-boosted periods:

- Overachieving non-discretionary work will not be capped to allow for higher throughput of discretionary work; that is, during the boost periods the system behaves as if Deactivate Discretionary Goal Management had been defined as Yes in the service definition.
- Resource groups and tenant resource groups will not be capped on boosted systems. For resource groups with a sysplex-wide limit, the non-boosted systems will cap the resource group as if no consumption had taken place on the boosted systems.
- The system long-term average consumption is based on the general purpose processor consumption assuming standard processor rating. Consequently, both zIIP boost and speed boost will not directly contribute to the four-hour rolling average MSU consumption.
- CPU protection is assigned to critical work. That is, any single-period service class of importance 1 or 2 is implicitly set to CPU Critical which ensures that less important work will have a lower dispatching priority. When the boost periods ends, the CPU Critical option is reset to the state as defined in the currently active WLM policy.
- Intelligent Resource Director (IRD) will not take weight management actions for LPARs that are being boosted.

For IPL boost, the WLM Sysplex Routing services may start reducing the routing weight as the end of the IPL boost period approaches and before the system returns to its regular capacity. When required, the lead time can be influenced via the RTBELEADTIME parameter in the IEAOPTxx member. When shutdown boost begins, the boosted system may be eliminated from the routing recommendations, or a very small weight may be assigned. Recovery boost periods have no impact on any routing recommendations; they are too short-term.

Starting with IBM z16, the System Recovery Boost solution is extended by an additional recovery process boost case for customer-selected middleware starts and restarts. By default, no system is boosted when starting or restarting middleware, but you may configure which started-task middleware region you want to be boost-eligible in WLM classification rules. See [“Defining recovery process boost for middleware recycle”](#) on page 77 for details. The recovery process boost expedites startup and recovery for the middleware regions and restores ready-state operations as quickly as possible with additional capacity for workload catch-up following the restart.

Chapter 22. Using the WLM ISPF application

This information explains how to use the ISPF application. It explains the functions that are available, and how you can navigate through the panels.

Before you begin

You should prepare at least one service policy and your classification rules to be ready to start using the ISPF application. Your service policies and classification rules make up a service definition. You can store a service definition in the following kinds of data sets:

WLM couple data set

In order for all systems in a sysplex to process with an active service policy, they must all be able to access a service policy. They all access the policy from a WLM couple data set. To use workload management, you must allocate a WLM couple data set, define it to the sysplex, and install your service definition onto it. You can allocate the WLM couple data set from the application. Only one service definition can be installed on the WLM couple data set.

MVS partitioned data set (PDS)

You do not need to preallocate the data sets. You specify a data set name, and the application allocates it for you. You can save one service definition per MVS PDS.

Notes:

1. If you use customized data sets in your installation, or if you use DFSMS, you can use WLM application exits IWMAREX1 and IWMAREX2 to specify those changes. See [Appendix A, “Customizing the WLM ISPF application,”](#) on page 217 for how to code the exits.
2. The data set *prefix*.WLM.SAVE*xx* (where *prefix* is either the data set name prefix of the user ID running the application, or, if no prefix is defined, the user's TSO ID, and *xx* is some numeric value, such as SAVE01) is allocated by the WLM application for recovery and is deleted by WLM upon exiting the application. This naming convention should therefore not be used for a new service definition.

MVS sequential data set (PS)

You can store a service definition in XML format in a sequential data set. You need not preallocate the sequential data sets. Specify a data set name, then the application allocates it for you.

Notes:

1. If you use customized data sets in your installation, or if you use DFSMS, you can use WLM application exits IWMAREX1 and IWMAREX2 to specify those changes. See [Appendix A, “Customizing the WLM ISPF application,”](#) on page 217 for how to code the exits.
2. The data set *prefix*.VDEF.TEMP.Ddddddd.Ttttttt (where *dddddd* is the current date, *tttttt* is the current time, and *prefix* is either the data set name prefix of the user ID running the application, or, if no prefix is defined, the user's TSO ID) is allocated by the WLM application to temporarily save the XML service definition as ISPF tables during editing. The data set is deleted by WLM upon exiting the application. The naming convention should therefore not be used for a new service definition.

Panel areas and how to use them

Most panels have a menu bar, action field, status line, scrollable area, function key area, and command line. You tell the application what actions to perform by making choices or typing information on a panel.

In this topic, examples of panels and pop-ups are shown to help familiarize you with the product. The examples closely match what you see on your terminal, but in some cases the spacing or function key settings may not exactly match what you see on your terminal.

Using the menu bar

A menu bar at the top of every panel shows the actions you can take on that panel. Press F10, or the Home key on some terminals, to move the cursor to the beginning of the menu bar from any position on a panel.

Figure 30 on page 168 shows an example of the menu bar on the Definition menu.



Figure 30. Menu Bar on the Definition Menu

To select an action, use the Tab or cursor movement keys to position the cursor on your choice, then press ENTER.

When you select an option on the menu bar, WLM displays a pull-down with choices related to the option you selected. While a pull-down is displayed, only the actions in the pull-down or on the menu bar are available. For example, if you select a pull-down and the option you want is not listed in it, you can select another pull-down on the menu bar.

To select an option in a pull-down, type the number of your choice in the action field and press ENTER. You can also use the cursor movement keys to position the cursor on your choice, then press ENTER. Figure 31 on page 168 shows an example of the pull-down choices on the File option on the Definition Menu.




Figure 31. Definition Menu File Choices

Using the menu bar on selection lists

The menu bar is a bit different on selection lists. You type a slash next to the name of the object you want to work with in the action field. Then, move to the menu bar, select an option, and press ENTER. You then choose the desired action from the pull-down.

For example, from the service class selection list, choose the STC_1 service class, move to the menu bar on the Service-Class option, and press ENTER. Then, type 3 in the menu pull-down, and press ENTER.

```

Service-Class View Notes Options Help
*****
* 3 1. Create *      Service Class Selection List      ROW 14 TO 26 OF 29
* 2. Copy *
* 3. Modify *
* 4. Browse * Create, 2=Copy, 3=Modify, 4=Browse, 5=Print, 6=Delete,
* 5. Print * Menu Bar
* 6. Delete *
* 7. Exit *
*****
Description                                Workload
-- MDLIMSR      IMS Model response          TRNIMS
-- PRDCICS
-- PRDCICSM     MSA application             PRDCICS
-- PRDIMSNR     Prod IMS non-response       PRDIMS
-- PRDIMSR      IMS response               PRDIMS
/ STC_1         Highest Priority stc         STC
-- STC_2        High Priority stc           STC

```

Figure 32. Service Class Selection List

Using the status line

Some, but not all panels have a status line. A status line is displayed on the right side of a panel or pop-up beneath the title. The status line indicates the number of items or lines currently displayed in a list or topic, and the total size of and your current location in that list or topic.

For example, a service class selection list status line such as Row 1 to 8 of 16 states that displayed in the panel is a list of eight of the 16 service classes contained in the service definition.

Using the scrollable area

On selection list type panels, there is a scrollable area that contains a list or text. In a service class selection list you see a list of service classes. The status line shows how many service classes there are in the list. You scroll backward or forward to move through the list. Selection lists can also be pop-ups, such as selecting a workload from a list to associate it with a service class.

Using the menu bar on a selection list

On selection lists, you can select the object you want to work with before you select actions you want to perform from the menu bar.

To mark items for selection in a scrollable area, type a slash (/) over the underscore in front of the listed choice. When you select an menu bar item, the application performs the action for the marked items only.

Figure 33 on page 169 shows an example of the scrollable area on a service class selection list. The first two service classes are marked with a / for actions on the menu bar.

```

Service-Class View Notes Options Help
-----
Service Class Selection List      ROW 13 TO 24 OF 29

Action Codes: 1=Create, 2=Copy, 3=Modify, 4=Browse, 5=Print, 6=Delete,
              /=Menu Bar

Action  Class      Description                                Workload
/      PRDIMS      IMS Production                                PRDIMS
/      PRDCICS
--     PRDCICSM     MSA application                                PRDCICS

```

Figure 33. Service Class Selection List panel

Using the Action field

The action field is where you specify the action to take. On the definition menu, the action field is where you specify the workload management object that you want to work with. The action codes are standard in the application—except on a few selection lists, such as the subsystem type selection list in classification rules, and the service policy selection list. [Figure 34 on page 170](#) shows the action codes and action field on the subsystem type selection list.

Note: The menu bar pull-down choices for the file match the action codes on the selection lists. So you can choose the method according to your preference.

```
Subsystem-Type  View  Notes  Options  Help
-----
Subsystem Type Selection List for Rules      ROW 1 TO 10 OF 10
Command ==> -----
Action Codes: 1=Create, 2=Copy, 3=Modify, 4=Browse, 5=Print, 6=Delete,
              /=Menu Bar

Action  Type      Description                      -----Class-----
--      ASCH      IBM-defined USAA almost modified      Service    Report
--      CICS      IBM-defined USAA modified              PRDCICS
```

Figure 34. Action field on the Subsystem Type Selection List panel

Using the command line

The command line is displayed according to the currently active user profile. You can issue the following commands from the command line:

- =value**
Repeats the previous command.
- BACKWARD**
Scrolls backward.
- DOWN**
Scrolls forward.
- EXIT**
Exits the panel.
- FORWARD**
Scrolls forward.
- FKA ON|OFF**
Determines whether to display the function key area.
- HELP**
Displays the help panel for the displayed panel.
- KEYLIST**
Displays the keylist utility where you can adjust PF key settings.
- PFSHOW**
Shows the PF key settings.
- RETRIEVE**
Displays any previous command.
- UP**
Scrolls backward.

Using the function keys

The function key area at the bottom of each panel or pop-up displays actions that you can complete by pressing a function key. When a pop-up is displayed, you can press only the function keys listed in that pop-up, not the keys listed at the bottom of the panel.

Standard actions are assigned to function keys 1 through 12 and are repeated for function keys 13 through 24. The function key assignments can vary slightly, depending on options selected during installation. If you want to customize the key settings for your installation, you can use the KEYLIST utility. See [“Customizing the keylists” on page 223](#) for more information about how to customize the key settings.

The WLM application displays function keys 1 to 12. If you want to display function keys 13 to 24, or see the standard function key settings, see *ISPF Dialog Management Guide and Reference*.

Figure 35 on page 171 shows a sample of the function keys on the Service Class Selection list.

F1=Help F9=Swap	F2=Split F10=Menu Bar	F3=Exit F12=Cancel	F4=Return	F7=Up	F8=Down
--------------------	--------------------------	-----------------------	-----------	-------	---------

Figure 35. Function key area

Starting the WLM application

The application is shipped in the IPCS library. When you start the application, the system needs to concatenate the WLM/IPCS data sets, allocate some data sets, and then invoke the WLM panels.

To start the application, specify:

```
ex 'SYS1.SBLSCLI0(IWMARIN0)'
```

If you have different data set conventions for your IPCS data sets, or if you use storage managed data sets, you should use the WLM application exits IWMAREX1 and IWMAREX2. For more information about IWMARIN0 and how to customize the application with the WLM exits, see [Appendix A, “Customizing the WLM ISPF application,” on page 217](#).

Now you're started

Upon entry to the interface, the WLM logo panel is displayed. Press Enter to continue, and the application displays the **Specify Definition** pop-up as shown in [Figure 36 on page 171](#). You should then specify which service definition you want to work with. You can work with one service definition at a time in the application.

```
Choose Service Definition

Select one of the following options.
-- 1. Read saved definition
   2. Extract definition from WLM
      couple data set
   3. Create new definition
```

Figure 36. Choose Service Definition pop-Up

If this is your first time in the application, choose option 3, **Create a new service definition**. This option brings you to the definition menu, where you can define your service definition. Once you created a new service definition, upon exiting the application, you can either:

- Save the service definition in a PDS as ISPF tables, or in a PS as XML.

The application prompts you for a data set name, allocates the data set, and saves the service definition.

- Install the service definition on the WLM couple data set.

The install option puts the service definition currently displayed in the application out on the WLM couple data set. When installed, any changes you made to the service definition are available when you

activate a policy. [“Installing and extracting a service definition” on page 204](#) explains how to install a service definition.

- Discard the service definition.

If you want to edit a service definition previously defined and stored in an MVS data set, choose option 1, **Read saved definition**.

If you want to work with the service definition on the WLM couple data set, choose option 2, **Extract definition from WLM couple data set**. You must have previously installed a service definition on the WLM couple data set. [“Installing and extracting a service definition” on page 204](#) explains how to extract a service definition.

Using the Definition Menu

The definition menu is the central place for entering your service definition. When you set up a service definition, you must enter a service definition name and optionally, a description on the Definition Menu.

[Figure 37 on page 172](#) shows a sample Definition Menu with the service definition name and a description filled in.

```
File Utilities Notes Options Help
-----
Functionality LEVEL001          Definition Menu          WLM Appl LEVEL025
Command ==> -----

Definition data set . . : none

Definition name . . . . . (Required)
Description . . . . .

Select one of the following options.
--- 1. Policies                      12. Tenant Resource Groups
     2. Workloads                   13. Tenant Report Classes
     3. Resource Groups
     4. Service Classes
     5. Classification Groups
     6. Classification Rules
     7. Report Classes
     8. Service Definition Options
     9. Application Environments
    10. Scheduling Environments
    11. Guest Platform Management Provider
```

Figure 37. Definition Menu panel

When you define your service definition for the first time, you should define it in the following order:

1. Policies

A policy consists of a name, a description, and policy overrides. The first time you set up a service definition, define a policy name and description. If you do not have a business need to change your goals, you can run with one service policy, without any policy overrides.

You use a policy override only if you have a business need to change a goal for a certain time, such as for the weekend, or for nighttime. You can define your policy overrides once you have defined your service classes.

2. Workloads

A workload logically consists of a group of one or more service classes. You associate a workload with a service class in the Service Class panel. Enter your workloads before creating your service classes.

3. Resource groups (optional)

A resource group is a minimum or maximum amount of processing capacity. You associate a resource group with a service class in the Service Class panel. Enter resource groups before creating your service classes.

4. Tenant resource groups (optional)

A tenant resource group is comparable to a resource group but accepts and processes a 64-character Solution ID. The processor consumption of all work classified into tenant report classes assigned to the tenant resource group is provided for metering capabilities.

5. Service classes

A service class is a group of work with similar performance goals, resource requirements, or business importance. You make the association with a workload and a resource group in the service class panel. You associate a service class with incoming work in the classification rules panel. Enter service classes before creating classification rules.

Policy overrides

Once you have created a service class, resource groups, or tenant resource groups, you can create a policy override. You specify the policy override by selecting Policies from the Definition Menu, and then specifying the action code for Override service class or Override resource group or Override tenant resource group.

6. Classification groups (optional)

You use groups to simplify classification. You associate a classification group with a service class in the classification rules panel. If you intend to use them, create groups before creating classification rules. See [Chapter 10, “Defining classification rules,” on page 57](#) for descriptions of group qualifiers.

7. Classification rules

Classification rules assign incoming work to service classes. Before you create your classification rules, you must understand which subsystem's work is represented in each of your service classes.

When you choose the option Classification Rules, you go to the Subsystem Type Selection List for Rules. This selection list is primed with all of the IBM-Supplied subsystem types. They are reserved names.

8. Report classes (optional)

A report class is a group of work for which you want reporting data. You must define report classes before assigning them to work in classification rules.

9. Tenant Report classes (optional)

A tenant report class is a report class that is assigned to a tenant resource group. When assigning work in classification rules to a tenant report class, the processor consumption is provided for metering capabilities of the tenant resource group.

10. Service definition options

This panel contains the following options:

- **I/O priority management:** The default is **no**, meaning that I/O priorities will be the same as dispatching priorities. Specifying **yes** means I/O priorities should be managed separately from dispatching priorities, according to the goals of the work. See [“Specifying I/O priority management” on page 95](#) for more information.
- **Enable I/O priority groups:** The default is **no**, meaning that I/O priority groups are ignored. Specifying **yes** will cause workload management to consider I/O priority groups. Work in service classes assigned to I/O priority group HIGH always has higher I/O priority than work in service classes assigned to I/O priority group NORMAL. When you specify **yes**, you also need to specify **yes** for I/O Priority Management. See [“Enabling I/O priority groups” on page 95](#) for more information.
- **Dynamic alias tuning management:** The default is **no**, meaning that dynamic alias management is disabled for the entire sysplex. Specifying **yes** will cause workload management to dynamically reassign parallel access volume aliases to help work meet its goals and to minimize IOS queueing. See [“Specifying dynamic alias management” on page 96](#) for more information.
- **Deactivate Discretionary Goal Management** The default is **no**, meaning that discretionary goal management is enabled. Specifying **yes** will cause workload management to deactivate discretionary goal management. See [“Deactivate discretionary goal management” on page 98](#) for more information.

11. Application Environments

An application environment is a group of application functions invoked by request and executed in server address spaces. You can have workload management start and stop these server address spaces automatically, or do this manually or through automation. You define the application environment, an optional procedure name for starting the server address spaces, and any start parameters needed for the start procedure.

12. Scheduling Environments

A scheduling environment is a list of resource names along with their required states. By associating incoming work with a scheduling environment, you ensure that work is assigned to a system only if that system satisfies all of the requirements. You define the scheduling environment, listing all of the resource names and required states that are contained within. You also define the resource names themselves.

13. Guest Platform Management Provider (GPMP)

Starts the guest platform management provider (GPMP) to allow for performance management of zEnterprise systems.

Using the menu bar on the Definition Menu

The menu bar on the Definition Menu has some functions not accessible from any other panel in the application. From the menu bar, you can:

- Verify a service definition
- Allocate a WLM couple data set
- Install a service definition on the WLM couple data set
- Activate a service policy

Table 16 on page 174 shows the options available from the menu bar on the Definition Menu. Each of the options are explained.

Table 16. Menu bar options on the Definition Menu

File	Utilities	Notes	Options	Help
New Open Save Save as Print Print as GML Cancel Exit	Install definition Extract definition Activate service policy Allocate couple data set Allocate couple data set using CDS values Validate definition	Edit notepad	Process ISPF list data set	General Help Keys Help Using Help Tutorial About...

File

New

Use new to define a new service definition.

Open

Use open to read a previously defined service definition. The Read saved definition panel is displayed, where you can specify the data set name.

Save

Use save to save the currently displayed service definition.

Save as

Use Save as to save the currently displayed service definition in a PDS as ISPF tables or in a PS as XML. The Save to... panel is displayed where you can specify the data set name and the save format. You do not need to preallocate the data set. If the data set does not exist, the application displays the Create Data Set? panel where you can continue with the data set create.

Print

Use Print to print the complete service definition to the ISPF list data set. Use the Options menu bar option to process the ISPF list data set. This option requires no formatting step.

Print as GML

Use Print as GML for a more readable, tabular display of service definition objects and values. This option creates a source data set with GML starter set tags imbedded. The data set must be allocated as variable block with logical record length 255. This data set can then be formatted with the SCRIPT/VS processor.

Cancel

Use cancel to cancel any actions performed. Cancel is the same as using the cancel PF key.

Exit

Use exit to exit from the definition menu and the application. Exit is the same as using the exit PF key.

Utilities**Install definition**

Use this option to install the service definition onto the WLM couple data set. Installing the service definition makes any changes available for policy activation.

Extract definition

Use this option to extract the service definition previously installed on the WLM couple data set.

Activate service policy

Use this option to activate a policy. When you select this option, the application displays a list of the service policies defined in the service definition currently installed on the WLM couple data set. You activate the service policy by selecting it from the list.

Note: If you have just made changes for a service definition, make sure you install it to have the changes take effect.

Allocate couple data set

Use this option to allocate both your primary and alternate WLM couple data sets. This option is for users who are allocating a WLM couple data set for the first time, or need a size recommendation which ensures that the service definition they are currently working with fits into the newly allocated WLM couple data set.

All other users should use the option "Allocate couple data set using CDS values". To make the WLM couple data set available for use in the sysplex, you must update your COUPLExx parmlib member and issue the SETXCF command.

Allocate couple data set using CDS values

Use this option to allocate both your primary and alternate WLM couple data sets based on your existing WLM couple data set size. The application displays the current size values on the panel.

To make the WLM couple data set available for use in the sysplex, you must update your COUPLExx parmlib member and issue the SETXCF command.

Validate definition

Use this option to verify that your service definition is free from certain errors that would otherwise be flagged when you attempt to save or install the service definition.

Notes**Edit notepad**

Use this option to create and edit a notepad. You can use the notepad to keep track of changes made to all parts of a service definition.

Options**Process ISPF list dataset**

Use this to process the list data set if you have previously done a Print.

Help

General Help

Use general help for information about the panel currently displayed.

Keys Help

Use keys help for information about the using PF keys.

Using Help

Use this option for information about how to get help while using the WLM application.

Tutorial

Use the tutorial option for information about how to use the panels. This options provides context-specific examples and scenarios.

About...

This option provides information about the copyright and license.

Working with service policies

When you choose the **Policy** option for the first time, the application displays the Create a Service Policy panel. [Figure 38 on page 176](#) shows a sample panel.

```
Service-Policy  Notes  Options  Help
-----
                          Create a Service Policy

Enter or change the following information:

Service Policy Name  . . . . . _____ (Required)
Description          . . . . . _____

Command ==> _____
```

Figure 38. Create a Service Policy panel

Once you have created a service policy, any other time you choose the policy option from the definition menu, the application displays a policy selection list. From here, you can modify your policy description, print and browse your service policies, and define your service policy overrides. [Figure 39 on page 177](#) shows a Service Policy Selection List panel.

```
Service-Policy View Notes Options Help
-----
Service Policy Selection List                                ROW 1 TO 3 OF 3

Action Codes: 1=Create, 2=Copy, 3=Modify, 4=Browse, 5=Print, 6=Delete,
              7=Override Service Classes, 8=Override Resource Groups,
              /=Menu Bar

Action  Name      Description                                ---Last Change---
--      HOLIDAY    Policy for shut-Down holidays      User      Date
--      WEEKDAY    Policy for Mon - Friday           KIRSTEN   1996/12/04
--      WEEKEND    Policy for Fri - Sun              KIRSTEN   1996/12/04
***** BOTTOM OF DATA *****

Command ==> _____
```

Figure 39. Service Policy Selection List panel

Working with workloads

When you choose the **Workload** option for the first time, the application displays the Create a Workload panel. [Figure 40 on page 177](#) shows a Create a Workload panel.

```
Workload Notes Options Help
-----
Create a Workload

Enter or change the following information:

Workload Name . . . . . _____ (Required)
Description . . . . . _____

Command ==> _____
```

Figure 40. Create a Workload panel

You associate the workload with a service class in the service class panel.

Once you have created a workload, any other time you choose the workload option from the definition menu, the application displays a workload selection list. The Workload Selection List is similar to the Policy Selection List. From here, you can modify your workload description, print, and browse your workloads. [Figure 41 on page 178](#) shows a Workload Selection List.

```
Workload  View  Notes  Options  Help
-----
Workload Selection List                                ROW 1 TO 9 OF 9

Action Codes: 1=Create, 2=Copy, 3=Modify, 4=Browse, 5=Print, 6=Delete,
              /=Menu Bar

Action  Name      Description      ---Last Change---
      User      Date
---
--- APPC          All batch          KIRSTEN  1996/10/07
--- BATCH         IMS application   KIRSTEN  1996/10/07
--- APIMS         CICS Production  KIRSTEN  1996/10/07
--- PRDCICS       CICS Production  ADRIAN   1996/10/17
--- PRDIMS        IMS Production   ADRIAN   1996/10/17
--- STC           Started tasks    KIRSTEN  1996/10/07
--- TRNCICS       CICS training    KIRSTEN  1996/10/07
--- TRNIMS        IMS training     GEORGEN  1996/10/07
--- TSO           All TSO          GEORGEN  1996/10/07
***** BOTTOM OF DATA *****

Command ==> _____
```

Figure 41. Workload Selection List panel

Working with resource groups

To define a resource group, choose option **3** on the Definition menu. Define a name, description (optional), resource group type (1, 2, 3, or 4), minimum capacity, maximum capacity, and memory limit. You must specify a value for at least one of these: minimum capacity, maximum capacity, or memory limit. If you want to include the consumption of specialty processors in the capacity minimum and maximum, specify YES in the corresponding field. Associate the resource group with a service class on the service class panel. [Figure 42 on page 178](#) shows the Create a Resource Group panel. (The panels for modifying an existing resource group and overriding attributes of a resource group in a service policy look exactly the same.)

```
Resource-Group  Notes  Options  Help
-----
Create a Resource Group

Command ==> _____

Enter or change the following information:

Resource Group Name . . . . . _____ (required)
Description . . . . . _____

Define Capacity:
-- 1. In Service Units (Sysplex Scope)
   2. As Percentage of the LPAR share (System Scope)
   3. As a Number or CPs times 100 (System Scope)
   4. In accounted workload MSU (Sysplex Scope)
Minimum Capacity . . . . . _____
Maximum Capacity . . . . . _____
Include Specialty Processor Consumption NO (YES or NO)

Memory Limit (System Scope):          512 GB
```

Figure 42. Create a Resource Group panel

As with a workload, once you have created a resource group, any other time you choose the resource group option from the definition menu, the application displays a selection list. From here, you can modify your resource group description, as well as print, and browse it.

Working with service classes

Once you have defined your workloads and resource groups, you can define your service classes. Choose the **Service Class** option on the definition menu. [Figure 43 on page 179](#) shows a Create a Service Class panel. You must assign a workload to the service class in the Workload field.


```

Service-Class  Notes  Options  Help
-----
                                Create a Service Class                                ROW 1 TO 1 OF 1

Service Class Name . . . . . _____ (Required)
Description . . . . . _____
Workload Name . . . . . _____ (name or ?)
Base Resource Group . . . . . _____ (name or ?)
Cpu Critical . . . . . NO (YES or NO)
I/O Priority Group . . . . . NORMAL (NORMAL or HIGH)
Honor Priority . . . . . DEFAULT (DEFAULT or NO)

Specify BASE GOAL information. Action Codes: I=Insert new period,
E=Edit period, D=Delete period.

    ---Period---  -----Goal-----
Action # Duration Imp. Description

***** BOTTOM OF DATA *****

Command ==> _____

```

Figure 43. Create a Service Class panel

Use the **Cpu Critical** field to specify CPU protection for critical regions and use the **I/O Priority Group** field to specify HIGH for I/O-sensitive work. Use the **Honor Priority** field to specify whether work in this service class is allowed to overflow to general purpose processors when there is insufficient specialty engine capacity for the workload demand in this service class.

Important: The use of these options limits WLM's ability to manage the system. This may affect system performance and/or reduce the system's overall throughput.

Defining goals

To enter the goal information, enter an **i** in the Action field, as shown in [Figure 43 on page 179](#). The goal selection pop-up is displayed, as shown in [Figure 44 on page 179](#). From this panel, select the type of goal you want to assign to the service class.

```

Choose a goal type for period 1

1_ 1. Average response time
    2. Response time with percentile
    3. Execution velocity
    4. Discretionary

```

Figure 44. Choose a Goal Type pop-up

When you choose option **1**, average response time, the application displays the average response time goal pop-up. There is a different pop-up for each goal type where you can fill in the information for the goal. If you are defining a single period goal, then you should not fill in a duration. If you are defining multiple periods then you must fill in a duration. [Figure 45 on page 180](#) shows an average response time goal pop-up.

```

                Average response time goal

Enter a response time of up to 24 hours for period 1

Hours . . . . . -- (0-24)
Minutes . . . . -- (0-99)
Seconds . . . . _5_ (0-9999)

Importance . . 2 (1=highest, 5=lowest)
Duration . . . ----- (1-999,999,999, or
                        none for last period)

```

Figure 45. Average Response Time Goal pop-up

When you press **Exit**, you return to the create a service class panel with the goal information filled in, as shown in [Figure 46 on page 180](#).

```

Service-Class  Notes  Options  Help
-----
                        Create a Service Class                        ROW 1 TO 2 OF 2

Service Class Name . . . . . QUACK      (Required)
Description . . . . . -----
Workload Name . . . . . APPC          (name or ?)
Base Resource Group . . . . . ----- (name or ?)
Cpu Critical . . . . . NO             (YES or NO)
I/O Priority Group . . . . . NORMAL    (NORMAL or HIGH)
Honor Priority . . . . . DEFAULT      (DEFAULT or NO)

Specify BASE GOAL information.  Action Codes: I=Insert new period,
E=Edit period, D=Delete period.

    ---Period---  -----Goal-----
Action # Duration  Imp.  Description
    --    1          2  Average response time of 00:00:05.000
***** BOTTOM OF DATA *****

```

Figure 46. Create a Service Class panel

Using action codes on service class panels

You use action codes on this panel to define and edit goals. [Figure 47 on page 180](#) shows the edit codes available for service class.

```

Specify BASE GOAL information.  Action Codes: I=Insert new period,
E=Edit period, D=Delete period.

    ---Period---  -----Goal-----
Action # Duration  Imp.  Description
    --    1          5  80% complete within 00:30:00.000
***** END OF DATA *****

```

Figure 47. Action Codes for Goal

I=Insert new period

Use I to define a new period. The application adds a line below. If you have multiple periods, then a duration is required on the previous period. Use action code E to edit the previous period. You'll go through the windows with the goals information filled in, and you can add a duration.

E=Edit period

Use E to edit a period.

D=Delete period

Use D to delete a period. If you have defined multiple periods for a service class, remember that you do not define a duration for the last period.

Defining service policy overrides

You define all service policy overrides from the service policy selection list. You can define the following kinds of service policy overrides:

- Override service class goals
- Override resource group assignment
- Override resource group attributes.
- Override tenant resource group attributes.

To override a service class goal, choose either the action code or the menu bar option to Override Service Classes. Figure 48 on page 181 shows a service policy selection list where you have chosen to override the service classes for the weekend policy.

Service-Policy View Notes Options Help				
Service Policy Selection List				ROW 1 TO 3 OF 3
Action Codes: 1=Create, 2=Copy, 3=Modify, 4=Browse, 5=Print, 6=Delete, 7=Override Service Classes, 8=Override Resource Groups, 9= Override Tenant Resource Groups, /=Menu Bar				
Action	Name	Description	---Last Change---	
--	HOLIDAY	Policy for shut-Down holidays	KIRSTEN	1996/12/04
--	WEEKDAY	Policy for Mon - Friday	KIRSTEN	1996/12/04
<u>7</u>	WEEKEND	Policy for Fri - Sun	KIRSTEN	1996/12/04
***** BOTTOM OF DATA *****				
Command ==> _____				

Figure 48. Service Policy Selection List panel

The application displays the Override Service Class Selection List panel. This is the list of all of your defined service classes, similar to the Service Class Selection list, except it has an extra field called **Overridden Goal** which indicates whether or not the service class goal or resource group assignment was overridden for that policy. Figure 49 on page 182 shows an Override Service Class Selection List. Select a service class whose goal or resource group assignment you want to change and specify the action code or menu bar option to override the service class.

```

  Override View Notes Options Help
-----
IWMAP4A          Override Service Class Selection List      ROW 1 TO 8 OF 14

Service Policy Name . . . . : BACKUPS

Action Codes: 3=Override Service Class, 4=Browse, 5=Print,
              6=Restore Base attributes, /=Menu Bar

Action  Service Class  Overridden  Description
---    -
--     BATCHJ         NO           Class J work
--     BATCHTST        NO           Test
--     BATCHX          NO           Class X work
--     CICSFAST         NO           Fast CICS work
--     CICSLOW          NO           Slow CICS work
3     HOTBATCH         NO           Hot batch
--     IMSNRESP        NO           IMS non response
--     IMSRESP         NO           IMS response

Command ==> _____

```

Figure 49. Override Service Class Selection List panel

When you choose the override service class option, the application displays the Override Attributes for a Service Class panel. Figure 50 on page 182 shows an Override Attributes for a Service Class panel. To override the goal, use the same codes to edit the goal as you do on the Create or Modify a Service Class panel. You can also change the **Cpu Critical**, **I/O Priority Group**, and **Honor Priority** settings, just as you do on the Create or Modify a Service Class panel. To change the resource group assignment of the service class, either enter in a resource group name, or put a ? in the resource group field to select a resource group from the selection list.

If you want to remove a service from a resource group, blank out the name.

```

  Service-Class Xref Notes Options Help
-----
              Override attributes for a Service Class      ROW 1 TO 2 OF 2

Service Policy Name . . . . : STANDARD
Service Class Name . . . . : BAT_0

Override the following information:
Resource Group . . . . . (name or ?)
Cpu Critical . . . . . NO (YES or NO)
I/O Priority Group . . . . . NORMAL (NORMAL or HIGH)
Honor Priority . . . . . DEFAULT (DEFAULT or NO)

Action Codes: I=Insert new period, E=Edit period, D=Delete period.

---Period--- -----Goal-----
Action # Duration Imp. Description
--      1          2 Execution velocity of 70
***** BOTTOM OF DATA *****

Command ==> _____

```

Figure 50. Override Attributes for a Service Class panel

Once you have edited your goal or changed the resource group assignment, press **Exit**, and you return to the Override Service Class Selection List. The **Overridden Goal** field for that service class now says YES.

Overriding resource group or tenant resource group attributes works the same way.

Working with tenant resource groups

To define a tenant resource group, chose option **12** on the Definition Menu. Define a name, and optionally a description, a tenant ID and name, and a 64-character Solution ID. If you want to specify a capacity limit, define the type (1, 2, 3, or 4) and capacity maximum. If you want to include the consumption of

specialty processors in the capacity maximum, specify YES in the corresponding field. For a memory limit, specify the maximum amount in GB.

```

Tenant-Resource-Group  Notes  Options  Help
-----
                                Create a Tenant Resource Group
Command ===> -----
Enter or change the following information:

Tenant Resource Group Name  _____ (required)
Description . . . . . _____
Tenant ID . . . . . _____
Tenant Name . . . . . _____
Solution ID . . . . . _____
-----
Define Capacity: __  1. In Service Units (Sysplex Scope)
                    2. As Percentage of the LPAR share (System Scope)
                    3. As a Number of CPs times 100 (System Scope)
                    4. In accounted workload MSU (Sysplex Scope)
Maximum Capacity . . . . . _____
Include Specialty Processor Consumption NO _____ (YES or NO)
Memory Limit (System Scope) . . . . . _____

```

Figure 51. Create a Tenant Resource Group panel

Once you have created a tenant resource group, any other time you choose the tenant resource group option from the definition menu, the application displays a selection list. From here, you can modify your tenant resource group, as well as print, and browse it.

Working with classification rules

Classification of work depends on having the rules that are defined for the correct subsystem type. When you choose the **Classification Rules** option from the Definition menu, you go to the Subsystem Type Selection List for Rules panel. This panel initially contains the reserved names of the IBM-supplied subsystem types.

Although you might want to change the description of the subsystem types, do not delete any of the entries that are provided by IBM unless your installation does not plan to ever use them. If your installation later does need to use them, they can be manually added then.

[Figure 52 on page 184](#) shows the subsystem type selection panel:

```

Subsystem-Type  View  Notes  Options  Help
-----
Subsystem Type Selection List for Rules          ROW 1 TO 15 OF 15

Action Codes: 1=Create, 2=Copy, 3=Modify, 4=Browse, 5=Print, 6=Delete,
              /=Menu Bar

Action  Type      Description                      -----Class-----
      ASCH      Use Modify to enter YOUR rules      Service  Report
      CB        Use Modify to enter YOUR rules
      CICS      CICS interactive
      DB2       Use Modify to enter YOUR rules
      DDF       Use Modify to enter YOUR rules
      EWLM      Use Modify to enter YOUR rules
      _3 IMS     Use Modify to enter YOUR rules
      IWEB      Use Modify to enter YOUR rules
      JES       batch
      LSFM      Use Modify to enter YOUR rules
      MQ        Use Modify to enter YOUR rules
      OMVS      Use Modify to enter YOUR rules
      SOM       Use Modify to enter YOUR rules
      STC       Use Modify to enter YOUR rules
      TSO       TSO
***** End of data *****

Command ==> _____

```

Figure 52. Subsystem Type Selection List for Rules panel

To create your rules, use the **Modify** option (3) to create rules for the IBM-supplied subsystem types. For example, use the modify option on subsystem type IMS as show in Figure 52 on page 184 to create the rules for your IMS work. Figure 53 on page 184 shows the Modify Rules for the Subsystem Type panel.

```

Subsystem-Type  Xref  Notes  Options  Help
-----
Modify Rules for the Subsystem Type          Row 1 to 2 of
Command ==> _____ SCROLL ==> PAG

Subsystem Type . : CICS          Fold qualifier names?  Y  (Y or N)
Description . . : IBM-defined subsystem type

Action codes:  A=After      C=Copy      M=Move      I=Insert rule
               B=Before     D=Delete row R=Repeat   IS=Insert Sub-rule
                                           More==>

Action  -----Qualifier-----
      Type      Name      Start      Service      Report
      -----
      1 SI      IMSTRN*    ---      PRDIMSR      -----
      2 TC      15          ---      TRNIMSR      -----
      1 SI      IMSMDL*    ---      MDLIMSR      -----
      2 TC      15          ---      MDLIMSNR      -----
      1 TC      15          ---      PRDIMSNR      -----

      DEFAULTS:

Command ==> _____

```

Figure 53. Modify Rules for the Subsystem Type panel

The **Fold qualifier names** option, set to the default Y, means that the qualifier names are folded to uppercase as soon as you type them in and then press Enter. If you set this option to N, then the qualifier names remain in the case they are typed in. Leave this option set to Y unless you know that you need mixed case qualifier names in your classification rules.

While you are creating rules, you can scroll right (PF11) to complete the description fields. Figure 54 on page 185 shows the *Modify Rules for the Subsystem Type* panel, scrolled right to the description fields.

```

Subsystem-Type  Xref  Notes  Options  Help
-----
Command ==>  Modify Rules for the Subsystem Type  Row 1 to 2 of
SCROLL ==> PAG

Subsystem Type . : CICS          Fold qualifier names?  Y  (Y or N)
Description . . . IBM-defined subsystem type

Action codes:  A=After    C=Copy    M=Move    I=Insert rule
                B=Before   D=Delete row R=Repeat  IS=Insert Sub-rule
                <=== More ===>

-----Qualifier-----
Action  Type  Name  Start  Description
-----
---- 1 SI IMSTRN* --- (Descriptions here...
---- 2 TC 15 --- Any valid characters,
---- 1 SI IMSDL* --- up to 32 in length.)
---- 2 TC 15 ---
---- 1 TC 15 ---
-----
Command ==>

```

Figure 54. Modify Rules for the Subsystem Type panel, scrolled right to description fields

After completing a description, you can scroll right (PF11) yet again to complete the **Storage Critical** and **Reporting Attribute** fields. For JES and STC work only, you can also complete the **Manage Regions Using Goals Of** field, with one of these values:

- TRANSACTION. The region is managed to the transaction response time goals.
- REGION. The region is managed to the goal of the service class that is assigned to the region.
- BOTH. The region is managed to the goal of the service class that is assigned to the region, but nevertheless tracks all transaction completions so that WLM can still manage the transaction service classes according to their response time goals.

For all subsystem types except JES and STC work, the **Manage Regions Using Goals Of** field contains N/A. See [Chapter 14, “Defining special protection options for critical work,” on page 99](#) for more information on using these fields.

Important: The use of the Storage Critical and Manage Region Using Goals Of options limits WLM's ability to manage the system. This may affect system performance and reduce the system's overall throughput.

The Reporting Attribute option lets you specify which transactions are mobile transactions that are eligible for mobile workload pricing. WLM gathers and accumulates CPU service separately for each value of the Reporting Attribute, and reports it at the service and report class level, and at the system level. See [“Defining special reporting options for workload reporting” on page 75](#) for more information on using this field.

[Figure 55 on page 186](#) shows the Modify Rules for the Subsystem Type panel, scrolled right to the **Storage Critical**, **Reporting Attribute**, and **Manage Regions Using Goals Of** fields.

Subsystem-Type	Xref	Notes	Options	Help	

Modify Rules for the Subsystem Type				Row 1 to 2 of	
Command ==>				SCROLL ==> PAG	

Subsystem Type . : STC		Fold qualifier names? Y (Y or N)			
Description . . . IBM-defined subsystem type					
Action codes: A=After C=Copy M=Move I=Insert rule					
B=Before D=Delete row R=Repeat IS=Insert Sub-rule					
<=== More					

Action	-----Qualifier-----		Storage	Reporting	Manage Region
	Type Name Start		Critical	Attribute	Using Goals Of
----	1 TN COMBL*	----	NO	NONE	TRANSACTION
----	2 UI COMBLD	----	NO	NONE	TRANSACTION
----	2 UI COMFTP	----	YES	MOBILE	TRANSACTION
----	1 UI SRVLIB	----	YES	NONE	TRANSACTION
----	1 PF 99	----	YES	NONE	REGION
----	1 TC B	----	NO	NONE	BOTH
----	1 TC C	----	NO	NONE	REGION

Figure 55. Modify Rules for the Subsystem Type panel, scrolled right to Storage Critical, Reporting Attribute, and Manage Regions Using Goals Of fields

After completing the **Storage Critical**, **Reporting Attribute**, and **Manage Regions Using Goals Of** fields, you can scroll right (PF11) yet again to fill in the **Boost** field. For STC work only, you can fill in one of the following values:

NO

The region does not initiate a recovery process boost when started or restarted. This is the default.

YES

The region initiates a recovery process boost when started or restarted.

See “[Defining recovery process boost for middleware recycle](#)” on page 77 for more information about using this field. For all other subsystem types except STC, the **Boost** field contains N/A.

Figure 56 on page 186 shows the Modify Rules for the Subsystem Type panel, scrolled right to the **Boost** field.

Subsystem-Type		Xref	Notes	Options	Help

Modify Rules for the Subsystem Type					Row 1 to 5 of
Command ==>					SCROLL ==> CSR

Subsystem Type		. : STC	Fold qualifier names? Y (Y or N)		
Description		. . . IBM-defined subsystem type			
Action codes:		A=After	C=Copy	M=Move	I=Insert rule
		B=Before	D=Delete row	R=Repeat	IS=Insert Sub-rule
		<=== More			
		-----Qualifier-----			
Action	Type	Name	Start	Boost	
----	1 TN	TV1*	---	YES	
----	1 TN	TV2*	---	NO	
----	1 TN	TOR	---	YES	
----	1 TN	AOR1	---	NO	
----	1 TN	AOR2	---	NO	

Figure 56. Modify Rules for the Subsystem Type panel, scrolled right to Boost field

Keep your classification rules as simple as possible. Use subsystem defaults to cover most cases, and list the exceptions. Remember the rules are order sensitive, and the first matched rule applies.

If you have a non-IBM subsystem type, you can use Create to create your subsystem type. You can also modify the qualifier selection list to include only the qualifier types that apply to your subsystem type.

For more information about defining the order of rules, and how to use the **Start** field, see [Chapter 10, “Defining classification rules,”](#) on page 57.

Using action codes on the Modify Rules panel

You use action codes on this panel to create and change your classification rules.

Subsystem-Type Xref Notes Options Help

Command ==> Modify Rules for the Subsystem Type Row 1 to 2 of 2

SCROLL ==> PAGE

Subsystem Type . : CICS Fold qualifier names? Y (Y or N)

Description . . . IBM-defined subsystem type

Action codes: A=After C=Copy M=Move I=Insert rule

B=Before D=Delete row R=Repeat IS=Insert Sub-rule

Figure 57. Action codes for classification rules

In the **Qualifier Type** field, enter the type of qualifier that you are defining. A qualifier type can be one of the following:

- AI**
Accounting information
- AIG**
Accounting information group
- CAI**
Client accounting information
- CAIG**
Client accounting information group
- CI**
Correlation information
- CIG**
Correlation information group
- CIP**
Client IP address
- CIPG**
Client IP address group
- CN**
Collection name
- CNG**
Collection name group
- CT**
Connection type
- CTG**
Connection type group
- CTN**
Client transaction name
- CTNG**
Client transaction name group
- CUI**
Client userid
- CUIG**
Client userid group
- CWN**
Client workstation name

CWNG

Client workstation name group

ESC

zEnterprise service class name from a Unified Resource Manager performance policy

LU

LU name

LUG

LU name group

NET

Net ID

NETG

Net ID group

PC

Process name

PCG

Process name group

PF

Perform

PFG

Perform group

PK

Package name

PKG

Package name group

PN

Plan name

PNG

Plan name group

PR

Procedure name

PRG

Procedure name group

PRI

Priority

PX

Sysplex name

PXG

Sysplex name group

SE

Scheduling environment name

SEG

Scheduling environment name group

SI

Subsystem instance

SIG

Subsystem instance group

SPM

Subsystem parameter

SPMG

Subsystem parameter group

SSC

Subsystem collection name

SSCG

Subsystem collection name group

SY

System name

SYG

System name group

TC

Transaction class

TCG

Transaction class group

TN

Transaction name

TNG

Transaction name group

UI

Userid

UIG

Userid group

You can either enter the qualifier type, or select it from a selection list. To select it from a list, enter a **?** in the **Qualifier Type** field. [“Using selection lists for classification rules” on page 190](#) explains more about using selection lists.

Then type in the name of the qualifier in the **Name** field, and the service class in the **Service Class** field.

You can use the action codes on this panel to enter in additional classification rules. The action codes are:

I=Insert rule

To create a rule at the same level as the rule you type the action code next to.

IS=Insert Sub-rule

To create a next level rule or a nest. IS=Insert Sub-rule specifies a rule under the previous rule; that is, a rule at the next indented level.

R=Repeat

To copy a rule and its sub-rules, if any. The copied rule is placed directly below the one you are copying. If a rule has sub-rules; that is, it is a family, the entire family is copied.

D=Delete row

To delete a rule.

A=After

Use with C=Copy and M=Move to specify that the copied/moved rule is to go after this rule.

B=Before

Use with C=Copy and M=Move to specify that the copied/moved rule is to go before this rule.

C=Copy

To copy a rule and its sub-rules, if any. Use B=Before or A=After with C=Copy to specify where to copy the rule. The rule is copied at the same level as the rule you are placing it Before or After. For example, a level 3 rule becomes a level 2 rule if you copy it before or after a level 2 rule.

When a rule changes levels as a result of a Copy, the levels of any sub-rules that were copied with it are bumped up or down accordingly. The rule family is copied at the same level as the Before or After rule.

M=Move

To move a rule and its sub-rules, if any. Use B=Before or A=After with M=Move to specify where to move the rule. The rule is moved according to the way you do a copy, by placing it Before or After.

Using selection lists for classification rules

For a list of applicable qualifiers for the subsystem type, enter ? in the qualifier type field. You can select a qualifier from the list by entering / next to the one you want to use.

For a list of the defined service classes enter ? in the service class field. You can select a service class from the list by entering / next to the one you want to use.

For a list of the defined report classes and tenant report classes, enter ? in the report class field.

Creating a subsystem type for rules

Use the **Create** option only if your installation has its own subsystem type, or a vendor subsystem type that supports workload management. You must check that product's documentation for its reserved subsystem type name.

Deleting a subsystem type for rules

Use the **Delete** option on the Subsystem Type Selection List for Rules panel only to remove an IBM-supplied subsystem type that your installation does not have, or does not plan on using. The application displays a pop-up for confirmation of the delete.

Working with classification groups

If you have a long list of work that you want to use in a classification rule, you can create a group. You can create groups for all qualifier types except for Priority and zEnterprise Service Class.

For example, you may want to create a transaction name group to use in classification rules for your started tasks. Figure 58 on page 190 shows a Create a Group panel. You can use wildcard and masking notation in qualifier groups. For work qualifiers that run longer than 8 characters, you can use a start position to indicate how far to index into the string. Note that there is also room next to each classification group for a description.

GroupXrefNotesOptionsHelp

Create a GroupROW 1 TO 10 OF 17

Enter or change the following information:

Qualifier type : Transaction Name

Group name : STC_GR1

Description : Low Priority STC

Fold qualifier names? Y (Y or N)

Qualifier Name

Start

Description

UCC7

WSF2*

PHOENIX

NVDM

BMC*

DBUS*

DFHSM*

EMAIL

NETEX

(Descriptions here...)

Any valid characters,

up to 32 in length.)

Figure 58. Create a Group panel

Then, you go to modify the STC subsystem on the Subsystem Type Selection List for Rules panel, and reference the group in the rules. Choose transaction name group for the qualifier type, and enter the name of the group. You can also enter ? in the qualifier name field for a list of the defined groups.

Figure 59 on page 191 shows a Modify Rules for STC Subsystem panel. On this panel, you specify TNG in the qualifier type field. Then you can enter the transaction group name STC_GR1 in the **Qualifier Name** field.

```

Subsystem-Type  Xref  Notes  Options  Help
-----
                          Modify Rules for the Subsystem Type                      Row 1 to 7 of 8

Subsystem Type . . . . . : STC
Description . . . . . : IBM-defined subsystem type
Fold qualifier names? . . . . Y (Y or N)

Enter one or more action codes: A=After B=Before C=Copy D=Delete
M=Move I=Insert rule IS=Insert Sub-rule R=Repeat

Action      -----Qualifier-----
Type      Name      Start      DEFAULTS: Service      Report
-----
   ____  1  TNG      STC_GR1  ____      STC_5
                                         STC_1

```

Figure 59. Modify Rules for STC Subsystem

Working with report classes

To define a report class, chose option **7** on the Definition Menu. Define the name of the report class, and optionally a description.

```

Report-Class  Notes  Options  Help
-----
                          Create a Report Class

Command ==> _____

Enter or change the following information:

Report Class name . . . . . _____ (Required)
Description . . . . . _____

```

Figure 60. Create a Report Class confirmation panel

Once you have created a report class, any other time you choose the report class option from the definition menu, the application displays a selection list. From here, you can modify your report class, as well as print, and browse it.

You can also type **?** in the report class field on the Modify Rules for a Subsystem Type panel for a selection list of report classes.

Working with tenant report classes

To define a tenant report class, chose option **13** on the Definition Menu. Define the name of the tenant report class, and optionally a description. You must assign a tenant resource group to the tenant report class. You can type **?** in the tenant resource group name field for a list of tenant resource groups.

You can use tenant report classes in classification rules to categorize work.

```

Tenant-Report-Class  Notes  Options  Help
-----
                          Create a Tenant Report Class

Command ==> _____

Enter or change the following information:

Tenant Report Class Name . . . _____ (Required)
Description . . . . . _____

Tenant Resource Group Name . . _____ (Required; name or ?)

```

Figure 61. Create a Tenant Report Class

Once you have created a tenant report class, any other time you choose the tenant report class option from the definition menu, the application displays a selection list. From here, you can modify your tenant report class, as well as print, and browse it.

You can also type ? in the report class field on the Modify Rules for a Subsystem Type panel for a selection list of tenant report classes.

Working with service definition options

On the Service Definition Options panel, you can specify whether you want workload management to manage your I/O priorities, enable I/O priority groups, manage your parallel access volume alias addresses, and deactivate discretionary goal management.

If you want workload management to manage I/O priorities for you, specify YES for **I/O priority management**. When you specify YES, workload management manages your I/O priorities and includes I/O usings and delays in its execution velocity calculation. When you specify NO (which is the default), workload management sets the I/O priority to be the same as the dispatching priority, and I/O usings and delays are not included in the execution velocity calculation.

If you want workload management to work with I/O priority groups, specify YES for **Enable I/O priority groups** to ensure that work managed by a service class assigned to I/O priority group HIGH always has a higher I/O priority than work in group NORMAL. This protection can be valuable for work which is extremely I/O-sensitive. See [“Enabling I/O priority groups” on page 95](#) for more information on this setting.

If you want workload management to manage parallel access volume alias addresses for you, specify YES for **Dynamic alias management**. When you specify YES, workload management dynamically reassigns alias addresses from one base to another to help work meet its goals and to minimize IOS queuing. See [“Specifying dynamic alias management” on page 96](#) for more information on this global setting and its relationship to the **WLMPAV** setting on each individual device. When you specify NO, which is the default, dynamic alias management is globally disabled for the entire sysplex. Systems will still use the aliases assigned to the base devices, but there will be no automatic reassignment of aliases based on goals or queuing.

If you want workload management to deactivate discretionary goal management, specify YES for **Deactivate Discretionary Goal Management**. If you specify NO, which is the default, workload management may cap certain types of work that are overachieving their goals in order to give discretionary work a better chance to run. Especially, work that is not part of a resource group or tenant resource group and has a velocity goal less than 30 or a response time goal of one minute or more will be eligible for this kind of resource donation when overachieving its goals. If you do not want the resources of such work to be diverted to run discretionary work, specify YES. Then, workload management will not cap any other work in order to give discretionary work a better chance to run.

Figure 62 on page 192 shows the Service Definition Options panel.

Options	Notes	Help
Service Definition Options		
Enter or change the service definition options:		
I/O priority management	NO	(Yes or No)
Enable I/O priority groups	NO	(Yes or No)
Dynamic alias tuning management	NO	(Yes or No)
Deactivate Discretionary Goal Management	NO	(Yes or No)
Command ==> _____		

Figure 62. Service Definition Options panel

Working with application environments

Define an application environment so that workload management can assist in managing work that runs in server address spaces. You can specify that workload management should dynamically start and stop server address spaces to process work running in the application environment. You can define application environments for the DB2, SOM, and IWEB IBM-supplied subsystem types. Refer to subsystem reference information for guidance on how to specify application environments for the subsystem.

Figure 63 on page 193 shows the Application Environments panel.

```
Application-Environment  Notes  Options  Help
-----
                                Create an Application Environment
Command ===> -----

Application Environment Name. ----- Required
Description . . . . . -----
Subsystem Type . . . . . ----- Required
Procedure Name . . . . . -----
Start Parameters . . . . . -----

Starting of server address spaces for a subsystem instance:
1  1.  Managed by WLM
    2.  Limited to a single address space per system
    3.  Limited to a single address space per sysplex
```

Figure 63. Create an Application Environments panel

Working with scheduling environments

Use the scheduling environment panels to define scheduling environments and their lists of resource names and required states, and to define the individual resource names themselves.

Creating a new scheduling environment

If you have not yet defined any scheduling environments, Figure 64 on page 193 shows the first panel you will see.

```
IWMAPA7                                Decide what to create?
Command ===> -----

No scheduling environments exist.  Would you like to create a
scheduling environment or list resources for scheduling
environments?

Select one of the following options.
--  1.  Create Scheduling Environment
    2.  Create Resource(s)
```

Figure 64. Decide What to Create panel

From here you can either enter **1** to create a scheduling environment, or a **2** to create resources. (You might want to create all of your resources, for instance, before creating your first scheduling environment. This is covered in “Creating a new resource directly from the main panel” on page 197.)

Note: Until you have created at least one scheduling environment (no matter how many resources you create), you will always see this initial panel.

Figure 65 on page 194 shows the main Scheduling Environment Selection List panel. Assuming that you have at least one scheduling environment already created, this is the first panel you see when you work with scheduling environments.

```

Scheduling-Environments  Notes  Options  Resources  Help
-----
IWMAPAA                  Scheduling Environment Selection List          Row 1 to 2 of 2
Command ==> _____

Action Codes: 1=Create, 2=Copy, 3=Modify, 4=Browse, 5=Print, 6=Delete,
              /=Menu Bar

Action  Scheduling Environment Name      Description
1_      IMSPRIME                         Prime IMS Processing
--      CICS_SPEC                       Special CICS Processing

```

Figure 65. Scheduling Environment Selection List panel

By entering **1** on any Action line, you will go to the Create a Scheduling Environment panel, as shown in [Figure 66 on page 194](#). (You can also get there by putting the cursor under the Scheduling-Environment field at the top of the screen, and then entering **1** in the pop-up box.)

```

Scheduling-Environments  Notes  Options  Help
-----
IWMAPAD                  Create a Scheduling Environment          Row 1 to 1 of 1
Command ==> _____

Scheduling Environment Name      DB2LATE_____ Required
Description . . . . . Offshift DB2 Processing_____

Action Codes: A=Add  D=Delete

Action  Resource Name      Required
a_      _____        State      Resource Description

```

Figure 66. Create a Scheduling Environment panel

Enter the scheduling environment name and description, and then enter **A** on the Action line to go to the next panel, Resource Definition List, as seen in [Figure 67 on page 194](#).

```

Resources  Notes  Options  XREF  Help
-----
IWMAPAS                  Resource Definition List          Row 1 to 4 of 4
Command ==> _____

Selection For Scheduling Environment DB2LATE

Action Codes: A=Add  S=Select  X=XREF  /=Menu Bar

Action  Resource Name      In Use  Resource Description
--      CICS001             YES     CICS Subsystem
S_      DB2A              YES     DB2 Subsystem
S_      IMS1              YES     IMS Subsystem
S_      PRIMETIME         YES     Peak Business Hours

```

Figure 67. Resource Definition List panel

This panel shows *all* of the resource definitions in the service definition. The YES in the **In Use** field simply means that the resource name is currently a part of some scheduling environment. (It does *not* mean that it is in use by the scheduling environment you are defining when you get to this screen, in this case DB2LATE.)

You can select as many resources as you like. In this case, we'll select DB2A and PRIMETIME. Both have already been defined (although only PRIMETIME is currently being used by another scheduling environment). To make the resource name part of the scheduling environment, enter **S** on the Action line next to it. (Alternately, you can enter **/** next to the resource names and then put the cursor under the **Resources** field at the top of the screen and press Enter. Then select **2** from the options in the pop-up box.)

If you have many resources, you can use the **LOCATE** primary command to scroll the display to a particular resource name.

Note: You can create new resources from this panel, as well. See [“Creating a new resource while working with a scheduling environment”](#) on page 199.

This will take you back to the Create a Scheduling Environment panel, as shown in [Figure 68 on page 195](#).

```

Scheduling-Environments  Notes  Options  Help
-----
IWMAPAD                Create a Scheduling Environment          Row 1 to 2 of 2
Command ===> -----

Scheduling Environment Name  DB2LATE_____ Required
Description . . . . . Offshift DB2 Processing_____

Action Codes: A=Add  D=Delete

Action  Resource Name      Required
      DB2A                ON_____   DB2 Subsystem
      PRIMETIME           OFF_____   Peak Business Hours

```

Figure 68. Create a Scheduling Environment panel

The DB2A and PRIMETIME names and descriptions are automatically brought back to this panel. Now you must specify either ON or OFF under the **Required State** field. In this example, we have chosen ON for DB2A and OFF for PRIMETIME (meaning that the DB2A resource state must be set to ON and the PRIMETIME resource state must be set to OFF for this scheduling environment to be satisfied).

Modifying a scheduling environment

Once a scheduling environment is created, you can modify it at any time, either changing the required states of resources, adding new resources to the scheduling environment, or deleting resources from the scheduling environment.

Now that DB2LATE has been created in the previous section, here's how we would modify it. From the main Scheduling Environment Selection List panel, enter a 3 in the Action line next to the scheduling environment you want to change, as shown in [Figure 69 on page 195](#). (Alternately, you can enter a / next to it, put your cursor under the Scheduling-Environments field at the top of the screen, and then select 3 from the pop-up box.)

If you have many scheduling environments, you can use the LOCATE primary command to scroll the display to a particular name.

```

Scheduling-Environments  Notes  Options  Resources  Help
-----
IWMAPAA                Scheduling Environment Selection List          Row 1 to 3 of 3
Command ===> -----

Action Codes: 1=Create, 2=Copy, 3=Modify, 4=Browse, 5=Print, 6=Delete,
              /=Menu Bar

Action  Scheduling Environment Name      Description
  3_    DB2LATE                          Offshift DB2 Processing
  --    IMSPRIME                         Prime IMS Processing
  --    CICS_SPEC                       Special CICS Processing

```

Figure 69. Scheduling Environment Selection List panel

This will take you to the Modify a Scheduling Environment panel. Here, you can add and delete resources, and change required states. In [Figure 70 on page 196](#), we could delete DB2A, and change the required state for PRIMETIME from OFF to ON. (To add new resources from this panel, see [“Creating a new resource while working with a scheduling environment”](#) on page 199.) When you press enter, you'll get a confirmation message, telling you to press EXIT to save your changes, or CANCEL to discard them.

```

Scheduling-Environments  Notes  Options  Help
-----
IWMAPAJ                  Modify a Scheduling Environment          Row 1 to 2 of 2
Command ==> -----

Scheduling Environment Name    DB2LATE_____ Required
Description . . . . . Offshift DB2 Processing_____

Action Codes: A=Add  D=Delete

Action  Resource Name      Required
d_      DB2A                ON_____ DB2 Subsystem
--      PRIMETIME          ON_____ Peak Business Hours

```

Figure 70. Modify a Scheduling Environment panel

Important: When you delete a resource name from this panel, you are simply deleting it *from the scheduling environment*. The resource name will still exist on the Resource Definitions List panel. To delete the resource definition itself, see [“Deleting a resource”](#) on page 201.

Copying a scheduling environment

To copy a scheduling environment, from the main Scheduling Environment Selection List panel (as shown in [Figure 69 on page 195](#)) enter a 2 on the Action line next to the name. This will bring you to the Copy a Scheduling Environment panel, as shown in [Figure 71 on page 196](#).

```

IWMAPAC                  Copy A Scheduling Environment          Row 1 to 2 of 2
Command ==> -----

Scheduling Environment Name    NEWSCHENV_____ Required
Description . . . . . _____

Action Codes: A=Add  D=Delete

Action  Resource Name      Required
--      DB2A                ON_____ DB2 Subsystem
--      PRIMETIME          OFF_____ Peak Business Hours

```

Figure 71. Copy a Scheduling Environment panel

You must give the new scheduling environment a new, unique name. From this screen, you can modify the new scheduling environment, as shown in [“Modifying a scheduling environment”](#) on page 195.

The copy function is useful when you are working with scheduling environments with large numbers of resource names. If you wish to create a new scheduling environment that is similar to an existing one, you can simply copy the original and then make whatever changes are necessary.

Browsing a scheduling environment

To browse a scheduling environment, from the main Scheduling Environment Selection List panel (as shown in [Figure 69 on page 195](#)) enter a 4 on the Action line next to the name. You'll see a browse screen as shown in [Figure 72 on page 197](#).

```

IWMAPUB                               Line 00000000 Col 001 072
Command ==>                           SCROLL ==> PAGE
***** Top of Data *****

Scheduling Environment Name. . DB2LATE
Description. . . . . Offshift DB2 Processing

Resource Name      State  Resource Description
-----
DB2A               ON    DB2 Subsystem
PRIMETIME          OFF    Peak Business Hours
***** End of Data *****

```

Figure 72. Browse a Scheduling Environment panel

Printing a scheduling environment

To print a scheduling environment, from the main Scheduling Environment Selection List panel (as shown in [Figure 69 on page 195](#)) enter a 5 on the Action line next to the name. The output will be written to your ISPF list data set.

Deleting a scheduling environment

To delete a scheduling environment, from the main Scheduling Environment Selection List panel (as shown in [Figure 69 on page 195](#)) enter a 6 on the Action line next to the name. This will bring you to a confirmation screen, as shown in [Figure 73 on page 197](#).

```

-----
IWMAPAX                               Delete A Scheduling Environment
Command ==> -----

Scheduling Environment Name : DB2LATE
Description . . . . . : Offshift DB2 Processing
-----

Confirm the deletion request for the above scheduling environment.

Response . . . . . yes (Yes or No)

```

Figure 73. Delete a Scheduling Environment panel

Note that all of the resource definitions that were part of this scheduling environment *still exist*. However, they are no longer members of this particular scheduling environment anymore.

Creating a new resource

In the example shown in [Figure 67 on page 194](#), as we were creating a new scheduling environment (DB2LATE), we chose resource names (DB2A and PRIMETIME) that already existed. What if we had needed to add a new resource name called VECTOR? As you saw on that Resource Definition List panel, VECTOR did not yet exist.

There are two ways to add a new resource definition:

- Directly from the main panel
- While working with a scheduling environment

Creating a new resource directly from the main panel

From the main Scheduling Environment Selection List panel, put the cursor under the Resources field at the top of the screen and press Enter. When the pop-up box appears, enter a 1, as shown in [Figure 74 on page 198](#). (In this pop-up, 1 is the only option.)

```

Scheduling-Environments  Notes  Options  Resources  Help
-----
Scheduling Environment * 1 1. Process Resources * to 3 of 3
Command ===> -----
Action Codes: 1=Create, 2=Copy, 3=Modify, 4=Browse, 5=Print, 6=Delete,
              /=Menu Bar

Action  Scheduling Environment Name  Description
--      CICS_SPEC                   Special CICS Processing
--      DB2LATE                     Offshift DB2 Processing
--      IMSPRIME                     Prime IMS Processing

```

Figure 74. Scheduling Environment Selection List panel

This will take you directly to the Resource Definition List panel, where you can add new resources. Enter an A on any Action line, as shown in Figure 75 on page 198. (Alternately, you can put a / next to the resource names and then put the cursor under the Resources field at the top of the screen and hit ENTER. Then select 1 from the options in the pop-up box.)

```

Resources  Notes  Options  XREF  Help
-----
IWMAPAR          Resource Definition List          Row 1 to 4 of 4
Command ===> -----
Action Codes: A=Add  D=Delete  X=XREF  /=Menu Bar

Action  Resource Name      In Use  Resource Description
--      CICS001             YES     CICS Subsystem
--      DB2A              YES     DB2 Subsystem
--      IMS1              YES     IMS Subsystem
a_      PRIMETIME         YES     Peak Business Hours

```

Figure 75. Resource Definition List panel

This would take you to the Define Resource panel, where you would enter the information for the new resource name, as shown in Figure 76 on page 198.

```

IWMAPAE          Define Resource
Command ===> -----
Resource name . . . . . VECTOR_____ Required
Resource Description . . . . Vector Processor_____

```

Figure 76. Define Resource panel

When we return to the Resource Definition List panel, the new resource name is there, as shown in Figure 77 on page 198.

```

Resources  Notes  Options  XREF  Help
-----
IWMAPAR          Resource Definition List          Row 1 to 5 of 5
Command ===> -----
Action Codes: A=Add  D=Delete  X=XREF  /=Menu Bar

Action  Resource Name      In Use  Resource Description
--      CICS001             YES     CICS Subsystem
--      DB2A              YES     DB2 Subsystem
--      IMS1              YES     IMS Subsystem
--      PRIMETIME         YES     Peak Business Hours
--      VECTOR            YES     Vector Processor

```

Figure 77. Resource Definition List panel

Note that the panel automatically alphabetizes the resource names. Note also that VECTOR is not yet shown as In Use. We would need to go create or modify a scheduling environment and then select VECTOR.

Creating a new resource while working with a scheduling environment

While you are in the middle of creating or modifying a scheduling environment, you can take this shortcut method to create new resources. In this case where you wanted to create the new VECTOR resource and add it to DB2LATE, this method would be the logical choice.

From either the Create a Scheduling Environment panel or the Modify a Scheduling Environment panel (they look very similar), enter an A on any Action line, as shown in [Figure 78 on page 199](#).

```

Scheduling-Environments  Notes  Options  Help
-----
IWMAPAJ                Modify a Scheduling Environment          Row 1 to 2 of 2
Command ===> -----

Scheduling Environment Name  DB2LATE_____ Required
Description . . . . . Offshift DB2 Processing_____

Action Codes: A=Add  D=Delete

Action  Resource Name      Required
--      DB2A              ON_____ DB2 Subsystem
a_      PRIMETIME        OFF_____ Peak Business Hours

```

Figure 78. Modify a Scheduling Environment panel

This would take you to the Resource Definition List panel, where you can enter an A on any Action line, as shown in [Figure 79 on page 199](#). (Alternately, you can enter a / next to the resource names and then put the cursor under the **Resources** field at the top of the screen and press Enter. Then select **1** from the options in the pop-up box.)

```

Resources  Notes  Options  XREF  Help
-----
IWMAPAS                Resource Definition List          Row 1 to 4 of 4
Command ===> -----

Selection For Scheduling Environment DB2LATE

Action Codes: A=Add  S=Select  X=XREF  /=Menu Bar

Action  Resource Name      In Use  Resource Description
--      CICS001            YES     CICS Subsystem
--      DB2A              YES     DB2 Subsystem
--      IMS1            YES     IMS Subsystem
a_      PRIMETIME        YES     Peak Business Hours

```

Figure 79. Resource Definition List panel

As in the method described in [“Creating a new resource directly from the main panel” on page 197](#), from here you'll go to the Define Resource panel (as was shown in [Figure 76 on page 198](#)) to enter the new resource name and description.

When you come back to the Resource Definition List panel, you can now select the new VECTOR resource to be part of the DB2LATE scheduling environment, as shown in [Figure 80 on page 200](#).

```

Resources  Notes  Options  XREF  Help
-----
IWMAPAS           Resource Definition List           Row 1 to 5 of 5
Command ==> -----

Selection For Scheduling Environment DB2LATE

Action Codes: A=Add  S=Select  X=XREF  /=Menu Bar

Action  Resource Name      In Use  Resource Description
--      -
--      CICS001             YES     CICS Subsystem
--      DB2A              YES     DB2 Subsystem
--      IMS1              YES     IMS Subsystem
--      PRIMETIME         YES     Peak Business Hours
s_      VECTOR           Vector Processor

```

Figure 80. Resource Definition List panel

Having done that and exiting, you come back to the Modify a Scheduling Environment panel, as shown in Figure 81 on page 200.

```

Scheduling-Environments  Notes  Options  Help
-----
IWMAPAJ           Modify a Scheduling Environment           Row 1 to 3 of 3
Command ==> -----

Scheduling Environment Name      DB2LATE_____ Required
Description . . . . . Offshift DB2 Processing_____

Action Codes: A=Add  D=Delete

Action  Resource Name      Required
--      -
--      DB2A              ON_____ DB2 Subsystem
--      PRIMETIME         OFF_____ Peak Business Hours
--      VECTOR           ON_____ Vector Processor

```

Figure 81. Modify a Scheduling Environment Panel

Now the VECTOR resource name is part of the DB2LATE scheduling environment. As always, you need to specify either ON or OFF under the **Required State**. In this case, we chose ON.

Summary of the two methods for creating new resources

You can create new resources in two ways:

- Directly from the main panel (“[Creating a new resource directly from the main panel](#)” on page 197). This method is useful when you want to create resources without actively working on one particular scheduling environment. Also, note that when you go to the Resource Definition List panel with this method, the Action Codes look like this:

```
Action Codes: A=Add  D=Delete  X=XREF  /=Menu Bar
```

There is no S=Select, because you are not actively working on any scheduling environment (and therefore there is no place for you to select resources to).

There is a D=Delete action code. This will be important when you are deleting resources, as in “[Deleting a resource](#)” on page 201.

- While creating or modifying scheduling environments (“[Creating a new resource while working with a scheduling environment](#)” on page 199). This method is useful when you want to create resources while in the midst of creating or modifying a scheduling environment. Note that when you go to the Resource Definition List panel with this method, the Action Codes (and the line above it) look like this:

```

Selection For Scheduling Environment DB2LATE

Action Codes: A=Add  S=Select  X=XREF  /=Menu Bar

```

The name of scheduling environment that you are currently working with appears on this panel, and there is a S=Select among the action codes. You can select the new resource to be a part of the scheduling environment immediately after creating it.

There is no D=Delete action code, because you *cannot* delete resources when you come the Resource Definition List panel this way. See [“Deleting a resource” on page 201](#).

Showing all cross-references for a resource definition

You can check which specific scheduling environments use a given resource definition by entering an X in the action column next to the resource name, as shown in [Figure 82 on page 201](#). (You can use either path to get to the Resource Definition List path, as discussed in [“Summary of the two methods for creating new resources” on page 200](#).)

```

Resources  Notes  Options  XREF  Help
-----
IWMAPAS          Resource Definition List          Row 1 to 4 of 4
Command ==>> -----

Selection For Scheduling Environment DB2LATE

Action Codes: A=Add  S=Select  X=XREF  /=Menu Bar

Action  Resource Name      In Use  Resource Description
--      -
X_      PRIMETIME             YES     Peak Business Hours
--      VECTOR                YES     Vector Processor

```

Figure 82. Resource Definition List panel

This will take you to the Resource Cross-Reference of Scheduling Environments panel, as shown in [Figure 83 on page 201](#).

```

IWMAPAY      Resource Cross-Reference Of Scheduling Environments Row 1 to 2 of 2
Command ==>> -----

Resource . . . . . : PRIMETIME
Description . . . . . : Peak Business Hours

Scheduling Environment Name  Description
IMSPRIME                    Prime IMS Processing
DB2LATE                     Offshift DB2 Processing

```

Figure 83. Resource Cross-Reference Of Scheduling Environments panel

Deleting a resource

Unlike adding a resource definition, there is only one path you can take to delete a resource definition: from the main Scheduling Environment Selection List panel (as discussed in [“Summary of the two methods for creating new resources” on page 200](#)).

Put the cursor under the Resources field at the top of the screen and hit ENTER. When the pop-up box appears, enter a 1, as was shown in [Figure 74 on page 198](#). (In this pop-up, 1 is the only option.)

This will take you directly to the Resource Definition List panel. Enter a D on the Action line next to the resource definition you wish to delete, as shown in [Figure 84 on page 202](#).

Resources	Notes	Options	XREF	Help
Resource Definition List				Row 1 to 5 of 5
Command ===> -----				
Action Codes: A=Add D=Delete X=XREF /=Menu Bar				
Action	Resource Name	In Use	Resource Description	
--	CICS001	YES	CICS Subsystem	
--	DB2A	YES	DB2 Subsystem	
--	IMS1	YES	IMS Subsystem	
--	PRIMETIME	YES	Peak Business Hours	
D_	VECTOR		Vector Processor	

Figure 84. Resource Definition List panel

Note that you can only delete a resource definition that is not currently in use by any scheduling environment. If you attempted to delete the PRIMETIME resource in [Figure 75 on page 198](#), you would receive an error message stating the resource cannot be deleted because a scheduling environment is using it. You must first check the cross-references for that resource definition (as in [“Showing all cross-references for a resource definition” on page 201](#)) and then go into every scheduling environment that uses it to delete those references.

Coordinating updates to a service definition

Since you can keep your service definition in either the WLM couple data set or in MVS data sets, it is possible to have multiple, uncoordinated updates. You should decide on a process for updating your service definition.

If you decide to work from the WLM couple data set, installing and extracting the service definition when you need to edit it, you should keep a copy in an MVS data set. The WLM application allows only one user to update an MVS data set at a time. If you do try to edit an MVS data set that is in use, you are locked out, and get a message saying the data set is in use.

If you select the Install option, and someone has done an install since you've extracted, the application displays a pop-up panel asking for confirmation. This way you can prevent inadvertent overwrites of the service definition. [Figure 85 on page 202](#) shows the Overwrite warning panel.

```

      Overwrite Service Definition

Another service definition was found on the WLM couple data
set.

Service definition name : WLMDEF

Definition installed by : SPFUSER      from system SP44
Definition installed on : 1996/04/16   at 22:00:46

Do you want to overwrite this?      NO   (Yes or No)

F1=Help      F2=Split      F5=KeysHelp  F9=Swap      F12=Cancel

```

Figure 85. Overwrite Service Definition panel

Using the WLM couple data set

The service definition installed on the WLM couple data set is the *installed* service definition. The policy that you activate must be in the installed service definition.

Of course, before you can install your service definition on the WLM couple data set, you must first allocate one, and define it to the sysplex. You can allocate a WLM couple data set through a function in the WLM application, or you can use a utility. For information on how to allocate using the utility, see [“Allocate a WLM couple data set” on page 138](#).

Allocating a WLM couple data set

For availability purposes, you should allocate both a primary and an alternate WLM couple data set.

You can allocate a new primary and alternate WLM couple data set from the application using the **Allocate couple data set using CDS values** function on the **Utilities** menu bar option of the Definition Menu. [Figure 86 on page 203](#) shows the allocate panel that uses CDS values.

```
Allocate couple data set for WLM using CDS values
Command ==> -----
Sysplex name      SYSPLEX1 (Required)
Data set name     'GAILW.PCOUPLE.P1' (Required)
-----
Size parameters   |
(optional):       |
Service policies  . . 10_ (1-99)
Workloads . . . . 35_ (1-999)
Service classes  . . 30_ (1-100)
Application      |
environments . . . . 50_ (1-3000)
Scheduling       |
environments . . . . 50_ (1-999)
SVDEF extensions . . 0___ (0-8092)
SVDCR extensions . . 0___ (0-8092)
SVAEA extensions . . 0___ (0-8092)
SVSEA extensions . . 0___ (0-8092)
Storage parameters:
Storage class . . . A
Management class . . -----
or
Volume . . . . . -----
Catalog data set? . . (Y or N)
```

Figure 86. Allocate couple data set using CDS values panel

This function primes the size parameters with values from the current couple data set. This way, you can ensure that the new couple data set is at least as large as the current one. If the new one is smaller than the current one, you will not be able to use SETXCF to make this data set available to the sysplex. (You will receive a series of messages starting with IXC255I UNABLE TO USE DATA SET.) You may need to increase one or more of these primed values if you have added new objects to your service definition since the last time you installed it.

If there is no current WLM couple data set, or you do not know by how much to increase the size parameters primed from the current WLM couple data set, use the **Allocate couple data set** function on the **Utilities** menu. This function fills in the size parameters based on the service definition you are about to install. It gets the values from the ISPF PDS containing the service definition, and calculates recommended values for the size parameters which ensure that the service definition you are currently working with fits into the newly allocated WLM couple data set. [Figure 87 on page 204](#) shows the allocate panel that uses service definition values.

Allocate couple data set for WLM		
Sysplex name	SYSPLEX2 (Required)	
Data set name	'KIRSTEN.PCOUPLE.P1'	(Required)

Size parameters (optional):		Storage parameters:
Service policies . . 10_ (1-99)		Storage class . . . A
Workloads 35_ (1-999)		Management class . . -----
Service classes . . 30_ (1-100)		or
Application environments 50_ (1-3000)		Volume ----
Scheduling environments 50_ (1-999)		Catalog data set? . . _ (Y or N)

Figure 87. Allocate couple data set panel using service definition values

If you have defined your service definition, the application fills in recommended values for the number of policies, workloads, service classes, application environments, and scheduling environments which ensure that the service definition you are currently working with fits into the newly allocated WLM couple data set. These values are the best estimate of what this service definition requires when installed on the couple data set. If you define too large a number, it can use up a lot of space.

If you are replacing couple data sets already in use, the new data sets must be at least as large as the existing ones. You need to run a special sizing utility to determine their size. Use this method to ensure that the new couple data set is at least as large as the current one, and can accommodate any new objects you might have added to the service definition:

1. First use the **Allocate couple data set** option as a quick way of displaying the values required for the service definition you have just created or modified. Write down these values and exit the panel without allocating a couple data set.
2. Then use the **Allocate couple dataset using CDS values** function to obtain a panel primed with the current couple data set values.
3. Take the maximum of the values from steps 1 and 2 and enter these values on the panel. To allow for future growth, increase each by 10%. Complete the couple data set allocation from this panel.

Once you have allocated the WLM couple data sets, you need to make them available for use in the sysplex. If you are making couple data sets available for the first time, see [“Make a WLM couple data set available to the sysplex for the first time” on page 140](#). If you are replacing couple data sets already in use, see [“Make a newly formatted couple data set available to the sysplex” on page 141](#).

Installing and extracting a service definition

You can install and extract the service definition using the **Install** and **Extract** functions on the **Utilities** menu bar option of the Definition Menu.

Installing the service definition overwrites any service definition previously installed on the WLM couple data set.

When you extract the service definition, a copy remains on the WLM couple data set until the next install.

Using MVS data sets

If you have multiple people updating the service definition, or if you want to work with more than one service definition, you can work in multiple MVS data sets. For example, if you want to work on the service definition for next year’s SLA, you can keep it in an MVS data set.

If you specify **Read saved definition**, you can choose from a list of data sets already created. The list is made up of all data sets your user IDs has worked with (the list is built based on use).

Restricting access to your service definition

To restrict access to the service definition stored in both the MVS data set and the WLM couple data set, you can use the same resource control facility as you do for an MVS data set. For information about how to restrict access to the WLM application functions, see “Restricting access to the WLM service definition” on page 134.

Activating a service policy

You can activate a service policy from the ISPF application, as well as from the operator console. To activate a policy from the operator console, you issue the **VARY WLM** command. For more information about issuing the **VARY** command, see “Migration activities” on page 134. To activate a policy from the application, choose the **Utilities** option from the menu bar on the Definition menu.

When you choose the activate option, the application extracts the service definition information from the WLM couple data set, and displays the Policy Selection List panel, as shown in Figure 88 on page 205. From the list, you select the service policy that you want to activate.

If you have been editing your service definition and want your changes to take effect, you have to install the changed service definition, and then activate the service policy.




Figure 88. Policy Selection List panel to activate a service policy

Printing in the application

The print function on the selection lists in the WLM application prints the information into an ISPF list data set. You can process the ISPF list data set just as you would any other ISPF list data set. For more information about using list data sets, see *Interactive System Productivity Facility (ISPF) User's Guide*.

The **Print as GML** function under the **File** action bar choice of the Definition menu prints the complete service definition to a data set in GML format. The data set can be formatted using SCRIPT/VS. For more information, see *DCF SCRIPT/VS User's Guide*.

Note: To use SCRIPT/VS, you must have Document Composition Facility (DCF) Version 3, or higher, installed.

Browsing definitions

The **Browse** function is available on selection lists in the application, and is similar to the print function. **Browse** prints information into a temporary data set, and displays it.

Figure 89 on page 206 shows the browse on the BAT_T service class from the service class selection list.

```

Browse                                     Line 00000000 Col 001 072
***** TOP OF DATA *****
* Service Class BAT_T - Batch class T

Created by user BERKEL on 1996/10/07 at 11:29:05
Base last updated by user BERKEL on 1996/10/07 at 11:29:05

Base goal:

#   Duration   Imp   Goal description
-   -
1           5    80% complete within 00:30:00.000

***** END OF DATA *****

Command ==>

```

Figure 89. Browse function from the Service Class Selection List

Using XREF function to view service definition relationships

To view the relationship between any two definitions (service class, workload resource group etc), you can use the XREF function. From any Modify panel in the application, you can use the XREF function to determine an definition's relationship to another.

For example, on the Modify Service Class panel, you may want to know whether a service policy overrides the defined goal. You use the XREF function to check whether its goals are overridden in a service policy. From the Modify Service Class panel, you can also check which subsystem types reference that service class in the classification rules. If there are some that do reference it, the application displays a pop-up selection list where you can browse the Rules referencing that service class. [Figure 90 on page 206](#) shows an example of the pop-up displayed for an Xref by Subsystem for a service class.

```

Service Class Reference ROW 1 TO 1 OF 1

These subsystem types refer to the service class.

Action Codes: 4=Browse

Action  Name  Description
_      STC    IBM-defined subsystem type
***** BOTTOM OF DATA *****

```

Figure 90. Service Class Subsystem Xref panel

WLM application messages

IWMAM040 **Unexpected error, RC=xx,
RSN=xxxxxxxx.**

Explanation

The application has detected an unexpected error.

In the message text:

xx

The return code.

xxxxxxxx

The hexadecimal reason code.

System action

The requested operation is not performed.

Programmer response

Search problem reporting data bases for a fix for the problem. If no fix exists, contact the IBM Support Center. Provide the text of this message.

Module

Workload management (WLM)

IWMAM041 **WLM couple data set is
unavailable.**

Explanation

Workload management (WLM) was unable to find the WLM couple data set. It is possible that it does not exist. Or it may exist, but it has not been defined to the sysplex.

System action

The requested operation is not performed.

Programmer response

Either:

- Make the couple data set available to the sysplex by updating the DATA keyword of the COUPLExx parmlib member or issuing the SETXCF command.
- Allocate the WLM couple data set.

Module

Workload management (WLM)

IWMAM042	Extract failed, no service definition was found on the WLM couple data set.
-----------------	--

Explanation

Workload management (WLM) was unable to find a service definition on the WLM couple data set.

System action

The extract is not performed.

Programmer response

Ensure that the service definition has been properly installed on the WLM couple data set.

Module

Workload management (WLM)

IWMAM043	Unable to obtain storage, RSN=xxxxxxxx.
-----------------	--

Explanation

Workload management (WLM) was unable to obtain enough storage to complete the operation.

In the message text:

xxxxxxxx
The hexadecimal reason code.

System action

The requested operation is not performed.

Programmer response

Increase the region size and repeat the operation. If this does not help, search problem reporting data bases for a fix for the problem. If no fix exists, contact the IBM Support Center. Provide the text of this message.

Module

Workload management (WLM)

IWMAM044	Install failed, service definition is not valid. Validation reason code: xxxx, Validation offset: yyyy
-----------------	---

Explanation

The service definition you are trying to install is not valid.

xxxx is the validation reason code. yyyy is the validation offset (a hex offset into the iwmszzz data structures where the problem exists).

System action

The install is not performed.

Programmer response

For further explanation of this error, see the topic "Application Validation Reason Codes" in *z/OS MVS Programming: Workload Management Services*. Search problem reporting data bases for a fix for the problem. If no fix exists, contact the IBM Support Center. Provide the text of this message.

Module

Workload management (WLM)

IWMAM046	Errors were found during validation of the service definition. The install has failed.
-----------------	---

Explanation

The errors listed on the previous panel (shown when you attempted to install) have prevented the installation of the service definition.

System action

The install is not performed.

Programmer response

Correct the errors and retry. To capture a list of the errors, go back to the error panel by either attempting to install the service definition again or by validating the service definition (use the “Validate definition” utility as described in [“Using the menu bar on the Definition Menu” on page 174](#)). From that panel, you can capture a list of the errors by selecting “Save listing” on the “File” menu bar option.

Module

Workload management (WLM)

IWMAM047	WLM couple data set is too small to hold the service definition.
-----------------	---

Explanation

The service definition being installed is too large to fit into the WLM couple data set.

System action

The requested action is not performed.

Programmer response

Re-allocate the WLM couple data set with a larger size, as described in [“Allocate a WLM couple data set” on page 138](#) and [“Make a WLM couple data set available to the sysplex for the first time” on page 140](#).

Module

Workload management (WLM)

IWMAM050	Exceeded the maximum number of attempts to read the service definition.
-----------------	--

Explanation

A failure in reading the service definition from the WLM couple data set has occurred repeatedly.

System action

The requested operation is not performed.

Programmer response

Search problem reporting data bases for a fix for the problem. If no fix exists, contact the IBM Support Center. Provide the text of this message.

Module

Workload management (WLM)

IWMAM051	Access was denied to the WLM couple data set.
-----------------	--

Explanation

The user does not have appropriate RACF authority to the WLM couple data set.

System action

The requested operation is not performed.

Programmer response

Verify that the user should be authorized and have the RACF administrator give the user appropriate access. For information about how to restrict access to the couple data set, see [“Restricting access to the WLM service definition” on page 134](#).

Module

Workload management (WLM)

IWMAM052	The service definition functionality level (LEVELxxx) is not compatible with the WLM ISPF application level (LEVELyyy). To extract a service definition or to activate a policy, the WLM ISPF application and the MVS system must be at the same level as the service definition.
-----------------	--

Explanation

The service definition in the WLM couple data set uses functions that are not compatible with this level of the WLM ISPF application

System action

The requested operation is not performed.

Programmer response

Use the WLM ISPF application on a system that is compatible with the functionality level of the service definition.

Module

Workload management (WLM)

IWMAM054	Failure in ISPF: ISPF error information.
-----------------	---

Explanation

An error occurred using the application.

System action

The requested operation is not performed.

Programmer response

The ISPF error information may provide a clue as to how to overcome the problem. If not, search problem reporting data bases for a fix for the problem. If no fix exists, contact the IBM Support Center. Provide the text of this message.

Module

Workload management (WLM)

IWMAM055	Extract failed, service definition is not valid. Validation reason code: xxxx, Validation offset: yyyy
-----------------	---

Explanation

The service definition on the WLM couple data set is not valid. The data set may be corrupted.

xxxx is the validation reason code. yyyy is the validation offset.

System action

The extract is not performed.

Programmer response

If the data set is corrupted, try restoring it from backups.

Module

Workload management (WLM)

IWMAM058	Install failed. WLM couple data set has not been reallocated for use with this OS/390 Release. Reallocate the WLM couple data set. Refer to the Migration Chapter in “MVS Planning: Workload Management.”
-----------------	--

Explanation

The WLM couple data set upon which you are attempting to install a service definition is not formatted for your service definition.

System action

The system does not install the service definition.

Programmer response

Re-allocate the WLM couple data set for the service definition.

Module

Workload management (WLM)

IWMAM065	Policy could not be activated. Unable to write the policy to the WLM couple data set. The WLM couple data set is too small to hold the policy.
-----------------	---

Explanation

The service policy being activated is too large to fit into the WLM couple data set.

System action

The requested action is not performed.

Programmer response

Re-allocate the WLM couple data set with a larger size, as described in [“Allocate a WLM couple data set”](#) on page 138 and [“Make a WLM couple data set available to the sysplex for the first time”](#) on page 140.

Module

Workload management (WLM)

IWMAM072	The service definition was not read due to a mismatch between the service definition PDS (LEVELxxx) and the WLM ISPF application (LEVELyyy). To read the service definition PDS, restart the WLM ISPF application at level LEVELxxx or higher.
-----------------	---

Explanation

The service definition in the PDS uses functions that are not compatible with this level of the WLM ISPF application.

System action

The requested operation is not performed.

Programmer response

Use the WLM ISPF application on a system that is compatible with the functionality level of the service definition.

Module

Workload management (WLM)

IWMAM077	Unable to use <i>datasetname</i> for service definition data, member <i>membername</i> has an unrecognized format.
-----------------	---

Explanation

WLM cannot use the *datasetname* definition data as a WLM service definition. WLM has determined that member *membername* in the PDS contains information that is not recognized by WLM. The incorrect member contains key and name information that does not match what WLM expects. Note that the member shown is the first member that was found to be invalid. It is possible that others are invalid, or that the entire data set is corrupted.

System action

The requested operation is not performed.

Programmer response

If you are using a downlevel version of the WLM ISPF, it may no longer be possible to open an ISPF service definition data set written by a higher level WLM Administrative Application. (See [“Migrating to a new z/OS release with an existing service definition” on page 133.](#)) Otherwise, the data set may be corrupted. If you cannot see an obvious problem in the data set, contact the IBM Support Center.

Module

Workload management (WLM)

IWMAM098	The service definition was not read due to a mismatch between the service definition XML (LEVELxxx) and the WLM ISPF application (LEVELyyy). To read the service definition XML restart the WLM ISPF application at LEVELxxx or higher.
-----------------	--

Explanation

The service definition in the data set uses functions that are not compatible with this level of the WLM ISPF application.

System action

The requested operation is not performed.

Programmer response

Use the WLM ISPF application on a system that is compatible with the functionality level of the service definition.

Module

Workload management (WLM)

IWMAM099	The service definition <i>datasetname</i> cannot be used because it has an incompatible format. Probable cause: the service definition was last modified by a WLM ISPF application at level <i>level</i> which is higher than the level of this application.
-----------------	---

Explanation

The service definition in the data set uses an ISPF table layout that is not compatible with this level of the WLM ISPF application.

System action

The requested operation is not performed.

Programmer response

Either use the WLM ISPF application on a system that is compatible with the ISPF table layout of the service definition, or use XML export and import to load the service definition on the backlevel system.

Module

Workload management (WLM)

IWMAM313	No more than 2047 report classes and tenant report classes may be defined.
-----------------	---

Explanation

It is not possible to define more than 2047 report classes and tenant report classes.

System action

The requested operation is not performed.

Programmer response

Do not use more than 2047 report classes and tenant report classes.

Module

Workload management (WLM)

IWMAM512	No more than 32 resource groups may be defined.
-----------------	--

Explanation

It is not possible to define more than 32 resource groups.

System action

The requested operation is not performed.

Programmer response

Do not use more than 32 resource groups.

Module

Workload management (WLM)

IWMAM540	No more than 32 tenant resource groups may be defined.
-----------------	---

Explanation

It is not possible to define more than 32 tenant resource groups.

System action

The requested operation is not performed.

Programmer response

Do not use more than 32 tenant resource groups.

Module

Workload management (WLM)

Chapter 23. Using the z/OS Management Facility (z/OSMF) to administer WLM

This information briefly describes the **Workload Management** task in the z/OS Management Facility (z/OSMF).

Overview of the z/OSMF workload management task

The workload management task in z/OS Management Facility (z/OSMF) provides a browser-based user interface that you can use to manage z/OS workload management (WLM) service definitions and provide guidelines for WLM to use when allocating resources. Specifically, you can define, modify, view, copy, import, export, and print WLM service definitions. You can also install a service definition into the WLM couple data set for the sysplex, activate a service policy, and view the status of WLM on each system in the sysplex.

Key functions of the Workload Management task in z/OSMF

The following information describes some of the key functions available in the Workload Management task in z/OSMF:

Display list of service definitions.

The Workload Management task provides a list of the WLM service definitions that have been defined in z/OSMF along with history information (for example, when the service definition was installed or modified), messages, and user activity. The list of service definitions is retrieved from the service definition repository, which refers to the directory in the z/OSMF data file system in which the data for the Workload Management task is stored.

Work with multiple service definitions.

In the Workload Management task, you can work with multiple service definitions simultaneously. To do so, open the service definitions with which you want to work in its own View, Modify, Copy, or Print Preview tab. You can also define multiple service definitions at the same time by opening several New tabs.

Install service definitions.

The Workload Management task provides features that you can use to install a service definition into the WLM couple data set for the z/OSMF host sysplex.

Extract the installed service definition.

The Workload Management task automatically extracts the service definition that is installed in the WLM couple data set for the z/OSMF host sysplex and stores it in the service definition repository so that you can view it, modify it, or activate one of its service policies.

Import and export service definitions.

The Workload Management task provides features that you can use to import a service definition from or export a service definition to your local workstation or a sequential data set on the z/OSMF host system. The exported service definition is formatted so that it can be opened with the z/OS WLM Administrative Application (also called the WLM ISPF application).

Provide table view and print preview of the service definition.

The Workload Management task provides two views of a service definition:

- **Table View.** The table view displays the parts of the service definition as tables. You can display the table view by opening the service definition in the **New**, **View**, **Modify**, or **Copy** tab. If you open the service definition in the **New**, **Modify**, or **Copy** tab, you can modify the service definition. In the **View** tab, you cannot modify the service definition.

- **Print Preview.** The print preview presents the service definition in HTML format and allows you to select which parts of the service definition you want to preview or print. You can display the print preview by opening the service definition in the **Print Preview** tab.

Activate service policies.

In the Workload Management task, you can specify which policy to activate when you install a service definition or you can activate a service policy that is defined in the service definition currently installed in the WLM couple data set for the sysplex.

Preview service policies with overrides applied.

The Workload Management task allows you to preview an HTML formatted version of the service policy with overrides applied. The HTML formatted service policy contains the information that would be included in the policy if it were activated. To preview a service policy, open the policy in the **Print Preview** tab.

View the sysplex status.

The Workload Management task provides an HTML formatted view (**WLM Status** tab) of the same data that is retrieved when you issue the D WLM,SYSTEMS command on the z/OS console. Specifically, the **WLM Status** tab displays the status of WLM on each system in the sysplex, and lists details about the installed service definition and the active service policy.

Define settings.

The Workload Management task provides a shared location (**Settings** tab) where you can specify for how long to keep the service definition history and define the code page, time zone, and backup sequential data set for the sysplex. You can also enable consistency checking between z/OSMF and the WLM couple data set, and indicate whether you want the Workload Management task to display or suppress information messages.

Actions that require the Workload Management task to interact with the sysplex are limited to the sysplex in which the z/OSMF host system is a member. Such actions include installing a service definition, activating a service policy, viewing the sysplex status, and so on. If you want to interact with another sysplex, z/OSMF must be installed on a system in that sysplex and you must log into that z/OSMF instance. You can use the service definition import and export functions to copy a service definition from one z/OSMF instance to another z/OSMF instance.

To display the Workload Management task, expand the Performance category in the z/OSMF navigation area and select **Workload Management**.

Figure 91 on page 215 shows the main panel for the Workload Management task. The **Overview** tab serves as the launch point for the actions that your user ID is authorized to access within the Workload Management task. To start using the Workload Management task, select one of the actions listed in the **Overview** tab.




Figure 91. z/OS Management Facility - Overview Panel

For more information about the configuration of the Workload Management task in z/OSMF, see [IBM z/OS Management Facility Configuration Guide](#).

Appendix A. Customizing the WLM ISPF application

This information explains how to customize your WLM application to:

- Customize the WLM application libraries.

If you have renamed or changed your IPCS/WLM library names, then you can use the IWMAREX1 exit to specify your library names.

- Customize the WLM application data sets.

If you would like to allocate the application data sets with your storage management policies, use IWMAREX2.

- Add the WLM application as an option on your ISPF menu.

If you plan to use the WLM application frequently, you can add the WLM application as an option on your ISPF application.

- Move pop-up windows.
- Customize the keylists.

Specifying the exits

To start the WLM application, you use a TSO/E REXX exec IWMARIN0. IWMARIN0 concatenates the IPCS/WLM data sets, allocates some data sets required for a service definition, and invokes the application panels. If EXITS is specified on the EXEC statement, IWMARIN0 uses the exits in the specified data set.

Table 17 on page 217 shows the return codes from IWMARIN0.

Table 17. Return codes from IWMARIN0	
Return Code	Explanation
4	Not in ISPF. Application cannot be started.
8	Unexpected keyword (parameter) on WLM application invocation. Unexpected keyword(parameter) is: <i>keyword</i> . <i>keyword</i> represents the keyword (parameter) from the command invocation.
12	Unexpected error occurred when calling installation exit IWMAREX1. One of the following: <ul style="list-style-type: none">• Installation exit IWMAREX1 must exist in <i>data-set name</i> for the WLM application to run. <i>data-set name</i> represents the data set that must contain the installation exit. Check to make sure the data set contains IWMAREX1.• Installation exit IWMAREX1 must exist in the current concatenation order for the WLM application to run.
16	Unexpected keyword (parameter) from WLM exit IWMAREX1. Please check coding in WLM installation exit IWMAREX1 for incorrect keyword (parameter): <i>parameter</i> . <i>parameter</i> represents the keyword (parameter) that is incorrect.
20	Unexpected RC="rc" from TSO ALTLIB ISPF LIBDEF for <i>data-set-name</i> The WLM application cannot be started due to ALTLIB or LIBDEF failures for <i>data-set-name</i> . See specific REXX messages for the names of the data sets which failed.

Table 17. Return codes from IWMARIN0 (continued)	
Return Code	Explanation
24	<p>ALTLIB failed during attempt to find installation exit data set. WLM application can not be started. TSO ALTLIB RC=xx.</p> <p>xx represents return code from TSO ALTLIB service.</p>

Coding the WLM exits

The exit stubs are shipped in SYS1.SBLSCLI0. If you want to customize the application with the exits, create a data set for your exits, copy IWMAREX1 or IWMAREX2 into the data set, and modify the exits with your options. When you create the data set for your exits, specify the same data set characteristics as SYS1.SBLSCLI0.

You specify the exit data set on the TSO/E EXEC statement when you start the WLM application. Specify the fully qualified data set name containing the exit. For example, suppose you created data set IPCS.EXITES, and coded IWMAREX1. To start the WLM application with the exit, you specify:

```
EX 'SYS1.SBLSCLI0(IWMARIN0)' 'EXIT(IPCS.EXITES)'
```

IWMARIN1

If you have previously allocated the required data sets, either in a logon procedure, or in a CLIST, you can use IWMARIN1 to start the WLM application. To use IWMARIN1, specify:

```
EX 'SYS1.SBLSCLI0(IWMARIN1)'
```

Customizing the WLM application libraries – IWMAREX1

WLM provides the IWMAREX1 exit to specify the IPCS/WLM libraries names. If you have renamed or customized the following IPCS/WLM libraries, use IWMAREX1 to specify your names.

Table 18. WLM Libraries	
Library	Content
SYS1.SBLSCLI0	Application REXX code data set
SYS1.SBLSKELO	Application skeleton data set
SYS1.SBLSPNL0	Application panel data set
SYS1.SBLSTBL0	Application keylists and commands data set
SYS1.SBLSMSG0	Application messages data set

If you have renamed them in your installation, use IWMAREX1 to set up the allocations.

IWMAREX1 is a REXX routine for specifying installation-customized data sets required for starting the WLM ISPF application.

If you have renamed or changed the WLM/IPCS data sets in your installation, use IWMAREX1 to set up the allocations.

Processing

IWMAREX1 is called from the IWMARIN0 REXX exec.

Parameters

IWMAREX1 has the following parameters:

REXXDS

The application REXX code data set.

SKELDS

The application skeleton data set.

PANELDS

The application panel data set.

TABLEDS

The application tables (keylist and commands) data set.

MESSAGEDS

The application messages data set.

Example

Suppose the IPCS/WLM application resides in SYS1.IPCS.SBLSCLI0, and you have renamed your IPCS/WLM libraries to:

```
SYS1.IPCS.SBLSMSG0  
SYS1.IPCS.SBLSPNL0  
SYS1.IPCS.SBLSKEL0  
SYS1.IPCS.SBLSTBL0
```

Suppose you have created your exit in a data set called WLM.EXIT0. You code IWMAREX1 in the following way:

```
/* REXX */  
queue 'REXXDS(SYS1.IPCS.SBLSCLI0)'  
queue 'SKELDS(SYS1.IPCS.SBLSKEL0)'  
queue 'PANELDS(SYS1.IPCS.SBLSPNL0)'  
queue 'TABLEDS(SYS1.IPCS.SBLSTBL0)'  
queue 'MESSAGEDS(SYS1.IPCS.SBLSMSG0)'  
Exit 0
```

To start the WLM application with the exit, you specify:

```
EX 'SYS1.IPCS.SBLSCLI0(IWMARIN0)' 'EXIT(WLM.EXIT0)'
```

Customizing the WLM application data sets – IWMAREX2

WLM provides the IWMAREX2 exit to specify:

- The application recovery data set and data set characteristics.
- The service definition data set and data set characteristics.

You should use this exit to allocate data sets according to your installation's storage management policies. You can not change any of the following TSO/E ALLOCATE parameters in IWMAREX2:

- Data set name (DA)
- Record format (RECFM)
- Logical record length (LRECL)
- Data set organization (DSORG)

Unless you code otherwise in this exit, the WLM application uses the following data set information as the defaults:

```
UNIT(SYSDA)
TRACKS SPACE(15,15)
```

Processing

This exit is called from the IWMARZAL REXX exec.

Parameters

IWMAREX2 has the following parameters:

ARDSDIR

Specifies the number of 256 byte records to be allocated for the application recovery data set.

ARDSOPTS

Specifies the options for the application recovery data sets, with the following sub-parameters:

UNIT(*xxxx*)

Specifies the unit type for the TSO ALLOCATE command.

STORCLAS

The SMS storage class.

MGMTCLAS

The SMS management class.

DATACLAS

The SMS data class.

To determine what to specify for unit, check which UNIT type is coded for the TSO ALLOCATE command in your installation.

ARDSSPACE

Specifies the options to allocate a data set. The options are:

SPACE(*quantity*,(*increment*))

TRACKS

CYLINDERS

BLOCKS(*value*)

PDDSDIR

Specifies the number of 256 byte records to be allocated for the print service definition data set.

PDDSOPTS

Specifies the options for the print service definition data set, with the following sub-parameters:

UNIT(*xxxx*)

Specifies the unit type for the TSO ALLOCATE command.

STORCLAS

The SMS storage class.

MGMTCLAS

The SMS management class.

DATACLAS

The SMS data class.

To determine what to specify for unit, check which UNIT type is coded for the TSO ALLOCATE command in your installation.

PDDSSPACE

Specifies the options to allocate a print definition data set. The options are:

SPACE(*quantity*,(*increment*))

TRACKS

CYLINDERS

BLOCKS(*value*)

SDDSDIR

Specifies the number of 256 byte records to be allocated for the service definition data set.

SDDSOPTS

Specifies the options for the service definition data sets, with the following sub-parameters:

UNIT(*xxxx*)

Specifies the unit type for the TSO ALLOCATE command.

STORCLAS

The SMS storage class.

MGMTCLAS

The SMS management class.

DATACLAS

The SMS data class.

SDDSSPACE

Specifies the options to allocate a data set. The options are:

SPACE(*quantity*,(*increment*))

TRACKS

CYLINDERS

BLOCKS(*value*)

XMLDSOPTS

Specifies the options for the service definition XML data sets, with the following sub-parameters:

UNIT(*xxxx*)

Specifies the unit type for the TSO ALLOCATE command.

STORCLAS

The SMS storage class.

MGMTCLAS

The SMS management class.

DATACLAS

The SMS data class.

XMLDSSPACE

Specifies the options to allocate a service definition XML data set. The options are:

SPACE(*quantity*,(*increment*))

TRACKS

CYLINDERS

BLOCKS(*value*)

Examples

The following examples show some uses of the IWMAREX2 exit:

- Suppose you want to specify that the UNIT type for your TSO allocate commands in your installation is type SYSDS. In exit IWMAREX2, you specify the following:

```
/* REXX */
'ARDSOPTS(UNIT(SYSDS))'
Exit 0
```

- Suppose you want to specify the service definition data sets as SMS managed data sets in the standard storage class, and in the NOMIG management class. In exit IWMAREX2, you specify the following:

```
/* REXX */  
queue 'ARDSOPTS(STORCLAS(STANDARD) MGMTCLAS(NOMIG))'  
queue 'ARDSSPACE(SPACE(10,10) TRACKS)'  
Exit 0
```

Adding WLM as an ISPF menu option

To add the WLM application as an option on your ISPF primary panel, you should make a copy of the ISPF primary option menu - ISR@PRIM. You need to add some information to the processing section of the panel. What you add depends on whether you use IWMARIN0 or IWMARIN1 to start the application.

If you use IWMARIN0, specify:

```
WLM, 'CMD(EXEC "SYS1.SBLSCLI0(IWMARIN0)") NEWAPPL(IWMP) PASSLIB'
```

If you use the WLM exits together with IWMARIN0, specify:

```
WLM, 'CMD(EXEC "SYS1.SBLSCLI0(IWMARIN0)" "EXIT(ISPF.EXITS)") NEWAPPL(IWMP) PASSLIB'
```

If you use IWMARIN1, specify:

```
WLM, 'CMD(EXEC "SYS1.SBLSCLI0(IWMARIN1)") NEWAPPL(IWMP) PASSLIB'
```

Make sure you concatenate the library containing your customized primary panel before any others in your logon procedure or CLIST.

Example: Adding WLM as an option on your ISPF menu

Figure 92 on page 223 shows the two lines added to a copy of the ISPF primary panel. In the example, IWMARIN1 is specified. The two lines are highlighted in the figure.

```

----- ISPF/PDF PRIMARY OPTION MENU -----
%OPTION ==>_ZCMD
%
% 0 +ISPF PARMS - Specify terminal and user parameters +USERID -
% 1 +BROWSE - Display source data or output listings +TIME -
% 2 +EDIT - Create or change source data +PF KEYS -
% 3 +UTILITIES - Perform utility functions
% 4 +FOREGROUND - Invoke language processors in foreground
% 5 +BATCH - Submit job for language processing
% 6 +COMMAND - Enter TSO/E command or CLIST
% 7 +DIALOG TEST - Perform dialog testing
% 8 +LM UTILITIES- Perform library management utility functions
% C +CHANGES - Display summary of changes for this release
% W +WLM - WLM administrative application
% T +TUTORIAL - Display information about ISPF/PDF
% X +EXIT - Terminate ISPF using log and list defaults
%
+Enter%END+command to terminate ISPF.
%
)INIT
.HELP = ISR00003
&ZPRIM = YES /* ALWAYS A PRIMARY OPTION MENU */
&ZHTOP = ISR00003 /* TUTORIAL TABLE OF CONTENTS */
&ZHINDEX = ISR91000 /* TUTORIAL INDEX - 1ST PAGE */
VPUT (ZHTOP,ZHINDEX) PROFILE
)PROC
&ZSEL = TRANS( TRUNC (&ZCMD, '.'))
0, 'PANEL(ISPOPTA)'
1, 'PGM(ISRBRO) PARM(ISRBRO01)'
2, 'PGM(ISREDIT) PARM(P,ISREDM01)'
3, 'PANEL(ISRUTIL)'
4, 'PANEL(ISRFPA)'
5, 'PGM(ISRJB1) PARM(ISRJPA) NOCHECK'
6, 'PGM(ISRPTC)'
7, 'PGM(ISRYXDR) NOCHECK'
8, 'PANEL(ISRLPRIM)'
C, 'PGM(ISPTUTOR) PARM(ISR00005)'
W, 'CMD(EXEC "SYS1.SBLSCLI0(IWMARIN1)") NEWAPPL(IWMP) PASSLIB'
T, 'PGM(ISPTUTOR) PARM(ISR00000)'
, , ,
X, 'EXIT'
*, '?' )
&ZTRAIL = .TRAIL
)END

```

Figure 92. Example of adding WLM as an option on the ISPF menu

Moving pop-up windows

If you would like to customize the placement of the pop-up windows in the WLM application, you can use a manual ISPF function. You must place the cursor anywhere on the active window frame and press Enter. ISPF acknowledges the window move request by displaying `WINDOW MOVE pending` message. Then place the cursor where you want the upper left corner of the pop-up placed. press Enter a second time, and the pop-up is moved to the new location.

Note: The placement lasts only for the duration of the session. If you exit the application, your changes are lost.

There are some other options for moving pop-up windows. For more information about them, see *ISPF Dialog Management Guide and Reference*.

Customizing the keylists

The WLM application uses a set of keylists which you can customize to your purposes. To edit a keylist, type:

```
KEYLIST
```

on the command line from any panel in the WLM application. The application displays the keylist utility panel, as shown in [Figure 93](#) on page 224. From this panel, select the keylist you would like to work with, and choose an action from **Options** on the menu bar.

```

Options  Change Keylists
-----
ISPKLUP      Keylist Utility for IWMP      ROW 1 TO 9 OF 9
Command ==>  -----

Enter keylist name _____ OR

Select one keylist name from the list below:
Select  Keylist  T  -
-       KEYSBRP   S
-       KEYSWRK   S
-       KEYS001   S
-       KEYS002   S
-       KEYS01H   S
-       KEYS01P   S
-       KEYS01S   S  *** CURRENTLY ACTIVE KEYLIST ***
-       KEYS02A   S
-       KEYS02B   S
-       KEYS02P   S
***** END OF DATA *****

```

Figure 93. Keylist Utility panel

The keylists and the type of panels on which they are used are:

Table 19. Keylist names and usage descriptions

Keylist	Function
KEYS001	Non-scrollable, non pop-up
KEYS002	Scrollable, non pop-up
KEYS01P	Non-scrollable, pop-up
KEYS02P	Scrollable, pop-up
KEYS01H	All help panels
KEYS01S	Non-scrollable, non pop-up, no PF4=RETURN
KEYS02A	Scrollable, non pop-up, PF1=HELPD, PF10=ACTIONS.
KEYS02B	Scrollable, non pop-up, PF1=HELPD, PF10=LEFT, PF11=RIGHT.
KEYSBRP	Browse panel
KEYSWRK	"Working..." panel

Appendix B. CPU capacity table

The tables presented at [Processor version codes and SRM constants \(www.ibm.com/support/pages/processor-version-codes-and-srm-constants\)](http://www.ibm.com/support/pages/processor-version-codes-and-srm-constants) show the unweighted CPU service units per second by CPU model. You use this information to define your minimum and maximum capacity for a resource group.

Also, for the latest information about the processor version codes and SRM constants, see the online documentation available at the same location.

If you plan to use these constants for purposes other than those suggested in this information, observe the following limitations:

- Actual customer workloads and performance may vary. For a more exact comparison of processors, see the internal throughput rate (ITR) numbers in [IBM Z Large Systems Performance Reference \(www.ibm.com/support/pages/ibm-z-large-systems-performance-reference\)](http://www.ibm.com/support/pages/ibm-z-large-systems-performance-reference).
- CPU time can vary for different runs of the same job step. One or more of the following factors might cause variations in the CPU time: CPU architecture (such as storage buffering), cycle stealing with integrated channels, and the amount of the queue searching (see [z/OS MVS System Management Facilities \(SMF\)](#)).
- The constants do not account for multiprocessor effects within logical partitions. For example, a logical 10-way partition on a particular machine has 94674.6 service units per second, while a 20-way partition on the same machine has 82901.6 service units per second.

Using SMF task time

For installations with no prior service data, the task time reported in SMF type 4, 5, 30, 34, and 35 records can be converted to service units using the tables in [Appendix B, “CPU capacity table,” on page 225](#).

Examples of resource groups

- To give a department a “dedicated 4381” amount of capacity, you can specify the following resource group:

Name

4381-91E

Description

Capacity of a 4381

Capacity Minimum

309

Capacity Maximum

309

- To assure half the capacity of a 9672 Model Y96 system, with 9 physical CPs, to a service class, specify the following:

Name

HALFSYS3

Description

Preserve half of SYS3 (9672 Mod Y96)

Capacity Maximum

24129

Since the 9672 Model Y96 has 5362 raw CPU service units per second, with 9 physical CPs, $0.5 \times 9 \times 5362$ is 24129. The 24129 is captured service units allocated to the address spaces in the resource group.

Appendix C. Return codes for the IWMINSTL sample job

This information describes the return codes issued by the IWMINSTL sample job. The Install Definition Utility is shipped as member IWMINSTL in SYS1.SAMPLIB. You can use the IWMINSTL job to install a WLM service definition or to activate a WLM policy without having to use the ISPF WLM application.

Table 20 on page 227 describes the return codes that are issued by IWMINSTL. An accompanying message text is written to the job output listing.

Table 20. Return codes from IWMINSTL

Return code	Message text and explanation
0	Successful execution.
104	The service definition was not processed due to a mismatch between the WLM address space level (current.wlm.level) and the level of this utility (IWMARIDU.level). Use the correct level of the IWMARIDU utility.
204	GetServiceDefinition Unable to use (your.definition.dataset) for service definition data. A table has an unrecognized format.
208	GetServiceDefinition Unable to use (your.definition.dataset), data set is in use.
212	GetServiceDefinition The service definition was not read due to a mismatch between the service definition PDS and the WLM Install Definition Utility. The service definition PDS has a higher functionality level than the current version of the WLM Install Definition Utility. Once a service definition was updated by a WLM instance with a higher functionality level it can no longer be updated by a WLM instance with lower functionality level.
216	GetServiceDefinition The service definition was not opened due to an ISPF dialog error.
220	GetServiceDefinition The service definition is passed in XML format, and the XML is invalid. See preceding message for details.
304	InstallServiceDefinition Install failed, service definition has no name. No service definition name was specified. To fix the error, do the following: <ul style="list-style-type: none">• Specify a valid service definition name for IWMINSTL parameter SVDEFPDS.• Verify in the IWMINSTL JCL, whether the SVDEF DD statement exists.

Table 20. Return codes from IWMINSTL (continued)

Return code	Message text and explanation
308	InstallServiceDefinition Install failed, no workloads are defined.
312	InstallServiceDefinition Install failed, no service classes are defined.
316	InstallServiceDefinition Install failed, no service policies are defined.
320	InstallServiceDefinition Install failed, access was denied to the WLM couple data set. The user ID does not have update authority to the RACF resource MVSADMIN.WLM.POLICY in the FACILITY class.
324	InstallServiceDefinition InstallServiceDefinition Install failed, service definition was modified Every WLM service definition contains a service definition ID. An attempt was made to install a service definition with a different ID than the service definition ID that is installed. A WLM service definition ID consists of the following: <ul style="list-style-type: none"> • The name of the service definition • A timestamp when the service definition was installed • A user ID that installed the service definition • The system name from which the installation was done Use the FORCE=Y parameter for the WLM install definition utility to install a service definition with a different ID. The default is FORCE=N.
336	InstallServiceDefinition Install failed, failure in WLM bridge layer. Additional messages regarding this error might be written to the job output listing.
404	ActivateServicePolicy The service policy was not activated due to an ISPF dialog error.
408	ActivateServicePolicy Activate failed, activation in progress on another system.
412	ActivateServicePolicy Activate failed, one or more systems were unable to activate the policy.
416	ActivateServicePolicy Activate failed, (POLNAME) was not found on the WLM couple data set.
420	ActivateServicePolicy Activate failed, failure in WLM bridge layer. Additional messages regarding this error might be written to the job output listing.

Appendix D. Accessibility

Accessible publications for this product are offered through [IBM Documentation \(www.ibm.com/docs/en/zos\)](http://www.ibm.com/docs/en/zos).

If you experience difficulty with the accessibility of any z/OS information, send a detailed message to the [Contact the z/OS team web page \(www.ibm.com/systems/campaignmail/z/zos/contact_z\)](http://www.ibm.com/systems/campaignmail/z/zos/contact_z) or use the following mailing address.

IBM Corporation
Attention: MHVRCFS Reader Comments
Department H6MA, Building 707
2455 South Road
Poughkeepsie, NY 12601-5400
United States

Notices

This information was developed for products and services that are offered in the USA or elsewhere.

IBM may not offer the products, services, or features discussed in this document in other countries. Consult your local IBM representative for information on the products and services currently available in your area. Any reference to an IBM product, program, or service is not intended to state or imply that only that IBM product, program, or service may be used. Any functionally equivalent product, program, or service that does not infringe any IBM intellectual property right may be used instead. However, it is the user's responsibility to evaluate and verify the operation of any non-IBM product, program, or service.

IBM may have patents or pending patent applications covering subject matter described in this document. The furnishing of this document does not grant you any license to these patents. You can send license inquiries, in writing, to:

*IBM Director of Licensing
IBM Corporation
North Castle Drive, MD-NC119
Armonk, NY 10504-1785
United States of America*

For license inquiries regarding double-byte character set (DBCS) information, contact the IBM Intellectual Property Department in your country or send inquiries, in writing, to:

*Intellectual Property Licensing
Legal and Intellectual Property Law
IBM Japan Ltd.
19-21, Nihonbashi-Hakozakicho, Chuo-ku
Tokyo 103-8510, Japan*

The following paragraph does not apply to the United Kingdom or any other country where such provisions are inconsistent with local law: INTERNATIONAL BUSINESS MACHINES CORPORATION PROVIDES THIS PUBLICATION "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF NON-INFRINGEMENT, MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. Some states do not allow disclaimer of express or implied warranties in certain transactions, therefore, this statement may not apply to you.

This information could include technical inaccuracies or typographical errors. Changes are periodically made to the information herein; these changes will be incorporated in new editions of the publication. IBM may make improvements and/or changes in the product(s) and/or the program(s) described in this publication at any time without notice.

This information could include missing, incorrect, or broken hyperlinks. Hyperlinks are maintained in only the HTML plug-in output for IBM Documentation. Use of hyperlinks in other output formats of this information is at your own risk.

Any references in this information to non-IBM websites are provided for convenience only and do not in any manner serve as an endorsement of those websites. The materials at those websites are not part of the materials for this IBM product and use of those websites is at your own risk.

IBM may use or distribute any of the information you supply in any way it believes appropriate without incurring any obligation to you.

Licensees of this program who wish to have information about it for the purpose of enabling: (i) the exchange of information between independently created programs and other programs (including this one) and (ii) the mutual use of the information which has been exchanged, should contact:

*IBM Corporation
Site Counsel
2455 South Road*

Poughkeepsie, NY 12601-5400
USA

Such information may be available, subject to appropriate terms and conditions, including in some cases, payment of a fee.

The licensed program described in this document and all licensed material available for it are provided by IBM under terms of the IBM Customer Agreement, IBM International Program License Agreement or any equivalent agreement between us.

Any performance data contained herein was determined in a controlled environment. Therefore, the results obtained in other operating environments may vary significantly. Some measurements may have been made on development-level systems and there is no guarantee that these measurements will be the same on generally available systems. Furthermore, some measurements may have been estimated through extrapolation. Actual results may vary. Users of this document should verify the applicable data for their specific environment.

Information concerning non-IBM products was obtained from the suppliers of those products, their published announcements or other publicly available sources. IBM has not tested those products and cannot confirm the accuracy of performance, compatibility or any other claims related to non-IBM products. Questions on the capabilities of non-IBM products should be addressed to the suppliers of those products.

All statements regarding IBM's future direction or intent are subject to change or withdrawal without notice, and represent goals and objectives only.

This information contains examples of data and reports used in daily business operations. To illustrate them as completely as possible, the examples include the names of individuals, companies, brands, and products. All of these names are fictitious and any similarity to the names and addresses used by an actual business enterprise is entirely coincidental.

COPYRIGHT LICENSE:

This information contains sample application programs in source language, which illustrate programming techniques on various operating platforms. You may copy, modify, and distribute these sample programs in any form without payment to IBM, for the purposes of developing, using, marketing or distributing application programs conforming to the application programming interface for the operating platform for which the sample programs are written. These examples have not been thoroughly tested under all conditions. IBM, therefore, cannot guarantee or imply reliability, serviceability, or function of these programs. The sample programs are provided "AS IS", without warranty of any kind. IBM shall not be liable for any damages arising out of your use of the sample programs.

Terms and conditions for product documentation

Permissions for the use of these publications are granted subject to the following terms and conditions.

Applicability

These terms and conditions are in addition to any terms of use for the IBM website.

Personal use

You may reproduce these publications for your personal, noncommercial use provided that all proprietary notices are preserved. You may not distribute, display or make derivative work of these publications, or any portion thereof, without the express consent of IBM.

Commercial use

You may reproduce, distribute and display these publications solely within your enterprise provided that all proprietary notices are preserved. You may not make derivative works of these publications, or

reproduce, distribute or display these publications or any portion thereof outside your enterprise, without the express consent of IBM.

Rights

Except as expressly granted in this permission, no other permissions, licenses or rights are granted, either express or implied, to the publications or any information, data, software or other intellectual property contained therein.

IBM reserves the right to withdraw the permissions granted herein whenever, in its discretion, the use of the publications is detrimental to its interest or, as determined by IBM, the above instructions are not being properly followed.

You may not download, export or re-export this information except in full compliance with all applicable laws and regulations, including all United States export laws and regulations.

IBM MAKES NO GUARANTEE ABOUT THE CONTENT OF THESE PUBLICATIONS. THE PUBLICATIONS ARE PROVIDED "AS-IS" AND WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING BUT NOT LIMITED TO IMPLIED WARRANTIES OF MERCHANTABILITY, NON-INFRINGEMENT, AND FITNESS FOR A PARTICULAR PURPOSE.

IBM Online Privacy Statement

IBM Software products, including software as a service solutions, ("Software Offerings") may use cookies or other technologies to collect product usage information, to help improve the end user experience, to tailor interactions with the end user, or for other purposes. In many cases no personally identifiable information is collected by the Software Offerings. Some of our Software Offerings can help enable you to collect personally identifiable information. If this Software Offering uses cookies to collect personally identifiable information, specific information about this offering's use of cookies is set forth below.

Depending upon the configurations deployed, this Software Offering may use session cookies that collect each user's name, email address, phone number, or other personally identifiable information for purposes of enhanced user usability and single sign-on configuration. These cookies can be disabled, but disabling them will also eliminate the functionality they enable.

If the configurations deployed for this Software Offering provide you as customer the ability to collect personally identifiable information from end users via cookies and other technologies, you should seek your own legal advice about any laws applicable to such data collection, including any requirements for notice and consent.

For more information about the use of various technologies, including cookies, for these purposes, see IBM's Privacy Policy at ibm.com/privacy and IBM's Online Privacy Statement at ibm.com/privacy/details in the section entitled "Cookies, Web Beacons and Other Technologies," and the "IBM Software Products and Software-as-a-Service Privacy Statement" at ibm.com/software/info/product-privacy.

Policy for unsupported hardware

Various z/OS elements, such as DFSMSdfp, JES2, JES3, and MVS, contain code that supports specific hardware servers or devices. In some cases, this device-related element support remains in the product even after the hardware devices pass their announced End of Service date. z/OS may continue to service element code; however, it will not provide service related to unsupported hardware devices. Software problems related to these devices will not be accepted for service, and current service activity will cease if a problem is determined to be associated with out-of-support devices. In such cases, fixes will not be issued.

Minimum supported hardware

The minimum supported hardware for z/OS releases identified in z/OS announcements can subsequently change when service for particular servers or devices is withdrawn. Likewise, the levels of other software products supported on a particular release of z/OS are subject to the service support lifecycle of those

products. Therefore, z/OS and its product publications (for example, panels, samples, messages, and product documentation) can include references to hardware and software that is no longer supported.

- For information about software support lifecycle, see: [IBM Lifecycle Support for z/OS \(www.ibm.com/software/support/systemsz/lifecycle\)](http://www.ibm.com/software/support/systemsz/lifecycle)
- For information about currently-supported IBM hardware, contact your IBM representative.

Trademarks

IBM, the IBM logo, and ibm.com are trademarks or registered trademarks of International Business Machines Corp., registered in many jurisdictions worldwide. Other product and service names might be trademarks of IBM or other companies. A current list of IBM trademarks is available on the Web at [Copyright and Trademark information \(www.ibm.com/legal/copytrade.shtml\)](http://www.ibm.com/legal/copytrade.shtml).

Linux is a registered trademark of Linus Torvalds in the United States, other countries, or both.

Microsoft, Windows, and the Windows logo are trademarks of Microsoft Corporation in the United States, other countries, or both.

UNIX is a registered trademark of The Open Group in the United States and other countries.

Java and all Java-based trademarks and logos are trademarks or registered trademarks of Oracle and/or its affiliates.

Other company, product, and service names may be trademarks or service marks of others.

Workload management terms

active service policy

The service policy that determines workload management processing.

application environment

A group of application functions requested by a client that execute in server address spaces.

application owning region (AOR)

In a CICSplex configuration, a CICS region devoted to running applications.

automatic control

One of two distinct methods of managing application environments. Under automatic control, the name of the startup JCL procedure has been defined for an application environment, giving workload management the ability to automatically start server address spaces. Contrast with *manual control*.

channel path identifier

The channel subsystem communicates with I/O devices by means of a channel path between the channel subsystem and devices. A CHPID is a value assigned to each channel path of the System z that uniquely identifies that path. Up to 256 CHPIDs are supported for each channel subsystem.

CICSplex

A configuration of interconnected CICS systems in which each system is dedicated to one of the main elements of the overall workload. See also *application owning region*, *file owning region*, and *terminal owning region*.

classification rules

The rules workload management and subsystems use to assign a service class and, optionally, a report class or tenant report class to a work request. A classification rule consists of one or more of work qualifiers such as subsystem type, subsystem instance, userid, accounting information, transaction name, transaction class, source LU, netid, and LU name.

compatibility mode

Prior to z/OS V1R3 a mode of processing, in which the IEAIPSxx and IEAICSxx parmlib members determine system resource management. See also *goal mode*.

control region

The main storage region that contains the subsystem work manager or subsystem resource manager control program.

couple data set

A data set created through the XCF couple data set format utility. The data set is shared by MVS systems in a sysplex. There are several types of couple data sets for different purposes. See also *WLM couple data set*.

CPU service units

A measure of the task control block (TCB) execution time multiplied by an SRM constant which is CPU model dependent. See also *unweighted CPU service units per second*, and *service unit*.

delay monitoring services

The workload management services that monitor the delays encountered by a work request.

distributed data facility (DDF)

An optional feature that allows a DB2 application to access data at other DB2s and at remote relational database systems that support IBM's Distributed Relational Database Architecture™ (DRDA).

duration

The length of a service class performance period in service units.

dynamic alias management

A service definition option — when enabled, workload management will dynamically reassign parallel access volume aliases to help work meet its goals and to minimize IOS queueing.

enclave

A transaction that can span multiple dispatchable units (SRBs and tasks) in one or more address spaces and is reported on and managed as a unit.

execution velocity

A service goal naming the rate at which you expect work to be processed for a given service class or a measure of the acceptable processor and storage delays while work is running.

fold qualifier names

When defining classification rules, the “Fold qualifier names” option, when set to the default Y, means that the qualifier names will be folded to upper case as soon as you type them in and then press Enter. If you set this option to N, then the qualifier names will remain in the case they are typed in.

goal mode

A mode of processing where the active service policy determines system resource management.

guest platform management provider (GPMP)

An optional suite of applications that is installed in specific z/OS, Linux, and AIX® operating system images to support platform management functions. For example, the guest platform management provider collects and aggregates performance data for virtual servers and workloads. Users view these reports through the ensemble-management Hardware Management Console (HMC).

Hardware Management Console (HMC)

A user interface through which data center personnel configure, control, monitor, and manage System z hardware and software resources. The HMC communicates with each central processor complex (CPC) through the CPC's Support Element (SE). On a zEnterprise 196, using the Unified Resource Manager on the HMCs/SEs, personnel can also create and manage an ensemble.

HMC

Accepted acronym for Hardware Management Console.

hypervisor

A program that allows multiple instances of operating systems or virtual servers to run simultaneously on the same hardware device. A hypervisor can run directly on the hardware, can run within an operating system, or can be imbedded in platform firmware. Examples of hypervisors include PR/SM, zVM, and PowerVM®.

IBM System z

Family name. After first use can be System z.

IBM z Application Assist Processor (zAAP)

A specialized processor that provides a Java™ execution environment, which enables Java-based Web applications to be integrated with core z/OS business applications and backend database systems.

IBM z Enterprise Unified Resource Manager (Unified Resource Manager)

Utilize on "first use". Then can use z Enterprise Unified Resource Manager or short form Unified Resource Manager. See "Unified Resource Manager".

IBM z Integrated Information Processor (zIIP)

A specialized processor that provides computing capacity for selected data and transaction processing workloads, and for selected network encryption workloads.

importance level

the degree of importance of a service goal relative to other service class goals, in five levels: lowest, low, medium, high, highest.

intranode management network (INMN)

A private 1000BASE-T Ethernet network operating at 1 Gbps that is required for the Unified Resource Manager to manage the resources within a single zEnterprise node. The INMN connects the Support Element (SE) to the z196 and to any attached zBX.

I/O priority management

A service definition option — when enabled, I/O priorities will be managed separately from dispatching priorities, according to the goals of the work.

I/O service units

A measure of individual data set I/O activity and JES spool reads and writes for all data sets associated with an address space.

installation

A particular computing system, including the work it does and the people who manage it, operate it, apply it to problems, service it, and use the results it produces.

installed service definition

The service definition residing in the WLM couple data set for WLM.

logical unit (LU)

In *VTAM*, the source and recipient of data transmissions. Data is transmitted from one logical unit (LU) to another LU. For example, a terminal can be an LU, or a CICS or IMS system can be an LU.

LU

Logical unit.

LU name

The second level of the source LU name after the “.” for fully qualified names.

LU 6.2 session

A session that is initiated by VTAM* programs on behalf of a logical unit (LU) 6.2 application program, or a session initiated by a remote LU in which the application program specifies that the VTAM programs are to control the session by using the APPCCMD macro instruction.

manual control

One of two distinct methods of managing application environments in goal mode. Under manual control, the name of the startup JCL procedure has not been defined for an application environment. The installation must therefore manually start server address spaces when needed. Contrast with *automatic control*.

masking

Using a % for a single character replacement in classification rules. See also *wild carding*.

MVS image

The system-id of any MVS system included in the sysplex as it appears in SYS1.PARMLIB member.

performance administration

The process of defining and adjusting workload management goals and resource groups based on installation business objectives.

performance block

A piece of storage containing workload management's record of execution delay information about work requests.

performance management

The process workload management uses to decide how to match resources to work according to performance goals and processing capacity.

performance period

A service goal and importance level assigned to a service class for a specific duration. You define performance periods for work that has changing performance requirements as work consumes resources.

policy

See *service policy*.

relational database management system (RDBMS)

A relational database manager that supports SAA.

report class

A group of work for which reporting information is collected separately. For example, you can have a report class for information combining two different service classes, or a report class for information on a single transaction.

resource

When used as part of a scheduling environment, a resource is an abstract element that can represent an actual physical entity (such as a peripheral device), or an intangible quality (such as a certain time of day). A resource is listed in a scheduling environment along with a required state of ON or OFF. If the corresponding resource state on a given system matches the required state, then the requirement is satisfied for that resource.

resource group

An amount of processing capacity across one or more MVS images, assigned to one or more service classes.

scheduling environment

A list of resource names along with their required states. If an MVS image satisfies all of the requirements in the scheduling environment associated with a given unit of work, then that unit of work can be assigned to that MVS image. If any of the requirements are *not* satisfied, then that unit of work *cannot* be assigned to that MVS image.

server address space

Any address space that does work on behalf of a transaction manager or a resource manager. For example, a server address space could be a CICS AOR, or an IMS control region.

service administration application

The online ISPF application used by the service administrator to specify the workload management service definition.

service class

A group of work which has the same performance goals, resource requirements, or business importance. For workload management, you assign a service goal and optionally a resource group to a service class.

service definition

A definition of the workloads and classification rules in an installation. The definition includes workloads, service classes, systems, resource groups, service policies, and classification rules.

service level administrator

The user role introduced by workload management whose main task is to make sure overall installation operation is consistent with performance goals and objectives.

service level agreement (SLA)

A written agreement of the information systems (I/S) service to be provided to the users of a computing installation.

service policy

A named set of performance goals workload management uses as a guideline to match resources to work. See also *active service policy*.

service request block (SRB) service units

A measure of the SRB execution time for both local and global SRBs, multiplied by an SRM constant which is CPU model dependent.

service unit

The amount of service consumed by a work request as calculated by CPU and SRB service units.

single-system sysplex

A sysplex in which only one MVS system is initialized as part of the sysplex. In a single-system sysplex, XCF provides XCF services on the system, but does not provide signalling services between MVS systems. See also *multi-system sysplex*, *XCF-local mode*, and *monoplex*.

source LU

A fully qualified two level name separated by a “.”, where the first level is the network id and the second is the LU name, OR merely a single LU name. See also *LU name*.

storage service units

A measure of the central storage page frames multiplied by 1/50 of the CPU service units. The 1/50 is a scaling factor designed to bring the storage service component in line with the CPU component.

subsystem instance

1) For application environments, a unique combination of subsystem type (as specified in the service definition for an application environment) and subsystem name (as specified by the work manager subsystem when it connects to workload management). 2) For classification, a work qualifier used to distinguish multiple instances of a subsystem.

subsystem work manager

An address space defined in the SYS1.PARMLIB member as SUBSYS=nnn.

Tenant report class

Same as a report class but assigned to a tenant resource group and thus provides the metering capability for the tenant resource group.

Tenant resource group

A tenant resource group that allows the metering and optional capping of workloads, along with the ability to map those workloads directly to Tailored Fit Pricing for IBM Z.

terminal owning region (TOR)

A CICS region devoted to managing the terminal network.

Unified Resource Manager

Full name: IBM zEnterprise Unified Resource Manager. Licensed Internal Code (LIC), also known as firmware, that is part of the Hardware Management Console. The Unified Resource Manager provides energy monitoring and management, goal-oriented policy management, increased security, virtual networking, and data management for the physical and logical resources of a given ensemble.

unweighted CPU service units per second

The unweighted service units per second of task or SRB execution time. This measure is CPU-model dependent.

velocity

A service goal naming the rate at which you expect work to be processed for a given service class or a measure of the acceptable processor and storage delays while work is running.

wild carding

The use of an asterisk (*) as a multiple character replacement in classification rules. See also *masking*.

WLM couple data set

A type of couple data set that is created through the XCF couple data set format utility for the WLM function. The data set contains the service definition information.

workload

A group of work to be tracked, managed and reported as a unit. Also, a group of service classes.

workload management mode

The mode in which workload management manages system resources on an MVS image. Prior to z/OS V1R3 this mode could be either *compatibility mode*, or *goal mode*. Starting with z/OS V1R3, compatibility mode has been removed.

work qualifier

An attribute of incoming work. Work qualifiers include: subsystem type, subsystem instance, userid, accounting information, transaction name, transaction class, source LU, netid, and LU name.

work request

A piece of work, such as a request for service, a batch job, an APPC, CICS, or IMS transaction, a TSO LOGON, or a TSO command.

zAAP

Approved acronym for IBM z Application Assist Processor (zAAP). See full name.

zIIP

Approved acronym for IBM z Integrated Information (zIIP). See full name.

Index

A

- access
 - restricting [134](#)
- accessibility
 - contact IBM [229](#)
- accounting information
 - nesting [65](#)
 - qualifier [65](#)
- action field [170](#)
- active service policy
 - definition [235](#)
- adjusting velocity goals [54](#)
- administer WLM
 - with z/OS Management Facility [213](#)
- administration application
 - definition [238](#)
- alias management, dynamic [96](#)
- APPC/MVS scheduler (ASCH) [64](#)
- application
 - action field [170](#)
 - classification groups [190](#)
 - command line [170](#)
 - commands [170](#)
 - create a group panel [190](#)
 - create workload panel [177](#)
 - customizing keylists [223](#)
 - definition menu [172](#)
 - function keys [170](#)
 - scrollable area [169](#)
 - starting [219](#), [222](#)
 - using the menu bar [168](#)
 - workload selection list [177](#)
 - workloads [177](#)
- application environment
 - definition [235](#)
- application environments
 - authorizing [121](#)
 - CB (WebSphere Application Server) [113](#)
 - changing the definition of [120](#)
 - DB2 [113](#)
 - defining [113](#)
 - getting started with [113](#)
 - handling error conditions in [121](#)
 - IWEB [113](#)
 - making changes to servers [120](#)
 - managing [119](#)
 - overview [11](#)
 - selecting server limits for [116](#)
 - SOM [113](#)
 - specifying to workload management [114](#)
 - using operator commands for [119](#)
- application owning region
 - definition [235](#)
- ASCH (APPC/MVS scheduler)
 - overview of work [59](#)

- ASCH (APPC/MVS scheduler) (*continued*)
 - work qualifiers supported by [64](#)
- assistive technologies [229](#)
- automatic control
 - definition [235](#)
- average response time
 - limit [47](#)
 - limits [47](#)

B

- balancing of WLM managed batch initiators [17](#), [144](#)
- batch initiator balancing [17](#), [144](#)
- batch initiator management [145](#)
- batch initiators [18](#)
- business importance
 - definition [7](#)

C

- capacity definition [25](#)
- capacity, minimum and maximum [37](#), [45](#)
- CB
 - overview of work [59](#)
- CB (WebSphere Application Server)
 - application environments [113](#)
 - work qualifiers supported by [64](#)
- changing goal types in performance periods [56](#)
- channel subsystem priority queuing [154](#)
- CHPID
 - definition [235](#)
- CICS (customer information control system)
 - overview of work [59](#)
 - work qualifiers supported by [64](#)
- CICSplex
 - definition [235](#)
- classification
 - defining rules [57](#)
 - defining the order [78](#)
 - inheritance [78](#)
 - nesting [59](#), [65](#)
 - qualifiers supported [62](#)
 - supporting subsystems [59](#)
- classification rules
 - creating for a subsystem type [184](#)
 - definition [235](#)
- client accounting information
 - qualifier [65](#)
- client IP address
 - qualifier [66](#)
- client transaction name
 - qualifier [66](#)
- client user ID
 - qualifier [66](#)
- client workstation name
 - qualifier [66](#)
- collection name

- collection name (*continued*)
 - qualifier [66](#)
- compatibility mode
 - definition [235](#)
- connection type
 - qualifier [67](#)
- contact
 - z/OS [229](#)
- control region
 - definition [235](#)
- correlation information
 - qualifier [67](#)
- couple data set
 - allocating [138](#)
 - calculating the size of [138](#)
 - definition [235](#)
 - increasing the size of [140](#)
 - installing service definition [202](#)
 - restricting access to [134](#)
 - SECTXCF command [140](#)
 - updating COUPLExx [140](#)
- COUPLExx member
 - DATA keyword [141](#)
- coupling facility
 - defining a structure [147](#), [151](#)
- CPSM environment [18](#)
- CPU protection [48](#), [100](#)
- CPU service units
 - definition [235](#), [239](#)
- customer information control system (CICS) [64](#)

D

- Db2
 - work qualifiers supported by [64](#)
- DB2
 - application environments [113](#)
 - overview of work [59](#)
- DB2 distributed data facility environment [18](#)
- DDF (distributed data facility)
 - overview of work [59](#)
 - work qualifiers supported by [64](#)
- DDF environment [18](#)
- defining application environments [113](#)
- defining capacity [25](#)
- defining scheduling environments [123](#)
- defining velocity goals [53](#)
- discretionary goal [48](#)
- discretionary goal management
 - migration considerations [143](#)
- discretionary goals
 - using [54](#)
- dispatch mode [20](#)
- distributed data facility (DDF) [64](#)
- duration
 - definition [48](#)
 - in a performance period [48](#)
- dynamic alias management
 - definition [235](#)
 - migration considerations [143](#)
- dynamic channel path management
 - coupling facility structure [151](#)

E

- enclave
 - definition [236](#)
- Enterprise Storage Server [96](#)
- execution velocity
 - calculation [95](#)
 - definition [236](#)
 - with I/O priority management [95](#)

F

- feedback [xvii](#)
- fold qualifier names
 - definition [236](#)
 - option explained [184](#)
- functionality level [136](#)

G

- goal
 - definition [47](#)
- goal mode
 - definition [236](#)
- goal types [16](#)
- goals, performance
 - defining [51](#)
- group capacity [26](#)

H

- Hardware Management Console (HMC)
 - definition [236](#)
- heterogeneous report class [93](#)
- heterogeneous tenant report class [91](#)
- HiperDispatch mode [20](#)
- HMC
 - definition [236](#)
- homogeneous report class [93](#)
- homogeneous tenant report class [91](#)
- honor priority [101](#)
- Honor Priority [48](#)
- hypervisor
 - definition [236](#)

I

- I/O priority
 - enabling [95](#)
 - management [95](#)
- I/O Priority Group [48](#)
- I/O priority management
 - definition [236](#)
- I/O priority queueing
 - defining [29](#)
 - dynamic [29](#)
- I/O service units
 - definition [236](#)
- I/O storage management [22](#)
- IBM MQ Workflow (MQ) [64](#)
- IBM z Integrated Information Processor (zIIP) [161](#)
- importance

- importance (*continued*)
 - definition [236](#)
- importance levels
 - in performance periods [56](#)
- IMS (information management system)
 - overview of work [59](#)
 - work qualifiers supported by [64](#)
- information management system (IMS) [64](#)
- inheritance
 - in classification rules [78](#)
- initiators, batch [18](#)
- Install Definition Utility
 - member IWMINSTL [132](#)
 - member IWMSSDEF [132](#)
- installation exit
 - IWMAREX1 [218](#)
 - IWMAREX2 [219](#)
- installed service definition
 - definition [237](#)
- intelligent resource director
 - channel subsystem priority queuing [154](#)
 - coupling facility structure [151](#)
 - dynamic channel path management [153](#)
 - LPAR CPU Management [153](#)
 - making it work [156](#)
- intranode management network (INMN)
 - definition [236](#)
- IO protection [100](#)
- IRD
 - coupling facility structure [151](#)
- IWEB
 - application environments [113](#)
 - overview of work [59](#)
 - work qualifiers supported by [64](#)
- IWMAM040 message [206](#)
- IWMAM041 message [206](#)
- IWMAM042 message [207](#)
- IWMAM043 message [207](#)
- IWMAM044 message [207](#)
- IWMAM046 message [207](#)
- IWMAM047 message [208](#)
- IWMAM050 message [208](#)
- IWMAM051 message [208](#)
- IWMAM052 message [208](#)
- IWMAM054 message [209](#)
- IWMAM055 message [209](#)
- IWMAM058 message [209](#)
- IWMAM065 message [209](#)
- IWMAM072 message [209](#)
- IWMAM077 message [210](#)
- IWMAM098 message [210](#)
- IWMAM099 message [210](#)
- IWMAM313 message [210](#)
- IWMAM512 message [211](#)
- IWMAM540 message [211](#)
- IWMAREX1 installation exit [218](#)
- IWMAREX2 installation exit [219](#)
- IWMINSTL [132](#)
- IWMINSTL, return codes [227](#)
- IWMSSDEF [132](#)

J

- JES (job entry subsystem)

- JES (job entry subsystem) (*continued*)
 - overview of work [59](#)
 - work qualifiers supported by [64](#)
- JES2 (job entry subsystem 2)
 - overview of work [59](#)
 - work qualifiers supported by [64](#)
- JES2 batch initiators [18](#)
- JES3 (job entry subsystem 3)
 - overview of work [59](#)
 - work qualifiers supported by [64](#)
- JES3 batch initiators [18](#)
- job entry subsystem (JES) [64](#)

K

- keyboard
 - navigation [229](#)
 - PF keys [229](#)
 - shortcut keys [229](#)

L

- LDAP
 - work qualifiers supported by [64](#)
- LPAR clustering
 - coupling facility structure [151](#)
- LPAR CPU management [153](#)
- LPAR weight management [153](#)
- LSFM
 - overview of work [59](#)
 - work qualifiers supported by [64](#)
- LU 6.2 session
 - definition [237](#)
- LU name
 - definition [237](#)
 - qualifier [67](#)

M

- managing batch initiators [145](#)
- managing resource states [125](#)
- manual control
 - definition [237](#)
- masking
 - definition [237](#)
- masking notation
 - examples [83](#)
- maximum capacity [37](#), [45](#)
- memory
 - limit [37](#), [45](#)
- memory limit [37](#), [45](#)
- menu bar
 - definition menu [174](#)
 - on selection list [169](#)
- middleware recycle, recovery process boost for [77](#)
- migration
 - creating service definition for the first time [131](#)
 - discretionary goal management considerations [143](#)
 - dynamic alias management considerations [143](#)
 - from pre-version 5 [131](#)
 - multisystem enclaves considerations [143](#)
 - overview [131](#)
 - velocity considerations [142](#)

- migration (*continued*)
 - with an existing service definition [133](#)
- minimum capacity [37, 45](#)
- mixed-release sysplex [136](#)
- mode
 - definition [239](#)
- modifications of
 - transaction server management [102](#)
- MQ (IBM MQ Workflow)
 - overview of work [59](#)
 - work qualifiers supported by [64](#)
- multiple periods [16](#)
- multisystem enclaves
 - coupling facility structure [147](#)
 - migration considerations [143](#)

N

- navigation
 - keyboard [229](#)
- nesting
 - accounting information [79](#)
 - subsystem parameter [79](#)
- netid
 - qualifier [67](#)
- NETV
 - work qualifiers supported by [64](#)
- non z/OS partition CPU management [23](#)
- notation
 - start position [84](#)
- notepad
 - updating [29](#)
 - using [29](#)

O

- OMVS (z/OS UNIX System Services)
 - overview of work [59](#)
 - work qualifiers supported by [64](#)

P

- package name
 - qualifier [67](#)
- parallel access volume [96](#)
- partitioned data set
 - restricting access to [134](#)
- PERFORM
 - qualifier [68](#)
- performance administration
 - definition [4](#)
- performance goal
 - definition [47](#)
- performance goals
 - defining [51](#)
 - definition [7](#)
 - discretionary [7](#)
 - execution velocity [7](#)
 - response-time [7](#)
- performance group
 - qualifier [68](#)
- performance management

- performance management (*continued*)
 - definition [5](#)
- performance period
 - definition [237](#)
 - maximum number [48](#)
- performance periods
 - using [55](#)
 - using importance levels in [56](#)
- periods, multiple [16](#)
- plan name
 - qualifier [68](#)
- policy overrides
 - defining [32, 181](#)
 - examples [32](#)
 - resource group association [32](#)
 - resource group capacity [32](#)
- printing
 - service definition [205](#)
 - service policy [205](#)
- priority
 - qualifier [68](#)
- procedure name
 - qualifier [69](#)
- process name
 - qualifier [69](#)
- processor model
 - service units [225](#)
 - task/SRB execution time [225](#)
- protection
 - CPU [100](#)
 - IO [100](#)
 - storage [99](#)
- protection options for critical work
 - defining [99](#)

Q

- qualifier
 - accounting information [65](#)
 - client accounting information [65](#)
 - client IP address [66](#)
 - client transaction name [66](#)
 - client user ID [66](#)
 - client workstation name [66](#)
 - collection name [66](#)
 - connection type [67](#)
 - correlation information [67](#)
 - grouping [86](#)
 - LU name [67](#)
 - nesting [79](#)
 - netid [67](#)
 - package name [67](#)
 - PERFORM [68](#)
 - performance group [68](#)
 - plan name [68](#)
 - priority [68](#)
 - procedure name [69](#)
 - process name [69](#)
 - scheduling environment name [69](#)
 - subsystem collection name [69](#)
 - subsystem instance [69](#)
 - subsystem parameter [70](#)
 - sysplex name [71](#)

- qualifier (*continued*)
 - system name [71](#)
 - transaction class [72](#)
 - transaction name [72](#)
 - user ID [74](#)
 - zEnterprise service class from a Unified Resource Manager performance policy [75](#)

- qualifier names
 - folding [184](#), [236](#)

- qualifiers
 - definition [57](#)

R

- RACF
 - restricting access to WLM service definition [134](#)

- recovery process boost, middleware recycle [77](#)

- report class
 - assigning [93](#)
 - definition [93](#), [237](#)
 - heterogeneous [93](#)
 - inhomogeneous [93](#)

- resource
 - definition [237](#)

- resource group
 - defining [37](#)
 - definition [238](#)
 - limitations [37](#)
 - maximum capacity [37](#)
 - minimum capacity [37](#)
 - overview [9](#)
 - removing a service class from [182](#)

- resource requirements
 - definition [7](#)

- resource states, managing [125](#)

- response time goals, system
 - determining [51](#)

- response time with percentile
 - limit [47](#)

- restricting access to WLM service definition [134](#)

- return codes
 - sample job IWMINSTL [227](#)

S

- SAF
 - restricting access to WLM service definition [134](#)

- samples included in velocity goals [54](#)

- scheduling environment
 - definition [238](#)

- scheduling environment name
 - qualifier [69](#)

- scheduling environments
 - associating with incoming work [128](#)
 - defining [123](#)
 - getting started with [123](#)
 - managing resource states [125](#)
 - overview [12](#)
 - specifying to workload management [123](#)
 - using special characters [123](#)

- security server
 - restricting access to WLM service definition [134](#)

- selection lists

- selection lists (*continued*)
 - in classification rules [190](#)
 - status line [169](#)

- sending to IBM
 - reader comments [xvii](#)

- server management, transaction [102](#)

- service class
 - definition [47](#), [238](#)
 - maximum number [47](#)
 - SYSOTHER [82](#)
 - SYSSTC [81](#)
 - SYSSTC1-SYSSTC5 [82](#)
 - SYSTEM [80](#)
 - system-provided [80](#)

- service definition
 - base [13](#)
 - contents [29](#)
 - creating for the first time [131](#)
 - defining [29](#)
 - definition [6](#), [238](#)
 - hierarchy [13](#)
 - installing [132](#), [202](#)
 - printing [205](#)
 - printing as GML [205](#)
 - restricting access to [134](#)
 - storing in MVS PDS [167](#)
 - storing in WLM couple data set [167](#)

- service level agreement (SLA)
 - definition [238](#)

- service policy
 - activating [205](#)
 - create service policy panel [176](#)
 - defining [6](#), [31](#)
 - defining overrides [181](#)
 - definition [238](#)
 - in service definition [31](#)
 - overview [13](#)
 - printing [205](#)

- service unit
 - definition [238](#)
 - processor model [225](#)
 - task/SRB execution time [225](#)

- SETXCF command
 - example [141](#)

- shark [96](#)

- shortcut keys [229](#)

- SOM
 - application environments [113](#)
 - overview of work [59](#)
 - work qualifiers supported by [64](#)

- source LU
 - definition [238](#)

- SRB (service request block)
 - execution time
 - processor model [225](#)
 - service units [225](#)

- SRB service units
 - definition [238](#)

- start position
 - using [84](#)

- started task control (STC) [64](#)

- started tasks

- started tasks (*continued*)
 - defining goals for [54](#)
 - servers [54](#)
- started tasks (STC)
 - defining classification rules [88](#)
 - defining service classes [88](#)
- STC (started task control)
 - overview of work [59](#)
 - work qualifiers supported by [64](#)
- STC (started tasks)
 - defining classification rules [88](#)
 - defining service classes [88](#)
- storage management
 - I/O [22](#)
- storage protection [99](#)
- storage service units
 - definition [238](#)
- substring notation
 - examples [84–86](#)
- subsystem collection name
 - qualifier [69](#)
- subsystem instance
 - definition [238](#)
 - qualifier [69](#)
- subsystem parameter
 - qualifier [70](#)
- subsystem type
 - creating [190](#)
 - deleting [190](#)
 - modify rules for [184](#)
- subsystem types
 - in classification [62](#)
- summary of changes
 - z/OS V2R3 [xxi](#)
 - z/OS V2R4 [xx](#)
- SYS_ [124](#)
- SYS1.PARMLIB
 - member IEAOPT [21](#)
- SYS1.SAMPLIB
 - member IWMINSTL [132](#)
 - member IWMSSDEF [132](#)
- SYSH
 - overview of work [59](#)
 - work qualifiers supported by [64](#)
- SYSOTHER
 - service class [82](#)
- sysplex couple data set
 - upgrading [132](#)
- sysplex name
 - qualifier [71](#)
- SYSSTC
 - service class [81](#)
- SYSSTC1-SYSSTC5
 - service class [82](#)
- SYSTEM
 - service class [80](#)
- system name
 - qualifier [71](#)
- System Recovery Boost [165](#)
- system response time goals
 - determining [51](#)
- System z Integrated Information Processor (zIIP) [161](#)

T

- task
 - processor model [225](#)
- TCP
 - work qualifiers supported by [64](#)
- tenant report class
 - assigning [91](#)
 - definition [91](#)
 - heterogeneous [91](#)
 - inhomogeneous [91](#)
- tenant resource group
 - defining [45](#)
 - limitations [45](#)
 - maximum capacity [45](#)
 - minimum capacity [45](#)
- terminal owning region (TOR)
 - definition [239](#)
- transaction class
 - qualifier [72](#)
- transaction name
 - qualifier [72](#)
- transaction server management, modifications of [102](#)
- TSO
 - overview of work [59](#)
 - work qualifiers supported by [64](#)

U

- Unified Resource Manager
 - definition [239](#)
- Unified Resource Manager performance policy, service
 - class
 - qualifier [75](#)
- user ID
 - qualifier [74](#)
- user interface
 - ISPF [229](#)
 - TSO/E [229](#)
- using
 - group capacity [26](#)
 - z/OS Management Facility [213](#)

V

- velocity
 - definition [239](#)
 - formula [50](#)
 - limit [47](#)
 - migration considerations [142](#)
- velocity goals
 - adjusting [54](#)
 - defining [53](#)
 - samples included in [54](#)

W

- WebSphere Application Server (CB) [64](#)
- wild carding
 - definition [239](#)
- wildcard notation
 - examples [83](#)

- WLM couple data set
 - allocating [138](#)
 - calculating the size of [138](#)
 - definition [239](#)
 - increasing the size of [140](#)
 - installing service definition [202](#)
 - restricting access to [134](#)
 - SEXTXCF command [140](#)
 - updating COUPLExx [140](#)
- work environments [15](#)
- work qualifier
 - definition [239](#)
- work request
 - definition [239](#)
- workload
 - definition [239](#)
 - in service definition [35](#)
- workload balancing
 - definition [5](#)
- Workload Management task
 - overview [213](#)

Z

- z/OS Management Facility [213](#)
- z/OS UNIX System Services (OMVS) [64](#)
- zAAP
 - definition [236](#)
- zIIP
 - definition [236](#)
- zIIP (IBM z Integrated Information Processor) [161](#)



Product Number: 5650-ZOS

SC34-2662-50

