

GREENGAUGE MATRIX PROTECTOR

How to Apply:

- Use the Greengauge Hose on Applicator provided with the black Fishmouth nozzle
- Set the hose on applicator dial to one of following settings
 - 'B' for standard application
 - 'C' for treating areas of high mould build up
- Hose over the playing surface in a slow sweeping manner

Directions & Safety:

- Best applied in the afternoon with 12 hrs of dry weather post application
- Best applied in low wind conditions
- Avoid skin contact, use disposable gloves and wear a P1 face mask
- Mains water pressure required (>4 bar)

How much to Apply:

- When using the standard 'B' setting on the applicator; each fill of the Hose on Applicator reservoir (2.3 Litres) is enough to do a half green
- For a full size green you will require 2 fills of the Hose on Applicator

Green size	Amount of Matrix fluid to cover green	Number of fills of Hose on Applicator reservoir	Yearly applications required	
			Outdoor Green	Undercover Green
Less than 22 m	2.3 L	1	4 times p.a.	1 times p.a.
Standard Green 37 m	4.6 L	2	4 times p.a.	2 times p.a.
Greater than 38 m	4.6 L	2	5 times p.a.	2 times p.a.

How to care for the Hose on Applicator:

- After use decant any left-over Matrix back into the 4.6 L jerrycan
- Allow water to flush thru the hose on applicator before storage



For any further information contact Ben at Greengauge on 0418 327 995



Fill up the Hose on Applicator Reservoir to the top with Greengauge Matrix Protector

1



Use the fish mouth nozzle supplied
Select 'B' for correct standard mixture ratio

-OR-

Select 'C' for stubborn areas

2



Assembled Hose on Applicator ready for use

3

A note on mould appearance:

- Black mould / Green moss – is actively growing new mould
- Orange / Brown mould – dying / dead mould appearance approx. 7 – 10 days after treatment
- Good housekeeping - make sure that you treat carpet edges and ditch grass

For any further information contact Ben at Greengauge on 0418 327 995