

Import Intelligence + Wizard Specification

Status: Current implementation snapshot

Scope: Import intelligence pipeline and multi-stage wizard flow

Brief description

Defines how raw/structured text is interpreted into process-map semantics and how the user is guided through TOC seeding, detail ingestion, review, and confirmation in the import wizard.

Visual overview

```

```mermaid
flowchart LR
 A[Raw Input: TOC / Chapter / OCR] --> B[Preprocess & Classification]
 B --> C[Bounded Semantic Graph Build]
 C --> D[Cluster Assignment]
 D --> E[Layout Pass]
 E --> F[Import Map Review]

 W1[Wizard: Seed Clusters] --> W2[Wizard: Ingest Detail]
 W2 --> W3[Wizard: Review & Refine]
 W3 --> W4[Wizard: Confirm & Exit]
```

```

Scope boundaries

- Includes parser/classifier budgets, semantic graph shaping, and wizard stage transitions.
- Excludes rendering-only layout details (covered in layout spec).
- Excludes template catalog details (covered in templates spec).

Wizard stages

Defined in UI state:

- `toc\_seed`
- `detail\_ingest`
- `review`
- `confirmed`

Transition intent:

1. Seed clusters from TOC lines (`Cluster: ...`).
2. Ingest detailed chapter content into seeded context.
3. Review resulting graph/map and refine manually.
4. Confirm import and continue in flow editing.

Intelligence pipeline

1. Input normalization (OCR cleanup available).
2. Line classification (`process`, `decision`, `fact`, `policy`, `unclassified`).

3. Bounded graph construction with budgets.
4. Decision branch normalization (explicit Yes/No semantics with fallback branch support).
5. Cluster assignment from TOC seeds and stage metadata.
6. Layout pass (separate engine) for position/handle routing.

Constraints and budgets

Current bounded defaults include limits for:

- input lines
- process nodes
- annotation nodes
- total nodes
- total edges
- per-section children
- title and note lengths

These guardrails prevent node/edge explosion and preserve readability.

AI assist integration points

- External assist provider selector (`none`, `gemini`, `copilot`).
- Gemini proxy endpoint: `/api/gemini/assist`.
- Structured payload mode supports:
 - TOC seeding
 - detail step structuring
 - OCR cleanup

Evidence of separation of concerns

- Content allocation/semantics are built before layout.
- Layout pass does not rewrite semantic meaning (only positions and edge handles).
- Wizard stage and import parser states are explicitly tracked in UI state.