```
                      ⟨program⟩ → [⟨metas⟩] ⟨object⟩ EOF
                        ⟨metas⟩ → ⟨meta⟩ {EOL ⟨meta⟩} EOP
                      ⟨comment⟩ → ⟨commentary⟩ EOL
              ⟨commentoptional⟩ → {⟨comment⟩}
                       ⟨object⟩ → (⟨commentoptional⟩ ⟨masterbody⟩)
                                 | ⟨bound⟩
                        ⟨bound⟩ → ⟨commentoptional⟩ (⟨application⟩ | ((⟨method⟩ | ⟨just⟩) (⟨onameortname⟩ | ⟨aphi⟩) EOL))
                       ⟨tbound⟩ → ⟨commentoptional⟩ (⟨tapplication⟩ | ((⟨method⟩ | ⟨just⟩) ⟨tname⟩ EOL))
                   ⟨tsubmaster⟩ → ⟨commentoptional⟩ ⟨tmasterbody⟩
                    ⟨submaster⟩ → ⟨commentoptional⟩ ⟨masterbody⟩
                   ⟨masterbody⟩ → ⟨formation⟩ | ⟨atom⟩ | (⟨hanonym⟩ ⟨onameortname⟩ EOL)
                  ⟨tmasterbody⟩ → ⟨tformation⟩ | ⟨atom⟩ | (⟨hanonym⟩ ⟨tname⟩ EOL)
                         ⟨just⟩ → ⟨beginner⟩ | ⟨finisher⟩
                         ⟨atom⟩ → ⟨voids⟩ ⟨suffix⟩ "␣" "?" ⟨testsoreol⟩
                    ⟨formation⟩ → ⟨voids⟩ ⟨onameortname⟩ ⟨innersoreol⟩
                   ⟨tformation⟩ → ⟨voids⟩ ⟨tname⟩ ⟨innersoreol⟩
                   ⟨testsoreol⟩ → ⟨tests⟩ | EOL
                  ⟨innersoreol⟩ → ⟨inners⟩ | EOL
                       ⟨inners⟩ → EOL TAB (⟨bound⟩ | ⟨submaster⟩) {(⟨bound⟩ | ([EOL] ⟨submaster⟩) )} UNTAB
                        ⟨tests⟩ → EOL TAB (⟨tbound⟩ | ⟨tsubmaster⟩) {(⟨tbound⟩ | ([EOL] ⟨tsubmaster⟩) )} UNTAB
                        ⟨voids⟩ → "[" [⟨void⟩ {"␣" ⟨void⟩}] "]"
                         ⟨void⟩ → ⟨name⟩ | "@"
                  ⟨application⟩ → (⟨happlicationextended⟩ ⟨onameortname⟩ EOL)
                                 | ⟨vapplication⟩
                 ⟨tapplication⟩ → (⟨happlicationextended⟩ ⟨tname⟩ EOL)
                                 | ⟨tvapplication⟩
                 ⟨happlication⟩ → (⟨happlicationhead⟩ ⟨happlicationtail⟩)
                                 | ⟨happlicationreversed⟩
     ⟨happlicationreversedhead⟩ → ⟨reversed⟩ "␣" ⟨happlicationreversedfirst⟩
         ⟨happlicationextended⟩ → (⟨happlicationheadextended⟩ ⟨happlicationtail⟩)
                                 | ⟨happlicationreversed⟩
                     ⟨onlyaphi⟩ → ⟨happlicationheadextended⟩ ⟨happlicationtail⟩ ⟨aphi⟩
                         ⟨aphi⟩ → "␣" ">" ">" "␣" ⟨voids⟩
         ⟨happlicationreversed⟩ → ⟨happlicationreversedhead⟩ [⟨happlicationtail⟩]
             ⟨happlicationhead⟩ → ⟨hmethod⟩ | ⟨applicable⟩
     ⟨happlicationheadextended⟩ → ⟨vmethod⟩ | ⟨happlicationhead⟩
                   ⟨applicable⟩ → "*" | ⟨name⟩ | "@"
       ⟨happlicationargunbound⟩ → "␣" ⟨happlicationarg⟩
       ⟨happlicationtailscoped⟩ → {⟨happlicationargunbound⟩} "␣" ⟨happlicationargscoped⟩
             ⟨happlicationtail⟩ → {⟨happlicationargunbound⟩ ⟨as⟩}+ | {⟨happlicationargunbound⟩}+
    ⟨happlicationreversedfirst⟩ → ⟨happlicationarg⟩
              ⟨happlicationarg⟩ → ⟨just⟩ | ⟨hmethod⟩ | ⟨scope⟩
        ⟨happlicationargscoped⟩ → ⟨voids⟩ ⟨aname⟩ ⟨innersoreol⟩
                 ⟨vapplication⟩ → (⟨vapplicationhead⟩ ⟨onameortname⟩ ⟨vapplicationargs⟩) | (⟨reversed⟩ ⟨onameortname⟩ ⟨vapplicationargsreversed⟩)
                ⟨tvapplication⟩ → (⟨vapplicationhead⟩ ⟨tname⟩ ⟨vapplicationargs⟩) | (⟨reversed⟩ ⟨tname⟩ ⟨vapplicationargsreversed⟩)
             ⟨vapplicationhead⟩ → ⟨applicable⟩ | ⟨hmethod⟩ | ⟨vmethod⟩ | ⟨compactarray⟩
                 ⟨compactarray⟩ → ("$" | "QQ" | ⟨name⟩) {"." ⟨name⟩} "␣" "*" [⟨int⟩]
             ⟨vapplicationargs⟩ → EOL TAB ⟨vapplicationargsspecific⟩ UNTAB
     ⟨vapplicationargsreversed⟩ → EOL TAB ⟨vapplicationargunbound⟩ [⟨vapplicationargsspecific⟩] UNTAB
     ⟨vapplicationargsspecific⟩ → {⟨vapplicationargbound⟩}+ | {⟨vapplicationargunbound⟩}+
         ⟨vapplicationargbound⟩ → (⟨vapplicationargboundcurrent⟩ EOL)
                                 | ⟨vapplicationargboundnext⟩
  ⟨vapplicationargboundcurrent⟩ → (( "(" ⟨happlicationextended⟩ ")") | ⟨just⟩ | ⟨method⟩ ⟨as⟩ [⟨oname⟩]} | (⟨commentoptional⟩ "(" ⟨hanonym⟩ ")" ⟨as⟩ [⟨fname⟩])
     ⟨vapplicationargboundnext⟩ → (⟨commentoptional⟩ ⟨voids⟩ ⟨as⟩ [⟨fname⟩] ⟨innersoreol⟩) | (⟨vapplicationhead⟩ ⟨as⟩ [⟨oname⟩] ⟨vapplicationargs⟩) | (⟨reversed⟩ ⟨as⟩ [⟨oname⟩] ⟨vapplicationargsreversed⟩)
       ⟨vapplicationargunbound⟩ → (⟨onlyaphi⟩ | (⟨vapplicationargunboundcurrent⟩ [⟨aphi⟩]) EOL)
                                 | ⟨vapplicationargunboundnext⟩
⟨vapplicationargunboundcurrent⟩ → (⟨happlicationextended⟩ | ⟨just⟩ | ⟨method⟩ [⟨oname⟩]) | (⟨commentoptional⟩ ⟨hanonym⟩ [⟨fname⟩])
   ⟨vapplicationargunboundnext⟩ → ⟨formationnamed⟩ | (⟨vapplicationhead⟩ [⟨oname⟩ | ⟨aphi⟩] ⟨vapplicationargs⟩) | (⟨reversed⟩ [⟨oname⟩] ⟨vapplicationargsreversed⟩) | (⟨happlicationhead⟩ | ⟨happlicationreversedhead⟩ ⟨happlicationtailscoped⟩)
               ⟨formationnamed⟩ → ⟨commentoptional⟩ ⟨voids⟩ [⟨fname⟩] ⟨innersoreol⟩
                   ⟨hformation⟩ → ⟨voids⟩ {⟨hanonyminner⟩}+
                      ⟨hanonym⟩ → ⟨hformation⟩ | (⟨hmethod⟩ | ⟨happlication⟩ | ⟨hformation⟩ | ⟨just⟩ {⟨onlyphitail⟩}+)
                  ⟨onlyphitail⟩ → ⟨arrow⟩ ⟨voids⟩
                 ⟨hanonyminner⟩ → "␣" "(" (⟨hmethod⟩ | ⟨happlication⟩ | ⟨hanonym⟩ | ⟨just⟩) ⟨oname⟩ ")"
                       ⟨method⟩ → ⟨hmethod⟩ | ⟨vmethod⟩
                      ⟨hmethod⟩ → (⟨just⟩ | ⟨scope⟩) {⟨methodtail⟩}+
                      ⟨vmethod⟩ → (⟨vmethodheadvapplication⟩ | (( ⟨just⟩ | ⟨hanonym⟩) [⟨oname⟩] EOL) | ⟨formationnamed⟩} ⟨methodtail⟩ {⟨vmethodheadapplicationtail⟩ ⟨methodtail⟩}
   ⟨vmethodheadapplicationtail⟩ → ([⟨oname⟩] ⟨vapplicationargs⟩ | EOL) | (⟨happlicationtail⟩ [⟨oname⟩] EOL)
      ⟨vmethodheadvapplication⟩ → (⟨applicable⟩ | ⟨hmethod⟩ [⟨oname⟩] ⟨vapplicationargs⟩) | (⟨reversed⟩ [⟨oname⟩] ⟨vapplicationargsreversed⟩)
                   ⟨methodtail⟩ → "." (⟨finisher⟩ | (" " ⟨int⟩))
                     ⟨beginner⟩ → "*" | "Q" | "QQ" | "$" | ⟨data⟩
                     ⟨finisher⟩ → ⟨name⟩ | "@" | "^"
                     ⟨reversed⟩ → (⟨finisher⟩ | (" " ⟨int⟩)) "."
                        ⟨aname⟩ → ">" ">" ["!"]
                        ⟨fname⟩ → ⟨oname⟩ | ("␣" ⟨aname⟩)
                 ⟨onameortname⟩ → ⟨oname⟩ | ⟨tname⟩
                        ⟨oname⟩ → ⟨suffix⟩ ["!"]
                        ⟨tname⟩ → ⟨tarrow⟩ ("@" | ⟨name⟩)
                       ⟨tarrow⟩ → "␣" "+" ">" "␣"
                       ⟨suffix⟩ → ⟨arrow⟩ ("@" | ⟨name⟩) ["'"]
                        ⟨arrow⟩ → "␣" ">" "␣"
                        ⟨scope⟩ → "(" (⟨happlication⟩ | ⟨hanonym⟩) ")"
                           ⟨as⟩ → ":" (⟨name⟩ | ⟨int⟩)
                         ⟨data⟩ → ⟨bytes⟩ | ⟨text⟩ | ⟨string⟩ | ⟨int⟩ | ⟨float⟩ | ⟨hex⟩
                   ⟨commentary⟩ → "#" [{[^\r\n]} [^␣\r\n\t]]
                         ⟨meta⟩ → "+" ⟨name⟩ {"␣" {[^␣\t\r\n]}}+
                       ⟨indent⟩ → "␣" "␣"
                    ⟨linebreak⟩ → ["\r"] "\n"
                         ⟨byte⟩ → [0-9A-F] [0-9A-F]
                  ⟨empty_bytes⟩ → "-" "-"
                   ⟨line_bytes⟩ → ⟨byte⟩ {"-" ⟨byte⟩}+
                        ⟨bytes⟩ → ⟨empty_bytes⟩ | (⟨byte⟩ "-") | (⟨line_bytes⟩ {"-" EOL ⟨line_bytes⟩})
              ⟨escape_sequence⟩ → "\{}" ([btnfr"'\{}] | ([[0-3]] [0-7]] [0-7]) | ({"u"}+ ⟨byte⟩ ⟨byte⟩))
                       ⟨string⟩ → DQ {([^"\{}\r\n] | ⟨escape_sequence⟩)} DQ
                          ⟨int⟩ → [("+" | "-")] ("0" | (["0"] [1-9] {[0-9]}))
                     ⟨exponent⟩ → ("e" | "E") [("+" | "-")] {[0-9]}+
                        ⟨float⟩ → [("+" | "-")] {[0-9]}+ "." {[0-9]}+ [⟨exponent⟩]
                          ⟨hex⟩ → "0x" {[0-9a-fA-F]}+
                         ⟨name⟩ → [a-z] {[^␣,.|':;!?][]{}()(\r\n\t\xF335]}
                         ⟨text⟩ → DQ DQ DQ ["\r"] "\n" {([^\{}] | ⟨escape_sequence⟩)} DQ DQ DQ
```