ShrinkageTrees: An R Package for Bayesian Tree Ensembles for Survival Analysis and Causal Inference

by Tijn Jacobs, Stéphanie van der Pas, and Wessel van Wieringen

Abstract ShrinkageTrees is an R package for fitting Bayesian tree ensemble models with flexible regularisation mechanisms for survival analysis and causal inference. The package provides unified implementations of BART, DART, and the τ-learner (Bayesian Causal Forests) for right-censored and interval-censored survival outcomes via accelerated failure time (AFT) formulations. Multiple regularisation strategies can be combined within a single model: structural sparsity through tree depth priors and Dirichlet splitting priors (DART), and parametric shrinkage on the leaf step heights through global–local scale mixture priors. A key contribution is the implementation of Horseshoe Forests, which place a horseshoe prior directly on the step heights, enabling adaptive shrinkage that aggressively regularises uninformative leaves while preserving strong signals — a strategy particularly suited to high-dimensional settings. An efficient Rcpp backend and coherent S3 interface support reproducible workflows for both prediction and causal effect estimation.

1 Introduction

Survival analysis in high-dimensional settings poses three interrelated challenges. First, the relationship between covariates and the time-to-event outcome is often complex and unknown, calling for flexible non-parametric models. Second, the outcome may be observed imprecisely: right-censored when a patient is lost to follow-up, or interval-censored when the event is known only to have occurred between two assessment times. Third, when a treatment is involved, its effect may vary across patient subgroups — and disentangling this heterogeneous treatment effect from prognostic factors requires dedicated methodology. These challenges arise routinely in clinical trials, observational studies, and genomics, often simultaneously.

Bayesian Additive Regression Trees [BART; Chipman et al. (2010)] offer a natural starting point. BART models the response as a sum of many shallow decision trees, each contributing a small piece of the overall prediction. Because each tree is simple but the ensemble is flexible, BART captures non-linearities and interactions automatically, without the analyst specifying a parametric form. A Bayesian prior regularises each tree, preventing overfitting.

However, existing BART implementations leave gaps in each of the three areas above. No R package provides Bayesian tree ensembles for interval-censored survival outcomes. No package implements the τ-learner — a dedicated causal forest architecture that separates the prognostic function from the treatment effect (Hahn et al., 2020; Caron et al., 2022) — for time-to-event endpoints. And standard BART's regularisation, while effective in moderate dimensions, does not adapt well to the truly high-dimensional settings ($p \gg n$) common in genomics: it treats every tree contribution equally, whether it carries a genuine signal or merely fits noise.

ShrinkageTrees addresses all three. The package provides a unified framework for fitting Bayesian tree ensembles to right-censored and interval-censored survival data via accelerated failure time (AFT) models, with optional τ-learner decomposition for causal inference. To handle high-dimensional settings, it implements multiple regularisation strategies that can be combined within a single model. *Structural sparsity* encourages the ensemble to split on a subset of relevant variables, following the Dirichlet splitting approach of DART (Linero, 2018). *Parametric shrinkage* targets the leaf parameters directly, silencing the contributions of uninformative trees while preserving strong signals. A key contribution is the implementation of Horseshoe Forests (Jacobs et al., 2025), which place a horseshoe prior (Carvalho et al., 2010) on the tree leaf parameters — a strategy particularly suited to sparse, high-dimensional problems.

The package is implemented with an efficient C++ backend via **Rcpp** (Eddelbuettel and François, 2011) and provides a coherent S3 interface with `print`, `summary`, `predict`, and `plot` methods. The paper is aimed at both practitioners encountering Bayesian tree ensembles for the first time and experienced users seeking functionality not available in existing packages. To give a first impression, a Horseshoe Forest for right-censored survival data can be fitted in a single call:

```
library(ShrinkageTrees)
data("ovarian")
fit <- HorseTrees(y = time, status = status, X_train = X,
```

```
                  outcome_type = "right-censored", number_of_trees = 200)
# see Section 2 for full data preparation
```

The remainder of this paper is organised as follows. Section 2 provides a first worked example — a survival prediction model on the ovarian cancer dataset — so that subsequent methodology is grounded in concrete code. Section 3 reviews the statistical methodology behind the models. Section 4 returns to the example and progressively adds horseshoe shrinkage, causal inference, and interval-censored outcomes. Section 5 describes the package architecture. Section 6 compares **ShrinkageTrees** with related R packages. Section 7 concludes.

2 A first example: survival prediction

We introduce the package through a complete worked example before discussing the underlying methodology. We use the `ovarian` dataset shipped with **ShrinkageTrees**, curated from The Cancer Genome Atlas ovarian cancer cohort [TCGA-OV; Cancer Genome Atlas Research Network (2011)]. The dataset contains overall survival times, a binary treatment indicator (carboplatin vs. cisplatin), clinical covariates, and expression levels of 2,000 genes selected by median absolute deviation. Ovarian cancer is one of the most lethal gynaecological malignancies, with a five-year survival rate below 50%. Gene expression patterns are known to be associated with survival duration and chemotherapy response (Cancer Genome Atlas Research Network, 2011). The dataset provides a challenging high-dimensional setting ($p \gg n$) that exercises the main features of the package.

```
library(ShrinkageTrees)
set.seed(42)
data("ovarian")

clin      <- ovarian$clinical
time      <- clin$OS_time / 30.44   # convert days to months
status    <- clin$OS_event
treatment <- clin$treatment

X <- cbind(age        = clin$age,
           figo_stage = clin$figo_stage,
           tumor_grade = clin$tumor_grade,
           ovarian$X)
```

The dataset comprises 357 patients with 2,000 gene expression features and three clinical covariates (age, FIGO stage, tumour grade). We hold out 20% of the patients for evaluating predictive accuracy.

```
train_idx <- sample(seq_len(nrow(clin)), size = floor(0.8 * nrow(clin)))
test_idx  <- setdiff(seq_len(nrow(clin)), train_idx)

X_train <- X[train_idx, ];  X_test <- X[test_idx, ]
time_train <- time[train_idx];  time_test <- time[test_idx]
status_train <- status[train_idx];  status_test <- status[test_idx]
```

We begin with the simplest model available in **ShrinkageTrees**: a standard BART survival model via `SurvivalBART()`. This uses an accelerated failure time (AFT) formulation with right-censoring and a conjugate normal prior on the leaf step heights — the classical BART specification of Chipman et al. (2010) applied to survival data.

```
fit_bart <- SurvivalBART(
  y               = time_train,
  status          = status_train,
  X_train         = X_train,
  X_test          = X_test,
  outcome_type    = "right-censored",
  timescale       = "time",
  number_of_trees = 200,
  N_post          = 5000,
  N_burn          = 5000,
  n_chains        = 4
)
```

The `print()` method provides a concise overview of the fitted model.

```
print(fit_bart)
```

TODO: Replace placeholder output with actual `SurvivalBART()` results.

```
ShrinkageTrees model
---------------------
Outcome type:         Right-censored (AFT, timescale = time)
Prior:                standard
Number of trees:      200
Training size (n):    285
Number of features:   2003
Chains:               4
Draws per chain:      5000 (burn-in 5000)
Acceptance ratio:     ..., ..., ..., ... (per chain)
Posterior mean sigma: ...
```

We evaluate predictive accuracy using the concordance index [C-index; Harrell et al. (1996)], where a value of 1 indicates perfect discrimination and 0.5 corresponds to random prediction.

```
library(survival)
c_train <- concordance(Surv(time_train, status_train) ~ fit_bart$train_predictions)
c_test  <- concordance(Surv(time_test, status_test) ~ fit_bart$test_predictions)
cat("Train C-index:", round(c_train$concordance, 3),
    " Test C-index:", round(c_test$concordance, 3), "\n")
```

TODO: Fill in actual C-index for `SurvivalBART()`.

The `plot()` method produces posterior survival curves. The population-averaged curve across all training observations can be overlaid with the Kaplan–Meier estimate for visual calibration:

```
plot(fit_bart, type = "survival", km = TRUE)
```

For individual patients, the `predict()` method generates posterior predictive survival curves with pointwise credible bands:

```
pred <- predict(fit_bart, newdata = X_test)
plot(pred, type = "survival", obs = 1)
```

This standard BART model serves as a baseline. In Section 4 we return to this dataset and show how horseshoe shrinkage and causal inference models can improve upon and extend this analysis. First, we review the statistical methodology that underpins these extensions.

3 Statistical methodology

Having seen **ShrinkageTrees** in action, we now formalise the models behind it. We build on three components. First, we review the BART model and the AFT formulation for survival outcomes — the model fitted by `SurvivalBART()` in Section 2. Second, we show how regularisation targets either the tree structures or the step heights — and how both strategies can be combined. Third, we extend the framework to causal inference via the τ-learner.

BART and the accelerated failure time model

BART (Chipman et al., 2010) models the response as a sum of m shallow decision trees:

$$Y_i = \sum_{j=1}^{m} g(\mathbf{x}_i; \mathcal{T}_j, \mathcal{H}_j) + \varepsilon_i, \quad \varepsilon_i \sim \mathcal{N}(0, \sigma^2).$$

Each tree j is characterised by two parameter groups. The *tree structure* $\mathcal{T}_j$ encodes the topology and the splitting rules: which variables to split on and at what thresholds. It determines how the covariate space is partitioned into disjoint regions. The *step heights* $\mathcal{H}_j = \{h_{j1}, \ldots, h_{jL_j}\}$ are the values assigned to



Figure 1: Schematic of a single regression tree. Interior nodes contain binary splitting rules of the form $x_\rho < c$; terminal nodes (leaves) contain step heights h_ℓ. An observation traverses the tree from root to leaf, and its prediction is the step height of the leaf it reaches.

the L_j leaves and determine each region's contribution to the fitted function. For input $\mathbf{x}$, the function $g(\mathbf{x}; \mathcal{T}_j, \mathcal{H}_j)$ returns the step height of the leaf that $\mathbf{x}$ reaches (see Figure 1). This distinction between $\mathcal{T}$ and $\mathcal{H}$ is central to the regularisation framework we develop below.

We specify independent priors on $\mathcal{T}_j$ and $\mathcal{H}_j$:

$$p(\mathcal{T}_j, \mathcal{H}_j) = p_{\mathcal{T}}(\mathcal{T}_j)\, p_{\mathcal{H}}(\mathcal{H}_j \mid \mathcal{T}_j) \quad \text{for } j = 1, \ldots, m.$$

The tree structure prior $p_{\mathcal{T}}$ is a branching process (Chipman et al., 1998; Ročková and Saha, 2020) in which a node at depth d splits with probability $\alpha\,(1+d)^{-\beta}$. At each internal node, the splitting variable is drawn uniformly from the available covariates and the split point uniformly from the observed range.

The step height prior $p_{\mathcal{H}}$ assigns independent Gaussian priors conditional on the tree structure:

$$h_{j\ell} \sim \mathcal{N}\left(0,\, \frac{1}{4\sqrt{m}}\right),$$

where the variance is scaled so that the prior places approximately 95% of its mass within the observed range of the response. This prior is conjugate, so the Gibbs sampler can update the step heights efficiently.

We model the error variance as $\sigma^2 \sim \text{Inv-}\chi^2(\nu,\, \psi)$, with $\nu = 3$ and ψ chosen so that the prior is centred around a rough estimate of σ^2 (Chipman et al., 2010).

For survival outcomes, we adopt an accelerated failure time (AFT) formulation. Let T_i denote the event time, C_i the censoring time, $Y_i = \min(T_i, C_i)$ the observed follow-up time, and $\delta_i \in \{0, 1\}$ the event indicator. The prediction model becomes

$$\log T_i = \sum_{j=1}^{m} g(\mathbf{x}_i;\, T_j, H_j) + \varepsilon_i, \quad \varepsilon_i \sim \mathcal{N}(0, \sigma^2).$$

Right-censored observations ($\delta_i = 0$) are handled by imputing $\log T_i$ from a truncated normal distribution within the Gibbs sampler. **ShrinkageTrees** also supports interval-censored outcomes, where the event time is known only to lie in an interval $(l_i, r_i]$; these are imputed analogously. This is the model behind the `SurvivalBART()` call in Section 2.

Regularisation

The parameters of a BART ensemble fall into two groups: tree structure parameters (nodes, splitting variables, split points) that determine how the covariate space is partitioned, and step heights that determine each partition's contribution to the fitted function. Regularisation can target either group.

Structural regularisation. Standard BART regularises the tree structure through the branching process prior of Chipman et al. (2010): each internal node at depth d splits with probability $\alpha(1+d)^{-\beta}$, where $\alpha \in (0, 1)$ and $\beta \geq 0$ discourage deep trees. Under the default values $\alpha = 0.95$ and $\beta = 2$, most trees remain shallow. DART (Linero, 2018) strengthens structural regularisation by replacing the uniform distribution over splitting variables with a Dirichlet prior on the splitting probabilities $\mathbf{s} = (s_1, \ldots, s_p)$. By concentrating the prior on sparse probability vectors, DART encourages the

ensemble to split on a subset of relevant variables, achieving structural variable selection.

Shrinkage on step heights. Rather than regularising the tree structure alone, we can place shrinkage priors directly on the leaf step heights. **ShrinkageTrees** adopts a scale mixture of normals representation,

$$h_\ell \mid \lambda_\ell, \tau, \omega \sim \mathcal{N}(0,\, \omega\, \lambda_\ell^2\, \tau^2),$$

where τ is a global shrinkage parameter shared across all leaves, λ_ℓ is a local scale specific to leaf ℓ, and ω is a fixed scaling constant. The global parameter τ controls the overall degree of regularisation, while the local parameters λ_ℓ allow individual leaves with strong signals to escape shrinkage.

The horseshoe prior (Carvalho et al., 2010) arises as a specific instantiation of this framework by placing independent half-Cauchy priors on both the local and global scales:

$$\lambda_\ell \sim \mathrm{C}^+(0, \alpha_\lambda), \qquad \tau \sim \mathrm{C}^+(0, \alpha_\tau),$$

where $\mathrm{C}^+(0, \alpha)$ denotes the half-Cauchy distribution with scale α. The half-Cauchy has its median at α and possesses heavy tails — its mean and variance do not exist — which allows the local scales to take very large values when the data support a strong effect (Polson and Scott, 2012). This combination aggressively shrinks the contributions of uninformative leaves towards zero while preserving large, data-supported signals. Following Jacobs et al. (2025), we set $\alpha_\tau = \alpha_\lambda = k/\sqrt{m}$. Smaller values of k yield stronger shrinkage. We recommend $k \in [0.05, 0.5]$ as a practical range; the default in **ShrinkageTrees** is $k = 0.1$. When domain knowledge does not suggest a specific value, k can be selected via cross-validation. Jacobs et al. (2025) provide a sensitivity analysis. The Dirichlet and horseshoe priors address complementary aspects of regularisation — structural sparsity and parametric shrinkage, respectively — and can be combined within a single model in **ShrinkageTrees**.

TODO: Add regularisation landscape figure — a 2D diagram mapping structural regularisation (x-axis: none → depth prior → Dirichlet/DART) against step height regularisation (y-axis: conjugate normal → horseshoe), with each cell annotated with the corresponding function name (`SurvivalBART`, `SurvivalDART`, `HorseTrees`, etc.).

The τ-learner for causal inference

BART has become a popular tool for causal inference (Hill, 2011; Dorie et al., 2019). The BART formulation above estimates a single function of the covariates — we refer to this as the *prediction model*. The prediction models can themselves be used for causal inference: including the treatment indicator as a covariate yields an S-learner, while fitting separate models per treatment arm yields a T-learner (Caron et al., 2022). However, the dedicated approach in **ShrinkageTrees** is the τ-learner, the decomposition proposed by Hahn et al. (2020) as Bayesian Causal Forests (BCF) and later termed the τ-learner by Caron et al. (2022). The **bcf** and **stochtree** packages implement the τ-learner for continuous outcomes; **ShrinkageTrees** extends it to survival endpoints. Given a binary treatment indicator $A_i \in \{0, 1\}$ and an estimate of the propensity score $\hat{e}(\mathbf{x}_i) = \hat{P}(A_i = 1 \mid \mathbf{x}_i)$, the *causal model* writes

$$y_i = \mu(\mathbf{x}_i, \hat{e}(\mathbf{x}_i)) + A_i\, \tau(\mathbf{x}_i) + \varepsilon_i,$$

where μ is a prognostic function modelled by a forest of m_μ trees and τ is a treatment effect function modelled by a separate forest of m_τ trees. This separation allows the prognostic and treatment effect components to have different regularisation and complexity. The conditional average treatment effect is $\mathrm{CATE}(\mathbf{x}) = \tau(\mathbf{x})$, and the average treatment effect is $\mathrm{ATE} = \mathbb{E}[\tau(\mathbf{X})]$.

More generally, the scalar multiplier on τ in the τ-learner need not equal the raw treatment indicator. Writing b_i for the coding applied to subject i, the model becomes $y_i = \mu(\mathbf{x}_i, \hat{e}(\mathbf{x}_i)) + b_i\, \tau(\mathbf{x}_i) + \varepsilon_i$. Hahn et al. (2020) discuss several choices. *Centered* coding sets $b_i = A_i - 1/2$, which is the original τ-learner parameterisation and the default in **ShrinkageTrees**. *Binary* coding uses $b_i = A_i$. *Adaptive* coding sets $b_i = A_i - \hat{e}(\mathbf{x}_i)$, incorporating the estimated propensity score directly into the treatment multiplier; this is the parameterisation adopted in the **bcf** package. Finally, the *invariant* (parameter-expanded) coding of Hahn et al. (2020, Section 5.2) assigns group-specific intercepts $b_0, b_1 \sim \mathcal{N}(0, 1/2)$ and writes $y_i = \mu(\mathbf{x}_i) + b_{A_i}\, \tilde{\tau}(\mathbf{x}_i) + \varepsilon_i$, where b_0 and b_1 are updated within the Gibbs sampler via conjugate normal updates and the treatment effect is recovered as $\tau(\mathbf{x}_i) = (b_1 - b_0)\, \tilde{\tau}(\mathbf{x}_i)$. This parameterisation is invariant to the labelling of treatment and control. All four options are available in **ShrinkageTrees** via the `treatment_coding` argument.

The τ-learner extends directly to the AFT setting by replacing y_i with $\log T_i$.

TODO: Add τ-learner decomposition figure — a diagram showing $y = \mu(\mathbf{x}, \hat{e}(\mathbf{x})) + b \cdot \tau(\mathbf{x}) + \varepsilon$ with two separate forests, annotated with which arguments/priors control each component, and which function names apply (`CausalHorseForest`, `CausalShrinkageForest`, `SurvivalBCF`).

Posterior computation

All models are fitted using Markov chain Monte Carlo (MCMC). The outer loop is a Gibbs sampler that cycles through updates of the tree topologies, the leaf step heights, the error variance σ^2, and — where applicable — the shrinkage parameters and censored event times. Trees are updated one at a time via Bayesian backfitting (Chipman et al., 2010): at each sweep, a partial residual is formed by subtracting the contributions of all other trees from the response, and tree j is then updated conditional on the current state of all other trees. The tree topology is modified through Metropolis–Hastings proposals that either grow a terminal node into an internal node with two new leaves, or prune an internal node back to a leaf.

Under the standard BART and Dirichlet (DART) priors, where the leaf parameters have a conjugate normal prior, the marginal likelihood of a proposed tree can be computed in closed form and the step heights are integrated out analytically. When global–local shrinkage priors such as the horseshoe are placed on the step heights, this conjugacy is lost: the local and global scale parameters λ_ℓ and τ must be sampled explicitly, and the tree proposals become reversible jump MCMC moves. The details of this reversible jump construction are given in Jacobs et al. (2025).

4 Building up the example

We return to the ovarian cancer dataset from Section 2 and progressively demonstrate more advanced features of **ShrinkageTrees**: horseshoe shrinkage for improved regularisation, causal inference for treatment effect estimation, and interval-censored survival modelling.

Adding horseshoe shrinkage

We now fit a Horseshoe Forest via `HorseTrees()` to the same data. The horseshoe prior applies global–local shrinkage to the leaf step heights, providing stronger regularisation than the conjugate normal prior used by `SurvivalBART()` — particularly beneficial in this high-dimensional setting where the number of predictors far exceeds the sample size.

```
fit_horse <- HorseTrees(
  y              = time_train,
  status         = status_train,
  X_train        = X_train,
  X_test         = X_test,
  outcome_type   = "right-censored",
  timescale      = "time",
  number_of_trees = 200,
  k              = 0.1,
  N_post         = 5000,
  N_burn         = 5000,
  n_chains       = 4
)
```

The `print()` and `summary()` methods provide a concise overview of the fitted model, including the outcome type, MCMC settings, acceptance ratio, and posterior summaries for σ.

```
print(fit_horse)

ShrinkageTrees model
---------------------
Outcome type:         Right-censored (AFT, timescale = time)
Prior:                horseshoe
Number of trees:      200
Training size (n):    285
Number of features:   2003
Chains:               4
Draws per chain:      5000 (burn-in 5000)
Acceptance ratio:     0.503, 0.504, 0.504, 0.504 (per chain)
Posterior mean sigma: 0.996

summary(fit_horse)
```



Figure 2: Left: traceplot of the posterior draws of σ for the Horseshoe Forest model. Right: posterior density of σ, estimated separately for each of the four chains.

```
ShrinkageTrees model summary
============================
Outcome: Right-censored (AFT, timescale = time) | Prior: horseshoe | Trees: 200
Data:    n = 285, p = 2003 | Draws: 5000 x 4 chains (burn-in 5000)

Posterior sigma:
  Mean: 0.996  SD: 0.059  95% CI: [0.889, 1.12]

Predictions (posterior mean):
  Train: mean = 48.235, sd = 4.101, range = [35.929, 58.447]
  Test:  mean = 48.093, sd = 2.868, range = [41.461, 54.333]

Variable importance (posterior inclusion probability):
  X482: 0.001  X419: 0.001  X124: 0.001  X1648: 0.001  X1229: 0.001
  X351: 0.001  X1110: 0.001  X1002: 0.001  X537: 0.001  X400: 0.001

MCMC acceptance ratio (per chain): 0.503, 0.504, 0.504, 0.504
```

We evaluate predictive accuracy using the C-index and compare with the BART baseline from Section 2.

```
c_train <- concordance(Surv(time_train, status_train) ~ fit_horse$train_predictions)
c_test  <- concordance(Surv(time_test, status_test) ~ fit_horse$test_predictions)
cat("Train C-index:", round(c_train$concordance, 3),
    " Test C-index:", round(c_test$concordance, 3), "\n")
```

The Horseshoe Forest achieves a test C-index of 0.582, indicating modest but above-chance discrimination — a reasonable result given the extremely high-dimensional setting ($p = 2{,}003 \gg n = 357$).

TODO: Add comparison with `SurvivalBART()` C-index from Section 2.

We assess convergence using σ traceplots and posterior densities. With `n_chains = 4`, each chain is plotted separately, allowing visual assessment of mixing and chain agreement. The `summary()` method automatically reports the effective sample size and Gelman–Rubin $\hat{R}$ statistic when the **coda** package is installed.

```
plot(fit_horse, type = "trace")
plot(fit_horse, type = "density")
```

Figure 2 shows good mixing: the four chains overlap throughout the sampling period and yield nearly identical posterior densities for σ.

We illustrate the posterior predictive survival curve for a randomly selected test-set patient.

```
pred <- predict(fit_horse, newdata = X_test)
idx <- sample(length(pred$mean), 1)
```

The individual posterior survival curve under the AFT log-normal model $S(t \mid \mathbf{x}) = 1 - \Phi((\log t - \hat{\mu}(\mathbf{x}))/\hat{\sigma})$ is plotted with pointwise 95% credible bands.



Figure 3: Left: posterior survival curve for a randomly selected test-set patient, with pointwise 95% credible bands. Right: population-averaged posterior survival curve (solid line) with 95% credible band (shaded) and Kaplan–Meier estimate (dashed).

```
plot(pred, type = "survival", obs = idx)
```

We also plot the population-averaged posterior survival curve across all training observations, overlaid with the Kaplan–Meier estimate for visual calibration.

```
plot(fit_horse, type = "survival", km = TRUE)
```

Figure 3 shows the individual and population-level posterior survival curves. The individual curve provides full uncertainty quantification for a single patient, while the population-averaged curve closely tracks the Kaplan–Meier estimate during the observed follow-up period, with expected divergence in the right tail where data are sparse.

Causal inference: treatment effects for survival

We now estimate heterogeneous treatment effects of carboplatin versus cisplatin using `CausalHorseForest()`, which fits a τ-learner with horseshoe shrinkage on both the prognostic and treatment effect forests. We first estimate propensity scores using a probit Horseshoe Forest on the clinical covariates. We choose a Horseshoe Forest over logistic regression because it handles potential non-linearities and interactions between clinical covariates without manual specification, while the horseshoe prior guards against overfitting in this low-sample-size setting. Using the full gene expression matrix for propensity estimation would risk overfitting given $p \gg n$; clinical covariates alone capture the main sources of confounding by indication.

```
X_ps <- cbind(age = clin$age, figo_stage = clin$figo_stage,
              tumor_grade = clin$tumor_grade)
ps_fit <- HorseTrees(
  y               = treatment,
  X_train         = X_ps,
  outcome_type    = "binary",
  number_of_trees = 200,
  k               = 0.1,
  N_post          = 2000,
  N_burn          = 2000
)
propensity <- ps_fit$train_predictions
X_control  <- cbind(propensity = propensity, X)

fit_causal <- CausalHorseForest(
  y                        = log(time),
  status                   = status,
  X_train_control          = X_control,
  X_train_treat            = X,
  treatment_indicator_train = treatment,
  outcome_type             = "right-censored",
  timescale                = "log",
```



Figure 4: Left: posterior density of the average treatment effect (ATE) of carboplatin versus cisplatin on the log-survival scale, with 95% credible interval (dashed lines). Right: patient-level conditional average treatment effects (CATEs) sorted by posterior mean with 95% credible intervals; the dashed line marks zero (no effect).

```
  number_of_trees           = 200,
  k                         = 0.1,
  N_post                    = 5000,
  N_burn                    = 5000,
  n_chains                  = 4
)
summary(fit_causal)

CausalShrinkageForest model summary
====================================
Outcome: Right-censored (AFT, timescale = log)
Prior:   control = horseshoe, treatment = horseshoe
Trees:   control = 200, treatment = 200
Data:   n = 357, p_control = 2004, p_treat = 2003 | Draws: 5000 x 4 chains (burn-in 5000)

Treatment effect (CATE):
  ATE:     -0.1518  95% CI: [-0.3991, 0.0688]
  CATE SD: 0.0133

Prognostic function (mu):
  Mean: 3.852  SD: 0.009  Range: [3.828, 3.875]

Posterior sigma:
  Mean: 0.993  SD: 0.051  95% CI: [0.898, 1.099]

MCMC acceptance ratios (per chain):
  control:   0.507, 0.507, 0.508, 0.508
  treatment: 0.476, 0.475, 0.476, 0.475
```

The `summary()` method reports the posterior average treatment effect (ATE) on the log-survival scale with a 95% credible interval. Here we pass `log(time)` directly with `timescale = "log"`, so all treatment effect estimates remain on the log-survival scale. A positive ATE indicates that carboplatin is associated with longer survival times.

The `plot()` method provides visualisations of the treatment effect posterior. The ATE density plot shows the full posterior distribution of the average treatment effect, while the CATE caterpillar plot displays patient-level treatment effect estimates sorted by posterior mean with 95% credible intervals.

```
plot(fit_causal, type = "ate")
plot(fit_causal, type = "cate")
```

Figure 4 shows the treatment effect posteriors. The posterior mean ATE is -0.15 on the log-survival scale, corresponding to an approximate 14% reduction in survival time under carboplatin relative to

cisplatin ($\exp(-0.15) \approx 0.86$). However, the 95% credible interval $[-0.40, 0.07]$ crosses zero, so the data do not provide clear evidence of a treatment effect. The individual CATEs cluster tightly around the ATE with narrow credible intervals, suggesting a relatively homogeneous treatment effect across the patient population — consistent with both platinum agents acting through similar mechanisms.

Although the ovarian dataset contains right-censored observations, **ShrinkageTrees** also supports interval-censored outcomes via `outcome_type = "interval-censored"` with `left_time` and `right_time` arguments following the convention of `survival::Surv(type = "interval2")`. See `?ShrinkageTrees` for details and examples. We demonstrate this capability in the following simulation.

Interval-censored outcomes: a simulation study

We validate **ShrinkageTrees** on a simulated interval-censored survival dataset with known ground truth. The simulation targets the setting where the horseshoe prior is expected to provide the largest benefit: a sparse, high-dimensional covariate space with interval-censored outcomes.

Design

We generate $n = 100$ observations with $p = 500$ covariates drawn independently from $\mathcal{N}(0, 1)$. Only the first 5 covariates are active. The true log-survival time follows

$$\log T_i = 2 + x_{i1} - 0.8\, x_{i2} + 0.6\, x_{i3} + 0.5\, x_{i1}\, x_{i4} - 0.4\, x_{i5} + \varepsilon_i, \quad \varepsilon_i \sim \mathcal{N}(0,\, 0.5^2).$$

We generate interval-censored observations by drawing inspection times $V_{i1} < V_{i2} < V_{i3}$ uniformly over the support of T and recording the interval $(L_i, R_i]$ in which the event falls. Approximately ...% of observations are interval-censored, ...% are right-censored (event after the last inspection), and ...% are exactly observed.

TODO: Fill in censoring percentages from actual simulation.

Code

We fit three models — standard BART, DART, and a Horseshoe Forest — each with $m = 200$ trees and 1,000 posterior draws after 250 burn-in iterations.

```
library(ShrinkageTrees)
set.seed(42)

# --- Data generation ---
n <- 100; p <- 500
X <- matrix(rnorm(n * p), n, p)
colnames(X) <- paste0("x", 1:p)
mu_true <- 2 + X[,1] - 0.8*X[,2] + 0.6*X[,3] + 0.5*X[,1]*X[,4] - 0.4*X[,5]
log_T <- mu_true + rnorm(n, sd = 0.5)
T_true <- exp(log_T)

# Interval censoring via inspection times
V <- matrix(runif(n * 3, min = min(T_true) * 0.5, max = max(T_true) * 1.2), n, 3)
V <- t(apply(V, 1, sort))
left_time <- right_time <- rep(NA, n)
for (i in 1:n) {
  inspections <- V[i, ]
  if (T_true[i] <= inspections[1]) {
    left_time[i] <- 0; right_time[i] <- inspections[1]
  } else if (T_true[i] > tail(inspections, 1)) {
    left_time[i] <- tail(inspections, 1); right_time[i] <- Inf
  } else {
    idx <- min(which(inspections >= T_true[i]))
    left_time[i] <- inspections[idx - 1]; right_time[i] <- inspections[idx]
  }
}

# --- Fit models ---
```

```
fit_bart <- SurvivalBART(
  y = left_time, X_train = X, outcome_type = "interval-censored",
  right_time = right_time, number_of_trees = 200,
  N_post = 1000, N_burn = 250
)
fit_dart <- SurvivalDART(
  y = left_time, X_train = X, outcome_type = "interval-censored",
  right_time = right_time, number_of_trees = 200,
  N_post = 1000, N_burn = 250
)
fit_horse <- HorseTrees(
  y = left_time, X_train = X, outcome_type = "interval-censored",
  right_time = right_time, number_of_trees = 200, k = 0.1,
  N_post = 1000, N_burn = 250
)
```

Results

We evaluate each model on a held-out test set of $n_{\text{test}} = 100$ observations using root mean squared error (RMSE) of the posterior mean of $\log T$ relative to the true $\log T$, and 95% credible interval coverage. We repeat the simulation . . . times and report averages.

TODO: Fill in with actual simulation results.

The Horseshoe Forest is expected to outperform standard BART and DART in this sparse setting because the horseshoe prior aggressively shrinks the step heights of trees that split on irrelevant covariates, effectively silencing 495 of the 500 predictors without relying on structural variable selection alone. The $p \gg n$ regime ($p = 500$, $n = 100$) makes adequate regularisation essential.

TODO: Update this paragraph with actual findings. Add a figure showing estimated vs. true survival curves for a representative observation if space permits.

5 Package architecture

ShrinkageTrees is available on CRAN and on GitHub at `https://github.com/tijn-jacobs/ShrinkageTrees`. The package is implemented in R with a C++ backend via **Rcpp** (Eddelbuettel and François, 2011). In this section we describe the design and implementation.

Fitting functions and S3 classes

The package provides four primary fitting functions and four convenience wrappers for common model configurations. Table 1 lists all eight functions. The primary functions accept arguments that control the outcome type (`outcome_type`), prior specification (`prior_type`, `local_hp`, `global_hp`), tree structure (`number_of_trees`, `power`, `base`), and MCMC settings (`N_post`, `N_burn`, `n_chains`).

`ShrinkageTrees()` is the most general prediction model function. It accepts a `prior_type` argument that selects the leaf prior: `"horseshoe"` (per-tree global scale), `"horseshoe_fw"` (forest-wide global scale), `"half-cauchy"` (local shrinkage only), `"standard"` (conjugate normal, as in classical BART), or `"dirichlet"` (Dirichlet splitting, as in DART). `HorseTrees()` is a convenience wrapper that fixes the prior to the horseshoe and exposes a single tuning parameter k controlling the half-Cauchy scales via $\alpha_\tau = \alpha_\lambda = k/\sqrt{m}$. The causal functions `CausalShrinkageForest()` and `CausalHorseForest()` mirror this design for the τ-learner, with independent prior configurations for the prognostic and treatment effect forests.

All prediction model functions return an object of class `"ShrinkageTrees"`; all causal model functions return `"CausalShrinkageForest"`. Both classes provide `print()`, `summary()`, `predict()`, and `plot()` methods. The `summary()` method reports posterior summaries for σ, variable inclusion probabilities, and — for causal models — the ATE with a credible interval. The `predict()` method re-runs the MCMC sampler on the new covariate matrix using the training data and hyperparameters stored in the fitted object; it always generates posterior samples internally, regardless of whether `store_posterior_sample` was set during fitting. The returned `ShrinkageTreesPrediction` object contains posterior means and credible intervals. The `plot()` method produces MCMC diagnostics (traceplots and posterior densities for σ), variable importance plots, and — for causal models — ATE and CATE visualisations. Plotting uses **ggplot2**, which is a suggested but not required dependency.

Table 1: Fitting functions in ShrinkageTrees. The first four are primary functions; the last four are convenience wrappers.

Function	Description
`ShrinkageTrees()`	Prediction model with user-specified leaf prior (horseshoe, half-Cauchy, standard, Dirichlet)
`HorseTrees()`	Prediction model with horseshoe prior; single tuning parameter k
`CausalShrinkageForest()`	τ-learner causal model with user-specified leaf priors for μ and τ forests
`CausalHorseForest()`	τ-learner causal model with horseshoe prior on both forests
`SurvivalBART()`	AFT survival with conjugate normal leaf prior (standard BART)
`SurvivalDART()`	AFT survival with Dirichlet splitting prior (DART)
`SurvivalBCF()`	AFT survival with τ-learner decomposition and conjugate normal leaf prior
`SurvivalShrinkageBCF()`	AFT survival with τ-learner decomposition and horseshoe leaf prior

Rcpp backend

We implement the computationally intensive components of the Gibbs sampler in C++ via Rcpp. This includes the Metropolis-within-Gibbs updates for tree topology (grow, prune, and change moves), the conditional updates for the leaf step heights, the horseshoe augmentation steps for the local and global scale parameters, the Gibbs update for σ, and the data augmentation for censored observations. The R layer handles input validation, data preprocessing (centering, scaling, log-transforming survival times), hyperparameter calibration, S3 class construction, and post-processing (back-transformation of predictions).

Internally, the C++ code dispatches between two forest implementations depending on the prior. Priors that require reversible jump proposals (`"horseshoe"`, `"horseshoe_fw"`, `"half-cauchy"`) use a `Forest` class with paired grow–prune moves that satisfy detailed balance. The `"standard"` and `"dirichlet"` priors use a separate `StanForest` class with birth–death moves, which is simpler and faster when global scale updates are not needed.

The scale mixture prior on the step heights is encapsulated in a C++ class `ScaleMixture` that follows the strategy pattern. An abstract base class `EtaPrior` defines a common interface — proposing new local parameters, computing the log prior and proposal densities needed for the Metropolis–Hastings ratio, and optionally performing a global update — while concrete subclasses implement the prior-specific sampling logic. The current subclasses are `FixedVariance` (conjugate normal, used by BART and DART), `HalfCauchy` (local shrinkage only), `Horseshoe` (per-tree global–local shrinkage), and `Horseshoe_fw` (forest-wide global shrinkage). A factory function selects the appropriate subclass at run time based on the user's `prior_type` argument. Because the tree update and reversible jump routines interact with the prior only through the `ScaleMixture` interface, adding a new global–local shrinkage prior — for example a regularised horseshoe or a Dirichlet–Laplace prior — requires only implementing a new `EtaPrior` subclass and registering it in the factory, without modifying the sampler logic.

TODO: Add package architecture figure — a layered diagram showing: R layer (input validation, preprocessing, S3 methods) → C++ layer (Forest / StanForest classes, ScaleMixture → EtaPrior subclasses) → output (predictions, diagnostics, coda bridge).

Multi-chain MCMC

All primary fitting functions accept an `n_chains` argument. When `n_chains > 1`, independent chains are dispatched in parallel via `parallel::mclapply()` using `min(n_chains, parallel::detectCores())` cores. After sampling, the posterior draws from all chains are pooled: sample matrices are concatenated row-wise and posterior means are recomputed from the pooled draws. The returned object is a standard `ShrinkageTrees` or `CausalShrinkageForest` instance, so all downstream methods work without modification. Per-chain diagnostics (acceptance ratios, σ traces) are retained for convergence assessment.

Convergence diagnostics via coda

Assessing MCMC convergence is an essential part of any Bayesian workflow, yet most BART implementations leave this task entirely to the user. **ShrinkageTrees** provides a bridge to the **coda** ecosystem (Plummer et al., 2006) through an `as.mcmc.list()` S3 method. This method extracts the posterior draws of σ — split by chain — and wraps each chain in a `coda::mcmc` object, returning a `coda::mcmc.list`. Because **coda** is a suggested rather than required dependency, all functionality remains available when it is not installed. When it is available, `summary()` automatically reports the effective sample size (ESS) and — for multi-chain fits — the Gelman–Rubin $\hat{R}$ statistic. Users who require more detailed diagnostics can pass the `mcmc.list` object directly to any **coda** function, including `geweke.diag()`, `heidel.diag()`, `autocorr.plot()`, and `gelman.plot()`, obtaining a complete convergence assessment without custom post-processing code.

Computational speed

TODO: Fill in with actual benchmark results.

We benchmark the computational cost of **ShrinkageTrees** along three axes: sample size n, number of covariates p, and number of trees m. All timings reported in this section are wall-clock seconds on a single core (Intel . . . , R version . . .).

Within-package comparison. We first compare the fitting functions shipped with **ShrinkageTrees**. For a simulated survival dataset with $n = \ldots$, $p = \ldots$, and $m = \ldots$ trees, the standard BART model (`SurvivalBART()`) runs in approximately . . . seconds per 1,000 MCMC iterations. Enabling the horseshoe prior (`HorseTrees()`) adds a per-iteration overhead of . . .% because each step height draws an individual shrinkage weight. The DART variant (`SurvivalDART()`) incurs a similar overhead due to the Dirichlet update on the tree-level inclusion probabilities. The causal forest wrapper (`CausalHorseForest()`) roughly doubles the cost relative to the prognostic-only model, as it fits separate ensembles for the prognostic and treatment-effect components.

External comparison. We compare **ShrinkageTrees** with **BART** (Sparapani et al., 2021), the only other CRAN package that provides Bayesian tree ensembles for survival data. On the same simulated dataset, `BART::abart()` runs in . . . seconds. The difference in speed is attributable to . . .. We note that XBART (He et al., 2019) uses a fundamentally different fitting strategy based on stochastic tree search rather than the standard Metropolis–Hastings back-fitting algorithm, so a direct wall-clock comparison would not be informative; we therefore exclude it from the benchmark.

Scaling behaviour. Figure~**??** shows how wall-clock time scales with n, p, and m individually. Time scales approximately linearly in m and n, and sub-linearly in p because only a subset of covariates is evaluated at each splitting rule proposal.

TODO: Add Figure **??** with benchmark plots.

6 Related packages

Several R packages implement Bayesian tree ensembles. We review five CRAN packages and compare their capabilities to **ShrinkageTrees**. Table 2 provides a summary.

BART (Sparapani et al., 2021) is the most comprehensive general-purpose BART package. It supports continuous, binary, and multinomial outcomes, and is, at the time of writing, the only other CRAN package to offer Bayesian tree ensembles for survival data. Survival models include a discrete-time hazard formulation (`surv.bart()`), an AFT formulation (`abart()`), competing risks (`crisk.bart()`), and recurrent events (`recur.bart()`). The package also supports Dirichlet splitting priors via `sparse = TRUE`. However, **BART** does not provide global–local shrinkage priors on the leaf step heights, causal forest models, or interval-censored survival outcomes. Multi-chain MCMC is not natively supported; the `mc.*` functions parallelise a single chain rather than running independent chains.

dbarts (Dorie, 2023) provides a fast, lightweight BART sampler for continuous and binary outcomes. Its key feature is an updatable sampler object: predictors and responses can be modified mid-sampling, which makes **dbarts** well suited as a conditional model within a larger Gibbs sampler. The package supports multi-chain MCMC but does not implement survival models, τ-learner models, or alternative leaf priors.

bcf (Hahn et al., 2020) implements the τ-learner with separate prognostic and treatment effect forests for continuous outcomes. It places half-Cauchy and half-Normal hyperpriors on the leaf scales of the two forests, respectively. The package does not support survival endpoints, horseshoe priors, or Dirichlet splitting.

stochtree is a recent package that implements BART, XBART, the τ-learner, and XBCF for continuous, binary, and ordinal outcomes. It supports variance forests for heteroskedastic modelling and provides model serialisation for warm-starting. However, **stochtree** does not implement AFT survival models, Dirichlet splitting priors, or horseshoe shrinkage on the leaf step heights.

SoftBart (Linero and Yang, 2018) replaces the hard axis-aligned splits of standard BART with smooth logistic splitting rules, yielding a posterior mean that is a continuous function of the covariates. This can improve performance when the true regression surface is smooth, but introduces additional computational cost and a fundamentally different regularisation mechanism. **ShrinkageTrees** uses hard decision splits, as in classical BART. Extending the horseshoe and Dirichlet priors to soft splitting rules is a natural direction for future work.

At the time of writing, **ShrinkageTrees** is the only implementation that combines global–local shrinkage priors on the step heights with Bayesian tree ensembles for survival and causal inference. It is also the only package to support interval-censored survival outcomes within a Bayesian tree ensemble framework and the only package to offer the τ-learner for survival endpoints.

Table 2: Comparison of Bayesian tree ensemble packages in R.

Package	Survival	Interval Censoring	Causal (τ-learner)	Dirichlet (DART)	Global–local shrinkage
BART	Yes	No	No	Yes	No
dbarts	No	No	No	No	No
bcf	No	No	Yes	No	No
stochtree	No	No	Yes	No	No
SoftBart	No	No	No	No	No
ShrinkageTrees	Yes	Yes	Yes	Yes	Yes

7 Discussion and conclusion

We have introduced **ShrinkageTrees**, an R package for Bayesian tree ensembles that combines global–local shrinkage priors with survival analysis and causal inference. The package decouples structural regularisation from parametric shrinkage, allowing practitioners to tailor the regularisation strategy to the problem at hand. To our knowledge, it is the first CRAN package to offer the τ-learner for survival endpoints, horseshoe priors on tree ensemble step heights, and interval-censored survival outcomes within a single framework.

We estimate the average treatment effect via the mixed average treatment effect [MATE; Li et al. (2023)], which averages the posterior CATEs over the observed covariate distribution. The MATE is straightforward to compute but tends to produce overly narrow credible intervals because it conditions on the observed covariates rather than accounting for covariate sampling variability. A similar form of overconfidence is visible in Figure 4, where the credible interval is notably tight. A natural remedy is the Bayesian bootstrap (Rubin, 1981), which reweights the covariate distribution with random Dirichlet weights at each MCMC iteration. We leave the integration of the Bayesian bootstrap into **ShrinkageTrees** as future work.

The package has several limitations that suggest directions for future work. Currently, all covariates must be numeric: continuous, binary, and ordered categorical variables (encoded as integers) are handled naturally by the axis-aligned splitting rules, but unordered categorical variables must be dummy-encoded by the user. This can be suboptimal for high-cardinality factors, where native subset splits — as implemented in **bartMachine** (Kapelner and Bleich, 2016) — may be more efficient. The current AFT formulation assumes normally distributed errors; extending the framework to alternative error distributions (e.g. logistic, log-logistic) would broaden its applicability. The Gibbs sampler can be slow to mix in very high-dimensional settings; incorporating warm-starting or accelerated sampling strategies could improve computational efficiency.

ShrinkageTrees is available on CRAN and actively maintained on GitHub at `https://github.com/tijn-jacobs/ShrinkageTrees`. The methodological foundations are developed in Jacobs et al. (2025).

8 Funding

Tijn Jacobs and Stéphanie van der Pas received funding from the European Research Council (ERC) under the European Union's Horizon Europe program under Grant agreement No. 101074082. Views and opinions expressed are however those of the author(s) only and do not necessarily reflect those of the European Union or the European Research Council Executive Agency. Neither the European Union nor the granting authority can be held responsible for them.

Bibliography

Cancer Genome Atlas Research Network. Integrated genomic analyses of ovarian carcinoma. *Nature*, 474:609–615, 2011. doi: 10.1038/nature10166. [p2]

A. Caron, G. Baio, and I. Manolopoulou. Estimating individual treatment effects using non-parametric regression models: A review. *Journal of the Royal Statistical Society Series A: Statistics in Society*, 185(3): 1115–1149, 2022. doi: 10.1111/rssa.12889. [p1, 5]

C. M. Carvalho, N. G. Polson, and J. G. Scott. The horseshoe estimator for sparse signals. *Biometrika*, 97(2):465–480, 2010. doi: 10.1093/biomet/asq017. [p1, 5]

H. A. Chipman, E. I. George, and R. E. McCulloch. Bayesian CART model search. *Journal of the American Statistical Association*, 93(443):935–948, 1998. doi: 10.1080/01621459.1998.10473750. [p4]

H. A. Chipman, E. I. George, and R. E. McCulloch. BART: Bayesian additive regression trees. *The Annals of Applied Statistics*, 4(1):266–298, 2010. doi: 10.1214/09-AOAS285. [p1, 2, 3, 4, 6]

V. Dorie. *dbarts: Discrete Bayesian Additive Regression Trees Sampler*, 2023. URL `https://CRAN.R-project.org/package=dbarts`. R package version 0.9-23. [p13]

V. Dorie, J. Hill, U. Shalit, M. Scott, and D. Cervone. Automated versus do-it-yourself methods for causal inference: Lessons learned from a data analysis competition. *Statistical Science*, 34(1):43–68, 2019. doi: 10.1214/18-STS667. [p5]

D. Eddelbuettel and R. François. Rcpp: Seamless R and C++ integration. *Journal of Statistical Software*, 40(8):1–18, 2011. doi: 10.18637/jss.v040.i08. [p1, 11]

P. R. Hahn, J. S. Murray, and C. M. Carvalho. Bayesian regression tree models for causal inference: Regularization, confounding, and heterogeneous effects. *Bayesian Analysis*, 15(3):965–1056, 2020. doi: 10.1214/19-BA1195. [p1, 5, 13]

F. E. Harrell, K. L. Lee, and D. B. Mark. Multivariable prognostic models: Issues in developing models, evaluating assumptions and adequacy, and measuring and reducing errors. *Statistics in Medicine*, 15 (4):361–387, 1996. doi: 10.1002/(SICI)1097-0258(19960229)15:4<361::AID-SIM168>3.0.CO;2-4. [p3]

J. He, S. Yalov, and P. R. Hahn. XBART: Accelerated Bayesian additive regression trees. In *Proceedings of the 22nd International Conference on Artificial Intelligence and Statistics (AISTATS)*, volume 89, pages 1130–1138, 2019. URL `https://proceedings.mlr.press/v89/he19a.html`. [p13]

J. L. Hill. Bayesian nonparametric modeling for causal inference. *Journal of Computational and Graphical Statistics*, 20(1):217–240, 2011. doi: 10.1198/jcgs.2010.08162. [p5]

T. Jacobs, W. N. van Wieringen, and S. L. van der Pas. Horseshoe forests for high-dimensional causal survival analysis. *arXiv preprint arXiv:2507.22004*, 2025. doi: 10.48550/arXiv.2507.22004. [p1, 5, 6, 14]

A. Kapelner and J. Bleich. bartMachine: Machine learning with Bayesian additive regression trees. *Journal of Statistical Software*, 70(4):1–40, 2016. doi: 10.18637/jss.v070.i04. [p14]

F. Li, P. Ding, and F. Mealli. Bayesian causal inference: A critical review. *Philosophical Transactions of the Royal Society A*, 381(2247):20220153, 2023. doi: 10.1098/rsta.2022.0153. [p14]

A. R. Linero. Bayesian regression trees for high-dimensional prediction and variable selection. *Journal of the American Statistical Association*, 113(522):626–636, 2018. doi: 10.1080/01621459.2016.1264957. [p1, 4]

A. R. Linero and Y. Yang. Bayesian regression tree ensembles that adapt to smoothness and sparsity. *Journal of the Royal Statistical Society: Series B (Statistical Methodology)*, 80(5):1087–1110, 2018. doi: 10.1111/rssb.12293. [p14]

M. Plummer, N. Best, K. Cowles, and K. Vines. CODA: Convergence diagnosis and output analysis for MCMC. *R News*, 6(1):7–11, 2006. URL https://journal.r-project.org/archive/. [p13]

N. G. Polson and J. G. Scott. On the half-Cauchy prior for a global scale parameter. *Bayesian Analysis*, 7 (4):887–902, 2012. doi: 10.1214/12-BA730. [p5]

V. Ročková and E. Saha. On the theory of BART. *arXiv preprint arXiv:1910.00597*, 2020. [p4]

D. B. Rubin. The Bayesian bootstrap. *The Annals of Statistics*, 9(1):130–134, 1981. doi: 10.1214/aos/1176345338. [p14]

R. Sparapani, C. Spanbauer, and R. McCulloch. Nonparametric machine learning and efficient computation with Bayesian additive regression trees: The BART R package. *Journal of Statistical Software*, 97(1):1–66, 2021. doi: 10.18637/jss.v097.i01. [p13]

Tijn Jacobs
Vrije Universiteit Amsterdam
Department of Mathematics
Amsterdam, The Netherlands
https://tijn-jacobs.github.io/
ORCiD: 0009-0003-6188-9296
t.jacobs@vu.nl

Stéphanie van der Pas
Vrije Universiteit Amsterdam
Department of Mathematics
Amsterdam, The Netherlands
https://www.stephanievanderpas.nl/
ORCiD: 0000-0002-2448-5378
s.l.vander.pas@vu.nl

Wessel van Wieringen
Vrije Universiteit AmsterdamAmsterdam University Medical Centre
Department of Mathematics, Amsterdam, The Netherlands
Epidemiology and Data Science, Amsterdam, The Netherlands
https://www.math.vu.nl/~wvanwie/
ORCiD: 0000-0002-5100-9123
w.n.vanwieringen@vu.nl