

BASE OILS

TŞ 05766698-60-2016



Description of index	Standard values				
	SN 80	SN 180	SN 350	SN 600	SN 1200
Kinematic viscosity 100°C, mm ² /c	2,5-3,5	4,5-6,0	8,0-9,5	11,5-13,5	18,0-23,0
Viscosity index, not more than	95	95	95	95*	90
Mass fraction of sulfur, %, not more than	0,03	0,03	0,03	0,03**	0,03**
Acid number, mg KOH per 1 g of oil, no more	0,02	0,03	0,05	0,05	0,06
Mass fraction of mechanical impurities, %, not more than	0,005	0,005	0,005	0,005	0,005
Flash point, determined in an open cup, °C, not lower than	170	205	220	225	250
Pour point, °C, not higher than	minus 12	minus 12	minus 12	minus 9	minus 9
Refractive index at 20°C	Not standardized, definition is required				
Color according to ASTM, not more than color of CNT units, not more than color in conventional units of CNT, not more than	0,5 - 0,5	0,5 - 0,5	1,0 1,0 -	2,0 2,0 -	3,0 3,0 -
Ash content, %, not more than	0,005	0,005	0,005	0,005	0,005
Density at 20°C, kg/m ³ , not more than	870	880	890	900	905

NOTE

* - when delivered for export, in accordance with the established procedure by agreement between the manufacturer and the consumer, it is allowed to produce with a viscosity index of at least 92;

** - when delivered for export, in accordance with the established procedure by agreement between the manufacturer and the consumer, a mass fraction of sulfur is allowed not more than 0.06%.