

DIESEL FUEL FROM LOW-SULFUR OILS
ТШ 05766698-06-2014



№	Indicators	Norm
1	Cetane number, not less	45
2	Fractional composition: - 50% distilled at temperature, °C, not higher - 96% distilled at temperature (end of boil), °C, not higher	290 360
3	Kinematic viscosity at 20°C, mm ² /C	3,0-6,0
4	Pour point, °C, not higher	Minus 10
5	Cloud point, °C, not higher	Minus 5
6	Flash point, determined in a closed crucible, °C, not lower: - for general purpose diesel engines - for general purpose diesel engines - for diesel and marine diesel engines and gas turbines	40 50 62
7	Mass fraction of sulfur, %, not more	0,20
8	Mass fraction of mercaptan sulfur, %, not more	0,008
9	Hydrogen sulfide content	Absence
10	Copper strip test	Resistant
11	Content of water-soluble acids and alkalis	Absence
12	Concentration of actual resins, mg per 100 cm ³ fuel, not more	40,0
13	Acidity, mg KOH per 100 cm ³ of fuel, no more	10,0
14	Iodine number, g of iodine per 100 g of fuel, no more	6,0
15	Ash content, %, not more	0,005
16	Coking capacity of 10% residue, %, no more	0,25
17	Filtration coefficient, no more	3,0
18	Content of mechanical impurities	Absence
19	Water content	Absence
20	Density at 20°C, kg / m ³ , no more	860