New Web Service

New Web Service

It looks like you're using **Node**, so we've autofilled some fields accordingly.

Source Code

tilahunm12 / DreamMorePlatform

Name

A unique name for your web service.

dream-more-api

Language

Choose the runtime environment for this service.

Node

Branch

The Git branch to build and deploy.

main

Region

Your services in the same region can communicate over a private network.

Ohio (US East)

Root Directory Optional

If set, Render runs commands from this directory instead of the repository root. Additionally, code changes outside of this directory do not trigger an auto-deploy. Most commonly used with a monorepo.

```
e.g. src
```

Build Command

Render runs this command to build your app before each deploy.

```
$ npm install && npm --prefix packages/shared run build && npm --prefix apps/api run p…
```

Start Command

Render runs this command to start your app with each deploy.

```
$ npm --prefix apps/api run start:prod
```

Compute

For more power and to get the most out of Render, we recommend using one of our paid compute plans.
All paid compute plans support:

- Zero Downtime
- SSH Access
- Scaling
- One-off jobs
- Support for persistent disks

Selected:

$0 / month **0.1** CPU **512** MB RAM

ⓘ Free instances spin down after periods of inactivity. They do not support SSH access, scaling, one-off jobs, or persistent disks.

◉ $0 / month
0.1 CPU 512 MB RAM

$7 / month
0.5 CPU 512 MB RAM

$25 / month
1 CPU 2 GB RAM

$85 / month
2 CPU 4 GB RAM

Show all 15 compute plans

Environment Variables

Set environment-specific config and secrets (such as API keys), then read those values from your code. Learn more.

NAME_OF_VARIABLE | value | Generate

+ Add Environment Variable | Add from .env

Advanced

Secret Files

Store plaintext files containing secret data (such as a `.env` file or a private key).

Access during builds and at runtime from your app's root, or from `/etc/secrets/<filename>`.

+ Add Secret File

Health Check Path

Provide an HTTP endpoint path that Render messages periodically to monitor your service. Learn More.

/healthz

Pre-Deploy Command

Render runs this command before the start command. Useful for database migrations and static asset uploads.

Auto-Deploy

By default, Render automatically deploys your service whenever you update its code or configuration. Disable to handle deploys manually. Learn more.

On Commit

Build Filters

Include or ignore specific paths in your repo when determining whether to trigger an auto-deploy. Paths are relative to your repo's root directory. Learn more.

Included Paths
Changes that match these paths will trigger a new build.

+ Add Included Path

Ignored Paths
Changes that match these paths will not trigger a new build.

+ Add Ignored Path

Deploy web service Cancel

T Tilahun's worksp... T