main.py

Share Run

```python
# Online Python compiler (interpreter) to run Python online.
# Write Python 3 code in this online editor and run it.
num = int(input("Enter a number: "))
if num > 0:
    print("Positive")
```

Output Clear

```
Enter a number: 3
Positive

=== Code Execution Successful ===
```

main.py

Share Run

```python
# Online Python compiler (interpreter) to run Python online.
# Write Python 3 code in this online editor and run it.
# input from user
num = int(input("Enter a number: ")
if num % 5 == 0:
    print("Divisible by 5")
if num % 5 != 0:
    print("Not divisible by 5")
```

Output

Clear

```
Enter a number: 6
Not divisible by 5

=== Code Execution Successful ===
```

main.py

Share Run

```python
# Online Python compiler (interpreter) to run Python online.
# Write Python 3 code in this online editor and run it.
# input from user
num = int(input("Enter a number: "))
if num % 2 == 0:
    print("The number is Even")
else:
    print("The number is Odd")
```

```python
# Online Python compiler (interpreter) to run Python online.
# Write Python 3 code in this online editor and run it.
# input from user
n = int(input("Enter number: "))

for i in range(1, 11):
    print(n * i)
```

```python
# Online Python compiler (interpreter) to run Python online.
# Write Python 3 code in this online editor and run it.
# input from user
n = int(input("Enter a number: "))
sum = 0
i =1
while i <= n:
    sum += i
    i += 1

print("Sum of first", n, "natural numbers is:", sum)
```

```python
# Online Python compiler (interpreter) to run Python online.
# Write Python 3 code in this online editor and run it.
# input from user
# Take input from the user
num = input("Enter a number: ")
reversed_num = num[::-1]
print("Reversed number:", reversed_num)
```

```
Enter a number: 4
Reversed number: 4

=== Code Execution Successful ===
```

```python
# Online Python compiler (interpreter) to run Python online.
# Write Python 3 code in this online editor and run it.
# input from user
# Take input from the user
num = input("Enter a number: ")
reversed_num = num[::-1]
print("Reversed number:", reversed_num)
```

```
Enter a number: 4
Reversed number: 4

=== Code Execution Successful ===
```

```python
# Online Python Compiler (Interpreter) to run Python online.
# Write Python 3 code in this online editor and run it.
# input from us
num = int(input("Enter a number: "))
num = abs(num)
count = 0
temp = num
while temp > 0:
    temp = temp // 10
    count += 1
if num == 0:
    count = 1
print("Number of digits:", count)
```

```
Enter a number: 3
Number of digits: 1

=== Code Execution Successful ===
```

```python
# Online Python compiler (interpreter) to run Python online.
# Write Python 3 code in this online editor and run it.
# input from us
num = int(input("Enter a number: "))
factorial = 1
for i in range(1, num + 1):
    factorial *= i
print("Factorial:", factorial)
```

```
Enter a number: 8
Factorial: 40320

=== Code Execution Successful ===
```

```python
# Online Python compiler (interpreter) to run Python online.
# Write Python 3 code in this online editor and run it.
# input from us
num = int(input("Enter a number: "))
factorial = 1
for i in range(1, num + 1):
    factorial *= i
print("Factorial:", factorial)
```

```
Enter a number: 8
Factorial: 40320

=== Code Execution Successful ===
```

main.c

Share Run

```c
    printf("Enter number of non-zero elements: ");
    scanf("%d", &n);

    printf("Enter rows, columns and values:\n");
    for(i = 0; i < n; i++)
    {
        scanf("%d %d %d", &sparse[i][0], &sparse[i][1],
            &sparse[i][2]);
    }

    // First row (metadata)
    transpose[0][0] = sparse[0][1];
    transpose[0][1] = sparse[0][0];
    transpose[0][2] = sparse[0][2];

```