

Implementierung der Cut & Count-Technik am Beispiel Steiner tree

Levin von Hollen, Tilman Beck

{stu127560-, stu127568-}@informatik.uni-kiel.de

Christian-Albrechts Universität Kiel

27. Oktober 2016

- 1 Cut & Count
 - Allgemeines
- 2 Cut & Count mit Steiner Tree
 - Cut
 - Count
 - (Nice) Tree Decomposition
- 3 Implementierung

- Technik um connectivity-type Probleme mithilfe von Randomisierung zu lösen (Marek Cygan, Jesper Nederlof, Marcin Pilipczuk, Michał Pilipczuk, Johan van Rooij, Jakub Onufry Wojtaszczyk)
- angewendet auf viele verschiedene Probleme (z.B. Longest Path, Steiner Tree, Feedback Vertex Set uvm)
- Randomisierung durch Isolation-Lemma
- als Ergebnis ein einseitiger Monte-Carlo-Algorithmus mit Laufzeit $c^{tw(G)} |V|^{\mathcal{O}(1)}$

Theorem

There exists a randomized algorithm, which given a graph G with n vertices, a tree decomposition of G of width t and a number k in $3^t n^{\mathcal{O}(1)}$ time either states that there exists a connected vertex cover of size at most k in G , or that it could not verify this hypothesis. If there indeed exists such a cover, the algorithm will return “unable to verify” with probability at most $1/2$.

Problem

Input: An undirected graph $G = (V, E)$, a set of terminals $T \subseteq V$ and an integer k .

Question: Is there a set $X \subseteq V$ of cardinality k such that $T \subseteq X$ and $G[X]$ is connected?

- definiere Gewichtsfunktion $\omega : V \rightarrow \{1, \dots, N\}$
- sei \mathcal{R}_W die Menge aller Teilmengen von X aus V mit $T \subseteq X$, $\omega(X) = W$ und $|X| = k$
- sei $\mathcal{S}_W = \{X \in \mathcal{R}_W \mid G[X] \text{ ist zusammenhängend}\}$
- $\cup_W \mathcal{S}_W$ ist die Menge der Lösungen
- gibt es ein W für das die Menge nichtleer ist, so gibt der Algorithmus eine positive Antwort

- einen beliebigen Terminalknoten $v \in T$ als v_1 festlegen
- sei \mathcal{C}_W die Menge aller Subgraphen, die einen konsistenten Cut $(X, (X_1, X_2))$ bilden, wobei $X \in \mathcal{R}_W$ und $v_1 \in X_1$

Lemma 3.3

Let $G = (V, E)$ be a graph and let X be a subset of vertices such that $v_1 \in X \subseteq V$. The number of consistently cut subgraphs $(X, (X_1, X_2))$ such that $v_1 \in X_1$ is equal to $2^{cc(G[X])-1}$.

- aus Lemma 3.3 ist bekannt: $|\mathcal{C}| = \sum_{X \in \mathcal{R}} 2^{cc(G[X])-1}$
- wir legen W fest und ignorieren die Indices:
 $|\mathcal{C}| \equiv |\{X \in \mathcal{R} \mid cc(G[X]) = 1\}| = |\mathcal{S}|$

Lemma 3.4

Let G, ω, \mathcal{C}_W and \mathcal{S}_W be as defined above. Then for every W ,
 $|\mathcal{S}_W| \equiv |\mathcal{C}_W|$.

Tree Decomposition

A tree decomposition of a graph G is a tree \mathbb{T} in which each vertex $x \in \mathbb{T}$ has an assigned set of vertices $B_x \subseteq V$ (called a bag) such that

$\bigcup_{x \in \mathbb{T}} B_x = V$ with the following properties:

- for any $uv \in E$, there exists an $x \in \mathbb{T}$ such that $u, v \in B_x$
- if $v \in B_x$ and $v \in B_y$, then $v \in B_z$ for all z on the path from x to y in \mathbb{T}

Nice Tree Decomposition

...

- **Leaf bag:** a leaf x of \mathbb{T} with $B_x = \emptyset$
- **Introduce vertex bag:** an internal vertex x of \mathbb{T} with one child vertex y for which $B_x = B_y \cup \{v\}$ for some $v \notin B_y$. This bag is said to introduce v
- **Introduce edge bag:** an internal vertex x of \mathbb{T} labeled with an edge $uv \in E$ with one child bag y for which $u, v \in B_x = B_y$. This bag is said to introduce uv
- **Forget bag:** an internal vertex x of \mathbb{T} with one child bag y for which $B_x = B_y \setminus \{v\}$ for some $v \in B_y$. This bag is said to forget v
- **Join bag:** an internal vertex x with two children vertices l and r with $B_r = B_l$

- Kardinalität von \mathcal{C}_W modulo 2 kann mit dynamischen Programm berechnet werden
-

- Lorem ipsum dolor sit amet, consectetur adipiscing elit
- Aliquam blandit faucibus nisi, sit amet dapibus enim tempus eu
- Nulla commodo, erat quis gravida posuere, elit lacus lobortis est, quis porttitor odio mauris at libero
- Nam cursus est eget velit posuere pellentesque
- Vestibulum faucibus velit a augue condimentum quis convallis nulla gravida

Blocks of Highlighted Text

Block 1

Lorem ipsum dolor sit amet, consectetur adipiscing elit. Integer lectus nisl, ultricies in feugiat rutrum, porttitor sit amet augue. Aliquam ut tortor mauris. Sed volutpat ante purus, quis accumsan dolor.

Block 2

Pellentesque sed tellus purus. Class aptent taciti sociosqu ad litora torquent per conubia nostra, per inceptos himenaeos. Vestibulum quis magna at risus dictum tempor eu vitae velit.

Block 3

Suspendisse tincidunt sagittis gravida. Curabitur condimentum, enim sed venenatis rutrum, ipsum neque consectetur orci, sed blandit justo nisi ac lacus.

Heading

- ➊ Statement
- ➋ Explanation
- ➌ Example

Lorem ipsum dolor sit amet, consectetur adipiscing elit. Integer lectus nisl, ultricies in feugiat rutrum, porttitor sit amet augue. Aliquam ut tortor mauris. Sed volutpat ante purus, quis accumsan dolor.

Treatments	Response 1	Response 2
Treatment 1	0.0003262	0.562
Treatment 2	0.0015681	0.910
Treatment 3	0.0009271	0.296

Tabelle : Table caption

Theorem

Theorem (Mass–energy equivalence)

$$E = mc^2$$

Example (Theorem Slide Code)

```
\begin{frame}  
\frametitle{Theorem}  
\begin{theorem}[Mass--energy equivalence]  
$E = mc^2$  
\end{theorem}  
\end{frame}
```

Figure

Uncomment the code on this slide to include your own image from the same directory as the template .TeX file.

An example of the `\cite` command to cite within the presentation:

This statement requires citation [Smith, 2012].



John Smith (2012)

Title of the publication

Journal Name 12(3), 45 – 678.

The End