



Refresh Homologação – MIGs (Netwin)

Procedimento por Monique Santos

Documentação e ajustes por Guilherme Costa

Dados de Acesso

Instância	IP	Hostname	Tipo
NETWINPRD	172.17.2.10	vmldbnetprd01	Produção
MIGS	172.19.2.22	vmldbmigs02	Homologação

Conectar a produção para capturar o último controlfile gerado pelo backup de archives

```
cd /u01/app/oracle/backup/backups/NETWINPRD/log_backups
```

```
[oracle@vmldbnetwprd01:/u01/app/oracle/backup/backups/NETWINPRD/log_backups [NETWINPRD] ]$ tail -30 20230524_10h00m01s_backup_DIARIO_ARCH_DISK.concluido
input archived log thread=1 sequence=28793 RECID=87143 STAMP=1137663562
input archived log thread=1 sequence=28794 RECID=87145 STAMP=1137663811
input archived log thread=1 sequence=28795 RECID=87147 STAMP=1137664012
input archived log thread=1 sequence=28796 RECID=87149 STAMP=1137664267
input archived log thread=1 sequence=28797 RECID=87151 STAMP=1137664438
input archived log thread=1 sequence=28798 RECID=87153 STAMP=1137664664
input archived log thread=1 sequence=28799 RECID=87155 STAMP=1137664813
channel ch2: starting piece 1 at 24-05-2023 10:00:14
channel ch2: finished piece 1 at 24-05-2023 10:05:49
piece handle=/mnt/oracle/rman/NETWINPRD/DIARIO_ARCH_NETWIN_P_b2lsuope_28002_1_1.bkp tag=DIARIO_ARCH_20230524_10H00 comment=NONE
channel ch2: backup set complete, elapsed time: 00:05:35
channel ch1: finished piece 1 at 24-05-2023 10:05:59
piece handle=/mnt/oracle/rman/NETWINPRD/DIARIO_ARCH_NETWIN_P_b1lsuope_28001_1_1.bkp tag=DIARIO_ARCH_20230524_10H00 comment=NONE
channel ch1: backup set complete, elapsed time: 00:05:45
Finished backup at 24-05-2023 10:05:59

Starting Control File and SPFILE Autobackup at 24-05-2023 10:05:59
piece handle=/mnt/oracle/rman/NETWINPRD/controlfile_NETWIN_P_c-3150329997-20230524-0b.bkp comment=NONE
Finished Control File and SPFILE Autobackup at 24-05-2023 10:06:02
released channel: ch1
released channel: ch2

RMAN> **end-of-file**

RMAN>

Recovery Manager complete.

 RMAN RETURN CODE : 0
```

Armazenar esta informação para posterior uso

!! DESCONECTAR DA PRODUÇÃO PARA EVITAR ERROS OPERACIONAIS !!

Conectar-se ao MIGS e validar se realmente está na homologação

```
export ORACLE_SID=MIGS
sqlplus / as sysdba <<EOF
show parameter name
EOF
```

Espera-se a seguinte saída do comando

```
NAME                           TYPE        VALUE
-------------------------------- ----------- ------------------------------
cdb_cluster_name                 string
cell_offloadgroup_name           string
db_file_name_convert             string
db_name                          string      MIGS
db_unique_name                   string      MIGS
global_names                     boolean     FALSE
instance_name                    string      MIGS
lock_name_space                  string
log_file_name_convert            string
pdb_file_name_convert            string
processor_group_name             string
service_names                    string      MIGS
```

Gerar o comando do asmcmd para realizar a exclusão dos arquivos de dados do ASM

```
sqlplus / as sysdba <<EOF
set lines 1000 pages 1000
select 'asmcmd rm -f ' || name from v\$datafile
union
select 'asmcmd rm -f ' || name from v\$tempfile where name != '+DATAC1'
union
select 'asmcmd rm -f ' || value from v\$parameter where name='control_files'
union
select 'asmcmd rm -f ' || value from v\$parameter where name like 'dg_broker_config_file%'
and value is not null
union
select 'asmcmd rm -f ' || member from v\$logfile
union
select 'asmcmd rm -f ' || replace(replace(VALUE,'TO ',''),'''','') from
v\$rman_configuration where name='SNAPSHOT CONTROLFILE NAME'
and value is not null;
EOF
```

Guardar a saída deste comando para posterior uso

Descer a instância do MIGs

```
srvctl stop database -d migs
```

or

```
sqlplus / as sysdba <<EOF
shutdown immediate;
EOF
```

Conectar-se com o usuário do grid e realizar o remove dos datafiles

```
su - grid
```

```
Exemplo:
#asmcmd rm -f +DATA/MIGS/CONTROLFILE/cntrlmigs.dbf, +RECO/MIGS/CONTROLFILE/cntrlmigs.dbf
#asmcmd rm -f +DATA/MIGS/DATAFILE/acc_fibrasil_database.280.1135364313
```

Iniciando o restore do ambiente

Subir o banco com os parâmetros de produção

```
export ORACLE_SID=NETWINPRD
sqlplus / as sysdba <<EOF
startup nomount pfile=/home/oracle/acndba/pfile_NETWIN.ora
EOF
```

Realizar o restore do controlfile e colocar o banco em estado mount

```
rman target /
```

```
run {
ALLOCATE CHANNEL disk1 DEVICE TYPE DISK FORMAT '/mnt/oracle/rman/NETWINPRD/*';
restore controlfile from '/mnt/oracle/rman/NETWINPRD/controlfile_NETWIN_P_c-3150329997-
20230516-0a.bkp';
release channel disk1;
 }
```

```
 alter database mount;
```

Realizar o restore do Banco

```
nohup rman target / trace restore_migs.log @/home/oracle/acndba/restore_migs.rman &
```

O arquivo restore_migs.rman contém o texto abaixo:

```
run {
ALLOCATE CHANNEL disk1 DEVICE TYPE DISK format '/mnt/oracle/rman/NETWINPRD/';
ALLOCATE CHANNEL disk2 DEVICE TYPE DISK format '/mnt/oracle/rman/NETWINPRD/';
ALLOCATE CHANNEL disk3 DEVICE TYPE DISK format '/mnt/oracle/rman/NETWINPRD/';
ALLOCATE CHANNEL disk4 DEVICE TYPE DISK format '/mnt/oracle/rman/NETWINPRD/';
ALLOCATE CHANNEL disk5 DEVICE TYPE DISK format '/mnt/oracle/rman/NETWINPRD/';
ALLOCATE CHANNEL disk6 DEVICE TYPE DISK format '/mnt/oracle/rman/NETWINPRD/';
restore database;
release channel disk1;
release channel disk2;
release channel disk3;
release channel disk4;
release channel disk5;
release channel disk6;
}
```

Realizar o recover do Banco

```
nohup rman target / trace recover_migs.log @/home/oracle/acndba/recover_migs.rman &
```

O arquivo recover_migs.rman contém o texto abaixo:

```
run {
ALLOCATE CHANNEL disk1 DEVICE TYPE DISK format '/mnt/oracle/rman/NETWINPRD/';
ALLOCATE CHANNEL disk2 DEVICE TYPE DISK format '/mnt/oracle/rman/NETWINPRD/';
ALLOCATE CHANNEL disk3 DEVICE TYPE DISK format '/mnt/oracle/rman/NETWINPRD/';
ALLOCATE CHANNEL disk4 DEVICE TYPE DISK format '/mnt/oracle/rman/NETWINPRD/';
ALLOCATE CHANNEL disk5 DEVICE TYPE DISK format '/mnt/oracle/rman/NETWINPRD/';
RECOVER DATABASE;
release channel disk1;
release channel disk2;
release channel disk3;
release channel disk4;
release channel disk5;
}
```

Validação do recover

Executar a seguinte query para validar o checkpoint time do header dos datafiles:

```
sqlplus / as sysdba <<EOF
set linesize 300
col file_name format a100
set pagesize 999
SELECT FILE# file_nr,
to_char(CHECKPOINT_TIME,'dd/mm/yyyy hh24:mi') checkpoint_time,
name file_name
from v$datafile_header;
EOF
```

Caso esteja de acordo com o horário do backup que foi realizado para o restore podemos prosseguir.

Realizando ajustes do ambiente MIGs

Abrir o banco com resetlogs

```
export ORACLE_SID=NETWINPRD
sqlplus / as sysdba <<EOF
alter database open resetlogs;
shutdown immediate;
EOF
```

Subir o ambiente com o novo instance name do MIGs

```
export ORACLE_SID=MIGS
sqlplus / as sysdba <<EOF
startup mount pfile=/home/oracle/acndba/pfile_NETWIN.ora
EOF
```

Realizar a troca do nome via NID

```
nid target=/ dbname=MIGS
```

Copiar o pfile para o Init do MIGS

```
cp /home/oracle/acndba/pfile_NETWIN.ora
/u01/app/oracle/product/19.0.0/dbhome_1/dbs/initMIGS.ora
```

No novo arquivo alterar o db_name para MIGS

***.db_name='NETWINPRD' → *.db_name='MIGS'**

Iniciar o database novamente com o init

```
sqlplus / as sysdba <<EOF
startup mount pfile=/u01/app/oracle/product/19.0.0/dbhome_1/dbs/initMIGS.ora
alter database open resetlogs;
create spfile from pfile;
EOF
```

Realizar o stop/start pela pilha do Oracle restart para utilizar o spfile

```
srvctl stop database -d migs
srvctl start database -d migs
```

Realizar a coleta de estatísticas do ambiente

```
sqlplus / as sysdba <<EOF
EXEC DBMS_STATS.GATHER_DICTIONARY_STATS(degree => 4, estimate_percent=> 100, CASCADE =>
TRUE);
EXEC DBMS_STATS.GATHER_DATABASE_STATS(degree => 4, estimate_percent=> 100, CASCADE =>
TRUE);
EOF
```

Caso seja solicitado, liberar o usuário MIGRAPTI após o refresh

```
alter user MIGRAPTI account unlock;
```

Observações gerais

- MANTER O ARCHIVE HABILITADO, VISTO QUE O CLIENTE UTILIZA A FEATURE DE FLASHBACK DATABASE

- CLIENTE NECESSITA QUE O AMBIENTE SEJA ATUALIZADO AO MENOS PARA O MESMO DIA DA DATA DE SOLICITAÇÃO, VISTO QUE O AMBIENTE É UTILIZADO COMO HOMOLOGAÇÃO DE MUDANÇAS DA APLICAÇÃO DO NETWIN