REFRESH MIGS

Localização dos Log dos backups de produção
/u01/app/oracle/backup/backups/NETWINPRD/log_backups

SQL> show parameter name

```
NAME                                 TYPE        VALUE
------------------------------------ ----------- ------------------------------
cdb_cluster_name                     string
cell_offloadgroup_name               string
db_file_name_convert                 string
db_name                              string      MIGS
db_unique_name                       string      MIGS
global_names                         boolean     FALSE
instance_name                        string      MIGS
lock_name_space                      string
log_file_name_convert                string
pdb_file_name_convert                string
processor_group_name                 string

NAME                                 TYPE        VALUE
------------------------------------ ----------- ------------------------------
service_names                        string      MIGS
```

1) Listar arquivos a serem apagados antes

```
set lines 1000 pages 1000
select 'asmcmd rm -f ' || name from v$datafile
union
select 'asmcmd rm -f ' || name from v$tempfile where name != '+DATAC1'
union
select 'asmcmd rm -f ' || value from v$parameter where name='control_files'
union
select 'asmcmd rm -f ' || value from v$parameter where name like 'dg_broker_config_file%' and value is not null
union
select 'asmcmd rm -f ' || member from v$logfile
union
select 'asmcmd rm -f ' || replace(replace(VALUE,'TO ',''),'''','') from v$rman_configuration where name='SNAPSHOT CONTROLFILE NAME'
and value is not null;
```

2) Descer a instancia

```
srvctl stop database -d migs
Ou
shutdown immediate
```

3) Conectar com usuário Grid e executar o resultado do passo 1.

Exemplo:

```
asmcmd rm -f +DATA/MIGS/CONTROLFILE/cntrlmigs.dbf, +RECO/MIGS/CONTROLFILE/cntrlmigs.dbf
asmcmd rm -f +DATA/MIGS/DATAFILE/acc_fibrasil_database.280.1135364313
asmcmd rm -f +DATA/MIGS/DATAFILE/docmanager.277.1135364313
asmcmd rm -f +DATA/MIGS/DATAFILE/migrapti_data_l.263.1135362205
asmcmd rm -f +DATA/MIGS/DATAFILE/migrapti_data_l.288.1135362205
.....
```

4) Exporta e subir o banco

```
export ORACLE_SID=NETWINPRD
sqlplus / as sysdba
startup nomount pfile=/home/oracle/acndba/pfile_NETWIN.ora
```

5) restaurar controlfile

O Ultimo controlfile pode ser pego via rman

```
        LIST BACKUP OF CONTROLFILE
    -- Restore controlfile
    run {
        ALLOCATE CHANNEL disk1 DEVICE TYPE DISK FORMAT '/mnt/oracle/rman/NETWINPRD/*';
        restore controlfile from '/mnt/oracle/rman/NETWINPRD/controlfile_NETWIN_P_c-3150329997-20230516-0a.bkp';
        release channel disk1;
      }
```

6) Subir o banco em mount

```
alter database mount;
```

7) Restore do banco

```
run {
ALLOCATE CHANNEL disk1 DEVICE TYPE DISK format '/mnt/oracle/rman/NETWINPRD/';
ALLOCATE CHANNEL disk2 DEVICE TYPE DISK format '/mnt/oracle/rman/NETWINPRD/';
ALLOCATE CHANNEL disk3 DEVICE TYPE DISK format '/mnt/oracle/rman/NETWINPRD/';
ALLOCATE CHANNEL disk4 DEVICE TYPE DISK format '/mnt/oracle/rman/NETWINPRD/';
ALLOCATE CHANNEL disk5 DEVICE TYPE DISK format '/mnt/oracle/rman/NETWINPRD/';
ALLOCATE CHANNEL disk6 DEVICE TYPE DISK format '/mnt/oracle/rman/NETWINPRD/';
restore database;
release channel disk1;
release channel disk2;
release channel disk3;
release channel disk4;
release channel disk5;
release channel disk6;
}
```

8) Recover do banco

```
  run {
ALLOCATE CHANNEL disk1 DEVICE TYPE DISK format '/mnt/oracle/rman/NETWINPRD/';
ALLOCATE CHANNEL disk2 DEVICE TYPE DISK format '/mnt/oracle/rman/NETWINPRD/';
ALLOCATE CHANNEL disk3 DEVICE TYPE DISK format '/mnt/oracle/rman/NETWINPRD/';
ALLOCATE CHANNEL disk4 DEVICE TYPE DISK format '/mnt/oracle/rman/NETWINPRD/';
ALLOCATE CHANNEL disk5 DEVICE TYPE DISK format '/mnt/oracle/rman/NETWINPRD/';
RECOVER DATABASE;
release channel disk1;
release channel disk2;
release channel disk3;
release channel disk4;
release channel disk5;
}
```

9) Executar os comandos abaixo

```
sqlplus / as sysdba
alter database open resetlogs;
shutdown immediate
export ORACLE_SID=MIGS
startup mount pfile=/home/oracle/acndba/pfile_NETWIN.ora
nid target=/ dbname=MIGS
cp /home/oracle/acndba/pfile_NETWIN.ora /u01/app/oracle/product/19.0.0/dbhome_1/dbs/initMIGS.ora
mudar o nome db_name do arquivo de init
    startup mount pfile=/u01/app/oracle/product/19.0.0/dbhome_1/dbs/initMIGS.ora
alter database open resetlogs; ( porque foi modificado o dbname)
create spfile from pfile;
```

10) Realizar stop/start para iniciar com spfile o banco

```
srvctl stop database -d migs
srvctl start database -d migs
```

11) Atualizar estatísticas do banco

```
EXEC DBMS_STATS.GATHER_DICTIONARY_STATS(degree => 4, estimate_percent=> 100, CASCADE => TRUE);
EXEC DBMS_STATS.GATHER_DATABASE_STATS(degree => 4, estimate_percent=> 100, CASCADE => TRUE);
```