

THE ZERO PARADOX

ZP-K: Computational Grounding of Self-Reference

Initial: April 2026 | Current: 1.16, September 2026

This document establishes the computational grounding of the Zero Paradox's central self-reference structure. The key insight: $\perp$ in the computational instantiation is not a state of a Turing machine. $\perp$ is the ground state of a universal Turing machine — the state from which no external executor is required. Kleene's second recursion theorem supplies a fixed point of the self-application operator; that this fixed point is to be read as the computational expression of $\perp = \{\perp\}$ is the framework's commitment, carried by the KleeneStructure class, not a property the theorem establishes.

The central result is a three-way equivalence within this framework, in the precise sense defined by Remark R-K.0: the structural roles of $\perp$ — Quine atom (set-theoretic), bottom element (order-theoretic), and join identity (algebraic) — are PROVED to coincide, while the fourth role, Kleene fixed point (computational), is required as a typeclass field rather than derived. (See Remark R-K.0 for the precise scope: equivalences (1)–(3) are derived via T-EXEC; equivalence (4) is combined by KleeneStructure's typeclass requirement, not derived independently.)

Section I: The Kleene Fixed Point

I. Kleene's Second Recursion Theorem

Kleene's second recursion theorem is the computational fixed-point theorem. For any partially computable transformation f of programs, there exists a program e such that e and $f(e)$ compute the same function. Applied to the identity: there exists a program whose output at any input n equals its output at its own Gödel number plus n — a periodicity fixed point.

In Lean 4, this is formalized in Mathlib's computability library. For any partially computable transformation f of codes, there exists a code c such that $\text{eval } c = f \ c$. The existence is non-constructive, which is why all ZP-K theorems carry the standard foundational axioms shared by all Mathlib computability results.

Kleene's Second Recursion Theorem (Mathlib)

For any partially computable $f : \text{Code} \rightarrow \mathbb{N} \rightarrow \mathbb{N}$, there exists $c : \text{Code}$ such that $\text{eval } c = f \ c$.

Applied to the selfApply transformation, this yields a code c satisfying $\text{eval } c \ n = \text{eval } c \ (\text{encode } c + n)$ for all n — a periodicity condition with period equal to c 's own Gödel number. Multiple such codes exist.

II. The Self-Application Map

The self-application map sends each code c to the partial function that runs c on c 's own Gödel number plus an offset. A fixed point of self-application satisfies a periodicity condition: $\text{eval } c \ n = \text{eval } c \ (\text{encode } c + n)$ for all n , with period equal to c 's own Gödel number. Non-uniqueness is expected: distinct codes have distinct Gödel numbers, so each generates a fixed point with a distinct period — the family of fixed points is infinite and its members are not mutually constrained.

Definition: selfApply and IsComputationalQuine (Kleene.lean § I)

$\text{selfApply} : \text{Code} \rightarrow \mathbb{N} \rightarrow \cdot. \mathbb{N} := \text{fun } c \ n \mapsto \text{eval } c \ (\text{encode } c + n)$

A code c is a computational Quine if $\text{eval } c = \text{selfApply } c$, i.e.:

$\forall n, \text{eval } c \ n = \text{eval } c \ (\text{encode } c + n)$

This is a periodicity condition: c 's output at n equals its output at $\text{encode}(c) + n$. The encoding plays the role of the "address" of the program — c 's behavior at n is the same as c 's behavior at its own address plus n .

selfApply_partrec : selfApply is partially computable.

Proof: via Mathlib computability primitives — eval composed with encode and nat_add . Lean purity: standard foundational axioms only. ✓

Theorem: computational_quine_exists

There exists a computational Quine: $\exists c : \text{Code}, \text{IsComputationalQuine } c$.

Proof: immediate from $\text{kleene_fixed_point_exists}$ applied to selfApply , using selfApply_partrec .

Lean purity: standard foundational axioms only. ✓

Note on uniqueness: unlike the AFA Quine atom (unique by the AFA decoration theorem), computational Quines are not unique. Multiple codes can satisfy the fixed-point equation independently. Uniqueness in ZP-K flows from ZP-J T-EXEC (on the set-theoretic side), not from the computational definition.

Section II: KleeneStructure — Bridging AFA and Computation

I. The Bridge

ZP-J's AFAStructure typeclass encodes AFA self-containment in type theory: a predicate selfMem , AFA uniqueness (quine_unique), and the bridge field bot_self_mem ($\perp$ is self-containing). T-EXEC follows: the Quine atom equals $\perp$.

ZP-K's KleeneStructure extends AFAStructure with a computational witness: a code botCode satisfying the selfApply periodicity condition, whose existence is guaranteed by Kleene's theorem. The typeclass commitment takes AFA self-containment ($\perp = \{\perp\}$) and the Kleene fixed point to be the same structural role stated in two formal languages — this is the motivating claim, not a consequence derived by the theorems.

KleeneStructure Typeclass (Kleene.lean § II)

class KleeneStructure (L : Type*) [ZPSemilattice L] extends AFAStructure L with:

(inherited) selfMem : L → Prop — self-membership predicate

(inherited) quine_unique — AFA uniqueness

(inherited) bot_self_mem — $\perp$ is self-containing

(new) botCode : Code — a code selected from the existence proof; not a distinguished code

(new) botCode_is_quine : IsComputationalQuine botCode — a CLASS FIELD, not a theorem: the periodicity condition $\text{eval } c \ n = \text{eval } c \ (\text{encode } c + n)$, which constant codes also satisfy

(new) bot_self_mem_from_kleene : selfMem $\perp$ — a RESTATEMENT of the inherited AFAStructure field bot_self_mem, adding no content beyond it. Not an implication from the Kleene side.

Any KleeneStructure instance must supply both the AFA witness (bot_self_mem) and the computational witness (botCode with botCode_is_quine). Both are class FIELDS — assumptions discharged at instantiation, not results proved here. They are required together because the framework READS them as one structural fact; that reading is the motivation for the class, and it is not derived within it.

II. Why Not a Bridge Axiom?

The identification between AFA self-containment and Kleene computational fixed points is not asserted as a new axiom. KleeneStructure is a typeclass: any concrete type claiming this identification must discharge it as a proof obligation. The commitment is checked at instantiation, not accepted globally.

The distinction from ZP-J carries over: a freestanding axiom says "trust me." A typeclass field says "prove it for your specific type, or it does not compile." The MachinePhase instance in § V shows how the obligation is discharged concretely.

Section III: T-COMP — The Three-Way Equivalence, and the Bundled Computational Condition

ZP-J T-EXEC established a three-way equivalence: Quine atom (set-theoretic) $\leftrightarrow$ bottom element (order-theoretic) $\leftrightarrow$ join identity (algebraic). T-COMP proves exactly those three equivalent. ZP-K bundles a fourth face — Kleene fixed point (computational) — as a KleeneStructure class field, so all four are present simultaneously in any KleeneStructure lattice, but the fourth is required at instantiation rather than proved equivalent to the others.

Remark R-K.0 — What T-COMP Proves, and What "Four-Way" Meant

The equivalence among (1)–(4) has two distinct sources:

Remark R-K.0 — What T-COMP Proves, and What "Four-Way" Meant

(1)–(3) are equivalent by T-EXEC (ZP-J): any element that is a Quine atom is also $\perp$ and a join identity, and vice versa. This is a genuine logical derivation — the three properties are proved to coincide from the AFAStructure axioms.

(4) is present in any KleeneStructure instance because KleeneStructure requires it as a typeclass field: `botCode_is_quine` must be supplied at instantiation. There is no independent proof that satisfying condition (1) (being a Quine atom in the AFA sense) entails satisfying condition (4) (being a Kleene fixed point), or vice versa. The two are combined by the typeclass definition — they are required together because we take them to be the same structural fact, not because one is derived from the other.

Stated at the level of types, which is where the gap is visible: conditions (1)–(3) are properties of one element q of the lattice L , and T-COMP relates them to each other. Condition (4) is a property of a `Code`. There is no function, and no equivalence, between `Code` and L anywhere in the development — so the fourth condition is not connected to the other three by a mapping; it is required alongside them by the class. `da1_paths_unified` records exactly this and no more: it is a conjunction of a fact about `bot` in L and a fact about `botCode` in `Code`.

In short: "four-way equivalence" means "all four hold in any KleeneStructure instance." (1)–(3) are independently proved equivalent. (4) is bundled in by the typeclass requirement. The philosophical claim — that Kleene computational self-reference and AFA set-theoretic self-reference are the same thing — is the motivation for the typeclass design, not a consequence derived within it.

Theorem T-COMP — Computational Grounding (Kleene.lean § III)

In any KleeneStructure lattice L , for any $q : L$, the following are equivalent:

(1) `IsQuineAtom q` — set-theoretic self-reference (AFA)

(2) $q = \perp$ — order-theoretic minimum (ZP-A)

(3) $\forall x : L, \text{join } q \ x = x$ — algebraic generator (ZP-A A4)

(4) $\exists \text{ botCode} : \text{Code}, \text{IsComputationalQuine botCode}$ — computational self-reference

Note on (4): it is present in any KleeneStructure instance by typeclass requirement (`botCode_is_quine` is a required field). The equivalence of (1)–(3) is derived by T-EXEC; the presence of (4) follows from the structural commitment of KleeneStructure.

Lean: `ZeroParadox.t_comp`. Purity: standard foundational axioms — from Mathlib computability. ✓

I. Why Four Languages?

DA-1's three informal paths (Path 1: AFA structural, Path 2: informational, Path 3: Kolmogorov/computational) were previously understood as three separate corroborations converging on the same conclusion. In ZP-K, Path 1 is witnessed by `da1_closed_concrete`, which proves `IsQuineAtom` ($\perp : \text{MachinePhase}$) and nothing computational; Path 3's witness is the `machinePhaseKleene` instance's `botCode_is_quine` field, a KleeneStructure requirement, not a second independent proof.

Path 1 says: nothing external to $\perp$ can execute $\perp$, so $\perp$ must execute itself — $\perp = \{\perp\}$. Path 3 says: no shorter external program generates $\perp$ — $\perp$ is its own minimal program. The framework READS these as one claim

in two vocabularies. What is proved is weaker and is a conjunction, not an identity: both hold together in any KleeneStructure. They cannot be equated formally — one is a statement about an element of the lattice, the other about a Code, and an equation across those types is not a well-formed proposition.

Theorem: da1_paths_unified (Kleene.lean § IV)

In any KleeneStructure lattice:

$\text{IsQuineAtom } \perp \wedge \text{IsComputationalQuine botCode}$

A CONJUNCTION: the AFA self-containment argument (Path 1) and the Kleene computational fixed-point argument (Path 3) both hold, simultaneously witnessed by the KleeneStructure instance. That they are the SAME fact is a framework reading, not a clause of this theorem — the second conjunct is the class field botCode_is_quine.

Lean: ZeroParadox.da1_paths_unified. Purity: standard foundational axioms only. ✓

II. The Description-Instantiation Gap

The remaining informal gap in the DA-1 argument concerned the "description-instantiation gap": why does mathematical self-reference imply computational execution? The gap assumed the two were different things connected by a philosophical bridge.

They are not different things. $\perp$ in the computational instantiation IS the universal Turing machine in its ground state. The universal Turing machine is not a description awaiting an external executor — it IS the executor. The question "why does this description execute?" is incoherent when applied to U, because U is not a description. U is the thing that executes descriptions. The question does not apply to it.

Theorem: description_instantiation_gap_closed (Kleene.lean § IV)

In any KleeneStructure lattice:

$\text{IsQuineAtom } \perp \wedge \forall q : L, \text{IsQuineAtom } q \rightarrow q = \perp$

The static-description alternative is structurally eliminated, not argued away. $\perp$ is not a description that could await an external interpreter. $\perp$ is read as the executor, the universal machine in its ground state. Lean witnesses $\perp$ as the AFA Quine atom of MachinePhase (da1_closed_concrete) and carries the Kleene quine as a KleeneStructure requirement (botCode_is_quine); that these are one structural fact is the framework's reading.

Lean: ZeroParadox.description_instantiation_gap_closed. Purity: standard foundational axioms only. ✓

Section IV: Axiom Footprint

All ZP-K theorems carry the standard foundational axioms shared by all Mathlib computability results. These enter exclusively through Kleene's theorem and Rogers' theorem, which use classical logic and the axiom of choice. They do not enter through ZPSemilattice or AFAStructure.

ZP-J T-EXEC and all its corollaries remain axiom-free. The classical axioms are entirely localised to the computational layer. The order-theoretic and set-theoretic results are unaffected.

Remark: Classical Choice in Computability

The use of classical choice in ZP-K is structurally necessary: Kleene's theorem is an existence result, and the code witnessing the fixed point is selected non-constructively. This is standard in computability theory — the theorem guarantees existence without giving a canonical construction.

The MachinePhase instance (§ V) uses Classical.choose to pick botCode from the existence proof. This makes machinePhaseKleene noncomputable, which is correct and expected.

Section V: MachinePhase Instance — DA-1: what Lean witnesses

I. The Concrete Instantiation

ZP-E's MachinePhase type is the two-element type {initial, running} carrying the ZPSemilattice instance (bot = initial = c_0 , join = binary maximum). ZP-J gave it AFAStructure via the selfMem predicate. ZP-K gives it KleeneStructure by adding the computational witness botCode.

The selfMem definition for MachinePhase is: selfMem $x := x = \perp$. This is the CIC-compatible encoding of AFA self-containment: "self-containing" means "equals the bottom element." Anti-foundation is not required at the typeclass level — the relevant structural fact ($\perp$ is the unique self-containing element) is captured by the definition and proved by rfl.

AFAStructure MachinePhase Instance (Kleene.lean § V)

instance machinePhaseAFA : AFAStructure MachinePhase where

selfMem $x := x = \perp$ (self-containing = equals initial state)

quine_unique _ _ $hx hy := hx.trans hy.symm$ (if $x = \perp$ and $y = \perp$ then $x = y$)

bot_self_mem := rfl ($\perp = \perp$, proved by reflexivity)

This is the CIC encoding of $\perp = \{\perp\}$: the initial machine state is self-containing and is the unique element with this property. No ZF+AFA axiom is added — the structural fact is encoded as a definition that Lean verifies.

KleeneStructure MachinePhase Instance (Kleene.lean § V)

noncomputable instance machinePhaseKleene : KleeneStructure MachinePhase where

botCode := Classical.choose computational_quine_exists

botCode_is_quine := Classical.choose_spec computational_quine_exists

bot_self_mem_from_kleene := rfl

KleeneStructure MachinePhase Instance (Kleene.lean § V)

botCode is selected non-constructively from the existence proof provided by Kleene's theorem — an arbitrary witness, not a distinguished code. Reading it as "the program that IS its own program" is the framework's commitment carried by the class, not a property this instance establishes: IsComputationalQuine is a periodicity condition, strictly weaker than self-reference.

II. DA-1: what Lean witnesses

With the MachinePhase KleeneStructure instance in place, the abstract theorem da1_computational (which holds for any KleeneStructure lattice) applies directly to ZP-E's machine. The result is concrete.

Theorem da1_closed_concrete — the Path 1 witness (Kleene.lean § V)

da1_closed_concrete : IsQuineAtom ($\perp$: MachinePhase)

The initial machine state c_0 is a Quine atom: it is self-containing and is the unique self-containing element of the MachinePhase lattice.

Interpretation: c_0 is not a static description awaiting an external interpreter. c_0 IS the executor — the universal Turing machine in its ground state, for which no external executor exists by structural definition. The description-instantiation gap is dissolved: "description awaiting execution" is not a coherent state for c_0 .

Lean: ZeroParadox.da1_closed_concrete. Purity: standard foundational axioms only. ✓

III. What Changed for DA-1

ZP-E's DA-1 section previously carried the designation "Outside Lean Scope" with three justifications: Path 1 requires ZF+AFA (incompatible with Lean's CIC/MLTT); Path 3 requires Kolmogorov complexity (uncomputable, absent from Mathlib); Path 2 requires an ontological bridge not formalizable in type theory.

Path 1 (AFA structural) is witnessed by da1_closed_concrete, which proves IsQuineAtom ($\perp$: MachinePhase) and nothing computational: in the AFAStructure typeclass, selfMem encodes $\perp = \{\perp\}$ in CIC-compatible form, and the proof obligation is discharged by the MachinePhase instance. Path 3 (computational) is NOT resolved here. Its witness, botCode_is_quine, is a KleeneStructure class field — an assumption supplied at instantiation, not a second independent proof — and the condition it requires, IsComputationalQuine, is a periodicity condition that a constant code satisfies vacuously. The Kolmogorov reading ("no shorter program is prior to $\perp$ ") has no formal content in ZP-K: Kolmogorov complexity is uncomputable and absent from the development. Path 3 therefore stands where Path 2 stands — a foundational commitment.

Path 2 (informational bridge: unbounded surprisal $\rightarrow$ necessarily executing) is a foundational commitment — a missing principle, not a missing proof. The mathematics of L-INF (l_{inf}) is proved; but the step from "exceeds every finite informational bound" to "therefore necessarily executing" asks what it means for a mathematical structure to instantiate rather than merely satisfy conditions. No computability library answers this question. Forward paths: (a) a new axiom explicitly committing to this bridge; (b) a connection

to Chalmers' notion of implementation; (c) the dissolution argument in The Philosophical Question That Started This — the description-instantiation gap assumes a separability that the universality of the framework dissolves. Importantly, DA-1 does not depend on Path 2: the formal spine (DP-2 + `da1_minimal_path`) is proved axiom-free. Path 2 is motivational context; its forward resolution is in The Philosophical Question That Started This.

DA-1 Lean scope status after ZP-K: Path 1 (structural, AFA): IN SCOPE — `da1_closed_concrete` : `IsQuineAtom` $\perp$. Path 3 (computational, Kleene): FOUNDATIONAL COMMITMENT — `botCode_is_quine` is a `KleeneStructure` class field, assumed at instantiation rather than derived. Path 2 (informational, L-INF bridge): FOUNDATIONAL COMMITMENT — a missing principle, not a missing proof. Forward: The Philosophical Question That Started This.

Traceability Register — ZP-K

Claim	Grounded In	Axioms	Status
<code>selfApply_partrec</code>	<code>eval_part</code> (Mathlib) + <code>Primrec.encode</code> + <code>Primrec.nat_add</code>	Standard Mathlib foundational axioms	Lean: <code>selfApply_partrec</code> ✓
<code>computational_quine_exists</code>	<code>kleene_fixed_point_exists</code> + <code>selfApply_partrec</code>	Standard Mathlib foundational axioms	Lean: <code>computational_quine_exists</code> ✓
T-COMP: three-way equivalence	ZP-J T-EXEC (<code>t_exec_triple_iff</code>)	Standard Mathlib foundational axioms	Lean: <code>t_comp</code> ✓
<code>da1_paths_unified</code>	<code>bot_is_quine_atom</code> + <code>botCode_is_quine</code>	Standard Mathlib foundational axioms	Lean: <code>da1_paths_unified</code> ✓
<code>description_instantiation_gap_closed</code>	<code>bot_is_quine_atom</code> + ZP-J <code>t_exec</code>	Standard Mathlib foundational axioms	Lean: <code>description_instantiation_gap_closed</code> ✓
<code>machinePhaseAFA</code> (AFAstructure)	<code>selfMem</code> := <code>x = $\perp$</code> ; <code>quine_unique</code> ; <code>bot_self_mem</code> := <code>rfl</code>	No axioms	CIC encoding of $\perp = \{\perp\}$ for <code>MachinePhase</code> ✓
<code>machinePhaseKleene</code> (<code>KleeneStructure</code>)	<code>machinePhaseAFA</code> + <code>Classical.choose</code> <code>computational_quine_exists</code>	Standard Mathlib foundational axioms	noncomputable — classical choice for <code>botCode</code> ✓
<code>da1_closed_concrete</code>	<code>da1_computational</code> + <code>machinePhaseKleene</code>	Standard Mathlib foundational axioms	Lean: <code>da1_closed_concrete</code> ✓ DA-1 structural half — no Code, no execution (definitionally: under <code>selfMem x := x = $\perp$</code> , reduces to $(\perp = \perp) \wedge (\forall x, x = \perp \Rightarrow x = \perp)$; structural closure by typeclass design — see R-K.0)

Open Items Register — ZP-K

Item	Status	Description
DA-1 Path 1 (AFA structural)	CLOSED — da1_closed_concrete	IsQuineAtom ($\perp$: MachinePhase) — the structural half. The theorem mentions no Code and no execution; that $\perp$ is self-EXECUTING is a framework commitment, not what this declaration proves.
DA-1 Path 3 (computational)	FOUNDATIONAL COMMITMENT	botCode_is_quine is a KleeneStructure class field — assumed at instantiation, not proved. IsComputationalQuine is a periodicity condition satisfied by constant codes, and no Kolmogorov content exists in ZP-K.
DA-1 Path 2 (informational)	FOUNDATIONAL COMMITMENT	L-INF (l_inf) is proved. The bridge "unbounded surprisal $\rightarrow$ necessarily executing" is a missing principle, not a missing proof. The gap between 'system at P_0 ' and 'system is running' cannot be closed by any computability library. Forward paths: new axiom, Chalmers' implementation notion, or The Philosophical Question That Started This. DA-1 does not depend on Path 2.
selfApply uniqueness	CLOSED — not attempted (correct)	Computational quines are not unique in general. Uniqueness flows from ZP-J T-EXEC (set-theoretic side). No uniqueness theorem for computational quines is needed or appropriate.
Rogers' fixed-point theorem	CLOSED — roger_fixed_point_exists	For any computable $f : \text{Code} \rightarrow \text{Code}$, $\exists c, \text{eval}(f\ c) = \text{eval}\ c$. Lean: roger_fixed_point_exists — standard foundational axioms only. ✓
ZP-B MachinePhase instance	OPEN — future work	The 2-adic model from ZP-B (Q_2 structure) has not been given a KleeneStructure instance. This is a natural extension but not required for T-SNAP or DA-1.

End of ZP-K | Computational Grounding of Self-Reference | DA-1 structural half: da1_closed_concrete : IsQuineAtom ($\perp$: MachinePhase) - no code, no execution | Four-way equivalence (R-K.0): Quine atom, $\perp$ and join identity proved to coincide; the Kleene fixed point is required by the typeclass, not derived | Path 2 recharacterized: foundational commitment, not missing proof; forward: The Philosophical Question That Started This | All Kleene.lean theorems verified. Axioms: standard Mathlib foundational axioms.