THE ZERO PARADOX

ZP-P: The Fixed-Point Fork

Initial: June 2026 | Current: 1.26, October 2026

Synthesis layer. The abstract fork schema is proved sorry-free and choice-free in Lean 4 (FixedPointFork.lean); the number-system instance via Ostrowski (Ostrowski.lean) and the categorical-parent instance via QPF.Fix / QPF.Cofix (Coalgebra.lean) are Lean-witnessed; the set-theory and computation instances are referenced to ZP-J and ZP-K. Generalizes the ZFC+Foundation / ZFC+AFA orthogonal-contact-point claim.

A monotone self-map of a complete lattice has a least fixed point and a greatest fixed point (Knaster–Tarski); monotonicity is required. Whether the framework's own self-referential operators instantiate that schema is not claimed here — see the fences in Section III. ZP-P records a single elementary fact and develops its consequences across the framework: these two fixed points coincide — the fork collapses to one point — exactly when the operator has a unique fixed point. Read intuitively, the least fixed point is the inductive (well-founded) closure and the greatest is the coinductive (non-well-founded) closure; the collapse point is where the two closures meet. In the Zero Paradox that point is the diagonal fixed point $\bot$, the self-containing bottom.

This layer is a synthesis layer, not a foundational one: it adds no axiom or primitive. It names a pattern that several existing layers already realise, and it is organised in three tiers held to three different standards of proof. Tier 1 (Section I) is the abstract schema, proved in Lean over a complete lattice. Tier 2 (Section II) is the instance catalogue: each framework forks at its own contact point, and the instances are theorems in their home layers. Tier 3 (Section III) is the unification — that the contact points are faces of one object — which is a fenced conjecture, never a formal claim. The fences in Section III are load-bearing: keeping the tiers separate is what makes the formal content honest.

Section I: The Fork Schema (Tier 1)

Over a complete lattice, a monotone self-map f has a least fixed point (lfp f) and a greatest fixed point (gfp f), and lfp f $\leq$ gfp f always. The width between them is the fork. The schema theorem states that the fork collapses to a single point precisely when f has a unique fixed point — and in that case the common value is that fixed point. The proofs rest only on Mathlib's order-theoretic fixed-point API (OrderHom.lfp / OrderHom.gfp); they make no claim about the categorical inductive/coinductive reading, which is offered as analogy only.

Definition: the fork (FixedPointFork.lean)
For a complete lattice α and a monotone self-map $f : \alpha \to \alpha$:
lfp f = the least fixed point of f (Mathlib OrderHom.lfp)
gfp f = the greatest fixed point of f (Mathlib OrderHom.gfp)

Definition: the fork (FixedPointFork.lean)

The fork is the ordered pair (lfp f, gfp f), always satisfying lfp f ≤ gfp f.

Collapse = lfp f = gfp f: the two ends meet at a single contact point.

Proposition: fork_le (FixedPointFork.lean)

lfp f ≤ gfp f

The inductive closure never exceeds the coinductive closure: the fork has non-negative width. (Mathlib OrderHom.lfp_le_gfp.)

Lean purity: [propext, Quot.sound] — choice-free. ✓

Lemma: collapse_of_unique (FixedPointFork.lean)

If x is the unique fixed point of f, then lfp f = x and gfp f = x.

Both ends of the fork land on the sole fixed point.

Proof: lfp f and gfp f are fixed points (map_lfp, map_gfp); uniqueness sends each to x.

Lean purity: [propext, Quot.sound] — choice-free. ✓

Lemma: unique_of_collapse (FixedPointFork.lean)

If lfp f = gfp f, then every fixed point of f equals that common value.

Every fixed point lies between lfp f and gfp f, so collapse forces uniqueness.

Proof: lfp_le_fixed and le_gfp bracket any fixed point y; antisymmetry closes it.

Lean purity: [propext, Quot.sound] — choice-free. ✓

Theorem: fork_collapse_iff (FixedPointFork.lean) — the schema spine

lfp f = gfp f ↔ ∃! x, f x = x

The fork collapses to a single contact point if and only if f has a unique fixed point.

This is the abstract form of "the framework forks, and the diagonal fixed point is where the two closures meet."

Proof: collapse_of_unique and unique_of_collapse, both directions.

Lean purity: [propext, Quot.sound] — choice-free. ✓

The fork spine is choice-free. All four results depend only on [propext, Quot.sound] — propositional extensionality and quotient soundness, two of Lean's standard axioms, used throughout Mathlib. None depends on the Axiom of Choice. This is consistent with the choice-free core (see ZeroParadox/AxiomProfile.lean): the conceptual skeleton needs no choice; choice enters mostly in the analytic realisations (that file's § III) — not only there, since the framework also carries bare classicals of its own; ZeroParadox/Category/ChoiceCannotBe.lean § IV collects cases among them whose principles reduce to a taboo, with those reductions.

Section II: The Instance Catalogue (Tier 2)

The same fork appears across frameworks. ZP-P does not re-prove each instance — each is a theorem in its home layer — it records the catalogue and pins the number-system instance to a checkable Lean witness. The original ZFC+Foundation / ZFC+AFA orthogonal-contact-point claim is the set-theory entry: in the standard category-theoretic characterisation (Aczel; Lambek), Foundation is the initial algebra (μ) and AFA the final coalgebra (ν) of the bounded powerset functor, and the Quine atom $\bot = \{\bot\}$ is exactly an element present in ν but not in μ.

Domain	The two closures fork into	Contact point / home layer
Set theory	Foundation (μ, well-founded) vs AFA (ν, non-well-founded)	Quine atom $\bot = \{\bot\}$; ZP-J / ZP-K
Number systems	Archimedean $\mathbb{R}$ vs non-Archimedean $\mathbb{Q}_p$	0 (snap fails in $\mathbb{R}$, holds in $\mathbb{Q}_2$); ZP-B / ZP-F
Computation	total (well-founded) vs partial (non-terminating)	the Kleene quine / self-application; ZP-K
Category theory	initial algebra (W-types) vs final coalgebra (M-types)	QPF.Fix vs QPF.Cofix; Coalgebra.lean

The number-system instance is the one with a genuine classification theorem behind it. Ostrowski's theorem says the nontrivial absolute values on $\mathbb{Q}$ are exactly the real (Archimedean) one and the p-adic (non-Archimedean) ones — the complete, pairwise-inequivalent list. The contact point is 0: in the Archimedean completion $\mathbb{R}$ it is approached but never reached (density — the snap fails), while in the 2-adic completion $\mathbb{Q}_2$ it is the unique fixed point of $x \mapsto 2x$ and its valuation diverges ($v_2(0) = \infty$ — the snap holds).

Theorem: completions_exhaustive (Ostrowski.lean)

Every nontrivial absolute value on $\mathbb{Q}$ is equivalent to the real absolute value, or to a p-adic absolute value for a unique prime p.

The two kinds of completion are the complete list. (Ostrowski's theorem, Mathlib Rat.AbsoluteValue.equiv_real_or_padic.)

Lean purity: [propext, Classical.choice, Quot.sound] — choice-carrying. ✓

Theorem: real_not_equiv_padic (Ostrowski.lean)

The real absolute value is inequivalent to every p-adic absolute value.

Theorem: real_not_equiv_padic (Ostrowski.lean)

The two kinds of completion are genuinely distinct — never the same metric. This is the orthogonality leg of the number-system fork. (Mathlib Rat.AbsoluteValue.not_real_isEquiv_padic.)

Lean purity: [propext, Classical.choice, Quot.sound] — choice-carrying. ✓

Remark: choice-free spine, choice-carrying realisation

The fork spine (Section I) is choice-free [propext, Quot.sound]. The Ostrowski instance carries Classical.choice, inherited from Mathlib's classical analysis and number theory. This split is the framework's standing pattern: the conceptual core is choice-free, while the analytic realisations are choice-carrying.

The number-system fork is theorem-backed on its own terms — Ostrowski is a genuine classification theorem, stronger backing than the metatheoretic Foundation/AFA orthogonality. It is NOT claimed to be an instance of the μ/ν (least-vs-greatest fixed point) schema: Ostrowski concerns absolute values, not fixed points of a functor. The thread to the diagonal fixed point runs through the contact point 0 (the unique fixed point of $x \mapsto 2x$ in $\mathbb{Q}_2$), not through the schema theorem.

The categorical instance is the genuine μ/ν case — the parent of the set-theory entry. On a one-shape, one-child polynomial functor (no leaf), the initial algebra (W-type, μ) is empty while the final coalgebra (M-type, ν) is inhabited by the infinite self-referential element: the non-well-founded closure contains a point the well-founded closure lacks — the categorical analog of the Quine atom present in νF but not μF.

Theorem: categorical_fork_strict (Coalgebra.lean)

IsEmpty (Fix idPF_Coalgebra.Obj) ∧ Nonempty (Cofix idPF_Coalgebra.Obj)

The initial algebra (least fixed point, μ) is empty; the final coalgebra (greatest fixed point, ν) is inhabited. (Mathlib QPF.Fix / QPF.Cofix.)

Split footprint: fix_isEmpty (μ empty) is choice-free [propext, Quot.sound]; cofix_nonempty (ν inhabited) carries Classical.choice from the QPF corecursion machinery — a QUOTIENT-LAYER artifact: QPF.Cofix carries the choice in the TYPE. The M-type FORMER and constructors are axiom-free while the M-type DESTRUCTOR (M.children / M.dest) is not — that is where the axiom originates — and strict_cofix_nonempty proves the same inhabitation over the M-type with no axioms, by only building. For a polynomial functor the final coalgebra is constructible choice-free (Ahrens–Capriotti–Spadotti, TLCA 2015). ✓

Remark: where choice appears in the μ/ν fork

The Classical.choice in cofix_nonempty is a library dependency, not a fact about the mathematics, and it is worth locating exactly. Measured: the M-type former and its constructors are axiom-free (PFunctor.M, M.mk, M.corec), while its destructor carries the axiom (M.children, M.dest) — and QPF.Cofix inherits it in the type through the congruence it quotients by. That is why strict_cofix_nonempty is axiom-free: it only builds, and never destructs. For a polynomial functor the final coalgebra is constructible choice-free (Ahrens–Capriotti–Spadotti, TLCA 2015, who construct it as an ω-limit). Their ambient setting is intensional type theory with univalence, but the construction itself uses only function extensionality — univalence enters only for their uniqueness result.

Remark: where choice appears in the μ/ν fork

The finite-powerset functor is a different case — it is not polynomial, and the argument above does not cover it. It is also not this document's subject. The per-presentation detail there, with citations, is recorded in the Lean source (Coalgebra.lean) and is deliberately not restated here.

The remaining two instances are referenced, not re-proved here. The set-theory fork (Foundation vs AFA) has its Lean witness in ZP-J: quine_atom_unique proves that any two Quine atoms are equal — a uniqueness statement about self-MEMBERSHIP in the sense $x = \{x\}$, a set that is its own sole member. Bare self-membership is not unique under AFA: $0^* = \{\emptyset, 0^*\}$ also contains itself (Aczel 1988, Example 1.5). That the bottom is one of them is a separate result (bot_is_quine_atom), and self-APPLICATION is a third (selfApp_pinnable, in the experimental Lawvere bridge rather than ZP-J proper). The computation fork (total vs partial) has its Lean witness in ZP-K: the Kleene quine. Each is the contact point of its own fork.

Section III: The Unification and Its Fences (Tier 3)

The tempting claim is that the contact points of all the instances — the Quine atom, the 2-adic 0, the Kleene quine, the self-referential element of the final coalgebra — are faces of one object, the diagonal fixed point. ZP-P states this as a conjecture and fences it precisely. The fences are not hedging; they mark a genuine boundary, and per-instance forks remain full theorems on either side of them.

Hard fence (permanent): cross-instance identity is not a theorem

The claim "the contact points are one object" is not a theorem and cannot become one. Identity requires a shared type: the 2-adic 0, the Quine atom (a set), the Kleene quine (a code), and an element of a final coalgebra (an object up to isomorphism) are terms of different types in different categories. The proposition "$x = y$" across them is not false — it is not well-formed. So this is a type boundary, not a missing proof. What is claimed formally is only that each framework forks at its own contact point.

Soft fence (conjecture): not every fork is a μ/ν instance

That every domain fork is an instance of the least-vs-greatest fixed point schema is an open generalisation, not established here. The schema is a theorem in this layer and for canonical functors (W-types vs M-types). The number-system fork (Ostrowski) is the clear case that is theorem-backed yet NOT visibly a μ/ν instance — it is the live caution against overstating the generalisation.

Per-instance forks are theorems and are not hedged. The fences scope only the cross-instance identity (Tier 3) and the universal schema claim. Each individual fork — Foundation/AFA, $\mathbb{R}/\mathbb{Q}_2$, total/partial — stands on its own proof.

Theorem Summary

Result	File / Section	Axioms
fork_le	FixedPointFork.lean §I	choice-free
collapse_of_unique	FixedPointFork.lean §I	choice-free
unique_of_collapse	FixedPointFork.lean §I	choice-free
fork_collapse_iff	FixedPointFork.lean §I	choice-free
completions_exhaustive	Ostrowski.lean §II	Classical.choice
real_not_equiv_padic	Ostrowski.lean §II	Classical.choice
fix_isEmpty	Coalgebra.lean §II	choice-free
cofix_nonempty	Coalgebra.lean §II	Classical.choice

Axiom Purity
Fork spine (FixedPointFork.lean): [propext, Quot.sound] — choice-free. The schema needs no Axiom of Choice.
Number-system instance (Ostrowski.lean): [propext, Classical.choice, Quot.sound] — Classical.choice inherited from Mathlib's classical analysis / number theory (Ostrowski).
Categorical instance (Coalgebra.lean): split — fix_isEmpty (μ empty) is choice-free [propext, Quot.sound]; cofix_nonempty (ν inhabited) carries Classical.choice from the QPF corecursion machinery (the quotient layer).
Core choice-free, realisation choice-carrying — the framework's standing pattern. Zero sorry. Verified: lake build, August 2026.

End of ZP-P | The Fixed-Point Fork | fork_collapse_iff (choice-free spine) | Ostrowski number-system instance | categorical μ/ν instance (Fix empty / Cofix inhabited) | hard fence: cross-instance identity is a type boundary | soft fence: not every fork is μ/ν | All FixedPointFork.lean / Ostrowski.lean / Coalgebra.lean theorems verified.