# BlueSen Series

NEW

KAC80DP2 / KAC100DP2 / KAC110DP2 / KAC125DP2
BC197DE2 / BC215DE2 / BC233DE2

## Versatile Application

- Ideal for factories, hotels, and farms with DC / AC-coupled solar-storage
- No external switching device is required, on/off-grid switching time about 10ms, support direct output backup load

## Safe & Reliable

- 280ah large capacity cell, higher energy density
- Carbon monoxide detection, Sound and light alarm, Exhaust fan, Explosion vent window, Inlet valve, Fire water injection port

## Smart Energy

- Supports self-consumption, peak shifting, time-of-use, and battery backup
- Integrated self-developed BMS / EMS for flexibility

## High Performance

- Small size, small footprint
- Long-lasting battery cycle life

## Easy Operation

- Compact design saves space
- Cloud control with 24 / 7 monitoring

### Outdoor Battery Cabinet Parameters

| Technical Parameters | BC197DE2 | BC215DE2 | BC233DE2 |
|---|---|---|---|
| Battery Type | LFP | | |
| Battery Module Capacity | 17.92 kWh | | |
| Cell Type | 280 Ah | | |
| Number of Modules | 11 | 12 | 13 |
| Total Battery Capacity | 197.12 kWh | 215.04 kWh | 232.96 kWh |
| Nominal Voltage | 704 V | 768 V | 832 V |
| Operating Voltage Range | 627 ~ 792 V | 684 ~ 864 V | 741 ~ 936 V |
| Charge / Discharge Rate | 0.5 C | | |
| DoD | 90% | | |
| **General Parameters** | | | |
| Dimensions (W x H x D) | 1324 x 2415 x 1440 mm | | |
| Weight | < 2.4 T | < 2.55 T | < 2.7 T |
| Installation Site | Outdoor | | |
| IP Protection | IP54 | | |
| Anti Corrosion Level | C4 | | |
| Operation Humidity | 5% ~ 95% (No Condensing) | | |
| Operation Temperature | -30°C ~ +50°C | | |
| Max. Operation Altitude | ≤ 3000 (>2000m Derating) | | |
| Communication Port | Ethernet ; CAN ; RS485 | | |
| Communication Protocol | CAN; MODBUS TCP / IP | | |
| Cooling Method | Air Conditioner | | |
| Certification | UL 9540A; UN38.3; MSDS; IEC 62040; IEC 62477; IEC 62619; IEC 63056; IEC 61000-6-2/4 | | |

### Hybrid Inverter Parameters

| Product Specifications | KAC80DP2 | KAC100DP2 | KAC110DP2 | KAC125DP2 |
|---|---|---|---|---|
| **PV Side** | | | | |
| MPPT Voltage Range | 250 ~ 950 V (Max. 1000 V) | | | |
| MPPT Rated Voltage | 720 V | | | |
| MPPT Rated Voltage (Full Load) | 450 ~ 800 V | 550 ~ 800 V | 600 ~ 800 V | 700 ~ 800 V |
| Max. PV Power | 160 kWp | 200 kWp | 220 kWp | 250 kWp |
| Number of MPPT / Strings per MPPT | 8 / 2 | | | |
| Max. Current per MPPT | 45 A | | | |
| **Battery Side** | | | | |
| Battery Voltage Range | 200 ~ 950 V | | | |
| Battery Rated Voltage Range | 250 ~ 850 V | | | |
| Max. DC Current | 160 A (80 A x 2) | | | |
| Max. DC Power | 88 kW | 110 kW | 121 kW | 125 kW |
| Number of DC Inputs | 2 | | | |
| **AC Side (On Grid)** | | | | |
| Nominal AC Output Power | 80 kW | 100 kW | 110 kW | 125 kW |
| Max. AC Output Power | 88 kVA | 110 kVA | 121 kVA | 125 kVA |
| Rated AC Output Current | 116 A | 144 A | 159 A | 181 A |
| Max.AC Input Current | 227 A | | | |
| AC Rated Voltage / Voltage Range | 230 / 400 Vac; 220 / 380 Vac; 3L+PE+N; -15% ~ +10% | | | |
| Nominal Grid Frequency / Frequency Range | 50 Hz / 60 Hz (±5 Hz) | | | |
| THDi | < 3% (100% Load ) | | | |
| Adjustable PF Range | 0.8 inductive(under-excited) to 0.8 capacitive(over-excited) | | | |
| **Backup Output** | | | | |
| Nominal AC Voltage | 230 / 400 V; 220 / 380 Vac; 3L+PE+N | | | |
| THDv | < 3% (Rated Power) | | | |
| Nominal Grid Frequency / Frequency Range | 50 Hz / 60 Hz | | | |
| Nominal AC Output Power | 80 kW | 100 kW | 110 kW | 125 kW |
| Max. AC Output Power (Single-phase) | 50 kW | | | |
| Max. Output Current | 227 A | | | |
| **Genset Input** | | | | |
| Max. Input Current | 227 A | | | |
| **Efficiency** | | | | |
| Max. Efficiency | 98% | | | |
| **Protection** | | | | |
| Reverse DC Connection Protection | Yes | | | |
| Anti-Islanding Protection | Yes | | | |
| Over-Temperature Protection | Yes | | | |
| Grid Monitoring / Earthing Fault Detection | Yes | | | |
| Insulation Monitoring | Yes | | | |
| DC / AC Surge Protection | DC Type II; AC Type II | | | |
| AFCI | Optional | | | |
| **General Parameters** | | | | |
| Dimensions (W x H x D) | 1120 x 760 x 365 mm | | | |
| Weight | 135 kg | | | |
| Topology | Transformerless | | | |
| IP Protection | IP66 | | | |
| Operation Temperature Range | -25 ~ 60℃ (> 45℃ Derating) | | | |
| Operation Humidity Range | 0 ~ 100% (No Condensing) | | | |
| Cooling Method | Intelligent Air Cooling | | | |
| Max. Operation Altitude | 4000 m (> 3000 m Derating) | | | |
| Communication Port | RS-485 / CAN | | | |