BluePulse Series NEW

KAC20DP2 / KAC25DP2 / KAC29.9DP2 / KAC30DP2 / KAC40DP2 / KAC49.9DP2 / KAC50DP2
BC80DE2A / BC100DE2A / BC120DE2A

Versatile Application

- ▶ Ideal for factories, hotels, and farms with DC / AC-coupled solar-storage
- ▶ No external switching device is required, on/off-grid switching time about 10ms, support direct output backup load

Safe & Reliable

- ▶ 314ah large capacity cell, higher energy density
- ▶ Carbon monoxide detection, Sound and light alarm, Exhaust fan, Explosion vent window, Inlet valve, Fire water injection port

Smart Energy

- ▶ Supports self-consumption, peak shifting, time-of-use, and battery backup
- ▶ Integrated self-developed BMS / EMS for flexibility

High Performance

- ▶ Small size, small footprint
- ▶ Long-lasting battery cycle life

Easy Operation

- ▶ Compact design saves space
- ▶ Cloud control with 24 / 7 monitoring

Technical Parameters	BC80DE2A	BC100DE2A	BC120DE2A
Battery Type	LiFe (LiFePO4)		
Battery Module Capacity	20.09 kWh		
Number of Modules	4	5	6
Total Battery Capacity	80.38 kWh	100.48 kWh	120.57 kWh
Nominal Voltage	256 V	320 V	384 V
Operating Voltage Range	228 ~ 288 V	285 ~ 360 V	342 ~ 432 V
Charging / Discharge Rate		0.5 C	
Standard Charging / Discharging Current	157 A / 157 A		
DoD	90%		
General Parameters			
Dimensions (W x H x D)	1062 x 2083 x 1371 mm		
Weight	< 1.36 T	< 1.5 T	< 1.64 T
Installation Site	Outdoor		
IP Protection	IP54		
Anti Corrosion Level	C4		
Operation Humidity	5% ~ 95% (No Condensing)		
Operation Temperature	-30°C ~ +50°C		
Max. Operation Altitude	≤ 3000 (>2000m Derating)		
Communication Port	Ethernet; CAN; RS485		
Communication Protocol	CAN; MODBUS TCP / IP		
Cooling Method	Air Conditioner		
Warranty	5 Year Product Warranty; 10 Year Performance Warranty		
Certification	UN38.3; MSDS; IEC 62040; IEC 62477; IEC 62619; IEC 63056; IEC 61000-6-2/4		

Hybrid Inverter Parameters

Product Specifications	KAC20DP2	KAC25DP2	KAC29.9DP2	KAC30DP2	KAC40DP2	KAC49.9DP2	KAC50DP2
PV Side							
MPPT Voltage Range	250 ~ 950 Vdc (Max. 1000 Vdc)						
MPPT Rated Voltage	720 Vdc						
MPPT Rated Voltage (Full Load)	300 ~ 800 V	350 ~ 800 V	400 ~ 800 V	400 ~ 800 V	500 ~ 800 V	600 ~ 800 V	620 ~ 800 V
Max. PV Power	40 kWp	50 kWp	60 kWp	60 kWp	80 kWp	100 kWp	100 kWp
Number of MPPT / Strings per MPPT	4 / 2						
Max. Current per MPPT	45 A						
Battery Side							
Battery Voltage Range	150 ~ 900 Vdc						
Battery Rated Voltage Range	180 ~ 800 Vdc						
Max. DC Current	40 Adc x 2	50 Adc x 2	60 Adc x 2	60 Adc x 2	80 Adc x 2	80 Adc x 2	80 Adc x 2
Max. DC Power	22 kW	27.5 kW	29.9 kW	33 kW	44 kW	49.9 kW	55 kW
Number of DC Input	2						
AC Side (On Grid)							
Nominal AC Output Power	20 kW	25 kW	29.9 kW	30 kW	40 kW	49.9 kW	50 kW
Max. AC Output Power	22 kVA	27.5 kVA	29.9 kVA	33 kVA	44 kVA	49.9 kVA	55 kVA
Max. AC Input Power (Single-phase)	20 kW	25 kW	25 kW	25 kW	27.5 kW	37.5 kW	37.5 kW
Rated AC Output	29 A	36 A	43 A	43 A	58.0 A	72 A	72 A
Max. AC Continuous Input	64 A	80 A	87 A	96 A	128 A	144 A	160 A
AC Rated Voltage / Voltage Range	230 / 400 Vac; 220 / 380 Vac; 3L+PE+N; -15% ~ +10%						
Nominal Grid Frequency / Frequency Range	50 Hz / 60 Hz (±5 Hz)						
THDi	< 3% (100% Load)						
Adjustable PF Range	0.8 inductive(under-excited) to 0.8 capacitive(over-excited)						
Backup Output							
Nominal AC Voltage	230 / 400 V; 220 / 380 Vac; 3L+PE+N						
THDv	< 3% (Rated Power)						
Nominal Grid Frequency / Frequency Range	50 Hz / 60 Hz						
Nominal AC Output Power	20 kW	25 kW	29.9 kW	30 kW	40 kW	49.9 kW	50 kW
Max. AC Output Power (Single-phase)	20 kW	20 kW	20 kW	20 kW	25 kW	25 kW	25 kW
Max. Output Current	87 A	87 A	87 A	87 A	110 A	110 A	110 A
Genset Input							
Max. Input Current	87 A	87 A	87 A	87 A	110 A	110 A	110 A
Efficiency							
Max. Efficiency	97%	97%	97%	97%	97.5%	97.5%	97.5%
Protection							
Reverse DC Connection Protection	Yes						
Anti-Islanding Protection	Yes						
Over-Temperature Protection	Yes						
Grid Monitoring / Earthing Fault Detection	Yes						
Insulation Mornitoring	Yes						
DC / AC Surge Protection	DC Type II; AC Type II						
AFCI	Optional						
General Parameters							
Dimensions (W x H x D)	900 x 730 x 355 mm						
Weight	101 kg						
Topology	Transformerless						
IP Protection	IP66						
Operation Temperature Range	-25 ~ 60℃ (> 45℃ Derating)						
Operation Humidity Range	0 ~ 100% (No Condensing)						
Cooling Method	Intelligent Air Cooling						
Max. Operation Altitude	4000 m (> 3000 m Derating)						
Communication Port	RS-485 / CAN						

BluePulse Series NEW

KAC80DP2 / KAC100DP2 / KAC110DP2 / KAC125DP2
BC197DE2 / BC215DE2 / BC233DE2

Versatile Application

- ▶ Ideal for factories, hotels, and farms with DC / AC-coupled solar-storage
- ▶ No external switching device is required, on/off-grid switching time about 10ms, support direct output backup load

Safe & Reliable

- ▶ 280ah large capacity cell, higher energy density
- ▶ Carbon monoxide detection, Sound and light alarm, Exhaust fan, Explosion vent window, Inlet valve, Fire water injection port

Smart Energy

- ▶ Supports self-consumption, peak shifting, time-of-use, and battery backup
- ▶ Integrated self-developed BMS / EMS for flexibility

High Performance

- ▶ Small size, small footprint
- ▶ Long-lasting battery cycle life

Easy Operation

- ▶ Compact design saves space
- ▶ Cloud control with 24 / 7 monitoring

Outdoor Battery Cabinet Parameters

Technical Parameters	BC197DE2	BC215DE2	BC233DE2
Battery Type	LFP		
Battery Module Capacity	17.92 kWh		
Cell Type	280 Ah		
Number of Modules	11	12	13
Total Battery Capacity	197.12 kWh	215.04 kWh	232.96 kWh
Nominal Voltage	704 V	768 V	832 V
Operating Voltage Range	627 ~ 792 V	684 ~ 864 V	741 ~ 936 V
Charge / Discharge Rate	0.5 C		
DoD	90%		
General Parameters			
Dimensions (W x H x D)	1324 x 2415 x 1440 mm		
Weight	< 2.4 T	< 2.55 T	< 2.7 T
Installation Site	Outdoor		
IP Protection	IP54		
Anti Corrosion Level	C4		
Operation Humidity	5% ~ 95% (No Condensing)		
Operation Temperature	-30°C ~ +50°C		
Max. Operation Altitude	≤ 3000 (>2000m Derating)		
Communication Port	Ethernet ; CAN ; RS485		
Communication Protocol	CAN; MODBUS TCP / IP		
Cooling Method	Air Conditioner		
Certification	UL 9540A; UN38.3; MSDS; IEC 62040; IEC 62477; IEC 62619; IEC 63056; IEC 61000-6-2/4		

Hybrid Inverter Parameters

Product Specifications	KAC80DP2	KAC100DP2	KAC110DP2	KAC125DP2
PV Side				
MPPT Voltage Range	250 ~ 950 V (Max. 1000 V)			
MPPT Rated Voltage	720 V			
MPPT Rated Voltage (Full Load)	450 ~ 800 V	550 ~ 800 V	600 ~ 800 V	700 ~ 800 V
Max. PV Power	160 kWp	200 kWp	220 kWp	250 kWp
Number of MPPT / Strings per MPPT	8 / 2			
Max. Current per MPPT	45 A			
Battery Side				
Battery Voltage Range	200 ~ 950 V			
Battery Rated Voltage Range	250 ~ 850 V			
Max. DC Current	160 A (80 A x 2)			
Max. DC Power	88 kW	110 kW	121 kW	125 kW
Number of DC Inputs	2			
AC Side (On Grid)				
Nominal AC Output Power	80 kW	100 kW	110 kW	125 kW
Max. AC Output Power	88 kVA	110 kVA	121 kVA	125 kVA
Rated AC Output Current	116 A	144 A	159 A	181 A
Max.AC Input Current	227 A			
AC Rated Voltage / Voltage Range	230 / 400 Vac; 220 / 380 Vac; 3L+PE+N; -15% ~ +10%			
Nominal Grid Frequency / Frequency Range	50 Hz / 60 Hz (±5 Hz)			
THDi	< 3% (100% Load)			
Adjustable PF Range	0.8 inductive(under-excited) to 0.8 capacitive(over-excited)			
Backup Output				
Nominal AC Voltage	230 / 400 V; 220 / 380 Vac; 3L+PE+N			
THDv	< 3% (Rated Power)			
Nominal Grid Frequency / Frequency Range	50 Hz / 60 Hz			
Nominal AC Output Power	80 kW	100 kW	110 kW	125 kW
Max. AC Output Power (Single-phase)	50 kW			
Max. Output Current	227 A			
Genset Input				
Max. Input Current	227 A			
Efficiency				
Max. Efficiency	98%			
Protection				
Reverse DC Connection Protection	Yes			
Anti-Islanding Protection	Yes			
Over-Temperature Protection	Yes			
Grid Monitoring / Earthing Fault Detection	Yes			
Insulation Monitoring	Yes			
DC / AC Surge Protection	DC Type II; AC Type II			
AFCI	Optional			
General Parameters				
Dimensions (W x H x D)	1120 x 760 x 365 mm			
Weight	135 kg			
Topology	Transformerless			
IP Protection	IP66			
Operation Temperature Range	-25 ~ 60℃ (> 45℃ Derating)			
Operation Humidity Range	0 ~ 100% (No Condensing)			
Cooling Method	Intelligent Air Cooling			
Max. Operation Altitude	4000 m (> 3000 m Derating)			
Communication Port	RS-485 / CAN			

BluePulse Series NEW

KAC80DP2 / KAC100DP2 / KAC110DP2 / KAC125DP2
BC220DE2A / BC240DE2A / BC260DE2A

Versatile Application

- ▶ Ideal for factories, hotels, and farms with DC / AC-coupled solar-storage
- ▶ No external switching device is required, on/off-grid switching time about 10ms, support direct output backup load

Safe & Reliable

- ▶ 314ah large capacity cell, higher energy density
- ▶ Carbon monoxide detection, Sound and light alarm, Exhaust fan, Explosion vent window, Inlet valve, Fire water injection port

Smart Energy

- ▶ Supports self-consumption, peak shifting, time-of-use, and battery backup
- ▶ Integrated self-developed BMS / EMS for flexibility

High Performance

- ▶ Small size, small footprint
- ▶ Long-lasting battery cycle life

Easy Operation

- ▶ Compact design saves space
- ▶ Cloud control with 24 / 7 monitoring

Technical Parameters	BC220DE2A	BC240DE2A	BC260DE2A
Battery Type	LiFe (LiFePO4)		
Battery Module Capacity	20.09 kWh		
Number of Modules	11	12	13
Total Battery Capacity	221.05 kWh	241.15 kWh	261.24 kWh
Nominal Voltage	704 V	768 V	832 V
Operating Voltage Range	627 ~ 792 V	684 ~ 864 V	741 ~ 936 V
Charging / Discharge Rate		0.5 C	
Standard Charging / Discharging Current	157 A / 157 A		
DoD	90%		
General Parameters			
Dimensions (W x H x D)	1324 x 2415 x 1440 mm		
Weight	< 2.45 T	< 2.60 T	< 2.71 T
Installation Site	Outdoor		
IP Protection	IP54		
Anti Corrosion Level	C4		
Operation Humidity	5% ~ 95% (No Condensing)		
Operation Temperature	-30°C ~ +50°C		
Max. Operation Altitude	≤ 3000 (>2000m Derating)		
Communication Port	Ethernet ; CAN ; RS485		
Communication Protocol	CAN; MODBUS TCP / IP		
Cooling Method	Air Conditioner		
Warranty	5 Year Product Warranty; 10 Year Performance Warranty		
Certification	UN38.3; MSDS; IEC 62040; IEC 62477; IEC 62619; IEC 63056; IEC 61000-6-2/4		

Hybrid Inverter Parameters

Product Specifications	KAC80DP2	KAC100DP2	KAC110DP2	KAC125DP2
PV Side				
MPPT Voltage Range	250 ~ 950 V (Max. 1000 V)			
MPPT Rated Voltage	720 V			
MPPT Rated Voltage (Full Load)	450 ~ 800 V	550 ~ 800 V	600 ~ 800 V	700 ~ 800 V
Max. PV Power	160 kWp	200 kWp	220 kWp	250 kWp
Number of MPPT / Strings per MPPT	8 / 2			
Max. Current per MPPT	45 A			
Battery Side				
Battery Voltage Range	200 ~ 950 V			
Battery Rated Voltage Range	250 ~ 850 V			
Max. DC Current	160 A (80 A x 2)			
Max. DC Power	88 kW	110 kW	121 kW	125 kW
Number of DC Inputs	2			
AC Side (On Grid)				
Nominal AC Output Power	80 kW	100 kW	110 kW	125 kW
Max. AC Output Power	88 kVA	110 kVA	121 kVA	125 kVA
Rated AC Current	116 A	144 A	159 A	181 A
Max. AC Current	227 A			
AC Rated Voltage / Voltage Range	230 / 400 Vac; 220 / 380 Vac; 3L+PE+N; -15% ~ +10%			
Nominal Grid Frequency / Frequency Range	50 Hz / 60 Hz (±5 Hz)			
THDi	< 3% (100% Load)			
Adjustable PF Range	0.8 inductive(under-excited) to 0.8 capacitive(over-excited)			
Backup Output				
Nominal AC Voltage	230 / 400 V; 220 / 380 Vac; 3L+PE+N			
THDv	< 3% (Rated Power)			
Nominal Grid Frequency / Frequency Range	50 Hz / 60 Hz			
Nominal AC Output Power	80 kW	100 kW	110 kW	125 kW
Max. AC Output Power (Single-phase)	50 kW			
Max. Output Current	220 A			
Genset Input				
Max. Input Current	220 A			
Efficiency				
Max. Efficiency	98%			
Protection				
Reverse DC Connection Protection	Yes			
Anti-Islanding Protection	Yes			
Over-Temperature Protection	Yes			
Grid Monitoring / Earthing Fault Detection	Yes			
Insulation Monitoring	Yes			
DC / AC Surge Protection	DC Type II; AC Type II			
AFCI	Optional			
General Parameters				
Dimensions (W x H x D)	1120 x 760 x 365 mm			
Weight	135 kg			
Topology	Transformerless			
IP Protection	IP66			
Operation Temperature Range	-25 ~ 60℃ (> 45℃ Derating)			
Operation Humidity Range	0 ~ 100% (No Condensing)			
Cooling Method	Intelligent Air Cooling			
Max. Operation Altitude	4000 m (> 3000 m Derating)			
Communication Port	RS-485 / CAN			

BluePulse Series

KAC100DH / KAC125DH - BC215DE2 / BC233DE2

Safe & Reliable

- CATL LFP Battery Cell
- Double Fire Suppression System Design

Economical & Efficient

- Save CapEx, Expanding as Required
- Efficient and Energy-saving HVAC Design

Simple & User-friendly

- Pre-installed in Factory for Easy Installation on site
- Integrated BMS / EMS, Suitable for Various Applications
- Effortless Operation, Cloud Control

Outdoor Battery Cabinet Parameters

Technical Parameters	BC215DE2	BC233DE2
Battery Type	LFP	
Battery Module Capacity	17.92 kWh	
Cell Type	280 Ah	
Number of Modules	12	13
Total Battery Capacity	215.04 kWh	232.96 kWh
Nominal Voltage	768 V	832 V
Operating Voltage Range	684 ~ 864 V	741 ~ 936 V
Charge / Discharge Rate	0.5 C	
DoD	90%	
General Parameters		
Dimensions (W x H x D)	1300 x 2380 x 1445 mm	
Weight	< 2.5 T	< 2.6 T
Installation Site	Outdoor	
IP Protection	IP54	
Anti Corrosion Level	C4	
Operation Humidity	5% ~ 95% (No Condensing)	
Operation Temperature	-30°C ~ +50°C	
Max. Operation Altitude	≤ 3000 (>2000m Derating)	
Communication Port	Ethernet ; CAN ; RS485	
Communication Protocol	CAN; MODBUS TCP / IP	
Cooling Method	Air Conditioner	
Certification	UL 9540A; UN38.3; MSDS; IEC 62040; IEC 62477; IEC 62619; IEC 63056; IEC 61000-6-2/4	

Energy Storage Inverter Parameters

Product Specifications	KAC100DH	KAC125DH
Battery Side		
Max. Input Voltage	1500 V	
Min. Input Voltage	600 V	
DC Voltage at Nominal Operation	650 ~ 1400 V	
Max. DC Current	187 A	233.8 A
Max. DC Input Power	112 kW	140 kW
Number of DC Inputs	1	
AC Side (On Grid)		
Nominal AC Output Power	100 kW	125 kW
Max. AC Output Power	110 kW	137.5 kW
Max. AC Current	159 A	199 A
Nominal AC Voltage	400 Vac, 3P + PE (N)	
AC Voltage Range	400 Vac, (-15% + 10%)	
Nominal Grid Frequency / Frequency Range	50 Hz / 60 Hz (±5 Hz)	
THDi	≤ 3% (Rated Power)	
Adjustable PF Range	> 0.99	
AC Side (Off Grid) [1]		
Nominal AC Voltage	400 Vac, 3P + PE (N)	
THDv	< 1.5% (Resistive Load)	
Nominal Grid Frequency / Frequency Range	50 Hz / 60 Hz (±5 Hz)	
Nominal AC Output Power	100 kW	125 kW
Max. AC Output Power	110 kVA	137.5 kVA
Efficiency		
Max. Efficiency	> 98%	
Protection		
Reverse Connection Protection	Yes	
DC Switch	Yes	
Over-Temperature Protection	Yes	
Insulation Monitoring	Yes	
DC / AC Surge Protection	Type II (DC side); Type II (AC side)	
General Parameters		
Dimensions (W x H x D)	650 x 952 x 310 mm	
Installation	Wall Mounted / Plug in	
Weight	93 kg	
Topology	Transformerless	
IP Protection	IP66	
Anti Corrosion Leve	C4	
Operation Temperature Range	-30℃ ~ 60℃ (> 45℃ Derating)	
Operation Humidity Range	0 ~ 100% (No Condensing)	
Cooling Method	Intelligent Air Cooling	
Max. Operation Altitude	4000 m (> 3000 m Derating)	
Communication Port	RS-485 / CAN	
Certificates	EN 50549-1:2019; EN 50549-2:2019; IEC 61000-6-2/4; IEC 62477-1: 2012; NC RFG; C10/C11; GB/T 34120; GB/T 34133:2023	

1) For off-grid application, STS250D automatic switching cabinet is needed.