

# Introduction

## `console.log()`

The `console.log()` method is used to log or print messages to the console. It can also be used to print objects and other info.

## JavaScript

JavaScript is a programming language that powers the dynamic behavior on most websites. Alongside HTML and CSS, it is a core technology that makes the web run.

## Methods

Methods return information about an object, and are called by appending an instance with a period `.`, the method name, and parentheses.

## Libraries

Libraries contain methods that can be called by appending the library name with a period `.`, the method name, and a set of parentheses.

## Numbers

Numbers are a primitive data type. They include the set of all integers and floating point numbers.

```
console.log('Hi there!');  
// Prints: Hi there!
```

```
// Returns a number between 0 and 1  
Math.random();
```

```
Math.random();  
// 📖 Math is the library
```

```
let amount = 6;  
let price = 4.99;
```

## String .length

The `.length` property of a string returns the number of characters that make up the string.

```
let message = 'good nite';  
console.log(message.length);  
// Prints: 9  
  
console.log('howdy'.length);  
// Prints: 5
```

## Data Instances

When a new piece of data is introduced into a JavaScript program, the program keeps track of it in an instance of that data type. An instance is an individual case of a data type.

## Booleans

Booleans are a primitive data type. They can be either `true` or `false`.

```
let lateToWork = true;
```

## Math.random()

The `Math.random()` function returns a floating-point, random number in the range from 0 (inclusive) up to but not including 1.

```
console.log(Math.random());  
// Prints: 0 - 0.9
```

## Math.floor()

The `Math.floor()` function returns the largest integer less than or equal to the given number.

```
console.log(Math.floor(5.95));  
// Prints: 5
```

## Single Line Comments

In JavaScript, single-line comments are created with two consecutive forward slashes `//`.

```
// This line will denote a comment
```

## Null

Null is a primitive data type. It represents the intentional absence of value. In code, it is represented as `null`.

## Strings

Strings are a primitive data type. They are any grouping of characters (letters, spaces, numbers, or symbols) surrounded by single quotes `'` or double quotes `"`.

## Arithmetic Operators

JavaScript supports arithmetic operators for:

- `+` addition
- `-` subtraction
- `*` multiplication
- `/` division
- `%` modulo

## Multi-line Comments

In JavaScript, multi-line comments are created by surrounding the lines with `/*` at the beginning and `*/` at the end. Comments are good ways for a variety of reasons like explaining a code block or indicating some hints, etc.

```
let x = null;
```

```
let single = 'Wheres my bandit hat?';  
let double = "Wheres my bandit hat?";
```

```
// Addition  
5 + 5  
// Subtraction  
10 - 5  
// Multiplication  
5 * 10  
// Division  
10 / 5  
// Modulo  
10 % 5
```

```
/*  
The below configuration must be  
changed before deployment.  
*/  
  
let baseUrl = 'localhost/taxwebapp/country';
```

## Assignment Operators

An assignment operator assigns a value to its left operand based on the value of its right operand. Here are some of them:

- `+=` addition assignment
- `-=` subtraction assignment
- `*=` multiplication assignment
- `/=` division assignment

## String Interpolation

String interpolation is the process of evaluating string literals containing one or more placeholders (expressions, variables, etc).

It can be performed using template literals: `text ${expression} text`.

## Variables

Variables are used whenever there's a need to store a piece of data. A variable contains data that can be used in the program elsewhere. Using variables also ensures code re-usability since it can be used to replace the same value in multiple places.

```
let number = 100;

// Both statements will add 10
number = number + 10;
number += 10;

console.log(number);
// Prints: 120
```

```
let age = 7;

// String concatenation
'Tommy is ' + age + ' years old.';

// String interpolation
`Tommy is ${age} years old.`;
```

```
const currency = '$';
let userIncome = 85000;

console.log(currency + userIncome + ' is more than the
average income.');
```

// Prints: \$85000 is more than the average income.

## Undefined

`undefined` is a primitive JavaScript value that represents lack of defined value. Variables that are declared but not initialized to a value will have the value `undefined`.

## Learn Javascript: Variables

A variable is a container for data that is stored in computer memory. It is referenced by a descriptive name that a programmer can call to assign a specific value and retrieve it.

## Declaring Variables

To declare a variable in JavaScript, any of these three keywords can be used along with a variable name:

- `var` is used in pre-ES6 versions of JavaScript.
- `let` is the preferred way to declare a variable when it can be reassigned.
- `const` is the preferred way to declare a variable with a constant value.

## Template Literals

Template literals are strings that allow embedded expressions,

`${expression}`. While regular strings use single `'` or double `"` quotes, template literals use backticks instead.

```
var a;  
  
console.log(a);  
// Prints: undefined
```

```
// examples of variables  
let name = "Tammy";  
const found = false;  
var age = 3;  
console.log(name, found, age);  
// Tammy, false, 3
```

```
var age;  
let weight;  
const numberOfFingers = 20;
```

```
let name = "Codecademy";  
console.log(`Hello, ${name}`);  
// Prints: Hello, Codecademy  
  
console.log(`Billy is ${6+8} years old.`)  
// Prints: Billy is 14 years old.
```

## let Keyword

`let` creates a local variable in JavaScript & can be re-assigned. Initialization during the declaration of a `let` variable is optional. A `let` variable will contain `undefined` if nothing is assigned to it.

## const Keyword

A constant variable can be declared using the keyword `const`. It must have an assignment. Any attempt of re-assigning a `const` variable will result in JavaScript runtime error.

## String Concatenation

In JavaScript, multiple strings can be concatenated together using the `+` operator. In the example, multiple strings and variables containing string values have been concatenated. After execution of the code block, the `displayText` variable will contain the concatenated string.

```
let count;
console.log(count); // Prints: undefined
count = 10;
console.log(count); // Prints: 10
```

```
const numberOfColumns = 4;
numberOfColumns = 8;
// TypeError: Assignment to constant variable.
```

```
let service = 'credit card';
let month = 'May 30th';
let displayText = 'Your ' + service + ' bill is due on ' + month + '.';

console.log(displayText);
// Prints: Your credit card bill is due on May 30th.
```