

API Documentation

Technical API reference documentation for the Product Care suite of extensions.

This section covers API endpoints, field references, caller workflows, and integration patterns for external systems connecting to Business Central.

PCG API — Integration Guide

App: PCG API

Publisher: Technology Management

Version: 27.3.x

BC Platform: 27.3 (Cloud, Runtime 16.0)

Description: A collection of API endpoints for reading and writing data in Business Central as part of the PCG integration.

Table of Contents

1. [API Endpoint Reference](#)
 2. [Functional Areas](#)
 - [Common / Setup](#)
 - [P5 — Order Cancellation](#)
 - [P6 — Sales Order Line Dispatch](#)
 - [P7 — Palletised Load Build](#)
 - [P8 — Freight Shipping Info](#)
 - [P9 — RTB Returns](#)
 - [P10 — Purchase Order](#)
 - [Sales Return Orders](#)
 3. [Service-Enabled Procedures](#)
 4. [Caller Workflows](#)
 - [P7 — Palletised Load Build](#)
 - [P8 — Freight Shipping Info](#)
 - [Sales Return Orders — PATCH](#)
 5. [Outbound JSON Payloads](#)
 6. [Data Model](#)
 - [Custom Tables](#)
 - [Table Extensions](#)
 7. [Internal Components](#)
 8. [Permission Set](#)
 9. [Dependencies](#)
-

API Endpoint Reference

All endpoints are OData v4 and follow the pattern:

`/api/{publisher}/{group}/{version}/{entitySetName}`

Page #	Entity Set Name	Entity Name	HTTP Methods	Notes
50048	items	item	GET, PATCH	OData key: Sys
50049	itemInventory	itemInventory	GET	Read-only; loc FlowFilter — p \$filter=locat 'MAIN'; not stc in responses
50050	itemReferences	itemReference	GET, POST, PATCH	POST will reject use PATCH to records. PATCH record if any k changed (item unitOfMeasure referenceType
50085	itemUnitOfMeasure	itemUnitOfMeasure	GET, POST, PATCH	
50051	salesOrders	salesOrder	GET, PATCH	Includes sales
50052	salesLines	salesLine	GET, POST, PATCH	Sub-page of s
50162	salesOrderCancellations	salesOrderCancellation	POST	Insert-only; inc salesOrderCan sub-page
50165	salesOrderCancellationLines	salesOrderCancellationLine	POST	Sub-page of salesOrderCan
50087	purchaseOrders	purchaseOrder	GET	Read-only; inc purchaseOrder

Page #	Entity Set Name	Entity Name	HTTP Methods	Notes
50181	purchaseOrderLines	purchaseOrderLine	GET	Read-only; sub-page of purchaseOrder
50229	purchaseOrderCancellations	purchaseOrderCancellation	POST	Insert-only; includes purchaseOrderCancellationLines sub-page
50230	purchaseOrderCancellationLines	purchaseOrderCancellationLine	POST	Sub-page of purchaseOrderCancellation
50164	pcgPalletisedLoadBuilds	pcgPalletisedLoadBuild	POST, PATCH	Includes pcgPalletisedLoadBuildLines page
50163	pcgPalletisedLoadLines	pcgPalletisedLoadLine	GET, POST, PATCH	Sub-page of pcgPalletisedLoadBuild
50231	salesReturnOrders	salesReturnOrder	GET, POST, PATCH, DELETE	Full Sales Return Order; includes salesReturnOrderLines
50232	salesReturnLines	salesReturnLine	GET, POST, PATCH	Sub-page of salesReturnOrder
50233	salesReturnOrdersExt	salesReturnOrderExt	GET, POST, PATCH	Slim variant — only; includes salesReturnOrderLinesExt
50234	salesReturnLinesExt	salesReturnLineExt	GET, POST, PATCH	Sub-page of salesReturnOrderExt
50167	warehouseReceiptFreight	warehouseReceiptFreight	GET, PATCH	Includes warehouseReceiptFreightLines sub-page

Page #	Entity Set Name	Entity Name	HTTP Methods	Notes
50169	warehouseReceiptFreightLines	warehouseReceiptFreightLine	GET	Sub-page of warehouseRece

Field Reference by Endpoint

items (PAG50048)

JSON Property	Description	Type	Editable
id	System identifier	Guid	No
number	Item No.	Code[20]	No
number2	Item No. 2	Code[20]	Yes
displayName	Description	Text[100]	Yes
subCategory	Sub Category	Code	Yes
warrantyCategory	Warranty Category	Code	Yes
supplyType	Supply Type	Option	Yes
customerProductCode	Customer Product Code	Code	Yes
storageWarehouse	Storage Warehouse	Code	Yes
boxType	Box Type	Code	Yes
productHeight	Product Height	Decimal	Yes
productWidth	Product Width	Decimal	Yes
productDepth	Product Depth	Decimal	Yes
outerCartonUnits	Number of Units per Outer Carton	Decimal	Yes
container20Qty	20ft Container Qty.	Decimal	Yes
container40Qty	40ft Container Qty.	Decimal	Yes
container40HQQty	40ft HQ Container Qty.	Decimal	Yes

JSON Property	Description	Type	Editable
container45Qty	45ft Container Qty.	Decimal	Yes
bundle	Bundle	Text	Yes
holdQuarantineQty	Hold / Quarantine Qty.	Decimal	Yes
nextPOQuantity	Next PO Quantity	Decimal	Yes
nextPODate	Next PO Date	Date	Yes
vendorNo	Vendor No.	Code	Yes
vendorItemNo	Vendor Item No.	Code	Yes
leadTimeCalculation	Lead Time Calculation	Duration	Yes
reorderQuantity	Reorder Quantity	Decimal	Yes
grossWeight	Gross Weight	Decimal	Yes
netWeight	Net Weight	Decimal	Yes
tariffNo	Tariff No.	Code	Yes
countryRegionPurchasedCode	Country/Region Purchased Code	Code	Yes
vatProdPostingGroup	VAT Prod. Posting Group	Code	Yes
minimumOrderQuantity	Minimum Order Quantity	Decimal	Yes
maximumOrderQuantity	Maximum Order Quantity	Decimal	Yes
dutyDue	Duty Due %	Decimal	Yes
unitVolume	Unit Volume	Decimal	Yes
endOfLifeDisposalReq	End-of-Life Disposal Req.	Option	Yes
salesBlocked	Sales Blocked	Option	Yes
purchasingBlocked	Purchase Blocked	Option	Yes
itemCategoryCode	Item Category Code	Code	Yes

JSON Property	Description	Type	Editable
<code>itemCategoryParentCode</code>	Item Category Parent Code	Code	No
<code>itemStatus</code>	Item Status	Option	No

Data Setup Notes: `subCategory` requires a Sub Category record; `warrantyCategory` requires a Warranty Category record; `storageWarehouse` requires a **Location** record; `boxType` requires a Box Type record; `vatProdPostingGroup` requires a **VAT Product Posting Group** record; `itemCategoryCode` requires an **Item Category** record.

`itemInventory` (PAG50049)

JSON Property	Description	Type	Editable
<code>id</code>	System identifier	Guid	No
<code>number</code>	Item No.	Code[20]	No
<code>displayName</code>	Description	Text	No
<code>inventory</code>	Inventory (at Location)	Decimal	No
<code>locationFilter</code>	Location Filter	Code	Yes
<code>holdQuarantineQty</code>	Hold / Quarantine Qty.	Decimal	No
<code>nextPOQuantity</code>	Next PO Quantity	Decimal	No
<code>nextPODate</code>	Next PO Date	Date	No
<code>onSalesOrder</code>	Qty. on Sales Order	Decimal	No
<code>onAssComponent</code>	Qty. on Assembly Component	Decimal	No
<code>lastModifiedDateTime</code>	Last Modified Date	DateTime	No

`locationFilter` — Behaviour

Functional behaviour

Applying `$filter=locationFilter eq 'MAIN'` does **not** reduce the number of records returned. Every item in the catalogue is always included in the response regardless of whether it has any stock at the

specified location.

What the filter *does* change is the value of the calculated inventory fields on each record. When a location filter is active, `inventory`, `onSalesOrder`, and `onAssComponent` are each scoped to that location only — they reflect quantities at the filtered location rather than the company-wide total. An item with no stock at the specified location will still appear in the response, but with `inventory: 0`.

Scenario	Records returned	inventory value
No <code>locationFilter</code> applied	All items	Company-wide total across all locations
<code>\$filter=locationFilter eq 'MAIN'</code>	All items	Stock at MAIN only (0 if none held there)

Example

Item `WIDGET-001` has 50 units at `MAIN` and 20 units at `SECONDARY`. Item `GADGET-002` has no stock at `MAIN` but 10 units at `SECONDARY`.

Without filter:

```
{ "number": "WIDGET-001", "inventory": 70 }  
{ "number": "GADGET-002", "inventory": 10 }
```

With `$filter=locationFilter eq 'MAIN'`:

```
{ "number": "WIDGET-001", "inventory": 50 }  
{ "number": "GADGET-002", "inventory": 0 }
```

Both items are returned in both cases. Only the `inventory` value changes.

Technical detail

`locationFilter` is a Business Central **FlowFilter** field. FlowFilters are not stored values — they are filter parameters that change how **FlowField** calculations are evaluated at runtime. When BC processes an OData `$filter` clause against a FlowFilter field, it does not apply a row-level predicate to the result set; instead it sets the filter context used when computing the dependent FlowField values (`inventory`, `onSalesOrder`, `onAssComponent`). The field is returned in the response body, but its value will reflect the filter that was applied — if no filter was sent, it will be returned as blank.

JSON Property	Description	Type	Editable
id	System identifier	Guid	No
itemNo	Item No.	Code[20]	Yes
variantCode	Variant Code	Code[10]	Yes
unitOfMeasure	Unit of Measure	Code[10]	Yes
referenceType	Reference Type	Option	Yes
referenceTypeNo	Reference Type No.	Code[30]	Yes
referenceNo	Reference No.	Code[50]	Yes
description	Description	Text[100]	Yes
description2	Description 2	Text[100]	Yes
startingDate	Starting Date	Date	Yes
endingDate	Ending Date	Date	Yes
supplierRefEntryNo	Supplier Ref. Entry No.	Integer	No

Note: POST will return an error if the item reference already exists (matched by `itemNo`, `variantCode`, `unitOfMeasure`, `referenceType`, `referenceTypeNo`, `referenceNo`). Use PATCH to update existing records. PATCH will rename the record if any key field is changed.

itemUnitOfMeasure (PAG50085)

JSON Property	Description	Type	Editable
id	System identifier	Guid	No
itemNo	Item No.	Code[20]	Yes
code	Unit of Measure Code	Code[10]	Yes
qtyPerUnitOfMeasure	Qty. per Unit of Measure	Decimal	Yes
length	Length	Decimal	Yes

JSON Property	Description	Type	Editable
width	Width	Decimal	Yes
height	Height	Decimal	Yes
cubage	Cubage	Decimal	Yes
weight	Weight	Decimal	Yes

Data Setup Notes: `itemNo` requires an existing **Item** record; `code` requires an existing **Unit of Measure** record.

salesOrders (PAG50051)

JSON Property	Description	Type	Editable
systemId	System identifier	Guid	No
number	Sales Order No.	Code[20]	No
customerNo	Customer No.	Code[20]	No
shipToEmailAddress	Ship-to E-mail Address	Text	Yes
miscReference1	Miscellaneous Reference 1	Text	Yes
miscReference2	Miscellaneous Reference 2	Text	Yes
miscReference3	Miscellaneous Reference 3	Text	Yes
externalRetailerName	External Retailer Name	Text	Yes
externalOrderReferences	External Order References	Text	Yes
invoiceName	Invoice Name	Text	Yes
invoiceAdd1	Invoice Address Line 1	Text	Yes
invoiceAdd2	Invoice Address Line 2	Text	Yes
invoiceAdd3	Invoice Address Line 3	Text	Yes
invoiceAdd4	Invoice Address Line 4	Text	Yes

JSON Property	Description	Type	Editable
invoicePostcode	Invoice Postcode	Code	Yes
transportMethod	Transport Method	Code	Yes
shipmentMethodCode	Shipment Method Code	Code	Yes
shipToPhoneNo	Ship-to Phone No.	Text	Yes
shipToPhoneNo2	Ship-to Phone No. 2	Text	Yes
shippingAgentServiceCode	Shipping Agent Service Code	Code	Yes
systemCreatedAt	Created date/time	DateTime	No
systemCreatedBy	Created by	Guid	No
systemModifiedAt	Last modified date/time	DateTime	No
systemModifiedBy	Last modified by	Guid	No

Data Setup Notes: `transportMethod` requires a **Transport Method** record; `shipmentMethodCode` requires a **Shipment Method** record; `shippingAgentServiceCode` requires a **Shipping Agent** record and a corresponding **Shipping Agent Service** record.

Known Issues: `shippingAgentServiceCode` is exposed without `shippingAgentCode`. If the Sales Order does not already have a Shipping Agent Code set, sending a service code alone will fail BC validation — the service code is a child of the agent code. Ensure the order has a Shipping Agent Code before patching this field.

salesLines (PAG50052) — sub-page of salesOrders

JSON Property	Description	Type	Editable
id	System identifier	Guid	No
documentNo	Sales Order No.	Code[20]	No
lineNo	Line No.	Integer	No
type	Line Type	Option	Yes

JSON Property	Description	Type	Editable
no	Item / Account No.	Code[20]	Yes
description	Description	Text	Yes
quantity	Quantity	Decimal	Yes
unitPrice	Unit Price	Decimal	Yes
lineAmount	Line Amount	Decimal	No
miscLineReference1	Miscellaneous Line Reference 1	Text	Yes
pcgUniqueLineReference	PCG Unique Line Reference	Text	Yes
serialNo	Serial No.	Code	Yes
locationCode	Location Code	Code	Yes
shippingAgentCode	Shipping Agent Code	Code	Yes
shippingAgentServiceCode	Shipping Agent Service Code	Code	Yes
vehicleRegistration	Vehicle Registration	Text	Yes
dropNumber	Drop Number	Text	Yes
height	Height	Decimal	Yes
width	Width	Decimal	Yes
grossWeight	Gross Weight	Decimal	Yes
depth	Depth	Decimal	Yes
commodityCode	Commodity Code / Tariff No.	Code[20]	Yes
attachToInventoryLine	Attach To Line No.	Integer	Yes

Data Setup Notes: no requires an **Item** record when type is Item, or a **G/L Account** record when type is G/L Account; locationCode requires a **Location** record; shippingAgentCode requires a **Shipping Agent** record; shippingAgentServiceCode requires a corresponding **Shipping Agent Service** record.

Customer Item Reference Resolution: When posting or patching a `no` value on a Sales line, if the supplied value does not match a direct Item No., the system will attempt to resolve it via the customer's item cross-references (`Item Reference` table, filtered to the order's Sell-to Customer No.). If a matching cross-reference is found, the Item No. is substituted automatically before the line is written. This allows callers to send customer-specific part numbers rather than internal item numbers.

Serial No. Tracking: On insert (POST), if a `serialNo` is provided, a surplus Reservation Entry is automatically created to register serial number item tracking. On modify (PATCH), if the serial no. changes, the existing tracking entry is replaced with the new value.

salesOrderCancellations (PAG50162)

JSON Property	Description	Type	Notes
<code>id</code>	System identifier	Guid	Auto-generated
<code>cancellationType</code>	Cancellation Type	Enum	Required. <code>Cancel</code> or <code>Modify</code>
<code>customerCode</code>	Customer No.	Code[20]	Required — must exist in Customer table
<code>orderRef</code>	Order Reference (Your Reference)	Code	Required
<code>requestedDeliveryDate</code>	Requested Delivery Date	Date	
<code>dueDate</code>	Due Date	Date	
<code>shippingAgentCode</code>	Shipping Agent Code	Code	Requires Shipping Agent record
<code>locationCode</code>	Location Code	Code	Requires Location record
<code>vehicleRegistration</code>	Vehicle Registration	Text	
<code>shipToName</code>	Ship-to Name	Text	
<code>shipToName2</code>	Ship-to Name 2	Text	
<code>shipToAddress</code>	Ship-to Address	Text	
<code>shipToAddress2</code>	Ship-to Address 2	Text	
<code>shipToCity</code>	Ship-to City	Text	

JSON Property	Description	Type	Notes
shipToCounty	Ship-to County	Text	
shipToPostCode	Ship-to Post Code	Code	
shipToContact	Ship-to Contact	Text	
shipToEmail	Ship-to E-mail	Text	
miscReference1	Miscellaneous Reference 1	Text	
miscReference2	Miscellaneous Reference 2	Text	
responseText	Response JSON	Text	Populated by system after processing

Known Issues: Processing errors (e.g. order not found, active warehouse picks) are returned as a JSON string in `responseText`, **not** as a 4xx HTTP status. An `HTTP 200` response does not indicate success — always inspect `responseText` for failure indicators. Avoid sending concurrent requests; the entry number allocation and line table cleanup do not isolate per-request, which can cause collisions under concurrent load.

salesOrderCancellationLines (PAG50165) — sub-page

JSON Property	Description	Type
gNumber	G Number (Item No.)	Code
cancellationReason	Cancellation Reason	Text
cancellationDate	Cancellation Date	Date
qty	Quantity	Decimal

purchaseOrders (PAG50087)

JSON Property	Description	Type	Editable
id	System identifier	Guid	No
orderNumber	Purchase Order No.	Code[20]	No

JSON Property	Description	Type	Editable
orderDate	Order Date	Date	No
supplierCode	Vendor No.	Code[20]	No
orderType	Order Type	Code	No
requiredByDate	Expected Receipt Date	Date	No
destinationWarehouse	Location Code	Code	No
containerType	Container Type	Code	No
status	Status	Option	No
currencyCode	Currency Code	Code	No

purchaseOrderLines (PAG50181) — sub-page of purchaseOrders

JSON Property	Description	Type	Editable
id	System identifier	Guid	No
itemNo	Item No.	Code[20]	No
description	Description	Text	No
quantityOrdered	Quantity Ordered	Decimal	No
directUnitCost	Direct Unit Cost	Decimal	No
quantityReceived	Quantity Received	Decimal	No
quantityInvoiced	Quantity Invoiced	Decimal	No

purchaseOrderCancellations (PAG50229)

JSON Property	Description	Type	Notes
id	System identifier	Guid	Auto-generated
cancellationType	Cancellation Type	Enum	Required. Cancel or Modify
customerCode	Vendor No.	Code[20]	Required — must exist in Vendor table

JSON Property	Description	Type	Notes
<code>orderRef</code>	Order Reference	Code	Required
<code>locationCode</code>	Location Code	Code	Requires Location record
<code>responseText</code>	Response JSON	Text	Populated by system after processing

Known Issues: Same response pattern as `salesOrderCancellations` — inspect `responseText` for failure, not only HTTP status. Note also that the `customerCode` JSON property maps to the **Vendor Code** field internally; BC error messages will reference "Vendor Code", not "Customer Code". Concurrent requests carry the same collision risks as `salesOrderCancellations`.

`purchaseOrderCancellationLines` (PAG50230) — sub-page

JSON Property	Description	Type
<code>gNumber</code>	G Number (Item No.)	Code
<code>cancellationReason</code>	Cancellation Reason	Text
<code>cancellationDate</code>	Cancellation Date	Date
<code>qty</code>	Quantity	Decimal

`pcgPalletisedLoadBuilds` (PAG50164)

JSON Property	Description	Type	Editable
<code>systemId</code>	System identifier	Guid	No
<code>salesOrderNo</code>	Sales Order No.	Code[20]	Yes
<code>collectionReference</code>	Collection Reference	Text	Yes
<code>loadReference</code>	Load Reference	Text	Yes
<code>collectionDate</code>	Collection Date	Date	Yes
<code>deliveryDate</code>	Delivery Date	Date	Yes
<code>status</code>	Sales Order Status	Option	No

Data Setup Notes: `salesOrderNo` must reference an existing open **Sales Order** (Sales Header table). The order must already exist before posting this record.

Known Issues: Sales Order must be in **Open** status; a Released order will be rejected, returning **HTTP 500** with an error message in the body.

Bound Action — `submit`

POST

`/api/technologyManagement/integrations/v2.0/pcgPalletisedLoadBuilds({id})/Microsoft.NAV.submit`

Triggers palletised load processing for the identified Sales Order. Validates the payload, processes all pallet lines, and creates Warehouse Shipments. Returns the updated entity.

Detail	Value
Parameters	None — entity resolved from <code>{id}</code> in the URL
Resolves order by	<code>id</code> (SystemId) or <code>salesOrderNo</code>
On success	Warehouse Shipments created; returns updated entity
On failure	HTTP error with processing error message

`pcgPalletisedLoadLines` (PAG50163) — sub-page of `pcgPalletisedLoadBuilds`

JSON Property	Description	Type	Editable
<code>id</code>	System identifier	Guid	No
<code>documentNo</code>	Sales Order No.	Code[20]	No
<code>lineNo</code>	Line No.	Integer	No
<code>number</code>	Item No.	Code[20]	Yes
<code>itemReferenceNumber</code>	Item Reference No.	Code[50]	Yes
<code>quantity</code>	Quantity on Sales Line	Decimal	No

JSON Property	Description	Type	Editable
quantityOnLoad	Quantity on Load	Decimal	Yes
quantityToCancel	Quantity to Cancel	Decimal	Yes
palletQuantityOnLoad	Pallet Quantity on Load	Decimal	Yes
weightOnLoad	Weight on Load	Decimal	Yes
unitsOnLoad	Units on Load	Decimal	Yes
palletRequirements	Pallet Requirements	Text	Yes
shipmentTag	Shipment Tag	Text	Yes
shipmentDate	Shipment Date	Date	Yes

salesReturnOrders (PAG50231)

JSON Property	Description	Type	Editable
id	System identifier	Guid	No
number	Document No.	Code[20]	Yes
externalDocumentNumber	External Document No.	Text	Yes
orderDate	Document Date	Date	Yes
postingDate	Posting Date	Date	Yes
customerId	Customer Id (Sell-to)	Guid	No
customerNumber	Customer No.	Code[20]	Yes
customerName	Customer Name	Text	No
billToName	Bill-to Name	Text	No
billToCustomerId	Bill-to Customer Id	Guid	No
billToCustomerNumber	Bill-to Customer No.	Code[20]	Yes
shipToName	Ship-to Name	Text	Yes

JSON Property	Description	Type	Editable
shipToContact	Ship-to Contact	Text	Yes
sellToAddressLine1	Sell-to Address	Text	Yes
sellToAddressLine2	Sell-to Address 2	Text	Yes
sellToCity	Sell-to City	Text	Yes
sellToCountry	Sell-to Country/Region Code	Code	Yes
sellToState	Sell-to County	Text	Yes
sellToPostCode	Sell-to Post Code	Code	Yes
billToAddressLine1	Bill-to Address	Text	No
billToAddressLine2	Bill-to Address 2	Text	No
billToCity	Bill-to City	Text	No
billToCountry	Bill-to Country/Region Code	Code	No
billToState	Bill-to County	Text	No
billToPostCode	Bill-to Post Code	Code	No
shipToAddressLine1	Ship-to Address	Text	Yes
shipToAddressLine2	Ship-to Address 2	Text	Yes
shipToCity	Ship-to City	Text	Yes
shipToCountry	Ship-to Country/Region Code	Code	Yes
shipToState	Ship-to County	Text	Yes
shipToPostCode	Ship-to Post Code	Code	Yes
shortcutDimension1Code	Shortcut Dimension 1 Code	Code	Yes
shortcutDimension2Code	Shortcut Dimension 2 Code	Code	Yes
currencyId	Currency Id	Guid	No

JSON Property	Description	Type	Editable
<code>currencyCode</code>	Currency Code	Code	Yes
<code>pricesIncludeTax</code>	Prices Including VAT	Boolean	Yes
<code>paymentTermsId</code>	Payment Terms Id	Guid	Yes
<code>shipmentMethodId</code>	Shipment Method Id	Guid	Yes
<code>salesperson</code>	Salesperson Code	Code	Yes
<code>partialShipping</code>	Partial Shipping	Boolean	No
<code>requestedDeliveryDate</code>	Requested Delivery Date	Date	Yes
<code>discountAmount</code>	Invoice Discount Amount	Decimal	No
<code>discountAppliedBeforeTax</code>	Discount Applied Before Tax	Boolean	No
<code>totalAmountExcludingTax</code>	Total Amount Excluding Tax	Decimal	No
<code>totalTaxAmount</code>	Total Tax Amount	Decimal	No
<code>totalAmountIncludingTax</code>	Total Amount Including Tax	Decimal	No
<code>fullyShipped</code>	Fully Shipped	Boolean	No
<code>status</code>	Status	Option	No
<code>lastModifiedDateTime</code>	Last Modified Date Time	DateTime	No
<code>phoneNumber</code>	Sell-to Phone No.	Text	Yes
<code>email</code>	Sell-to E-Mail	Text	Yes

Data Setup Notes: `paymentTermsId` accepts a Guid — if the value does not match a Payment Terms record, an error is raised. `shipmentMethodId` likewise accepts a Guid matching a Shipment Method record. `customerId`, `billToCustomerId`, and `currencyId` are read-only Guids resolved from the Customer and Currency tables via `OnAfterGetRecord`.

salesReturnLines (PAG50232) — sub-page of salesReturnOrders

JSON Property	Description	Type	Editable
id	System identifier	Guid	No
documentId	Document Id	Text[20]	No
sequence	Line No.	Integer	No
itemId	Item Id	Text[20]	Yes
accountId	Account Id	Text[20]	Yes
lineType	Line Type	Option	Yes
lineObjectNumber	Item / Account No.	Code[20]	Yes
description	Description	Text	Yes
description2	Description 2	Text	Yes
unitOfMeasureId	Unit of Measure Id	Guid	Yes
unitOfMeasureCode	Unit of Measure Code	Code[10]	Yes
quantity	Quantity	Decimal	Yes
unitPrice	Unit Price	Decimal	Yes
discountAmount	Line Discount Amount	Decimal	Yes
discountPercent	Line Discount %	Decimal	Yes
discountAppliedBeforeTax	Discount Applied Before Tax	Boolean	No
amountExcludingTax	Amount Excluding Tax	Decimal	No
taxCode	VAT Prod. Posting Group	Code	Yes
taxPercent	VAT %	Decimal	No
totalTaxAmount	Total Tax Amount	Decimal	No
amountIncludingTax	Amount Including Tax	Decimal	No
invoiceDiscountAllocation	Invoice Discount Allocation	Decimal	No

JSON Property	Description	Type	Editable
netAmount	Net Amount	Decimal	No
netTaxAmount	Net Tax Amount	Decimal	No
netAmountIncludingTax	Net Amount Including Tax	Decimal	No
shipmentDate	Shipment Date	Date	Yes
shippedQuantity	Return Qty. Received	Decimal	No
invoicedQuantity	Quantity Invoiced	Decimal	No
invoiceQuantity	Qty. to Invoice	Decimal	Yes
shipQuantity	Return Qty. to Receive	Decimal	Yes
itemVariantId	Item Variant Id	Guid	Yes
locationId	Location Id	Guid	Yes

Customer Item Reference Resolution: When posting or patching a `lineObjectNumber` value on a return line, if the supplied value does not match a direct Item No., the system will attempt to resolve it via the customer's item cross-references (`Item Reference` table, filtered to the return order's Customer No.). If a matching cross-reference is found, the Item No. is substituted automatically before the line is written. This allows callers to send customer-specific part numbers rather than internal item numbers.

salesReturnOrdersExt (PAG50233)

JSON Property	Description	Type	Editable
systemId	System identifier	Guid	No
number	Document No.	Code[20]	Yes
customerNo	Customer No.	Code[20]	Yes
shipToEmailAddress	Ship-to E-mail Address	Text	Yes
miscReference1	Miscellaneous Reference 1	Text	Yes

JSON Property	Description	Type	Editable
<code>miscReference2</code>	Miscellaneous Reference 2	Text	Yes
<code>miscReference3</code>	Miscellaneous Reference 3	Text	Yes
<code>externalRetailerName</code>	External Retailer Name	Text	Yes
<code>externalOrderReferences</code>	External Order References	Text	Yes
<code>invoiceName</code>	Invoice Name	Text	Yes
<code>invoiceAdd1</code>	Invoice Address Line 1	Text	Yes
<code>invoiceAdd2</code>	Invoice Address Line 2	Text	Yes
<code>invoiceAdd3</code>	Invoice Address Line 3	Text	Yes
<code>invoiceAdd4</code>	Invoice Address Line 4	Text	Yes
<code>invoicePostcode</code>	Invoice Postcode	Code	Yes
<code>transportMethod</code>	Transport Method	Code	Yes
<code>shipmentMethodCode</code>	Shipment Method Code	Code	Yes
<code>shipToPhoneNo</code>	Ship-to Phone No.	Text	Yes
<code>shipToPhoneNo2</code>	Ship-to Phone No. 2	Text	Yes
<code>shippingAgentServiceCode</code>	Shipping Agent Service Code	Code	Yes
<code>shippingAgentCode</code>	Shipping Agent Code	Code	Yes
<code>systemCreatedAt</code>	Created date/time	DateTime	No
<code>systemCreatedBy</code>	Created by	Guid	No
<code>systemModifiedAt</code>	Last modified date/time	DateTime	No
<code>systemModifiedBy</code>	Last modified by	Guid	No

Note: `salesReturnOrdersExt` / `salesReturnOrdersExt` expose only the custom PCG/TM fields alongside the system identifier and document number. Use `salesReturnOrders` (PAG50231) when you need the full standard address and header fields.

salesReturnLinesExt (PAG50234) — sub-page of salesReturnOrdersExt

JSON Property	Description	Type	Editable
id	System identifier	Guid	No
documentNo	Document No.	Code[20]	No
lineNo	Line No.	Integer	No
type	Line Type	Option	Yes
no	Item / Account No.	Code[20]	Yes
description	Description	Text	Yes
quantity	Quantity	Decimal	Yes
unitPrice	Unit Price	Decimal	Yes
lineAmount	Line Amount	Decimal	No
miscLineReference1	Miscellaneous Line Reference 1	Text	Yes
pcgUniqueLineReference	PCG Unique Line Reference	Text	Yes
serialNo	Serial No.	Code	Yes
locationCode	Location Code	Code	Yes
shippingAgentServiceCode	Shipping Agent Service Code	Code	Yes
shippingAgentCode	Shipping Agent Code	Code	Yes
height	Height	Decimal	No
width	Width	Decimal	Yes
grossWeight	Gross Weight	Decimal	No
depth	Depth	Decimal	No
commodityCode	Commodity Code / Tariff No.	Code[20]	No
vehicleRegistration	Vehicle Registration	Text	Yes
dropNumber	Drop Number	Text	Yes

JSON Property	Description	Type	Editable
<code>attachToInventoryLine</code>	Attach To Line No.	Integer	Yes

Serial No. Tracking: On insert, if a `serialNo` is provided, a surplus Reservation Entry is automatically created to register serial number item tracking. On modify, if the serial no. changes, the existing tracking entry is replaced with the new value. Fields `height`, `depth`, and `commodityCode` are read-only — they are populated from the Item card via `PopulateItemData`. `grossWeight` is read-only on PATCH but can be provided on POST via the insert handler.

`warehouseReceiptFreight` (PAG50167)

JSON Property	Description	Type	Editable
<code>id</code>	System identifier	Guid	No
<code>receiptNumber</code>	Warehouse Receipt No.	Code[20]	No
<code>locationCode</code>	Location Code	Code	No
<code>assignedUserId</code>	Assigned User ID	Code	No
<code>postingDate</code>	Posting Date	Date	No
<code>lastFreeDate</code>	Last Free Date	Date	Yes
<code>containerNumber</code>	Container Number	Code/Text	Yes
<code>vesselName</code>	Vessel Name	Text	Yes
<code>inboundBookingDate</code>	Inbound Booking Date	Date	Yes
<code>inboundBookingTime</code>	Inbound Booking Time	Time	Yes
<code>freightForwarder</code>	Freight Forwarder	Text	Yes
<code>portOfDischarge</code>	Port of Discharge	Text	Yes
<code>portOfLoading</code>	Port of Loading	Text	Yes

`warehouseReceiptFreightLines` (PAG50169) — sub-page of `warehouseReceiptFreight`

JSON Property	Description	Type	Editable
<code>id</code>	System identifier	Guid	No
<code>orderNo</code>	Source Order No.	Code	No
<code>itemNo</code>	Item No.	Code[20]	No
<code>description</code>	Description	Text	No
<code>quantity</code>	Quantity	Decimal	No

Read-only: All fields on `warehouseReceiptFreightLines` are read-only. This is a reporting sub-page that displays the line items received on the warehouse receipt.

Service-Enabled Procedures

`submit` — Palletised Load Build

OData Bound Action

POST

/api/technologyManagement/integrations/v2.0/pcgPalletisedLoadBuilds({`id`})/Microsoft.NAV.submit

Property	Detail
Defined in	PAG50164 "PCG Pallet Load Build TMA2B9"
Signature	<code>procedure submit(var ActionContext: WebServiceActionContext)</code>
Parameters	None in body — entity resolved via <code>{id}</code> in the URL
Returns	Updated <code>pcgPalletisedLoadBuild</code> entity

Behaviour:

1. Resolves the real `Sales Header` record from the temp record's `SystemId` or `No..`
2. Calls `PCGPalletLoadAPIHandlerTMA2B9.ProcessPayload()` to validate and process all pallet lines.
3. Builds Warehouse Shipment(s) via `PCGWhseShpmtBuilder`.
4. Reloads the temp record from the updated Sales Header.

5. Sets `ActionContext` result to `Updated`, returning the refreshed entity to the caller.

Errors are returned as HTTP errors with a descriptive message.

GetOrCreateWarehouseReceipt — Warehouse Receipt Lookup

OData / SOAP Function

Property	Detail
Defined in	COD50086 "Whse. Receipt Lookup TMA2B9"
Signature	procedure GetOrCreateWarehouseReceipt(documentType: Text; documentNo: Code[20]): Code[20]
Returns	Warehouse Receipt No. (Code[20])

Parameters:

Parameter	Type	Required	Accepted Values
documentType	Text	Yes	"Purchase" or "Transfer" (case-insensitive)
documentNo	Code[20]	Yes	Existing Purchase Order or Transfer Order No.

Behaviour:

1. Validates `documentNo` is not blank.
2. Parses `documentType` to the internal `Warehouse Activity Source Document` enum — errors if unrecognised.
3. Verifies the source document exists (Purchase Order or Transfer Header).
4. Returns the existing Warehouse Receipt No. if one already references that source document.
5. If no receipt exists, creates a new Warehouse Receipt and returns its No.

This is Step 1 of the P8 Freight Shipping Info workflow. See [Caller Workflows — P8](#) for the full sequence.

Caller Workflows

This section describes the complete sequence of HTTP calls required for integrations that involve more than one request.

P7 — Palletised Load Build

Two calls are required: one to write the pallet load data, then a second to trigger processing.

Step 1 — Write pallet load assignments (deep insert)

POST .../pcgPalletisedLoadBuilds

Content-Type: application/json

```
{
  "salesOrderNo": "S0001234",
  "collectionReference": "COL-001",
  "loadReference": "LOAD-001",
  "collectionDate": "2026-05-01",
  "deliveryDate": "2026-05-02",
  "pcgPalletisedLoadLines": [
    { ... }
  ]
}
```

The response body contains the created record including its `id` (SystemId). Capture this for Step 2.

Step 2 — Trigger processing

POST .../pcgPalletisedLoadBuilds({id})/Microsoft.NAV.submit

Content-Type: application/json

```
{}
```

On success, returns the updated `pcgPalletisedLoadBuild` entity (HTTP 200). On failure, returns an HTTP error with the processing error message.

Step	Method	Endpoint	Purpose
1	POST	<code>pcgPalletisedLoadBuilds</code>	Write pallet load header + lines
2	POST	<code>pcgPalletisedLoadBuilds({id})/Microsoft.NAV.submit</code>	Validate, process lines, create Warehouse Shipments

P8 — Freight Shipping Info

Three calls are required: look up or create a Warehouse Receipt, find the API record by receipt number, then update the freight fields.

Step 1 — Get or create Warehouse Receipt

```
POST .../ODataV4/Whse_Receipt_Lookup_TMA2B9_GetOrCreateWarehouseReceipt
```

```
Content-Type: application/json
```

```
{
  "documentType": "Purchase",
  "documentNo": "P0001234"
}
```

The response contains the Warehouse Receipt No. (e.g. "WR001234"). Capture this for Step 2.

Accepted values for `documentType`: "Purchase" or "Transfer" (case-insensitive).

Step 2 — Locate the `warehouseReceiptFreight` record

```
GET .../warehouseReceiptFreight?$filter=receiptNumber eq 'WR001234'
```

The response returns the matching record. Capture its `id` for Step 3.

Step 3 — Update freight fields

```
PATCH .../warehouseReceiptFreight({id})
```

```
Content-Type: application/json
```

```
{
  "lastFreeDate": "2026-05-10",
  "containerNumber": "CONT-XYZ",
  "vesselName": "MV Example",
  "inboundBookingDate": "2026-05-08",
  "inboundBookingTime": "09:00:00",
  "freightForwarder": "Acme Freight",
  "portOfDischarge": "Felixstowe",
  "portOfLoading": "Shanghai"
}
```

Step	Method	Endpoint	Purpose
1	POST	<code>GetOrCreateWarehouseReceipt</code> web service	Get or create Warehouse Receipt; returns receipt number
2	GET	<code>warehouseReceiptFreight?\$filter=receiptNumber eq '{no}'</code>	Locate the API record; returns <code>id</code>
3	PATCH	<code>warehouseReceiptFreight({id})</code>	Write freight fields

Sales Return Orders — PATCH

Two strategies are available depending on which fields need updating. Use the **full** endpoint pair when updating standard header or line fields; use the **slim** endpoint pair when updating only PCG-specific custom fields.

Full Order (`salesReturnOrders` / `salesReturnLines`)

Step 1 — Locate the return order

```
GET .../salesReturnOrders?$filter=number eq 'SR0001234'
```

The response returns the matching record. Capture the `systemId` value for Step 2.

Step 2 — Update header fields

```
PATCH .../salesReturnOrders({systemId})
```

```
Content-Type: application/json
```

```
If-Match: *
```

```
{
  "externalDocumentNumber": "CUST-REF-001",
  "requestedDeliveryDate": "2026-06-01",
  "shipToName": "Customer Warehouse",
  "miscReference1": "REF001"
}
```

Only include the fields that need to be changed — fields omitted from the body are left unchanged.

Step 3 (optional) — Locate return lines

To update a specific line, first retrieve the lines to obtain each line's `id`:

```
GET .../salesReturnOrders({systemId})/salesReturnLines
```

Step 4 (optional) — Update a return line

```
PATCH .../salesReturnOrders({systemId})/salesReturnLines({lineId})
Content-Type: application/json
If-Match: *

{
  "rtbCondition": "Used",
  "rtbRoutingCode": "ROUTE-A",
  "quantity": 2
}
```

Step	Method	Endpoint	Purpose
1	GET	<code>salesReturnOrders?\$filter=number eq '{no}'</code>	Locate return order; returns <code>systemId</code>
2	PATCH	<code>salesReturnOrders({systemId})</code>	Update header fields
3	GET	<code>salesReturnOrders({systemId})/salesReturnLines</code>	Retrieve lines; returns line <code>id</code> values
4	PATCH	<code>salesReturnOrders({systemId})/salesReturnLines({lineId})</code>	Update a specific return line

Steps 3 and 4 may be omitted when only header fields need updating.

Slim (`salesReturnOrdersExt` / `salesReturnLinesExt`)

Use `salesReturnOrdersExt` when only PCG-specific custom fields need updating. The slim endpoint exposes only custom fields alongside the system identifier and document number, so the request body can be kept minimal.

Step 1 — Locate the return order

```
GET .../salesReturnOrdersExt?$filter=number eq 'SR0001234'
```

The response returns the matching record. Capture the `systemId` value for Step 2.

Step 2 — Update custom fields

```
PATCH .../salesReturnOrdersExt({systemId})
Content-Type: application/json
If-Match: *

{
  "miscReference1": "REF001",
  "miscReference2": "REF002",
  "externalRetailerName": "Retailer Name",
  "externalOrderReferences": "EXT-ORDER-001"
}
```

Step	Method	Endpoint	Purpose
1	GET	<code>salesReturnOrdersExt?\$filter=number eq '{no}'</code>	Locate return order; returns <code>systemId</code>
2	PATCH	<code>salesReturnOrdersExt({systemId})</code>	Update PCG custom fields

Choosing between Full and Slim: If the caller only needs to write custom PCG fields (e.g. `miscReference1`, `externalRetailerName`), prefer `salesReturnOrdersExt` — the payload is smaller and the request will not inadvertently touch standard BC header fields. Use `salesReturnOrders` when standard fields (address, dates, shipping details, RTB line fields) also need to be written.

Functional Areas

Common / Setup

Central configuration and integration framework objects shared across all functional areas.

Setup Page: PAG50086 `PCG Setup TMA2B9` (Card page — not an API endpoint)

Setup Field	Purpose
Connector Code	TMXIF connection to PCG API

Setup Field	Purpose
Auto-Send Manifest	Automatically send manifests on shipment posting
Manifest Batch Mode	Send manifests in batch
Auto-Release Pallet Load	Automatically release palletised load on creation
RTB Customer No.	Default customer for RTB return sales orders
RTB Location Code	Default location for RTB returns
Retry Count	Number of retries on manifest send failure
Failure Email	Email address for manifest send failure alerts

TMXIF Integration: The app extends the **Int. Connector TMXIF** (51910) table and card with two additional fields:

Field	Type	Purpose
PCG API Version	Code[10]	Target API version
OAuth Token Endpoint	Text[250]	OAuth2 token URL for authentication

P5 — Order Cancellation

Handles inbound cancellation or modification requests for both Sales Orders and Purchase Orders. The caller POSTs a cancellation request with a header and lines in a single call. The system validates the order, checks for active warehouse picks or posted receipts, and either removes the specified lines or deletes the order entirely.

The **responseText** field on the returned record contains a JSON object indicating success or failure. See the [API Endpoint Reference](#) for request body examples.

Flow:

```

POST salesOrderCancellations → Sales Cancel Request + Lines inserted
  → OnInsert → SalesOrderCancelMgt.ProcessCancellation()
    → Find Sales Order → Check picks/shipments → Reopen if needed
    → Delete requested lines or full order → Archive
    → SalesCancelResponse.BuildSuccessResponse() / BuildErrorResponse()
    → responseText field populated on record

```

POST purchaseOrderCancellations → PO Cancel Request + Lines inserted
→ OnInsert → POCancelMgt.ProcessCancellation()
→ Find Purchase Order → Check receipts → Reopen if needed
→ Delete requested lines or full order → Archive
→ POCancelResponse.BuildSuccessResponse() / BuildErrorResponse()
→ responseText field populated on record

Cancellation Type values:

Value	Meaning
Cancel	Remove the specified lines (or the entire order if all lines are cancelled)
Modify	Modify the order — lines are removed and the order is re-released with remaining lines

P6 — Sales Order Line Dispatch

Outbound only. When a Sales Shipment is posted in Business Central, the system automatically builds a JSON dispatch confirmation payload and sends it to the configured PCG endpoint. No inbound API call is required for this area.

Flow:

Sales Shipment Header → OnAfterInsert event
→ DispConfOutboundMgt.CreateOutboundEntityChange()
→ Resolves Connector Code from PCG Setup
→ Inserts Outbound Entity Change TMXIF record

[TMXIF Integration Framework processes pending changes]
→ DispConfExportAPI.OnRun() (TableNo = Int. Entity Interface TMXIF)
→ ManifestJSONBuilder.BuildCompleteDispatchConfirmation()
→ TMXIF communication library exports JSON payload

The payload is a JSON array — one flat object per shipment line. See [Outbound JSON Payloads — P6 Sales Order Line Dispatch](#) for the full structure.

P7 — Palletised Load Build

Inbound integration — PCG POSTs palletised load assignments against existing Sales Orders. The app validates the payload, processes lines, creates Warehouse Shipments, and optionally releases the Sales

Order.

Flow:

```
POST pcgPalletisedLoadBuilds → Sales Header (temp) + Lines inserted
→ OnInsert → PCGPalletLoadAPIHandler.Handle()
→ ValidateHeaderState() → ValidateHeaderFields() → ValidateLines()
→ PCGPalletisedLineProcessor.ProcessLines()
→ PCGWhseShpmtBuilder.BuildShipments()
→ (optional) ReleaseSalesOrder()
```

Buffer Table (TAB50164 **Palletised Load Buffer TMA2B9**) — temporary, holds processing state including **Error Message** and **Result JSON**.

See [Caller Workflows — P7](#) for the full step-by-step request sequence.

P8 — Freight Shipping Info

Two-step integration:

1. **Step 1 (Lookup):** **WhseReceiptLookup.GetOrCreateWarehouseReceipt()** — given a document type and number, returns the Warehouse Receipt No. (creates a receipt if none exists).
2. **Step 2 (Update):** **GET/PATCH warehouseReceiptFreight** — PCG reads or updates freight-specific fields on the Warehouse Receipt Header.

The lookup codeunit supports **Purchase Order** and **Transfer Order** document types.

See [Caller Workflows — P8](#) for the full step-by-step request sequence.

P9 — RTB Returns

Inbound Excel-based integration processed within the Business Central client. A warehouse operator uploads an RTB (Return To Base) Excel file via the **Sales Return Order List** action; the app parses, validates, and creates Sales Return Orders (SROs). There are no direct API calls for this area — the upload is handled through the BC UI.

Flow:

```
Action: "Import RTB Returns" → Upload Excel file stream
→ PCGRTBExcelParser.ParseFile() → populates PCG RTB Import Line (temp table)
→ PCGRTBManifestVal.ValidateLines()
→ Show PCG RTB Import Preview (PAG50168) → operator reviews / blocks rows
→ PCGRTBSROManager.ProcessImportLines()
```

- [Group by Load](#) Reference
- CreateSROForLoadRef() → CreateSROLine()
 - PCGRTBItemResolver.ResolveItemNo()
 - (tries: Vendor Reference → Item [No.](#) 2 → Barcode)

RTB Condition Enum (50052):

Value	Caption
0	<i>(blank)</i>
1	New
2	Used

Sales Line extensions added for RTB lines:

Field	Type
RTB Condition TMA2B9	Enum RTBCondition
RTB Routing Code TMA2B9	Code
Original Case No. TMA2B9	Text
Original Customer Postcode TMA2B9	Code
RTB Tracking No. TMA2B9	Code

RTB-specific fields are readable via the [salesReturnLines](#) (PAG50232) sub-page:

JSON Property	Description	Type
rtbCondition	RTB Condition (New or Used)	Option
rtbRoutingCode	RTB Routing Code	Code
originalCaseNo	Original Case No.	Text
origCustomerPostcode	Original Customer Postcode	Code
rtbTrackingNo	RTB Tracking No.	Code

P10 — Purchase Order

Outbound — When a Purchase Order is released in Business Central, the system automatically builds a JSON payload and sends it to the configured PCG endpoint. No inbound API call is required for this direction. See [Outbound JSON Payloads — P10 Purchase Order Export](#) for the full structure.

Outbound flow:

```
Purchase Order Released → OnAfterReleasePurchaseDoc (event)
→ POReleaseMgt.CreateOutboundEntityChange()
→ POJSONBuilder.BuildPurchaseOrderJSON()
→ POExportCodeunitAPI.OnRun() (TableNo = Int. Entity Interface TMXIF)
```

Inbound (CSV Import) — Operators can import Purchase Orders from a CSV file via the **PCG Purchase Import** list page (PAG50183).

Inbound CSV Import flow:

```
Action: Import CSV → stream
→ PCGPurchaseImportMgt.ImportFromStream() → Purchase Import Buffer (temp)
→ POImportValidation.ValidateBuffer()
→ POImportCreate.CreatePurchaseOrders()
```

Purchase Import Buffer fields (TAB50182):

Field	Type	Notes
Entry No.	Integer	Key
Order Number	Code	
Order Date	Date	
Supplier Code	Code[20]	Validated against Vendor
Buyer Code	Code[20]	
Order Type	Code	
Required By Date	Date	
Destination Warehouse	Code	Validated against Location
Part	Code[20]	Validated against Item

Field	Type	Notes
Description	Text	
Quantity Ordered	Decimal	
Supplier Quantity	Decimal	
Container Type	Code	
Import Status	Option	Blank / Error
Error Message	Text	

Inbound (read) — The `purchaseOrders` and `purchaseOrderLines` endpoints are available read-only for PCG to query purchase order status.

Sales Return Orders

Two API endpoint pairs are available for reading and writing Sales Return Orders:

Pair	Header page	Lines sub-page	When to use
Full	<code>salesReturnOrders</code> (PAG50231)	<code>salesReturnLines</code> (PAG50232)	Creating or reading return orders where full standard address and header fields are needed
Slim	<code>salesReturnOrdersExt</code> (PAG50233)	<code>salesReturnLinesExt</code> (PAG50234)	Patching only PCG-specific custom fields on an existing return order

Both pairs support GET, POST, and PATCH. `salesReturnOrders` additionally supports DELETE.

See [Field Reference by Endpoint](#) for complete field lists:

- [Full header fields \(PAG50231\)](#)
- [Full line fields \(PAG50232\)](#)
- [Slim header fields \(PAG50233\)](#)
- [Slim line fields \(PAG50234\)](#)

Outbound JSON Payloads

P6 Sales Order Line Dispatch

Sent automatically when a Sales Shipment is posted. The payload is a **JSON array** — one flat object per shipment line, with header fields repeated on each entry.

Data Source: All fields are populated from the Sales Shipment Header, Sales Shipment Lines, and the related Sales Order. The mapping of each JSON property to its source BC table/field is documented in the Field Reference table below.

```
[
  {
    "shipmentNumber": "string",
    "salesOrderNumber": "string",
    "customerNumber": "string",
    "customerName": "string",
    "shipToName": "string",
    "shipToAddress": "string",
    "shipToAddress2": "string",
    "shipToCity": "string",
    "shipToPostCode": "string",
    "shipToCountryCode": "string",
    "shipmentDate": "2026-04-27",
    "shippingAgent": "string",
    "trackingNumber": "string",
    "externalRetailerName": "string",
    "salesLineItemSequenceNumber": "string",
    "lineObjectNumber": "string",
    "lineObjectNumber2": "string",
    "lineObjectCustomerReference": "string",
    "lineObjectDescription": "string",
    "quantity": 0,
    "externalDocumentNumber": "string",
    "vehicleRegistration": "string",
    "dropNumber": "string",
    "miscReference1": "string",
    "miscReference2": "string",
    "miscReference3": "string",
    "miscellaneousLineReference1": "string",
    "pcgUniqueLineReference": "string"
  }
]
```

`dropNumber` is only included when it has a value.

Field Reference:

JSON Property	Source Table	Source Field	Notes
shipmentNumber	Sales Shipment Header	No.	
salesOrderNumber	Sales Header	No.	From the related Sales Order
customerNumber	Sales Shipment Header	Sell-to Customer No.	
customerName	Customer	Name	Resolved from Sell-to Customer No.
shipToName	Sales Shipment Header	Ship-to Name	
shipToAddress	Sales Shipment Header	Ship-to Address	
shipToAddress2	Sales Shipment Header	Ship-to Address 2	
shipToCity	Sales Shipment Header	Ship-to City	
shipToPostCode	Sales Shipment Header	Ship-to Post Code	
shipToCountryCode	Sales Shipment Header	Ship-to Country/Region Code	
shipmentDate	Sales Shipment Header	Shipment Date	ISO 8601: yyyy-MM-dd
shippingAgent	Sales Shipment Header	Shipping Agent Code	
trackingNumber	Sales Shipment Header	Package Tracking No.	
externalRetailerName	Sales Header	External Retailer Name	Sourced from open Sales Order if available

JSON Property	Source Table	Source Field	Notes
salesLineItemSequenceNumber	Sales Shipment Line	Line No.	
lineObjectNumber	Sales Shipment Line	Item No.	
lineObjectNumber2	Item	No. 2	SKU / Model No.
lineObjectCustomerReference	Item Reference	Reference No.	Customer cross-reference
lineObjectDescription	Sales Shipment Line	Description	
quantity	Sales Shipment Line	Quantity	Quantity shipped
externalDocumentNumber	Sales Header	External Document No.	Customer PO reference
vehicleRegistration	Sales Shipment Line	Vehicle Registration	
dropNumber	Sales Shipment Line	Drop Number	Omitted if blank
miscReference1	Sales Header	Miscellaneous Reference 1	Header-level
miscReference2	Sales Header	Miscellaneous Reference 2	Header-level
miscReference3	Sales Header	Miscellaneous Reference 3	Header-level
miscellaneousLineReference1	Sales Shipment Line	Miscellaneous Line Reference 1	Line-level
pcgUniqueLineReference	Sales Shipment Line	PCG Unique Line Reference	

P10 Purchase Order Export

Sent automatically when a Purchase Order is released. The payload is a single JSON object.

Note: The `orderNumber` field in the outbound payload maps to `Purchase Header."Vendor Order No."` (the supplier's order reference), **not** `Purchase Header."No."` (the internal BC number). This differs from the `purchaseOrders` API endpoint (PAG50087) where `orderNumber` maps to `Purchase Header."No."`.

Data Source: Header fields are populated from the Purchase Header table. Line fields and item tracking information are populated from the Purchase Line and Item Tracking tables. The mapping of each JSON property to its source BC table/field is documented in the Field Reference tables below.

```
{
  "orderNumber": "string",
  "orderDate": "2026-04-27T00:00:00",
  "supplierCode": "string",
  "requiredByDate": "2026-04-27T00:00:00",
  "destinationWarehouse": "string",
  "containerType": "string",
  "status": "string",
  "currencyCode": "string",
  "lines": [
    {
      "itemNo": "string",
      "description": "string",
      "quantityOrdered": 0,
      "directUnitCost": 0,
      "quantityReceived": 0,
      "quantityInvoiced": 0,
      "serialNumbers": [
        {
          "serialNo": "string",
          "quantity": 0
        }
      ]
    }
  ]
}
```

`serialNumbers` is only included on lines where the item has item tracking enabled.

Header Field Reference:

JSON Property	Source Table	Source Field	Notes
orderNumber	Purchase Header	Vendor Order No.	Supplier's order reference
orderDate	Purchase Header	Order Date	ISO 8601 with time
supplierCode	Purchase Header	Buy-from Vendor No.	
requiredByDate	Purchase Header	Expected Receipt Date	ISO 8601 with time
destinationWarehouse	Purchase Header	Location Code	
containerType	Purchase Header	Container Type TM9FA3	
status	Purchase Header	Status	Text value e.g. Released
currencyCode	Purchase Header	Currency Code	

Line Field Reference:

JSON Property	Source Table	Source Field	Notes
itemNo	Purchase Line	No.	
description	Purchase Line	Description	
quantityOrdered	Purchase Line	Quantity	
directUnitCost	Purchase Line	Direct Unit Cost	
quantityReceived	Purchase Line	Quantity Received	
quantityInvoiced	Purchase Line	Quantity Invoiced	
serialNo	Item Tracking	Serial No.	Only included when item has tracking enabled

JSON Property	Source Table	Source Field	Notes
quantity	Item Tracking	Quantity	Only included when item has tracking enabled

Note: `orderType` is mapped in the JSON builder but currently commented out pending availability of dependency symbols (`TM9FA3` field).

Permission Set

Permission Set 50048 — `PCGAPIPerm TMA2B9` (Assignable: Yes)

Grants `RIMD` (Read, Insert, Modify, Delete) on all app objects. Assign this permission set to any service or integration user account that needs to call the PCG API endpoints.

Data Model

Custom Tables

Table #	Name	Type	Primary Key	Purpose
50048	PO Cancel Request TMA2B9	Permanent	Entry No. (Integer)	Staging: inbound PO cancellation header
50049	PO Cancel Req. Line TMA2B9	Permanent	Entry No., Line No.	Staging: inbound PO cancellation lines
50050	Sales Cancel Request TMA2B9	Permanent	Entry No. (Integer)	Staging: inbound Sales cancellation header
50051	Sales Cancel Req. Line TMA2B9	Permanent	Entry No., Line No.	Staging: inbound Sales cancellation lines
50162	PCG Setup TMA2B9	Permanent	Primary Key (Code[10])	App configuration singleton
50164	Palletised Load Buffer TMA2B9	Temporary	Entry No.	Processing buffer for pallet load API

Table #	Name	Type	Primary Key	Purpose
50167	PCG RTB Import Line TMA2B9	Temporary	Entry No.	Staging: parsed RTB Excel rows
50182	Purchase Import Buffer TMA2B9	Temporary	Entry No.	Staging: parsed CSV purchase import rows

Table Extensions

Extension #	Extended Table	Extended Table #	New Fields Summary
EXT50051	Int. Connector TMXIF	51910	PCG API Version, OAuth Token Endpoint
EXT50048	Sales Line	37	Serial No., Cancellation Date, Cancellation Reason, Cancel Parent Ref
EXT50049	Sales Header	36	Cancellation Type, Cancellation Response
EXT50050	Purchase Line	39	Cancellation Date, Cancellation Reason
EXT50052	Sales Line (RTB)	37	RTB Condition, RTB Routing Code, Original Case No., Original Customer Postcode, RTB Tracking No.
EXT50212	Sales Line (Item Data)	37	Height TMA2B9, Width TMA2B9, Depth TMA2B9, Commodity Code TMA2B9
EXT50211	Purchase Header	38	Cancellation Type

Note: Freight fields on Warehouse Receipt Header (7316) — [Last Free Date](#), [Container Number](#), [Vessel Name](#), [Inbound Booking Date/Time](#), [Freight Forwarder](#), [Port of Discharge](#), [Port of Loading](#) — are provided by the [PCG Config](#) dependency app (publisher: Technology Management, id: [14a38d9c-69ef-4c65-bc46-b5d449e1fd68](#)).

Internal Components

Codeunits

Codeunit #	Name	Area	Role
50048	Sales Order Cancel Mgt TMA2B9	P5	Orchestrates Sales Order cancellation/modification
50049	Sales Cancel Response TMA2B9	P5	Builds success/error JSON response for Sales cancellation
50050	TMXIF Event Handler TMA2B9	Common	Implements TMXIF connection type interface (PCG)
50051	PCG RTB Excel Parser TMA2B9	P9	Parses RTB Excel upload into import buffer
50052	PCG RTB Manifest Val. TMA2B9	P9	Validates parsed RTB import lines
50085	PCG RTB Item Resolver TMA2B9	P9	Resolves item by vendor ref / Item No. 2 / barcode
50086	Whse. Receipt Lookup TMA2B9	P8	Finds or creates Warehouse Receipt for a document
50087	Cancel Line Buffer TMA2B9	P5	SingleInstance buffer: Sales cancellation lines
50162	PCG RTB SRO Manager TMA2B9	P9	Creates Sales Return Orders from RTB import lines
50163	Manifest JSON Builder TMA2B9	P6	Builds dispatch confirmation JSON from posted Sales Shipment
50164	Manifest Event Handler TMA2B9	P6	Test helper: builds dispatch confirmation JSON for test verification (no event subscribers)
50165	PCG Rest Client TMA2B9	Common	REST HTTP client with OAuth2 authentication
50166	SalesLine Item Data Mgt TMA2B9	Common	Event subscriber: resolves customer item references on APIV2 Sales Order Lines; auto-populates Height, Width, Depth, and Commodity Code on Sales Line validation
50167	Http Client Handler API TMA2B9	Common	Mockable HTTP client handler (test injection point)

Codeunit #	Name	Area	Role
50168	PO Release Mgt TMA2B9	P10	Event subscriber: triggers PO export on release
50169	PO JSON Builder TMA2B9	P10	Builds Purchase Order JSON for outbound export
50181	PCG Purchase Import Mgt TMA2B9	P10	Parses CSV stream into Purchase Import Buffer
50182	PO Cancel Line Buf TMA2B9	P5	SingleInstance buffer: PO cancellation lines
50183	PO Cancel Mgt TMA2B9	P5	Orchestrates Purchase Order cancellation/modification
50184	PO Import Validation TMA2B9	P10	Validates Purchase Import Buffer rows
50185	PO Import Create TMA2B9	P10	Creates Purchase Orders from validated import buffer
50186	PO Export Codeunit API TMA2B9	P10	TMXIF export runner for Purchase Order outbound flow
50211	PCGPalletLoadAPIHandler TMA2B9	P7	Orchestrates palletised load API processing
50212	PCG Whse.Shipmt. Builder TMA2B9	P7	Creates Warehouse Shipment headers and lines
50213	PCGPalletisedLineProces TMA2B9	P7	Processes individual pallet load lines
50229	PO Cancel Response TMA2B9	P5	Builds success/error JSON response for PO cancellation
50230	Disp.Conf. Outbound Mgt TMA2B9	P6	Event subscriber: creates Outbound Entity Change on Sales Shipment posting
50231	Disp.Conf. Export API TMA2B9	P6	TMXIF export runner for dispatch confirmation outbound flow

Dependencies

Publisher	App Name	Version	Purpose
Technology Management	Tecman X-Integration Framework Core	≥ 18.1.0.0	TMXIF connector and export interface base
Technology Management	PCG Config	≥ 27.3.0.0	Freight table extensions on Warehouse Receipt Header
Clever Dynamics	Clever Config	≥ 1.15.1	Configuration framework
Clever Dynamics	Clever Trade Plus	≥ 2.0.5	Trade extensions used by Sales/Item fields
Microsoft	Sustainability	≥ 27.3.0.0	Standard BC sustainability module
Microsoft	Subscription & Recurring Billing	≥ 27.0.0.0	Standard BC subscription billing module