

# Package ‘isismdl’

April 23, 2020

**Type** Package

**Title** Solve macroeconomic models

**Version** 1.6.0

**Date** 2016-02-18

**Author** Rob van Harrevelt [aut, cre]

**Maintainer** Rob van Harrevelt <rvanharrevelt@gmail.com>

**Description** Solve macroeconomic models.

**Depends** R (>= 3.5.0),  
regts

**SystemRequirements** GNU make

**License** GPL-3

**LazyData** TRUE

**RoxygenNote** 7.1.0

**Roxygen** list(markdown = TRUE, r6 = FALSE)

**Imports** methods,  
R6,  
readr,  
tools

**Suggests** testthat,  
knitr

**VignetteBuilder** knitr

## R topics documented:

all.equal . . . . .	3
change_data-methods . . . . .	4
clear_fit . . . . .	5
clear_fix . . . . .	6
convert_mdl_file . . . . .	6
copy . . . . .	7
fill_mdl_data . . . . .	7

fix_variables . . . . .	8
get_data-methods . . . . .	9
get_data_period . . . . .	10
get_endo_names . . . . .	10
get_eq_names . . . . .	12
get_exo_names . . . . .	13
get_labels . . . . .	13
get_last_solve_period . . . . .	14
get_maxlag . . . . .	14
get_maxlead . . . . .	14
get_param . . . . .	15
get_par_names . . . . .	15
get_period . . . . .	16
get_solve_status . . . . .	16
get_text . . . . .	17
get_var_names . . . . .	18
ifn_mdl . . . . .	19
init_data . . . . .	19
IsisMdl . . . . .	20
isis_mdl . . . . .	23
islm_mdl . . . . .	25
order . . . . .	25
read_mdl . . . . .	26
run_eqn . . . . .	26
serialize . . . . .	27
set_cvgcrit . . . . .	28
set_data-methods . . . . .	29
set_debug_eqn . . . . .	31
set_eq_status . . . . .	31
set_fit_options . . . . .	33
set_ftrelax . . . . .	34
set_labels . . . . .	35
set_param . . . . .	36
set_period . . . . .	36
set_rms . . . . .	37
set_solve_options . . . . .	38
set_values-methods . . . . .	41
solve . . . . .	43
solve_mdl . . . . .	44
write_mdl . . . . .	45

---

all.equal	Test if two <a href="#">IsisMdl</a> objects are (nearly) equal
-----------	--

---

## Description

`all.equal(x, y)` is a utility to compare R objects `x` and `y` testing near equality. If they are different, comparison is still made to some extent, and a report of the differences is returned. Do not use `all.equal` directly in if expressions - use `isTRUE(all.equal(...))`.

## Usage

```
## S3 method for class 'IsisMdl'
all.equal(target, current, ...)
```

## Arguments

<code>target</code>	and <code>IsisMdl</code> object
<code>current</code>	another <code>IsisMdl</code> object, to be compared with <code>target</code>
<code>...</code>	Arguments passed to the internal call of <a href="#">all.equal</a> .

## Details

The implementation of `all.equal` for `IsisMdl` objects first serialized the model using the `IsisMdl` method `serialize` and then uses [all.equal](#) of the base package.

## Value

Either `TRUE` or a character vector describing the differences between `target` and `current`.

## See Also

[all.equal](#)

## Examples

```
mdl <- islm_mdl("2017Q2/2018Q2")
mdl2 <- mdl$copy()
print(all.equal(mdl, mdl2))

# now modify mdl2
mdl2$set_values(600, names = "c")
print(all.equal(mdl, mdl2))
```

---

change\_data-methods    *IsisMdl methods: changes the model data or constant adjustments by applying a function.*

---

## Description

This methods of R6 class `IsisMdl` changes the model data or constant adjustments by applying a function.

## Usage

```
mdl$change_data(fun, names, pattern, period = mdl$get_data_period())

mdl$change_ca(fun names, pattern, period = mdl$get_data_period())

mdl is an IsisMdl object
```

## Arguments

`fun` a function applied each model timeseries or constant adjustment specified with argument `names` or `pattern`

`names` a character vector with variable names

`pattern` a regular expression

`period` an `period_range` object or an object that can be coerced to a `period_range`

... arguments passed to `fun`

## Details

The function specified with argument `fun` should be a function with at least one argument, for example `fun = function(x) {x + 0.1}`. The first argument (named `x` in the example) will be the model variable. The function is evaluated for each model variable separately. The values of the model variables for period range `period` are passed as a normal numeric vector (not a timeseries) to the first argument.

An example may help to clarify this. Consider the following statement

```
mdl$change_data(fun = myfun, names = c("c", "y"),
                period = "2017q1/2017q2"),
```

where `mdl` is a `DynMdl` object and `myfun` some function whose details are not relevant here. Method `change_data` evaluates this as

```
data <- mdl$get_data(names = c("c", "y"), period = "2017q1/2017q2")
data[, "c"] <- myfun(as.numeric(data[, "c"]))
data[, "y"] <- myfun(as.numeric(data[, "y"]))
mdl$set_data(data)
```

The function result must be a vector (or timeseries) of length one or with the same length as the number of periods in the period range `period`.

**Methods**

changes\_data Changes the model data

change\_ca Changes the constant adjustments

**See Also**

[get\\_data-methods](#), [set\\_data-methods](#) and [set\\_values-methods](#)

**Examples**

```
mdl <- islm_mdl(period = "2017Q1/2017Q3")

# increase y and yd with 10% for the full data period
mdl$change_data(pattern = "^y.?$", fun = function(x) {x * 1.1})

# increase ms in 2017Q1 and 2017Q2 with 10 and 20, resp.
mdl$change_data(names = "ms", fun = function(x, dx) {x + dx},
                dx = c(10, 20), period = "2017Q1/2017Q2")
print(mdl$get_data())
```

---

clear\_fit

---

[IsisMdl](#) method: *deletes all fit targets and rms values values*


---

**Description**

This methods of R6 class [IsisMdl](#) deletes all fit targets and root mean square (rms) error values for the fit procedure.

**Usage**

```
mdl$clear_fit()
```

mdl is an [IsisMdl](#) object

**See Also**

[set\\_fit](#) and [get\\_fit](#)

---

clear_fix	<a href="#">IsisMdl</a> method: deletes all fix values
-----------	--

---

### Description

This methods of R6 class [IsisMdl](#) deletes all fix values

### Usage

```
mdl$clear_fix()
mdl is an IsisMdl object
```

### See Also

[set\\_fix](#), [fix\\_variables](#) and [get\\_fix](#)

---

convert_md1_file	Converts an <a href="#">IsisMdl</a> a model file.
------------------	---

---

### Description

Converts an [IsisMdl](#) a model file.

### Usage

```
convert_md1_file(
  model_file,
  output_file,
  conversion_options = list(),
  parse_options = list()
)
```

### Arguments

model_file	The name of the model file. An extension md1 is appended to the specified name if the filename does not already have an extension
output_file	The name of the output file.
conversion_options	conversion options. See section Conversion options.
parse_options	a named list with options passed to the model parser. See section "Parse option" in the description of function <a href="#">isis_md1</a> .

### Conversion options

The following conversion options can be specified with argument `conversion_options`. This argument should be a named list (for example, `list(substitute = TRUE)`).

`substitute` Specify TRUE to substitute user functions. The default is FALSE.

`make_dynare` Specify TRUE to convert the model to a Dynare mod file. The default is FALSE.

---

copy	<i>IsisMdl method: Returns a copy of this IsisMdl object</i>
------	--

---

### Description

This method of R6 class `IsisMdl` returns a deep copy of an `IsisMdl` object

### Usage

```
mdl$copy()
```

mdl is an `IsisMdl` object

### Details

`mdl$copy()` is equivalent to `mdl$clone(deep = TRUE)`

### Examples

```
mdl <- isl_mdl("2017Q1/2019Q2")
mdl2 <- mdl$copy()
```

---

fill_mdl_data	<i>IsisMdl method: Calculates missing model data from identities</i>
---------------	--

---

### Description

This method of R6 class `IsisMdl` attempts to calculate missing data for endogenous variables of a model by solving the identity equations in solution order.

The procedure can be used to fill in data before and beyond the model period (as set by method `set_period` for as many variables as possible.

### Usage

```
mdl$fill_mdl_data(period = mdl$get_data_period(),
                  report = c("period", "minimal", "no"))
```

mdl is an `IsisMdl` object

**Arguments**

period a [period\\_range](#) object

report Defines the type of report about the number of replaced missing values. See details.

**Details**

Argument `report` can be used to specify the type of report about the number of replaced missing values. Specify

`minimal` to get a minimal report. Only the total number of replaced missing values is reported

`period` to get a report per period (default). For each period the number of replaced missing values is reported

`no` to not generate a report

**Examples**

```
mdl <- islm_mdl(period = "2017Q1/2018Q4")

mdl$set_values(200, names = "t", period = "2017Q1")
mdl$fill_mdl_data(period = "2017Q1")
print(mdl$get_data(names = "yd"))
```

---

fix_variables	<a href="#">IsisMdl</a> method: Fix variables to their current values
---------------	---

---

**Description**

This method of R6 class [IsisMdl](#) fixes the specified model variables to their current values.

**Usage**

```
mdl$fix_variables(names, pattern, period = mdl$get_period())
```

mdl is an [IsisMdl](#) object

**Arguments**

pattern a regular expression specifying the variable names

names a character vector with variable names

period an [period\\_range](#) object or an object that can be coerced to a `period_range`

**See Also**

[set\\_fix](#) and [get\\_fix](#)



## Examples

```
mdl <- islm_mdl("2015Q2/2016Q3")
mdl$solve()

# fix variable "c" for a specific period:
mdl$fix_variables(names = "c", period = "2015Q3/2015Q4")

# fix all stochastic model variables
mdl$fix_variables(pattern = ".*")
```

---

get_data-methods	<a href="#">IsisMdl</a> methods: Retrieve timeseries from the model data, constant adjustments, fix values or fit targets
------------------	---

---

## Description

These methods of R6 class [IsisMdl](#) can be used to retrieve timeseries from the model data, constant adjustments, fix values or fit targets.

## Usage

```
mdl$get_data(pattern, names, period = mdl$get_data_period())

mdl$get_ca(pattern, names, period = mdl$get_data_period())

mdl$get_fix()

mdl$get_fit()

mdl is an IsisMdl object
```

## Arguments

`names` a character vector with variable names  
`pattern` a regular expression  
`period` an [period\\_range](#) object or an object that can be coerced to a `period_range`

## Methods

- `get_mdl_data`: Model data
- `get_ca`: Constant adjustments
- `get_fix_values`: Fix values
- `get_fit_targets`: Fit targets

## See Also

[set\\_data-methods](#), [set\\_values-methods](#) and [change\\_data-methods](#)

### Examples

```
mdl <- islm_mdl(period = "2016Q1/2017Q4")

print(mdl$get_data())

# print data for 2017Q2 and later
print(mdl$get_data(names = c("g", "y"), period = "2017Q2/"))

# print data for all quarters in 2017 (2017Q1/2017Q4)
print(mdl$get_data(names = c("g", "y"), period = "2017"))

print(mdl$get_data(pattern = "^ymdl"))
```

---

get_data_period	<a href="#">IsisMdl</a> method: returns the model data period
-----------------	---

---

### Description

This method of R6 class [IsisMdl](#) returns the model data period.

### Usage

```
mdl$get_data_period()
```

mdl is an [IsisMdl](#) object

### See Also

[set\\_period](#)

---

get_endo_names	<a href="#">IsisMdl</a> method: returns the names of the endogenous model variables
----------------	---

---

### Description

This method of R6 class [IsisMdl](#) returns the names of the endogenous model variables. By default, the function returns the names of all active endogenous variables. Argument `pattern` can be specified to select only variables with names matching a regular expression. Argument `type` can be specified to select variables with a specific type. The following types are supported

"frml" stochastic variables. Stochastic variables are variables that occur on the left hand side of frml equations

"endolead" all variables with endogenous leads

"all" all endogenous variables, the default

If some equation have been deactivated (see [set\\_eq\\_status](#), then argument status may be useful. By default, the function only returns the names of the active endogenous variables, i.e. the variables that occur on the left hand side of active equation. This behaviour can be modified by specifying the statusstatus. The following options for argument status are recognized:

"active" active endogenous variables, the default

"inactive" inactive endogenous variables

"all" all endogenous variables

## Usage

```
mdl$get_endo_names(pattern = ".*",
                  type = c("all", "frml", "endolead"),
                  status = c("active", "inactive", "all"))
```

mdl is an IsisMdl object

## Arguments

pattern a regular expression specifying variable names

type a character string specifying the variable type. See the description above

status a character string specifying the status of the endogenous variable (inactive or active). See the description above

## See Also

[get\\_exo\\_names](#) and [get\\_var\\_names](#)

## Examples

```
mdl <- islm_mdl()

# get the names of all stochastic variables
mdl$get_endo_names(type = "frml")

# get all variables with names starting with "y":
mdl$get_endo_names(pattern = "^y.*")
```

---

get\_eq\_names

*IsisMdl method: returns the the equation names*


---

## Description

This method of R6 class `IsisMdl` returns the the equation names. Argument `pattern` can be specified to select only equations with names matching a regular expression. Argument `status` can be specified to select only the active or inactive equations. Possible options for argument `status` are

"active" active equations

"inactive" inactive equations

"all" all equations, the default

Argument `order` specifies the order of the equations returned. The following ordering options are recognized:

"sorted" alphabetically ordering

"solve" ordered according to the solution sequence

"natural" same order as in the mdl file

## Usage

```
mdl$get_eq_names(pattern = ".*", status = c("all", "active", "inactive"),
                 order = c("sorted", "solve", "natural"))
```

mdl is an `IsisMdl` object

## Arguments

`pattern` a regular expression specifying equation names

`status` the equation status, see Description

`order` the ordering of the equations (see description)

## Examples

```
mdl <- islm_mdl()

# get the names of equations in solution order
mdl$get_eq_names(order = "solve")

# get all equations with names starting with "y":
mdl$get_eq_names(pattern = "^y.*")
```

---

get_exo_names	<a href="#">IsisMdl</a> method: returns the names of the exogenous model variables
---------------	--

---

### Description

This method of R6 class [IsisMdl](#) returns the names of the exogenous model variables, including the left hand side variables of inactive equations (see [set\\_eq\\_status](#)).

### Usage

```
mdl$get_exo_names(pattern = ".*")  
mdl is an IsisMdl object
```

### Arguments

pattern a regular expression specifying variable names

### See Also

[get\\_endo\\_names](#) and [get\\_var\\_names](#)

### Examples

```
mdl <- islm_mdl()  
  
# get the names of all exogenous model variables  
mdl$get_exo_names()  
  
# get all variables with names starting with "g":  
mdl$get_exo_names(pattern = "^g.*")
```

---

get_labels	<a href="#">IsisMdl</a> method: Returns the labels of the model variables.
------------	--

---

### Description

This method of R6 class [IsisMdl](#) returns the labels of the model variables.

### Usage

```
mdl$get_labels()  
  
mdl is an IsisMdl object
```

### See Also

[set\\_labels](#)

---

get\_last\_solve\_period [IsisMdl](#) *method: Returns the last solve period*

---

### Description

This method of R6 class [IsisMdl](#) returns the last solve period, i.e. the last period for which method [solve](#) attempted to find a solution (whether succesful or not). The period is returned as a [period](#) object. The function returns NULL when method solve has not yet been used fot this IsisMdl object.

### Usage

```
mdl$get_last_solve_period()
```

mdl is an [IsisMdl](#) object

### Examples

```
mdl <- islm_mdl(period = "2018q1/2018q4")$solve()
mdl$get_last_solve_period()
```

---

get\_maxlag [IsisMdl](#) *method: returns the maximum lag of the model*

---

### Description

This method of R6 class [IsisMdl](#) returns the maximum lag of the model

### Usage

```
mdl$get_maxlag()
```

mdl is an IsisMdl object

---

get\_maxlead [IsisMdl](#) *method: returns the maximum lead of the model*

---

### Description

This method of R6 class [IsisMdl](#) returns the maximum lead of the model

### Usage

```
mdl$get_maxlead()
```

mdl is an IsisMdl object

---

get_param	<a href="#">IsisMdl</a> method: Returns model parameters
-----------	--

---

### Description

This method of R6 class [IsisMdl](#) returns model parameters

### Usage

```
mdl$get_param(pattern, names)
```

mdl is an [IsisMdl](#) object

### Arguments

pattern a regular expression specifying parameter names

names a character vector with parameter names

### See Also

[set\\_param](#)

### Examples

```
mdl <- islm_mdl()

# print all model parameters
print(mdl$get_param())

# print parameters c0, c1, c2 and c3
print(mdl$get_param(pattern = "^c.*"))
```

---

get_par_names	<a href="#">IsisMdl</a> method: returns the names of the model variables
---------------	--

---

### Description

This method of R6 class [IsisMdl](#) returns the names of the model parameters

### Usage

```
mdl$get_par_names(pattern = ".*")
```

mdl is an [IsisMdl](#) object

**Arguments**

pattern a regular expression specifying parameter names

**Examples**

```
mdl <- islm_mdl()

# print all model parameter names
print(mdl$get_par_names())

# print names of model paramters with names starting with c
print(mdl$get_par_names(pattern = "^c.*"))
```

---

get_period	<a href="#">IsisMdl</a> method: returns the model period
------------	--

---

**Description**

This method of R6 class [IsisMdl](#) returns the model period.

**Usage**

```
mdl$get_period()
```

mdl is an [IsisMdl](#) object

**See Also**

[set\\_period](#)

---

get_solve_status	<a href="#">IsisMdl</a> method: Returns the solve status of the last model solve.
------------------	---

---

**Description**

This method of R6 class [IsisMdl](#) returns the status of the last model solve as a text string. If the last model solve was succesfull, it returns the string "OK".

**Usage**

[IsisMdl](#) method:

```
mdl$get_solve_status()
```

mdl is an [IsisMdl](#) object



## Details

The possible return values are:

- "Method solve has not yet been called"
- "OK"
- "Simulation not possible" (usually this means that exogenous or feedback variables have NA values)
- "Simulation stopped" (it was not possible to find a solution)
- "Initial lags/leads missing/invalid. Simulation not possible"
- "Invalid parameter values detected. Simulation not possible"
- "Fair-Taylor has not converged"
- "Out of memory. Simulation not succesfull"
- "Unknown problem in solve. Simulation not succesfull"

## See Also

[solve](#)

## Examples

```
## Not run:
mdl <- islm_mdl(period = "2017Q1/2018Q4")
mdl$set_values(NA, names = "y", period = "2017Q1")
mdl$solve()
if (mdl$get_solve_status() != "OK") {
  stop("Error solving the model. Check the warnings!")
}

## End(Not run)
```

---

get\_text

[IsisMdl](#) method: Returns the model text file

---

## Description

This method of R6 class [IsisMdl](#) returns the model text, i.e. the contents of the model file passed to function [isis\\_mdl](#).

In principle, it is possible to remove the original model file after the [IsisMdl](#) object has been created and saved to a file with method [write\\_mdl](#), since the model text used to create the model is stored in this file. However, this is not a good idea if the model contains preprocessor directives (`#include` or `#if`). The current version of `isismdl` does not handle preprocessor directives yet, but in future versions `isismdl` will store the preprocessed model text (the model text obtained by evaluating the preprocessor directives). *Therefore, we recommend to always keep the original model file.*

**Usage**

```
mdl$get_text()
```

mdl is an [IsisMdl](#) object

**Examples**

```
mdl <- islm_mdl()
cat(mdl$get_text())
```

---

get_var_names	<a href="#">IsisMdl</a> method: returns the names of the model variables
---------------	--

---

**Description**

This method of R6 class [IsisMdl](#) returns the names of the model variables, both exogenous and endogenous.

Argument type can be specified to select variables with a specific type. The following types are supported

"all" All model variables

"lags" Model variables with lags

"leads" Model variables with leads

**Usage**

```
mdl$get_var_names(pattern = ".*", type = c("all", "lags", "leads"))
```

mdl is an [IsisMdl](#) object

**Arguments**

pattern a regular expression specifying variable names

type a character string specifying the variable type. See the description above

**See Also**

[get\\_endo\\_names](#) and [get\\_exo\\_names](#)

**Examples**

```
mdl <- islm_md1()

# get the names of all model variables
mdl$get_var_names()

# get all variables with names starting with "m":
mdl$get_var_names(pattern = "^y.*")

# get the names of all lagged variables
mdl$get_var_names(type = "lags")
```

---

ifn_md1	<i>Returns an IFN model This function returns an uninitialized IFN model.</i>
---------	---

---

**Description**

Returns an IFN model This function returns an uninitialized IFN model.

**Usage**

```
ifn_md1()
```

**Value**

a [IsisMdl](#) object

**Examples**

```
mdl <- ifn_md1()
```

---

init_data	<a href="#">IsisMdl</a> method: initialized the model data.
-----------	---

---

**Description**

This method of R6 class [IsisMdl](#) sets the data period and initializes the model variables and constant adjustments.

If the model period has not yet been specified (in function [isis\\_md1](#) or method [set\\_period](#)), then this method also sets the model period, the standard period for which the model will be solved. The model period is obtained from the data period by subtracting the lag and lead periods.

The method initializes all model timeseries with NA and all constant adjustments with 0 for the data period. If arguments data or ca have been specified, then the model variables or constant adjustments are subsequently updated with the timeseries in data or ca, respectively.

**Usage**

```
mdl$init_data(data_period, data, ca)
```

mdl is an IsisMdl object

**Arguments**

data\_period [period\\_range](#) object, or an object that can be coerced to [period\\_range](#). If not specified then the data period is based on the period range of argument data (if this argument has been specified) and the model period.

data a [ts](#) or [regts](#) object with model variables

ca a [ts](#) or [regts](#) object with constant adjustments

---

IsisMdl

---

*An R6 class class representing an Isis model*


---

**Description**

This class is used to solve a system of non-linear equations with lagged variables. The model equations are specified in a separate text file, the so called model file. Function [isis\\_mdl](#) parses the model file and generates an IsisMdl object. The vignette "Introduction" gives a detailed description of the usage of IsisMdl objects.

**Format**

[R6Class](#) object.

**Details**

The syntax of the model file is the same of the syntax of model file in Isis, and is described in detail in the Isis Reference Manual (a vignette with a detailed model syntax description for package IsisMdl will be available in a future).

The package included a number of example models in directory `models` of the package library. It is also possible to directly create IsisMdl objects with functions [islm\\_mdl](#) to create an ISLM model and [ifn\\_mdl](#) to create another example model, the IFN model. The latter model is a model with leads and can be solved with the Fair-Taylor-method.

**Value**

Object of [R6Class](#) representing an Isis model.

## Methods

IsisMdl objects support the following methods. These methods are described in detail in the different subsection of the documentation For example, method `solve` is described in section [solve](#).

- `copy` Returns a deep copy of the IsisMdl object
- `get_text` Returns the textual representation of the model
- `get_maxlag` Returns the maximum lag
- `get_maxlead` Returns the maximum lead
- `get_var_names` Returns the names of the model variables
- `get_exo_names` Returns the names of the exogenous model variables
- `get_endo_names` Returns the names of the endogenous model variables
- `get_par_names` Returns the names of the model parameters
- `get_eq_names` Returns the names of the equations
- `init_data` Initializes the model data
- `set_period` Sets the model period
- `get_period` Returns the model period
- `get_data_period` Returns the model data period
- `set_labels` Set labels for the model variables
- `get_labels` Returns the labels of the model variables.
- `set_param` Sets the model parameter
- `get_param` Returns model parameters
- `set_data` Transfer timeseries to the model data
- `set_ca` Transfer timeseries to the constant adjustments
- `set_fix` Transfer timeseries to the fix values
- `set_fit` Transfer timeseries to the fit targets
- `set_values` Sets the values of the model data
- `set_ca_values` Sets the values of the constant adjustments
- `set_fix_values` Sets the fix values
- `set_fit_values` Sets the values of the fit targets
- `set_fit` Transfer timeseries to the fit targets
- `change_data` Change model data by applying a function
- `change_ca` Change the constant adjustments by applying a function
- `get_data` Returns the model data
- `get_ca` Returns the constant adjustments
- `get_fix` Returns the fix values
- `get_fit` Returns the fit targets
- `set_rms` Sets or updates the rms values
- `set_solve_options` Sets the solve options

[get\\_solve\\_options](#) Returns the solve options  
[set\\_fit\\_options](#) Sets the options for the fit procedure  
[get\\_fit\\_options](#) Returns the options for the fit procedure  
[set\\_debug\\_eqn](#) Sets the debug equation option  
[get\\_debug\\_eqn](#) Returns the debug equation option  
[set\\_cvgcrit](#) Sets the convergence criterion for selected variables  
[get\\_cvgcrit](#) Returns the convergence criterion for selected variables  
[set\\_eq\\_status](#) Sets the equation status "active" or "inactive")  
[set\\_ftrelax](#) Sets the Fair-Taylor relaxation factors  
[get\\_ftrelax](#) Returns the Fair-Taylor relaxation factors  
[solve](#) Solves the model  
[get\\_solve\\_status](#) Returns the status of the last model solve attempt  
[fill\\_mdl\\_data](#) Calculates missing model data from identities  
[write\\_mdl](#) Serializes the model object and writes it to an RDS file  
[order](#) Orders the equations of the model

### See Also

[isis\\_mdl](#), [islm\\_mdl](#) and [ifn\\_mdl](#)

### Examples

```

# create an example ISLM model
mdl <- islm_mdl()

# prepare input timeseries
r <- regts(3.35, start = "2015Q1", end = "2016Q3", labels = "interest rate")
y <- regts(980, start = "2015Q1", end = "2016Q3", labels = "income")
yd <- regts(790, start = "2015Q1", labels = "disposable income")
g <- regts(210 * cumprod(rep(1.015, 6)), start = "2015Q2",
          labels = "government spending")
ms <- regts(200 * cumprod(rep(1.015, 6)), start = "2015Q2",
          labels = "money supply")
islm_input <- cbind(r, y, yd, g, ms)
print(islm_input)

# set period and update model timeseries
mdl$set_period("2015Q2/2016Q3")
mdl$set_data(islm_input)

mdl$set_labels(c(i = "investment", c = "consumption", md = "money demand",
                t = "tax"))

mdl$solve()

```

---

isis_mdl	Creates an <a href="#">IsisMdl</a> object from a model file.
----------	--

---

## Description

This function creates an [IsisMdl](#) object. A model as defined on an external ASCII file is parsed, analysed and converted into an internal code. This internal code is used to evaluate the model equations.

## Usage

```
isis_mdl(
  model_file,
  period,
  data,
  ca,
  fix_values,
  parse_options,
  silent = FALSE
)
```

## Arguments

model_file	The name of the model file. An extension <code>mdl</code> is appended to the specified name if the filename does not already have an extension
period	a <a href="#">period_range</a> object
data	the model data as a <a href="#">regts</a> object with column names
ca	the constant adjustments as a <a href="#">regts</a> object with column names
fix_values	the fix values as a <a href="#">regts</a> object with column names
parse_options	a named list with options passed to the model parser. See section "Parse options"
silent	A logical (default FALSE). If TRUE, then output of the model parser is suppressed.

## Details

The file containing the model must have an extension `mdl`.

Some technical information about the model and a cross reference of the model is written to an external file with extension `mr.f`. For each variable its maximum lag and lead are given and a list of equations (by name) in which it occurs.

The parser also orders the equations of the model into three separate blocks.

- the *pre-recursive* block containing equations which can be solved recursively from exogenous and lagged variables only.
- the *simultaneous* block containing all equations with interdependent endogenous variables.
- the *post-recursive* block containing equations which can be solved recursively once the two previous blocks have been solved.

The ordering process also provides a list of so-called feedback variables, i.e. variables whose value must be assumed known to make the *simultaneous* block recursive. Initial guesses for these variables must be provided in order to solve a model. If a model has no feedback variables, it is a recursive model (it can be solved in one pass through the equations).

If the parser encounters errors in the model, these are written to a file with an extension `err`. All generated files have the same basename as the model file.

### Parse options

The following parse options can be specified with argument `parse_options`. This argument should be a named list

`"flags"` This flag is used for conditional compilation. Consult Section 3.11.2 "Conditional compilation" in the Isis reference manual for more information about conditional compilation

`"include_dirs"` Add directory `include_dir` to the list of directories to be searched for include files. In the model file, the `#include` directive (see Section 3.11.1 "File inclusion" in the Isis Reference Manual) is used to include another file in the model. The specified name of the include file can be a relative or absolute path. If the path is relative, then the model searches for the include file. It first searches in the same directory where the source file is located. If not found there, then the compiler searches in the directories specified with argument `include_dir`, in the order that the directories have been specified. If the include file is still not found, the parser searches in the current directory

`"gen_dep_file"` Specify `TRUE` to generate a file with dependency information. The default is `FALSE`. The dependency information is written to an external file with extension `dep`. The file gives for each equation a list of the variables that occur in the right hand side of the equation with lags and leads included. This file may be useful for model analysis with other software. Currently this option cannot be used for models with user functions.

### See Also

[IsisMdl](#), [islm\\_mdl](#) and [ifn\\_mdl](#)

### Examples

```
# copy the islm.mdl file in the directory models of the package
# directory to the current directory
mdl_file <- system.file("models", "islm.mdl", package = "isismdl")
file.copy(mdl_file, "islm.mdl")

mdl <- isis_mdl("islm.mdl")

# an example with parse option "include_dirs":
mdl <- isis_mdl("islm.mdl", parse_options = list(include_dirs = "mdlincl"))
```



---

islmdl	Returns an example ISLM model
--------	-------------------------------

---

### Description

This function returns an example ISLM model. If argument `period` has been specified, then this function also generates some example data for the feedback variables, lags and exogenous variables. The model returned is ready to be solved.

### Usage

```
islmdl(period = NULL)
```

### Arguments

`period` the model period for the ISLM model

### Value

a `Islmdl` object

### Examples

```
mdl <- islmdl()
```

---

order	<code>Islmdl</code> method: orders the equations of a model
-------	---

---

### Description

This method of R6 class `Islmdl` orders the equations of a model. This can be useful after (de)activation equations. By specifying argument `orfnam` it is also possible to write ordering information to a file.

### Usage

```
mdl$order(orfnam, silent = FALSE)
```

`mdl` is an `Islmdl` object

### Arguments

`orfnam` Name of file on which to print ordering information. If no output file is specified no ordering information will be written

`silent` A logical (default FALSE). If TRUE, then output is suppressed.

---

read_md1	<i>Reads an IsisMdl object from a file</i>
----------	--

---

### Description

This function reads a model from a file that has been written by [IsisMdl](#) method [write\\_md1](#)

### Usage

```
read_md1(file, silent = FALSE)
```

### Arguments

file	filename (typically with extension .ismdl)
silent	A logical (default FALSE). If TRUE, then output is suppressed.

### Details

`read_md1` employs the serialization interface provided by base R function [readRDS](#).

### Value

an [IsisMdl](#) object

### See Also

[write\\_md1](#)

### Examples

```
mdl <- islm_md1("2017Q1/2019Q2")
mdl$write_md1("islm_md1.ismdl")
mdl2 <- read_md1("islm_md1.ismdl")
```

---

run_eqn	<a href="#">IsisMdl</a> method: runs model equations
---------	--

---

### Description

This method of R6 class [IsisMdl](#) runs specific equations of the model separately. Each specified equation is run separately for the specified period. If the equation is a stochastic equation (a `frml` equation) and the corresponding endogenous variable has been fixed then the constant adjustment for the equation will be calculated such that the result of the equation equals the predetermined required value for the left-hand side.

If neither argument `pattern` or `names` have been specified, then all active model equations are ran in solve order.

**Usage**

```
mdl$run_eqn(pattern, names, period = mdl$get_data_period())
```

mdl is an [IsisMdl](#) object

**Arguments**

pattern a regular expression. Equations with names matching the regular expression are run in solve order

names a character vector with equation names. The corresponding equations are solved in the order as they are specified

period a [period\\_range](#) object

**Examples**

```
mdl <- islm_mdl("2017Q1/2019Q3")
mdl$run_eqn(names = c("c", "t"))
```

---

 serialize

---

*Serializes the model to an serialized\_isismdl S3 class*


---

**Description**

This method of R6 class [IsisMdl](#) serializes the model object and returns an `serialized_isismdl` object, an S3 object that contains all the information about the model. The serialized model can be used to create a new `IsisMdl` object with the command `IsisMdl$new(serialized_mdl)`

**Usage**

```
mdl$serialize()
```

mdl is an [IsisMdl](#) object

**See Also**

[write\\_mdl](#) and [read\\_mdl](#)

**Examples**

```
mdl <- islm_mdl("2017Q1/2019Q2")
serialized_mdl <- mdl$serialize()

# create a new model from the serialized model
mdl2 <- IsisMdl$new(serialized_mdl)
```

---

set_cvgcrit	<i>IsisMdl method: Sets the convergence criterion for selected variables.</i>
-------------	---

---

## Description

This method of R6 class `IsisMdl` sets the convergence criterion for one or more endogenous model variables. A variable  $x$  has converged when two successive values  $x_2$  and  $x_1$  satisfy the following condition

$$|x_2 - x_1| \leq \epsilon \max(1, |x_1|)$$

where  $\epsilon$  is the convergence criterion for the tested variable.

The default value of  $\epsilon$  for all variables is the square root of the machine precision (`sqrt(.Machine$double.eps)`), typically about  $1.5e-8$

Method `get_cvgcrit()` returns the convergence criteria for all model variables

## Usage

```
mdl$set_cvgcrit(value, pattern, names)
```

```
mdl$get_cvgcrit()
```

mdl is an `IsisMdl` object

## Arguments

**value** convergence criterion. This must be a small positive number

**pattern** a regular expression specifying the variable names

**names** a character vector with variable names

If neither **pattern** nor **names** have been specified, then the convergence criterion of all endogenous variables will be set to the specified value.

## Examples

```
mdl <- islm_mdl()

# set convergence criterion for variables "c" and "i":
mdl$set_cvgcrit(1e-4, names = c("c", "i"))

# set convergence criterion for variables "y" and "yd":
mdl$set_cvgcrit(1e-4, pattern = "^y*")

print(mdl$get_cvgcrit())
```

---

set_data-methods	<i>IsisMdl methods: transfers data from a timeseries object to the model data, constant adjustments, fix values or fit targets.</i>
------------------	---

---

## Description

These methods of R6 class `IsisMdl` Transfers data from a timeseries object to the model data, constant adjustments, fix values or fit targets.

## Usage

```
mdl$set_data(data, names = colnames(data), upd_mode = c("upd", "updval"),
             fun)

mdl$set_ca(data, names = colnames(data), upd_mode = c("upd", "updval"),
           fun)

mdl$set_fix(data, names = colnames(data), upd_mode = c("upd", "updval"))

mdl$set_fit(data, names = colnames(data), upd_mode = c("upd", "updval"))

mdl is an IsisMdl object
```

## Arguments

**data** a `ts` or `regts` timeseries object

**names** a character vector with variable names, with the same length as the number of timeseries in data. Defaults to the column names of data. If data does not have column names, then argument names is mandatory

**upd\_mode** the update mode, a character string specifying how the timeseries are updated: "upd" (standard update, default) or "updval" (update only with valid numbers). See details.

**fun** a function used to update the model data. This should be a function with two arguments. The original model data is passed to the first argument of the function and data to the second argument. See the examples.

## Methods

**set\_data** Sets model data. If data has labels, then `set_data` will also update the labels of the corresponding model variables

**set\_ca** Set constant adjustments, i.e. the residuals of behavioural (frml) equations

**set\_fix** Set fix values for the stochastic model variables (i.e. model variables that occur at the left hand side of a frml equation). The model variables will be fixed at the specified value. A fix value of NA implies that the corresponding variable is not fixed. `set_fix` also updates the model data with all non NA values

**set\_fit** Set fit targets for the fit procedure. A fit target value of NA implies that the corresponding variable is no fit target

## Details

Method `set_data` transfers data from a timeseries object to the model data. If data is a multivariate timeseries object, then each column is used to update the model variable with the same name as the column name. If data does not have column names, or if the column names do not correspond to the model variable names, then argument names should be specified.

By default, all values in data are used to update the corresponding model variable. Sometimes it is desirable to skip the NA values in data. This can be achieved by selecting `"updval"` for argument `upd_mode`. Other non finite numbers (NaN, Inf, and -Inf) are also disregarded for this update mode.

`set_ca`, `set_fix` and `set_fit` and `set_data` works similarly.

## See Also

[get\\_data-methods](#), [set\\_values-methods](#), [change\\_data-methods](#), [fix\\_variables](#), [clear\\_fix](#) and [clear\\_fit](#).

## Examples

```
mdl <- islm_mdl(period = "2017Q1/2017Q3")

# create a multivariate regts object for exogenous variables g and md
exo <- regts(matrix(c(200, 210, 220, 250, 260, 270), ncol = 2),
               start = "2017Q1", names = c("g", "ms"))

# set and print data
mdl$set_data(exo)
print(mdl$get_data())

# create a univariate regts object for exogenous variable ms,
# with a missing value in 2017Q2
ms <- regts(c(255, NA, 273), start = "2017Q1")

# update with update mode updval (ignore NA)
# note that here we have to specify argument names,
# because ms does not have column names
mdl$set_data(ms, names = "ms", upd_mode = "updval")
print(mdl$get_data())

# in the next example, we use argument fun to apply an additive shock to the
# exogenous variables g and ms.
shock <- regts(matrix(c(-5, -10, -15, 3, 6, 6), ncol = 2),
                  start = "2017Q1", names = c("g", "ms"))
mdl$set_data(shock, fun = function(x1, x2) {x1 + x2})

# the statement above can be more concisely written as
mdl$set_data(shock, fun = `+`)
#`+` is a primitive function that adds its two arguments.
```

---

set_debug_eqn	<i>IsisMdl method: R Sets the debug equation option</i>
---------------	---

---

### Description

This method of R6 class `IsisMdl` sets the debug equation option (TRUE or FALSE)  
 Method `get_debug_eqn()` returns the debug equation option.

### Usage

```
mdl$set_debug_eqn(value)
```

```
mdl$get_debug_eqn()
```

mdl is an `IsisMdl` object

### Arguments

value A logical. If TRUE, then equation debugging is turned on. The default is FALSE

### Details

When a model cannot be solved this may be caused by errors in the model equations or even errors in the initial data. If debug mode is set to on, Isis will print messages in the output file whenever it encounters numerical problems during calculation of an equation.

### Examples

```
mdl <- islm_mdl()
mdl$set_debug_eqn(TRUE)

print(mdl$get_debug_eqn())
```

---

set_eq_status	<i>IsisMdl method: activates or de-activates one or more equations.</i>
---------------	---

---

### Description

This method of R6 class `IsisMdl` can be used to set the equation status (active or inactive) of one or more equations.

This procedure is used to activate or deactivate a specified set of equations. After compiling a model, all equations are active. Sometimes however it can be necessary to temporarily exclude an equation from the model and the solution process without actually removing it.

Deactivating an equation implies that the left-hand side variable becomes an exogenous variable. As long as an equation is inactive, the corresponding left-hand side variable and any constant adjustment (for *frml* equations) will remain *unchanged* in the model workspace.

However the methods `set_data`, `set_ca`, `get_data` and `get_ca` will still transfer data to and from the model workspace.

A deactivated equation can also be reactivated. It will again participate in the solution process and its left-hand side variable will be treated as endogenous.

Since deactivating effectively changes the structure of the model, it may be necessary to compute a new ordering of the model. This is not done automatically. You must do it by hand. Currently, package `isismdl` does not yet support reordering the model, but this feature will become available in the future.

If the left-hand side variable of a deactivated equation appears as lead in the model, that lead will temporarily be marked as an exogenous lead. However, if a lead of another endogenous variable occurs only in the deactivated equation that particular lead will *not* be registered as exogenous. The model will still be regarded as containing endogenous leads and therefore the default solution mode will be `ratex`, i.e. the Fair-Taylor method will be used for solving the model.

### Usage

```
mdl$set_eq_status(status = c("active", "inactive"), pattern, names)
```

`mdl` is an `IsisMdl` object

### Arguments

`status` a character string specifying the equation status ("active" or code "inactive")

`pattern` a regular expression specifying the names of the equations

`names` a character vector with the names of the equations

If neither `pattern` nor `status` have been specified, then all equations will be activated or deactivated.

### See Also

[get\\_eq\\_names](#)

### Examples

```
mdl <- islm_mdl()

# deactivate equation "c" and "i"
mdl$set_eq_status("inactive", names = c("c", "i"))

# deactivate all equations starting with "y" ("y" and "yd")
mdl$set_eq_status("inactive", pattern = "^y*")

# print all deactivated equations
print(mdl$get_eq_names(status = "inactive"))
```



---

set_fit_options	<a href="#">IsisMdl</a> method: Sets the options for the fit procedure.
-----------------	---

---

## Description

This method of R6 class [IsisMdl](#) can be used to set one or more options for the fit procedure. These options will be stored in the [IsisMdl](#) object.

Method `get_fit_options` returns the solve options as a named list

## Usage

```
mdl$set_fit_options(maxiter, cvgabs, mkdcrt, zero_ca, warn_ca,
                    accurate_jac, zealous, report, dbgopt, svdtest_tol)
```

```
mdl$get_fit_options()
```

mdl is an [IsisMdl](#) object

## Arguments

All arguments below expect a numerical value unless mentioned otherwise.

**maxiter** The maximum number of iterations (default 5)

**cvgabs** Criterion for absolute convergence. When the largest scaled discrepancy of the fit target values is less than `cvgabs`, the fit procedure has converged. The default value is 100 times the square root of the machine precision ( $100 * \sqrt{\text{Machine\$double.eps}}$ ), which is typically  $1.5e-6$ .

**mkdcrt** Criterion for calculating a new fit jacobian. When the ratio of two successive largest scaled discrepancies of the fit target values is larger than `mkdcrt` a new fit jacobian will be calculated in the next iteration. Any value specified must lie between 0.05 and 0.95. The default value is 0.5.

**zero\_ca** A logical. If TRUE, then the initial values of the constant adjustments used in the fit procedure are initialised to 0. The default is FALSE

**warn\_ca** A logical. If TRUE (default), then warnings are given for possibly too large constant adjustments at the end of the fit procedure for each period.

**accurate\_jac** A logical. If TRUE (default), then the fit jacobian is calculated accurately, otherwise the jacobian is calculated approximately. See Details

**zealous** A logical. If TRUE (default), then a zealous version of the fit procedure is used, otherwise a lazy version is used (see Details). The recommended option is to use the zealous version, although this may require much more CPU time.

**report** A character string specifying the the type of report of the fit procedure for each period. Possible values are "fullrep" (the default, an iteration report is printed for each period) and "minimal" (for a one line summary).

dbgopt A character vector specifying one or more debugging options. See section "Debugging options" below

svdtest\_tol Singular Value Decomposition (SVD) test tolerance parameter. If the inverse condition of the fit Jacobian is smaller than this parameter, then an SVD analysis of the Jacobian is performed. This may help to find the equations that cause (near) singularity of the Jacobian. The default value is -1, which implies that the SVD test is never performed. Specify a number between 0 and 1 to enable an SVD analysis depending on the inverse condition of the Jacobian. When this option has been specified a copy of the fit Jacobian is kept in memory, even if the Jacobian is not ill-conditioned. This option should therefore only be used during testing. It should be turned off in production calculations

### Debugging options

Argument dbgopt can be used to specify one or more options for debugging the fit procedure. Possible values are

prica print the fit jacobian every time it is calculated

noprca do not print the fit jacobian every time it is calculated

prijac print the fit jacobian every time it is calculated

noprijac do not print the fit jacobian every time it is calculated

supstot to suppress all output of the normal solution process

nosupstot to not suppress all output of the normal solution process. Output will be a mess if this option is used

The default debug options are c("noprca", "noprijac", "supstot")

---

set\_ftrelax

*IsisMdl method: Sets the Fair-Taylor relaxation factors*

---

### Description

This method of R6 class [IsisMdl](#) sets the Fair-Taylor relaxation factors for the endogenous leads.

Method `get_ftrelax()` returns the Fair-Taylor relaxation factors for all endogenous leads.

### Usage

```
mdl$set_ftrelax(value, pattern, names)
```

```
mdl$get_ftrelax()
```

mdl is an [IsisMdl](#) object

**Arguments**

value Fair-Taylor relaxation number. This must be a positive number or NA to disable any previously set value. The default value for all endogenous leads is NA, which means that the general uniform Fair-taylor relaxation (solve option `ftrelax`, see [set\\_solve\\_options](#)) will be applied

pattern a regular expression specifying the variable names

names a character vector with variable names

If neither pattern nor names have been specified, then the Fair-Taylor relaxation factors of all variables with endogenous leads will be set to the specified values.

**Examples**

```
mdl <- ifn_mdl()

# set Fair-relaxtion factor all all variables with names of length 2
# to 0.5:
mdl$set_ftrelax(0.5, pattern = "^..$")

# set Fair-relaxtion factor for variable "lambda":
mdl$set_ftrelax(0.5, names = "lambda")

print(mdl$get_ftrelax())
```

---

set_labels	<a href="#">IsisMdl</a> method: Sets labels for the model variables.
------------	--

---

**Description**

This method of R6 class [IsisMdl](#) sets labels for the model variables.

**Usage**

```
mdl$set_labels(labels)
```

mdl is an [IsisMdl](#) object

**Arguments**

labels a named character vector. The names are the names of the model variables

**Examples**

```
mdl <- islm_mdl()
mdl$set_labels(c(c = "Consumption", i = "investments"))
```

---

set_param	<a href="#">IsisMdl</a> method: Sets the model parameters
-----------	---

---

### Description

This method of R6 class [IsisMdl](#) sets the model parameters

### Usage

```
mdl$set_param(p)
```

mdl is an [IsisMdl](#) object

### Arguments

p a named list. The names are the names of the parameter names. The list elements are numeric vectors with a length equal to the length of the corresponding parameter

### Examples

```
mdl <- islm_mdl()
mdl$set_param(list(i0 = 101))
```

---

set_period	<a href="#">IsisMdl</a> method: sets the model period
------------	---

---

### Description

This method of R6 class [IsisMdl](#) sets the model period. This is the default period used when solving the model.

If the model data has not already been initialized with method [init\\_data](#), then `set_period` also initializes the model data. In that case the model data period is set to the specified model period extended with a lag and lead period. Model timeseries are initialized with NA and all constant adjustments with 0.

If the model data has already been initialized with method [init\\_data](#), then the new model period should be compatible with the model data period. In particular, the new model period extended with a lag and lead period should not contain periods outside the model data period.

### Usage

```
mdl$set_period(period)
```

mdl is an [IsisMdl](#) object

## Arguments

period [period\\_range](#) object, or an object that can be coerced to [period\\_range](#)

## Examples

```
mdl <- islm_mdl()
mdl$set_period("2017Q2/2021Q3")
```

---

set\_rms

[IsisMdl](#) method: Sets or updates the root mean square errors

---

## Description

This method of R6 class [IsisMdl](#) sets or updates the root mean square (rms) error data used in the fit procedure. All variables whose rms value is larger than 0 and not NA are used as instruments of the fit procedure.

Method `get_rms` returns all rms values larger than 0 and not equal to NA.

## Usage

```
mdl$set_rms(values)
```

```
mdl$get_rms()
```

mdl is an [IsisMdl](#) object

## Arguments

values a named numeric vector with rms values. If a value is positive and not "NA", then the corresponding value will be used as fit instrument

## Examples

```
mdl <- islm_mdl(period = "2017Q1/2018Q4")

mdl$set_rms(c(c = 5.0, t = 2, i = 21, md = 2))
print(mdl$get_rms())

# stop using variable t as fit instrument
mdl$set_rms(c(t = NA))
print(mdl$get_rms())
```

---

set\_solve\_options      *IsisMdl method: Sets the solve options*

---

### Description

This method of R6 class `IsisMdl` can be used to set one or more solve options. These options will be stored in the `IsisMdl` object.

Method `get_solve_options` returns the solve options as a named list

### Usage

```
mdl$set_solve_options(mode, fbstart, maxiter, maxjacupd, rlxspeed,
                      rlxmin, rlxmax, cstpbk, cnmtrx, xrelax,
                      xmaxiter, xupdate, dbgopt, erropt,
                      report, ratreport, ratreport_rep, ratfullreport_rep,
                      bktmax, xtfac, svdtest_tol)
```

```
mdl$get_solve_options()
```

mdl is an `IsisMdl` object

### Arguments

All arguments below expect a numerical value unless mentioned otherwise.

**mode** a character string specifying the solution mode ("auto", "ratex", "dynamic", "reschk", "backward" or "static"). "auto" is the default. See section "Solution modes" below

**fbstart** a character string specifying the method of initialising feedback values. ("current", "previous", "curifok" or "previfok"). The default is "current". See section "Feedback initialisation methods" below

**maxiter** the maximum number of iterations per period (default 50)

**maxjacupd** the maximum number of Newton Jacobian updates per period (default 10)

**rlxspeed** Newton relaxation shrinkage (default is 0.5)

**rlxmin** Minimum Newton relaxation factor (default is 0.05)

**rlxmax** Maximum Newton relaxation factor (default is 1.0)

**cstpbk** Stepback criterion (default is 1.3). If the convergence criterium `Fcrit` is larger than `cstpbk` or invalid feedback variables have been obtained then the Newton step is not accepted and linesearching will be initiated. If the linesearching procedure failed (`Fcrit` is still larger than `cstpbk` after the maximum number of linesearch steps `bktmax` has been reached or if the relaxation factor has become smaller than `rlxmin`), a new Jacobian matrix is computed. In each linesearch step the current relaxation factor is shrunk by `rspeed`. The relaxation factor is set to its maximum value `rlxmax` when a new Jacobian has been calculated.

**cnmtrx** Recalculate matrix criterion (default is 0.9). If the convergence criterium `Fcrit` is larger than `cnmtrx` but smaller than `cstpbk`, the Newton step is accepted but a new Jacobian is computed and the relaxation factor is set to its maximum value `rlxmax`. The new Jacobian is used in the next step. However, the Jacobian will not be recalculated if the number of Jacobian updates in a period is larger than `maxjacupd`

- xrelax Rational expectations relaxation factor (default is 1)
- xmaxiter Maximum number of rational expectation iterations (default is 10)
- xupdate Character string defining the method of updating leads. Possible values are "fixed" (the default) and "lastval". For "fixed" the leads beyond the solution period are fixed at the initial values. For "lastval" leads beyond the solution period take on the values from the last solution date
- dbgopt A character vector specifying one more debugging options. See section "Debugging options" below
- erropt Character string defining the error handling when invalid lags, leads, constant adjustments and/or exogenous variables are detected. Possible values are "stop" (stop on errors), "cont" (continue on errors but write a message to the output) and "silent" (also continue but without message). The default is "stop"
- report A character string defining the type of computation progress report. Possible values are "period" (for a report per period), "fullrep" (for a full report), "minimal" (for a minimal report), and "none" (for no report). The default is "period" The report options "none" also suppresses all output of the fit procedure and the Fair-Taylor progress report.
- ratreport Defines the type of rational expectations progress report. See section "Ratex report options" below
- ratreport\_rep An integer number specifying the Fair-Taylor report repetition count. See Section "Ratex report options" below
- ratfullreport\_rep An integer number, specifying the Fair-Taylor full report repetition count. See Section "Ratex report options" below
- bktmax Maximum number of backtracking linesearch steps with old jacobian. Sometimes it is necessary for the Broyden method to take a shorter step than the standard step. This is called backtracking linesearch. bktmax is the maximum number of line search steps before a new Jacobian is computed
- xtfac Rational expectations convergence test multiplier When using the "ratex" solution mode, convergence of endogenous leads cannot be tested to the accuracy used in testing for convergence in the solution of the model. This option specifies the multiplier to apply to the convergence criterion for each endogenous variable if the variable has an endogenous lead. Suppose for example that some variable has a convergence criterion of  $10^{-5}$  and assume a value of 10 for the multiplier. Then its endogenous lead will be regarded as converged
- svdtest\_tol Singular Value Decomposition (SVD) test tolerance parameter. If the inverse condition of the Jacobian is smaller than this parameter, then an SVD analysis of the Jacobian is performed. This may help to find the equations that cause (near) singularity of the Jacobian. The default value is -1, which implies that the SVD test is never performed. Specify a number between 0 and 1 to enable an SVD analysis depending on the inverse condition of the Jacobian. When this option has been specified a copy of the Jacobian is kept in memory, even if the Jacobian is not ill-conditioned. This option should therefore only be used during testing. It should be turned off in production calculations

### Solution modes

The solution mode can be specified with argument mode. Possible values are:

"auto" determine the solution mode automatically: "ratex" for models with endogenous leads and "dynamic" for models without endogenous leads

"dynamic" to update lags and current values of all right-hand side endogenous variables (leads are not updated). This is the default for models without endogenous leads

"ratex" to update lags, leads and current values of all right-hand side endogenous variables. This is the default mode for models with endogenous leads. The model is solved in dynamic mode for all periods conditional on the endogenous right-hand side leads. After solving for the complete solution period the endogenous leads are updated with the results for the corresponding endogenous variables. The solution process thus consists of an two loops: an inner loop solving the model for all periods given the leads and an outer loop which solves for the endogenous leads

"static" to update only current values of right-hand side endogenous variables lags and leads are not modified

"reschk" to not update right-hand side endogenous variables from the solution

"backward" same as dynamic, except that the model is solved backwards. The model is solved in reversed order by starting at the last solution period and ending at the first solution period. Leads are updated and lags are not updated

If a model contains leads then the "ratex" mode is the default; this is a Fair-Taylor algorithm.

The default is "auto".

### Feedback initialisation methods

Argument fbstart can be used to specify the way how the feedback variables at the current period (i.e. the period for which the model is being solved) are initialised from the model data. Possible values of fbstart are:

"current" the initial values are always taken from the current period. This is the default

"previous" The initial values are taken from the previous period except when the first period to be solved is the start of the model data period. In that case current period values are used

"curifok" Current period values are used if they are valid otherwise previous period values are used

"previfok" At the start of the solution period, previous period values will be used if they are available and valid; otherwise current period values will be used. Thereafter previous period initial values are always used, which is equivalent to the "previous" method

The default is "current".

### Debugging options

Argument dbgopt can be used to specify one or more options for debugging. Possible values are

"prifb" print feedback variables at each iteration

"prild" print all leads at each ratex iteration

"prijac" print jacobian matrix when updated

"prinoconv" print all not converged endogenous variables



"prinotconvl" print all not converged leads  
 "allinfo" all of the above  
 "noprifb" do not print feedback variables at each iteration  
 "noprild" do not print all leads at each ratex iteration  
 "noprijac" do not print jacobian matrix when updated  
 "nopriinoconv" print only the largest discrepancy of all not converged endogenous variables  
 "noprinotconvl" print only the largest discrepancy of all not converged leads  
 "noinfo" no debugging output  
 "priscal" print scaling factors as determined from the jacobian  
 nopriscal do not print scaling factors as determined from the jacobian  
  
 Default is no printing of debugging information.

### Ratex report options

The type of report is determined by argument `ratreport`. Arguments `ratreport_rep` (the report repetition count) and `ratfullreport_rep` (the full report repetition count), both specified as integer numbers, can be used to further modify the progress report.

Possible values for `ratreport` are

"iter" print the number of not converged expectation values every `ratreport_rep` Fair Taylor iteration (the default)  
 "fullrep" full report. The number of not converged expectation values is printed every `ratreport_rep` Fair Taylor iteration and the largest remaining discrepancy every `ratfullreport_rep` Fair Taylor iteration  
 "minimal" for a full report only after the last Fair Taylor iteration

If `ratfullreport_rep` is NA, then the full report is printed every `ratreport_rep` Fair-Taylor iteration. The default values for `ratreport_rep` and `ratfullreport_rep` are 1 and NA, respectively.

### Examples

```
mdl <- islm_mdl(period = "2017Q1/2018Q4")
mdl$set_solve_options(maxiter = 100)
```

---

set_values-methods	<i>IsisMdl methods: Sets the values of the model data, constant adjustments, fix values or fit targets</i>
--------------------	--

---

### Description

These methods of R6 class `IsisMdl` can be used to set the values of the model data, constant adjustments, fix values or fit targets.

**Usage**

```
mdl$set_values(value, names, pattern, period = mdl$get_data_period())

mdl$set_ca_values(value, names, pattern, period = mdl$get_data_period())

mdl$set_fix_values(value, names, pattern, period = mdl$get_data_period())

mdl$set_fit_values(value, names, pattern, period = mdl$get_data_period())

mdl is an IsisMdl object
```

**Arguments**

**value** a numeric vector of length 1 or with the same length as the length of the range of period

**names** a character vector with variable names

**pattern** a regular expression specifying the variable names

**period** an [period\\_range](#) object or an object that can be coerced to a period\_range. The default is the data period

**Methods**

**set\_values** Sets the values of model data

**set\_ca** Sets the values of the constant adjustments, i.e. the residuals of behavioural (frml) equations.

**set\_fix** Set fix values for the stochastic model variables (i.e. model variables that occur at the left hand side of a frml equation). The model variables will be fixed at the specified value. A fix value of NA implies that the corresponding variable is not fixed. **set\_fix** also updates the model data with all non NA values

**set\_fit** Set fit targets for the fit procedure. A fit target value of NA implies that the corresponding variable is no fit target

**See Also**

[get\\_data-methods](#), [set\\_data-methods](#) and [change\\_data-methods](#)

**Examples**

```
mdl <- islm_mdl(period = "2017Q1/2017Q3")

# set the values for y in the full data period
mdl$set_values(1000, names = "y")

# set the values of ms and md in 2017Q1 and 2017Q2
mdl$set_values(c(205,206), pattern = "^m.$", period = "2017Q1/2017Q2")

# set the values of ms and md in all quarters of 2017 (2017Q1/2017Q4)
mdl$set_values(c(205, 206, 207, 208), pattern = "^m.$", period = "2017")
```

```
print mdl$get_data())
```

---

solve

*IsisMdl method: Solves the model.*


---

## Description

This method of R6 class [IsisMdl](#) solves the model. It requires that the model period has been set with methods [isis\\_mdl](#), [init\\_data](#) or [set\\_period](#).

## Usage

IsisMdl method:

```
mdl$solve(period = mdl$get_period(), options = list(),
          fit_options = list())
```

mdl is an [IsisMdl](#) object

## Arguments

period [period\\_range](#) object, or an object that can be coerced to [period\\_range](#)

options a named list with solve options, for example `list(maxiter = 50)`. The names are the corresponding argument names of method [set\\_solve\\_options](#). The specified options will only be used in this call of `solve()` and will not be stored in the [IsisMdl](#) object.

fit\_options a named list with options for the fit procedure, for example `list(maxiter = 10)`. The names are the corresponding argument names of method [set\\_fit\\_options](#). The specified options will only be used in this call of `solve()` and will not be stored in the [IsisMdl](#) object.

## Details

The model will be solved for each subperiod from the solution period sequentially. The solution is stored in the [IsisMdl](#) object, and can be retrieved by methods [get\\_data](#) (or [get\\_ca](#) for the constant adjustments). Any subsequent solves of a model will use these data. If a solve has converged and no data have changed, then a second solve will report convergence in 0 iterations.

The solve options specified are only applied to the current solve. If none are specified the solve options as specified with method [set\\_solve\\_options](#) are used.

The solve procedure *never* raises an error, even if the solve was not successful. In that case a warning may be issued. It is up to the user to perform any checks. Method [get\\_solve\\_status](#) can be used to check whether the solve was successfully terminated or not. The solve method outputs a report which the user should check.

## See Also

[set\\_solve\\_options](#), [set\\_fit\\_options](#) and [get\\_solve\\_status](#)

**Examples**

```
mdl <- islm_mdl(period = "2017Q1/2018Q4")
mdl$solve(options = list(report = "fullrep"))

# solve the model for all periods before 2018Q1
mdl$solve(period = "/2017Q4")

# solve the model for all quarters in 2017 (2017Q1/2017Q4)
mdl$solve(period = "2017")
```

---

solve_mdl	<i>Function solve_mdl solves model for given data and returns resulting data and constant adjustments</i>
-----------	---

---

**Description**

Function solve\_mdl solves model for given data and returns resulting data and constant adjustments

**Usage**

```
solve_mdl(model_file, data, period, fix_values, ca, fit_targets)
```

**Arguments**

model_file	is a reference to the file containing the <a href="#">IsisMdl</a> model
data	is a regts object containing time series data
period	is a period object describing a time interval
fix_values	is a regts object containing known time series data that should be fixed during analysis
ca	describes the so-called constant adjustment values
fit_targets	describes the so-called fit targets

**See Also**

[set\\_data-methods](#), [get\\_period](#)

---

write_md1	<i>Writes an IsisMdl object to a file</i>
-----------	---

---

**Description**

This method of R6 class [IsisMdl](#) serializes the model object and writes it to a binary file. The model can be read back by function [read\\_md1](#).

**Details**

write\_md1 employs the serialization interface provided by base R function [saveRDS](#).

**Usage**

```
mdl$write_md1(file)
mdl is an IsisMdl object
```

**Arguments**

file the filename. Preferably use the extension .ismdl so that it is obvious that the written file contains a serialized IsisMdl object.

**See Also**

[read\\_md1](#)

**Examples**

```
mdl <- islm_md1("2017Q1/2019Q2")
mdl$write_md1("islmdl.ismdl")
```

# Index

## \*Topic **data**

- IsisMdl, [20](#)
- all.equal, [3](#), [3](#)
- change\_ca, [21](#)
- change\_ca (change\_data-methods), [4](#)
- change\_data, [21](#)
- change\_data (change\_data-methods), [4](#)
- change\_data-methods, [4](#)
- clear\_fit, [5](#), [30](#)
- clear\_fix, [6](#), [30](#)
- convert\_mdl\_file, [6](#)
- copy, [7](#), [21](#)
- fill\_mdl\_data, [7](#), [22](#)
- fix\_variables, [6](#), [8](#), [30](#)
- get\_ca, [21](#), [43](#)
- get\_ca (get\_data-methods), [9](#)
- get\_cvgcrit (set\_cvgcrit), [28](#)
- get\_data, [21](#), [43](#)
- get\_data (get\_data-methods), [9](#)
- get\_data-methods, [9](#)
- get\_data\_period, [10](#), [21](#)
- get\_debug\_eqn, [22](#)
- get\_debug\_eqn (set\_debug\_eqn), [31](#)
- get\_endo\_names, [10](#), [13](#), [18](#), [21](#)
- get\_eq\_names, [12](#), [21](#), [32](#)
- get\_exo\_names, [11](#), [13](#), [18](#), [21](#)
- get\_fit, [5](#), [21](#)
- get\_fit (get\_data-methods), [9](#)
- get\_fit\_options, [22](#)
- get\_fit\_options (set\_fit\_options), [33](#)
- get\_fix, [6](#), [8](#), [21](#)
- get\_fix (get\_data-methods), [9](#)
- get\_ftrelax, [22](#)
- get\_ftrelax (set\_ftrelax), [34](#)
- get\_labels, [13](#), [21](#)
- get\_last\_solve\_period, [14](#)
- get\_maxlag, [14](#), [21](#)
- get\_maxlead, [14](#), [21](#)
- get\_par\_names, [15](#), [21](#)
- get\_param, [15](#), [21](#)
- get\_period, [16](#), [21](#), [44](#)
- get\_rms (set\_rms), [37](#)
- get\_solve\_options, [22](#)
- get\_solve\_options (set\_solve\_options), [38](#)
- get\_solve\_status, [16](#), [22](#), [43](#)
- get\_text, [17](#), [21](#)
- get\_var\_names, [11](#), [13](#), [18](#), [21](#)
- ifn\_mdl, [19](#), [20](#), [22](#), [24](#)
- init\_data, [19](#), [21](#), [36](#), [43](#)
- isis\_mdl, [6](#), [17](#), [19](#), [20](#), [22](#), [23](#), [43](#)
- IsisMdl, [3–10](#), [12–19](#), [20](#), [23–29](#), [31–38](#), [41–45](#)
- islm\_mdl, [20](#), [22](#), [24](#), [25](#)
- order, [22](#), [25](#)
- period, [14](#)
- period\_range, [4](#), [8](#), [9](#), [20](#), [23](#), [27](#), [37](#), [42](#), [43](#)
- R6Class, [20](#)
- read\_mdl, [26](#), [27](#), [45](#)
- readRDS, [26](#)
- regts, [20](#), [23](#), [29](#)
- run\_eqn, [26](#)
- saveRDS, [45](#)
- serialize, [27](#)
- set\_ca, [21](#)
- set\_ca (set\_data-methods), [29](#)
- set\_ca\_values, [21](#)
- set\_ca\_values (set\_values-methods), [41](#)
- set\_cvgcrit, [22](#), [28](#)
- set\_data, [21](#)
- set\_data (set\_data-methods), [29](#)
- set\_data-methods, [29](#)

set\_debug\_eqn, [22](#), [31](#)  
set\_eq\_status, [11](#), [13](#), [22](#), [31](#)  
set\_fit, [5](#), [21](#)  
set\_fit(set\_data-methods), [29](#)  
set\_fit\_options, [22](#), [33](#), [43](#)  
set\_fit\_values, [21](#)  
set\_fit\_values(set\_values-methods), [41](#)  
set\_fix, [6](#), [8](#), [21](#)  
set\_fix(set\_data-methods), [29](#)  
set\_fix\_values, [21](#)  
set\_fix\_values(set\_values-methods), [41](#)  
set\_ftrelax, [22](#), [34](#)  
set\_labels, [13](#), [21](#), [35](#)  
set\_param, [15](#), [21](#), [36](#)  
set\_period, [10](#), [16](#), [19](#), [21](#), [36](#), [43](#)  
set\_rms, [21](#), [37](#)  
set\_solve\_options, [21](#), [35](#), [38](#), [43](#)  
set\_values, [21](#)  
set\_values(set\_values-methods), [41](#)  
set\_values-methods, [41](#)  
solve, [14](#), [17](#), [21](#), [22](#), [43](#)  
solve\_mdl, [44](#)  
  
ts, [20](#), [29](#)  
  
write\_mdl, [17](#), [22](#), [26](#), [27](#), [45](#)