Stolpe,
Graal-LSP

Graal-LSP: A Zero-overhead Polyglot Language Server Implementation for the GraalVM

Graal-LSP: Eine Overhead-freie Language Server Implementierung für die GraalVM

by

Daniel Stolpe

A thesis submitted to the
Hasso Plattner Institute
at the University of Potsdam, Germany
in partial fulfillment of the requirements for the degree of

Master of Science in IT-Systems Engineering

Supervisors

Prof. Dr. Robert Hirschfeld
Dr. John Doe

Software Architecture Group
Hasso Plattner Institute
University of Potsdam, Germany

December 26, 2018

Abstract

The english abstract.

Zusammenfassung

Die Zusammenfassung auf deutsch.

Acknowledgments

I owe everything to my cat.

Contents

1. Introduction **1**
1.1. Contributions . . . 1
1.2. Structure of this Thesis . . . 2

2. Context **3**
2.1. Terms and Concepts . . . 3
2.2. Truffle and GraalVM . . . 3
2.3. Language Server Protocol . . . 4

3. Approach **7**
3.1. A Language-agnostic Language Server . . . 7
3.1.1. Language Server Initialization . . . 8
3.1.2. Parsing Source Code . . . 8
3.1.3. Diagnostics . . . 9
3.1.4. Mapping Caret Position to Abstract Syntax Tree (AST) Node . . . 9
3.1.5. Static Completion of Globals and Locals . . . 10
3.1.6. Using Runtime Information . . . 12
3.1.7. completion of object properties . . . 12
3.1.8. Document symbols . . . 13
3.1.9. Workspace-wide Symbols . . . 14
3.2. Architecture + Language Server Bootstrapping . . . 15

4. Implementation **17**
4.1. Language Server Implementation . . . 17
4.1.1. Architecture . . . 17
4.1.2. Using runtime information . . . 17
4.1.3. LSP features implementation overview . . . 17
4.1.4. LSP client - VSCode extension example . . . 19
4.2. Requirements on Truffle Language Implementations . . . 19

5. Experience Report **21**
5.1. Between IDE and Language Workbench . . . 21
5.2. Completion response time . . . 21
5.3. Limitations . . . 21

6. Related Work **23**
6.1. Helvetia . . . 23
6.2. Self . . . 23
6.3. Smalltalk+Squeak . . . 23

6.4. Squimera 23
6.5. Language Workbenches 23
6.6. Run-time type collection 23
6.7. CTags 23

7. Conclusion and Future Work **25**

A. First Unimportant stuff. **29**

List of Figures

2.1. Truffle languages hosted by the Truffle framework on top of the GraalVM 5
2.2. example for how a tool and a language server communicate during a routine editing session 6

3.1. lang specific server vs lang-agnostic server 7
3.2. A Visual Studio Code extension for the Python language showing the completions of globals and locals available in a function scope, together with reserved keywords. 10
3.3. A Visual Studio Code extension for the Python language showing all detected symbols in the current document. There are different icons for modules, classes, functions and variables. 14

List of Tables

3.1. Selected Language Server Protocol (LSP) features and their descriptions 8

List of Listings

1. An example Python code snippet showing two functions to explain scopes. 11

List of Abbreviations

LSP	Language Server Protocol
IDE	Integrated Development Environment
AST	Abstract Syntax Tree
API	Application Programming Interface
VM	Virtual Machine
URI	Uniform Resource Identifier
VSCode	Visual Studio Code

1. Introduction

- language development is challenging task
- what makes a good language: amongst performance, std lib, ecosystem and community, tools (for language developers and users) are important
- who provides the tools? language developers vs. language users
- normally tools are developed for a specific language and cannot be reused or need lots of adaptation
- In the Truffle framework, tooling (instrumentation) is part of the framework and therefore tools are implemented language-agnostic once
- Truffle has already some language-agnostic tools implemented (debugger, profiler, ...) and new ones can be easily built
- Truffle tooling support does not interfere with implementing high-performance languages
- Compared to a full IDE, some tools are missing
- Implementing LSP can provide further IDE-like features
- We propose an approach to build a generic LSP server on top of Truffle with:
  - minimal to zero language runtime performance overhead
  - minimal API changes to Truffle
  - minimal impl and maintenance overhead for language developers
- Benefits for the language developers: get IDE-like tools with minimal effort
- Benefits for language users: can choose from wide range of LSP clients + consistent dev-tools experience for different Truffle languages
- As proof of concept, we have implemented Graal-LSP- A Zero-overhead Polyglot Language Server Implementation for the GraalVM
- ?: focus on dynamically type languages? Or is this focus already included in Truffle (most impls are dynamically type langs)?

1.1. Contributions

- Contribution in detail:
  - An approach to build a generic LSP server on top of Truffle
  - An implementation of said approach: Graal-LSP
  - Proposals to extend the Truffle Framework with new interfaces needed to support more LSP features
  - An experience report how well existing Graal/Truffle-implemented languages work with Graal-LSP(with and without implementing the said interface proposals)

1.2. Structure of this Thesis

2. Context

In this chapter we explain terms, concepts and technologies helping to understand our approach in Chapter 3 and the implementation of Graal-LSP in Chapter 4.

2.1. Terms and Concepts

Abstract Syntax Tree (AST) Parsers for programming languages usually transform plain text source code into an intermediate representation which can be processed by compilers, interpreters or programming environment tools. An AST is such a typical representation which stores structural information of the source code implicitly in its tree structure. Therefore, concrete syntactic elements needed to write parsable code in plain text can be omitted. In general, inner nodes of the AST represent programming language operations and leaf nodes store the values needed for these operations. Depending on the use case, an AST can store additional information in its nodes. For example the original source section from which a node was derived. Programming environment tools can use these information to display any kind of errors, warnings or hints directly in the plain text source code. An AST interpreter evaluates an AST by traversing its tree structure and executing the operations defined in the nodes.

Scopes and Frames A Scope defines a region of a program in which a set of name bindings is valid, e.g. a local variable name. Most programming languages have a concept of a global (program wide) scope and local scopes defined by functions, blocks or modules. During execution of a program, frames store the actual values of the name bindings of visible scopes.

Static vs. Dynamic?

VM?

2.2. Truffle and GraalVM

Truffle is a language implementation framework written in Java [13]. The language developer uses the framework to write an AST interpreter, which is able to optimize itself during interpretation [16]. To achieve that, Truffle uses runtime type information to rewrite AST nodes. Callable elements of a language, e.g. functions or methods, are modeled as root nodes. They can be executed by providing a frame object. A node can have a source section attribute which encodes the range in the source code file it

relates to. How source code is parsed and the AST is structured leaves Truffle in the responsibility of the language implementation.

Truffle has built-in support for developing language-agnostic tools by providing an instrumentation Application Programming Interface (API) [10]. It is designed to work well with the optimization techniques for language implementations so that instrumentation can be done with nearly zero-overhead [11]. Instruments can be installed by putting it on the Java class path and then be registered and unregistered dynamically as listeners for different events. For example, an instrument can be notified when a new source or source section is loaded, a statement is going to be executed or an expression will return a value. It is also possible to alter the current execution flow and let a function return a different value when called under certain conditions. This enables building powerful tools like debuggers or profilers which need to be implemented only once and can then be used for all Truffle languages. To control which AST nodes of a language are available for instrumentation, language implementors need to mark nodes as instrumentable. A tagging mechanism allows adding meta information, like "this node represents a statement in my language", which can be used by instruments to filter for specific nodes. For example, a debugger can facilitate these information to implement stepping. The tools available at the date of writing are mostly runtime-tools like debuggers, dynamic profilers and language extensions [11].

Cross-language interoperability is another feature of the Truffle framework [3]. Language implementations can be hosted by the Truffle framework in a multi-language runtime and communicate via language-independent messages. Foreign language objects can be accessed directly without marshalling.

To get high-performance language implementations, Truffle uses the language-independent just-in-time compiler named Graal. It has its roots in the research project of the Maxine VM [12]. Among other optimizations, Graal applies partial evaluation to compile stable AST subtrees into optimized machine code [14, 2]. These optimizations do not stop at language boundaries, so that the access of foreign language objects can also be optimized.

cite or footnote?

GraalVM[1] is the umbrella term for a HotSpot VM which is bundled with the Truffle language implementation and instrumentation framework and the Graal compiler, building a high-performance polyglot VM for applications written in a Truffle-implemented language [15]. Figure 2.1 visualizes that.

2.3. Language Server Protocol

In 2016 a group of IT companies, including Microsoft, Red Hat, and Codenvy, started to standardize the Language Server Protocol (LSP) [5]. This protocol describes an approach to tackle the problem of language and tool developers, which need to repeatedly implement language support (e.g. code completion, jump-to-definition and syntax error reporting) for every new code editor, Integrated Development Environment (IDE) or development tool. The LSP defines a *language server* and a *language*

[1] https://www.graalvm.org/




Figure 2.1.: Truffle languages hosted by the Truffle framework on top of the GraalVM

client. The server needs to be implemented only once for every language, providing the language-specific smarts. A development tool implementing a language client can make use of any language server and therefore support multiple languages with minimal effort.

At the date of writing, language servers for more than 50 languages exist[2], including almost all popular programming and scripting languages. Not all implementations support the full feature set defined in the LSP. Usually, these language server implementations support exactly one language, but the LSP allows multiple languages per server.

Language client and server communication LSP client and server communicate via JSON-RPC[3] requests, responses and notifications. The LSP version 3.7.0, which is the reference for our approach and implementation of Graal-LSP, specifies requests for typical features of an IDE: e.g. code and signature completion, navigational features (goto-definition, find all references and implementations, etc.), information on hover and code formatting. During initialization client and server can exchange which features are supported.

Figure 2.2 shows an exemplary communication between server and client. The client notifies the server that a file has been opened, the server parses the source code and pushes diagnostics to the client. Client-side changes to the source code are incrementally sent to the server.

LSP4J Our implementation of Graal-LSP uses LSP4J[4] version 0.4.x as Java binding for the Language Server Protocol. This framework maps the LSP requests and notifications to methods of Java interfaces so that the language server implementor does not have to deal with the JSON-RPC communication layer.

version

[2] https://microsoft.github.io/language-server-protocol/implementors/servers/ Sep. 2018
[3] https://www.jsonrpc.org/specification
[4] https://github.com/eclipse/lsp4j




Figure 2.2.: example for how a tool and a language server communicate during a routine editing session

Visual Studio Code We used Microsoft's editor Visual Studio Code (VSCode)[5] to create an exemplary language client extension and experiment with Graal-LSP.

[5] https://code.visualstudio.com

3. Approach

- language implementation + tool development = challenging task
- we propose: implement LSP for Truffle
- typically one specific language server impl for one language
- Our approach: a language-agnostic language server impl for languages created by the language implementation framework Truffle, Figure 3.1

3.1. A Language-agnostic Language Server

- LSP enables arbitrary language clients to communicate with arbitrary language servers
- Normally a language server provides support for one specific language only
- To build a language-agnostic language server for Truffle we have to define what Truffle languages need to provide in general to support LSP
- LSP is trade-off - there are lang-specific IDEs with more/other features
- Therefore our solution will also be a trade-off using general language features available for all Truffle languages
- Truffle ASTs have runtime focus. Existing languages are implemented with performance focus. Infos not relevant for execution are dropped.

In the following sections we suggest how the existing Truffle language and instrumentation APIs can be facilitated to provide the needed data for LSP requests and notifications. When needed, we also suggest small API extensions to get access to additional language-specific information which have not been exposed yet, due to fact that the existing tools are mostly runtime-focused and do not require them.

Table 3.1 gives an overview over the most interesting requests and notifications of the LSP version 3.7.0 which we cover in our approach.




Figure 3.1.: lang specific server vs lang-agnostic server

Table 3.1.: Selected LSP features and their descriptions

Request/Notification	Description	Section
initialize	First request containing client capabilities. Response contains server capabilities.	3.1.1
didOpen	Notification sent from client to sever that a file was opened. Contains URI and content.	3.1.2
didChange	Notification sent from client to sever that a file has changed. Contains URI and changes.	3.1.2
diagnostics	Notification sent from server to client to display errors, warnings or hints.	3.1.3
completion	Completion request at caret position. Can be triggered automatically via registered completion trigger characters.	3.1.5
signatureHelp	Request to find signature information (e.g. parameter names and details for a function) at caret position. Is triggered via registered signatureHelp trigger characters.	
hover	Request for information at caret-hovering position.	
documentSymbol	Request for symbols of a specific source file (function names, variable names, module names, etc.).	3.1.8
symbol	Like documentSymbol, but for all files in the client workspace.	3.1.9
definition	Goto-definition request for functions, variables, etc.	
references	Request to find all references of a symbol.	
documentHighlight	Request to highlight all ranges related to a symbol (e.g. variable reads and writes).	
codeLense	Request to provide executable actions at arbitrary source locations.	

3.1.1. Language Server Initialization

The first request sent from the client to the server is the "initialize" request. Among other parameters, it contains client capabilities, telling the server which LSP features the client supports. The server responds to this by sending its own capabilities. When a server supports "completion" and "signatureHelp" the response needs to include trigger characters which tell the client when "completion" or "signatureHelp" shall be triggered automatically. A language-specific language server implementation can provide these characters statically. In our language-agnostic approach, where Truffle languages can be installed dynamically, we have to collect these characters for all available languages during server initialization. Using the Truffle instrumentation environment, we can get a list of all registered languages, but an interface extension is needed to get the trigger characters for "completion" and "signatureHelp" of a language.

3.1.2. Parsing Source Code

To parse source code in Truffle, we need to define a `Source` object, containing the language and the content of the file. The language can be derive from its supported media types. The "didOpen" or "didChange" requests contain an Uniform

Resource Identifier (URI) pointing to the concerning source file, which we use to find the required media type. The "didOpen" request also contains the file content. The "didChange" request contains only incremental changes if configured during initialization. Therefore we have to continuously store the content and apply all incoming changes to keep track of the client-side file state.

The "initialize" request can contain a workspace URI. If present, we parse all files with Truffle language-associated media types in that folder and its subfolders at start-up. To do so, we need to collect all media types of all installed languages via the Truffle environment.

Truffle's parsing result is a `CallTarget`, ready to be executed. It holds a reference to a root node of a runtime-focused AST.

In case of a parsing error, we can notify the client using the "diagnostics" notification.

3.1.3. Diagnostics

Truffle languages typically throw a `TruffleException` in case of a parsing error. The parsers are not designed to be syntax error tolerant and will stop parsing at the first syntax error. A `TruffleException` can have a reference to the location where the exception occurred in the AST. If available, we map these information to line and column of the original source code and send a "diagnostics" notification to the client. If the location is not available, we use the first column in the first line as reference for the notification. The error message needed for the notification is also derived from the `TruffleException`.

The "diagnostics" notification is also used to display code coverage information, which will be described in xyz. ref

3.1.4. Mapping Caret Position to AST Node

Most LSP requests are context-sensitive and include line and column as reference in the request. The language server has the responsibility to map these information to data structures of the language. For Truffle, this means mapping line and column to AST nodes via their associated source section. The challenge for our language-agnostic language server is that the Truffle framework leaves the creation of the runtime-focused ASTs completely to the language implementation. We cannot simply traverse an AST by starting at the `CallTarget`'s executable root node which we get as parsing result. There might be more root nodes, which will be executed dynamically at runtime, depending on the language implementation. However, we can use the Truffle instrumentation environment to access all already loaded nodes which have a source section, under the condition, that the source code is parsable.

Depending on the use cases described in the next sections, we are either interested in a node directly at the caret position ("hover", "definition" and other requests) or a node near the caret position ("completion" request for globals and locals). To find these nodes in a language-agnostic way, we have to define two assumptions.




Figure 3.2.: A Visual Studio Code extension for the Python language showing the completions of globals and locals available in a function scope, together with reserved keywords.

Eager Source Code Parsing First of all we assume, that parsing a Truffle `Source` object is done when we call the corresponding API and not lazily when the `CallTarget` is executed. Otherwise no nodes and source sections will be available via the Truffle instrumentation environment.

Consistent Source Section Hierarchy We assume furthermore, that source sections of ASTs follow the rule: if a node has a source section and is a child of another node, then the source section of the child is fully contained in all source sections of its direct parent or indirect parents. A parent without a source section in this hierarchy is skipped.

3.1.5. Static Completion of Globals and Locals

ref?

A context-sensitive code completion is one of the most important features to increase productivity of programmers. It suggests valid symbols regarding the current scope and thereby supports programmers to explore, for example, the built-in functions of a language, read their documentation or select predefined code snippets.

For Truffle, we have to distinguish between two kinds of code completion, both depending on the current caret position. The first one we call *completion of globals and locals*, described in this section. The second one we call *completion of object properties*, described in Section 3.1.7.

Completion of globals and locals is the completion you typically get in IDEs when the caret is placed in an empty line and the user presses a keyboard shortcut, e.g. `Ctrl+Space`. With *globals* we refer to all the symbols which we can derive from global scopes of languages and with *locals* we analogously refer to all symbols which we can derive from local scopes of languages. In the Python programming language [9] globals are, for example, built-in functions or classes. Locals of a function scope are function parameters or local variables. Locals of a class scope are fields or methods. Figure 3.2 exemplarily shows a code completion for globals and locals of a Python file in Visual Studio Code.

If the assumptions in Section 3.1.4 (eager source code parsing and a consistent source section hierarchy) are true, we can provide *static* code completion for globals and locals by using existing Truffle APIs. With *static*, we refer to a code completion, where we can only access lexical scopes to find locals. An approach to use runtime information for code completion, e.g. via a frame, is explained in Section 3.1.6.

Statically Deriving Local Scopes From a Node Global scopes are always accessible via the Truffle instrumentation environment. To find the relevant local scopes statically, we need to find a node which has a source section *relevantly near* the client's caret position. In the following we use some Python code snippets to explain what we mean by *relevantly near*.

Listing 1: An example Python code snippet showing two functions to explain scopes.

```
1  def foo(param1, param2):
2      x = 42
3
4      y = param1 + param2
5
6      print(x * y)
7
8
9  def bar():
10     return 42
```

listing 1 shows Python source code with a function definition `foo`, containing two parameters and two local variables in its scope and a function `bar` without definition of locals. Imagine that the caret is placed in the empty line 3 between the two variable assignments and code completion is triggered. The caret is clearly placed inside the scope of the function `foo` and we would assume that the code completion suggests, among globals, the two parameters `param1` and `param2`, and the local variable `x`. The local variable `y` is also in the function scope of `foo`, but is not written until line 4 and should therefore not be included in the suggestions. Whereas, if the caret is placed in line 5, `y` should be included.

label counter wrong?

As already mentioned, Truffle cannot derive scopes directly from the caret position, but from a node. The difficulty is, that the scopes, which the Truffle API derives from a node, contain variables valid *at* that node. This means translated to our Python example, that if we use the node representing `x = 42` in line 2 to derive local scopes, the scopes do not include the variable `x`. One could say, that we get all locals valid before the node's source section starts. Therefore we have to decide in a language-agnostic way, which node is near[1] the caret and provides the relevant information we need for the code completion.

Imagine code completion is triggered in line 3. Then the most inner node, which contains the caret, could be the function definition of `foo` ranging from line 1 to 6. The nearest node behind the caret could be the assignment of `y` in line 4 and the nearest node before the caret could be the assignment of `x` in line 2.

[1] For simplicity, we say in the following *a node near/after/before/containing the caret* instead of *a node which has a source section near/starting after/ending before/containing the caret position*

3. *Approach*

We suggest finding the node *relevantly near* the client's caret position following the rule:

1. If the caret is not contained in a node, we are not in a local scope. No completion of locals necessary. (Example: caret at line 8)
2. If contained, pick the node which is nearest behind the caret position and which is also an (indirect) child of the node which contains the caret. (Example: caret at line 3, picking node `y = param1 + param2`)
3. If not found, pick the node which is nearest before the caret. (Example: caret indented at line 7, picking `y = param1 + param2`)
4. If still not found, use the node which contains the caret.

At this point, we have to note that this rule is only a best effort approach. Which locals are included in the lexical scopes provided via the Truffle API is depending on the language implementation. None the less, we are able to provide the needed information for a language-agnostic, static code completion of globals and locals with this approach. For the globals we can additionally provide ...

details, docu etc., querying TruffleObjects

3.1.6. Using Runtime Information

- to display details e.g. about globals/locals, type information are needed
- easy for statically typed languages - not for dynamic
- so we need a generic approach
- idea: at runtime we can track type information (see type harvesting etc)
- -> learn
- run code
- challenges: side-effects, endless execution, (caret position not reached)
- side-effects -> sandboxing
- endless execution -> abort when caret position reached + TODO(timeout)
- caret position not reached -> define run-script-path to a script or test which covers the caret position
- run: observe frame at every source section, store a snapshot of the frame associated to the source section
- completion of globals/locals -> if node near caret has source section associated with coverage data -> use frame for globals/locals completion to get more details
- user interface to start code evaluation: see codeLense

3.1.7. completion of object properties

- define "object property completion"
- check trigger character
- assumption: inserting a completion character => code might be not parsable
- fix code by undoing last change + parse again
- derive type information from node at caret
- run code to caret position
- optimizations: try different evaluation strategies

  - literal -> type can be derived without execution
  - coverage data (explained later)
  - run-to-section
  - globals

- getting infos from evaluation result object
- use TruffleObject interface to check object kind, documentation, signature, etc...

hover

- same preconditions as for completion (parsable code, find node at caret)
- if coverage data available: parse in-line + eval in-line
- for language developers: show debug infos (AST structure)

signatureHelp

- same preconditions as for completion (parsable code, find node at caret)
- need to know the signatureHelp trigger character
- when triggered -> assumption: code still parsable (e.g. editor has smart character insertion)
- find callable node at caret
- run to section
- listen for callable object
- ask via message to TruffleObject for signature and number of arguments

3.1.8. Document symbols

The *documentSymbol* request is sent from client to server to get all symbols available in a specific source file. An URI parameter is included in the request. Each symbol in the response must be associated with a source section. If the symbol, for example, relates to a function definition, the range of the definition including the function body could be taken as the source section. Additionally, a symbol kind can be added for each symbol in the response. Figure 3.3 shows how the *documentSymbol* response looks like in Visual Studio Code with active Python extension.

To implement the *documentSymbol* request for Truffle languages, we have to think about which kind of symbols we can support with the current Truffle API. With the instrumentation environment we can access all loaded nodes which have a source section. We can filter them based on their meta information to find all root nodes. Because a root node is executable, we assume that the name of the root node is a valid symbol of a callable element of the corresponding Truffle language. However, to add a symbol kind we need more meta-information about the nodes.

Tagging Nodes with Meta-information To get the required meta-information, we suggest to add a new `Tag` for nodes introducing new symbols in a scope. There are already some tags existing to mark statements, expressions, calls, and root nodes. They are mainly used to implement debugger features like stepping. Using again




Figure 3.3.: A Visual Studio Code extension for the Python language showing all detected symbols in the current document. There are different icons for modules, classes, functions and variables.

the example of the Python language, the tag we suggest could be used to mark function and class definition nodes, first occurrences of a variable assignment node (Python has no variable declarations), or import nodes. This way we could support the *documentSymbol* request in a language-agnostic way with results equal to those language-specific ones already shown in Figure 3.3.

3.1.9. Workspace-wide Symbols

The *symbol* request is the union of *documentSymbol* requests for all files in the workspace. Therefore, if we use the solution for *documentSymbol* explained in Section 3.1.8, we can easily add support for the workspace-wide *symbol* request.

documentHighlight

- parsable code + find node at caret
- variables only
- find other variable read/writes nodes in scope
- need to tag such nodes with ReadVariableTag+WriteVariableTag

definition

- parsable code + find node at caret
- function vs variable
- function
  - dynamic approach: run-to-section to get function object

  - ask function object for its source section of definition
  - static fallback: search for symbols in workspace
- variable
  - not all languages have a variable definition syntax -> first write is definition
  - so we interpret goto-definition for variables as goto-first-write
  - find first write in scopes

references

- parsable code + find node at caret
- function vs variable
- function
  - dynamic approach: run-to-section to get function object
  - search for function calls
- variable
- ...

codeLense / Coverage analysis

Language features not implemented

- completion resolve
- typeDefinition
- implementation
- codeAction
- documentLink
- documentLink resolve
- documentColor
- colorPresentation
- formatting
- rangeFormatting
- onTypeFormatting
- rename
- foldingRange

3.2. Architecture + Language Server Bootstrapping

- graphic showing launcher, lsp server, truffle api communication
- comparison to other language server impls (built on top of language)

4. Implementation

4.1. Language Server Implementation

- lsp4j - Java binding for LSP (see Context)

4.1.1. Architecture

- Truffle-API + Graal-SDK
- Launcher, Instrument, Server
- lsp4j adapters

4.1.2. Using runtime information

Implementation of:

- Observe execution via instrumentation
- Side-effects -> Truffle-sandboxing
- Nested Contexts
- Evaluation strategies:
  - Literals
  - Coverage data
    - storing frames (copies)
    - source location format
    - migrating coverage data on source edit
  - Run-to-section
  - Globals

4.1.3. LSP features implementation overview

Feature impl matrix:

- TextDocumentService interface
  - completion
    - locals+globals vs object property completion (via checking completion character)
    - locals+globals completion
      - find nearest node

4. *Implementation*

    - check coverage data
    - globals only fallback
    - Used Truffle-API: findLocalScopes() + findGlobalScopes() + (parseInline() for coverage) + ForeignAccess.sendIsExecutable() + ForeignAccess.sendIsInstantiable() + ForeignAccess.sendIsNull()
    - Used new Truffle-API: env.boxPrimitive() + GetSignature + GetDocumentation

  * object property completion

    - fixing source code (undo last edit + re-parse)
    - find nearest node
    - tryDifferentEvalStrategies() (literals -> coverage data -> run-to-section -> globals)
    - Used Truffle-API: findLocalScopes() + findGlobalScopes()

  – hover
  – signatureHelp
  – definition
  – typeDefinition
  – implementation
  – references
  – documentHighlight
  – documentSymbol
  – codeAction
  – codeLense
  – formatting
  – rangeFormatting
  – onTypeFormatting
  – rename
  – didOpen
  – didChange
  – didClose
  – didSave
  – willSave
  – willSaveWaitUntil
  – documentLink
  – documentLinkResolve
  – documentColor
  – colorPresentation

- WorkspaceService interface

  – executeCommand
  – symbol
  – didChangeConfiguration
  – didChangeWatchedFiles

- didChangeWorkspaceFolders

4.1.4. LSP client - VSCode extension example

4.2. Requirements on Truffle Language Implementations

- Implement existing API:
  - ExpressionTag + StatementTag
  - findTopScopes()
  - findLocalScopes()
  - findMetaObject()
  - findSourceLocation()
  - parseInline()
- Implement proposed/new API:
  - getCompletionTriggerCharacters()
  - getSignatureHelpCharacters() (TODO)
  - boxPrimitive()
  - GetSignature + GetDocumentation custom message
  - DefinitionTag + ReadVariableTag + WriteVariableTag

5. Experience Report

5.1. Between IDE and Language Workbench

Language Workbench focus/aim: Efficient language (DSL) development, performance is not main focus vs. Graal/Truffle aim: Efficient execution

Assumption: Language Workbenches use static information only, our Truffle-based solution uses dynamic type information

5.2. Completion response time

5.3. Limitations

own chapter? or in 4?

- VSCode: Need to define supported languages in extension
- VSCode: Syntax highlighting defined at client-side
- LSP: No incremental sending of (completion) results
- Server: Only TCP (connecting to already running server), no std-in/-out impl
- Truffle: Only first syntax error is reported. Lang parsers fail on first error

6. Related Work

6.1. Helvetia

[8]

6.2. Self

6.3. Smalltalk+Squeak

6.4. Squimera

[7] [6]

6.5. Language Workbenches

[1]

6.6. Run-time type collection

[4]

6.7. CTags

- tagging a language object in an index file
- tag-file supported by editors
- allows user to locate the tagged object via name (goto-definition, list symbols)
- for new languages you need to define a regex or parser to find language objects
- only static analysis, no scoped completion (everything is suggested)

SemanticDB

7. Conclusion and Future Work

Bibliography

[1] Sebastian Erdweg, Tijs Van Der Storm, Markus Völter, Meinte Boersma, Remi Bosman, William R Cook, Albert Gerritsen, Angelo Hulshout, Steven Kelly, Alex Loh, et al. "The State of the Art in Language Workbenches". In: *International Conference on Software Language Engineering*. Springer. Springer International Publishing, 2013, pp. 197–217. DOI: 10.1007/978-3-319-02654-1_11.

[2] Yoshihiko Futamura. "Partial evaluation of computation process–an approach to a compiler-compiler". In: *Higher-Order and Symbolic Computation* 12.4 (1999), pp. 381–391. DOI: 10.1023/A:1010095604496.

[3] Matthias Grimmer, Chris Seaton, Roland Schatz, Thomas Würthinger, and Hanspeter Mössenböck. "High-performance cross-language interoperability in a multi-language runtime". In: *ACM SIGPLAN Notices*. Vol. 51. 2. ACM. 2015, pp. 78–90. DOI: 10.1145/2936313.2816714.

[4] Michael Haupt, Michael Perscheid, and Robert Hirschfeld. "Type harvesting: a practical approach to obtaining typing information in dynamic programming languages". In: *Proceedings of the 2011 ACM Symposium on Applied Computing*. ACM. 2011, pp. 1282–1289. DOI: 10.1145/1982185.1982464.

[5] Microsoft. *Language Server Protocol*. https://microsoft.github.io/language-server-protocol/. Visited on 2018-09-24. 2017.

[6] Fabio Niephaus, Tim Felgentreff, Tobias Pape, and Robert Hirschfeld. "Squeak Makes a Good Python Debugger: Bringing Other Programming Languages Into Smalltalk's Tools". In: *Companion to the first International Conference on the Art, Science and Engineering of Programming*. ACM. 2017, p. 27. DOI: 10.1145/3079368.3079402.

[7] Fabio Niephaus, Tim Felgentreff, Tobias Pape, Robert Hirschfeld, and Marcel Taeumel. "Live Multi-language Development and Runtime Environments". In: *arXiv preprint arXiv:1803.10200* 2.3 (Mar. 2018). DOI: 10.22152/programming-journal.org/2018/2/8.

[8] Lukas Renggli, Tudor Gîrba, and Oscar Nierstrasz. "Embedding languages without breaking tools". In: *European Conference on Object-Oriented Programming*. Springer. 2010, pp. 380–404. DOI: 10.1007/978-3-642-14107-2_19.

[9] Guido van Rossum. *Python Tutorial*. Tech. rep. CS-R9526. Centrum voor Wiskunde en Informatica (CWI), 1995.

[10] Michael L Van De Vanter. "Building debuggers and other tools: we can have it all". In: *Proceedings of the 10th Workshop on Implementation, Compilation, Optimization of Object-Oriented Languages, Programs and Systems*. ACM. 2015, p. 2. DOI: 10.1145/2843915.2843917.

[11] Michael Van De Vanter, Chris Seaton, Michael Haupt, Christian Humer, and Thomas Würthinger. "Fast, Flexible, Polyglot Instrumentation Support for Debuggers and other Tools". In: *arXiv preprint arXiv:1803.10201* (2018). DOI: 10.22152/programming-journal.org/2018/2/14.

[12] Christian Wimmer, Michael Haupt, Michael L Van De Vanter, Mick Jordan, Laurent Daynès, and Douglas Simon. "Maxine: An approachable virtual machine for, and in, java". In: *ACM Transactions on Architecture and Code Optimization (TACO)* 9.4 (2013), p. 30. DOI: 10.1145/2400682.2400689.

[13] Christian Wimmer and Thomas Würthinger. "Truffle: a self-optimizing runtime system". In: *Proceedings of the 3rd annual conference on Systems, programming, and applications: software for humanity*. ACM. 2012, pp. 13–14. DOI: 10.1145/2384716.2384723.

[14] Thomas Würthinger, Christian Wimmer, Christian Humer, Andreas Wöß, Lukas Stadler, Chris Seaton, Gilles Duboscq, Doug Simon, and Matthias Grimmer. "Practical Partial Evaluation for High-performance Dynamic Language Runtimes". In: *Proceedings of the 38th ACM SIGPLAN Conference on Programming Language Design and Implementation - PLDI 2017*. Vol. 52. 6. ACM. 2017, pp. 662–676. DOI: 10.1145/3062341.3062381.

[15] Thomas Würthinger, Christian Wimmer, Andreas Wöß, Lukas Stadler, Gilles Duboscq, Christian Humer, Gregor Richards, Doug Simon, and Mario Wolczko. "One VM to rule them all". In: *Proceedings of the 2013 ACM international symposium on New ideas, new paradigms, and reflections on programming & software*. ACM. 2013, pp. 187–204. DOI: 10.1145/2509578.2509581.

[16] Thomas Würthinger, Andreas Wöß, Lukas Stadler, Gilles Duboscq, Doug Simon, and Christian Wimmer. "Self-optimizing AST interpreters". In: *ACM SIGPLAN Notices*. Vol. 48. 2. ACM. 2012, pp. 73–82. DOI: 10.1145/2384577.2384587.

Appendix A.

First Unimportant stuff.

Hello, here is some text without a meaning. This text should show what a printed text will look like at this place. If you read this text, you will get no information. Really? Is there no information? Is there a difference between this text and some nonsense like “Huardest gefburn”? Kjift – not at all! A blind text like this gives you information about the selected font, how the letters are written and an impression of the look. This text should contain all letters of the alphabet and it should be written in of the original language. There is no need for special content, but the length of words should match the language.

Eigenständigkeitserklärung

Hiermit versichere ich, dass ich die vorliegende Arbeit selbständig verfasst sowie keine anderen Quellen und Hilfsmittel als die angegebenen benutzt habe.

Berlin, den 26. Dezember 2018

Daniel Stolpe

Todo list

cite or footnote? . . . 4
version . . . 5
ref . . . 9
ref? . . . 10
label counter wrrong? . . . 11
details, docu etc., querying TruffleObjects . . . 12
own chapter? or in 4? . . . 21