Stolpe,
Graal-LSP

Graal-LSP: A Zero-overhead Polyglot Language Server Implementation for the GraalVM

Graal-LSP: Eine Overhead-freie Language Server Implementierung für die GraalVM

by

Daniel Stolpe

A thesis submitted to the
Hasso Plattner Institute
at the University of Potsdam, Germany
in partial fulfillment of the requirements for the degree of

Master of Science in IT-Systems Engineering

Supervisors

Prof. Dr. Robert Hirschfeld
Dr. John Doe

Software Architecture Group
Hasso Plattner Institute
University of Potsdam, Germany

December 26, 2018

Abstract

The english abstract.

Zusammenfassung

Die Zusammenfassung auf deutsch.

Acknowledgments

I owe everything to my cat.

Contents

1. Introduction **1**
1.1. Contributions . . . 1
1.2. Structure of this Thesis . . . 2

2. Context **3**
2.1. Terms and Concepts . . . 3
2.2. Truffle and GraalVM . . . 3
2.3. Language Server Protocol . . . 4

3. Approach **5**
3.1. A Language-agnostic Language Server . . . 5
3.2. Architecture . . . 9

4. Implementation **11**
4.1. Language Server Implementation . . . 11
4.1.1. Architecture . . . 11
4.1.2. Using runtime information . . . 11
4.1.3. LSP features implementation overview . . . 11
4.1.4. LSP client - VSCode extension example . . . 13
4.2. Requirements on Truffle Language Implementations . . . 13

5. Experience Report **15**
5.1. Between IDE and Language Workbench . . . 15
5.2. Completion response time . . . 15
5.3. Limitations . . . 15

6. Related Work **17**
6.1. Graal . . . 17
6.2. Squimera . . . 17
6.3. Language Workbenches . . . 17
6.4. Run-time type collection . . . 17
6.5. CTags . . . 17

7. Conclusion and Future Work **19**

A. First Unimportant stuff. **23**

List of Figures

3.1. lang-specific-server-vs-lang-agnostic-server 5

List of Tables

List of Listings

List of Abbreviations

LSP Language Server Protocol
IDE Integrated Development Environment
AST Abstract Syntax Tree
API Application Programming Interface

1. Introduction

- language development is challenging task
- what makes a good language: amongst performance, std lib, ecosystem and community, tools (for language developers and users) are important
- who provides the tools? language developers vs. language users
- normally tools are developed for a specific language and cannot be reused or need lots of adaptation
- In the Truffle framework, tooling (instrumentation) is part of the framework and therefore tools are implemented language-agnostic once
- Truffle has already some language-agnostic tools implemented (debugger, profiler, ...) and new ones can be easily built
- Truffle tooling support does not interfere with implementing high-performance languages
- Compared to a full IDE, some tools are missing
- Implementing LSP can provide further IDE-like features
- We propose an approach to build a generic LSP server on top of Truffle with:
  - minimal to zero language runtime performance overhead
  - minimal API changes to Truffle
  - minimal impl and maintenance overhead for language developers
- Benefits for the language developers: get IDE-like tools with minimal effort
- Benefits for language users: can choose from wide range of LSP clients + consistent dev-tools experience for different Truffle languages
- As proof of concept, we have implemented Graal-LSP- A Zero-overhead Polyglot Language Server Implementation for the GraalVM
- ?: focus on dynamically type languages? Or is this focus already included in Truffle (most impls are dynamically type langs)?

1.1. Contributions

- Contribution in detail:
  - An approach to build a generic LSP server on top of Truffle
  - An implementation of said approach: Graal-LSP
  - Proposals to extend the Truffle Framework with new interfaces needed to support more LSP features
  - An experience report how well existing Graal/Truffle-implemented languages work with Graal-LSP(with and without implementing the said interface proposals)

1.2. Structure of this Thesis

2. Context

In this chapter we explain terms, concepts and technologies helping to understand our approach in Chapter 3 and the implementation of Graal-LSP in Chapter 4.

2.1. Terms and Concepts

Abstract Syntax Tree (AST) Parsers for programming languages usually transform plain text source code into an intermediate representation which can be processed by compilers, interpreters or programming environment tools. An AST is such a typical representation which stores structural information of the source code implicitly in its tree structure. Therefore, concrete syntactic elements needed to write parsable code in plain text can be omitted. In general, inner nodes of the AST represent programming language operations and leaf nodes store the values needed for these operations. Depending on the use case, an AST can store additional information in its nodes. For example the original source section from which a node was derived. Programming environment tools can use these information to display any kind of errors, warnings or hints directly in the plain text source code. An AST interpreter evaluates an AST by traversing its tree structure and executing the operations defined in the nodes.

Scopes and Frames A Scope defines a region of a program in which a set of name bindings is valid, e.g. a local variable name. Most programming languages have a concept of a global (program wide) scope and local scopes defined by functions, blocks or modules. During execution of a program, frames store the actual values of the name bindings of visible scopes.

2.2. Truffle and GraalVM

Truffle is a language implementation framework written in Java [8]. The language developer uses the framework to write an AST interpreter, which is able to optimize itself during interpretation [9]. To achieve that, Truffle uses runtime type information to rewrite AST nodes. Callable elements of a language, e.g. functions or methods, are modeled as root nodes. They can be executed by providing a frame object. Nodes can have an associated source section.

To get high-performance language implementations, Truffle uses the language-independent just-in-time compiler named Graal. It uses partial evaluation to compile stable AST subtrees into optimized machine code [7].

Truffle has built-in support for developing language-agnostic tools by providing an instrumentation Application Programming Interface (API) [6]. It is designed to

work well with the optimization techniques for language implementations so that instrumentation can be done with nearly zero-overhead.

- Truffle language implementation framework
  - Nodes
  - Sources + SourceSections
  - CallTargets
  - Truffle instrumentation
  - Loading languages (dynamic classpath detection)
- GraalVM - high-performance polyglot VM

2.3. Language Server Protocol

- definition
- URIs to identify a source file and Locations
- client + server
- JSON-RPC
- graphic of exemplary LSP communication
- lsp4j - Java binding for LSP
  - version
  - map to Java types
  - JSON-RPC wrap
- LSP client: VSCode example

3. Approach

- language implementation + tool development = challenging task
- we propose: implement LSP for Truffle
- typically one specific language server impl for one language
- Our approach: a language-agnostic language server impl for languages created by the language implementation framework Truffle, Figure 3

3.1. A Language-agnostic Language Server

- LSP enables arbitrary language clients to communicate with arbitrary language servers
- Normally a language server provides support for one specific language only
- To build a language-agnostic language server for Truffle we have to define what Truffle languages need to provide in general to support LSP
- LSP is trade-off - there are lang-specific IDEs with more/other features
- Therefore our solution will also be a trade-off using general language features available for all Truffle languages
- In the following we will describe which LSP features we want to support and how we get the relevant information needed in a language-agnostic way

Selected LSP features LSP features (version 3.7.0) we want to support: diagnostics, completion, hover, signatureHelp, documentSymbol, symbol, definition, references, documentHighlight, codeLens

Language server initialization




Figure 3.1.: lang-specific-server-vs-lang-agnostic-server

3. *Approach*

- At start-up, server and client exchange capabilities, defining which LSP features are supported
- The server also needs to list completion trigger characters and signature help trigger characters
- These characters are used for ...
- For a language-agnostic language server we have to collect these characters for all available languages
- No language association to trigger character possible -> normally one server only for one language
- We have to check on every call if the trigger character belongs to the current language
- To get the language we have to compare the registered MIME-types of a Truffle language with the MIME-type derived from the file extension
- After initialization we parse all files in the workspace

Parsing Sources

- a source is parsed when opened in the editor
- at start-up the files in the workspace are parsed
- collect all MIME-types of all languages
- walking file tree
- parsing every file which has a known MIME-type
- Client is notified about syntax errors via LSP Diagnostics

Diagnostics

- In our approach we use Diagnostics to notify the client about syntax errors in the source code. (Also used for highlighting code coverage, see ...)
- map syntax error to range in source file
- Truffle AST nodes have source sections
- Parsing-exceptions have a reference to erroneous node, if not -> use first char in first line
- Typically, exception is thrown on first syntax error
- => Display only first syntax error

Mapping the client caret position to AST node of a Truffle language

- Most LSP language features are context-sensitive and include line+column in the request
- Already explained: AST nodes have source sections
- The Truffle framework remembers every loaded Source and its source sections
- We use Truffle instrumentation to iterate over all loaded sections
- Precondition: Source needs to be parsable
- Two different use cases
- Find the "nearest" node: containing at end, next, previous, containing, root
- Find node at caret: containing

- Both filtered by node kind (Expression, Statement, Callable ...)

completion of globals/locals (static)

- language needs to derive a scope from an AST node
- if not parsable -> only global scope possible
- list valid symbols in the scope
- use TruffleObject interface to check object kind, documentation, signature, etc...
- for variables not many information can be display
- language-agnostic => Truffle has no type information for variables

Using runtime type information

- to display details e.g. about globals/locals, type information are needed
- easy for statically typed languages - not for dynamic
- so we need a generic approach
- idea: at runtime we can track type information (see type harvesting etc)
- run code
- challenges: side-effects, endless execution, (caret position not reached)
- side-effects -> sandboxing
- endless execution -> abort when caret position reached + TODO(timeout)
- caret position not reached -> define run-script-path to a script or test which covers the caret position
- run: observe frame at every source section, store a snapshot of the frame associated to the source section
- completion of globals/locals -> if node near caret has source section associated with coverage data -> use frame for globals/locals completion to get more details
- user interface to start code evaluation: see codeLense

completion of object properties

- define "object property completion"
- assumption: inserting a completion character => code might be not parsable
- fix code by undoing last change + parse again
- derive type information from node at caret
- run code to caret position
- optimizations: try different evaluation strategies
  - literal -> type can be derived without execution
  - coverage data (explained later)
  - run-to-section
  - globals
- getting infos from evaluation result object
- use TruffleObject interface to check object kind, documentation, signature, etc...

hover

3. *Approach*

- same preconditions as for completion (parsable code, find node at caret)
- if coverage data available: parse in-line + eval in-line
- for language developers: show debug infos (AST structure)

signatureHelp

- same preconditions as for completion (parsable code, find node at caret)
- need to know the signatureHelp trigger character
- when triggered -> assumption: code still parsable (e.g. editor has smart character insertion)
- find callable node at caret
- run to section
- listen for callable object
- ask via message to TruffleObject for signature and number of arguments

documentSymbol

- parsable code
- find all symbols in a specific source
- use Truffle Tagging -> new DefinitionTag needed to define which kind of symbol it is (class, variable, ...)
- fallback: search for RootTagged nodes

symbol

- find all symbols in workspace
- same as documentSymbol for all sources in workspace

documentHighlight

- parsable code + find node at caret
- variables only
- find other variable read/writes nodes in scope
- need to tag such nodes with ReadVariableTag+WriteVariableTag

definition

- parsable code + find node at caret
- function vs variable
- function
  - dynamic approach: run-to-section to get function object
  - ask function object for its source section of definition
  - static fallback: search for symbols in workspace
- variable
  - not all languages have a variable definition syntax -> first write is definition
  - so we interpret goto-definition for variables as goto-first-write

  - find first write in scopes

references

- parsable code + find node at caret
- function vs variable
- function
  - dynamic approach: run-to-section to get function object
  - search for function calls
- variable
- ...

Language features not implemented

- completion resolve
- typeDefinition
- implementation
- codeAction
- documentLink
- documentLink resolve
- documentColor
- colorPresentation
- formatting
- rangeFormatting
- onTypeFormatting
- rename
- foldingRange

3.2. Architecture

- graphic showing launcher, lsp server, truffle api communication
- comparison to other language server impls (built on top of language)

4. Implementation

4.1. Language Server Implementation

- lsp4j - Java binding for LSP (see Context)

4.1.1. Architecture

- Truffle-API + Graal-SDK
- Launcher, Instrument, Server
- lsp4j adapters

4.1.2. Using runtime information

Implementation of:

- Observe execution via instrumentation
- Side-effects -> Truffle-sandboxing
- Nested Contexts
- Evaluation strategies:
  - Literals
  - Coverage data
    - storing frames (copies)
    - source location format
    - migrating coverage data on source edit
  - Run-to-section
  - Globals

4.1.3. LSP features implementation overview

Feature impl matrix:

- TextDocumentService interface
  - completion
    - locals+globals vs object property completion (via checking completion character)
    - locals+globals completion
      - find nearest node

4. *Implementation*

    - check coverage data
    - globals only fallback
    - Used Truffle-API: findLocalScopes() + findGlobalScopes() + (parseInline() for coverage) + ForeignAccess.sendIsExecutable() + ForeignAccess.sendIsInstantiable() + ForeignAccess.sendIsNull()
    - Used new Truffle-API: env.boxPrimitive() + GetSignature + GetDocumentation

  * object property completion

    - fixing source code (undo last edit + re-parse)
    - find nearest node
    - tryDifferentEvalStrategies() (literals -> coverage data -> run-to-section -> globals)
    - Used Truffle-API: findLocalScopes() + findGlobalScopes()

  – hover
  – signatureHelp
  – definition
  – typeDefinition
  – implementation
  – references
  – documentHighlight
  – documentSymbol
  – codeAction
  – codeLense
  – formatting
  – rangeFormatting
  – onTypeFormatting
  – rename
  – didOpen
  – didChange
  – didClose
  – didSave
  – willSave
  – willSaveWaitUntil
  – documentLink
  – documentLinkResolve
  – documentColor
  – colorPresentation

- WorkspaceService interface

  – executeCommand
  – symbol
  – didChangeConfiguration
  – didChangeWatchedFiles

- didChangeWorkspaceFolders

4.1.4. LSP client - VSCode extension example

4.2. Requirements on Truffle Language Implementations

- Implement existing API:
  - ExpressionTag + StatementTag
  - findTopScopes()
  - findLocalScopes()
  - findMetaObject()
  - findSourceLocation()
  - parseInline()
- Implement proposed/new API:
  - getCompletionTriggerCharacters()
  - getSignatureHelpCharacters() (TODO)
  - boxPrimitive()
  - GetSignature + GetDocumentation custom message
  - DefinitionTag + ReadVariableTag + WriteVariableTag

5. Experience Report

5.1. Between IDE and Language Workbench

Language Workbench focus/aim: Efficient language (DSL) development, performance is not main focus vs. Graal/Truffle aim: Efficient execution

Assumption: Language Workbenches use static information only, our Truffle-based solution uses dynamic type information

5.2. Completion response time

5.3. Limitations

own chapter? or in 4?

- VSCode: Need to define supported languages in extension
- VSCode: Syntax highlighting defined at client-side
- LSP: No incremental sending of (completion) results
- Server: Only TCP (connecting to already running server), no std-in/-out impl
- Truffle: Only first syntax error is reported. Lang parsers fail on first error

6. Related Work

6.1. Graal

[5]

6.2. Squimera

[4] [3]

6.3. Language Workbenches

[1]

6.4. Run-time type collection

[2]

6.5. CTags

- tagging a language object in an index file
- tag-file supported by editors
- allows user to locate the tagged object via name (goto-definition, list symbols)
- for new languages you need to define a regex or parser to find language objects
- only static analysis, no scoped completion (everything is suggested)

SemanticDB

7. Conclusion and Future Work

Bibliography

[1] Sebastian Erdweg, Tijs Van Der Storm, Markus Völter, Meinte Boersma, Remi Bosman, William R Cook, Albert Gerritsen, Angelo Hulshout, Steven Kelly, Alex Loh, et al. "The State of the Art in Language Workbenches". In: *International Conference on Software Language Engineering*. Springer. Springer International Publishing, 2013, pp. 197–217. DOI: 10.1007/978-3-319-02654-1_11.

[2] Michael Haupt, Michael Perscheid, and Robert Hirschfeld. "Type harvesting: a practical approach to obtaining typing information in dynamic programming languages". In: *Proceedings of the 2011 ACM Symposium on Applied Computing*. ACM. 2011, pp. 1282–1289. DOI: 10.1145/1982185.1982464.

[3] Fabio Niephaus, Tim Felgentreff, Tobias Pape, and Robert Hirschfeld. "Squeak Makes a Good Python Debugger: Bringing Other Programming Languages Into Smalltalk's Tools". In: *Companion to the first International Conference on the Art, Science and Engineering of Programming*. ACM. 2017, p. 27. DOI: 10.1145/3079368.3079402.

[4] Fabio Niephaus, Tim Felgentreff, Tobias Pape, Robert Hirschfeld, and Marcel Taeumel. "Live Multi-language Development and Runtime Environments". In: *arXiv preprint arXiv:1803.10200* 2.3 (Mar. 2018). DOI: 10.22152/programming-journal.org/2018/2/8.

[5] Chris Seaton, Michael L Van De Vanter, and Michael Haupt. "Debugging at Full Speed". In: *Proceedings of the Workshop on Dynamic Languages and Applications*. ACM. ACM Press, 2014, pp. 1–13. DOI: 10.1145/2617548.2617550.

[6] Michael L Van De Vanter. "Building debuggers and other tools: we can have it all". In: *Proceedings of the 10th Workshop on Implementation, Compilation, Optimization of Object-Oriented Languages, Programs and Systems*. ACM. 2015, p. 2. DOI: 10.1145/2843915.2843917.

[7] Thomas Würthinger, Christian Wimmer, Christian Humer, Andreas Wöß, Lukas Stadler, Chris Seaton, Gilles Duboscq, Doug Simon, and Matthias Grimmer. "Practical Partial Evaluation for High-performance Dynamic Language Runtimes". In: *Proceedings of the 38th ACM SIGPLAN Conference on Programming Language Design and Implementation - PLDI 2017*. Vol. 52. 6. ACM. 2017, pp. 662–676. DOI: 10.1145/3062341.3062381.

[8] Thomas Würthinger, Christian Wimmer, Andreas Wöß, Lukas Stadler, Gilles Duboscq, Christian Humer, Gregor Richards, Doug Simon, and Mario Wolczko. "One VM to rule them all". In: *Proceedings of the 2013 ACM international symposium on New ideas, new paradigms, and reflections on programming & software*. ACM. 2013, pp. 187–204. DOI: 10.1145/2509578.2509581.

[9] Thomas Würthinger, Andreas Wöß, Lukas Stadler, Gilles Duboscq, Doug Simon, and Christian Wimmer. "Self-optimizing AST interpreters". In: *ACM SIGPLAN Notices*. Vol. 48. 2. ACM. 2012, pp. 73–82. DOI: 10.1145/2384577.2384587.

Appendix A.

First Unimportant stuff.

Hello, here is some text without a meaning. This text should show what a printed text will look like at this place. If you read this text, you will get no information. Really? Is there no information? Is there a difference between this text and some nonsense like “Huardest gefburn”? Kjift – not at all! A blind text like this gives you information about the selected font, how the letters are written and an impression of the look. This text should contain all letters of the alphabet and it should be written in of the original language. There is no need for special content, but the length of words should match the language.

Eigenständigkeitserklärung

Hiermit versichere ich, dass ich die vorliegende Arbeit selbständig verfasst sowie keine anderen Quellen und Hilfsmittel als die angegebenen benutzt habe.

Berlin, den 26. Dezember 2018

Daniel Stolpe

Todo list

own chapter? or in 4? 15