NAME

insilicut.bash - manual page for insilicut.bash 1.1.0

SYNOPSIS

insilicut.bash [OPTIONS] ...

DESCRIPTION

'insilicut.bash' reports fragments when cutting genomic DNA with a restriction enzyme.

OPTIONS

-h, --help

display the help and exit

- -V, --version output version information and exit
- -v, --verbose verbosity level (0/default=1/2/3)
- **--gf** path to the file containing the genomic DNA (fasta format)
- **--gn** name of the genomic DNA (e.g. 'Athaliana')
- **--ef** path to the file containing the restriction enzyme (fasta format)
- **−−en** name of the enzyme (e.g. 'ApeKI')
- **--ls** lower bound on fragments size (default=100)
- **--us** upper bound on fragments size (default=300)
- --fullh

use full fasta header (e.g. keep "chr1 Atha" instead of "chr1")

--clean

remove temporary files

--p2i absolute path to the insilicut directory (default=) used for testing purposes only (e.g. in 'make check')

EXAMPLES

insilicut.bash —gf Athaliana_genome.fa —gn Athaliana —ef ApeKI.fa —en ApeKI

Remarks:

if R is installed, a histogram of fragments size is also produced

AUTHOR

Written by Timothée Flutre [cre,aut].

REPORTING BUGS

Report bugs to <timothee.flutre@supagro.inra.fr>.

COPYRIGHT

 $Copyright © 2014-2015 \ Institut \ National \ de \ la \ Recherche \ Agronomique \ (INRA). \ License \ GPL-3+: \ GNU \ GPL \ version \ 3 \ or \ later \ <http://gnu.org/licenses/gpl.html>$

This is free software; see the source for copying conditions. There is NO warranty; not even for MER-CHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE.