

Class 11

Tim

Today before delving into structure prediction with AlphaFold we will finish off our previous lab10v”comparative structure analysis” section

```
library(bio3d)

id <- "1ake_A"

aa <- get.seq(id)
```

Warning in get.seq(id): Removing existing file: seqs.fasta

Fetching... Please wait. Done.

aa

```

      1      .      .      .      .      .      60
pdb|1AKE|A  MRIILLGAPGAGKGTQAQFIMEKYGIPQISTGDMRLAAVKSGSELGKQAKDIMDAGKLV
      1      .      .      .      .      .      60

      61      .      .      .      .      .      120
pdb|1AKE|A  DELVIALVKERIAQEDCRNGFLLDGFPR TIPQADAMKEAGINVDYVLEFDVPDELIVDRI
      61      .      .      .      .      .      120

      121      .      .      .      .      .      180
pdb|1AKE|A  VGRRVHAPSGRVYHV KFNPPKVEGKDDVTGEELTTRKDDQEETVRKRLVEYHQMTAPLIG
      121      .      .      .      .      .      180

      181      .      .      .      214
pdb|1AKE|A  YYSKEAEAGNTKYAKVDGTPVAEVRADLEKILG
      181      .      .      .      214
```

```
Call:
  read.fasta(file = outfile)
```

```
Class:
  fasta
```

```
Alignment dimensions:
  1 sequence rows; 214 position columns (214 non-gap, 0 gap)
```

```
+ attr: id, ali, call
```

```
b <- blast.pdb(aa)
```

```
Searching ... please wait (updates every 5 seconds) RID = JRZVU8AE016
...
Reporting 85 hits
```

```
attributes(b)
```

```
$names
[1] "hit.tbl" "raw"      "url"
```

```
$class
[1] "blast"
```


```
head(b$hit.tbl)
```

	queryid	subjectids	identity	alignmentlength	mismatches	gapopens	q.start		
1	Query_7229911	1AKE_A	100.000	214	0	0	1		
2	Query_7229911	8BQF_A	99.533	214	1	0	1		
3	Query_7229911	4X8M_A	99.533	214	1	0	1		
4	Query_7229911	6S36_A	99.533	214	1	0	1		
5	Query_7229911	8Q2B_A	99.533	214	1	0	1		
6	Query_7229911	8RJ9_A	99.533	214	1	0	1		
	q.end	s.start	s.end	evaluate	bitscore	positives	mlog.evaluate	pdb.id	acc
1	214	1	214	1.58e-156	432	100.00	358.7458	1AKE_A	1AKE_A
2	214	21	234	2.58e-156	433	100.00	358.2555	8BQF_A	8BQF_A
3	214	1	214	2.82e-156	432	100.00	358.1665	4X8M_A	4X8M_A
4	214	1	214	4.14e-156	432	100.00	357.7826	6S36_A	6S36_A
5	214	1	214	1.10e-155	431	99.53	356.8054	8Q2B_A	8Q2B_A
6	214	1	214	1.10e-155	431	99.53	356.8054	8RJ9_A	8RJ9_A

```
hits <- plot(b)
```

```
* Possible cutoff values: 197 11
    Yielding Nhits:      19 85
```

```
* Chosen cutoff value of: 197
    Yielding Nhits:      19
```



```
attributes(hits)
```

```
$names
[1] "hits"    "pdb.id"  "acc"     "inds"
```

```
$class
[1] "blast"
```

Top hits that we

```
hits$pdb.id
```

```
[1] "1AKE_A" "8BQF_A" "4X8M_A" "6S36_A" "8Q2B_A" "8RJ9_A" "6RZE_A" "4X8H_A"
[9] "3HPR_A" "1E4V_A" "5EJE_A" "1E4Y_A" "3X2S_A" "6HAP_A" "6HAM_A" "4K46_A"
[17] "4NP6_A" "3GMT_A" "4PZL_A"
```

```
#download releated PDB files
files <- get.pdb(hits$pdb.id, path = "pdbs", split = TRUE, gzip = TRUE)
```

```
Warning in get.pdb(hits$pdb.id, path = "pdbs", split = TRUE, gzip = TRUE):
pdbs/1AKE.pdb exists. Skipping download
```

```
Warning in get.pdb(hits$pdb.id, path = "pdbs", split = TRUE, gzip = TRUE):
pdbs/8BQF.pdb exists. Skipping download
```

```
Warning in get.pdb(hits$pdb.id, path = "pdbs", split = TRUE, gzip = TRUE):
pdbs/4X8M.pdb exists. Skipping download
```

```
Warning in get.pdb(hits$pdb.id, path = "pdbs", split = TRUE, gzip = TRUE):
pdbs/6S36.pdb exists. Skipping download
```

```
Warning in get.pdb(hits$pdb.id, path = "pdbs", split = TRUE, gzip = TRUE):
pdbs/8Q2B.pdb exists. Skipping download
```

```
Warning in get.pdb(hits$pdb.id, path = "pdbs", split = TRUE, gzip = TRUE):
pdbs/8RJ9.pdb exists. Skipping download
```

```
Warning in get.pdb(hits$pdb.id, path = "pdbs", split = TRUE, gzip = TRUE):
pdbs/6RZE.pdb exists. Skipping download
```

```
Warning in get.pdb(hits$pdb.id, path = "pdbs", split = TRUE, gzip = TRUE):
pdbs/4X8H.pdb exists. Skipping download
```

```
Warning in get.pdb(hits$pdb.id, path = "pdbs", split = TRUE, gzip = TRUE):
pdbs/3HPR.pdb exists. Skipping download
```

```
Warning in get.pdb(hits$pdb.id, path = "pdbs", split = TRUE, gzip = TRUE):
pdbs/1E4V.pdb exists. Skipping download
```

```
Warning in get.pdb(hits$pdb.id, path = "pdbs", split = TRUE, gzip = TRUE):
pdbs/5EJE.pdb exists. Skipping download
```

Warning in get.pdb(hits\$pdb.id, path = "pdbs", split = TRUE, gzip = TRUE):
pdbs/1E4Y.pdb exists. Skipping download

Warning in get.pdb(hits\$pdb.id, path = "pdbs", split = TRUE, gzip = TRUE):
pdbs/3X2S.pdb exists. Skipping download

Warning in get.pdb(hits\$pdb.id, path = "pdbs", split = TRUE, gzip = TRUE):
pdbs/6HAP.pdb exists. Skipping download

Warning in get.pdb(hits\$pdb.id, path = "pdbs", split = TRUE, gzip = TRUE):
pdbs/6HAM.pdb exists. Skipping download


Warning in get.pdb(hits\$pdb.id, path = "pdbs", split = TRUE, gzip = TRUE):
pdbs/4K46.pdb exists. Skipping download

Warning in get.pdb(hits\$pdb.id, path = "pdbs", split = TRUE, gzip = TRUE):
pdbs/4NP6.pdb exists. Skipping download

Warning in get.pdb(hits\$pdb.id, path = "pdbs", split = TRUE, gzip = TRUE):
pdbs/3GMT.pdb exists. Skipping download

Warning in get.pdb(hits\$pdb.id, path = "pdbs", split = TRUE, gzip = TRUE):
pdbs/4PZL.pdb exists. Skipping download

	0%
====	5%
=====	11%
=====	16%
=====	21%
=====	26%
=====	32%



I have now found and downloaded all the ADK structures in the PDB database but viewing them is difficult as they need to be aligned and superposed.

I am going to install BiocManager package from CRAN. Then I can use `BiocManager::install()` to install any bioconductor package.

```
BiocManager::install()
```

Bioconductor version 3.20 (BiocManager 1.30.25), R 4.4.1 (2024-06-14 ucrt)

Installation paths not writeable, unable to update packages

path: C:/Program Files/R/R-4.4.1/library

packages:

boot, foreign, MASS, Matrix, nlme, survival

```
Old packages: 'askpass', 'bio3d', 'bit', 'bit64', 'broom', 'commonmark',
'credentials', 'curl', 'data.table', 'evaluate', 'fs', 'gert', 'glue',
'gtable', 'httr2', 'jsonlite', 'pkgbuild', 'ps', 'R.oo', 'Rcpp', 'rgl',
'rmarkdown', 'rstudioapi', 'sf', 'sys', 'tinytex', 'waldo', 'withr', 'xfun'
```

```
# Align related PDBs
pdbs <- pdbaln(files, fit = TRUE, exefile="msa")
```


Reading PDB files:

```
pdbs/split_chain/1AKE_A.pdb
pdbs/split_chain/8BQF_A.pdb
pdbs/split_chain/4X8M_A.pdb
pdbs/split_chain/6S36_A.pdb
pdbs/split_chain/8Q2B_A.pdb
pdbs/split_chain/8RJ9_A.pdb
pdbs/split_chain/6RZE_A.pdb
pdbs/split_chain/4X8H_A.pdb
pdbs/split_chain/3HPR_A.pdb
pdbs/split_chain/1E4V_A.pdb
pdbs/split_chain/5EJE_A.pdb
pdbs/split_chain/1E4Y_A.pdb
pdbs/split_chain/3X2S_A.pdb
pdbs/split_chain/6HAP_A.pdb
pdbs/split_chain/6HAM_A.pdb
pdbs/split_chain/4K46_A.pdb
pdbs/split_chain/4NP6_A.pdb
pdbs/split_chain/3GMT_A.pdb
pdbs/split_chain/4PZL_A.pdb
  PDB has ALT records, taking A only, rm.alt=TRUE
.   PDB has ALT records, taking A only, rm.alt=TRUE
..  PDB has ALT records, taking A only, rm.alt=TRUE
.   PDB has ALT records, taking A only, rm.alt=TRUE
.   PDB has ALT records, taking A only, rm.alt=TRUE
.   PDB has ALT records, taking A only, rm.alt=TRUE
..  PDB has ALT records, taking A only, rm.alt=TRUE
..  PDB has ALT records, taking A only, rm.alt=TRUE
.... PDB has ALT records, taking A only, rm.alt=TRUE
.   PDB has ALT records, taking A only, rm.alt=TRUE
....
```


Extracting sequences

```
pdb/seq: 1    name: pdbs/split_chain/1AKE_A.pdb
      PDB has ALT records, taking A only, rm.alt=TRUE
pdb/seq: 2    name: pdbs/split_chain/8BQF_A.pdb
      PDB has ALT records, taking A only, rm.alt=TRUE
pdb/seq: 3    name: pdbs/split_chain/4X8M_A.pdb
pdb/seq: 4    name: pdbs/split_chain/6S36_A.pdb
      PDB has ALT records, taking A only, rm.alt=TRUE
pdb/seq: 5    name: pdbs/split_chain/8Q2B_A.pdb
      PDB has ALT records, taking A only, rm.alt=TRUE
pdb/seq: 6    name: pdbs/split_chain/8RJ9_A.pdb
      PDB has ALT records, taking A only, rm.alt=TRUE
pdb/seq: 7    name: pdbs/split_chain/6RZE_A.pdb
      PDB has ALT records, taking A only, rm.alt=TRUE
pdb/seq: 8    name: pdbs/split_chain/4X8H_A.pdb
pdb/seq: 9    name: pdbs/split_chain/3HPR_A.pdb
      PDB has ALT records, taking A only, rm.alt=TRUE
pdb/seq: 10   name: pdbs/split_chain/1E4V_A.pdb
pdb/seq: 11   name: pdbs/split_chain/5EJE_A.pdb
      PDB has ALT records, taking A only, rm.alt=TRUE
pdb/seq: 12   name: pdbs/split_chain/1E4Y_A.pdb
pdb/seq: 13   name: pdbs/split_chain/3X2S_A.pdb
pdb/seq: 14   name: pdbs/split_chain/6HAP_A.pdb
pdb/seq: 15   name: pdbs/split_chain/6HAM_A.pdb
      PDB has ALT records, taking A only, rm.alt=TRUE
pdb/seq: 16   name: pdbs/split_chain/4K46_A.pdb
      PDB has ALT records, taking A only, rm.alt=TRUE
pdb/seq: 17   name: pdbs/split_chain/4NP6_A.pdb
pdb/seq: 18   name: pdbs/split_chain/3GMT_A.pdb
pdb/seq: 19   name: pdbs/split_chain/4PZL_A.pdb
```

```
pc <- pca(pdbbs)
plot(pc)
```

```
plot(pc, pc.axes = c(1:2))
```



to examine in more details what PC1 (or any P_c) is capturing here we can plot the loading or make a wee movie (trajectory) of moving along PC1

```
mktrj(pc, pc=1, file = "pc1.pdb")
```