Four Stud **P/N 6600-404**

PowerBar

Busbars & Insulators

- All Stainless Steel Hardware With Integrated Self-Locking Features
- Includes Protective Cover With Breakaway Tabs
- Height Compatible With Other FLEX System Components



600 Amp

Four Stud **P/N 6600-404**

PowerBar

Scan For Product Information!



MEMBER ABYC

8 50074 33151 3

Quatre Poste **P/N 6600-404**

PowerBar

Busbars & Insulators

Key Specifications

Max Operational Voltage	80 Vdc
M10 Nut Recommended Torque	120 in-lbs (13.6 N-m)
M10 Nut Max Torque	140 in-lbs (15.8 N-m)
Mounting Screw Max Torque	50 in-lbs (5.5 N-m)
Max Storage/Shipping Temperatures	-50C To 140C
Base Material	Nylon 6 30% Glass Filled
Busbar Material	Tin Plated Copper
Mounting Holes	4x #10(M5) & 2x ¼"(M6)

Related Products

2x10 Screw Dual Busbar	6100-010
3 Stud - 11 Screw Dual Level Busbar	6200-225
3 Stud - 19 Screw Dual Level Busbar	6200-229
2 Stud - 10 Screw 150Amp Busbar	6150-210
2 Stud - 8 Screw 250 Amp Busbar	6251-208
2 Stud - 14 Screw 250 Amp Busbar	6251-214
4 Stud - 4 Screw 250 Amp Busbar	6251-404
6 Stud 250 Amp Busbar	6251-600

WARNING: Cancer and Reproductive Harm
www.p65warnings.ca.gov

600 Amp