

COSC2148/COSC3130 Computing Research and Project Preparation

Assignment 2

Group Members

Name	Student ID	Student Email
Krati Awasthi	s3898306	s3898306@student.rmit.edu.au
Timothy Kohlman	s4110661	s4110661@student.rmit.edu.au
Lyris Tri Lestya	s4155150	s4155150@student.rmit.edu.au
Vaidehi Patel	s3895545	s3895545@student.rmit.edu.au
Laiba Siraj	s3960652	s3960652@student.rmit.edu.au

Tutor Name: Dr. Tutor Name

Project Leader: Timothy Kohlman

Submission Date: April 13, 2026

School of Computer Science and Information Technology

RMIT University

Contents

1	Introduction	1
1.1	DELETE original question	1
1.2	aaaSection2	1
1.2.1	aaaSection2Subsection1	1
1.3	Research Questions	2
2	Literature Review	4
2.1	DELETE original question	4
2.2	aaaSection2	4
2.2.1	aaaSection2Subsection1	4
3	Research Methodologies	5
3.1	System Overview	5
3.2	Proposed Framework Architecture	5
3.2.1	Baseline Architecture: DANES/GETAE	5
3.2.2	Proposed Modifications to Baseline Architecture	6
3.2.3	Multimodal Branch Design	6
3.2.4	Experimental Design	6
3.2.5	Processing Pipeline	7
3.2.6	Evaluation Metrics	7
3.2.7	Datasets and Data Preparation	7
3.2.8	Timeline	7
4	Evaluation	8
4.1	DELETE original question	8
4.2	aaaSection2	8
4.2.1	aaaSection2Subsection1	8
5	Project Management	9
5.1	DELETE original question	9
5.2	aaaSection2	10
5.2.1	aaaSection2Subsection1	10
A	Generative AI Usage	12

List of Figures

List of Tables

A.1	Generative AI usage report — [Tool Name]	13
-----	--	----

Section 1

Introduction

1.1 DELETE original question

Introduction - 1 page (2 marks)

Briefly describe your topic and why it is important or interesting. You could start by describing the area of interest and later summarise the existing solutions and their limitations. You could also explain the specific focus of your research and why you are doing so. Feel free to include specific information, such as detailed statistics, that will back up your claims (and thus make your statements much stronger).

In summary, an introduction should:

- Introduce the topic and its significance.
- Give background and context.
- Outline your problem and research questions.

Some important questions to guide your introduction include:

- Who is interested in the topic (e.g. scientists, practitioners, policymakers, particular members of society)?
- How much is already known about the problem?
- What is missing from current body knowledge?
- What new insights will your research contribute?
- Why is this research worth doing

1.2 aaaSection2

1.2.1 aaaSection2Subsection1

aaa

1.3 Research Questions

This research aims to develop a context-aware misinformation detection framework that substitutes the text-only content branch used in established context-aware ensemble models, such as DANES [1] and GETAE [2], with a multimodal content branch that jointly captures textual and visual information. While recent work has shown that multimodal content features and social context features each independently improve fake news detection, the closest existing combinations [3, 4] use social branches that differ architecturally from the propagation-graph ensembles of the DANES/GETAE family. As a result, two questions remain unanswered, and together they form the technical core of this project.

RQ1. *How does replacing a text-only content branch with a multimodal content branch affect the performance of context-aware inauthentic social media content detection models, and to what extent?*

What it addresses. This question isolates a single architectural change: keeping the social context branch of DANES and GETAE intact while substituting the text-only content processor with a content branch that fuses textual and visual features (e.g., BERT for text and a CNN- or transformer-based visual encoder for images). The effect is measured against the original text-only baselines on the same benchmark datasets used in the DANES and GETAE papers (Twitter15 and Twitter16), as well as the multimodal Fakeddit dataset [5], using accuracy, F1-score, precision, and recall.

Significance. Misinformation on social platforms increasingly relies on manipulated images, memes, and screenshots, where the textual signal alone is insufficient or misleading [6]. Even strong context-aware ensembles inherit the blindness of their text-only content component, meaning a measurable portion of detectable misinformation may be missed not because the social signal is weak, but because the content signal is incomplete. Quantifying the gain (or absence of gain) from a multimodal substitution directly informs whether the established DANES/GETAE family of architectures is leaving accuracy on the table.

Novelty and complexity. No prior work directly performs this controlled substitution and isolates its effect on the DANES/GETAE backbone. Existing multimodal-plus-context models such as EFND [7], DPSG [8], and the framework of Dellys et al. [9] use fundamentally different social branches (engagement signals, dynamic propagation graphs, or attention-based fusion), so their results cannot be cleanly attributed to the multimodal component. Answering RQ1 requires re-implementing a non-trivial baseline, designing a compatible multimodal branch, and ensuring the comparison remains controlled — a challenging but well-defined contribution.

RQ2. *How does the relative contribution of the multimodal content branch and the social context branch affect overall detection performance?*

What it addresses. This question moves beyond headline accuracy to decompose where the model’s predictive power comes from. Through ablation studies (content-only, social-only, and full ensemble configurations) and analysis of the fusion-layer weights, the project will quantify how much each branch contributes to correct classification, and

whether the two branches are complementary or redundant on different categories of misinformation.

Significance. Knowing that a combined model performs well is not enough; researchers and practitioners need to know *which* signal is doing the work. If the social context branch dominates, then the additional engineering cost of multimodal feature extraction may not be justified for deployment. Conversely, if the multimodal branch dominates, the field should reconsider its current emphasis on increasingly complex propagation-graph architectures. The answer therefore has direct design implications for the next generation of misinformation detectors.

Novelty and complexity. Most prior multimodal-plus-context studies report only aggregate performance and do not cleanly decompose contributions across a propagation-graph social branch of the DANES/GETAE family. Approaches such as TMEF-BI ? perform reliability-aware weighting but on a different social signal (speaker behaviour rather than propagation), so their findings do not transfer directly. A principled contribution analysis on the proposed backbone is therefore both novel and methodologically demanding, requiring careful experimental design to avoid confounding the two branches.

Together, RQ1 and RQ2 form a coherent investigation: RQ1 establishes *whether* multimodal substitution improves context-aware misinformation detection, while RQ2 explains *why*, by revealing how the content and social signals interact. Answering both is necessary to make a defensible contribution to the context-aware fake news detection literature.

Section 2

Literature Review

2.1 DELETE original question

Literature Review - 2 pages (7 marks)

It is indeed essential to demonstrate that you are familiar with the most important research on your selected topic. A strong literature review convinces the reader that your research/project has a solid foundation in existing knowledge or theory. It also shows that you are not simply repeating what others have already done or said.

The aim of this section is to show exactly how your project will contribute to discussions in the field.

- Compare and contrast: what are the main theories, methods, debates, and controversies?
- Be critical: what are the strengths and weaknesses of different approaches?
- Show how your research fits in: how will you build on, challenge, or synthesise the work of others?

2.2 aaaSection2

2.2.1 aaaSection2Subsection1

aaa

Section 3

Research Methodologies

This research adopts a comparative experimental design to investigate the effectiveness of multimodal content and social context features in the detection of inauthentic social media posts.

note Dellys et al. (2025) is flagged as the closest prior work (how does this differentiate?)

3.1 System Overview

Prior research has demonstrated that combining text-based content features with social context improved detection performance in identifying inauthentic social media posts. Separate studies have shown that multimodal models can outperform text-based models.

Limited research has been conducted to investigate the combined effectiveness of multimodal content features and social context features by substituting text-based representations with multimodal representations within a context-aware framework.

The proposed system aims to address this gap by utilising existing DANES [Truică et al., 2024] and GETAE feature ensemble architectures that combine text content with social context features, and extending them to incorporate multimodal content features.

3.2 Proposed Framework Architecture

3.2.1 Baseline Architecture: DANES/GETAE

DANES (cite) and GETAE (cite) each comprise two branches: a text-based content branch that encodes textual content using word embeddings and transformer-based representations in a neural network, and a social context branch (referred to as the Propagation Branch in GETAE) that models the social network user interactions and behaviour using graph neural networks and deriving node embeddings.

Outputs from these branches are combined using an ensemble approach produce a classification embedding. These models achieve state-of-the-art performance in detecting inauthentic social media posts in Twitter15 and Twitter16 datasets, outperforming text-only models and other context-aware models that do not utilise multimodal content features.

These models represent a principled starting point for the proposed architecture modification.

3.2.2 Proposed Modifications to Baseline Architecture

The proposed architecture modification involves substituting the text-based content branch with a multimodal content branch that incorporates visual features extracted from social media posts as well as textual features. The social context branch is retained, as in the baseline architectures, allowing the contribution of the multimodal content branch to be evaluated against the baseline models.

3.2.3 Multimodal Branch Design

This research will adopt a well validated multimodal architecture from the literature that has been designed for the task of multimodal fake news detection. This approach maintains a focus on the architectural substitution question rather than the design and optimisation of a novel multimodal architecture.

The key considerations for the selection are: task alignment, dataset compatibility, ease of integration and widespread validation.

From our review of the literature, HMCAN and MPFN models have both demonstrated excellent accuracy (0.89.7% and 83.3% respectively) in multimodal fake news detection using the Multimodal Twitter dataset, outperforming other common multimodal models for fake news detection (such as EANN). HMCAN’s BERT + ResNet encoding pipeline is consistent with the text branch of DANES/GETAE and has been independently validated on the Multimodal Twitter dataset as well as Fakedit dataset, making it a suitable candidate for the multimodal content branch. MPFN utilises a more complex image pipeline which could be beneficial for detecting manipulated or artificially generated images, and is another potential candidate.

Our system will adopt HMCAN with MPFN as a fallback option as this provides a robust foundation for handling multimodal content.

3.2.4 Experimental Design

The initial stage is to replicate the published DANES/GETAE architectures and evaluate their performance on the Twitter15 and Twitter16 datasets and ensure that the results are consistent with those reported in the original papers.

This is followed by the transition to a dataset that contains multimodal content and the implementation of the proposed architecture modification to incorporate multimodal content features.

The following configurations are proposed for evaluation:

- **Stage 1 — Condition A (Implementation Baseline):** Replicate the published DANES/GETAE architectures using the Twitter 15/16 datasets to confirm the implementation reproduces performance consistent with the original papers before any modifications are introduced.
- **Stage 2 — Condition A (Dataset Baseline):** Evaluate the DANES/GETAE architectures on a multimodal dataset in text-only mode (i.e. ignoring the visual content)

to establish a baseline for the DANES/GETAE architectures on the new dataset that Stage 2 conditions will be compared with.

- **Stage 2 — Condition B (Ablation 1):** Text-only content branch with no social context branch to isolate the contribution of textual features without social context features.
- **Stage 2 — Condition C (Ablation 2):** Multimodal content branch with no social context branch to isolate the contribution of multimodal features without social context features.
- **Stage 2 — Condition D (Proposed):** Multimodal content branch with a social context branch to represent the full proposed framework for primary evaluation.

Each stage 2 condition is compared against the stage 2 condition A baseline to evaluate the attribution of performance improvements.

RQ1 is directly addressed by comparing the performance of the proposed architecture (Condition D) against the baseline architecture (Condition A) with the multimodal dataset.

A pairwise comparison of condition’s B, C and D address RQ2 by evaluating the contribution of the multimodal content branch and the social context branch to the overall performance of the model.

It is anticipated that the transition from Twitter15/16 datasets to a multimodal datasets will result in a performance difference in Stage 2 Condition A relative to Stage 1 depending on the extent to which these models generalise to a new dataset. This does not impact the evaluation of the proposed architecture change since all Stage 2 conditions are evaluated against the Stage 2 Condition A baseline. (TODO: this would require a mention under the LIMITATIONS section, we aren’t interested in researching the generalisability of these models this is rather an expected degradation)

This methodology enables direct evaluation of the research questions by isolating the impact of multimodal content through controlled substitution of the content branch and by analysing the relative contribution of content and context features through ablation experiments. The structured experimental design ensures that performance differences can be attributed to specific components of the model.

3.2.5 Processing Pipeline

3.2.6 Evaluation Metrics

3.2.7 Datasets and Data Preparation

3.2.8 Timeline

Section 4

Evaluation

4.1 DELETE original question

evaluation - 1 page (3 marks)

This section is important and should clearly show the evaluation plan of your research. This evaluation plan could be used later during your thesis to clearly demonstrate that you made research contributions in the field of study.

This section will need to address the following points:

- Benchmarking: clearly select some existing methods/algorithms you will need to compare your research work with. It is important to clearly explain these methods/algorithms as well as justify the reasons for choosing them.
- Data sets: describe at least two well-accepted data sets that you will be using to compare your research work against the selected benchmarked methods/algorithms. Again, you will need to justify the reasons for selecting such data sets.
- Metrics: to compare your research work with benchmarked methods/algorithms, you clearly need to list the metrics to be used for this purpose. This could be, for example, "execution time" if you are comparing the performance of your work with other methods/algorithms. You also need to explain why you have selected such metrics. List at least two metrics.

4.2 aaaSection2

4.2.1 aaaSection2Subsection1

aaa

Section 5

Project Management

5.1 DELETE original question

project management - 1 page (1 mark)

This section should outline how you plan to manage your research project throughout the semester.

It is essentially a Project Plan that clearly defines the scope and deliverables, including explicit exclusions.

It should present a structured schedule with milestones and a transparent critical path, while assigning responsibility to specific individuals to ensure accountability.

It must also incorporate risk management to anticipate threats and formulate appropriate responses, protecting project objectives from avoidable failure.

This section should also clearly state the methods you will use to manage the project, such as Agile sprints, Scrum ceremonies, Kanban, etc., and specify the enabling tools (e.g., MS Project, Trello, JIRA, Slack, etc.) that will operationalise these methods.

Briefly explain how these methods and the supporting tools together will facilitate scheduling, progress tracking, communication, and reporting. Specifically, you must include the following:

- High-level scope and deliverables of your research project. Clearly state exactly what you will deliver and explicitly rule out what you will not.
- Timeline with major milestones derived from the Work Breakdown Structure (WBS). This should reflect the schedule of your research project and include any critical paths. Note: you don't need to include the WBS itself.
- Clear assignment (ownership) of each task to project team member(s), not roles, for accountability and monitoring.
- Approach in risk management, identify risks and proposed mitigation and contingency plan, as well as escalation paths. List the major risks, rank them, and state what you will do before, when, and after they occur.

5.2 aaaSection2

5.2.1 aaaSection2Subsection1

aaa

Bibliography

C.-O. Truică, E.-S. Apostol, and P. Karras. Danes: Deep neural network ensemble architecture for social and textual context-aware fake news detection. *Knowledge-Based Systems*, 294: 111715, 2024. ISSN 0950-7051. doi: <https://doi.org/10.1016/j.knosys.2024.111715>. URL <https://www.sciencedirect.com/science/article/pii/S0950705124003502>.

Appendix A

Generative AI Usage

Declaration

[REPLACE THIS LINE WITH YOUR GENERATED DECLARATION FROM
<https://aiattribution.github.io/>]

Tool Report: [Tool Name, e.g. ChatGPT / RMIT Val / Copilot]

Field	Details
1. GenAI tool used	[e.g. ChatGPT 4o, RMIT Val, GitHub Copilot]
2. Purpose for this assignment	[e.g. Brainstorming research questions, drafting outline, rewriting for clarity, code generation]
3. Prompts or instructions given	[Include key prompts used. If conversation was lengthy, include all your prompts in full and use [...] to truncate AI responses only.]
4. Number of prompts given	[e.g. 7]
5. Summary of GenAI output	[Describe what the AI produced. Include brief excerpts where relevant.]
6. Verification of GenAI output	[Explain how you checked the AI’s output for factual accuracy, source validity, and logical soundness. e.g. “All cited sources were manually located and verified via Google Scholar.”]
7. Usage or modification of output	[Explain how you used, adapted, or discarded the AI-generated content in your final submission.]
8. Reflection	[What worked well? What did not? How did it support your learning? What value did it add?]

Table A.1: Generative AI usage report — [Tool Name]