



**ITMO UNIVERSITY**

NATIONAL RESEARCH UNIVERSITY ITMO

FACULTY OF SOFTWARE ENGINEERING AND COMPUTER SYSTEMS

---

**SYSTEM SOFTWARE FUNDAMENTALS**

**Lab Work #4 (3)**

System Calls

---

Timothy Labushev

Group P3302

Saint Petersburg

2019

# Assignment

## Part I

Using raw system calls, write a C program that mimics the behavior of the *head* utility.

### Requirements

1. The program should perform input and output via `read(2)` and `write(2)`.
2. The program should accept multiple input files and use standard input when `-` is given as a filename.
3. The program should handle errors and print informative messages to `stderr`.

## Part II

Rewrite the same program in Perl.

### Requirements

1. Use `use strict; use warnings qw(FATAL all);` pragmas.
2. Enable *taint mode* with `#!/usr/bin/perl -T`.

## Part III

Write a C program that mimics the behavior of the *xargs* utility without optional arguments.

## Relevant Sections from POSIX.1-2008

### Synopsis

```
head [-n number] [file...]
```

### Description

The *head* utility shall copy its input files to the standard output, ending the output for each file at a designated point.

Copying shall end at the point in each input file indicated by the **-n** *number* option. The option-argument number shall be counted in units of lines.

## Options

The following option shall be supported:

**-n** *number*

The first *number* lines of each input file shall be copied to standard output. The application shall ensure that the number option-argument is a positive decimal integer.

When a file contains less than number lines, it shall be copied to standard output in its entirety. This shall not be an error.

If no options are specified, *head* shall act as if **-n 10** had been specified.

## Stdout

The standard output shall contain designated portions of the input files.

If multiple *file* operands are specified, *head* shall precede the output for each with the header:

```
"\n==> %s <==\n", <pathname>
```

except that the first header written shall not include the initial <newline>.

## Code Listing

### head (C)

```
1  #define _POSIX_C_SOURCE 2
2  #include <unistd.h>
3  #include <stdlib.h>
4  #include <stdio.h>
5  #include <fcntl.h>
6  #include <stdbool.h>
7  #include <stdarg.h>
8  #include <errno.h>
9
10 #define BUF_SIZE 4096
11
12 void print_lines_buffered(int fd, unsigned int num_lines) {
13     unsigned int printed = 0;
14
15     char inbuf[BUF_SIZE];
16     int bytes_read;
17     while (printed < num_lines && (bytes_read = read(fd, inbuf, BUF_SIZE)) > 0) {
18         unsigned int pos;
19         for (pos = 0; pos < bytes_read; ++pos)
20             if (inbuf[pos] == '\n' && ++printed == num_lines) break;
21
22         write(STDOUT_FILENO, inbuf, pos);
23     }
24
25     write(STDOUT_FILENO, "\n", sizeof("\n"));
26 }
27
28 bool try_parse_uint(const char* str, unsigned int* val) {
29     errno = 0;
30     char* endptr;
31     *val = strtoul(str, &endptr, 10);
32     return *str != '-' && errno == 0 && endptr != str && *endptr == '\0';
```

```

33 }
34
35 // An fprintf()-like wrapper over write().
36 // Rationale: the assignment requires we only use raw syscalls to perform IO.
37 void fdprintf(int fd, const char* fmt, ...) {
38     #define MSG_BUF_SIZE 512
39     char buf[MSG_BUF_SIZE];
40     va_list args;
41     va_start(args, fmt);
42     int msg_len = vsnprintf(buf, MSG_BUF_SIZE, fmt, args);
43     va_end(args);
44     write(fd, buf, msg_len < MSG_BUF_SIZE ? msg_len : MSG_BUF_SIZE);
45 }
46
47 void handle_filename_args(int argc, char** argv, int num_lines) {
48     // According to POSIX,
49     // If multiple file operands are specified, head shall precede the output for each with the header:
50     // "\n==> %s <==\n", <pathname>
51     // except that the first header written shall not include the initial <newline>.
52     #define HEADER_STDIN "\n==> standard input <==\n"
53     #define HEADER_FILE_FMT "\n==> %s <==\n"
54
55     bool first_header = true;
56     do {
57         int header_offset = first_header ? 1 : 0;
58         first_header = false;
59
60         if (*argv[optind] == '-') {
61             write(STDOUT_FILENO, HEADER_STDIN + header_offset, sizeof(HEADER_STDIN) - header_offset);
62             print_lines_buffered(STDIN_FILENO, num_lines);
63         }
64         else {
65             errno = 0;
66             int fd = open(argv[optind], O_RDONLY);
67             if (fd == -1) {
68                 const char* error_fmt = "%s: Cannot open %s for reading\n";
69                 switch (errno) {
70                     case EACCES:
71                         error_fmt = "%s: Cannot open %s for reading (access denied)\n";
72                         break;
73                     case ENOENT:
74                         error_fmt = "%s: Cannot open %s for reading (file not found)\n";
75                         break;
76                 }
77                 fdprintf(STDERR_FILENO, error_fmt, argv[0], argv[optind]);
78             }
79             else {
80                 fdprintf(STDOUT_FILENO, HEADER_FILE_FMT + header_offset, argv[optind]);
81                 print_lines_buffered(fd, num_lines);
82                 close(fd);
83             }
84         }
85     }
86     while (++optind < argc);
87 }
88
89 int main(int argc, char** argv) {
90     unsigned int num_lines = 10;
91
92     int c;
93     while ((c = getopt(argc, argv, "n:")) != EOF) {
94         switch (c) {
95             case 'n':
96                 if (!try_parse_uint(optarg, &num_lines)) {
97                     fdprintf(STDERR_FILENO, "%s: invalid number of lines: '%s'\n", argv[0], optarg);
98                     return 1;
99                 }
100                 break;
101             case '?':

```

```

102         fprintf(STDERR_FILENO, "Usage: %s [-n num-lines] [file...]\n", argv[0]);
103         return 1;
104     }
105 }
106
107 if (optind == argc)
108     print_lines_buffered(STDIN_FILENO, num_lines);
109 else
110     handle_filename_args(argc, argv, num_lines);
111
112 return 0;
113 }

```

## head (Perl)

```

1  #!/usr/bin/perl -T
2
3  # Run
4  # cpan Getopt::Long
5  # to fetch script dependencies
6
7  use strict;
8  use warnings qw(FATAL all);
9  use Getopt::Long;
10
11 my $num_lines = 10;
12
13 GetOptions("n=i" => \$num_lines) or die("Usage: $0 [-n num-lines] [file...]\n");
14 $num_lines > 0 or die("$0: invalid number of lines: '$num_lines'\n");
15
16 my $printed = 0;
17 my $first_file = 1;
18
19 while (1) {
20     if ($printed == 0) {
21         if (not @ARGV and $first_file) {
22             # No arguments = don't print the header, read from stdin
23             undef $first_file;
24         }
25         elsif (@ARGV) {
26             my $leading_newline = $first_file ? "" : "\n";
27             my $filename = $ARGV[0] eq "-" ? "standard input" : $ARGV[0];
28             print "$leading_newline==> $filename <==\n";
29             undef $first_file;
30         }
31         else {
32             last;
33         }
34     }
35     if ($printed++ < $num_lines) {
36         my $line = <>;
37         print $line;
38     }
39     if ($printed == $num_lines or eof) {
40         $printed = 0;
41         close ARGV;
42     }
43 }

```

## xargs (C)

```

1  #define _POSIX_C_SOURCE 2
2  #include <unistd.h>
3  #include <stdlib.h>
4  #include <string.h>
5

```

```

6  #define BUF_SIZE 4096
7  #define MAX_ARG_SIZE 1024 * 1024
8
9  void read_arg_string(char* arg_buf) {
10     unsigned int args_pos = strlen(arg_buf);
11
12     char inbuf[BUF_SIZE];
13     int bytes_read;
14     while (args_pos < MAX_ARG_SIZE - 1 &&
15           (bytes_read = read(STDIN_FILENO, inbuf, BUF_SIZE)) > 0)
16         for (unsigned int pos = 0;
17             pos < bytes_read && args_pos < MAX_ARG_SIZE - 1;
18             ++pos)
19             arg_buf[args_pos++] = inbuf[pos] == '\n' ? ' ' : inbuf[pos];
20 }
21
22 int main(int argc, char** argv) {
23     char* arg_string = calloc(1, MAX_ARG_SIZE);
24
25     if (argc == 1) {
26         strcat(arg_string, "echo ");
27     }
28     else {
29         for (int i = 1; i < argc; ++i) {
30             strcat(arg_string, argv[i]);
31             strcat(arg_string, " ");
32         }
33     }
34
35     read_arg_string(arg_string);
36     return system(arg_string);
37 }

```