

july.jl

```

1  module July
2      help = """
3          JULY : fun stuff
4          (c)2022 Tim Menzies, timm@ieee.org, BSD-2
5
6          USAGE: julia july.jl [OPTIONS]
7
8          OPTIONS:
9              -h --help  show help      = false
10             -p --p     distance coeffecient = 2
11             -s --seed  random number seed  = 10019
12             """
13     using Random, Parameters
14     includes(dir,files) = map(f->include("../src/$dir/$f.jl"),files)
15     includes("lib", ["2thing", "settings", "2string", "lists"])
16     includes("col", ["col", "sample"])
17     the = cli(settings(help))
18 end

```

col/col.jl

```

19 "Add stuff to `i`. Ignore unknown values. Increment `n`, call `inc!`."
20 function inc!(i,a::Array) for x in a inc!(i,x,1) end; a end
21 function inc!(i,x, n=1)
22     if x != the[:unknown] i.n = i.n + n
23     inc!(i,x,n) end end

```

col/sample.jl

```

24 "Keep, at most `the[:max]` items."
25 @with_kw mutable struct Sample
26     _has=[] # where we keep, at most, the[:sample] items
27     ok=false end # true if we have sorted _has since its last chandge
28
29 "Add something to `_has`. If full, replace anything at random."
30 function inc!(i::Sample,x,n) # <== tedious detail, ignore n (used only in Sym)
31     a = i._has
32     n = length(a)
33     if ( n < the[:max] ) begin i.ok=false; push!(a,x) end
34     elseif ( rand() < n/i.n ) begin i.ok=false; a[Int(n*rand()+1)]=x end end end
35
36 " `mid` = median. `div` = standard deviation. `per` returns the n-th item."
37 mid(i::Sample, a=nums(i)) = per(a,.5)
38 div(i::Sample, a=nums(i)) = (per(a,.9) - per(a,.1)) / 2,58
39 nums(i::Sample) = begin ( !i.ok || sort!(i._has) ); i.ok=true ; i._has end

```

lib/2string.jl

```

40 "print a struct"
41 function say(i)
42     s,pre="$${typeof(i)}{",""
43     for f in sort!([x for x in fieldnames(typeof(i)) if !("$x"[1] == '_')])
44         s,pre = s * pre * ":\$f \$getfield(i,f)" , " " end
45     print(s * "}") end

```

lib/2thing.jl

```

47 "Coerce string to thing."
48 function coerce(s)
49     for t in [Int64,Float64,Bool] if (x=tryparse(t,s)) != nothing return x end end
50     return strip(s) end
51
52 "Coerce rows to cells. Pass each row to `fun`."
53 function csv(src, fun)
54     for line in eachline(file)
55         line = strip(line)
56         if sizeof(line) > 0 fun(map(coerce, split(line, ","))) end end end

```

lib/lists.jl

```

58 "Return the n-th item of `a`. e.g. `per(a,.5)` returns median."
59 per(a, n) = begin l=length(a); a[max(1,min(1,l + trunc(Int,n*1)))] end

```

lib/settings.jl

```

60 "For e.g. slot x=1, update if cli has `-x 10`. For bool, cli flags flip default."
61 function cli(d::Dict)
62     for (slot, v) in d
63         for (i, v) in pairs(ARGS)
64             if v == "-" * "$slot"[1]
65                 d[slot] = coerce(x==true ? "false" : (
66                     x==false ? "true" : (
67                         ARGS[i+1]))) end end end; d end
68
69 "Return dictionary of settings, extracted from help string."
70 function settings(s) # -> dictionary of settings
71     d=Dict()
72     # for example: -h --help show help = false
73     for m in eachmatch(r"\n\s+[-~]+\s+[\S+][^=]\s+(\S+)",s)
74         d[Symbol(m[1])] = coerce(m[2] ) end; d end

```