

Aug 27, 22 19:09

csv.lua

Page 1/5

```

1 local b4={}; for k,v in pairs(_ENV) do b4[k]=v end -- LUA trivia. Ignore.
2 local help={
3   CSV : summarized csv file
4   (c) 2022 Tim Menzies <tim@ieee.org> BSD-2 license
5
6   USAGE: lua seen.lua [OPTIONS]
7
8   OPTIONS:
9   -e --eg          start-up example      = nothing
10  -d --dump         on test failure, exit with stack dump = false
11  -f --file         file with csv data    = ../data/auto93.csv
12  -h --help         show help             = false
13  -n --nums         number of nums to keep = 512
14  -s --seed         random number seed   = 10019
15  -S --separator    field separator       = ,
16
17  -- Function argument conventions:
18  -- 1. two blanks denote options, four blanks denote locals:
19  -- 2. prefix n,s,i,s,fun denotes number,string,bool,function;
20  -- 3. suffix s means list of thing (so names is list of strings)
21  -- 4. c is a column index (usually)
22
23  -- ## Misc routines
24  -- ## Handle Settings
25  local the,coerce,cli
26  -- Parse 'the' config settings from 'help'.
27  function coerce(s, fun)
28  function fun(s)
29    if s=="true" then return true end
30    if s=="false" then return false end
31    return s end
32  return math.tointeger(s) or tonumber(s) or fun(s:match"%s*(-)%s*$") end
33
34  -- Create a 'the' variables
35  the={}
36  help:gsub("n[-]%%S+{%%s+}[-]%%S+{%%s+}%%n+= ({%%s+})",
37    function(k,x) the[k]=coerce(x) end)
38
39  -- Update settings from values on command-line flags. Booleans need no values
40  -- (we just flip the defaults).
41  function cli(t)
42    for slot,v in pairs(t) do
43      v = tostring(v)
44      for n,x in ipairs(arg) do
45        if x=="-." (slot:sub(1,1)) or x=="-."..slot then
46          v = v=="false" and "true" or v=="true" and "false" or arg[n+1] end end
47        t[slot] = coerce(v) end
48      if t.help then os.exit(print("n"..help.."")) end
49      return t end
50
51  -- ## Linting code
52  -- ## Lists
53  local copy,per,push,csv
54  -- deepcopy
55  function copy(t, u)
56    if type(t) == "table" then return t end
57    u={}; for k,v in pairs(t) do u[k]=copy(v) end
58    return setmetatable(u, getmetatable(t)) end
59
60  -- Return the 'p'-th thing from the sorted list 't'.
61  function per(t,p)
62    p=math.floor(((p or .5)*#t)+.5); return t[math.max(1,math.min(#t,p))] end
63
64  -- Add to 't', return 'x'.
65  function push(t,x) t[#t+1]=x; return x end
66
67  -- ## Call 'fun' on each row. Row cells are divided in 'the.separator'.
68  function csv(fname,fun, sep,src,s,t)
69    sep = "([".. the.separator .. "])"
70    src = io.input(fname)
71    while true do
72      s = io.read()
73      if not s then return io.close(src) else
74        t={}
75        for sl in s:gmatch(sep) do t[#t+1] = coerce(sl) end
76        fun(t) end end end
77
78  -- ## Strings
79  local o,oo
80  -- 'o' is a telescope and 'oo' are some binoculars we use to exam stucts.
81  -- 'o': generates a string from a nested table.
82  function o(t, show,u)
83    if type(t) == "table" then return tostring(t) end
84    function show(k,v)
85      if not tostring(k):find"^_" then
86        v = o(v)
87        return #t==0 and string.format("%s%s",k,v) or tostring(v) end end
88    u={}; for k,v in pairs(t) do u[#u+1]=show(k,v) end
89    if #t==0 then table.sort(u) end
90    return "{"..table.concat(u, ",").."}" end
91
92  -- 'oo': prints the string from 'o'.
93  function oo(t) print(o(t)) return t end
94
95  -- ## Misc
96  local roques, rnd, obj
97  -- Find rogue locals.
98  function roques()
99    for k,v in pairs(_ENV) do if not b4[k] then print("?",k,type(v)) end end end
100
101  -- ## Maths
102  function rnd(x, places)
103    local mult = 10^places or 2
104    return math.floor(x * mult + 0.5) / mult end
105
106  -- obj("Thing") enables a constructor Thing:new() ... and a pretty-printer
107  -- for Things.
108  function obj(s, t,i,new)
109    function new(k,...) i=setmetatable({},k);
110      return setmetatable(t.new(i,...) or i,k) end
111    t.__tostring = function(x) return s..o(x) end
112    t.__index = t;return setmetatable(t,{__call=new}) end

```

Aug 27, 22 19:09

csv.lua

Page 2/5

```

113 -----
114 -- ## Objects
115 local Cols,Data,Num,Row,Sym=obj"Cols",obj"Data",obj"Num",obj"Rows",obj"Sym"
116
117 -- 'Sym's summarize a stream of symbols.
118 function Sym:new(c,s)
119   return {n=0, -- items seen
120     at=c or 0, -- column position
121     name=s or "", -- column name
122     _has={}} -- kept data
123   } end
124
125 -- 'Num' ummarizes a stream of numbers.
126 function Num:new(c,s)
127   return {n=0,at=c or 0, name=s or "", _has={}, -- as per Sym
128     lo=math.huge, -- lowest seen
129     hi=math.huge, -- highest seen
130     isSorted=true, -- no updates since last sort of data
131     w = ((s or ""):find"$" and -1 or 1)
132   } end
133
134 -- 'Columns' Holds of summaries of columns.
135 -- Columns are created once, then may appear in multiple slots.
136 function Cols:new(names)
137   self.names=names -- all column names
138   self.all={} -- all the columns (including the skipped ones)
139   self.klass=nil -- the single dependent klass column (if it exists)
140   self.x={} -- independent columns (that are not skipped)
141   self.y={} -- dependent columns (that are not skipped)
142   for c,s in pairs(names) do
143     local col = push(self.all, -- Numerics start with Uppercase.
144       (s:find"^[A-Z]" and Num or Sym)(c,s))
145     if not s:find"$" then -- some columns are skipped
146       push(s:find"[+]" and self.y or self.x, col) -- some cols are goal cols
147     if s:find"$" then self.klass=col end end end end
148
149 -- 'Row' holds one record
150 function Row:new(t) return {cells=t, -- one record
151   cooked=copy(t), -- used if we discretize data
152   isEval=false -- true if y-values evaluated.
153 } end
154
155 -- 'Data' is a holder of 'rows' and their summaries (in 'cols').
156 function Data:new(src)
157   self.cols = nil -- summaries of data
158   self.rows = {} -- kept data
159   if type(src) == "string"
160   then csv(src, function(row) self:add(row) end)
161   else for _,row in pairs(src or {}) do self:add(row) end end end

```

Aug 27, 22 19:09

csv.lua

Page 3/5

```

162 -----
163 -- ## Sym
164 -- Add one thing to 'col'. For Num, keep at most 'nums' items.
165 function Sym:add(v)
166   if v=="?" then self.n=self.n+1; self._has[v] = 1 + (self._has[v] or 0) end end
167
168 function Sym:mid(col, most,mode)
169   most = -1; for k,v in pairs(self._has) do if v>most then mode,most=k,v end end
170   return mode end
171
172 function Sym:div(e,fun)
173   function fun(p) return p*math.log(p,2) end
174   e=0; for _,n in pairs(self._has) do if n>0 then e=e - fun(n/self.n) end end
175   return e end
176
177 -----
178 -- ## Num
179 -- Return kept numbers, sorted.
180 function Num:nums()
181   if not self.isSorted then table.sort(self._has); self.isSorted=true end
182   return self._has end
183
184 -- Reservoir sampler. Keep at most 'the.nums' numbers
185 -- (and if we run out of room, delete something old, at random).
186 function Num:add(v, pos)
187   if v=="?" then
188     self.n = self.n + 1
189     self.lo = math.min(v, self.lo)
190     self.hi = math.max(v, self.hi)
191     if #self._has < the.nums then pos = 1 + (#self._has)
192     elseif math.random() < the.nums/self.n then pos = math.random(#self._has) end
193     if pos then self.isSorted = false
194       self._has[pos] = tonumber(v) end end end
195
196 -- Diversity (standard deviation for Nums, entropy for Syms)
197 function Num:div(a a=self:nums(); return (per(a,.9)-per(a,.1))/2.58 end
198
199 -- Central tendency (median for Nums, mode for Syms)
200 function Num:mid() return per(self:nums(),.5) end

```

Aug 27, 22 19:09

csv.lua

Page 4/5

```

200 -----
201 -- ## Data
202 -- Add a 'row' to 'data'. Calls 'add()' to update the 'cols' with new values.
203 function Data:add(xs, row)
204 if not self.cols
205 then self.cols = Cols(xs)
206 else row = push(self.rows, xs.cells and xs or Row(xs)) -- ensure xs is a Row
207 for _,col in pairs(self.cols.x, self.cols.y) do
208   col:add(row.cells[col.at]) end end end end
209
210 -- For 'showCols' (default='data.cols.x') in 'data', report 'fun' (default='mid'),
211 -- rounding numbers to 'places' (default=2)
212 function Data:stats( places, showCols, fun, t, v)
213 showCols, fun = showCols or self.cols.y, fun or "mid"
214 t = {}; for _,col in pairs(showCols) do
215   v = type(v) == "number" and rnd(v, places) or v
216   t[col.name] = v end; return t end
217
218
219

```

Aug 27, 22 19:09

csv.lua

Page 5/5

```

220 -----
221 -- ## Test Engine
222 local eg, fails = {}, 0
223
224 -- 1. reset random number seed before running something.
225 -- 2. Cache the defaults settings, and...
226 -- 3. ... restore them after the test
227 -- 4. Print error messages or stack dumps as required.
228 -- 5. Return true if this all went well.
229 local function runs(k, old, status, out, msg)
230 if not eg[k] then return end
231 math.randomseed(the.seed) -- reset seed [1]
232 old = {} for k,v in pairs(the) do old[k] = v end -- [2]
233 if the.dump then -- [4]
234   status, out = true, eg[k]()
235 else
236   status, out = pcall(eg[k]) -- pcall means we do not crash and dump on error
237 end
238 for k,v in pairs(old) do the[k] = v end -- restore old settings [3]
239 msg = status and (out == true and "PASS") or "FAIL" or "CRASH" -- [4]
240 print("!!!!!!", msg, k, status)
241 return out or err end
242
243 -----
244 -- ## Tests
245 -- Test that the test happens when something crashes?
246 function eg.BAD() print(eg.dont.have.this.field) end
247
248 -- Sort all test names.
249 function eg.LIST(t)
250   t = {}; for k,_ in pairs(eg) do t[#t+1] = k end; table.sort(t); return t end
251
252 -- List test names.
253 function eg.LS()
254   print("UnExamples lua csv -e...")
255   for _,k in pairs(eg.LIST()) do print(string.format("%15s", k)) end
256   return true end
257
258 -- Run all tests
259 function eg.ALL()
260   for _,k in pairs(eg.LIST()) do
261     if k ~= "ALL" then
262       print("-----")
263       if not runs(k) then fails = fails + 1 end end end
264   return true end
265
266 -- Settings come from big string top of "sam.lua"
267 -- (maybe updated from command line)
268 function eg.the() oo(the); return true end
269
270 -- The middle and diversity of a set of symbols is called "mode"
271 -- and "entropy" (and the latter is zero when all the symbols
272 -- are the same).
273 function eg.sym( sym, entropy, mode)
274   sym = Sym()
275   for _,x in pairs{"a","a","a","a","b","b","c"} do sym:add(x) end
276   mode, entropy = sym:mid(), sym:div()
277   entropy = (1000*entropy)/1/1000
278   oo((mid=mode, div=entropy))
279   return mode=="a" and 1.37 <= entropy and entropy <= 1.38 end
280
281 -- The middle and diversity of a set of numbers is called "median"
282 -- and "standard deviation" (and the latter is zero when all the nums
283 -- are the same).
284 function eg.num( num, mid, div)
285   num = Num()
286   for i=1,100 do num:add(i) end
287   mid, div = num:mid(), num:div()
288   print(mid, div)
289   return 50 <= mid and mid <= 52 and 30.5 < div and div < 32 end
290
291 -- Nums store only a sample of the numbers added to it (and that storage
292 -- is done such that the kept numbers span the range of inputs).
293 function eg.bignum( num)
294   num = Num()
295   the.nums = 32
296   for i=1,1000 do num:add(i) end
297   oo(num:nums())
298   return 32 == #num._has; end
299
300 -- Show we can read csv files.
301 function eg.csv( n)
302   n = 0
303   csv("../data/auto93.csv", function(row)
304     n = n + 1; if n > 10 then return else oo(row) end end); return true end
305
306 -- Can I load a csv file into a Data?
307 function eg.data( d)
308   d = Data("../data/auto93.csv")
309   for _,col in pairs(d.cols.y) do oo(col) end
310   return true
311 end
312
313 -- Print some stats on columns.
314 function eg.stats( data, mid, div)
315   data = Data("../data/auto93.csv")
316   div = function(col) return col:div() end
317   mid = function(col) return col:mid() end
318   print("xmid", o( data:stats(2, data.cols.x, mid)))
319   print("xdiv", o( data:stats(3, data.cols.x, div)))
320   print("ymid", o( data:stats(2, data.cols.y, mid)))
321   print("ydiv", o( data:stats(3, data.cols.y, div)))
322   return true
323 end
324
325 -----
326 the = cli(the)
327 runs(the.eg)
328 rogues()
329 os.exit(fails)

```