```lisp
(defun cli (key flag help b4)
  "if the command line has `flag`, update `b4`."
  (let* ((args #+clisp ext:*args* #+sbcl (cdr sb-ext:*posix-argv*))
         (it   (member flag args :test #'equal)))
    (list key flag help (if (not it)
                            b4
                            (if (eq b4 t) nil (if (eq b4 nil) t (elt it 1)))))))

(defparameter *options* (list '(about "
asdasdasds

(c) 2022

line 1 3wwesas
line 33323 3242323

OPTIONS:")
  (cli 'cautious  "-c"  "abort on any error      "  t)
  (cli 'enough    "-e"  "enough items for a sample "  512)
  (cli 'far       "-F"  "far away              "  .9)
  (cli 'file      "-f"  "read data from file     "  "../data/auto93.lisp")
  (cli 'help      "-h"  "show help             "  nil)
  (cli 'license   "-l"  "show license          "  nil)
  (cli 'p         "-p"  "euclidean coefficient   "  2)
  (cli 'seed      "-s"  "random number seed      "  10019)
  (cli 'todo      "-t"  "start up action        "  "")))

---      ._ _    _.   _  ._   _    _
---      | | |  (_|  (_  |   (_)  _>

(defmacro !! (x)
  "short hand for querying options"
  `(third (cdr (assoc ',x *options* :test #'equal))))

(defun show-options (o)
  "print options"
  (format t "~&~a~%" (second (car o)))
  (dolist (x (cdr o)) (format t "~& ~a ~a = ~a" (elt x 1) (elt x 2) (elt x 3))))

(defmacro ? (s x &rest xs)
 "shorthand for recurisve calls to slot-valyes"
  (if xs `(? (slot-value ,s ',x) ,@xs) `(slot-value ,s ',x)))

(defmacro has (x a)
  "ensure `a` has a cells `(x . number)` (where number defaults to 0)"
  `(cdr (or (assoc ,x ,a :test #'equal)
            (car (setf ,a (cons (cons ,x 0) ,a))))))

(defmacro with-csv ((lst file &optional out) &body body)
  "file reading iterator"
  `(progn (%with-csv ,file (lambda (,lst) ,@body)) ,out))

---       _         ._    ._     _    ._  _|_
---      _>  |_|   |_)   |_)   (_)   |    |_
---                |     |

(defun ako (x kind)
  "check for certain `kind`s or suffixes or prefixes"
  (let ((l1 '((ignore #\:) (klass #\!) (less #\-) (more #\+) (goal #\+ #\- #\!))
)
        (l2 '(num #\$))
        (s  (symbol-name x)))
    (or (member (char s (1- (length s))) (cdr (assoc kind l1)))
        (member (char s 0)                (cdr (assoc kind l2))))))
---                                 _
---       _  _|_  ._   o   ._   _    )    _|_  |_   o  ._   _
---      _>   |_  |    |   | |  (_|  /_     |_  | |  |  | |  (_|
---                              _|                           _|

(defun thing (x)
  "return a number (if appropriate) or a string"
  (unless (equal x "?") (let ((y (ignore-errors (read-from-string x))))
                          (if (numberp y) y x))))

(defun cells (s &optional (x 0) (y (position #\, s :start (1+ x))))
  "return string `s` divided on comma"
  (cons (string-trim '(#\Space #\Tab) (subseq s x y))
        (and y (cells s (1+ y)))))

(defun %with-csv (file)
  (with-open-file (str file)
    (loop (cells  (or (read-line str nil) (return-from %csv))))))

---      ._   _.  ._    _|   _   ._ _
---      |   (_|  | |  (_|  (_)  | | |

(defvar *seed* (!! seed))
(labels ((park-miller (&aux (multipler 16807.0d0) (modulus 2147483647.0d0))
                      (setf seed (mod (* multiplier seed) modulus))
                      (/ seed modulus)))
  (defun randf (&optional (n 1)) (* n (- 1.0d0 (park-miller))))
  (defun randi (&optional (n 1)) (floor (* n (park-miller)))))

---      |  o   _  _|_      _.         _   ._
---      |  |  _>   |_     (_|  |_|  (/_  |   \/
---                           |               /

(defun per (seq &optional (p .5) &aux (v (coerce seq 'vector)))
  (elt v (floor (* p (length v)))))

(defun sd (seq &optional (key #'identity))
  (/ (- (funcall key (per seq .9)) (funcall key (per seq .1))) 2.56))

(defun ent (alist &aux (n 0) (e 0))
  (dolist (two alist)   (incf n (second two)))
  (dolist (two alist e) (let ((p (/ (second two) n))) (decf e (* p (log p 2)))))
)

(defun csv (file &aux out it)
  (with-open-file (str file)
    (loop (if (setf it (read str nil))
              (push it out)
              (return-from csv (reverse out))))))
---       _  _|_  ._        _  _|_   _
---      _>   |_  |   |_|  (_   |_  _>

(defstruct (egs  (:constructor %make-egs )) rows cols)
(defstruct (cols (:constructor %make-cols)) all x y klass)
(defstruct (sym  (:constructor %make-sym )) (n 0) at name all mode (most 0))
(defstruct (num  (:constructor %make-num )) (n 0) at name
  (all (make-array 5 :fill-pointer 0))
  (size (!! enough))
  ok w (hi -1E32) (lo 1E32))

(defun make-num (&optional (at 0) (name ""))
  (%make-sym :at at :name name :w (if (ako name 'less) -1 1)))

(defun make-sym (&optional (at 0) (name ""))
  (%make-num :at at :name name))

(defun make-cols (names)
  (let ((at -1) all x y klass)
    (dolist (name names (%make-cols :all (reverse all) :x x :y y :klass klass))
      (let* ((what (if (ako name 'num)  #'make-name #'make-sym))
             (now  (funcall what (incf at) name)))
        (push now all)
        (when (not (ako name 'ignore))
          (if (ako name 'goal) (push x now) (push y now))
          (if (ako name 'klass) (setf klass now)))))))

(defun make-egs (&optional from)
  (let ((self (%make-egs)))
    (cond ((stringp from)
           (dolist (row (csv (!! files))) (add self row)))
          ((consp from)
           (dolist (row from) (add self row))))
    self))

(defmethod add ((self egs) row)
  (with-slots (cols rows) self
    (if cols
      (push (mapcar #'add cols row) rows)
      (setf cols (make-cols row))))
  row)

(defmethod add ((self sym) x)
  (with-slots (n all mode most) self
    (unless (eq x #\?)
      (incf n)
      (let ((now (incf (has x all))))
        (if (> now most)
          (setf most now
                mode x)))))
  x)

(defmethod add ((self num) x)
  (with-slots (n lo hi all size) self
    (unless (eq x #\?)
      (incf n)
      (setf lo (min x lo)
            hi (max x hi))
      (cond ((< (length all) size)  (vector-push x all) (setf ok nil))
            ((< (randf) (/ size n)) (setf (elt (randi (length all))) x)
                                          ok nil)))))
  x)

---       _          _  _|_   _   ._ _
---      _>  \/  _>   |_  (/_  | | |
---          /

(defun make () (load 'bnb))
```