

```

5: #!/usr/bin/env python3.9
6: # vim: ts=2 sw=2 sts=2 et :
7: """
8: ,_|\ Contrast set learner( c) Tim Menzies, 2021, unlicense.org
9: / \ The delta between things is
10: \_/_* simpler than the things.
11: v
12: """
13: import re, sys, math, copy, argparse, random, itertools
14:
15: def config(): return dict(
16:     BINS = (float, .5, 'bins are of size n**BINS'),
17:     COLS = (str, 'x', 'columns to use for inference'),
18:     DATA = (str, './data/auto2.csv', 'where to read data'),
19:     FAR = (float, .9, 'where to look for far things'),
20:     GOAL = (str, 'best', 'learning goals: best|rest|other'),
21:     IOTA = (float, .3, 'small = sd**iota'),
22:     K = (int, 2, 'bayes low class frequency hack'),
23:     M = (int, 1, 'bayes low range frequency hack'),
24:     P = (int, 2, 'distance calculation exponent'),
25:     SAMPLES = (int, 20, 'samples to find far things?'),
26:     SEED = (int, 10013, 'seed for random numbers'),
27:     VERBOSE = (bool, False, 'set verbose'),
28:     TOP = (int, 20, 'focus on this many'),
29:     WILD = (int, False, 'run example, no protection'),
30:     XAMPLE = (str, "", 'egs: "-x ls" lists all, "-x all" runs all'))
31:
32: class o(object):
33:     def __init__(i, **k): i.__dict__.update(**k)
34:     def __setitem__(i, k, v): i.__dict__[k] = v
35:     def __getitem__(i, k): return i.__dict__[k]
36:     def __repr__(i): return i.__class__.__name__ + str(
37:         {k:v for k, v in i.__dict__.items() if k[0] != "_"})
38:
39: # Columns
40: class Col(o):
41:     "Store columns in 'Col', 'Skip', 'Sym', 'Num'."
42:     def __init__(i, at=0, txt="", inits=[]):
43:         i.n, i.at, i.txt = 0, at, txt
44:         i.w = -1 if "-" in txt else 1
45:         [i.add(x) for x in inits]
46:
47:     def add(i, x, n=1):
48:         if x != "?": i.n += n; x = i.add1(x, n)
49:         return x
50:
51: #
52: class Skip(Col):
53:     def add1(i, x, n=1): return x
54:
55: #
56: class Sym(Col):
57:     def __init__(i, **kw):
58:         i.has, i.mode, i.most = {}, None, 0
59:         super().__init__(**kw)
60:
61:     def add1(i, x, n=1):
62:         new = inc(i.has, x, n)
63:         if new > i.most: i.most, i.mode = new, x
64:         return x
65:
66:     def bins(i, j, _):
67:         for k in (i.has | j.has):
68:             yield i.at, (k, k)
69:
70:     def dist(i, x, y): return 0 if x == y else 1
71:
72:     def ent(i):

```

```

73:         return sum(-v/i.n * math.log(v/i.n) for v in i.has.values())
74:
75:     def merge(i, j):
76:         k = Sym(at=i.at, txt=i.txt)
77:         [k.add(x, n) for has in (i.has, j.has) for x, n in has.items()]
78:         return k
79:
80:     def merged(i, j):
81:         k = i.merge(j)
82:         e1, n1, e2, n2, e, n = i.ent(), i.n, j.ent(), j.n, k.ent(), k.n
83:         tmp = n1/n * e1 + n2/n * e2
84:         #print(e1, e2, e, tmp)
85:         if e1 + e2 < 0.01 or e * .95 < tmp:
86:             return k
87:
88:     def mid(i): return i.mode
89:
90: #
91: class Num(Col):
92:     def __init__(i, **kw):
93:         i._all, i.ok = [], False
94:         super().__init__(**kw)
95:
96:     def add1(i, x, n):
97:         x, i.ok = float(x), False
98:         for _ in range(n): i._all += [x]
99:         return x
100:
101:     def all(i):
102:         if not i.ok: i.ok = True; i._all = sorted(i._all)
103:         return i._all
104:
105:     def bins(i, j, the):
106:         xy = [(z, True) for z in i._all] + [(z, False) for z in j._all]
107:         iota = the.IOTA * (i.n * i.sd() + j.n * j.sd()) / (i.n + j.n)
108:         for (lo, hi), _ in bins(xy, iota=iota, size=len(xy) * the.BINS):
109:             yield i.at, (lo, hi)
110:
111:     def dist(i, x, y):
112:         if x == "?": y = i.norm(y); x = 1 if y < 0.5 else 0
113:         elif y == "?": x = i.norm(x); y = 1 if x < 0.5 else 0
114:         else: x, y = i.norm(x), y.norm(y)
115:         return abs(x-y)
116:
117:     def mid(i): return per(i.all(), p=.5)
118:
119:     def norm(i, x):
120:         if x == "?": return x
121:         a = i.all()
122:         return max(0, min(1, (x-first(a))/(last(a)-first(a)+1E-32)))
123:
124:     def sd(i): return (per(i.all(), .9) - per(i.all(), .1))/2.56
125:
126:     def span(i): return (first(i.all()), last(i.all()))
127:
128:     def wide(i, n=0): return last(i.all()) - first(i.all()) >= n
129:
130: # Row and Rows
131: class Row(o):
132:     def __init__(i, lst, rows=None): i.rows, i.cells = rows, lst
133:
134:     def __lt__(i, j):
135:         goals = i.rows.cols.y
136:         s1, s2, n = 0, 0, len(goals)
137:         for col in goals:
138:             a = col.norm(i.cells[col.at])
139:             b = col.norm(j.cells[col.at])
140:             s1 -= math.e**(col.w * (a - b) / n)
141:             s2 -= math.e**(col.w * (b - a) / n)

```

```

142:         return s1 / n < s2 / n
143:
144:     def dist(i, j, the):
145:         d = n = 1E-32
146:         for col in i.rows.cols[the.COLS]:
147:             n += 1
148:             x, y = i.cells[at], j.cells[at]
149:             d += 1 if x == "?" and y == "?" else col.dist(x, y) ** the.P
150:         return (d/n) ** (1/the.P)
151:
152:     def far(i, rows, the):
153:         tmp = [(dist(i, j), j) for _ in range(the.SAMPLE)]
154:         return per(sorted(tmp, key=first), the.FAR)
155:
156:     def ys(i): return [i.cells[col.at] for col in i.rows.cols.y]
157:
158: #
159: class Rows(o):
160:     def __init__(i, inits=[]):
161:         i.rows = []
162:         i.cols = o(all=[], names=[], x=[], y=[], klass=None)
163:         [i.add(x) for x in inits]
164:
165:     def add(i, a): i.data(a) if i.cols.names else i.header(a)
166:
167:     def best(i, the):
168:         i.rows.sort()
169:         ds = [the.IOTA * y.sd() for y in i.cols.y]
170:         best, rest = i.clone(), i.clone()
171:         for n, row in enumerate(i.rows):
172:             bestp = False
173:             for n1, n2, d in zip(i.rows[0].ys(), row.ys(), ds):
174:                 bestp |= abs(n1-n2) <= d
175:             (best if bestp else rest).add(row)
176:         return best, rest
177:
178:     def clone(i, inits=[]): return Rows([i.cols.names] + inits)
179:
180:     def data(i, a):
181:         a = a.cells if type(a) == Row else a
182:         i.rows += [Row([col.add(a[col.at]) for col in i.cols.all],
183:             rows=i)]
184:
185:     def header(i, a):
186:         i.cols.names = a
187:         for at, x in enumerate(a):
188:             new = Skip if i.skipp(x) else (Num if i.nump(x) else Sym)
189:             new = new(at=at, txt=x)
190:             i.cols.all += [new]
191:             if not i.skipp(x):
192:                 i.cols["y"] if i.y(x) else "x" += [new]
193:             if i.klass(x):
194:                 i.cols.klass = new
195:
196:     def klassp(i, x): return "!" in x
197:
198:     def nump(i, x): return x[0].isupper()
199:
200:     def skipp(i, x): return "x" in x
201:
202:     def ys(i): return [col.mid() for col in i.cols.y]
203:
204:     def ysd(i): return [col.sd() for col in i.cols.y]
205:
206:     def yp(i, x): return "-" in x or "+" in x or i.klassp(x)
207:
208: #
209: def stratify(src):
210:     all, klass = None, {}
211:     for n, row in enumerate(src):
212:         if all:
213:             kl = row[all.cols.klass.at]
214:             here = klass[kl] = klass.get(kl, None) or all.clone()

```

```

203:     here.add(row)
204:     all.add(row)
205:     else:
206:         all = Rows([row])
207:     return o(all=all, klass=klass)
208:
209: # Discretizations
210: # Use 'bins' to divide numeric data into ranges.
211: def bins(xy, iota=0, size=30):
212:     def merge(b4):
213:         j, tmp, n = 0, [], len(b4)
214:         while j < n:
215:             ((lo, _), ay) = a = b4[j]
216:             if j < n - 1:
217:                 ((_, hi), by) = b4[j + 1]
218:                 if cy := ay.merged(by):
219:                     a = ((lo, hi), cy)
220:                     j += 1
221:             tmp += [a]
222:             j += 1
223:         return merge(tmp) if len(tmp) < len(b4) else b4
224:
225:     def divide(xy):
226:         bin = o(x=Num(), y=Sym())
227:         bins = [bin]
228:         for i, (x, y) in enumerate(xy):
229:             if bin.x.n >= size and x != b4:
230:                 if i < len(xy)-size and bin.x.wide(iota):
231:                     bin = o(x=Num(), y=Sym())
232:                     bins += [bin]
233:                 bin.x.add(x)
234:                 bin.y.add(y)
235:                 b4 = x
236:             return bins
237:
238:     xy = sorted(xy, key=first)
239:     return merge([(bin.x.span(), bin.y) for bin in divide(xy)])
240:
241: # Learn class deltas
242: def contrasts(here, there, the):
243:     goal = {'best': lambda b, r: b**2/b+r,
244:            'rest': lambda b, r: r**2/(b+r),
245:            'other': lambda b, r: 1/(b+r)}[the.GOAL]
246:
247:     def like(d, kl):
248:         out = prior = (hs[kl] + the.K) / (n + the.K*2)
249:         for at, span in d.items():
250:             f = has.get((kl, (at, span)), 0)
251:             out *= (f + the.M*prior) / (hs[kl] + M)
252:         return out
253:
254:     def val(d): return goal((like(d, True), like(d, False)), d)
255:     def top(a): return sorted(a, reversed=True, key=first)[the.TOP]
256:
257:     has = {(kl, (at, (lo, hi))): f
258:            for col1, col2 in zip(here.cols.x, there.cols.x)
259:            for at, (lo, hi) in col1.bins(col2, the)}
260:     n = len(here.rows, there.rows)
261:     hs = {True: len(here.rows), False: len(there.rows)}
262:     solos = [val(dict(at=x)) for at, x in set([z for _, z in has])]
263:     ranges = {}
264:     for _, d in top(solos):
265:         for k in d:
266:             ranges[k] = ranges.get(k, set()).add(d[k])
267:     for rule in top([val(d) for d in dict_product(ranges)]):
268:         print(rule)

```

```

269:
270: # Misc utils
271: # string stuff
272: def color(end="\n", **kw):
273:     s, a, z = "", "\u001b[", ";1m"
274:     c = dict(black=30, red=31, green=32, yellow=33,
275:             purple=34, pink=35, blue=36, white=37)
276:     for col, txt in kw.items(): s = s + a + str(c[col]) + z + txt + "\033[0m"
277:     print(s, end=end)
278:
279: def mline(m): m += [{"-"*len(str(x)) for x in m[-1]]]
280:
281: def printm(matrix):
282:     s = [str(e) for e in row] for row in matrix]
283:     lens = [max(map(len, col)) for col in zip(*s)]
284:     fmt = ' | '.join('{{: > {} }}'.format(x) for x in lens)
285:     for row in [fmt.format(*row) for row in s]: print(row)
286:
287: # maths stuff
288: def r3(a): return [round(x,3) for x in a]
289:
290: # dictionary stuff
291: def has(d, k): return d.get(k, 0)
292: def inc(d, k, n=1): tmp = d[k] = n + d.get(k, 0); return tmp
293:
294: def dict_product(d):
295:     keys = d.keys()
296:     for p in itertools.product(*d.values()):
297:         yield dict(zip(keys, p))
298:
299: # list stuff
300: def first(a): return a[0]
301: def last(a): return a[-1] # $Label{comment}$
302: def per(a, p=.5): return a[int(p*len(a))]
303:
304: # file stuff
305: def csv(f=None, sep=","):
306:     def prep(s): return re.sub(r'([\\n\\r ]{#.*})', "", s)
307:     if f:
308:         with open(f) as fp:
309:             for s in fp:
310:                 if s := prep(s): yield s.split(sep)
311:     else:
312:         for s in sys.stdin:
313:             if s := prep(s): yield s.split(sep)
314:
315: # command-line stuff
316: def cli(use, txt, config):
317:     fmt = argparse.RawTextHelpFormatter
318:     used, p = {}, argparse.ArgumentParser(prog=use, description=txt,
319:                                           formatter_class=fmt)
320:     for k, (_, b4, h) in config.items():
321:         k0 = k[0]
322:         used[k0] = c = k0 if k0 in used else k0.lower()
323:         if b4==False:
324:             p.add_argument("-"+c, dest=k, default=False,
325:                           help=h,
326:                           action="store_true")
327:         else: p.add_argument("-"+c, dest=k, default=b4,
328:                             help=h + " [" + str(b4) + "]",
329:                             type=type(b4), metavar=k)
330:     return o(**p.parse_args().__dict__)
331:
332: # Unit tests
333: class Eg:
334:     def ls(the):

```

```

335:     "list all examples."
336:     print("\nexamples:")
337:     for k, f in vars(Eg).items():
338:         if k[0] != "_": print(f" {k:<13} {f.__doc__}")
339:
340:     def _fail(the):
341:         "testing failure"
342:         assert False, "failing"
343:
344:     def data(the, file="./data/vote.csv"):
345:         "simple load of data into a table"
346:         r = Rows(csv(file))
347:         assert 435 == len(r.rows)
348:         assert 195 == r.cols.all[1].has['y']
349:
350:     def nclasses(the, file="./data/diabetes.csv", kl="positive"):
351:         "read data with nclasses"
352:         rs = stratify(csv(file))
353:         assert 2 == len(rs.klass)
354:         assert 268 == len(rs.klass[kl].rows)
355:         assert 768 == len(rs.all.rows)
356:         assert 3.90625 == rs.klass[kl].cols.all[0].sd()
357:
358:     def bins(the, file="./data/diabetes.csv",
359:             k1="positive", k2="negative"):
360:         "discretize some data"
361:         rs = stratify(csv(file))
362:         bins1(rs.klass[k1], rs.klass[k2], the)
363:
364:     def bestrest(the, file="./data/auto93.csv"):
365:         "discretize some multi-goal data"
366:         r = Rows(csv(file))
367:         goods, bads = r.best(the)
368:         bins1(goods, bads, the)
369:
370:     def bins1(goods, bads, the):
371:         for good, bad in zip(goods.cols.x, bads.cols.x):
372:             bins = list(good.bins(bad, the))
373:             if len(bins) > 1:
374:                 print(f"\n{good.txt}")
375:                 for bin in bins: print("\t", bin)
376:
377: # Main program
378: def main(the):
379:     def run(fun, fails, the):
380:         s = f" {fun.__name__:<12}"
381:         if the.WILD:
382:             print("raw")
383:             fun(copy.deepcopy(the)); sys.exit()
384:         try:
385:             fun(copy.deepcopy(the))
386:             random.seed(the.SEED)
387:             color(green= (chr(10003)+ s), white=fun.__doc__)
388:         except Exception as err:
389:             fails = fails + 1
390:             color(red= (chr(10007)+ s), white= str(err))
391:         return fails
392:
393:     fails=0
394:     if the.XAMPLE == "all":
395:         for k, f in vars(Eg).items():
396:             if k[0] != "_" and kl!="ls": fails = run(f, fails, the)
397:     else:
398:         if the.XAMPLE and the.XAMPLE in vars(Eg):
399:             f = vars(Eg)[the.XAMPLE]
400:             if the.XAMPLE=="ls": f(the)

```

```
401:     else : fails=run(f,fails,the)
402: sys.exit(fails)
403:
404: if __name__ == "__main__":
405:     main( cli("./keys", __doc__, config()) )
```