

LIB: Commonly used predicates

Tim Menzies

Lane Department of Computer Science, West Virginia University, PO Box 6109, Morgantown, WV, 26506-6109, USA;
<http://tim.menzies.us>; tim@menzies.us

Wp ref: `~menzies/src/pl/prod/lib.pl`, February 23, 2003.

Abstract Commonly used Prolog predicates.

Contents

1	Change log	1
2	Installation	1
3	Pre-load actions	1
3.1	Operators	1
3.2	Flags	1
3.3	Hooks	2
4	Predicates	2
4.1	Code to demonstrate predicates	2
4.2	List stuff	2
4.3	Maths stuff	3
4.4	Lookup tables	3
4.5	Random numbers	3
4.6	String Stuff	4
4.7	Predicates for Pairs	5
4.8	Input/output stuff	8
4.9	Meta-level predicates	8
5	Start-up commands	9
6	Bugs	9
A	License	10
A.1	nowarranty.txt	10
A.2	warranty.txt	10
A.3	conditions.txt	10

List of Figures

1	egwrites.spy	3
2	egdeletes.spy	3
3	eglookup.spy	3
4	eggrands.spy	3
5	egbeta.spy	4
6	egnnormal.spy	4
7	egggamma.spy	4
8	egformat.spy	5
9	eginc.spy	5
10	egdist.spy	5
11	egbarsNormal.spy	6
12	egbarsBeta.spy	6

13	egbarsGamma1.spy	6
14	egbarsGamma2.spy	6
15	egbarsGamma3.spy	7
16	egnnormalize.spy	7
17	nowarranty.txt	8
18	egchars.spy	8
19	egtidy.spy	8
20	egdemand.spy	8
21	egtimes.spy	9
22	Find out more about PROD.	10

1 Change log

Added: **ensure**/1 Ensure that some assertion exists.

2 Installation

```
1 :- load_files([lib0 % pre-load actions
2               ,lib1 % predicates
3               ,lib2 % start-up commands
4               ],[silent(yes),if(changed)]).
```

3 Pre-load actions

3.1 Operators

Define an operator to handle numeric ranges **Min** to **Max**.

```
5 :- op(1,xfx,to).
```

3.2 Flags

Define an **infinity** function.

```
6 :- arithmetic_function(inf/0).
```

Define a **random** function.

```
7 :- arithmetic_function(rand/0).
```

Define a **rand(Min,Max)** function.

```
8 :- arithmetic_function(rand/2).
```

Define a **rand(Min,Max,Mean)** function.

```
9 :- arithmetic_function(rand/3).
```

Define a **normal** function.

```
10 :- arithmetic_function(normal/2).
```

Define a **beta** function.

```
11 :- arithmetic_function(beta/1).
```

Define a **gamma** function.

```
12 :- arithmetic_function(gamma/2).
```

Add a “left-justify” command to **format**.

```
13 :- format_predicate('>',padChars(_,_)).
```

Add a “right-justify” command to **format**.

```
14 :- format_predicate('<',charsPad(_,_)).
```

Add a “print squiggles” command to **format**.

```
15 :- format_predicate('S',squiggle(_,_)).
```

Define a predicate for the lookup tables.

```
16 :- discontinuous lookUp1/4.
17 :- multifile lookUp1/4.
18 :- index(lookUp1(1,1,1,0)).
```

3.3 Hooks

A hook for lookup tables.

```
19 term_expansion(Table = ColsRows , Out) :-
20     nonvar(ColsRows),
21     ColsRows = (Cols+Rows),
22     lookUpTable(Table=Cols+Rows,Out).
```

4 Predicates

4.1 Code to demonstrate predicates

4.1.1 Define demos

```
23 eglib :-
24     forall(member(G,[
25         egwrites, egdeletes,    egmaths,  eglookup,
26         eginc,
27         egrands,  egbeta,      egnormal,  eggamma,
28         egformat, eginc,       egdist,
29         egbarsNormal, egbarsBeta,
30         egbarsGamma1, egbarsGamma2, egbarsGamma3,
31         egnormalize, egchars,  egtidy,
32         egdemand, egtimes
33     ]),
34     demos(G)).
```

4.1.2 Processing demos

To demo our code, we need to:

- Write a demo predicate that shows off our code in action. In **PROD**, these predicates are named `egXXX/0`. Include with this predicate, a pointer to the output; e.g.

```
egXXX :- % See \fig{egXXX.spy}
...

```

- Trap the output to a file. This is accomplished using the `demos/1` predicate shown below. The goal `demos(egXXX)` generates a file `egXXX.spy`.
- Include that file. This is accomplished using the following \LaTeX magic:

```
\SRC{egXXX.spy}{From \tion{egXXX/1}.}
```

Note the call to `\tion{egXXX/1}`. Sections can be referenced symbolically when (e.g.) `\label{sec:egXXXX/1}` is added on the first line after a heading definition. Once this has been done, then `\tion{egXXX/1}` will be typeset as a reference to the relevant section.

After all that, then:

- The output of the demo will be shown in the document,
- The demo predicate will include a pointer to the figure,
- The caption of the figure will include a pointer to the section in the text that generated it.

Most of the demonstrations in this file use this approach.

4.1.3 demos(+Goal) `Demos/1` runs a goal `G` and catches the output to the file `G.spy`. Also, just so you know what is going on, it runs the goal `G` a second time and sends the output to the screen.

```
35 demos(G) :-
36     sformat(Out,'~w.spy',G),
37     freshFile(Out),
38     tell(Out),
39     format('% output from '':- demos(~w).''\n\n',G),
40     T1 is cputime,
41     ignore(forall(G,true)),
42     T2 is (cputime - T1),
43     format('\n% runtime = ~w sec(s)\n',[T2]),
44     told,
45     nl,write('\n%-----\n'),
46     format('% output from '':- demos(~w).''\n',G),
47     ignore(forall(G,true)),
48     format('\n% runtime = ~w sec(s)',[T2]).
```

`Demos/1` needs a helper predicate. `FreshFile/1` makes sure that no one else has scribbled, or is currently scribbling, on our output file.

```
49 freshFile(X) :-
50     (current_stream(X,_,S) -> close(S) ; true),
51     (exists_file(X) -> delete_file(X) ; true).
```

4.1.4 Using Demos/1. Next, we need to run the demo code as follows:

```
?- demos(egXXX).
```

Once that is done, then when this document will include the output in the figure with the label `egXXX.spy`.

4.2 List stuff

4.2.1 writes(+List): print a list

```
52 writes([H|T]) :-
53     forall(member(One,[H|T]),(print(One),nl)).
```

Demonstration code:

```
62 egwrites :- % see Figure 1
63     writes([aa,bb,cc,dd]).
```

4.2.2 deletes(+List1,+List2,-List3): delete items from a list

```
64 deletes([],_,[]).
65 deletes([Doomed|T],Doomeds,Rest) :-
66     member(Doomed,Doomeds),!,
67     deletes(T,Doomeds,Rest).
68 deletes([Saved|T],Doomeds,[Saved|Rest]) :-
69     deletes(T,Doomeds,Rest).
```

```

egwrites.spy
% output from ':- demos(egwrites).'

aa
bb
cc
dd

% runtime = 0 sec(s)

```

Fig. 1 From §4.2.1.

```

egdeletes.spy
% output from ':- demos(egdeletes).'

If we take [b, c] from
[a, b, r, a, c, a, d, a, b, r, a] we get
[a, r, a, a, d, a, r, a].

% runtime = 0 sec(s)

```

Fig. 2 From §4.2.2.

Demonstration code:

```

77 egdeletes :- % see Figure 2
78     List = [a,b,r,a,c,a,d,a,b,r,a],
79     Doomed=[b,c],
80     deletes(List,Doomed,Out),
81     format('If we take ~w from~n~w we get~n~w.~n',
82           [Doomed,List,Out]).

```

4.3 Maths stuff

4.3.1 sum(+List,-Num): sum a list of numbers

```

83 sum([H|T],S) :-
84     sum(T,H,S).
85
86 sum([],S,S).
87 sum([H|T],In,Out) :- Temp is H + In, sum(T,Temp,Out).

```

4.3.2 average(+List,-Num): average a list of numbers

```

88 average(L,Av) :- average(L,_,Av).
89 average([H|T],N,Av) :- average1(T,1,N,H,Sum), Av is Sum/N.
90
91 average1([],N,N,Out,Out).
92 average1([H|T],N0,N,In,Out) :-
93     Temp is H+In,
94     N1 is N0 + 1,
95     average1(T,N1,N,Temp,Out).

```

Demonstration code:

```

96 egmaths :- % See Figure ??
97     Nums = [2,3,5,2,4,6,3,4,2,4],
98     average(Nums,Av),
99     sum(Nums,Sum),
100     format('The sum and average of~n~w~n are ~w and ~w~n.',
101           [Nums,Sum,Av]).

```

4.4 Lookup tables

Convert a list of tabular data to one fact for each cell.

```

102 lookUpTable(X,Out) :-
103     bagof(Y,X^list2Relation1(X,Y),Out).
104
105 list2Relation1(Table=Cols+Rows, lookUp1(Table,R,C,X)):-
106     nth1(Pos,Cols,C),
107     member([R|Cells],Rows),
108     nth1(Pos,Cells,X),
109     nonvar(X).

```

```

eglookup.spy
% output from ':- demos(eglookup).'

[age(30),weight(40)]= avg

% runtime = 0 sec(s)

```

Fig. 3 From §4.4.

```

egrand.spy
% output from ':- demos(egrand.s).

0.279609 is a random number between 0 and 1.
18.9953 is a random number between 10 and 20.

% runtime = 0 sec(s)

```

Fig. 4 From §4.5.1.

Access the cells

```

110 lookUp(T,X,Y,Out) :-
111     lookUp1(T,R,C,Out), gt(X,R), gt(Y,C).

```

Cell access can be via an exact match or via a range query:

```

112 gt(Value,X to Y) :- !,X <= Value, Value <= Y.
113 gt(Value,Value).

```

Demonstration code:

```

119 egLookUpDemo =
120     % age          weight
121     % -----
122     [1 to 19, 20 to 50, 51 to inf]+
123     [[ 0 to 20,      low,      low,      avg]
124      ,[21 to 40,      low,      avg,      high]
125      ,[41 to inf,    avg,      high,      high]
126      ].
127
128 eglookup :- % see Figure 3
129     Age=30,
130     Weight=40,
131     lookUp(egLookUpDemo,Age,Weight,X),
132     format('[age(~w),weight(~w)]= ~w~n',
133           [Age,Weight,X]).

```

4.5 Random numbers

4.5.1 Basic randoms Generate a number $0 \leq X \leq 1$.

```

134 rand(X) :-
135     X is random(inf+1)/inf.

```

Generate a number X between some Min and Max value.

```

136 rand(Min,Max,X) :-
137     X is Min + (Max-Min)*rand.

```

Demonstration code:

```

144 egrands :- % see Figure 4
145     Rand1 is rand,
146     format('~w is a random number between 0 and 1.~n',
147           [Rand1]),
148     Rand2 is rand(10,20),
149     format('~w is a random number between 10 and 20.~n',
150           [Rand2]).

```

4.5.2 Beta distributions Generate a number X whose mean is $B\%$ between Min and Max . Technically, this is an application of a *beta* function. Here, I use a very simplistic method that only works for certain values of B : ($B = 0.1, 0.2, 0.3, \dots, 0.9, 1$).

```

egbeta.spy
% output from ':- demos(egbeta).'

[11.2313, 14.5453, 11.2714, 13.4645, 10.2245]
are random numbers 20% between 10 and 20.

% runtime = 0 sec(s)

```

Fig. 5 From §4.5.2.

```

egnormal.spy
% output from ':- demos(egnormal).'

[10.479, 11.2775, 7.82854, 9.13898, 5.80684]
are random numbers from normal(10,2).

% runtime = 0 sec(s)

```

Fig. 6 From §4.5.3.

```

151 rand(Min,Max,B,X) :-
152   X is Min + (Max-Min)*beta(B).
153
154 beta(B,X) :- betal(B,X),!.
155 beta(B,X) :- B1 is 1 - B, betal(B1,X),X is 1 - Y.
156
157 betal(0.50,X) :- X is rand.
158 betal(0.60,X) :- X is rand^0.67.
159 betal(0.67,X) :- X is rand^0.5.
160 betal(0.75,X) :- X is rand^0.33.
161 betal(0.80,X) :- X is rand^0.25.
162 betal(0.9,X) :- X is rand^(1/9).
163 betal(1,1).

```

Demonstration code:

```

170 egbeta :- % see Figure 5
171   R1 is rand(10,20,0.2),
172   R2 is rand(10,20,0.2),
173   R3 is rand(10,20,0.2),
174   R4 is rand(10,20,0.2),
175   R5 is rand(10,20,0.2),
176   Nums=[R1,R2,R3,R4,R5],
177   format('~w\n are random numbers 20% between 10 and 20.\n',
178     [Nums]).

```

Note that the numbers in Figure 5 may not look like they are, on average, 20% between 10 and 20. Later, we run this code 10,000 times and the true average results can be seen.

4.5.3 Normal distributions Generate a random number from a normal distribution with mean M and standard deviation S . This number is generated using the Box-Muller method (no, I don't understand it either).

```

179 normal(M,S,N) :-
180   box_muller(M,S,N).
181
182 box_muller(M,S,N) :-
183   wloop(W0,X),
184   W is sqrt((-2.0 * log(W0))/W0),
185   Y1 is X * W,
186   N is M + Y1*S.
187
188 wloop(W,X) :-
189   X1 is 2.0 * rand - 1,
190   X2 is 2.0 * rand - 1,
191   W0 is X1*X1 + X2*X2,
192   (W0 >= 1.0 -> wloop(W,X) ; W0=W, X = X1).

```

Demonstration code:

```

198 egnormal :- % see Figure 6
199   R1 is normal(10,2),
200   R2 is normal(10,2),
201   R3 is normal(10,2),
202   R4 is normal(10,2),
203   R5 is normal(10,2),
204   Nums=[R1,R2,R3,R4,R5],
205   format('~w\n are random numbers from normal(10,2).',
206     [Nums]).

```

```

egggamma.spy
% output from ':- demos(egggamma).'

[19.7148, 7.15347, 4.25717, 8.11787, 16.355]
are random numbers from gamma(10,2).

% runtime = 0 sec(s)

```

Fig. 7 From §4.5.4.

4.5.4 Gamma distributions Generate random numbers from zero to infinity.

```

207 gamma(Mean,Alpha,Out) :-
208   Beta is Mean/Alpha,
209   (Alpha > 20
210   -> Mean is Alpha * Beta,
211       Sd is sqrt(Alpha*Beta*Beta),
212       Out is normal(Mean,Sd)
213   ; gamma(Alpha,Beta,0,Out)).
214
215 gamma(0,_,X,X) :- !.
216 gamma(Alpha,Beta, In, Gamma) :-
217   Temp is In + (-1 * Beta * log(1-rand)),
218   Alpha1 is Alpha - 1,
219   gamma(Alpha1,Beta,Temp,Gamma).

```

Technically, this is *gamma* distribution. A standard random *gamma* distribution has the mean = $\frac{\alpha}{\beta}$. The *alpha* value is the “spread” of the distribution and controls the clustering of the distribution around the mean. As *alpha* increases, the *gamma* distribution flattens out to become more evenly-distributed about the mean. That is, for large *alpha* (i.e. $\alpha \geq 20$), *gamma* can be modeled as a normal function. The standard *alpha, beta* terminology can be confusing to some audiences. Hence, I define a (slightly) more-intuitive *gamma* distribution where:

$$myGamma(mean, alpha) = gamma\left(alpha, \frac{alpha}{mean}\right)$$

Demonstration code:

```

225 egggamma :- % see Figure 7
226   R1 is gamma(10,2),
227   R2 is gamma(10,2),
228   R3 is gamma(10,2),
229   R4 is gamma(10,2),
230   R5 is gamma(10,2),
231   Nums=[R1,R2,R3,R4,R5],
232   format('~w\n are random numbers from gamma(10,2).',
233     [Nums]).

```

4.6 String Stuff

4.6.1 Right-justify a string. Right-justifies a string **A** in a space **S**:

```

234 right_justify(S,A) :-
235   writeThing(A,Thing,N),
236   Pad is S - N,
237   forall(between(1,Pad,_),put(32)),
238   write(Thing).
239
240 writeThing(X,S,L) :-
241   sformat(S,'~w',[X]),
242   string_length(S,L).

```

Map `right_justify` into the `format` predicate.

```

243 padChars(default,A) :- right_justify(S,A).
244 padChars(S, A) :- right_justify(S,A).

```

```

      egformat.spy
% output from ':- demos(egformat).'

[ tim]
[      tim]
[tim  ]
[tim      ]
[~~~~~]
[~~]

% runtime = 0 sec(s)

```

Fig. 8 From §4.6.

4.6.2 Left-justify a string

```

245 left_justify(S,A) :-
246     writeThing(A,Thing,N),
247     atom_length(A,N),
248     Pad is S - N,
249     write(Thing),
250     forall(between(1,Pad,_),put(32)).
251
252 charsPad(default,A) :- left_justify(5,A).
253 charsPad(S,A)         :- left_justify(S,A).

```

4.6.3 *Print some squiggles* Generates **N** squiggles in a space normalized to a screen with maximum width **W**.

```

254 squiggles(W,N) :-
255     N1 is round(N/W),
256     forall(between(1,N1,_),put(126)).
257
258 squiggle(default,A) :- squiggles(25,A).
259 squiggle(W,N)         :- squiggles(W,N).

```

Demonstration code.

```

270 egformat :- % Figure 8
271     format('~>~\n',tim), % right-justify
272     format('~12>~\n',tim), %
273     format('~<~\n',tim), % left-justify
274     format('~12<~\n',tim), %
275     format('~S~\n',100), % print some twiddles
276     format('~50S~\n',100), %

```

4.7 Predicates for Pairs

4.7.1 pairs(?Keys,?Values,?Pairs): key-value pairs

```

277 pairs([],[],[]).
278 pairs([X|Xs],[Y|Ys],[X=Y|T]) :- pairs(Xs,Ys,T).

```

4.7.2 *key(+Pairs,?Key,?Value,?Pairs): a key-in-front working memory* Access values in a list of key=value pairs. As a side-effect of accessing, move the accessed pair to the front of the list.

```

279 key(L0,K,V0,V,[K=V|L]) :-
280     less1(L0,K=V0,L).
281
282 less1([H|T],H,T).
283 less1([H|T],Out,[H|Rest]) :-
284     less1(T,Out,Rest).

```

4.7.3 inc(+Pairs,+Key,?Pairs): a lists of counters

Maintain a list of keys. Incrementing a key add one to its value.

```

285 inc([], A, [A=1]).
286 inc([A=B|C],D,E) :-
287     compare(F,A,D),inc(F,A=B,C,D,E).
288
289 inc(<, A, B, C, [A|D]) :- inc(B, C, D).
290 inc(=, A=B, C, A, [A=D|C]) :- D is B+1.
291 inc(>, A, B, C, [C=1, A|B]).

```

```

      eginc.spy
% output from ':- demos(eginc).'

The keys in
[a, b, r, a, c, a, d, a, b, r, a]
occur with frequencies
[a=5, b=2, c=1, d=1, r=2].
% runtime = 0 sec(s)

```

Fig. 9 From §4.7.3.

```

      egdist.spy
% output from ':- demos(egdist).'

The distribution of symbols
[a, b, r, a, c, a, d, a, b, r, a] is
[r=2, d=1, c=1, b=2, a=5].

% runtime = 0 sec(s)

```

Fig. 10 From §4.7.4.

Demonstration code:

```

299 eginc :- % see Figure 9
300     List = [a,b,r,a,c,a,d,a,b,r,a],
301     eginc1(List,[],Incs),
302     format('The keys in~\nw~\n occur with frequencies~\nw. ',
303           [List,Incs]).
304
305 eginc1([],W,W).
306 eginc1([H|T],W0,W) :- inc(W0,H,W1), eginc1(T,W1,W).

```

4.7.4 dist(+List,-Pairs): Simple collection of histogram data

```

307 dist(L0,L) :-
308     dist(L0,_,_,L,_).
309
310 dist(L0,L,Most) :-
311     dist(L0,_,_,L,Most).
312
313 dist(L0,Min,Max,L) :-
314     dist(L0,Min,Max,L,_).
315
316 dist(L0,Min,Max,L,Most) :-
317     msort(L0,[Min|L1]), % ◀..... 317
318     dist([Min|L1],[Min,Max,L,0,Most]).
319
320 dist([],X,Max,Max,X,Most,Most).
321 dist([H|T],[H=N0|Rest],_,Max,Out,Most0,Most) :- !,
322     N is N0 + 1,
323     Most1 is max(Most0,N),
324     dist(T,[H=N|Rest],H,Max,Out,Most1,Most).
325 dist([H|T],In,Min,Max,Out,Most0,Most) :-
326     Most1 is max(Most0,1),
327     dist(T,[H=1|In],Min,Max,Out,Most1,Most).

```

Demonstration code:

```

335 egdist :- % see Figure 10
336     List = [a,b,r,a,c,a,d,a,b,r,a],
337     dist(List,Dist),
338     format('The distribution of symbols~\nw is~\nw.~\nw',
339           [List,Dist]).

```

Note that *dist/2 could be implemented using inc/3*. However, the call of *msort* at line 317 makes *dist/2* faster for large lists.

4.7.5 bars(+Num1,+Num2,+Num3,+Pairs): print a bar chart

Display the pairs as a bar chart. **Num1** is the width of the first “item” column displaying the name of each bar; **Num2** is the width of the second “frequency” column showing how many items fall into that bar; **Num3** is the width of the last column showing the population size.

```

egbarsNormal.spy
% output from ':- demos(egbarsNormal).'
```

item	frequency
29	1
27	7
26	32
25	92 ~
24	249 ~~
23	668 ~~~~~
22	1195 ~~~~~~
21	1760 ~~~~~~
20	1963 ~~~~~~
19	1767 ~~~~~~
18	1271 ~~~~~~
17	603 ~~~~~~
16	288 ~~~~
15	76 ~~~~
14	26 ~~~~
13	2 ~~~~

```

% runtime = 0.540778 sec(s)

```

Fig. 11 From §4.7.5.

```

egbarsBeta.spy
% output from ':- demos(egbarsBeta).'
```

item	frequency
19	4
18	30
17	109 ~
16	244 ~
15	499 ~~~~
14	860 ~~~~~
13	1401 ~~~~~~
12	2059 ~~~~~~
11	2961 ~~~~~~
10	1833 ~~~~~~

```

% runtime = 0.310446 sec(s)

```

Fig. 12 From §4.7.5.

```

egbarsGamma1.spy
% output from ':- demos(egbarsGamma1).'
```

item	frequency
22	3
21	4
20	10
19	11
18	34
17	76 ~
16	144 ~
15	241 ~
14	451 ~~~~
13	665 ~~~~~
12	942 ~~~~~~
11	1321 ~~~~~~
10	1548 ~~~~~~
9	1593 ~~~~~~
8	1378 ~~~~~~
7	901 ~~~~~~
6	466 ~~~~~~
5	169 ~~~~
4	38 ~~~~
3	5 ~~~~

```

% runtime = 1.94279 sec(s)

```

Fig. 13 From §4.7.5.

```

egbarsGamma2.spy
% output from ':- demos(egbarsGamma2).'
```

item	frequency
36	1
34	1
33	1
32	3
31	2
30	5
29	2
28	10
27	17
26	7
25	12
24	26
23	31
22	52 ~
21	61 ~
20	86 ~
19	139 ~
18	184 ~
17	236 ~
16	293 ~
15	348 ~
14	433 ~
13	578 ~
12	662 ~
11	783 ~
10	900 ~
9	949 ~
8	947 ~
7	906 ~
6	824 ~
5	709 ~
4	463 ~
3	244 ~
2	77 ~
1	8 ~

```

% runtime = 0.761094 sec(s)

```

Fig. 14 From §4.7.5.

```

340 bars(Num1,Num2,Num3,List) :-

```

Use **sformat** to build a string that stores the widths and scale factor for our columns. Note the use of "c" and "S" which are special format commands defined above.

```

341 sformat(S, '~w> ~w> ~wS\n',
342 [Num1,Num2,Num3]),
343 dist(List,Dist),
344 nl,
345 format(S,[item,frequency,0]),
346 forall(member(What=N,Dist),
347 format(S,[What,N,N])).

```

A useful default call.

```

348 bars(List) :-
349 bars(5, % the "item" column is 5 wide
350 5, % the "frequency" column is 5 wide
351 3, % the "scale factor" is 3
352 List % now, go display these pairs
353 ).

```

Demonstration code:

```

egbarsGamma3.spy
% output from ':- demos(egbarsGamma3).'

---| 10000 * gamma(10, 2) |-----
item frequency
64 1
55 1
53 1
52 3
50 1
48 1
46 2
45 1
44 1
43 6
42 6
41 2
40 9
39 4
38 12
37 8
36 10
35 14
34 14
33 22
32 27
31 30
30 32
29 27
28 43
27 52 ~
26 53 ~
25 64 ~
24 72 ~
23 95 ~
22 99 ~
21 121 ~
20 158 ~
19 167 ~
18 182 ~
17 227 ~
16 267 ~
15 290 ~
14 367 ~
13 389 ~
12 448 ~
11 485 ~
10 534 ~
9 601 ~
8 634 ~
7 699 ~
6 743 ~
5 719 ~
4 757 ~
3 632 ~
2 534 ~
1 295 ~
0 38

% runtime = 0.41059 sec(s)

```

Fig. 15 From §4.7.5.

```

egnnormalize.spy
% output from ':- demos(egnnormalize).'

When [a=10, b=5, c=20, d=50, e=5, c=10]
is normalized it generates
[a=0.1, b=0.05, c=0.2, d=0.5, e=0.05, c=0.1].

% runtime = 0 sec(s)

```

Fig. 16 From §4.7.6.

```

542 egbarDemos(Repeats,F) :-
543     format('\n\n---| ~w * ~w |-----',[Repeats,F]),
544     Size=1,
545     findall(X,(between(1,Repeats,_),X is F),L0),
546     cutDown2Sizes(Size,L0,L),
547     bars(5,5,100,L).
548
549 cutDown2Sizes(Size) --> maplist(cutDown2Size(Size)).
550 cutDown2Size(Size,X,Y) :- Y is round(X/Size).

```

4.7.6 normalize(+Pairs1,-Pairs2): *normalize a list of numbers* Input list with values $M_1, M_2 \dots M_i$ with sum $M_1 + M_2 + \dots + M_i$ to a second list of numbers N_1, N_2, \dots, N_i where $0 \leq N_i \leq 1$ and $N_1 + N_2 + \dots + N_i = 1$.

```

551 normalize(L,N) :-
552     mostnormal(L,N,_).
553
554 mostnormal(L,N,Most) :-
555     sumpairs(L,Sum),
556     mostnormal1(L,Sum,junk= -1,N,Most).
557
558 mostnormal1([],_,Out,[],Out).
559 mostnormal1([X=V0|T],Sum,Y=N,[X=N1|Out],Most) :-
560     N1 is V0/Sum,
561     (N1 > N
562     -> mostnormal1(T,Sum,X=N1,Out,Most)
563     ; mostnormal1(T,Sum,Y=N,Out,Most)).
564
565 sumpairs([_H=V|T],S) :-
566     sumpairs(T,V,S).
567
568 sumpairs([],S,S).
569 sumpairs([_V|T],In,Out) :-
570     Temp is V + In, sumpairs(T,Temp,Out).

```

Demonstration code:

```

578 egnormalize :- % see Figure 16
579     L=[a=10,b=5,c=20,d=50,e=5,c=10],
580     normalize(L,Normals),
581     format('When ~w\n is normalized it generates\n~w.\n',
582            [L,Normals]).

```

4.7.7 Ordered Sets Standard definition:

```

583 oset_add([], El, [El]).
584 oset_add([H|T], El, Add) :-
585     compare(Order, H, El),
586     addel(Order, H, T, El, Add).
587
588 addel(<, H, T, El, [H|Add]) :- oset_add(T, El, Add).
589 addel(=, H, T, _El, [H|T]).
590 addel(>, H, T, El, [El,H|T]).

```

With key-value pairs Bulk additions

```

591 koset_adds(L,Out) :- koset_adds(L,[],Out).
592
593 koset_adds([],Out,Out).
594 koset_adds([H|T],In,Out) :- koset_add(In,H,Temp), koset_adds(T,Temp,Out).
595
596 koset_add([], El, [El]).
597 koset_add([H=X|T], El=Y, Add) :-
598     compare(Order, H, El),
599     kaddel(Order, H, X,T, El, Y,Add).
600
601 kaddel(<, H, X,T, El, Y,[H=X |Add]) :- koset_add(T, El=Y, Add).
602 kaddel(=, H, X,T, _El, Y,[H=Y |T]).
603 kaddel(>, H, X,T, El, Y,[El=Y,H=X|T]).

```

```

528 egbarsNormal :- % see Figure 11
529     egbarDemos(10000,normal(20,2)).
530
531 egbarsBeta :- % see Figure 12
532     egbarDemos(10000,rand(10,20,0.2)).
533
534 egbarsGamma1 :- % see Figure 13
535     egbarDemos(10000,gamma(10,15)).
536
537 egbarsGamma2 :- % see Figure 14
538     egbarDemos(10000,gamma(10,5)).
539
540 egbarsGamma3 :- % see Figure 15
541     egbarDemos(10000,gamma(10,2)).

```

Support code for the demonstration code:

```

nowarranty.txt
comes with ABSOLUTELY NO WARRANTY:
for more details type 'warranty'.

This is free software, and you are welcome to
redistribute it under certain conditions: for
more details, type 'conditions'.

```

Fig. 17 A text file.

```

egchars.spy
% output from ':- demos(egchars).'

comes with ABSOLUTELY NO WARRANTY:
for more details type 'warranty'.

This is free software, and you are welcome to
redistribute it under certain conditions: for
more details, type 'conditions'.
% runtime = 0 sec(s)

```

Fig. 18 The code in §4.8.4 displays the contents of Figure 17 to the screen.

4.8 Input/output stuff

Demonstrations are offered for only some of the predicates in this section. I/O code can make explicit calls to input/output streams which mucks up our demonstration system.

4.8.1 sneak(+List): load files. Don't bother loading the files if they haven't changed. But if you do load them, don't print anything to the screen.

```

603 sneak(X) :-
604     load_files(X,[silent(true),if(changed)]).

```

4.8.2 spit(+Num1,+Num2,+Term): Print something, sometimes. Useful for tracking a long process since it, sometimes, spits out a marker.

```

605 spit(N1,N2,X) :-
606     (0 is N1 mod N2 -> blurt(X) ; true).

```

4.8.3 blurt(+Term): print, then flush.

```

607 blurt(X) :-
608     write(user,X),flush_output(user).

```

4.8.4 chars(+String): copy a file to the screen.

```

615 chars(File) :-
616     see(File), get_byte(X), ignore(chars1(X)), seen.
617
618 chars1(-1) :- !.
619 chars1(X) :- put(X), get_byte(Y), chars1(Y).

```

Demonstration code:

```

629 egchars :- % see Figure 18.
630     chars('nowarranty.txt').

```

4.8.5 barph(+Term): print a warning, then fail. A standard barph:

```

631 barph(X) :- format('%W> ~p~n',X),fail.

```

A barph that also prints line numbers showing the origin of the barph.

```

632 barphln(X) :-
633     here(File,Line),
634     format('%W> ~p~p : ~p~n',[File,Line,X]),
635     fail.
636
637 here(File,Line) :-
638     source_location(Path,Line),
639     file_base_name(Path,File).

```

```

egtidy.spy
% output from ':- demos(egtidy).'

a :-
    b,
    c,
    (
        d
        -> true
    ;
        e
    ).
f.

% runtime = 0 sec(s)

```

Fig. 19 From §4.9.1.

```

egdemand.spy
% output from ':- demos(egdemand).'

%W> failed(10>20)

% runtime = 0 sec(s)

```

Fig. 20 From §4.9.3.

4.9 Meta-level predicates

4.9.1 tidy(+Rule0,-Rule1: remove stray “trues” from a rule body.

```

640 tidy(A,C) :-
641     tidy1(A,B),
642     (B = (Head :- true) -> C=Head ; C=B).
643
644 tidy1(A,C) :- once(tidy2(A,C)).
645
646 tidy2(A,          A) :- var(A).
647 tidy2((A,B),      (A,TB)) :- var(A), tidy1(B,TB).
648 tidy2((A,B),      (TA,B)) :- var(B), tidy1(A,TA).
649 tidy2(((A,B),C),  R) :- tidy1((A,B,C), R).
650 tidy2((true,A),   R) :- tidy1(A,R).
651 tidy2((A,true),   R) :- tidy1(A,R).
652 tidy2((A;true),   R) :- tidy1(A,R).
653 tidy2((true;A),   R) :- tidy1(A,R).
654 tidy2((A;B),      (TA;TB)) :- tidy1(A,TA), tidy1(B,TB).
655 tidy2((A->B),      (TA->TB)) :- tidy1(A,TA), tidy1(B,TB).
656 tidy2(not(A),      not(TA)) :- tidy1(A,TA).
657 tidy2((A :- B), R) :-
658     tidy1(B,TB), (TB=true -> R=A; R=(A:-TB)).
659 tidy2((A,B),      R) :-
660     tidy1(A,TA), tidy1(B,TB), (TB=true -> R=TA; R=(TA,TB)).
661 tidy2(A,A).

```

Demonstration code:

```

674 egtidy :- % see Figure 19
675     In1= (a :- b, true,c, (d->true;e)),
676     In2= (f :- true,(true;true;true),true),
677     tidy(In1,Out1),
678     portray_clause(Out1),
679     tidy(In2,Out2),
680     portray_clause(Out2).

```

4.9.2 ensure(+Term): some assertion exists

```

681 ensure(X) :- X,!.
682 ensure(X) :- assert(X).

```

4.9.3 demand(+Goal): warn if a goal fails.

```

683 demand(X) :- X,!.
684 demand(X) :- numbervars(X,0,_),barph(failed(X)).

```

Demonstration code:

```

690 egdemand :- % see Figure 20
691     demand(3 > 2),
692     demand(10 > 20).

```



```

egtimes.spy
% output from ':- demos(egtimes).'

In 10000 repeats, each run took 8.01152e-006 seconds.

% runtime = 0.100144 sec(s)

```

Fig. 21 From §4.9.5.

4.9.4 repeats(+Num,+Goal): run a goal N times

```

693 repeats(N0,G) :-
694     N is N0,
695     forall(between(1,N,_),G).

```

4.9.5 times(+Num,+Goal,-Time): time an execution

```

696 times(N,G,Out) :-
697     T1 is cputime, repeats(N,true),
698     T2 is cputime, repeats(N,G),
699     T3 is cputime, Out is (T3-T2-(T2-T1))/N.

```

Demonstration code:

```

705 egtimes :- % see Figure 21
706     N=10000,
707     List = [a,b,r,a,c,a,d,a,b,r,a,s],
708     times(N,member(s,List),T),
709     format('In ~w repeats, each run took ~w seconds.\n',
710           [N,T]).

```

4.9.6 !Repeats*!Goal1/!Goal2: compare runtimes

```

711 N*X/Y :- !,
712     times(N,X,T1),
713     times(N,Y,T2),
714     Inc=0.000001,
715     Ratio is (T1+Inc)/(T2+Inc),
716     write(goal1=X),nl,
717     write(time(goal1)=T1),nl,
718     write(goal2=Y),nl,
719     write(time(goal2)=T2),nl,
720     write(time(goal1)/time(goal2)=Ratio),nl.
721
722
723 N*X :- time(times(N,X,_)).

```

4.9.7 Lists/ conjunctions conversions. Convert a conjunction to a list:

```

724 c2l((X,Y),[X|Z]) :- !,c2l(Y,Z).
725 c2l(X,[X]).

```

Convert everything but the last item of a conjunction to a list:

```

726 mostC2l((X,Y),[X|Z]) :- !,mostC2l(Y,Z).
727 mostC2l(_,[]).

```

Convert a list to a conjunction:

```

728 l2c([W,X|Y],(W,Z)) :- l2c([X|Y],Z).
729 l2c([X],X).

```

Convert disjunctions to a list.

```

730 d2l((X;Y),[X|Z]) :- !,d2l(Y,Z).
731 d2l(X,[X]).

```

4.9.8 clause1(?Head,?Body): does a goal match only one clause?

```

732 clause1(X,Y) :-
733     singleton(X), clause(X,Y).
734
735 singleton(X) :-
736     Sym='$singleton_',
737     flag(Sym,_,0),
738     \+ singleton1(Sym,X),
739     flag(Sym,1,1).
740
741 singleton1(Sym,X) :-
742     clause(X,_),flag(Sym,N,N+1),N > 1,!

```

4.9.9 only(?Goal): can a goal only succeed once?

```

743 only(X) :-
744     Sym='$only_',
745     flag(Sym,_,0),
746     \+ only1(Sym,X),
747     flag(Sym,1,1).
748
749 only1(Sym,X) :-
750     X, flag(Sym,N,N+1),N > 1,!
751
752 solo(X) :-
753     only(X), X.

```

5 Start-up commands

```

754 :- current_prolog_flag(max_integer,X),
755     X1 is X - 1,
756     retractall(inf(_)),
757     assert(inf(X1)).

```

6 Bugs

None known but many suspected.

Acknowledgements This research was conducted at West Virginia University under NASA contract NCC2-0979. The work was sponsored by the NASA Office of Safety and Mission Assurance under the Software Assurance Research Program led by the NASA IV&V Facility. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise, does not constitute or imply its endorsement by the United States Government.

References

1. T. Menzies. PROD: A PROlog Documentation, and Delivery tool, 2003. Available from <http://tim.menzies.com/pdf/03prod2.pdf>.
2. T. Menzies. PROD: the source code, 2003. Available from <http://tim.menzies.com/prodfiles.zip>.
3. T. Menzies. An example of the PROD prolog delivery and documentation system, 2003. Available from <http://tim.menzies.com/pdf/03prod1.pdf>.
4. T. Menzies. A family database: documentation of a very simple prolog family database using PROD., 2003. Available from <http://tim.menzies.com/pdf/03family.pdf>.
5. T. Menzies. Including gpl-2 in PROD, 2003. Available from <http://tim.menzies.com/pdf/03gpl.pdf>.
6. T. Menzies. Monte carlo simulations in prolog: a PROD tool, 2003. Available from <http://tim.menzies.com/pdf/03lurch.pdf>.
7. T. Menzies. Motivations: the why and who of PROD, 2003. Available from <http://tim.menzies.com/pdf/03prodabout.pdf>.
8. T. Menzies. PROD's commonly used predicates, 2003. Available from <http://tim.menzies.com/pdf/03lib.pdf>.
9. T. Menzies. PROD's handler for config files and command line options, 2003. Available from <http://tim.menzies.com/pdf/03cfg.pdf>.

This paper was prepared using the PROD Prolog document and delivery preparation system [1, 2]:

- PROD was created to help me train my graduate students. It also is a nice demonstration of the utility of Prolog. For more on this point, see [7] (warning: includes sermonizing).
- PROD comes with a simple examples of documenting Prolog source code (e.g. a predicate to sum a list of numbers [3] and the standard Prolog family database [4] as well as a “bare-bones” example [11].
- PROD was designed as an open source tool. The GNU public license (version 2) can be shown from any PROD application and is added to every PROD document [5]).
- PROD comes with some handy little utilities and some applications:
 - A handler for config files, user preferences, and command line options [9].
 - A library of commonly used predicates [8].
 - A software cost estimation tool [10].
 - A monte carlo simulation package for Prolog [6].

Fig. 22 This document is part of the PROD delivery and documentation tool for Prolog applications. To find out more about PROD, the best place to start is [1].

10. T. Menzies. Software cost estimation: a PROD tool, 2003. Available from <http://tim.menzies.com/pdf/03omo.pdf>.
11. T. Menzies. Title: a bare-bones minimal example of PROD., 2003. Available from <http://tim.menzies.com/pdf/03prod3.pdf>.

A License

This software is distributed under the GNU General Public License.

A.1 *nowarranty.txt*

LIB comes with ABSOLUTELY NO WARRANTY: for more details type ‘warranty’.
This is free software, and you are welcome to redistribute it under certain conditions: for more details, type ‘conditions’.

A.2 *warranty.txt*

This program is free software; you can redistribute it and/or modify it under the terms of the GNU General Public License as published by the Free Software Foundation; version 2 (see <http://www.gnu.org/copyleft/gpl.html> or type ‘conditions’).

This program is distributed in the hope that it will be useful, but WITHOUT ANY WARRANTY; without even the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU General Public License for more details.

You should have received a copy of the GNU General Public License along with this program; if not, write to the Free Software Foundation, Inc., 59 Temple Place - Suite 330, Boston, MA 02111-1307, US.

A.3 *conditions.txt*

TERMS AND CONDITIONS FOR COPYING, DISTRIBUTION AND MODIFICATION

0. This License applies to any program or other work which contains a notice placed by the copyright holder saying it may be distributed under the terms of this General Public License. The ‘Program’, below, refers to any such program or work, and a ‘work based on the Program’ means either the Program or any derivative work under copyright law: that is to say, a work containing the Program or a portion of it, either verbatim or with modifications and/or translated into another language. (Hereinafter, translation is included without limitation in the term ‘modification’.) Each licensee is addressed as ‘you’.

Activities other than copying, distribution and modification are not covered by this License; they are outside its scope. The act of running the Program is not restricted, and the output from the Program is covered only if its contents constitute a work based on the Program (independent of having been made by running the Program). Whether that is true depends on what the Program does.

1. You may copy and distribute verbatim copies of the Program’s source code as you receive it, in any medium, provided that you conspicuously and appropriately publish on each copy an appropriate copyright notice and disclaimer of warranty; keep intact all the notices that refer to this License and to the absence of any warranty; and give any other recipients of the Program a copy of this License along with the Program.

You may charge a fee for the physical act of transferring a copy, and you may at your option offer warranty protection in exchange for a fee.

2. You may modify your copy or copies of the Program or any portion of it, thus forming a work based on the Program, and copy and distribute such modifications or work under the terms of Section 1 above, provided that you also meet all of these conditions:

a) You must cause the modified files to carry prominent notices stating that you changed the files and the date of any change.

b) You must cause any work that you distribute or publish, that in whole or in part contains or is derived from the Program or any part thereof, to be licensed as a whole at no charge to all third parties under the terms of this License.

c) If the modified program normally reads commands interactively when run, you must cause it, when started running for such interactive use in the most ordinary way, to print or display an announcement including an appropriate copyright notice and a notice that there is no warranty (or else, saying that you provide a warranty) and that users may redistribute the program under these conditions, and telling the user how to view a copy of this License. (Exception: if the Program itself is interactive but does not normally print such an announcement, your work based on the Program is not required to print an announcement.)

These requirements apply to the modified work as a whole. If identifiable sections of that work are not derived from the Program, and can be reasonably considered independent and separate works in themselves, then this License, and its terms, do not apply to those sections when you distribute them as separate works. But when you distribute the same sections as part of a whole which is a work based on the Program, the distribution of the whole must be on the terms of this License, whose permissions for other licensees extend to the entire whole, and thus to each and every part regardless of who wrote it.

Thus, it is not the intent of this section to claim rights or contest your rights to work written entirely by you; rather, the intent is to exercise the right to control the distribution of derivative or collective works based on the Program.

In addition, mere aggregation of another work not based on the Program with the Program (or with a work based on the Program) on a volume of a storage or distribution medium does not bring the other work under the scope of this License.

3. You may copy and distribute the Program (or a work based on it, under Section 2) in object code or executable form under the terms of Sections 1 and 2 above provided that you also do one of the following:

a) Accompany it with the complete corresponding machine-readable source code, which must be distributed under the terms of Sections 1 and 2 above on a medium customarily used for software interchange; or,

b) Accompany it with a written offer, valid for at least three years, to give any third party, for a charge no more than your cost of physically performing source distribution, a complete machine-readable copy of the corresponding source code, to be distributed under the terms of Sections 1 and 2 above on a medium customarily used for software interchange; or,

c) Accompany it with the information you received as to the offer to distribute corresponding source code. (This alternative is allowed only for noncommercial distribution and only if you received the program in object code or executable form with such an offer, in accord with Subsection b above.)

The source code for a work means the preferred form of the work for making modifications to it. For an executable work, complete source code means all the source code for all modules it contains, plus any associated interface definition files, plus the scripts used to control compilation and installation of the executable. However, as a special exception, the source code distributed need not include anything that is normally distributed (in either source or binary form) with the major components (compiler, kernel, and so on) of the operating system on which the executable runs, unless that component itself accompanies the executable.

If distribution of executable or object code is made by offering access to copy from a designated place, then offering equivalent access to copy the source code from the same place counts as distribution of the source code, even though third parties are not compelled to copy the source along with the object code.

4. You may not copy, modify, sublicense, or distribute the Program except as expressly provided under this License. Any attempt otherwise to copy, modify, sublicense or distribute the Program is void, and will automatically terminate your rights under this License. However, parties who have received copies, or rights, from you under this License will not have their licenses terminated so long as such parties remain in full compliance.

5. You are not required to accept this License, since you have not signed it. However, nothing else grants you permission to modify or distribute the Program or its derivative works. These actions are prohibited by law if you do not accept this License. Therefore, by modifying or distributing the Program (or any work based on the Program), you indicate your acceptance of this License to do so, and all its terms and conditions for copying, distributing or modifying the Program or works based on it.

6. Each time you redistribute the Program (or any work based on the Program), the recipient automatically receives a license from the original licensor to copy, distribute or modify the Program subject to these terms and conditions. You may not impose any further restrictions on the recipients' exercise of the rights granted herein. You are not responsible for enforcing compliance by third parties to this License.

7. If, as a consequence of a court judgment or allegation of patent infringement or for any other reason (not limited to patent issues), conditions are imposed on you (whether by court order, agreement or otherwise) that contradict the conditions of this License, they do not excuse you from the conditions of this License. If you cannot distribute so as to satisfy simultaneously your obligations under this License and any other pertinent obligations, then as a consequence you may not distribute the Program at all. For example, if a patent license would not permit royalty-free redistribution of the Program by all those who receive copies directly or indirectly through you, then the only way you could satisfy both it and this License would be to refrain entirely from distribution of the Program.

If any portion of this section is held invalid or unenforceable under any particular circumstance, the balance of the section is intended to apply and the section as a whole is intended to apply in other circumstances.

It is not the purpose of this section to induce you to infringe any patents or other property right claims or to contest validity of any such claims; this section has the sole purpose of protecting the integrity of the free software distribution system, which is implemented by public license practices. Many people have made generous contributions to the wide range of software distributed through that system in reliance on consistent application of that system; it is up to the author/donor to decide if he or she is willing to distribute software through any other system and a licensee cannot impose that choice.

This section is intended to make thoroughly clear what is believed to be a consequence of the rest of this License.

8. If the distribution and/or use of the Program is restricted in certain countries either by patents or by copyrighted interfaces, the original copyright holder who places the Program under this License may add an explicit geographical distribution limitation excluding those countries, so that distribution is permitted only in or among countries not thus excluded. In such case, this License incorporates the limitation as if written in the body of this License.

9. The Free Software Foundation may publish revised and/or new versions of the General Public License from time to time. Such new versions will be similar in spirit to the present version, but may differ in detail to address new problems or concerns.

Each version is given a distinguishing version number. If the Program specifies a version number of this License which applies to it and 'any later version', you have the option of following the terms and conditions either of that version or of any later version published by the Free Software Foundation. If the Program does not specify a version number of this License, you may choose any version ever published by the Free Software Foundation.

10. If you wish to incorporate parts of the Program into other free programs whose distribution conditions are different, write to the author to ask for permission. For software which is copyrighted by the Free Software Foundation, write to the Free Software Foundation; we sometimes make exceptions for this. Our decision will be guided by the two goals of preserving the free status of all derivatives of our free software and of promoting the sharing and reuse of software generally.

NO WARRANTY

11. BECAUSE THE PROGRAM IS LICENSED FREE OF CHARGE, THERE IS NO WARRANTY FOR THE PROGRAM, TO THE EXTENT PERMITTED BY APPLICABLE LAW. EXCEPT WHEN OTHERWISE STATED IN WRITING THE COPYRIGHT HOLDERS AND/OR OTHER PARTIES PROVIDE THE PROGRAM 'AS IS' WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. THE ENTIRE RISK AS TO THE QUALITY AND PERFORMANCE OF THE PROGRAM IS WITH YOU. SHOULD THE PROGRAM PROVE DEFECTIVE, YOU ASSUME THE COST OF ALL NECESSARY SERVICING, REPAIR OR CORRECTION.

12. IN NO EVENT UNLESS REQUIRED BY APPLICABLE LAW OR AGREED TO IN WRITING WILL ANY COPYRIGHT HOLDER, OR ANY OTHER PARTY WHO MAY MODIFY AND/OR REDISTRIBUTE THE PROGRAM AS PERMITTED ABOVE, BE LIABLE TO YOU FOR DAMAGES, INCLUDING ANY GENERAL, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES ARISING OUT OF THE USE OR INABILITY TO USE THE PROGRAM (INCLUDING BUT NOT LIMITED TO LOSS OF DATA OR DATA BEING RENDERED INACCURATE OR LOSSES SUSTAINED BY YOU OR THIRD PARTIES OR A FAILURE OF THE PROGRAM TO OPERATE WITH ANY OTHER PROGRAMS), EVEN IF SUCH HOLDER OR OTHER PARTY HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

END OF TERMS AND CONDITIONS