

# template.pl

Tim Menzies  
Lane Department of Computer Science and Electrical Engineering  
West Virginia University  
Morgantown, WV 26506  
tim@menzies.us

## Contents

<b>1</b>	<b>Template</b>	<b>2</b>
<b>2</b>	<b>Header */</b>	<b>2</b>
2.1	Loads . . . . .	2
2.2	Operators . . . . .	2
2.3	Flags . . . . .	2
2.4	Hooks . . . . .	2
2.5	Hacks . . . . .	3
<b>3</b>	<b>Body</b>	<b>3</b>
3.1	Utils . . . . .	3
<b>4</b>	<b>Footer */</b>	<b>3</b>
4.1	Start-ups . . . . .	3

# 1 Template

Standard Prolog file structure \*/  
/\*

## 2 Header \*/

/\*

### 2.1 Loads

Load some code using "ensure\_loaded". e.g.: \*/

```
:- ensure_loaded([xx]).
```

/\*

(Warning: there is some quirk in the Prolog loader when doing goal\_expansions. If you are using ecgs or defs, then DON'T ensure\_loaded those files; rather, load them the old-fashioned way: \*/

```
:- [ecg]. */
```

### 2.2 Operators

Change the Prolog parser using op/3x. e.g.: \*/

```
:- op(700,xfx,and).
```

/\*

### 2.3 Flags

Index predicates (with index/1) or make some dynamic (with dynamic/1) or discontinuous (with discontinuous/1) or .... e.g.: \*/

```
:- index(myemp(1,1,0,1,00)).  
:- discontinuous defs/2.  
:- mulitfile defs/2.  
:- dynamic defs/2.
```

/\*

### 2.4 Hooks

Change the Prolog parser using term\_expansion/2 and goal\_expansion/2. e.g. \*/

```
term_expansion(X and Y,Z) :- xpands(X and Y, Z).
```

```
goal_expansion(L with M and N,Z) :- tupleCompile(L with M and N,Z).
```

/\*

## 2.5 Hacks

We won't talk about these. I didn't not write these. You did not see them. \*/

```
goal_expansion(true(X,X),true).  
  
/*
```

## 3 Body

Insert your applciation code here.

### 3.1 Utils

Finally, add any general utilities last. e.g. \*/

```
barph(X) :- format('W> ~w\n',X), fail. /*
```

## 4 Footer \*/

```
/*
```

### 4.1 Start-ups

After all the above is loaded, how do we get this stuff started. \*/