

```

1  -----
2
3
4
5
6
7
8
9
10
11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28
29
30
31
32
33 local b4={}; for k,_ in pairs(_ENV) do b4[k]=k end
34 local help={}
35
36 lua 15.lua [OPTIONS]
37 (c) 2022, Tim Menzies, BSD-2-Clause
38 Explore the world better; explore it for good.
39
40 OPTIONS:
41 -cohen      -c cohen              = .35
42 -far        -F how far to seek poles = .9
43 -goal       -g goal class         = recurrence-events
44 -keep       -k items to keep      = 256
45 -K          -K manage low class counts = 1
46 -M          -M manage low evidence counts = 2
47 -minItems   -m min items in a range = .5
48 -p          -p euclidean coefficient = 2
49 -some       -S sample size for rows = 512
50 -wait       -w wait inference some items = 10
51 -want       -W range optimization goal = plan
52
53 OPTIONS, other:
54 -dump       -d stackdump on error   = false
55 -file       -f data file            = ../etc/data/breastcancer.csv
56 -help       -h show help            = false
57 -rnd        -r round numbers        = %5.2f
58 -seed       -s random number seed   = 10019
59 -todo       -t start-up action       = nothing
60 -n1         -n1 #repeated trials     = 20
61 -n2         -n2 samples per trial    = 100
62 ]]
63
64 local the
65 local r,ish,cosine -- maths tricks
66 local any,many,last,per,pop,push,sort,firsts,strif,copy,map,sum -- list tricks
67 local inc,inc2,inc3, has,has2,has3, powerset, shuffle -- more list trics
68 local words, things, thing, lines -- tricks for strings 2 things
69 local fmt,o,oo,slots,rnds,rnd -- tricks for things 2 strings
70 local cli -- tricks for settings
71 local ok,go -- tricks for test suites
72 local as, is -- tricks for objects
73 local nbl, trainl,testl,classifyl,scorel -- intro to classifiers
74 local Egs,Cols,Ratio,Nominal=is"Egs",is"Cols",is"Ratio", is"Nominal" -- data
75 local akow{} -- column creation t
76 local Nb = is"Nb" -- classifiers, round2
77 local eg={} -- demo tricks

```

```

78
79
80
81
82
83
84
85
86
87
88
89
90
91
92
93
94
95
96
97
98
99
100
101
102
103
104
105
106
107
108
109
110
111
112
113
114
115
116
117
118
119
120
121
122
123
124
125
126
127
128
129
130
131
132
133
134
135
136
137
138
139
140
141
142
143
144
145
146
147
148
149
150
151
152
153
154
155
156
157
158
159
160
161
162
163
164
165
166
167
168
169
170
171
172
173
174
175
176
177
178
179
180
181
182
183
184
185
186
187
188
189
190
191
192
193
194
195
196
197
198
199
200
201
202
203
204
205
206
207
208
209
210
211
212

```

TRICKS

maths

Maths Tricks

```

-- 'r()': Random number shorthand.
r=math.random

-- 'ish()': is 'x' is close-ish to 'y'?
-- 'cosine()': for three ABC with sides abc where does C fall between AB?
function ish(x,y,z) return math.abs(y-x) < z end
function cosine(a,b,c)
  return math.max(0,math.min(1, (a^2+c^2-b^2)/(2*c+1E-32))) end

```

lists

List Tricks

```

-- 'any()': returns any thing from a list
-- 'many()': return multiple 'any()' things.
function any(a) return a[ math.random(#a) ] end
function many(a,n, u) u={}; for j=1,n do u[1+#u] =any(a) end; return u end

-- 'last()': last item in a list
-- 'per()': p-th item in a list
function last(a) return a[ #a ] end
function per(a,p) return a[ (p*#a)//1 ] end

-- 'pop()': dump from end
-- 'push()': add to ed
function pop(a) return table.remove(a) end
function push(t,x) t[1 + #t] = x; return x end

-- 'sort()': return a list, ordered on function 'f'.
-- 'firsts()': order on sub-list first items
function sort(t,f) table.sort(t,f); return t end
function firsts(a,b) return a[1] < b[1] end
function strif(a,b) return a[1] > b[1] end

-- 'copy()': deep copy
function copy(t, u)
  if type(t)~="table" then return t end
  u={}; for k,v in pairs(t) do u[copy(k)]=copy(v) end
  return setmetatable(u, getmetatable(t)) end

-- 'map()': return a list with 'f' run over all items
function map(t,f, u) u={};for k,v in pairs(t) do u[1+#u]=f(v) end;return u end

-- 'sum()': sum all list items, filtered through 'f'
-- (which defaults to just use the ran values).
function sum(t,f, n)
  n=0; map(t,function(v) n=n+(f and f(v) or v) end)
  return n end

-- 'inc()': increment a 1,2, or 3 nested dictionary counter
function inc(f,a,n) f=f or {};f[a]=f[a] or 0) + (n or 1); return f end
function inc2(f,a,b,n) f=f or {};f[a]=inc( f[a] or {},b,n); return f end
function inc3(f,a,b,c,n) f=f or {};f[a]=inc2(f[a] or {},b,c,n);return f end

-- 'has()': implements a 1,2, or level nested lookup
function has(f,a) return f[a]
function has2(f,a,b) return f[a] and has( f[a],b) or 0 end
function has3(f,a,b,c) return f[a] and has2(f[a],b,c) or 0 end

-- 'shuffle()': randomize order (sorts in place)
function shuffle(t, j)
  for i=#t,2,-1 do j=math.random(i); t[i],t[j]=t[j],t[i] end; return t end

-- 'powerset()': return all subsets
function powerset(s)
  local t = {}
  for i = 1, #s do
    for j = 1, #t do
      t[#t+1] = {s[i],table.unpack(t[j])} end end
  return t end

```

strings '2 things

String -> Things

```

-- 'words()': split string into list of substrings
function words(s,sep, t)
  sep="([^\n" .. (sep or ",") .. "\n|)"+
  t={}; for y in s:gmatch(sep) do t[1+#t] = y end; return t end

-- 'things()': convert strings in a list to things
-- 'thing()': convert string to a thing
function things(s) return map(words(s), thing) end
function thing(x)
  x = x:match"%s*(-)%s*$"
  if x=="true" then return true elseif x=="false" then return false end
  return tonumber(x) or x end

-- 'lines()': (iterator) return lines in a file. Standard usage is
-- 'for cells in file(NAME,things) do ... end'
function lines(file,f, x)
  file = io.input(file)
  f = f or things
  return function() x=io.read(); if x then return f(x) else io.close(file) end end

```

things '2 strings

Things -> Strings

```

-- 'fmt()': String format shorthand
fmt = string.format

-- 'oo()': Print string from nested table.
-- 'o()': Generate string from nested table.
function oo(t) print(o(t)) end
function o(t, seen, u)
  if type(t)~="table" then return tostring(t) end
  seen = seen or {}
  if seen[t] then return "..." end
  seen[t] = t
  local function show1(x) return o(x, seen) end
  local function show2(k) return fmt("%s%s",k, o(t[k],seen)) end
  u = #t>0 and map(t,show1) or map(slots(t),show2)
  return (t.s or "").."{"..table.concat(u,"").."}" end

-- 'slots()': return table slots, sorted.
function slots(t, u)
  local function public(k) return tostring(k):sub(1,1) ~= "-" end
  u={};for k,v in pairs(t) do if public(k) then u[1+#u]=k end end
  return sort(u) end

-- 'rnds()': round list of numbers
-- 'rnd()': round one number.
function rnds(t,f) return map(t, function(x) return nd(x,f) end) end

```

```

213 function rnd(x,f)
214     f = not f and "%s" or number and fmt("%f",f) or f
215     return fmt(type(x)=="number" and (x~=x//1 and f) or "%s",x) end
216
217 ---
218 ---
219 ---
220 ---
221 --- ### Make settings from help string and CLI (command-line interface)
222 --- 'cli()': In a string, look for lines indented with two spaces, starting with
223 --- a dash.
224 --- Each such line should have a long and short flag, some help text
225 --- and (at end of line), a default values. e.g.
226 ---
227 ---         -seed -S set the random number seed = 10019
228 ---
229 --- Each line generates a setting with key "seed" and
230 --- default value "10019". If the command line contains one of the flags
231 --- ('-seed' or '-s') then update those defaults.
232 function cli(help)
233     local d,used = {},{}
234     help:gsub("\n ([-|^%s+)][%s]+(-|^%s+)]^\n)%s([%s]+)",
235         function(long,key,short,x)
236             assert(not used[short], "repeated short flag ["..short.."]")
237             used[short]=short
238             for n,flag in ipairs(arg) do
239                 if flag==short or flag==long then
240                     x = x=="false" and true or x=="true" and "false" or arg[n+1] end end
241                 d[key] = x==true and true or thing(x) end
242             if d.help then os.exit(print(help)) end
243             return d end
244 ---
245 ---
246 ---
247 --- ### Test suites
248 --- 'ok()': maybe, print stack dump on errors.
249 --- Increment the 'fails' counter on failed 'test'.
250 function ok(tests,test,msg)
251     print(test and " PASS:" or " FAIL:",msg or "")
252     if not test then
253         tests._fails = tests._fails+1
254         if the and the.dump then assert(test,msg) end end end
255
256 --- 'go()': run some 'tests', controlled by 'settings'.
257 --- Maybe update the '_fails' counter.
258 --- Return the total fails to the operating system.
259 function go(settings,tests,b4, defaults)
260     tests._fails = 0
261     defaults={}; for k,v in pairs(settings) do defaults[k]=v end
262     local todo = settings.todo or "all"
263     for k,one in pairs(todo=="all" and slots(tests) or {todo}) do
264         if k ~= "main" and type(tests[one]) == "function" then
265             for k,v in pairs(defaults) do settings[k]=v end
266             math.randomseed(settings.seed or 1)
267             print(fmt("#%s",one))
268             tests[one](tests) end end
269     if b4 then
270         for k,v in pairs(_ENV) do
271             if not b4[k] then print("???",k,type(v)) end end end
272     os.exit(tests._fails) end
273 ---
274 ---
275 ---
276 ---
277 ---
278 --- ### Objects
279 --- 'new()': make a new instance.
280 --- 'class()': define a new class of instances
281 as = setmetatable
282 function is(s, t)
283     t={tostring=o,s=s or ""}; t.index=t
284     return as(t, {call=function(...) return t.new(...) end}) end
285

```

```

285 ---
286 ---
287 ---
288 ---
289 ---
290 --- ## Intro to Classifiers
291 function nbl(file)
292     local i = {h={}, nh=0,e={}, names=nil, n=0, wait=the.wait, log={}}
293     for row in lines(file) do
294         if not i.names then i.names=row else test1(i,row); train1(i,row) end end
295     return score1(i.log) end
296
297 function train1(i,t)
298     i.n = i.n + 1
299     if not i.h[t[#t]] then i.nh = i.nh + 1 end
300     inc(i.h, t[#t])
301     for col,x in pairs(t) do if x=="?" then inc3(i.e,col,x,t[#t]) end end end
302
303 function test1(i,t)
304     if i.n > i.wait then push(i.log,{want=t[#t], got=classify1(i,t)}) end end
305
306 function classify1(i,t)
307     local hi,out = -1
308     for h,_ in pairs(i.h) do
309         local prior = ((i.h[h] or 0) + the.K)/(i.n + the.K*i.nh)
310         local l = prior
311         for col,x in pairs(t) do
312             if x ~= "?" and col ~= #t then
313                 l=l*(has3(i.e,col,x,h) + the.M*prior)/((i.h[h] or 0) + the.M) end end
314             if l>hi then hi,out=l,h end end
315         return out end
316
317 function score1(log, n)
318     n=0; for _,x in pairs(log) do if x.want==x.got then n=n+1 end end
319     return n/#log end
320

```

```

320 -----
321 --- EGS
322 ---
323 ---
324 ---
325 -- ## Egs
326 -- Egs store examples (in 'rows'), summarized in columns (in 'cols')
327 function Egs:new(names) return as({rows={}, cols=Cols(names)}, Egs) end
328
329 function Egs:new4file(file, i)
330   for _,row in lines(file) do if i then i:add(row) else i=Egs(row) end end
331   return i end
332
333 function Egs.add(i,t)
334   t = t.cells or t -- detail (for future extension)
335   push(i.rows, map(i.cols.all, function(col) return col:add(t[col.at]) end)) end
336
337 function Egs.mid(i,cols) return map(cols or i.cols.all, function(col) return col
338   :mid() end) end
339
340 function Egs.clone(i) return Egs(i.cols.names) end
341
342 function Egs.klass(i,row) return row[i.cols.klass.at] end
343
344 -- ## Col
345 -- Convert names into various Column types.
346 ako.ratio = function(x) return x:find("[A-Z]" end
347 ako.goal = function(x) return x:find("[+]" end
348 ako.klass = function(x) return x:find("$" end
349 ako.ignore = function(x) return x:find("$" end
350 ako.less = function(x) return x:find("-$" end
351
352 -- Every new column goes into 'all'. Also, for any column that we we
353 -- are not ignoring, then that also gets added to (a) either the list
354 -- of 'x' independent columns or 'y' dependent columns; and (b) maybe,
355 -- the 'klass' slot.
356 function Cols:new(names)
357   local i = as({names=names, klass=nil, all={}, x={}, y={}, Cols)
358   for at,name in pairs(names) do
359     local col = (ako.ratio(name) and Ratio or Nominal)(at,name)
360     col.is_goal = ako.goal(name)
361     push(i.all, col)
362     if not ako.ignore(name) then
363       if ako.klass(name) then i.klass = col end
364       push(ako.goal(name) and i.y or i.x, col) end end
365   return i end
366
367 -- ## Nominal
368 -- Summarize symbols in 'Nominal's
369 function Nominal:new(at,name)
370   at,name = at or 0, name or ""
371   return as({at=at, name=name, n=0, has={}, mode=nil, most=0}, Nominal) end
372
373 function Nominal.add(i,x)
374   if x ~= "?" then
375     i.n=i.n+1
376     i.has[x] = 1 + (i.has[x] or 0)
377     if i.has[x] > i.most then i.most, i.mode = i.has[x], x end end
378   return x end
379
380 function Nominal.mid(i) return i.mode end
381
382 -- ## Ratio
383 -- Summarize numbers in 'Ratio's
384 function Ratio:new(at,name)
385   at,name = at or 0, name or ""
386   return as({at=at, name=name, n=0, mu=0, m2=0, sd=0, w=ako.less(name) and -1 or
387     1}, Ratio) end
388
389 function Ratio.add(i,x)
390   if x ~= "?" then
391     i.n=i.n+1
392     local d= x - i.mu
393     i.mu = i.mu + d/i.n
394     i.m2 = i.m2 + d*(x - i.mu)
395     i.sd = ((i.m2<0 or i.n<2) and 0) or ((i.m2/(i.n - 1))^0.5)
396     i.lo = i.lo and math.min(x, i.lo) or x
397     i.hi = i.hi and math.max(x, i.hi) or x end
398   return x end
399
400 function Ratio.mid(i) return i.mu end
401

```

```

399 -----
400 --- NBNNLM
401 ---
402 ---
403 ---
404 -- ## Add likelihood calculators
405 function Egs.like(i,t,prior)
406   local like = prior
407   for at,x in pairs(t) do
408     local col = i.cols.all[at]
409     if not col.is_goal then
410       like = like * (x=="?" and 1 or i.cols.all[at]:like(x,prior)) end end
411   return like end
412
413 function Ratio.like(i,x,prior)
414   if x < i.mu - 3*i.sd then return 0 end
415   if x > i.mu + 3*i.sd then return 0 end
416   local denom = (math.pi*2*i.sd^2)^.5
417   local nom = math.exp(1)^(-(x-mu)^2/(2*i.sd^2+1E-32))
418   return nom/(denom + 1E-32) end
419
420 function Nominal.like(i,x,prior)
421   return ((i.has[x] or 0) + the.M*prior)/(i.n + the.M) end
422
423 -- ## Create and update
424 function Nb:new()
425   return as({h={}, all=nil, nh=0, n=0, wait=the.wait, log={},Nb) end
426
427 function Nb:new4file(file, i)
428   i = Nb()
429   for row in lines(file) do i:add(row) end end
430
431 function Nb.add(i,row)
432   if not i.all then print(1); i.all = Nb(row) else i:test(row); i:train(row) end
433   end
434
435 -- ## Train, test, classify
436 function Nb:train(i,t)
437   i.n = i.n + 1
438   print(2,o(i.all))
439   local h = i.all:klass(t)
440   print(3)
441   if not i.h[h] then i.nh = i.nh + 1; i.h[h] = i.all:clone() end
442   i.h[h]:add(row)
443   i.all:add(row) end
444
445 function Nb:test(i,t)
446   if i.n > i.wait then push(i.log, {want=i.all:klass(t), got=classify(i,t)}) end
447   end
448
449 function Nb.classify(i,t)
450   local hi,out = -1
451   for klass,h in pairs(i.h) do
452     local prior = (h.n + the.K) / (i.n + the.K*i.nh)
453     local like = h:like(t,prior)
454     if like > hi then hi,out=like,klass end end
455   return out end
456
457 -- ## Score
458 function Nb.score(i, n)
459   n=0 for _,x in pairs(i.log) do if x.want==x.got then n=n+1 end end
460   return n/#i.log end
461

```

```

459 --- -----
460 ---
461 --- DEMOS
462 ---
463
464 -- ## Demos
465 function eg.last(tst)
466   ok(tst, 30 == last{10,20,30}, "lasts") end
467
468 function eg.per(tst, t)
469   t={};for i=1,100 do push(t,i*1000) end
470   ok(tst,70000 == per(t,.7), "per") end
471
472 function eg.many(tst, t)
473   t={};for i=1,100 do push(t,i) end; many(t,10) end
474
475 function eg.sum(tst, t)
476   t={};for i=1,100 do push(t,i) end; ok(tst,5050==sum(t),"sum") end
477
478 function eg.shuffle(tst, t, good)
479   t={1,2,3,4,5,6,7,8,9}
480   good = true
481   for j=1,10^5 do
482     t= shuffle(t);
483     good = good and sum(t)==45,"shuffle"..j end
484   ok(tst,good, "shuffling") end
485
486 function eg.powersets(tst, t)
487   ok(tst,1024==#powerset{1,2,3,4,5,6,7,8,9,10}) end
488
489 function eg.inc(tst, f)
490   f=inc3({},"a","b","c"); oo(f)
491   f=inc2({},"a","b"); oo(f)
492   f=inc({},"a"); oo(f)
493 end
494
495 function eg.nb(tst, abcd)
496   print(nbl("../etc/data/breastcancer.csv")) end
497
498 function eg.nbnum(tst, i)
499   i=Egs({"Clndrs", "Volume", "Hp.", "Lbs-", "Acc+", "Model", "origin", "Mpg+"})
500   print("nx::"); map(i.cols.x,oo)
501   print("ny::"); map(i.cols.y,oo) end
502
503 function eg.nbtest(tst)
504   Nb:new4file("../etc/data/diabetes.csv") end
505

```

```

506 --- -----
507 ---
508 --- START UP
509 ---
510 -- ## Statup
511 the=cli(help)
512
513 go(the, eg, b4)

```