

```

1  -----
2  ---
3  ---
4  ---
5  ---
6  ---
7  ---
8  ---
9  ---
10 ---
11 ---
12 ---
13 ---
14 ---
15 ---
16 ---
17 ---
18 ---
19 ---
20 ---
21 ---
22 ---
23 ---
24 ---
25 ---
26 ---
27 ---
28 ---
29 ---
30 ---
31 ---
32 local b4={}; for k, _ in pairs(_ENV) do b4[k]=k end
33 local the
34 local help=[[
35
36 lua 15.lua [OPTIONS]
37 (c) 2022, Tim Menzies, BSD-2-Clause
38 Explore the world better; explore it for good.
39
40 OPTIONS:
41 -cohen      -c cohen              = .35
42 -far        -F how far to seek poles = .9
43 -goal       -g goal class          = recurrence-events
44 -keep       -k items to keep       = 256
45 -K          -K manage low class counts = 1
46 -M          -M manage low evidence counts = 2
47 -minItems   -m min items in a range = .5
48 -p          -p euclidean coefficient = 2
49 -some       -S sample size for rows = 512
50 -wait       -W wait inference some items = 10
51 -want       -W range optimization goal = plan
52
53 OPTIONS, other:
54 -dump       -d stackdump on error    = false
55 -file       -f data file              = ../etc/data/breastcancer.csv
56 -help       -h show help              = false
57 -rnd        -r round numbers          = %5.2f
58 -seed       -s random number seed    = 10019
59 -todo       -t start-up action        = nothing
60 -n1         -n1 #repeated trials     = 20
61 -n2         -n2 samples per trial     = 100
62 ]]

```

```

63 ---
64 ---
65 ---
66 ---
67 ---
68 ---
69 ---
70 ---
71 local r,ish,cosine
72
73 --- **r(): Random number shorthand.
74 r=math.random
75
76 --- **ish(): is 'x' is close-ish to 'y'?
77 --- **cosine(): for three ABC with sides abc,
78 --- where does C falls on the line running AB?
79 function ish(x,y,z) return math.abs(y -x ) < z end
80 function cosine(a,b,c)
81   return math.max(0,math.min(1, (a^2+c^2-b^2)/(2*c+1E-32))) end
82
83 ---
84 ---
85 ---
86 ---
87 ---
88 local any,many,last,per,pop,push,sort,firsts,strif,copy,map,sum
89 local inc,inc2,inc3, has,has2,has3, powerset, shuffle
90 --- **any(): returns any thing from a list
91 --- **many(): return multiple **any() things.
92 function any(a) return a[math.random(#a)] end
93 function many(a,n, u) u={}; for j=1,n do u[1+#u] =any(a) end; return u end
94
95 --- **last(): last item in a list
96 --- **per(): p-th item in a list
97 function last(a) return a[#a] end
98 function per(a,p) return a[(p*#a)//1] end
99
100 --- **pop(): dump from end
101 --- **push(): add to ed
102 function pop(a) return table.remove(a) end
103 function push(t,x) t[1 + #t] = x; return x end
104
105 --- **sort(): return a list, ordered on function 'f'.
106 --- **firsts(): order on sub-list first items
107 function sort(t,f) table.sort(t,f); return t end
108 function firsts(a,b) return a[1] < b[1] end
109 function strif(a,b) return a[1] > b[1] end
110
111 --- **copy(): deep copy
112 function copy(t, u)
113   if type(t)~="table" then return t end
114   u={}; for k,v in pairs(t) do u[copy(k)]=copy(v) end
115   return setmetatable(u, getmetatable(t)) end
116
117 --- **map(): return a list with 'f' run over all items
118 function map(t,f, u) u={};for k,v in pairs(t) do u[1+#u]=f(v) end;return u end
119
120 --- **sum(): sum all list items, filtered through 'f'
121 --- (which defaults to just use the ran values).
122 function sum(t,f, n)
123   n=0; map(t,function(v) n=n+(f and f(v) or v) end)
124   return n end
125
126 --- **inc(): increment a 1,2, or 3 nested dictionary counter
127 function inc(f,a,n) f=f or {};f[a]=f[a] or 0 + (n or 1); return f end
128 function inc2(f,a,b,n) f=f or {};f[a]=inc(f[a] or {},b,n); return f end
129 function inc3(f,a,b,c,n) f=f or {};f[a]=inc2(f[a] or {},b,c) or 0 end
130
131 --- **has(): implements a 1,2, or level nested lookup
132 function has(f,a) return f[a] or 0 end
133 function has2(f,a,b) return f[a] and has(f[a],b) or 0 end
134 function has3(f,a,b,c) return f[a] and has2(f[a],b,c) or 0 end
135
136 --- **shuffle(): randomize order (sorts in place)
137 function shuffle(t, j)
138   for i=#t,2,-1 do j=math.random(i); t[i],t[j]=t[j],t[i] end; return t end
139
140 --- **powerset(): return all subsets
141 function powerset(s)
142   local t = {}
143   for i = 1, #s do
144     for j = 1, #t do
145       t[#t+1] = {s[i],table.unpack(t[j])} end end
146   return t end
147
148 ---
149 ---
150 ---
151 ---
152 local words, things, thing, lines
153
154 --- **words(): split string into list of substrings
155 function words(s,sep, t)
156   sep="([^\n... (sep or ".") .. "]+)"
157   t={}; for y in s:gmatch(sep) do t[1+#t] = y end; return t end
158
159 --- **things(): convert strings in a list to things
160 --- **thing(): convert string to a thing
161 function things(s) return map(words(s), thing) end
162 function thing(x)
163   x = x:match("%s*(~)%s*$")
164   if x=="true" then return true elseif x=="false" then return false end
165   return tonumber(x) or x end
166
167 --- **lines(): (iterator) return lines in a file. Standard usage is
168 --- 'for cells in file(NAME,things) do ... end'
169 function lines(file,f, x)
170   file = io.input(file)
171   f = f or things
172   return function() x=io.read(); if x then return f(x) else io.close(file) end end
173
174 ---
175 ---
176 ---
177 ---
178 ---
179 local fmt,o,oo,slots,rnds,rnd
180
181 --- **fmt(): String format shorthand
182 fmt = string.format
183
184 --- **oo(): Print string from nested table.
185 --- **o(): Generate string from nested table.
186 function oo(t) print(o(t)) end
187 function o(t, seen, u)
188   if type(t)~="table" then return tostring(t) end
189   seen = seen or {}
190   if seen[t] then return "..." end
191   seen[t] = t
192   local function show1(x) return o(x, seen) end
193   local function show2(k) return fmt("%s%s",k, o(t[k],seen)) end
194   u = #t>0 and map(t,show1) or map(slots(t),show2)
195   return (t.s or "").."{"..table.concat(u, ",").."}" end
196
197 --- **slots(): return table slots, sorted.

```

```

198 function slots(t, u)
199     local function public(k) return tostring(k):sub(1,1) ~= "-" end
200     u={};for k,v in pairs(t) do if public(k) then u[l+#u]=k end end
201     return sort(u) end
202
203 -- **rnds()**: round list of numbers
204 -- **rnd()**: round one number.
205 function rnds(t,f) return map(t, function(x) return nd(x,f) end) end
206 function rnd(x,f)
207     f = not f and "%s" or number and fmt("%%%sf",f) or f
208     return fmt(type(x)=="number" and (x~x//1 and f) or "%s",x) end
209
210 ---
211 ---
212 ---
213
214 -- ### Make settings from help string and CLI (command-line interface)
215 local cli
216
217 -- **cli()**: In a string, look for lines indented with two spaces, starting with a dash.
218 -- Each such line should have a long and short flag, some help text
219 -- and (at end of line), a default values. e.g.
220
221 -- -seed -S set the random number seed = 10019
222
223 -- Each line generates a setting with key "seed" and
224 -- default value "10019". If the command line contains one of the flags
225 -- ('-seed' or '-s') then update those defaults.
226 function cli(help)
227     local d,used = {},{}
228     help:gsub("\n ([^%s+)]([%s+)](-[^%s+)]^\n)%s([%s+)]",
229         function(long,key,short,x)
230             assert(not used[short], "repeated short flag ["..short.."]")
231             used[short]=short
232             for n,flag in ipairs(arg) do
233                 if flag==short or flag==long then
234                     x = x=="false" and true or x=="true" and "false" or arg[n+1] end end
235             d[key] = x==true and true or thing(x) end
236             if d.help then os.exit(print(help)) end
237             return d end
238
239 ---
240 ---
241
242 -- ### Test suites
243 local ok,go
244
245 -- **ok()**: maybe, print stack dump on errors.
246 -- Increment the 'fails' counter on failed 'test'.
247 function ok(tests,test,msg)
248     print(test and " PASS:" or " FAIL:",msg or "")
249     if not test then
250         tests.ails = tests.ails+1
251         if the and the.dump then assert(test,msg) end end end
252
253 -- **go()**: run some 'tests', controlled by 'settings'.
254 -- Maybe update the 'ails' counter.
255 -- Return the total fails to the operating system.
256 function go(settings,tests,b4, defaults)
257     tests.ails = 0
258     defaults={}; for k,v in pairs(settings) do defaults[k]=v end
259     local todo = settings.todo or "all"
260     for k,one in pairs(todo=="all" and slots(tests) or {todo}) do
261         if k ~= "main" and type(tests[one]) == "function" then
262             for k,v in pairs(defaults) do settings[k]=v end
263             math.randomseed(settings.seed or 1)
264             print(fmt("#%s",one))
265             tests[one](tests) end end
266     if b4 then
267         for k,v in pairs(_ENV) do
268             if not b4[k] then print("??",k,type(v)) end end end
269     os.exit(tests.ails) end
270
271 ---
272 ---
273 ---
274
275 -- ### Objects
276 local as, is
277
278 -- **new()**: make a new instance.
279 -- **class()**: define a new class of instances
280 as = setmetatable
281 function is(s, t)
282     t={tostring=o,s=s or ""}; t.index=t
283     return as(t, {call=function(...) return t.new(...) end}) end
284
285
286
287
288
289
290
291
292
293
294
295
296
297
298
299
300
301
302
303
304
305
306
307
308
309
310
311
312
313
314
315
316
317
318
319
320
321
322

```

```

322 -----
323 ---
324 --- EGS
325 ---
326
327 -- ## Egs
328 -- Egs store examples (in 'rows'), summarized in columns (in 'cols')
329 function Egs:new(names) return as({rows={}, cols=Cols(names)}, Egs) end
330
331 function Egs:new4file(file, i)
332   for _,row in lines(file) do if i then i:add(row) else i=Egs(row) end end
333   return i end
334
335 function Egs.add(i,t)
336   t = t.cells or t -- detail (for future extension)
337   push(i.rows, map(i.cols.all, function(col) return col:add(t[col.at]) end)) end
338
339 function Egs.mid(i,cols) return map(cols or i.cols.all, function(col) return col
340   :mid() end) end
341
342 function Egs.clone(i) return Egs(i.cols.names) end
343
344 function Egs.klass(i,row) return row[i.cols.klass.at] end
345
346 -- ## Col
347 -- Convert names into various Column types.
348 local ako={}
349 ako.ratio = function(x) return x:find("[A-Z]" end
350 ako.goal = function(x) return x:find("[~!]" end
351 ako.klass = function(x) return x:find("$" end
352 ako.ignore = function(x) return x:find("$" end
353 ako.less = function(x) return x:find("-$" end
354
355 -- Every new column goes into 'all'. Also, for any column that we we
356 -- are not ignoring, then that also gets added to (a) either the list
357 -- of 'x' independent columns or 'y' dependent columns; and (b) maybe,
358 -- the 'klass' slot.
359 function Cols:new(names)
360   local i = as({names=names, klass=nil,all={}, x={}, y={}, Cols)
361   for at,name in pairs(names) do
362     local col = (ako.ratio(name) and Ratio or Nominal)(at,name)
363     col.is_goal = ako.goal(name)
364     push(i.all, col)
365     if not ako.ignore(name) then
366       if ako.klass(name) then i.klass = col end
367       push(ako.goal(name) and i.y or i.x, col) end end
368     return i end
369
370 -- ## Nominal
371 -- Summarize symbols in 'Nominal's
372 function Nominal:new(at,name)
373   at,name = at or 0, name or ""
374   return as({at=at, name=name, n=0, has={}, mode=nil, most=0}, Nominal) end
375
376 function Nominal.add(i,x)
377   if x ~= "" then
378     i.n = i.n+1
379     i.has[x] = 1 + (i.has[x] or 0)
380     if i.has[x] > i.most then i.most, i.mode = i.has[x], x end end
381   return x end
382
383 function Nominal.mid(i) return i.mode end
384
385 -- ## Ratio
386 -- Summarize numbers in 'Ratio's
387 function Ratio:new(at,name)
388   at,name = at or 0, name or ""
389   return as({at=at, name=name, n=0, mu=0, m2=0, sd=0, w=ako.less(name) and -1 or
390     1}, Ratio) end
391
392 function Ratio.add(i,x)
393   if x ~= "" then
394     i.n = i.n+1
395     local d= x - i.mu
396     i.mu = i.mu + d/i.n
397     i.m2 = i.m2 + d*(x - i.mu)
398     i.sd = ((i.m2<0 or i.n<2) and 0) or ((i.m2/(i.n - 1))^0.5)
399     i.lo = i.lo and math.min(x, i.lo) or x
400     i.hi = i.hi and math.max(x, i.hi) or x end
401   return x end
402
403 function Ratio.mid(i) return i.mu end
404
405 -- ## Return
406 return {Egs=Egs, Ratio=Ratio, Nominal=Nominal}

```

```

405 -----
406

```

```

406 -- ## Demos
407 local eg={}
408 function eg.last(tst)
409   ok(tst, 30 == last{10,20,30}, "lasts") end
410
411 function eg.per(tst, t)
412   t={};for i=1,100 do push(t,i*1000) end
413   ok(tst,70000 == per(t,.7), "per") end
414
415 function eg.many(tst, t)
416   t={};for i=1,100 do push(t,i) end; many(t,10) end
417
418 function eg.sum(tst, t)
419   t={};for i=1,100 do push(t,i) end; ok(tst,5050==sum(t),"sum")end
420
421 function eg.shuffle(tst, t, good)
422   t={1,2,3,4,5,6,7,8,9}
423   good = true
424   for j=1,10^5 do
425     t= shuffle(t);
426     good = good and sum(t)==45,"shuffle"..j end
427   ok(tst,good, "shuffling") end
428
429 function eg.powersets(tst, t)
430   ok(tst,1024==#powerset{1,2,3,4,5,6,7,8,9,10}) end
431
432 function eg.inc(tst, f)
433   f=inc3({}, "a", "b", "c"); oo(f)
434   f=inc2({}, "a", "b"); oo(f)
435   f=inc({}, "a"); oo(f)
436 end
437
438 function eg.nb(tst, abcd)
439   print(nb1("../etc/data/breastcancer.csv")) end
440
441

```

```

441 --- -----
442 ---
443 ---  START UP
444 ---
445
446 -- ## Statup
447 the=cli(help)
448
449 go(the, eg, b4)

```