

```

1  -----
2  ---
3  ---
4  ---
5  ---
6  ---
7  ---
8  ---
9  ---
10 ---
11 ---
12 ---
13 ---
14 ---
15 ---
16 ---
17 ---
18 ---
19 ---
20 ---
21 ---
22 ---
23 ---
24 ---
25 -----
26 local b4={}; for k,_ in pairs(_ENV) do b4[k]=k end
27 local the,help={},{}
28
29 lua l5.lua [OPTIONS]
30 L5 == a very little LUA learning lab
31
32 OPTIONS (inference):
33 -boot -b P #bootstrap samples          DEFAULT
34 -cohen -c F cohen's small effect size    256
35 -cliffs -C F threshold on Cliff's delta  .35
36 -far -F F look no further than "far"     .147
37 -keep -k items to keep in a number      .9
38 -leaves -l leaf size                    512
39 -conf -n F confidence for stats tests    .5
40 -p -p P distance calcs coefficient       .05
41 -seed -S P random number seed          10019
42 -some -s look only at "some" items      512
43
44 OPTIONS (housekeeping):
45 -dump -d on error, exit+ stacktrace      false
46 -file -f S where to get data             ./etc/data/auto93.csv
47 -help -h show help                      false
48 -rnd -r S format string                  %5.2f
49 -todo -t S start-up action               nothing
50 ]]
51 -----
52 --[[
53 Copyright 2022, Tim Menzies
54
55 Redistribution and use in source and binary forms, with or without
56 modification, are permitted provided that the following conditions
57 are met:
58
59 1. Redistributions of source code must retain the above copyright
60 notice, this list of conditions and the following disclaimer.
61
62 2. Redistributions in binary form must reproduce the above copyright
63 notice, this list of conditions and the following disclaimer in the
64 documentation and/or other materials provided with the distribution.
65
66 THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS
67 "AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT
68 LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS
69 FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE
70 COPYRIGHT HOLDER OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT,
71 INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING,
72 BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES;
73 LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER
74 CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT
75 LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN
76 ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE
77 POSSIBILITY OF SUCH DAMAGE. --]]
78
79 -----
80 -- ## Coding Conventions
81 --
82 -- - All config options in "the" (which is generated by parsing the help text)
83 -- - LOTS OF SHORT FUNCTIONS
84 -- - Line width = 80
85 -- - when you can, write functions down on one line
86 -- - "i" not "self" (so we can fit more on each line)
87 -- - for loop index variables, do not use i. try j,k instead.
88 -- - if something holds a list of thing, name the holding variable "all"
89 -- - no inheritance
90 -- - only define a method if that is for polymorphism
91 -- - all config items into a global "the" variable
92 -- - all the test cases (or demos) are "function Demo.xxx".
93 -- - If test case assertion crashed, add "1" to Demo.fail
94 -- - On exit return the value of Demo.fail as the exit status
95 -- - random seed reset so carefully, just once, at the end of the code.
96 -- - usually, no line with just "end" on it

```

```

97 -----
98 ---
99 ---
100 ---
101 ---
102 --- This code reads data from csv files (where "?" denotes "missing value").
103 local is={}
104 function is.missing(x) return x=="?" end
105
106 -- The names on row1 of that file define the role of that column.
107 -- Names in row1 ending with ":" are to be ignored
108 function is.skip(x) return x:find"$" end
109
110 -- Names in row1 starting in upper case are numbers
111 function is.num(x) return x:find"[A-Z]" end
112
113 -- Names in row1 ending with "!" are classes.
114 function is.class(x) return x:find"$" end
115
116 -- Names in row1 ending with "-" are objectives to be minimized.
117 function is.less(x) return x:find"$" end
118
119 -- Names in row1 ending with "+" are objectives to be maximized.
120 function is.more(x) return x:find"+$" end
121
122 -- Objectives or classes are dependent variables.
123 function is.dependent(x) return is.more(x) or is.less(x) or is.class(x) end
124
125 -- For example, in this data file, we will ignore column 3 (Hp:),
126 -- try to minimize weight (Lbs-) and maximize acceleration and
127 -- miles per hour (Acc+, Mpg+). Also, with one exception (origin),
128 -- everything is numeric. Finally, there are some missing values on
129 -- lines 3 and lines 7.
130
131 ---
132 ---
133 ---
134 ---
135 ---
136 ---
137 ---
138 ---
139 ---
140 ---
141 ---
142 ---
143 ---
144 ---
145 ---
146 ---
147 ---
148 ---
149 ---
150 ---
151 ---
152 ---
153 ---
154 ---
155 ---
156 ---
157 ---
158 ---
159 ---
160 ---
161 ---
162 ---
163 ---
164 ---
165 ---
166 ---
167 ---
168 ---
169 ---
170 ---
171 ---
172 ---
173 ---
174 ---
175 ---
176 ---
177 ---
178 ---
179 ---
180 ---
181 ---
182 ---
183 ---
184 ---
185 ---
186 ---
187 ---
188 ---
189 ---
190 ---
191 ---
192 ---
193 ---
194 ---
195 ---
196 ---
197 ---
198 ---
199 ---
200 ---
201 ---
202 ---
203 ---
204 ---
205 ---

```

```

206 -----
207 --- MISC TOOLS
208 ---
209 ---
210 ---
211 local r = math.random
212 local fmt = string.format
213 local unpack = table.unpack
214 local function push(t,x) table.insert(t,x); return x end
215 ---
216 ---
217 ---
218 local thing,things,file2things
219 function thing(x)
220 x = x:match("%s*(-)%s*$")
221 if x=="true" then return true elseif x=="false" then return false end
222 return tonumber(x) or x end
223 ---
224 function things(x,sep, t)
225 t={}; for y in x:gmatch(sep or "([^\s]+)") do t[1+#t]=thing(y) end
226 return t end
227 ---
228 function file2things(file, x)
229 file = io.input(file)
230 return function()
231 x=io.read();
232 if x then return things(x) else io.close(file) end end end
233 ---
234 ---
235 ---
236 ---
237 local last,per,any,many
238 function last(a) return a[#a] end
239 function per(a,p) return a[(p*#a)//1] end
240 function any(a) return a[math.random(#a)] end
241 function many(a,n, u) u={}; for j=1,n do push(u,any(a)) end; return u end
242 ---
243 ---
244 ---
245 local firsts,sort,map,slots,copy
246 function firsts(a,b) return a[1] < b[1] end
247 function sort(t,f) table.sort(t,f); return t end
248 function map(t,f, u) u={};for k,v in pairs(t) do push(u,f(v)) end; return u end
249 function slots(t, u,s)
250 u={}
251 for k,v in pairs(t) do s=tosstring(k);if s:sub(1,1)~="_" then push(u,k) end end
252 return sort(u) end
253 ---
254 function copy(t, u)
255 if type(t)~="table" then return t end
256 u={}; for k,v in pairs(t) do u[copy(k)]=copy(v) end
257 return setmetatable(u, getmetatable(t)) end
258 ---
259 ---
260 ---
261 ---
262 ---
263 local oo,o, rnd, rnds
264 function oo(t) print(o(t)) end
265 function o(t,seen, key,xseen,u)
266 seen = seen or {}
267 if type(t)~="table" then return tostring(t) end
268 if seen[t] then return "..." end
269 seen[t] = t
270 key = function(k) return fmt("%.5s %s",k,o(t[k],seen)) end
271 xseen = function(x) return o(x,seen) end
272 u = #t>0 and map(t,xseen) or map(slots(t),key)
273 return (t.is or "")..'{'..table.concat(u,"")..'}' end
274 ---
275 function rnds(t,f) return map(t, function(x) return rnd(x,f) end) end
276 function rnd(x,f)
277 return fmt(type(x)=="number" and (x~=x//1 and f or the.rnd) or "%s",x) end
278 ---
279 ---
280 ---
281 local Demo, ok = {fails=0}
282 function ok(test,msg)
283 print(test and "PASS:" or "FAIL:",msg or "")
284 if not test then
285 Demo.fails=Demo.fails+1
286 if the.dump then assert(test,msg) end end end
287 ---
288 function Demo.main(todo,seed)
289 for k,one in pairs(todo=="all" and slots(Demo) or {todo}) do
290 if k ~="main" and type(Demo[one]) == "function" then
291 math.randomseed(seed)
292 Demo[one]() end end
293 for k,v in pairs(_ENV) do if not b4[k] then print("?",k,type(v)) end end
294 return Demo.fails end
295 ---
296 ---
297 ---
298 ---
299 local function settings(txt, d)
300 d={}
301 txt:gsub("\n ([-]|([^\s]+))([^\s]+)([^\s]+)[^\n]*%s([^\s]+)",
302 function(long,key,short,x)
303 for n,flag in ipairs(arg) do
304 if flag==short or flag==long then
305 x = x=="false" and true or x=="true" and "false" or arg[n+1] end end
306 if x=="false" then the[key]=false elseif x=="true" then the[key]=true else
307 d[key] = tonumber(x) or x end end
308 if d.help then print(txt) end
309 return d end

```

```

310 -----
311 --- USE CASES
312 ---
313 ---
314 ---
315 ---
316 --- update cols
317 ---
318 ---
319 local add
320 function add(i,x, inc)
321 inc = inc or 1
322 if not is.missing(x) then
323 i.n = i.n + inc
324 i:internalAdd(x,inc) end
325 return x end
326 ---
327 function Sym.internalAdd(i,x,inc)
328 i.all[x] = inc + (i.all[x] or 0)
329 if i.all[x] > i.most then i.most, i.mode = i.all[x], x end end
330 ---
331 function Num.internalAdd(i,x,inc, d)
332 for j=1,inc do
333 d = x - i.mu
334 i.mu = i.mu + d/i.n
335 i.m2 = i.m2 + d*(x - i.mu)
336 i.sd = (i.m2<0 or i.n<2) and 0 or ((i.m2/(i.n-1))^0.5)
337 i.lo = math.min(x, i.lo)
338 i.hi = math.max(x, i.hi)
339 if i.all < the.keep then i.ok=false; push(i.all,x)
340 elseif r() < the.keep/i.n then i.ok=false; i.all[r(#i.all)]=x end end end
341 ---
342 function Num.sorted(i)
343 if not i.ok then i.all = sort(i.all) end
344 i.ok=true
345 return i.all end
346 ---
347 ---
348 ---
349 local file2Egs -- not "local data" (since defined above)
350 function data(i,row)
351 push(i.all, row)
352 for _,col in pairs(i.cols) do add(col, row[col.at]) end
353 return i end
354 ---
355 function file2Egs(file, i)
356 for row in file2things(file) do
357 if i then data(i,row) else i = Egs(row) end end
358 return i end
359 ---
360 ---
361 ---
362 local mids
363 function mids(i,rows,cols) return i:clone(rows):mid(cols) end
364 ---
365 function Egs.mid(i,cols)
366 return map(cols or i.y,function(col) return col:mid(i) end) end
367 ---
368 function Sym.mid(i) return i.mode end
369 function Num.mid(i) return i.mu end
370 ---
371 function Num.div(i) return i.sd end
372 function Sym.div(i, e)
373 e=0; for _,n in pairs(i.all) do e = e + n/i.n*math.log(n/i.n,2) end
374 return -e end
375 ---
376 ---
377 ---
378 local far,furthest,neighbors,dist
379 function far(i,r1,rows,far)
380 return per(neighbors(i,r1,rows),far or the.far)[2] end
381 ---
382 function furthest(i,r1,rows)
383 return last(neighbors(i,r1,rows))[2] end
384 ---
385 function neighbors(i,r1,rows)
386 return sort(map(rows, function(r2) return {dist(i,r1,r2),r2} end),firsts) end
387 ---
388 function dist(i,row1,row2, d,n,a,b,inc)
389 d,n = 0,0
390 for _,col in pairs(i.x) do
391 a,b = row1[col.at], row2[col.at]
392 inc = is.missing(a) and is.missing(b) and 1 or col:dist1(a,b)
393 d = d + inc*the.p
394 n = n + 1 end
395 return (d/n)^(1/the.p) end
396 ---
397 function Sym.dist1(i,a,b) return a==b and 0 or 1 end
398 ---
399 function Num.dist1(i,a,b)
400 if is.missing(a) then b=i:norm(b); a=b<.5 and 1 or 0
401 elseif is.missing(b) then a=i:norm(a); b=a<.5 and 1 or 0
402 else a,b = i:norm(a), i:norm(b) end
403 return math.abs(a - b) end
404 ---
405 function Num.norm(i,x)
406 return i.hi - i.lo < 1E-32 and 0 or (x - i.lo)/(i.hi - i.lo) end

```

```

407 --- c | | | | | | | |
408 ---
409 local half, cluster, clusters
410 function half(i, rows, project, row, some, left, right, lefts, rights, c, mid)
411 function project(row, a, b)
412 a = dist(i, left, row)
413 b = dist(i, right, row)
414 return {(a^2 + c^2 - b^2)/(2*c), row}
415 end
416 some = many(rows, the.some)
417 left = furthest(i, any(some), some)
418 right = furthest(i, left, some)
419 c = dist(i, left, right)
420 lefts, rights = {}, {}
421 for n, projection in pairs(sort(map(rows, project), firsts)) do
422 if n == #rows//2 then mid = row end
423 push(n <= #rows//2 and lefts or rights, projection[2]) end
424 return lefts, rights, left, right, mid, c end
425
426 function cluster(i, rows, here, lefts, rights)
427 rows = rows or i.all
428 here = {all=rows}
429 if #rows >= 2* (#i.all)^the.leaves then
430 lefts, rights, here.left, here.right, here.mid = half(i, rows)
431 if #lefts < #rows then
432 here.lefts = cluster(i, lefts)
433 here.rights = cluster(i, rights) end end
434 return here end
435
436 function clusters(i, format, t, pre, front)
437 if t then
438 pre = pre or ""
439 front = fmt("%s%s", pre, #t.all)
440 if not t.lefts and not t.rights then
441 print(fmt("%-20s", front, o(rnds(mids(i, t.all), format))))
442 else
443 print(front)
444 clusters(i, format, t.lefts, "|" .. pre)
445 clusters(i, format, t.rights, "|" .. pre) end end end

```

```

447 --- c | | | | | | | |
448 ---
449 local merge, merged, spans, bestSpan
450 function Sym.spans(i, j)
451 local xys, all, one, last, x, y, n = {}, {}
452 for x, n in pairs(i.all) do push(xys, {x, "lefts", n}) end
453 for x, n in pairs(j.all) do push(xys, {x, "rights", n}) end
454 for _, tmp in ipairs(sort(xys, firsts)) do
455 x, y, n = unpack(tmp)
456 if x == last then
457 last = x
458 one = push(all, {lo=x, hi=x, all=Sym(i.at, i.name)}) end
459 add(one.all, y, n) end
460 return all end
461
462 function Num.spans(i, j)
463 local xys, all, lo, hi, gap, one, x, y, n = {}, {}
464 lo, hi = math.min(i.lo, j.lo), math.max(i.hi, j.hi)
465 gap = (hi - lo) / (6/the.cohen)
466 for _, n in pairs(i.all) do push(xys, {n, "lefts", 1}) end
467 for _, n in pairs(j.all) do push(xys, {n, "rights", 1}) end
468 one = {lo=lo, hi=hi, all=Sym(i.at, i.name)}
469 all = {one}
470 for _, tmp in ipairs(sort(xys, firsts)) do
471 x, y, n = unpack(tmp)
472 if one.hi - one.lo > gap
473 then one = push(all, {lo=one.hi, hi=x, all=one.all:clone()}) end
474 one.hi = x
475 add(one.all, y, n) end
476 all = merge(all)
477 all[1].lo = -math.huge
478 all[#all].hi = math.huge
479 return all end
480
481 function merge(b4, j, n, now, a, b, both)
482 j, n, now = 0, #b4, {}
483 while j < #b4 do
484 j = j+1
485 a, b = b4[j], b4[j+1]
486 if b then
487 both = a.all:merged(b.all)
488 if both
489 then a = {lo=a.lo, hi=b.hi, all=both}
490 j = j + 1 end end
491 push(now, a) end
492 return #now == #b4 and b4 or merge(now) end
493
494 function Sym.merge(i, j, k)
495 k = i:clone()
496 for x, n in pairs(i.all) do add(k, x, n) end
497 for x, n in pairs(j.all) do add(k, x, n) end
498 return k end
499
500 function Sym.merged(i, j, k, ei, ej, ek)
501 k = i:merge(j)
502 ei, ej, ek = i:div(), j:div(), k:div()
503 if ek*.99 <= (i.n*ei + j.n*ej)/k.n then return k end end
504
505 function spans(egs1, egs2, spans, tmp, coll, col2)
506 spans = {}
507 for c, coll in pairs(egs1.x) do
508 col2 = egs2.x[c]
509 tmp = coll:spans(col2)
510 if #tmp > 1 then
511 for _, one in pairs(tmp) do push(spans, one) end end end
512 return spans end
513
514 function bestSpan(spans)
515 local divs, ns, n, div, stats, dist2heaven = Num(), Num()
516 function dist2heaven(s) return {(1 - n(s))^2 + (0 - div(s))^2}^0.5, s} end
517 function div(s) return divs:norm(s.all:div()) end
518 function n(s) return ns:norm(s.all.n) end
519 for _, s in pairs(spans) do
520 add(divs, s.all:div())
521 add(ns, s.all.n) end
522 return sort(map(spans, dist2heaven), firsts)[1][2] end
523
524 ---
525 ---
526 ---
527
528 local xplain, xplains, selects, spanShow
529 function xplain(i, rows, used, stop, here, left, right, lefts0, rights0, lefts1, rights1)
530 used = used or {}
531 rows = rows or i.all
532 here = {all=rows}
533 stop = (#i.all)^the.leaves
534 if #rows >= 2*stop then
535 lefts0, rights0, here.left, here.right, here.mid, here.c = half(i, rows)
536 if #lefts0 < #rows then
537 here.selector = bestSpan(spans(i:clone(lefts0), i:clone(rights0)))
538 push(used, {here.selector.all.name, here.selector.lo, here.selector.hi})
539 lefts1, rights1 = {}, {}
540 for _, row in pairs(rows) do
541 push(selects(here.selector, row) and lefts1 or rights1, row) end
542 if #lefts1 > stop then here.lefts = xplain(i, lefts1, used) end
543 if #rights1 > stop then here.rights = xplain(i, rights1, used) end end end
544 return here end
545
546 function xplains(i, format, t, pre, how, sel, front)
547 pre, how = pre or "", how or ""
548 if t then
549 pre = pre or ""
550 front = fmt("%s%s%s", pre, how, #t.all, t.c and rnd(t.c) or "")
551 if t.lefts and t.rights then print(fmt("%-35s", front)) else
552 print(fmt("%-35s", front, o(rnds(mids(i, t.all), format))))
553 end
554 sel = t.selector
555 xplains(i, format, t.lefts, "|" .. pre, spanShow(sel, "."))
556 xplains(i, format, t.rights, "|" .. pre, spanShow(sel, true) .. ":") end end
557
558 function selects(span, row, lo, hi, at, x)
559 lo, hi, at = span.lo, span.hi, span.all.at
560 x = row[at]
561 if is.missing(x) then return true end
562 if lo == hi then return x == lo else return lo <= x and x < hi end end
563
564 function spanShow(span, negative, hi, lo, x, big)
565 if not span then return "" end
566 lo, hi, x, big = span.lo, span.hi, span.all.name, math.huge
567 if not negative
568 then if lo == hi then return fmt("%s==%s", x, lo) end
569 if hi == big then return fmt("%s>=%s", x, lo) end
570 if lo == -big then return fmt("%s<=%s", x, hi) end
571 return fmt("%s<=%s<%s", lo, x, hi)
572 else if lo == hi then return fmt("%s!=%s", x, lo) end
573 if hi == big then return fmt("%s<%s", x, lo) end
574 if lo == -big then return fmt("%s>=%s", x, hi) end
575 return fmt("%s<%s and %s>=%s", x, lo, x, hi) end end
576
577 ---
578 ---
579
580 local quintiles, smallfx, bootstrap
581 function quintiles(ts, width, nums, out, all, n, m)
582 width = width or 32

```

```

583 nums=Num(); for _,t in pairs(ts) do
584     for _,x in pairs(sort(t)) do add(nums,x) end end
585 all,out = nums.all, {}
586 for _,t in pairs(ts) do
587     local s, where = {}
588     where = function(n) return (width*nums:norm(n))/1 end
589     for j = 1, width do s[j]=" " end
590     for j = where(per(t,.1)), where(per(t,.3)) do s[j]="-" end
591     for j = where(per(t,.7)), where(per(t,.9)) do s[j]="-" end
592     s[where(per(t,.5))]= " "
593     push(out,{display=table.concat(s),
594             data = t,
595             pers = map({.1,.3,.5,.7,.9},
596                       function(p) return rnd(per(t,p))end)}) end
597 return out end
598
599 function smallfx(xs,ys,      x,y,lt,gt,n)
600     lt,gt,n = 0,0,0
601     if #ys > #xs then xs,ys=ys,xs end
602     for _,x in pairs(xs) do
603         for j=1, math.min(64,#ys) do
604             y = any(ys)
605             if y<x then lt=lt+1 end
606             if y>x then gt=gt+1 end
607             n = n+1 end end
608     return math.abs(gt - lt) / n <= the.cliffs end
609
610 function bootstrap(y0,z0)
611     local x, y, z, b4, yhat, zhat, bigger
612     local function obs(a,b, c)
613         c = math.abs(a.mu - b.mu)
614         return (a.sd + b.sd) == 0 and c or c/((x.sd^2/x.n + y.sd^2/y.n)^.5) end
615     local function adds(t, num)
616         num = num or Num(); map(t, function(x) add(num,x) end); return num end
617     y,z = adds(y0), adds(z0)
618     x = adds(y0, adds(z0))
619     b4 = obs(y,z)
620     yhat = map(y.all, function(y1) return y1 - y.mu + x.mu end)
621     zhat = map(z.all, function(z1) return z1 - z.mu + x.mu end)
622     bigger = 0
623     for j=1,the.boot do
624         if obs( adds(many(yhat,#yhat)), adds(many(zhat,#zhat))) > b4
625             then bigger = bigger + 1/the.boot end end
626     return bigger >= the.conf end
627
628 -- function scottKnot(nums,the,      all,cohen)
629 -- local mid = function(z) return z.some:mid()
630 -- end -----
631 -- local function summary(i,j,      out)
632 --     out = copy( nums[i] )
633 --     for k = i+1, j do out = out:merge(nums[k]) end
634 --     return out
635 -- end -----
636 -- local function div(lo,hi,rank,b4,      cut,best,l1,l,r,r1,now)
637 --     best = 0
638 --     for j = lo,hi do
639 --         if j < hi then
640 --             l = summary(lo, j)
641 --             r = summary(j+1, hi)
642 --             now = (l.n*(mid(l) - mid(b4))^2 + r.n*(mid(r) - mid(b4))^2
643 --                   ) / (l.n + r.n)
644 --             if now > best then
645 --                 if math.abs(mid(l) - mid(r)) >= cohen then
646 --                     cut, best, l1, r1 = j, now, copy(l), copy(r)
647 --                 end end end end
648 --                 if cut and not l1:same(r1,the) then
649 --                     rank = div(lo, cut, rank, l1) + 1
650 --                     rank = div(cut+1, hi, rank, r1)
651 --                 else
652 --                     for i = lo,hi do nums[i].rank = rank end end
653 --                 return rank
654 --             end -----
655 --         table.sort(nums, function(x,y) return mid(x) < mid(y) end)
656 --         all = summary(1,#nums)
657 --         cohen = all.sd * the.iota
658 --         div(l, #nums, 1, all)
659 --         return nums end
660
661 -----
662 ---
663 ---
664 ---
665 ---
666 function Demo.the() oo(the) end
667
668 function Demo.many(a)
669     a={1,2,3,4,5,6,7,8,9,10}; ok("{1023}" == o(many(a,3)), "manys") end
670
671 local function normal(m,s)
672     local pi, sqrt, cos, log = math.pi, math.sqrt, math.cos, math.log
673     local function z() return sqrt(-2*log(r())) * cos(2* pi * r()) end
674     return m + s*z() end
675
676 function Demo.tiles()
677     local function ns(m,s,r,      u)
678     u={}; for j=1,r do u[1+#u] = normal(m,s) end; return u end
679     local ts={}
680     local m=100
681     for mu=8,12,.25 do ts[1+#ts] = ns(mu, 5, m) end
682     ts= sort(map(ts,sort), function(a,b) return per(a,.5) < per(b,.5) end)
683     for j,one in pairs(quintiles(ts,20)) do
684         print(fmt("%s",one.display),o(one.pers),
685               smallfx( ts[1], ts[j]),
686               bootstrap(ts[1], ts[j])) end end
687
688 function Demo.stats( t1,t2,inc,n,a,b)
689     for _,n in pairs{20} do --25,50,100,250,500,1000 do
690         inc=1
691         while inc < 3 do
692             print("")
693             t1={}; for j=1,n do push(t1, j*r()) end
694             t2={}; for j,x in pairs(t1) do t2[j]=x+inc end
695             a,b = smallfx(t1,t2), bootstrap(t1,t2)
696             for _,x in pairs(quintiles(t1,t2)) do print(rnd(inc), x.display,a,b) end
697             inc = inc*1.1 end end end
698
699 function Demo.stats1(x)
700     x1={0.34, 0.49, 0.51, 0.6}
701     x2={ 0.6, 0.7, 0.8, 0.9}
702     x3={ 0.15, 0.25, 0.4, 0.35}
703     x4={ 0.6, 0.7, 0.8, 0.9}
704     x5={0.1, 0.2, 0.3, 0.4}
705     print(bootstrap(x5,x3))
706     print(bootstrap(x3,x1))
707     print(bootstrap(x1,x2))
708     print(bootstrap(x2,x4))
709 end
710
711 function Demo.egs()
712     ok(5140==file2Egs(the.file).y[1].hi,"reading") end
713
714 function Demo.dist(i)
715     i = file2Egs(the.file)
716     for n,row in pairs(i.all) do print(n,dist(i, i.all[1], row)) end end
717
718 function Demo.far( i,j,row1,row2,row3,d3,d9)
719     i = file2Egs(the.file)
720     for j=1,10 do
721         row1 = any(i.all)
722         row2 = far(i,row1, i.all, .9)
723         d9 = dist(i,row1,row2)
724         row3 = far(i,row1, i.all, .3)
725         d3 = dist(i,row1,row3)
726         ok(d3 < d9, "closer far") end end
727
728 function Demo.half( i, lefts, rights)
729     i = file2Egs(the.file)
730     lefts, rights = half(i, i.all)
731     oo(mids(i, lefts))
732     oo(mids(i, rights))
733     end
734
735 function Demo.cluster( i)
736     i = file2Egs(the.file)
737     clusters(i,"%0f",cluster(i)) end
738
739 function Demo.spans( i, lefts, rights)
740     i = file2Egs(the.file)
741     lefts, rights = half(i, i.all)
742     oo(bestSpan(spans(i:clone(lefts), i:clone(rights)))) end
743
744 function Demo.xplain( i,j,tmp,lefts,rights,used)
745     i = file2Egs(the.file)
746     used={}
747     xplains(i,"%0f",xplain(i, i.all,used))
748     map(sort(used,function(a,b)
749         return ((a[1] < b[1]) or
750               (a[1]==b[1] and a[2] < b[2]) or
751               (a[1]==b[1] and a[2]==b[2] and a[3] < b[3]))end),oo) end
752
753 -----
754 the = settings(help)
755 Demo.main(the.todo, the.seed)

```