```
\_\\
\'_\\
                                                                                                                                                              , <u>, i ,</u> , / / /
                                Ва
                                                          Bad <
                                                                                                planning= (better - bad)
monitor = (bad - better)
                                          56
                                                         В
                                                                   5
                                                                           Better
 local b4={}; for k,_ in pairs(_ENV) do b4[k]=k end
local help=[[
       -bins -b
                                            number of bins
       -bins -b
-cohen -c
-file -f
-goal -g
-K -K -M
-m -m
-seed -S
-todo -t
-wait -w
                                             cohen
file name
goal
                                                                                                                                    = .35
= ../etc/data/breastcancer.csv
= recurrence-events
                                           = 10019
local max,min,ent,per
local push,map,sort,up1,upx,down1,slots,up1,down1
local words,thing, things, lines
local words,thing, things, lines
local cli
local fmt,o,oo
local inc,inc2,inc3,has,has2,has3
local rogues
local classify,test,train,score,nb1,nb2,abcd
local bins,nb3
local eg,the,ako={},{},{}
                        CO | 1 | 1 | 1 | 7 | 5 0 - 5
local ako={}
ako.num = function(x) return x:find"^[A-Z]" end
ako.goal = function(x) return x:find"[-+!]" end
ako.klass = function(x) return x:find"[5" end
ako.less = function(x) return x:find"[5" end
ako.less = function(x) return x:find"[5" end
         BSD 2-Clause License
Copyright (c) 2022, Tim Menzies
         Redistribution and use in source and binary forms, with or without modification, are permitted provided that the following conditions are met:
-- 1. Redistributions of source code must retain the above copyright notice, this list of conditions and the following disclaimer.

-- 2. Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution.
         Redistributions in binary form must reproduce the above copyright notice,
this list of conditions and the following disclaimer in the documentation
and/or other materials provided with the distribution.
        THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS"
AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE
IMPLIED WARRANTIES OF MERCHANTABILITY & FITNESS FOR A PARTICULAR PURPOSE ARE
DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT HOLDER OR CONTRIBUTORS BE LIABLE
FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL
DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR
SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER
CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY,
OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE
OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
```

```
BHSI
 function classify(i,t)
      unction classify(i,t)
local hi,out = -1
for h, _ in pairs(i.h) do
local prior = ((i.h(h) or 0) + the.K)/(i.n + the.K*i.nh)
local 1 = prior
for col, x in pairs(t) do
    if x ~= "?" and col ~= #t then
        l=1*(has3(i.e,col,x,h) + the.M*prior)/((i.h[h] or 0) + the.M) end end
if l>hi then hi,out=1,h end end
return out end
 function test(i,t)
  if i.n > i.wait then push(i.log, {want=t[#t], got=classify(i,t)}) end end
function train(i,t)
  local more, kl = false, t[#t]
  for col,x in pairs(t) do
    if x ~="?" then
                      fx == :: Lien
more = true
inc3 (i.e, col, x, kl)
if col == #t then
inc2(kl==the.goal and i.best or i.rest, col,x) end end end
        if more then
    i.n = i.n + 1
    if not i.h[kl] then i.nh = i.nh + 1 end
               inc(i,h, kl)

if kl==the.goal then i.bests=i.bests+1 else i.rests=i.rests+1 end end end
       motion score(i)
local acc,out=0,{}
for _,x in pairs(i.log) do if x.want==x.got then acc=acc+1/#i.log end end
for col,xns in pairs(i.best) do
    for x,b in pairs(xns) do
    local r1 = has2(i.rest,col,x)/i.rests
    local b1 = b/i.bests
    push(out, {100* (b1^2/(b1+r1))//1, col,x,b}) end end
return acc, sort(out,down1) end
vv | -|- |-<sub>|</sub> (7_ vv (_|
function nb2(file, log)
local tmp, i, create, update, discretize, discretize1 = {}
i = {b={}, nb=0,e={}, names=nil, n=0, wait=the.wait,
bests=0,rests=0,best={}, rest={},log=log or {},
hi={},lo={}, nums={}}
        function create(t)
  for j,txt in pairs(t) do
    if ako.num(txt) then i.nums[j] = {lo=1E32, hi=-1E32} end end; return t end
        function update(t, x)
for j,n in pairs(i.nums) do
    x=t[j]
if x-="?" then n.lo=min(x,n.lo); n.hi=max(x,n.hi) end end; return t end
            function discretize(x, j)
if x = """ then
    n = i.nums[j]
    x = n and (x - n.lo) // ((n.hi - n.lo+1E-32) / the.bins) or x end
                    return x end
         for row in lines(file) do
       if not i.names then i.names = create(row) else push(tmp,update(row)) end end
for _,row in pairs(tmp) do
  row=collect(row,discretize)
        test(i,row); train(i,row) end
return i end
                         function abcd(gotwants, show)
local i, exists, add, report, pretty = {
   data=data or "data", rx= rx or "rx",known={},a={},b={},c={},d={},yes=0,no=0}
        function exists(x, n
  new = not i.known[x]
  inc(i.known,x)
  if new then
                      i.a[x]=i.yes + i.no; i.b[x]=0; i.c[x]=0; i.d[x]=0 end end
      i.a(x)=i.yes + i.no; i.b(x)=0; i.c(x)=0; i.a(x)=0 end end
function report(
    p = function (z) return math.floor(100*z + 0.5) end
    out= {}
    for x, in pairs( i.known ) do
        pd,pf,pn,prec,g,f,acc = 0,0,0,0,0,0,0
        a= (i.a(x) or 0); b= (i.b(x) or 0); c= (i.c(x) or 0); d= (i.d(x) or 0);
    if b+d > 0 then pd = d / (b+d) end
    if a+c > 0 then pf = c / (a+c) end
    if a+c > 0 then pn = (b+d) / (a+c) end
    if a+c > 0 then pr = c / (c+d) end
    if i-pf+pd > 0 then pz=*(1-pf) * pd / (1-pf+pd) end
    if i-pg+pd > 0 then fz=*prec*pd / (prec + pd) end
    if i.yes + i.no > 0 then
        acc = i.yes / (i.yes + i.no) end
    out[x] = {data=i.data,rx=i.rx,num=i.yes+i.no,a=a,b=b,c=c,d=d,acc=p(acc), precturn out end
end
end
end
                return out end
         function pretty(t)
            unction pretty(t)
print""
local s1 = "\(0\) \(\%\) \(0\) \(\%\) \(\%\) \(\%\) \(\%\) \(\%\) \(\%\) \(\%\) \(\%\) \(\%\) \(\%\) \(\%\) \(\%\) \(\%\) \(\%\) \(\%\) \(\%\) \(\%\) \(\%\) \(\%\) \(\%\) \(\%\) \(\%\) \(\%\) \(\%\) \(\%\) \(\%\) \(\%\) \(\%\) \(\%\) \(\%\) \(\%\) \(\%\) \(\%\) \(\%\) \(\%\) \(\%\) \(\%\) \(\%\) \(\%\) \(\%\) \(\%\) \(\%\) \(\%\) \(\%\) \(\%\) \(\%\) \(\%\) \(\%\) \(\%\) \(\%\) \(\%\) \(\%\) \(\%\) \(\%\) \(\%\) \(\%\) \(\%\) \(\%\) \(\%\) \(\%\) \(\%\) \(\%\) \(\%\) \(\%\) \(\%\) \(\%\) \(\%\) \(\%\) \(\%\) \(\%\) \(\%\) \(\%\) \(\%\) \(\%\) \(\%\) \(\%\) \(\%\) \(\%\) \(\%\) \(\%\) \(\%\) \(\%\) \(\%\) \(\%\) \(\%\) \(\%\) \(\%\) \(\%\) \(\%\) \(\%\) \(\%\) \(\%\) \(\%\) \(\%\) \(\%\) \(\%\) \(\%\) \(\%\) \(\%\) \(\%\) \(\%\) \(\%\) \(\%\) \(\%\) \(\%\) \(\%\) \(\%\) \(\%\) \(\%\) \(\%\) \(\%\) \(\%\) \(\%\) \(\%\) \(\%\) \(\%\) \(\%\) \(\%\) \(\%\) \(\%\) \(\%\) \(\%\) \(\%\) \(\%\) \(\%\) \(\%\) \(\%\) \(\%\) \(\%\) \(\%\) \(\%\) \(\%\) \(\%\) \(\%\) \(\%\) \(\%\) \(\%\) \(\%\) \(\%\) \(\%\) \(\%\) \(\%\) \(\%\) \(\%\) \(\%\) \(\%\) \(\%\) \(\%\) \(\%\) \(\%\) \(\%\) \(\%\) \(\%\) \(\%\) \(\%\) \(\%\) \(\%\) \(\%\) \(\%\) \(\%\) \(\%\) \(\%\) \(\%\) \(\%\) \(\%\) \(\%\) \(\%\) \(\%\) \(\%\) \(\%\) \(\%\) \(\%\) \(\%\) \(\%\) \(\%\) \(\%\) \(\%\) \(\%\) \(\%\) \(\%\) \(\%\) \(\%\) \(\%\) \(\%\) \(\%\) \(\%\) \(\%\) \(\%\) \(\%\) \(\%\) \(\%\) \(\%\) \(\%\) \(\%\) \(\%\) \(\%\) \(\%\) \(\%\) \(\%\) \(\%\) \(\%\) \(\%\) \(\%\) \(\%\) \(\%\) \(\%\) \(\%\) \(\%\) \(\%\) \(\%\) \(\%\) \(\%\) \(\%\) \(\%\) \(\%\) \(\%\) \(\%\) \(\%\) \(\%\) \(\%\) \(\%\) \(\%\) \(\%\) \(\%\) \(\%\) \(\%\) \(\%\) \(\%\) \(\%\) \(\%\) \(\%\) \(\%\) \(\%\) \(\%\) \(\%\) \(\%\) \(\%\) \(\%\) \(\%\) \(\%\) \(\%\) \(\%\) \(\%\) \(\%\) \(\%\) \(\%\) \(\%\) \(\%\) \(\%\) \(\%\) \(\%\) \(\%\) \(\%\) \(\%\) \(\%\) \(\%\) \(\%\) \(\%\) \(\%\) \(\%\) \(\%\) \(\%\) \(\%\) \(\%\) \(\%\) \(\%\) \(\%\) \(\%\) \(\%\) \(\%\) \(\%\) \(\%\) \(\%\) \(\%\) \(\%\) \(\%\) \(\%\) \(\%\) \(\%\) \(\%\) \(\%\) \(\%\) \(\%\) \(\
```

208

```
|-|-|-|-|-|-
   min = math.min
max = math.max
   function per(t,p) return t[ (p or .5)*#t//1 ] end
   function ent(t)
     local n=0; for _,m in pairs(t) do n = n+m end
local n=0; for _,m in pairs(t) do if m>0 then e= e+m/n*math.log(m/n,2) end end
return -e end
   function rogues()
  for k,v in pairs(_ENV) do if not b4[k] then print("??",k,type(v)) end end end
            function push(t,x) t[1 + #t] = x; return x end
   function map(t, f, u) u={}; for k,v in pairs(t) do u[1+\sharpu]=f(v) end; return u end function collect(t,f, u) u={}; for k,v in pairs(t) do u[k]=f(v,k) end; return u end d
   function sort(t,f) table.sort(t,f); return t end
   function slots(t, u)
local function public(k) return tostring(k):sub(1,1) ~= "_" end
u={};for k,v in pairs(t) do if public(k) then u[1+#u]=k end end
return sort(u) end
           function words (s, sep, t)  sep="([^n" \dots (sep \ or ",") \dots "]+)" \\ t=\{\}; \ \textbf{for} \ y \ \textbf{in} \ s: gmatch (sep) \ \textbf{do} \ t[1+\#t] \ = \ y \ \textbf{end}; \ \textbf{return} \ t \ \textbf{end} 
    function things(s) return map(words(s), thing) end
   function lines(file,f,
   file = io.input(file) f
    f = f or things
    return function() x=io.read(); if x then return f(x) else io.close(file) end end end
            363
366
367 fmt = string.format
   function oo(t) print(o(t)) end
  function o(t, seen, u)
  if type(t)~="table" then return tostring(t) end
  seen = seen or {}
  if seen[t] then return "..." end
  seen[t] = t
  local function show1(x) return o(x, seen) end
  local function show2(k) return fmt(":%%%%",k, o(t[k],seen)) end
  u = #t>0 and map(t,show1) or map(slots(t),show2)
  return (t.s or "")..."{"..table.concat(u,"")..."}" end
```

```
| Section | Sect
```