```
-- CODING CONVENTIONS:
     -- Leading__upper_case : class
                                                                                                            : instance var
: reference to a library function
: some internal function, variable
     -- type hints: where practical, on function arguments,
     -- - t = table
     -- - class names in lower case denote vars of that class
   --- suffix s denotes table of things
local 1 = require"lib"
local the = 1.settings[[
RL.LUA : stings
(c)2022 Tim Menzies <timm@ieee.org> BSD(2clause).
USAGE:
          lua rlgo.lua [ -bFghksS [ARG] ]
   OPTIONS:
-b --bins
-F --Far
                                                               discretization control
in "far", how far to seek
start-up action
                                                             start-up action = pass show help = pass ekep only these nums = 256 distance coefficient = 2 random number see = 10019 in "far", how many to search = 512]]
                           --keep
   local About= {} -- factory for making columns
  local Data = {| -- store rows, and their column summaries | local Row = {| -- store sone row. | local Row = {| -- stores one row. | local Col = {| -- stores one row. | local Col = {| -- stores one row. | local Col = {| -- stores one row. | local Col = {| -- stores one row. | local Col = {| -- stores one row. | local Col = {| -- stores one row. | local Col = {| -- stores one row. | local Col = {| -- stores one row. | local Col = {| -- stores one row. | local Col = {| -- stores one row. | local Col = {| -- stores one row. | local Col = {| -- stores one row. | local Col = {| -- stores one row. | local Col = {| -- stores one row. | local Col = {| -- stores one row. | local Col = {| -- stores one row. | local Col = {| -- stores one row. | local Col = {| -- stores one row. | local Col = {| -- stores one row. | local Col = {| -- stores one row. | local Col = {| -- stores one row. | local Col = {| -- stores one row. | local Col = {| -- stores one row. | local Col = {| -- stores one row. | local Col = {| -- stores one row. | local Col = {| -- stores one row. | local Col = {| -- stores one row. | local Col = {| -- stores one row. | local Col = {| -- stores one row. | local Col = {| -- stores one row. | local Col = {| -- stores one row. | local Col = {| -- stores one row. | local Col = {| -- stores one row. | local Col = {| -- stores one row. | local Col = {| -- stores one row. | local Col = {| -- stores one row. | local Col = {| -- stores one row. | local Col = {| -- stores one row. | local Col = {| -- stores one row. | local Col = {| -- stores one row. | local Col = {| -- stores one row. | local Col = {| -- stores one row. | local Col = {| -- stores one row. | local Col = {| -- stores one row. | local Col = {| -- stores one row. | local Col = {| -- stores one row. | local Col = {| -- stores one row. | local Col = {| -- stores one row. | local Col = {| -- stores one row. | local Col = {| -- stores one row. | local Col = {| -- stores one row. | local Col = {| -- stores one row. | local Col = {| -- stores one row. | local 
  -- FYI: I considered splitting Col into two (one for -- NOMinals and one for RATIOs). But as shown in Col (below), -- one of those two cases can usually be handled as a -- one-liner. So the benefits of that reory is not large.
              One nuance here is that Rows are created by the FIRST table and then shared
            One nuance here is that kows are created by the risk table and then shared with any other Data that uses that Row (e.g. if some Data is clustered into sub-Datas). This means that that (a) the total memory used is saved (since the same Row can be used by multiple tables) and (b) that Row can be used as palce to store behavior stats across the whole the contract of the property of the contract of 
              say, distance).
              Factory for making columns.
     function About.new(sNames)
  return About._cols({names=sNames, all={}, x={}, y={}, klass=nil},sNames) end
               How to recognize different column types
  -- How to recognize different column types local _is=' - ratio cols start with uppercase goal = "[!+-|S" -- !+klass, [*, -]-maximize,minimize klass = "[$" -- klass if ";" skip = ".5", -- klass if ";" less = ".5", -- minimize if "-"
 -- Turn a list of column names into Col objects. If the new col is independent
-- or dependent or a goal attribute then remember that in i.x or i.y or i.klass.
function About__cols(i,sNames)
for at_name in pairs(sNames) do
local col = l.push(i.all, Col.new(name,at))
if not name:find(_is.skip) then
l.push(name:find(_is.gaal) and i.y or i.x, col)
if name:find(_is.klass) then i.klass=col end end end
return ie
  -- Update, only the non-skipped cols (i.e. those found in i.x and j.x. function About.add(i,t) local row = t.cells and t or Row.new(i, t) for __cols in pairs(i.x.i.y) do for __coll in pairs(cols) do
                            Col.add(coll, row.cells[coll.at]) end end
              return row end
     -- Hold one record
function Row.new(about.t)
           return {_about=about, cells=t, cooked=1.map(t,1.same)} end
            - Everything in rows, sorted by distance to i.
  -- Everything in rows, soften by distance to 1: function Row.acound(i,rows) local fun = function(j) return {row=j, d=Row.dist(i,j)} end return 1.sort(1.map(rows, fun), 1.1t"d") end
          - Recommend sorting i before j (since i is better).
     function Row.better(i, j)
       Function Row.better(1,j)
i.evaled, j.evaled=true,true
local sl, s2,d,n,x,y=0,0,0,0
local ys,e = i._about.y,math.exp(l)
for _,col in pairs(ys) do
x,y= i.ells[col.at], j.cells[col.at]
x,y= Col.norm(col,x), Col.norm(col,y)
sl = sl - e'(Col.w * (x-y)/#ys)
s2 = s2 - e^(Col.w * (y-x)/#ys) end
return sl/#ys < s2/#ys end
 -- Distance
function Row.dist(i,j)
local d,n,x,y,dist|=0,0
local cols = cols or i, about.x
for cols = cols or cols do
x, y = i, cells[col.at], j,cells[col.at]
a = d + Col.dist(col,x,y)^the.p
            n = n + 1 end
return (d/n)^{(1/the.p)} end
```

```
-- Summarize one column.
function Col.new(txt,at)
           txt = txt or ""

return {n = 0,
    at = at or 0,
                                                                                                                                                                                                -- how many items seen?
-- position ot column
-- column header
                                                         -- Update. Optically, repeat n times.
function Col.add(i,x, n)
if x ~= "?" then
n = n or 1
                        if i.isNom then i._has[x] = n + (i._has[x] or 0) else
for _ = 1,n do
                                     if pos then
  i.ok=false -- kept items are no longer sorted
                                                            i._has[pos]=x end end end end end
        - Distance. If missing values, assume max distance.
function Col.dist(i,x,y)
function Col.dist(i,x,y)
function in the color of the colo
                  Diversity: divergence from central tendency (sd,entropy for NOM,RATIO).
function of divergence from tentral tendency (supericle) for nows, Arity).

function of divergence from tentral tendency (supericle) for the following from tentral tendency (supericle) for the following from tentral tendency (supericle) for the following from tendency (supericle) for t
                Sorted contents
   -- Sorted contents
function Col.has(i)
if i.isNom then return i._has else
if not i.ok then table.sort(i._has) end
                           i.ok=true
return i. has end end
   - Central transency (mode, median for NOMs, RATIOs) function Col.mid(i) if not i.isNom then return l.per(Col.has(i),.5) else local mode, most=nil,-1 for k,v in pairs(i_has) do if v>most then mode, most=k,v end end return mode end end
   - Return num, scaled to 0.1 for lo..hi
function Col.norm(i,y)
if i.isNom then return x else
local has= Col.has(i) -- "a" contains all our numbers, sorted.
local lo,hi = has[1], has[$has]
return hi - lo < 1E-9 and 0 or (x-lo)/(hi-lo) end end
           — Map x to a small range of values. For NOMs, x maps to itself. unction Col.discretize(i, x) if i.isNow then return x else
                        local has = has(i) has[#has]
local lo,hi = has[1], has[#has]
local b = (hi - lo)/the.bins
return hi==lo and l or math.floor(x/b+.5)*b end end
```

page 3

```
--- Holds n records
function Data.new(t) return {rows={}, about=About.new(t) } end
   function Data.add(i,t) 1.push(i.rows, About.add(i.about,t)) end
    -- Replicate structure
function Data.clone(i, t)
  local out = Data.new(i.about.names)
         for _,row in pairs(t or {}) do Data.add(out,row) end
return out end
  -- Discretize all row values (writing those vals to "cooked").

function Data.discretize(i)
for _row in pairs(i.rows) do
for _col in pairs(i.about.x) do
loal x = row.cells[col.at]
if x= "Them
row.cooked[col.at] = Col.discretize(col,x) end end end
 -- Recursively bi-cluster one Data into sub-Datas.
function Data.cluster(i, rowhove,stop)
stop = stop or ($i.rows)'the Min
it local A,B,B,S,B,C = Data.half(i.rows,rowAbove)
i.halves = (c=c, A+A, B=B, kids = { Data.cluster(Data.clone(i,As), A, stop), }
kids = { Data.cluster(Data.clone(i,As), A, stop), }
Data.cluster(Data.clone(i,Bs), B, stop) }]end
-Split data according to distance to two distant points A,B
- To dodge outliers, don't search all the way to edge (see the.Far).
- To speed things up:
- try to reuse a distant point from above (see rowAbove).
- only look at some of the rows (see the.Some).
- find distant points in linear time via
- A=far(any()) and B=far(A).
- function Data.half(i, rows, rowAbove)
- local some: l.many (rows, the.Some)
- local runction far (row)
- local function far (row)
- local function project(row)
- local sometion project(row)
- local sometion project(row)
- local a,b = Row.dist(row,A), Row.dist(row,B)
- return (row=row, x=(a*2 + c*2 - b*2)/(2*c*) end
        return (row=row, x=(a^2 + c^2 - b^2)/(2*c)) end local A= rowAbove or far(1.any(some)) local B= far(A) local C= Row.dist(A,B)
          local As,Bs = {},{}
for n,rowx in pairs(1.sort(1.map(rows, project),1.lt"x")) do
              push (n < #rows/2 and As or Bs, rowx.row) end
         return A,B,As,Bs,c end
   function Data.load(sFilename,
                                                                                                                   data)
      1.csv(sFilename, function(row)
  if data then Data.add(data,row) else data=Data.new(row) end end)
        return data end
    function Data.mid(i) return 1.map(i.about.y, Col.mid) end
-- Guess the sort order of the rows by peeking at a few distant points.

function Data.optimize(i, rows)ove, stop,out)

stop = stop or (fi.rows)^the.Min

out = out or []

if fi.rows < 2*stop

then for __row in pairs(i.rows) do push(out,row) end

else local A,B,As,Bs,c = Data.half(i.rows, rowshove)

if Row.better(A,B)

then for j=Psl, do push(out,Bs[j]) end

Data.optimize(Data.clone(i,rev(As)), A, stop, out)

else for __row in pairs(As) do push(out,row) end

Data.optimize(Data.clone(i,Bs), B, stop, out)

end end
```

return {Data=Data,Row=Row,Col=Col,About=About,the=the}