Power [uW]	Theta		Power [uW]	x [cm]				Max Power [uW]	1/e Power [uW]	Max Measurement	1/e Measurement	Beam Diameter	z [cm]
186	3	0	849	10.267	0.055	844	10.273	788	106.6442032	1.083	1.008	0.075	4
113	3	10	849	10.262	0.05	843	10.272		0	1.072	0.975	0.097	9
g)	30	847	10.257	0.045 new r	nax after: 858	10.283		0	1.029	0.943	0.086	14
26	6	50	841	10.252	0.04				0	1.02	0.947	0.073	19
80)	60	829	10.247	0.035				0	0.987	0.856	0.131	24
149)	70	808	10.242	0.03				0			0	
240)	80	778	10.237	0.025				0			0	
502	2	120	725	10.232	0.02				0			0	
512	2	130	654	10.227	0.015				0			0	
492	2	140	567	10.222	0.01				0			0	
442	2	150	467	10.217	0.005				0			0	
365	5	160	368	10.212	0				0			0	
191		180	276	10.207	-0.005				0			0	
110)	190	188	10.202	-0.01				0			0	
9)	210	121	10.197	-0.015								
2	2	220	72	10.192	-0.02								
25	5	230	39	10.187	-0.025								
79)	240	20	10.182	-0.03								
152	2	250	9	10.177	-0.035								
330)	270	5	10.172	-0.04								
411	ı	280	3	10.167	-0.045								
474	l .	290	2	10.162	-0.05								
510)	300	1	10.157	-0.055								
518	3	310											
491		320											
438	3	330											
275	5	350											
186	3	360											
46	3	200											
401		110											
520)	309.7											
1		218											